

# LET'S GET GO-ING

**An introduction to Go  
programming for COS 316**

# TODAY'S AGENDA

Just enough Go to  
get started on  
Assignment 1.

- What is Go?
  - Variables, loops, and functions in Go
  - Navigating the standard library documentation
-

WHAT IS GO?

# WHAT IS GO?

Go is a programming language  
designed for large, distributed  
systems.

# WHAT IS GO?

Go is a programming language designed for large, distributed systems.


Widely used in industry.

# WHAT IS GO?

Go is a programming language designed for large, distributed systems.

Widely used in industry.

Features native, efficient concurrency primitives (i.e., *goroutines* and *channels*).



Okay, let's write our first program

# VARIABLES

- <https://play.golang.org/>



# VARIABLES

```
package main
```

```
func main() {
```

```
}
```

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
}
```

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
}
```

Variable types come  
*after* variable names

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
}
```

Variable types come  
*after* variable names

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='



# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
    var e, f int = -1, -2  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
    var e, f int = -1, -2  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

```
func main() {
```

```
    var
```

```
    var
```

```
    c :=
```

```
    var
```

```
    var
```

```
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

Okay, looks good!

Let's run our code.

accept  
(e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

```
func main() {
```

```
    var
```

```
    var
```

```
    c :=
```

```
    var
```

```
    var
```

```
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

Okay, looks good!

Let's run our code.

```
> go run main.go
```

accept  
e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

Variable types come  
*after* variable names

Variable types can be

Compiler says nope!

X



```
./main.go:4:7: a declared and not used  
./main.go:5:7: b declared and not used  
./main.go:6:3: c declared and not used  
./main.go:7:7: d declared and not used  
./main.go:8:7: e declared and not used  
./main.go:8:10: f declared and not used
```

default value (i.e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

```
func main() {
```

```
    var
```

```
    var
```

```
    c :=
```

```
    var
```

```
    var
```

```
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

Go prevents you from  
compiling code with  
unused variables, so  
let's print them out

accept  
(e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
    var e, f int = -1, -2  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

Can declare and init.  
multiple vars in 1 line



# VARIABLES

```
package main
```

```
import "fmt"
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
    var e, f int = -1, -2  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

```
import "fmt"
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
    var e, f int = -1, -2  
  
    fmt.Println(a, b, c)  
}
```

Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

Can declare and init.  
multiple vars in 1 line

# VARIABLES

```
package main
```

```
import "fmt"
```

```
func main() {  
    var a int = 3  
    var b = 2  
    c := 1  
    var d int  
    var e, f int = -1, -2  
  
    fmt.Println(a, b, c)  
    fmt.Println(d, e, f)  
}
```


Variable types come  
*after* variable names

Variable types can be  
omitted and inferred

A shorthand for  
'var c =' is 'c :='

Can choose to accept  
default value (i.e., 0)

Can declare and init.  
multiple vars in 1 line



Let's see this in action!

# PLAY TIME!

"Go" to  
[play.golang.org](https://play.golang.org) and  
try out some variable  
declarations.

# PLAY TIME!

"Go" to  
[play.golang.org](https://play.golang.org) and  
try out some variable  
declarations.

Here are some ideas.

1. Can you declare multiple variables with different types on the same line?

# PLAY TIME!

"Go" to [play.golang.org](https://play.golang.org) and try out some variable declarations.

Here are some ideas.

1. Can you declare multiple variables with different types on the same line?

2. Can you infer the types of variables when declaring more than one on a line?

# PLAY TIME!

"Go" to [play.golang.org](https://play.golang.org) and try out some variable declarations.

Here are some ideas.



1. Can you declare multiple variables with different types on the same line?

2. Can you infer the types of variables when declaring more than one on a line?

3. What does `fmt.Println()` print when it's given multiple arguments?

# PLAY TIME!

"Go" to [play.golang.org](https://play.golang.org) and try out some variable declarations.

Here are some ideas.

# LOOPS

```
package main
```

```
func main() {
```

```
}
```

# LOOPS

```
package main
```

```
import "fmt"
```

```
func main() {  
    for i := 1; i <= 3; i++ {  
        fmt.Println(i)  
    }  
}
```

# LOOPS

```
package main
```

```
import "fmt"
```

```
func main() {  
    for i := 1; i <= 3; i++ {  
        fmt.Println(i)  
    }  
}
```

# LOOPS

'for' loops work like in Java/C, but don't require ()

Must use {}, even for 1-line loops

```
package main
```

```
import "fmt"
```

```
func main() {  
    for i := 1; i <= 3; i++ {  
        fmt.Println(i)  
    }  
    i := 4  
    for i <= 10 {  
        fmt.Println(i)  
        i++  
    }  
}
```

# LOOPS

'for' loops work like in Java/C, but don't require ()

Must use {}, even for 1-line loops

```
package main
```

```
import "fmt"
```

```
func main() {  
    for i := 1; i <= 3; i++ {  
        fmt.Println(i)  
    }  
    i := 4  
    for i <= 10 {  
        fmt.Println(i)  
        i++  
    }  
}
```

# LOOPS

'for' loops work like in Java/C, but don't require ()

Must use {}, even for 1-line loops

No such thing as 'while' loops in Go

```
package main
```

```
import "fmt"
```

```
func main() {  
    for i := 1; i <= 3; i++ {  
        fmt.Println(i)  
    }  
    i := 4  
    for i <= 10 {  
        fmt.Println(i)  
        i++  
    }  
    for {  
        fmt.Println("done!")  
        break  
    }  
}
```

# LOOPS

'for' loops work like in Java/C, but don't require ()

Must use {}, even for 1-line loops

No such thing as 'while' loops in Go



```
package main
```

```
import "fmt"
```

```
func main() {  
    for i := 1; i <= 3; i++ {  
        fmt.Println(i)  
    }  
    i := 4  
    for i <= 10 {  
        fmt.Println(i)  
        i++  
    }  
    for {  
        fmt.Println("done!")  
        break  
    }  
}
```


# LOOPS

'for' loops work like in Java/C, but don't require ()

Must use {}, even for 1-line loops

No such thing as 'while' loops in Go

Can use 'break' and 'continue'



Let's try it ourselves

# LET'S GET LOOPY

---

Navigate to  
[play.golang.org](https://play.golang.org)  
and write a few Go  
loops.

1. Does the scoping of the index variable in a Go 'for' loop extend beyond the loop?

# LET'S GET LOOPY

---

Navigate to  
[play.golang.org](https://play.golang.org)  
and write a few Go  
loops.

1. Does the scoping of the index variable in a Go 'for' loop extend beyond the loop?

2. Can you skip the conditional part in a 'for' loop but still use the init and post statements?

# LET'S GET LOOPY

—  
Navigate to  
[play.golang.org](https://play.golang.org)  
and write a few Go  
loops.

1. Does the scoping of the index variable in a Go 'for' loop extend beyond the loop?

2. Can you skip the conditional part in a 'for' loop but still use the init and post statements?

3. Does Go support 'labeled breaks' that let you choose which loop to leave?

# LET'S GET LOOPY

—  
Navigate to  
[play.golang.org](https://play.golang.org)  
and write a few Go  
loops.

# FUNCTIONS

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```



# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

A function's return type is listed after its args

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

```
func g(a, b int) int {  
    return a * b  
}
```

A function's return type is listed after its args

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

```
func g(a, b int) int {  
    return a * b  
}
```

A function's return type is listed after its args

If args are same type, can specify type once at end

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

```
func g(a, b int) int {  
    return a * b  
}
```

```
func h(a, b int) (int,int) {  
    return f(a, b), g(a, b)  
}
```

A function's return type is listed after its args

If args are same type, can specify type once at end

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

```
func g(a, b int) int {  
    return a * b  
}
```

```
func h(a, b int) (int,int) {  
    return f(a, b), g(a, b)  
}
```

A function's return type is listed after its args

If args are same type, can specify type once at end

Functions can return more than one result

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

```
func g(a, b int) int {  
    return a * b  
}
```

```
func h(a, b int) (int,int) {  
    return f(a, b), g(a, b)  
}
```

```
func main() {  
    a, b := h(1, 2)  
    _, c := h(3, 4)  
}
```

A function's return type is listed after its args

If args are same type, can specify type once at end

Functions can return more than one result

# FUNCTIONS

```
func f(a int, b int) int {  
    return a + b  
}
```

```
func g(a, b int) int {  
    return a * b  
}
```

```
func h(a, b int) (int,int) {  
    return f(a, b), g(a, b)  
}
```


```
func main() {  
    a, b := h(1, 2)  
    _, c := h(3, 4)  
}
```

A function's return type is listed after its args

If args are same type, can specify type once at end

Functions can return more than one result

'\_' throws away a return value



Last programming exercise!



1. Does Go allow you to use '\_' to ignore all the return values of a function?

2. Can you use recursion with a function that returns multiple values?

3. Does Go require a return value for each function?

# FUNCTIONAL GOGRAMMING

Let's get back to  
[play.golang.org](https://play.golang.org)  
and write a few  
programs using  
functions in Go.

GO STANDARD LIBRARY

# GO STANDARD LIBRARY

All Go programs have access to  
to a massive standard library of  
packages. (See [golang.org/pkg](https://golang.org/pkg))

# GO STANDARD LIBRARY

All Go programs have access to to a massive standard library of packages. (See [golang.org/pkg](https://golang.org/pkg))

This collection of officially supported packages is one of the reasons Go is a useful language for systems programmers.

# READING THE DOCUMENTATION

# READING THE DOCUMENTATION

Navigating the documentation is  
hard.

# READING THE DOCUMENTATION

Navigating the documentation is hard.

There's a lot of it and you'll be learning about the language as you read it.

# READING THE DOCUMENTATION

Navigating the documentation is hard.

There's a lot of it and you'll be learning about the language as you read it.

Expect to spend some time poring over it.



# EXTERNAL SOURCES


# EXTERNAL SOURCES

Googling is allowed, even encouraged, in this course. You may use any online resource.

# EXTERNAL SOURCES

Googling is allowed, even encouraged, in this course. You may use any online resource.

If you base a significant portion of your code on it, cite it in a comment in your code.



Let's see the docs

1. Find some  
“interesting” packages

2. Can you experiment  
using the provided  
examples?

# DOC HUNT

---

Navigate to

[golang.org/pkg](https://golang.org/pkg)

Use

[play.golang.org](https://play.golang.org)

# QUESTIONS?

Please don't hesitate to ask!

# ADDITIONAL RESOURCES

- [golang.org](https://golang.org)
- [play.golang.org](https://play.golang.org)
- [gobyexample.com](https://gobyexample.com)
- ["Learn Go Programming"](#)  
[\(7 hour YouTube tutorial\)](#)

# ASSIGNMENT 0

- Set up common development environment
  - Go, Git, etc.
  - Virtual Machine (optional)
  - Necessary for precepts and assignments



# GIT & GO

- Command line Git
- Desktop Git
- Git Tutorial
- Git Cheatsheet
- Download Go