

PAPER WHITE TECHNOLOGY

Loan Management System

API Reference & Usage Manual

Version	1.0
Generated	2026-08-22
Total endpoints	479 across 47 modules
Server root	http://<server-ip>:3001
Global prefix	/api/v1 (already included in every path)
Authentication	Bearer JWT — POST /api/v1/auth/login

About this document

This manual documents every HTTP endpoint exposed by the LMS backend. It is generated directly from the live OpenAPI specification, so it always matches the code.

Each entry states what the endpoint does, its impact (whether it reads or changes data), the authentication it needs, its parameters, and a copy-paste working example with a sample response.

BASE URL & PREFIX

Every path already includes the /api/v1 prefix. Prepend the server root, e.g. http://<server-ip>:3001/api/v1/auth/login

AUTHENTICATION FLOW

1) POST /auth/login with username & password. 2) Copy accessToken from the response. 3) Send it as an Authorization: Bearer header on every other call.

```
# 1) Log in and capture the token
TOKEN=$(curl -s -X POST "http://<server-ip>:3001/api/v1/auth/login" \
  -H "Content-Type: application/json" \
  -d '{ "username": "admin", "password": "your-password" }' | jq -r .data.accessToken)

# 2) Use it on any endpoint
curl "http://<server-ip>:3001/api/v1/members" -H "Authorization: Bearer $TOKEN"
```

STANDARD RESPONSE ENVELOPE

Successful responses are wrapped in this envelope; the payload is in "data". Errors set success=false with an HTTP 4xx/5xx status and a message.

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* endpoint payload */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

IMPACT LEGEND

- **READ-ONLY** — Safe. Returns data only.
- **WRITES / ACTION** — POST — creates a record or performs an action.
- **UPDATES DATA** — PUT / PATCH — modifies an existing record.
- **DELETES DATA** — DELETE — removes a record (usually irreversible).
- **CRITICAL** — Destructive, system-wide (e.g. database restore).

Admin - Cast Categories

Endpoints in the Admin - Cast Categories module. (5 endpoints)

GET /admin/cast-categories

Get all caste categories

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/cast-categories"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/cast-categories

Create a new caste category

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "id": 0,
  "name": "string"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/cast-categories" \
-H "Content-Type: application/json" \
-d '{
  "id": 0,
  "name": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/cast-categories/{id}

Delete a caste category

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/cast-categories/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/cast-categories/{id}

Get a caste category by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/cast-categories/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/cast-categories/{id}

Update a caste category

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "name": "string"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/cast-categories/{id}" \
-H "Content-Type: application/json" \
-d '{
  "name": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - Certificate Templates

Endpoints in the Admin - Certificate Templates module. (6 endpoints)

GET /admin/certificate-templates

List all certificate templates

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/certificate-templates" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/certificate-templates

Create a certificate template

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/certificate-templates" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/certificate-templates/{id}

Delete a certificate template by id

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/certificate-templates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/certificate-templates/{id}

Get a certificate template by id

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/certificate-templates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/certificate-templates/{id}

Update a certificate template by id

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/certificate-templates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/certificate-templates/default

Get the default certificate template for an account type

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
accountType	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/certificate-templates/default" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```


Admin - Designations

Endpoints in the Admin - Designations module. (5 endpoints)

GET /admin/designations

Get all designations

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/designations"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/designations

Create a new designation

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "code": "string",
  "name": "string",
  "level": 0
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/designations" \
  -H "Content-Type: application/json" \
  -d '{
    "code": "string",
    "name": "string",
    "level": 0
  }'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/designations/{code}

Delete a designation

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
code	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/designations/{code}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/designations/{code}

Get a designation by code

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
code	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/designations/{code}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/designations/{code}

Update a designation

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
code	path	yes	—

REQUEST BODY (JSON)

```
{
  "name": "string",
  "level": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/designations/{code}" \
-H "Content-Type: application/json" \
-d '{
  "name": "string",
  "level": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - FD Accounts

Endpoints in the Admin - FD Accounts module. (3 endpoints)

GET /admin/fd-accounts

Get all FD accounts (or filter by memberNo)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/fd-accounts"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/fd-accounts/{accountNumber}

Get FD account by Account Number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
accountNumber	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/fd-accounts/{accountNumber}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/fd-accounts/{accountNumber}

Update FD account details

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
accountNumber	path	yes	—

REQUEST BODY (JSON)

```
{
  "memberNo": 0,
  "prefix": "string",
  "firstName": "string",
  "middleName": "string",
  "lastName": "string",
  "certificateNo": "string",
  "depositUnit": 0,
  "depositPeriod": 0,
  "rate": 0,
  "depositDate": "2026-07-25T10:00:00.000Z",
  "maturityDate": "2026-07-25T10:00:00.000Z",
  "fdAmount": 0,
  "maturityAmount": 0,
  "interestBalance": 0,
  "interestAmount": 0,
  "lastIntPaymentDate": "2026-07-25T10:00:00.000Z",
  "interestPaid": 0,
  "status": "string",
  "nominee": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string",
  "modeOfPayment": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/fd-accounts/{accountNumber}" \
-H "Content-Type: application/json" \
-d '{
  "memberNo": 0,
  "prefix": "string",
  "firstName": "string",
  "middleName": "string",
  "lastName": "string",
  "certificateNo": "string",
  "depositUnit": 0,
  "depositPeriod": 0,
  "rate": 0,
  "depositDate": "2026-07-25T10:00:00.000Z",
  "maturityDate": "2026-07-25T10:00:00.000Z",
  "fdAmount": 0,
  "maturityAmount": 0,
  "interestBalance": 0,
  "interestAmount": 0,
  "lastIntPaymentDate": "2026-07-25T10:00:00.000Z",
  "interestPaid": 0,
  "status": "string",
  "nominee": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string",
  "modeOfPayment": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - Member Balances

Endpoints in the Admin - Member Balances module. (2 endpoints)

GET /admin/member-balances/{memberNo}

Get member balance by Member No

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/member-balances/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/member-balances/{memberNo}

Update member balance

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

REQUEST BODY (JSON)

```
{
  "shares": 0,
  "rdAmount": 0,
  "savingAmount": 0,
  "loanBalance": 0,
  "emergencyLoanBalance": 0,
  "frsBalance": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/member-balances/{memberNo}" \
-H "Content-Type: application/json" \
-d '{
  "shares": 0,
  "rdAmount": 0,
  "savingAmount": 0,
  "loanBalance": 0,
  "emergencyLoanBalance": 0,
  "frsBalance": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```


Admin - Member Funds (Migration)

Endpoints in the Admin - Member Funds (Migration) module. (4 endpoints)

GET /admin/member-funds/{memberNo}

Get member detailed balances

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/member-funds/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/member-funds/{memberNo}

Update member detailed balances

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

REQUEST BODY (JSON)

```
{
  "sharesOpeningBalance": 0,
  "sharesInstallment": 0,
  "monthlyContributionOpeningBalance": 0,
  "monthlyContributionInstallment": 0,
  "compulsoryDepositOpeningBalance": 0,
  "compulsoryDepositInstallment": 0,
  "loanExecutionReceipt": 0,
  "suspenseBalance": 0,
  "rlnOpBal": 0,
  "rlnAmt": 0,
  "elnOpBal": 0,
  "elnAmt": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/member-funds/{memberNo}" \
-H "Content-Type: application/json" \
-d '{
  "sharesOpeningBalance": 0,
  "sharesInstallment": 0,
  "monthlyContributionOpeningBalance": 0,
  "monthlyContributionInstallment": 0,
  "compulsoryDepositOpeningBalance": 0,
  "compulsoryDepositInstallment": 0,
  "loanExecutionReceipt": 0,
  "suspenseBalance": 0,
  "rlnOpBal": 0,
  "rlnAmt": 0,
  "elnOpBal": 0,
  "elnAmt": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/member-funds/list

Get ordered list of member numbers in fundsmaster (optionally filtered by wing)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
wing	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/member-funds/list"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/member-funds/wings

Get wings that have members in fundsmaster

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/member-funds/wings"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - Member Management

Endpoints in the Admin - Member Management module. (2 endpoints)

GET /admin/members/{memberNo}

Get member details by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/members/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/members/transfer

Transfer member to a new office

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/members/transfer"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - Office Master

Endpoints in the Admin - Office Master module. (5 endpoints)

GET /admin/offices

Get all offices

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/offices"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/offices

Create a new office

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "officeId": 0,
  "officeName": "string",
  "division": "string",
  "address": "string",
  "city": "string"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/offices" \
-H "Content-Type: application/json" \
-d '{
  "officeId": 0,
  "officeName": "string",
  "division": "string",
  "address": "string",
  "city": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/offices/{id}

Delete an office

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/offices/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/offices/{id}

Get an office by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/offices/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/offices/{id}

Update an office

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "officeId": 0,
  "officeName": "string",
  "division": "string",
  "address": "string",
  "city": "string"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/offices/{id}" \
-H "Content-Type: application/json" \
-d '{
  "officeId": 0,
  "officeName": "string",
  "division": "string",
  "address": "string",
  "city": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - Passbook Templates

Endpoints in the Admin - Passbook Templates module. (6 endpoints)

GET /admin/passbook-templates

Get all passbook templates

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/passbook-templates" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/passbook-templates

Create a new passbook template

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/passbook-templates" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/passbook-templates/{id}

Delete a passbook template

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/passbook-templates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/passbook-templates/{id}

Get passbook template by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/passbook-templates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/passbook-templates/{id}

Update an existing passbook template

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/passbook-templates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/passbook-templates/default

Get default passbook template by account type

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
accountType	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/passbook-templates/default" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - RD Account

Endpoints in the Admin - RD Account module. (6 endpoints)

GET /admin/rd-accounts

Get all RD Accounts, optionally filtered by memberNo

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/rd-accounts"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/rd-accounts

Create a new RD Account

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "accountNumber": 0,
  "memberNo": 0,
  "prefix": "string",
  "firstName": "string",
  "middleName": "string",
  "lastName": "string",
  "depositDate": "2026-07-25T10:00:00.000Z",
  "amount": 0,
  "rate": 0,
  "depositPeriod": 0,
  "depositUnit": 0,
  "maturityDate": "2026-07-25T10:00:00.000Z",
  "maturityAmount": 0,
  "openingBalance": 0,
  "nominee": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string",
  "specialInstructions": "string",
  "recoveryThroughDemand": true,
  "headCode": "string"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/rd-accounts" \
-H "Content-Type: application/json" \
-d '{
  "accountNumber": 0,
  "memberNo": 0,
  "prefix": "string",
  "firstName": "string",
  "middleName": "string",
  "lastName": "string",
  "depositDate": "2026-07-25T10:00:00.000Z",
  "amount": 0,
  "rate": 0,
  "depositPeriod": 0,
  "depositUnit": 0,
  "maturityDate": "2026-07-25T10:00:00.000Z",
  "maturityAmount": 0,
  "openingBalance": 0,
  "nominee": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string",
  "specialInstructions": "string",
  "recoveryThroughDemand": true,
  "headCode": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/rd-accounts/{id}

Delete an RD Account

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/rd-accounts/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/rd-accounts/{id}

Get an RD Account by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/rd-accounts/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/rd-accounts/{id}

Update an RD Account

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "accountNumber": 0,
  "memberNo": 0,
  "prefix": "string",
  "firstName": "string",
  "middleName": "string",
  "lastName": "string",
  "depositDate": "2026-07-25T10:00:00.000Z",
  "amount": 0,
  "rate": 0,
  "depositPeriod": 0,
  "depositUnit": 0,
  "maturityDate": "2026-07-25T10:00:00.000Z",
  "maturityAmount": 0,
  "openingBalance": 0,
  "nominee": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string",
  "specialInstructions": "string",
  "recoveryThroughDemand": true,
  "headCode": "string"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/rd-accounts/{id}" \
-H "Content-Type: application/json" \
-d '{
  "accountNumber": 0,
  "memberNo": 0,
  "prefix": "string",
  "firstName": "string",
  "middleName": "string",
  "lastName": "string",
  "depositDate": "2026-07-25T10:00:00.000Z",
  "amount": 0,
  "rate": 0,
  "depositPeriod": 0,
  "depositUnit": 0,
  "maturityDate": "2026-07-25T10:00:00.000Z",
  "maturityAmount": 0,
  "openingBalance": 0,
  "nominee": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string",
  "specialInstructions": "string",
  "recoveryThroughDemand": true,
  "headCode": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/rd-accounts/next-number

Get next auto-generated account number (MAX + 1 from fdmaster)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/rd-accounts/next-number"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - SB Account

Endpoints in the Admin - SB Account module. (6 endpoints)

GET /admin/sb-accounts

Get all SB Accounts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/sb-accounts"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/sb-accounts

Create a new SB Account

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "accountNo": "string",
  "memberNo": "string",
  "openingDate": "2026-07-25T10:00:00.000Z",
  "openingBalance": 0,
  "ledgerGroup": "string",
  "specialInstructions": "string",
  "nomineeName": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string"
}
```

EXAMPLE REQUEST


```
curl -X POST "http://<server-ip>:3001/api/v1/admin/sb-accounts" \
-H "Content-Type: application/json" \
-d '{
  "accountNo": "string",
  "memberNo": "string",
  "openingDate": "2026-07-25T10:00:00.000Z",
  "openingBalance": 0,
  "ledgerGroup": "string",
  "specialInstructions": "string",
  "nomineeName": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/sb-accounts/{id}

Delete an SB Account

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/sb-accounts/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/sb-accounts/{id}

Get an SB Account by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/sb-accounts/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/sb-accounts/{id}

Update an SB Account

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "accountNo": "string",
  "memberNo": "string",
  "openingDate": "2026-07-25T10:00:00.000Z",
  "openingBalance": 0,
  "ledgerGroup": "string",
  "specialInstructions": "string",
  "nomineeName": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/sb-accounts/{id}" \
-H "Content-Type: application/json" \
-d '{
  "accountNo": "string",
  "memberNo": "string",
  "openingDate": "2026-07-25T10:00:00.000Z",
  "openingBalance": 0,
  "ledgerGroup": "string",
  "specialInstructions": "string",
  "nomineeName": "string",
  "nomineeAge": "string",
  "nomineeAddress": "string",
  "nomineeRelation": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/sb-accounts/next-number

Get next auto-generated SB account number (MAX + 1)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/sb-accounts/next-number"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Admin - Wing Master

Endpoints in the Admin - Wing Master module. (5 endpoints)

GET /admin/wings

Get all wings

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/wings"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/wings

Create a new wing

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "wingId": "string",
  "wingName": "string",
  "state": "string"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/wings" \
  -H "Content-Type: application/json" \
  -d '{
    "wingId": "string",
    "wingName": "string",
    "state": "string"
  }'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/wings/{id}

Delete a wing

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/wings/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/wings/{id}

Get a wing by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/wings/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/wings/{id}

Update a wing

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "wingId": "string",
  "wingName": "string",
  "state": "string"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/wings/{id}" \
-H "Content-Type: application/json" \
-d '{
  "wingId": "string",
  "wingName": "string",
  "state": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Administration

Endpoints in the Administration module. (8 endpoints)

GET /admin/dashboard

Get admin dashboard data

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/dashboard" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/deposit-loan-slabs

Get all deposit/loan slabs

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/deposit-loan-slabs" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/deposit-loan-slabs

Create new deposit/loan slab

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "type": "fixed_deposit",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/deposit-loan-slabs" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "type": "fixed_deposit",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/deposit-loan-slabs/{id}

Delete deposit/loan slab

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST


```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/deposit-loan-slabs/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/deposit-loan-slabs/{id}

Get deposit/loan slab by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/deposit-loan-slabs/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /admin/deposit-loan-slabs/{id}

Update deposit/loan slab

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/admin/deposit-loan-slabs/{id}" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/saakh-score/{mbno}

Calculate Saakh Score (member financial health index 0-10) for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	Member number (mbno)

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/saakh-score/{mbno}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/system-info

Get system information

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/system-info" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

AI Chat

Endpoints in the AI Chat module. (1 endpoint)

POST /ai-chat

Chat with AI assistant

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/ai-chat"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Application

Endpoints in the Application module. (2 endpoints)

GET /

Get application information

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /health

Health check endpoint

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/health"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Authentication

Login, logout, token refresh and current-user endpoints. Start here to obtain the Bearer token. (8 endpoints)

POST /auth/change-password

Change user password

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "currentPassword": "currentPassword123",
  "newPassword": "newSecurePassword123"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/auth/change-password" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "currentPassword": "currentPassword123",
  "newPassword": "newSecurePassword123"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /auth/login

User login

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "username": "admin@example.com",
  "password": "password123"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/auth/login" \
-H "Content-Type: application/json" \
-d '{
  "username": "admin@example.com",
  "password": "password123"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /auth/logout

User logout

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/auth/logout" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /auth/me

Get current user profile

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/auth/me" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /auth/refresh

Refresh access token

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/auth/refresh" \
-H "Content-Type: application/json" \
-d '{
  "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /auth/register

Register new user (Admin only)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)


```
{
  "username": "john_doe",
  "email": "john.doe@example.com",
  "password": "securePassword123",
  "firstName": "John",
  "lastName": "Doe",
  "role": "data_operator",
  "permissions": [
    "create_member"
  ]
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/auth/register" \
  -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "username": "john_doe",
    "email": "john.doe@example.com",
    "password": "securePassword123",
    "firstName": "John",
    "lastName": "Doe",
    "role": "data_operator",
    "permissions": [
      "create_member"
    ]
  }'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /auth/usernames

Get usernames only for password change dropdown (no sensitive data)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/auth/usernames"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /auth/users-list

Get list of all users for dropdown (authenticated admins only)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/auth/users-list" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Cash Book

Endpoints in the Cash Book module. (6 endpoints)

GET /cashbook/interest-rate

Current savings interest rate used by the cash book

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/cashbook/interest-rate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /cashbook/member/balance

Get a member current cash/savings balance by member code

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberCode	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/cashbook/member/balance"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /cashbook/members/active

List active members (for cash book entry dropdowns)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/cashbook/members/active"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /cashbook/report

Daily cash book report (receipts & payments) for a given date

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/cashbook/report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /cashbook/transaction

Record a cash book transaction (receipt or payment entry)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/cashbook/transaction"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /cashbook/transactions

List cash book transactions within a start/end date range

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
startDate	query	yes	—
endDate	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/cashbook/transactions"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Client Logs

Endpoints in the Client Logs module. (1 endpoint)

POST /client-logs

Ingest a batch of client-side (desktop app) log entries

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/client-logs"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Compulsory Deposit Transactions

Endpoints in the Compulsory Deposit Transactions module. (3 endpoints)

GET /transactions/cd/income-heads

Get Income Ledger heads from main table

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/cd/income-heads"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /transactions/cd/members

Get list of members for CD transaction matrix

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/cd/members"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/cd/post

Execute bulk CD interest/incentive posting

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/cd/post"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```


Consolidation

Endpoints in the Consolidation module. (1 endpoint)

GET /consolidation/report

Consolidation report (all-branch day totals) for a given date

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/consolidation/report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Dashboard Notices

Endpoints in the Dashboard Notices module. (4 endpoints)

GET /dashboard-notices

List all dashboard notices, shared across every PC

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/dashboard-notices"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /dashboard-notices

Post a new dashboard notice

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/dashboard-notices"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /dashboard-notices/{id}

Delete a dashboard notice

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/dashboard-notices/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /dashboard-notices/reorder

Persist a new drag-and-drop order for the board

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/dashboard-notices/reorder"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Database Backup

Create, list, validate, clean up and RESTORE encrypted database backups. (7 endpoints)

POST /backup/cleanup

Clean up old backups based on retention policy

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "backupPath": "string",
  "retentionDays": 0
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/backup/cleanup" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "backupPath": "string",
  "retentionDays": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /backup/create

Create database backup

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "destinationPath": "C:\\Backups",
  "includeSchema": true,
  "includeData": true,
  "compressionLevel": 0,
  "customName": "string"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/backup/create" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "destinationPath": "C:\\Backups",
  "includeSchema": true,
  "includeData": true,
  "compressionLevel": 0,
  "customName": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /backup/database-info

Get database configuration information

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/backup/database-info" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /backup/list

Get list of existing backups

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
backupPath	query	no	Custom backup directory path

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/backup/list" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /backup/restore

Restore the database from a backup file (DESTRUCTIVE — overwrites all current data)

Decrypts and restores a backup created by POST /backup/create. Overwrites the current database. Requires "confirm" to equal the exact target database name. Automatically takes a pre-restore safety backup first (unless skipSafetyBackup=true) so the operation is reversible.

CRITICAL Overwrites the ENTIRE database with a backup. Irreversible except via the auto pre-restore safety backup. Recovery use only. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "fileName": "backup_2026-07-25T10-00-00-000Z.sql.safe",
  "filePath": "string",
  "confirm": "EMP_Espat_Society",
  "skipSafetyBackup": true
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/backup/restore" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "fileName": "backup_2026-07-25T10-00-00-000Z.sql.safe",
  "filePath": "string",
  "confirm": "EMP_Espat_Society",
  "skipSafetyBackup": true
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /backup/test-connection

Test database connection

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/backup/test-connection" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /backup/validate-destination

Validate backup destination path

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "destinationPath": "C:\\Backups"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/backup/validate-destination" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "destinationPath": "C:\\Backups"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Day Book

Endpoints in the Day Book module. (6 endpoints)

GET /daybook/active-members

List active members holding savings accounts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/daybook/active-members"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /daybook/calculate-interest

Calculate accrued savings interest for a member over a period (preview, no posting)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/daybook/calculate-interest"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /daybook/interest-rate

Current savings interest rate used by the day book

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/daybook/interest-rate"
```


EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /daybook/pay-interest

Post an interest payment to a member savings account

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/daybook/pay-interest"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /daybook/report

Day book report (all day transactions) for a given date, optionally filtered

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/daybook/report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /daybook/report/sb

Day book report limited to savings-bank (SB) transactions for a date

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/daybook/report/sb"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Day-End Processing

Endpoints in the Day-End Processing module. (8 endpoints)

POST /admin/day-end/initialize

Create the genesis getworkingdate row (only when none exists)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/day-end/initialize" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/day-end/initiate

Initiate day-end processing

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "processDate": "2024-01-15",
  "forceReprocess": false,
  "processTypes": [
    "interest_calculation"
  ],
  "nextWorkingDate": "2024-01-16"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/day-end/initiate" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "processDate": "2024-01-15",
  "forceReprocess": false,
  "processTypes": [
    "interest_calculation"
  ],
  "nextWorkingDate": "2024-01-16"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/day-end/processes

Get all day-end processes

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/day-end/processes" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/day-end/processes/{id}

Get day-end process by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Process ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/day-end/processes/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/day-end/processes/{id}/interest-calculations

Get interest calculation results for a day-end process

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Process ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/day-end/processes/{id}/interest-
calculations" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/day-end/processes/{id}/summary

Get day-end process summary

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Process ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/day-end/processes/{id}/summary" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/day-end/summary

Get current day-end summary

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/day-end/summary" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/day-end/working-date

Reset a mis-set initial working date (only before any day-end has completed)

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/day-end/working-date" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Deposits

Fixed and recurring deposit accounts: creation, installments, closure and maturity. (19 endpoints)

POST /deposits/calculate-interest

Calculate and post interest for all deposits

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/deposits/calculate-interest" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /deposits/certificates/download/{fileName}

Download certificate file

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
fileName	path	yes	Certificate file name

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/certificates/download/{fileName}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /deposits/fixed-deposits

Get all fixed deposits

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/fixed-deposits" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /deposits/fixed-deposits

Create a new fixed deposit

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "memberId": 0,
  "principalAmount": 100000,
  "interestRate": 8.5,
  "depositDate": "2024-01-01",
  "tenureMonths": 12,
  "isAutoRenewal": true
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/deposits/fixed-deposits" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "memberId": 0,
  "principalAmount": 100000,
  "interestRate": 8.5,
  "depositDate": "2024-01-01",
  "tenureMonths": 12,
  "isAutoRenewal": true
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```


GET /deposits/fixed-deposits/{id}

Get fixed deposit by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Fixed deposit ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/fixed-deposits/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /deposits/fixed-deposits/{id}

Update fixed deposit

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Fixed deposit ID

REQUEST BODY (JSON)

```
{
  "memberId": 0,
  "principalAmount": 100000,
  "interestRate": 8.5,
  "depositDate": "2024-01-01",
  "tenureMonths": 12,
  "isAutoRenewal": true
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/deposits/fixed-deposits/{id}" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "memberId": 0,
  "principalAmount": 100000,
  "interestRate": 8.5,
  "depositDate": "2024-01-01",
  "tenureMonths": 12,
  "isAutoRenewal": true
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /deposits/fixed-deposits/{id}/certificate

Generate fixed deposit certificate

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Fixed deposit account number

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/deposits/fixed-deposits/{id}/certificate" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /deposits/fixed-deposits/{id}/close

Close fixed deposit

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Fixed deposit ID

REQUEST BODY (JSON)

```
{
  "closureDate": "string",
  "closureReason": "string",
  "penaltyRate": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/deposits/fixed-deposits/{id}/close" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "closureDate": "string",
  "closureReason": "string",
  "penaltyRate": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /deposits/fixed-deposits/{id}/maturity

Process fixed deposit maturity

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Fixed deposit ID

REQUEST BODY (JSON)

```
{
  "maturityDate": "string",
  "renewalAction": "string",
  "newTenureMonths": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/deposits/fixed-deposits/{id}/maturity" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "maturityDate": "string",
  "renewalAction": "string",
  "newTenureMonths": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /deposits/member/{memberNo}

Get deposits by member Number (e.g. M-001)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	Member Number

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/member/{memberNo}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /deposits/members/{memberId}/fixed-deposits

Get fixed deposits by member ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	Member ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/members/{memberId}/fixed-deposits" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /deposits/members/{memberId}/recurring-deposits

Get recurring deposits by member ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	Member ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/members/{memberId}/recurring-deposits" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /deposits/members/{memberId}/share-certificate

Generate share certificate for member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	Member ID

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/deposits/members/{memberId}/share-certificate" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /deposits/rd-installments/{id}/pay

Pay RD installment

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	RD installment ID

REQUEST BODY (JSON)

```
{
  "paidAmount": 0,
  "paidDate": "string",
  "paymentMode": "string",
  "receiptNumber": "string",
  "remarks": "string"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/deposits/rd-installments/{id}/pay" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "paidAmount": 0,
  "paidDate": "string",
  "paymentMode": "string",
  "receiptNumber": "string",
  "remarks": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /deposits/recurring-deposits

Get all recurring deposits

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/recurring-deposits" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

POST /deposits/recurring-deposits

Create a new recurring deposit

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{  
  "memberId": 0,  
  "monthlyInstallment": 5000,  
  "interestRate": 9,  
  "startDate": "2024-01-01",  
  "tenureMonths": 24  
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/deposits/recurring-deposits" \  
-H "Authorization: Bearer $TOKEN" \  
-H "Content-Type: application/json" \  
-d '{  
  "memberId": 0,  
  "monthlyInstallment": 5000,  
  "interestRate": 9,  
  "startDate": "2024-01-01",  
  "tenureMonths": 24  
}'
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 201,  
  "message": "Operation successful",  
  "data": { /* affected record */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

GET /deposits/recurring-deposits/{id}

Get recurring deposit by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Recurring deposit ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/deposits/recurring-deposits/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /deposits/recurring-deposits/{id}/certificate

Generate recurring deposit certificate

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Recurring deposit ID

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/deposits/recurring-deposits/{id}/certificate" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /deposits/recurring-deposits/{id}/close

Close recurring deposit

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	Recurring deposit ID

REQUEST BODY (JSON)

```
{
  "closureDate": "string",
  "closureReason": "string",
  "penaltyRate": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/deposits/recurring-deposits/{id}/close" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "closureDate": "string",
  "closureReason": "string",
  "penaltyRate": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Financial Year Management

Endpoints in the Financial Year Management module. (8 endpoints)

DELETE /admin/financial-year/{yearCode}

Delete an un-closed, un-archived financial year

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
yearCode	path	yes	—
force	query	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/financial-year/{yearCode}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/financial-year/balance-transfer

Perform manual balance transfer between accounts

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/financial-year/balance-transfer" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/financial-year/close-year

Formally close (lock) a financial year

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/financial-year/close-year" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/financial-year/create

Create a financial year (including the genesis year when none exist)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/financial-year/create" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/financial-year/current

Get current active financial year

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/financial-year/current" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/financial-year/list

Get all financial years

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/financial-year/list" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/financial-year/pl-year-end-process

Initiate P&L Year End Process

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/financial-year/pl-year-end-process" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/financial-year/transfer-entries

Initiate transfer entries for year closing

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/financial-year/transfer-entries" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 201,  
  "message": "Operation successful",  
  "data": { /* affected record */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

general-ledger

Endpoints in the general-ledger module. (2 endpoints)

GET /general-ledger/head-masters

Get all head masters for dropdown

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/general-ledger/head-masters"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /general-ledger/report

Generate general ledger report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
headCode	query	yes	Head code for the account
fromDate	query	yes	From date for the report
toDate	query	yes	To date for the report
outputType	query	no	Output type

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/general-ledger/report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Interest Management

Endpoints in the Interest Management module. (7 endpoints)

GET /interest/current-rate

Get current interest rate for savings accounts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/interest/current-rate" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /interest/history

Get interest calculation history

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/interest/history" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /interest/preview-calculation

Preview interest calculation without saving to database

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/interest/preview-calculation" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /interest/preview-yearly-fund

Preview yearly fund (Interest, Dividend, Insurance) calculation

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}
```


EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/interest/preview-yearly-fund" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /interest/process-yearly-fund

Process yearly fund calculation and post to ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/interest/process-yearly-fund" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /interest/update-saving-interest

Calculate and update saving interest for all eligible members

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/interest/update-saving-interest" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /interest/validate-parameters

Validate interest calculation parameters

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/interest/validate-parameters" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "fromDate": "2025-01-01",
  "toDate": "2025-03-31",
  "interestRate": 4,
  "accountHead": "A1001",
  "accountType": "SB",
  "voucherNumber": "INT2025001",
  "narration": "Interest credited for Q1 2025",
  "memberNo": "1001",
  "expenseHeadCode": "L1028"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Jotting Report

Endpoints in the Jotting Report module. (4 endpoints)

GET /jotting-report

Generate the jotting report (head balances as-on-date, by wing/office)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
headCode	query	yes	—
asOnDate	query	yes	—
wingName	query	yes	—
officeName	query	yes	—
sortBy	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/jotting-report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /jotting-report/head-masters

List account head masters (for jotting-report head dropdown)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/jotting-report/head-masters"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /jotting-report/offices

List offices (for jotting-report office filter)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/jotting-report/offices"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /jotting-report/wings

List wings (for jotting-report wing filter)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/jotting-report/wings"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Journal Transfer Transactions

Endpoints in the Journal Transfer Transactions module. (1 endpoint)

POST /transactions/journal/post

Post a multi-row balanced journal entry

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/journal/post"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

License

Endpoints in the License module. (3 endpoints)

POST /license/activate

Public: activate a license key (self-validating; replaces active license on this machine)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/license/activate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /license/list

Admin: list all license records (debugging)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/license/list"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /license/status

Public: current software license status (valid/grace/expired)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/license/status"
```


EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Loans

Loan application, sanction, disbursement, repayment, EMI schedules, sureties and month-end snapshots. (31 endpoints)

POST /loans/amortization-schedule

Generate amortization schedule

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/loans/amortization-schedule"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /loans/calculate-emi

Calculate EMI for given parameters

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/loans/calculate-emi"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/case/{caseNo}

Get loan details by case number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/case/{caseNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/case/{caseNo}/due-status

Get the oldest-unpaid-first due breakdown for a loan (principal/interest/penal)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/case/{caseNo}/due-status"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/case/{caseNo}/early-closure

Calculate the final amount to close a loan early

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—
closureDate	query	yes	—
adjustment	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/case/{caseNo}/early-closure"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /loans/case/{caseNo}/early-closure

Execute an early closure — settles every remaining installment and zeroes the balance

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/loans/case/{caseNo}/early-closure"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/case/{caseNo}/repayment-summary

Get repayment summary for a specific loan case

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/case/{caseNo}/repayment-summary"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/cases

Get all loan cases for processing

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/cases"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/eligibility/{memberNo}

Check member eligibility for loan based on Share and FD values

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—
amount	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/eligibility/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/generate/loan-case-number

Generate next sequential loan case number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/generate/loan-case-number"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /loans/loan-application

Save a new loan application

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/loans/loan-application"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/master/{caseNo}

Get loan from loan_master (active loans)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/master/{caseNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/master/{caseNo}/emi-schedule

Get EMI schedule for loan from loan_master with payment status

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/master/{caseNo}/emi-schedule"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/all

Get all loans for a member from loan_pending

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/all"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/balance-history

Get month-end balance history for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/balance-history"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/balances

Get member outstanding loan balances from member_balances

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/balances"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/cases

Get loan cases for a specific member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/cases"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/master

Get all active loans for a member from loan_master

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/master"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/pending

Get pending loans for a specific member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/pending"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/repayment-history

Get full repayment history for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/repayment-history"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/member/{memberNo}/surety-cases

Get all loan cases for a member (pending + active) for surety change form

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/member/{memberNo}/surety-cases"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/month-end/report

Get month-end loan balance report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
month	query	yes	—
year	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/month-end/report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /loans/month-end/snapshot

Capture month-end loan balance snapshot for all members

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/loans/month-end/snapshot"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/pending/{caseNo}

Get loan from loan_pending (pending loans)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/pending/{caseNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /loans/repayment

Record a loan repayment installment

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/loans/repayment"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /loans/sanction/{caseNo}

Update loan with sanction details

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/loans/sanction/{caseNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/sanctioned

Get all sanctioned loan cases ready for disbursement

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/sanctioned"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/search/member-loans

Search loans across loan_master and loan_pending

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNumber	query	yes	—
loanCaseNo	query	yes	—
loanType	query	yes	—
status	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/search/member-loans"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/surety/{caseNo}

Get current sureties for a loan case

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/surety/{caseNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /loans/surety/{caseNo}

Change loan sureties (guarantors)

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
caseNo	path	yes	—

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/loans/surety/{caseNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /loans/surety/validate/{memberNo}

Validate if a member can be a surety

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/loans/surety/validate/{memberNo}"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```


Member Ledger

Endpoints in the Member Ledger module. (5 endpoints)

GET /member-ledger/detail-columnar

Columnar member ledger (Share/LTL/Emergency/CD columns with per-date Dr/Cr/Bal)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/member-ledger/detail-columnar"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /member-ledger/detail-report

Detailed member ledger across all heads over a date range

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/member-ledger/detail-report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /member-ledger/head-masters

List account head masters (for ledger head dropdowns)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/member-ledger/head-masters"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /member-ledger/report

Member ledger for a single head/account over a date range

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/member-ledger/report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /member-ledger/validate-member

Check a member number exists and return the member name

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/member-ledger/validate-member"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Members

Member master records: create, update, lookup, KYC documents, photos, signatures and lifecycle status. (27 endpoints)

GET /members

Get all members with pagination

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNumber	query	no	Search by member number
firstName	query	no	Search by first name (partial match)
lastName	query	no	Search by last name (partial match)
phoneNumber	query	no	Search by phone number
email	query	no	Search by email
aadharNumber	query	no	Search by Aadhar number
panNumber	query	no	Search by PAN number
status	query	no	Filter by status
search	query	no	General search term (searches across name, phone, email)
page	query	no	Page number for pagination
limit	query	no	Number of items per page
sortBy	query	no	Sort field
sortOrder	query	no	Sort order

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /members

Create a new member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

REQUEST BODY (JSON)

```
{
  "firstName": "John",
  "lastName": "Doe",
  "dateOfBirth": "1990-01-15",
  "address": "123 Main Street, City, State - 123456",
  "phoneNumber": "+919876543210",
  "email": "john.doe@example.com",
  "aadharNumber": "123456789012",
  "panNumber": "ABCDE1234F",
  "occupation": "Software Engineer",
  "shareAmount": 1000
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/members" \
-H "Content-Type: application/json" \
-d '{
  "firstName": "John",
  "lastName": "Doe",
  "dateOfBirth": "1990-01-15",
  "address": "123 Main Street, City, State - 123456",
  "phoneNumber": "+919876543210",
  "email": "john.doe@example.com",
  "aadharNumber": "123456789012",
  "panNumber": "ABCDE1234F",
  "occupation": "Software Engineer",
  "shareAmount": 1000
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /members/{id}

Delete member

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/members/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/{id}

Get member by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /members/{id}

Update member

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "firstName": "John",
  "lastName": "Doe",
  "dateOfBirth": "1990-01-15",
  "address": "123 Main Street, City, State - 123456",
  "phoneNumber": "+919876543210",
  "email": "john.doe@example.com",
  "aadharNumber": "123456789012",
  "panNumber": "ABCDE1234F",
  "occupation": "Software Engineer",
  "shareAmount": 1000,
  "status": "ACTIVE"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/members/{id}" \
-H "Content-Type: application/json" \
-d '{
  "firstName": "John",
  "lastName": "Doe",
  "dateOfBirth": "1990-01-15",
  "address": "123 Main Street, City, State - 123456",
  "phoneNumber": "+919876543210",
  "email": "john.doe@example.com",
  "aadharNumber": "123456789012",
  "panNumber": "ABCDE1234F",
  "occupation": "Software Engineer",
  "shareAmount": 1000,
  "status": "ACTIVE"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /members/{id}/signature

Delete member signature

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/members/{id}/signature"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/{id}/signature

Get member signature image

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/{id}/signature"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /members/{id}/signature

Upload member signature

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/members/{id}/signature"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /members/{id}/status

Change a member lifecycle status (active/inactive/resigned/expired/...)

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "status": "INACTIVE",
  "reason": "Member resigned from the society"
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/members/{id}/status" \
-H "Content-Type: application/json" \
-d '{
  "status": "INACTIVE",
  "reason": "Member resigned from the society"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/balance/{memberNo}

Get comprehensive member balance

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/balance/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/balance/{memberNo}/quick

Get quick balance summary

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/balance/{memberNo}/quick"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/details/{memberNo}

Get member details by member number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/details/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/find/{memberNo}

Find member by member number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/find/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/generate/member-number

Generate next sequential member number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/generate/member-number"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/lookup

Lookup members for forms and dropdowns

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
search	query	yes	—
limit	query	yes	—
offset	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/lookup"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /members/master/{mbno}/document

Upload a KYC document (body: docType) for a member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/members/master/{mbno}/document"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /members/master/{mbno}/document/{id}

Delete a KYC document

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/members/master/{mbno}/document/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/master/{mbno}/document/{id}

Stream/download a KYC document file

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/master/{mbno}/document/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/master/{mbno}/documents

List KYC documents for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/master/{mbno}/documents"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /members/master/{mbno}/photo/{type}

Delete photo for member_master member

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—
type	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/members/master/{mbno}/photo/{type}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/master/{mbno}/photo/{type}

Get photo for member_master member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—
type	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/master/{mbno}/photo/{type}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /members/master/{mbno}/photo/{type}

Upload photo for member_master member (type: profile | doc_front | doc_back)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—
type	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/members/master/{mbno}/photo/{type}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /members/master/{mbno}/signature

Delete signature for legacy member_master member

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/members/master/{mbno}/signature"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/master/{mbno}/signature

Get signature image for legacy member_master member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/master/{mbno}/signature"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /members/master/{mbno}/signature

Upload signature for legacy member_master member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
mbno	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/members/master/{mbno}/signature"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /members/save-member

Save member to legacy member_master table

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/members/save-member"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /members/statistics

Get member statistics

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/members/statistics"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```


Notifications

Endpoints in the Notifications module. (11 endpoints)

POST /notifications/cancel-batch

Cancel a batch of queued notifications by their ids

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/cancel-batch"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /notifications/channel-status

Configured/available notification channels and their status (SMS/email/etc.)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/notifications/channel-status"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /notifications/history

List recent notification log entries (default last 100)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
limit	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/notifications/history"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/queue-manual

Queue a manual notification to a member for later sending

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/queue-manual"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/queue-transaction-alert

Queue a transaction alert notification for a member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/queue-transaction-alert"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/send-batch

Send a batch of queued notifications by their ids

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/send-batch"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/send-manual

Send a manual notification to a member immediately

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/send-manual"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/send-one/{id}

Send a single queued notification by its log id

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/send-one/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /notifications/stats

Notification counts/stats (sent, failed, pending)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/notifications/stats"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/trigger-emi-check

Manually run the EMI-due check and queue EMI reminder alerts

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/trigger-emi-check"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /notifications/trigger-maturity-check

Manually run the deposit-maturity check and queue maturity alerts

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/notifications/trigger-maturity-check"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Print Voucher

Endpoints in the Print Voucher module. (4 endpoints)

GET /print-voucher/{voucherNo}

Get a voucher by number (printable payload)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
voucherNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/print-voucher/{voucherNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /print-voucher/journal/{voucherNo}

Get a journal voucher by number (printable payload)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
voucherNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/print-voucher/journal/{voucherNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /print-voucher/journal/list/all

List all journal voucher numbers

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/print-voucher/journal/list/all"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /print-voucher/list/all

List all voucher numbers (for the print-voucher picker)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/print-voucher/list/all"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Reports

Read-only reporting endpoints (statements, registers, certificates) with optional PDF/Excel output. (112 endpoints)

GET /report/account-closing

Get account closing register

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/account-closing"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/adhoc-reports

Get AdHoc reports

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/adhoc-reports"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/annual-member-statement

Get annual member statement

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/annual-member-statement"
```


EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/balance-sheet

Get Balance Sheet

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
asOnDate	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/balance-sheet"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/bank/ledger

Get bank detail ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/bank/ledger"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/banks

Get list of bank accounts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/banks"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/cashbook/daily

Get daily cash book report (voucher-wise)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/cashbook/daily"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/cashbook/monthly

Get monthly cash book summary

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/cashbook/monthly"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/cashbook2/daily

Get daily cash book report (head-wise from tblcashbook)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/cashbook2/daily"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/defaulters

Get defaulter list

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/defaulters"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/deposit/maturity

Get deposit maturity report

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/deposit/maturity"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/diagnostic

Run diagnostic check

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/diagnostic"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/dividend-paid

Get dividend paid report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/dividend-paid"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/dividend-report

Get dividend report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/dividend-report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/dividend-warrant

Get dividend warrant

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/dividend-warrant"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/divisions

Get division list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
wingNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/divisions"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/fd-certificate

Get FD certificate

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/fd-certificate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/fd/statement

Get FD statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/fd/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/financial-summary

Get financial summary (Trial Balance)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/financial-summary"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/heads

Get list of account heads

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/heads"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/interest-certificate

Get interest certificate

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/interest-certificate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/interest-list

Get interest list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/interest-list"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/jotting

Get jotting report

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/jotting"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/ledger/detail

Get detail ledger for a head code

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/ledger/detail"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/lien-account-information

Get lien account information

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/lien-account-information"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/loan-contributions-register

Get loan contributions register

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/loan-contributions-register"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/loan-nil-certificate/{memberNo}

Get loan nil certificate

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/loan-nil-certificate/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/loan-types

Get loan types

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/loan-types"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/loans/interest-statement

Get interest receivable/received statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/loans/interest-statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/loans/new-disbursed

Get newly disbursed loans

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/loans/new-disbursed"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/member-balance-range

Get members by account number range

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/member-balance-range"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/member-ledger

Get member ledger

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/member-ledger"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/member-loan-detail

Get member loan detail report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/member-loan-detail"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/member/{memberNo}/loan-cases

Get loan cases for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/member/{memberNo}/loan-cases"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/member/balance-range

Get members by balance range

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/member/balance-range"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/member/loan-ledger

Get member loan ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/member/loan-ledger"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/member/profile/{memberNo}

Get member profile

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/member/profile/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/member/statement

Get member statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/member/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/offices

Get office list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
wingNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/offices"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/passbook-printing

Get passbook printing data

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/passbook-printing"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/passbook-reset

Reset passbook print tracking for a member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/passbook-reset"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/passbook-update-tracking

Update passbook tracking after print

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/passbook-update-tracking"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/rd/statement

Get RD statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/rd/statement"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/recovery-details

Get recovery details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/recovery-details"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/recurring-details

Get recurring details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/recurring-details"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/saving/statement

Get saving statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/saving/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/schedule

Get all report schedules

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
type	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/schedule"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/schedule

Create or update report schedule

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/schedule"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/schedule/{id}

Get report schedule details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/schedule/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /report/schedule/execute

Execute report schedule

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/report/schedule/execute"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/share-certificate

Get share certificate

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/share-certificate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/share-warrant

Get share warrant

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/share-warrant"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/surety-register

Get surety register

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/surety-register"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/voters-list

Get voters list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/voters-list"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/wings

Get wing list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/wings"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /report/yearly-member-statement

Get yearly member statement

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/report/yearly-member-statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/account-closing

Get account closing register

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/account-closing"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/adhoc-reports

Get AdHoc reports

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/adhoc-reports"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/annual-member-statement

Get annual member statement

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/annual-member-statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/balance-sheet

Get Balance Sheet

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
asOnDate	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/balance-sheet"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/bank/ledger

Get bank detail ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/bank/ledger"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/banks

Get list of bank accounts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/banks"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/cashbook/daily

Get daily cash book report (voucher-wise)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/cashbook/daily"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/cashbook/monthly

Get monthly cash book summary

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/cashbook/monthly"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/cashbook2/daily

Get daily cash book report (head-wise from tblcashbook)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/cashbook2/daily"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/defaulters

Get defaulter list

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/defaulters"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/deposit/maturity

Get deposit maturity report

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/deposit/maturity"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/diagnostic

Run diagnostic check

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/diagnostic"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/dividend-paid

Get dividend paid report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/dividend-paid"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/dividend-report

Get dividend report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/dividend-report"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/dividend-warrant

Get dividend warrant

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/dividend-warrant"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/divisions

Get division list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
wingNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/divisions"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/fd-certificate

Get FD certificate

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/fd-certificate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/fd/statement

Get FD statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/fd/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/financial-summary

Get financial summary (Trial Balance)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/financial-summary"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/heads

Get list of account heads

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/heads"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/interest-certificate

Get interest certificate

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/interest-certificate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/interest-list

Get interest list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/interest-list"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/jotting

Get jotting report

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/jotting"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/ledger/detail

Get detail ledger for a head code

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/ledger/detail"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/lien-account-information

Get lien account information

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/lien-account-information"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/loan-contributions-register

Get loan contributions register

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/loan-contributions-register"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/loan-nil-certificate/{memberNo}

Get loan nil certificate

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/loan-nil-certificate/{memberNo}"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/loan-types

Get loan types

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/loan-types"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/loans/interest-statement

Get interest receivable/received statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/loans/interest-statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/loans/new-disbursed

Get newly disbursed loans

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/loans/new-disbursed"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/member-balance-range

Get members by account number range

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/member-balance-range"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/member-ledger

Get member ledger

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/member-ledger"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/member-loan-detail

Get member loan detail report

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/member-loan-detail"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/member/{memberNo}/loan-cases

Get loan cases for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/member/{memberNo}/loan-cases"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/member/balance-range

Get members by balance range

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/member/balance-range"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/member/loan-ledger

Get member loan ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/member/loan-ledger"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/member/profile/{memberNo}

Get member profile

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/member/profile/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/member/statement

Get member statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/member/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/offices

Get office list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
wingNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/offices"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/passbook-printing

Get passbook printing data

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/passbook-printing"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/passbook-reset

Reset passbook print tracking for a member

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/passbook-reset"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/passbook-update-tracking

Update passbook tracking after print

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/passbook-update-tracking"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/rd/statement

Get RD statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/rd/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/recovery-details

Get recovery details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/recovery-details"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/recurring-details

Get recurring details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/recurring-details"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/saving/statement

Get saving statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/saving/statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/schedule

Get all report schedules

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
type	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/schedule"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/schedule

Create or update report schedule

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/schedule"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/schedule/{id}

Get report schedule details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/schedule/{id}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /reports/schedule/execute

Execute report schedule

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/reports/schedule/execute"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/share-certificate

Get share certificate

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/share-certificate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/share-warrant

Get share warrant

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/share-warrant"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/surety-register

Get surety register

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/surety-register"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/voters-list

Get voters list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/voters-list"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/wings

Get wing list

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/wings"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /reports/yearly-member-statement

Get yearly member statement

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/reports/yearly-member-statement"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Reports - Demand List

Endpoints in the Reports - Demand List module. (1 endpoint)

POST /transactions/reports/demand-list/generate

Generate detailed Members Demand List

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/reports/demand-list/generate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Role Management

User levels, default rights and menu permission mappings. (5 endpoints)

POST /admin/roles/defaults

Update default rights for a user level

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "userlevelid": 0,
  "menuIds": [
    0
  ]
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/roles/defaults" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "userlevelid": 0,
  "menuIds": [
    0
  ]
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/roles/defaults/{levelId}

Get default rights for a user level

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
levelId	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/roles/defaults/{levelId}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/roles/levels

Get all user levels

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/roles/levels" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/roles/levels

Create a new user level

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/roles/levels" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/roles/menus

Get all menu items

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/roles/menus" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```


Search

Endpoints in the Search module. (2 endpoints)

GET /search/global

Global search across all data types

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
q	query	yes	Search query
type	query	no	Search type filter
limit	query	no	Maximum results to return

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/search/global"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /search/suggestions

Get search suggestions

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
q	query	yes	Search query for suggestions
limit	query	no	Maximum suggestions to return

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/search/suggestions"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

System Configuration

Business rules, interest rates, deposit slabs and system settings. (19 endpoints)

GET /admin/config/business-rules

Get all business rules in a flat structure

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/business-rules" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/config/business-rules/bulk

Update multiple business rules at once

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "rules": {
    "RULE_LOAN_R_MAX_AMT": "150000",
    "SYS_DATA_ENTRY_MODE": true
  }
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/config/business-rules/bulk" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "rules": {
    "RULE_LOAN_R_MAX_AMT": "150000",
    "SYS_DATA_ENTRY_MODE": true
  }
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/config/deposit-slabs

Get all deposit slabs

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
type	query	no	—
isActive	query	no	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/deposit-slabs" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/config/deposit-slabs

Create deposit slab

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "type": "fixed_deposit",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/config/deposit-slabs" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "type": "fixed_deposit",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/config/deposit-slabs/{id}

Delete deposit slab

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/config/deposit-slabs/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/config/deposit-slabs/{id}

Get deposit slab by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/deposit-slabs/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/config/deposit-slabs/{id}

Update deposit slab

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/config/deposit-slabs/{id}" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "FD Slab 1-5 Lakhs",
  "description": "Fixed deposit slab for amounts between 1-5 lakhs",
  "minAmount": 100000,
  "maxAmount": 500000,
  "minTenure": 365,
  "maxTenure": 1825,
  "interestRate": 8.5,
  "penaltyRate": 1,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/config/deposit-slabs/bulk

Bulk replace all deposit slabs for a given type

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "type": "fixed_deposit",
  "rows": [
    {
      "name": null,
      "description": null,
      "type": null,
      "minAmount": null,
      "maxAmount": null,
      "minTenure": null,
      "maxTenure": null,
      "interestRate": null,
      "penaltyRate": null,
      "isActive": null,
      "effectiveFrom": null,
      "effectiveTo": null
    }
  ]
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/config/deposit-slabs/bulk" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "type": "fixed_deposit",
  "rows": [
    {
      "name": null,
      "description": null,
      "type": null,
      "minAmount": null,
      "maxAmount": null,
      "minTenure": null,
      "maxTenure": null,
      "interestRate": null,
      "penaltyRate": null,
      "isActive": null,
      "effectiveFrom": null,
      "effectiveTo": null
    }
  ]
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/config/interest-rates

Get all interest rates

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
type	query	no	—
isActive	query	no	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/interest-rates" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

POST /admin/config/interest-rates

Create interest rate

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{  
  "name": "Personal Loan Rate",  
  "description": "Standard interest rate for personal loans",  
  "type": "loan",  
  "rate": 12.5,  
  "calculationMethod": "reducing_balance",  
  "minAmount": 10000,  
  "maxAmount": 1000000,  
  "minTenure": 30,  
  "maxTenure": 3650,  
  "isActive": true,  
  "effectiveFrom": "2024-01-01",  
  "effectiveTo": "2024-12-31"  
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/config/interest-rates" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "Personal Loan Rate",
  "description": "Standard interest rate for personal loans",
  "type": "loan",
  "rate": 12.5,
  "calculationMethod": "reducing_balance",
  "minAmount": 10000,
  "maxAmount": 1000000,
  "minTenure": 30,
  "maxTenure": 3650,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/config/interest-rates/{id}

Delete interest rate

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/config/interest-rates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/config/interest-rates/{id}

Get interest rate by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/interest-rates/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/config/interest-rates/{id}

Update interest rate

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "name": "Personal Loan Rate",
  "description": "Standard interest rate for personal loans",
  "rate": 12.5,
  "calculationMethod": "reducing_balance",
  "minAmount": 10000,
  "maxAmount": 1000000,
  "minTenure": 30,
  "maxTenure": 3650,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/config/interest-rates/{id}" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "Personal Loan Rate",
  "description": "Standard interest rate for personal loans",
  "rate": 12.5,
  "calculationMethod": "reducing_balance",
  "minAmount": 10000,
  "maxAmount": 1000000,
  "minTenure": 30,
  "maxTenure": 3650,
  "isActive": true,
  "effectiveFrom": "2024-01-01",
  "effectiveTo": "2024-12-31"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/config/system

Get all system configurations

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
category	query	no	—
isActive	query	no	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/system" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/config/system

Create system configuration

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "key": "default_loan_interest_rate",
  "name": "Default Loan Interest Rate",
  "description": "Default interest rate applied to new loans",
  "value": "12.5",
  "dataType": "percentage",
  "category": "interest_rates",
  "isActive": true,
  "isReadonly": false,
  "validationRules": "{\"min\": 0, \"max\": 100}",
  "defaultValue": "10.0",
  "unit": "%"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/config/system" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "key": "default_loan_interest_rate",
  "name": "Default Loan Interest Rate",
  "description": "Default interest rate applied to new loans",
  "value": "12.5",
  "dataType": "percentage",
  "category": "interest_rates",
  "isActive": true,
  "isReadonly": false,
  "validationRules": "{\"min\": 0, \"max\": 100}",
  "defaultValue": "10.0",
  "unit": "%"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/config/system/{id}

Delete system configuration

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/config/system/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/config/system/{id}

Update system configuration

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	—

REQUEST BODY (JSON)

```
{
  "name": "Default Loan Interest Rate",
  "description": "Default interest rate applied to new loans",
  "value": "12.5",
  "dataType": "percentage",
  "category": "interest_rates",
  "isActive": true,
  "validationRules": "{\"min\": 0, \"max\": 100}",
  "defaultValue": "10.0",
  "unit": "%"
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/config/system/{id}" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "name": "Default Loan Interest Rate",
  "description": "Default interest rate applied to new loans",
  "value": "12.5",
  "dataType": "percentage",
  "category": "interest_rates",
  "isActive": true,
  "validationRules": "{\"min\": 0, \"max\": 100}",
  "defaultValue": "10.0",
  "unit": "%"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/config/system/initialize

Initialize default system configurations

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/config/system/initialize" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/config/system/key/{key}

Get system configuration by key

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
key	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/config/system/key/{key}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Transaction - Demand Generation

Endpoints in the Transaction - Demand Generation module. (3 endpoints)

POST /transactions/demand-generation/generate

Generate demand specifically for a period

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/demand-generation/generate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/demand-generation/import-preview

Parse Excel/CSV file and return preview data

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/demand-generation/import-preview"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/demand-generation/import-process

Save imported demand data to demand_master

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/demand-generation/import-process"
```


EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Transaction - Ledger Posting

Endpoints in the Transaction - Ledger Posting module. (2 endpoints)

POST /transactions/ledger-posting/post

Post demand recovery to General Ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/ledger-posting/post"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /transactions/ledger-posting/summary

Get member-wise demand summary for ledger posting

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
month	query	yes	—
year	query	yes	—
branch	query	yes	—
fromMember	query	yes	—
toMember	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/ledger-posting/summary"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Transaction - Short Recovery

Endpoints in the Transaction - Short Recovery module. (2 endpoints)

GET /transactions/short-recovery

Get all short recoveries

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
month	query	yes	—
year	query	yes	—
wing	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/short-recovery"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/short-recovery/adjust

Adjust a short recovery

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/short-recovery/adjust"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Transactions

Endpoints in the Transactions module. (16 endpoints)

POST /transactions/fix-trans-types

One-time fix: convert P/R to DR/CR in transactions table

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/fix-trans-types"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/fixed-deposit

Create a new Fixed Deposit

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/fixed-deposit"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/fixed-deposit/close

Close/Withdraw Fixed Deposit

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/fixed-deposit/close"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/fixed-deposit/interest-voucher

Create Interest Voucher

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/fixed-deposit/interest-voucher"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /transactions/fixed-deposit/member/{memberNo}

Get active FDs for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/fixed-deposit/member/{memberNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/loan-pass-flag

Update loan pass flag (Y=Approve, N=Pending, D=Decline)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/loan-pass-flag"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/loan-voucher

Generate a loan disbursement voucher

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/loan-voucher"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/member-balance-transfer/generate

Generate member balance transfer preview

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/member-balance-transfer/generate"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/member-balance-transfer/post

Post member balance transfer to ledger

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/member-balance-transfer/post"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/pass/{voucherNo}

Pass transaction - final posting to ledger and cashbook

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
voucherNo	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/pass/{voucherNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /transactions/pending-loans

Get all pending loan applications for approval

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/pending-loans"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/reverse/{voucherNo}

Reverse a posted transaction (ADMIN ONLY — destructive)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
voucherNo	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/reverse/{voucherNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /transactions/voucher

Create a generic voucher (Payment/Receipt/Journal)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/transactions/voucher"
```


EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /transactions/voucher/{voucherNo}

Delete/Reject a pending voucher

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
voucherNo	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/transactions/voucher/{voucherNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /transactions/voucher/{voucherNo}

Get voucher details by number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
voucherNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/voucher/{voucherNo}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /transactions/vouchers/pending

Get all pending vouchers

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/transactions/vouchers/pending"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

User Management

Create, update and administer users, roles, permissions, sessions and audit trail. (15 endpoints)

GET /admin/users

Get all users with pagination and filtering

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
page	query	no	Page number
limit	query	no	Items per page
role	query	no	Filter by role
isActive	query	no	Filter by active status
username	query	no	Filter by username (partial match)

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/users

Create a new user

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "username": "john_doe",
  "email": "john.doe@example.com",
  "password": "securePassword123",
  "firstName": "John",
  "lastName": "Doe",
  "role": "data_operator",
  "permissions": [
    "create_member"
  ],
  "isActive": true,
  "avatar": "/uploads/avatars/user-1.jpg"
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/users" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "username": "john_doe",
  "email": "john.doe@example.com",
  "password": "securePassword123",
  "firstName": "John",
  "lastName": "Doe",
  "role": "data_operator",
  "permissions": [
    "create_member"
  ],
  "isActive": true,
  "avatar": "/uploads/avatars/user-1.jpg"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /admin/users/{id}

Delete user

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/admin/users/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/users/{id}

Get user by ID

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users/{id}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/users/{id}

Update user information

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID

REQUEST BODY (JSON)

```
{
  "username": "john_doe",
  "password": "newSecurePassword123",
  "email": "john.doe@example.com",
  "firstName": "John",
  "lastName": "Doe",
  "role": "data_operator",
  "permissions": [
    "create_member"
  ],
  "isActive": true,
  "avatar": "string"
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/users/{id}" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "username": "john_doe",
  "password": "newSecurePassword123",
  "email": "john.doe@example.com",
  "firstName": "John",
  "lastName": "Doe",
  "role": "data_operator",
  "permissions": [
    "create_member"
  ],
  "isActive": true,
  "avatar": "string"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/users/{id}/activities

Get user activities

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users/{id}/activities" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/users/{id}/activities

Log user activity

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID

REQUEST BODY (JSON)

```
{
  "activityType": "LOGIN",
  "description": "User logged in successfully",
  "ipAddress": "192.168.1.1",
  "userAgent": "Mozilla/5.0..."
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/users/{id}/activities" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "activityType": "LOGIN",
  "description": "User logged in successfully",
  "ipAddress": "192.168.1.1",
  "userAgent": "Mozilla/5.0..."
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/users/{id}/login-history

Get a user login/logout history (audit trail)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users/{id}/login-history" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/users/{id}/password

Change user password (admin)

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID

REQUEST BODY (JSON)

```
{
  "newPassword": "newSecurePassword123"
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/users/{id}/password" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "newPassword": "newSecurePassword123"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/users/{id}/role

Update user role and permissions

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
id	path	yes	User ID

REQUEST BODY (JSON)

```
{
  "role": "system",
  "permissions": [
    "create_member"
  ]
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/users/{id}/role" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "role": "system",
  "permissions": [
    "create_member"
  ]
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/users/active-sessions/matrix

Get all active user sessions

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users/active-sessions/matrix" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /admin/users/active-sessions/terminate

Force logout a user session (Admin)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/admin/users/active-sessions/terminate" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/users/activities

Get all user activities

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users/activities" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PUT /admin/users/change-password

Change own password

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "currentPassword": "currentPassword123",
  "newPassword": "newSecurePassword123"
}
```

EXAMPLE REQUEST

```
curl -X PUT "http://<server-ip>:3001/api/v1/admin/users/change-password" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "currentPassword": "currentPassword123",
  "newPassword": "newSecurePassword123"
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /admin/users/roles/permissions

Get role permissions mapping

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/admin/users/roles/permissions" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

Utilities

Endpoints in the Utilities module. (70 endpoints)

GET /utilities

Legacy: list available utility services (index/health ping)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/balance-transfer

Process a manual balance transfer between accounts

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/balance-transfer" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/balance/account/{accountType}/{accountId}

Get account balance

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
accountType	path	yes	—

Name	In	Required	Description
accountId	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/balance/account/{accountType}/{accountId}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/balance/member/{memberId}

Get member balance inquiry

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	—
asOfDate	query	no	Balance as of date (YYYY-MM-DD)

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/balance/member/{memberId}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/balance/member/{memberId}/accounts

Get all account balances for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/balance/member/{memberId}/accounts" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/balance/member/{memberId}/realtime

Get real-time member balance

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/balance/member/{memberId}/realtime" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/business-rules

Get current business rules from busrules table

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/business-rules" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/business-rules

Save business rules to busrules table

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/business-rules" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/calculator/loan-rates

Get current loan interest rates from business rules

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/calculator/loan-rates"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/calculator/member-eligibility

Check loan eligibility for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	Member number

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/calculator/member-eligibility"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/data-consistency/check

Run comprehensive data consistency checks

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/data-consistency/check" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/data-correction/auto-fix

Auto-fix consistency issues

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/data-correction/auto-fix" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/data-correction/balance-discrepancies

Correct balance discrepancies

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
[
  "string"
]
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/data-correction/balance-discrepancies" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '[
  "string"
]'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/data-correction/fix-integrity

Fix data integrity issues

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/data-correction/fix-integrity" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/data-correction/orphaned-records

Fix orphaned records

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
[
  "string"
]
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/data-correction/orphaned-records" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '[
  "string"
]'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/data-correction/recalculate-balances

Recalculate all balances

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/data-correction/recalculate-balances" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/data-correction/remove-duplicates

Remove duplicate records

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "recordType": "member",
  "keepStrategy": "oldest",
  "manualKeepIds": [
    0
  ]
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/data-correction/remove-duplicates" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "recordType": "member",
  "keepStrategy": "oldest",
  "manualKeepIds": [
    0
  ]
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/demand-print-order

Get demand print order configuration

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/demand-print-order" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/demand-print-order

Save demand print order configuration

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/demand-print-order" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/deposit-loan-slabs

Get deposit/loan interest slabs from fdrd_slab_details

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
type	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/deposit-loan-slabs" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/deposit-loan-slabs

Save deposit/loan interest slabs to fdrd_slab_details

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/deposit-loan-slabs" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/dividend/pay

Process dividend payment — DR L1024, update dividend_master

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/dividend/pay" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/dividend/pending

Get pending dividends for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/dividend/pending" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

GET /utilities/divisions

Get all divisions from division_master

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/divisions" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

GET /utilities/fd-accounts/member

Get active FD accounts for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/fd-accounts/member" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/fd-interest/pay

Pay FD interest out to member — DR A003/FD, CR cash/bank, vchr_type=P

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/fd-interest/pay" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/fd-interest/post

Post FD interest voucher (accrual) — CR A003/FD, vchr_type=J

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/fd-interest/post" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/fd-rd-sb/accounts

Get FD/RD/SB accounts for a member

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	—
type	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/fd-rd-sb/accounts" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

POST /utilities/fd-rd-sb/entry

Save FD/RD/SB ledger entry

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/fd-rd-sb/entry" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 201,  
  "message": "Operation successful",  
  "data": { /* affected record */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

POST /utilities/fd-receipt

Create FD receipt — inserts into fdmaster + ledger (CR A003/FD)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/fd-receipt" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE


```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/financial-year/current

Get the current (latest) financial year

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/financial-year/current" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/financial-year/transfer-entries

Transfer entries for financial year closing

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/financial-year/transfer-entries" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/financial-years

Get distinct financial years from yearend table

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/financial-years" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/head-balance/{code}

Get the running ledger balance for an account head (e.g. a bank/cash account)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
code	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/head-balance/{code}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/head-master

Get all account heads from headmaster with balance sheet data

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/head-master" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/head-master

Add or update an account head in headmaster

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/head-master" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

DELETE /utilities/head-master/{code}

Delete an account head (blocked if it has children)

DELETES DATA Removes the target record. Generally irreversible — confirm the id before calling. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
code	path	yes	—

EXAMPLE REQUEST

```
curl -X DELETE "http://<server-ip>:3001/api/v1/utilities/head-master/{code}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/head-master/rebuild-tree

Rebuild balancesheet from ledger transactions (like legacy Build Tree)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/head-master/rebuild-tree" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/head-opening-balance

Get head opening balances for a financial year

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
yearcode	query	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/head-opening-balance" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/head-opening-balance

Save head opening balances for a financial year

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/head-opening-balance" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/head-opening-balance/apply/{yearcode}

Apply year opening balances to headmaster.op_bal

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
yearcode	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/head-opening-balance/apply/{yearcode}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/health/alerts

Get active health alerts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/health/alerts" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/health/alerts/{alertId}/resolve

Resolve a health alert

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
alertId	path	yes	—

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/health/alerts/{alertId}/resolve" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/health/alerts/all

Get all health alerts

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
hours	query	no	Number of hours to look back (default: 24)

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/health/alerts/all" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/health/diagnostics

Run comprehensive system diagnostics

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/health/diagnostics" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/health/history

Get system health history

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
hours	query	no	Number of hours to look back (default: 24)

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/health/history" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/health/performance

Get performance metrics

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/health/performance" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/health/status

Get current system health status

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/health/status" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/loan/entry

Save loan entry to loan_master and suretymaster

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/loan/entry" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/member/balance

Get member balance information

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	Member number

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/member/balance"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/payment-voucher

Save payment voucher to ledger (vchr_type=P, acc_type=BANK)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/payment-voucher" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/preferences

Get current user UI preferences

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/preferences" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /utilities/preferences

Update user UI preferences

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "interfaceMode": "light",
  "accentColor": "string",
  "fontScale": 0,
  "density": 0,
  "cornerRadius": 0,
  "fontFamily": "string",
  "backgroundType": "image",
  "backgroundColor1": "string",
  "backgroundColor2": "string",
  "backgroundImage": "string",
  "textColor": "string",
  "notifications": true,
  "syncAcrossWindows": true,
  "soundEffects": true,
  "inactivityLogout": true,
  "inactivityTimeoutMinutes": 0
}
```

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/utilities/preferences" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "interfaceMode": "light",
  "accentColor": "string",
  "fontScale": 0,
  "density": 0,
  "cornerRadius": 0,
  "fontFamily": "string",
  "backgroundType": "image",
  "backgroundColor1": "string",
  "backgroundColor2": "string",
  "backgroundImage": "string",
  "textColor": "string",
  "notifications": true,
  "syncAcrossWindows": true,
  "soundEffects": true,
  "inactivityLogout": true,
  "inactivityTimeoutMinutes": 0
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/rd-accounts/holders

List members who have at least one active RD account (for Premature Information dropdown)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/rd-accounts/holders"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/receipt

Save receipt: CR rows (vchr_type=R) + DR bank (vchr_type=P), same R_VCHR_NO

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/receipt" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/receipt-voucher

Save receipt voucher to ledger (vchr_type=R, DR CINH + CR rows)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/receipt-voucher" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 201,  
  "message": "Operation successful",  
  "data": { /* affected record */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

GET /utilities/saving/account/{accountNo}

Get saving account details and transaction history

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
accountNo	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/saving/account/{accountNo}" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

POST /utilities/saving/transaction

Save SB transaction to ledger (acc_type=SB)

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/saving/transaction" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/sb-accounts/holders

List members who have an SB account (for Premature Information dropdown)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/sb-accounts/holders"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/search/deposits

Search for deposit accounts (RD/FD) by member number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	Member number
type	query	yes	Deposit type

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/deposits"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/search/deposits-filtered

Search deposit accounts with filters (generic multi-field filter version)

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
query	query	no	General search query
memberNumber	query	no	Member number to search
accountNumber	query	no	Account number to search
status	query	no	Status filter
dateFrom	query	no	Date from (YYYY-MM-DD)
dateTo	query	no	Date to (YYYY-MM-DD)
amountFrom	query	no	Minimum amount
amountTo	query	no	Maximum amount
loanType	query	no	Loan type filter
memberIds	query	no	Member IDs to filter
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/deposits-filtered" \  
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* requested data */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```

GET /utilities/search/global

Global search across all entities

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
query	query	no	Search query
entityType	query	no	Entity type to search
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/global" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/search/loans

Search loan accounts with filters

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
query	query	no	General search query
memberNumber	query	no	Member number to search
accountNumber	query	no	Account number to search
status	query	no	Status filter
dateFrom	query	no	Date from (YYYY-MM-DD)
dateTo	query	no	Date to (YYYY-MM-DD)
amountFrom	query	no	Minimum amount
amountTo	query	no	Maximum amount
loanType	query	no	Loan type filter
memberIds	query	no	Member IDs to filter
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/loans" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/search/members

Search members with filters

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
query	query	no	General search query
memberNumber	query	no	Member number to search
accountNumber	query	no	Account number to search
status	query	no	Status filter
dateFrom	query	no	Date from (YYYY-MM-DD)
dateTo	query	no	Date to (YYYY-MM-DD)
amountFrom	query	no	Minimum amount
amountTo	query	no	Maximum amount
loanType	query	no	Loan type filter
memberIds	query	no	Member IDs to filter
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/members" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/search/sb-accounts

Search for savings bank accounts by member number

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
memberNo	query	yes	Member number

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/sb-accounts"
```


EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/search/transactions

Search transactions with filters

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
query	query	no	General search query
memberNumber	query	no	Member number to search
accountNumber	query	no	Account number to search
status	query	no	Status filter
dateFrom	query	no	Date from (YYYY-MM-DD)
dateTo	query	no	Date to (YYYY-MM-DD)
amountFrom	query	no	Minimum amount
amountTo	query	no	Maximum amount
loanType	query	no	Loan type filter
memberIds	query	no	Member IDs to filter
page	query	no	Page number
limit	query	no	Items per page

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/search/transactions" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

POST /utilities/statement/generate

Generate account statement

WRITES / ACTION Creates a record or performs an action. Modifies data or triggers processing. *Auth: Bearer JWT required.*

REQUEST BODY (JSON)

```
{
  "memberId": 0,
  "accountType": "string",
  "accountId": 0,
  "fromDate": "string",
  "toDate": "string",
  "includeClosed": true
}
```

EXAMPLE REQUEST

```
curl -X POST "http://<server-ip>:3001/api/v1/utilities/statement/generate" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "memberId": 0,
  "accountType": "string",
  "accountId": 0,
  "fromDate": "string",
  "toDate": "string",
  "includeClosed": true
}'
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 201,
  "message": "Operation successful",
  "data": { /* affected record */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/statement/member/{memberId}

Generate member statement for date range

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
memberId	path	yes	—
fromDate	query	yes	From date (YYYY-MM-DD)
toDate	query	yes	To date (YYYY-MM-DD)
accountType	query	no	Account type filter
accountId	query	no	Account ID filter
includeClosed	query	no	Include closed accounts

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/statement/member/{memberId}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

GET /utilities/system-settings/{key}

Get global system setting

READ-ONLY Safe. Returns data only; does not change anything on the server. *Auth: No auth guard declared in the spec (verify before relying on it).*

PARAMETERS

Name	In	Required	Description
key	path	yes	—

EXAMPLE REQUEST

```
curl -X GET "http://<server-ip>:3001/api/v1/utilities/system-settings/{key}"
```

EXAMPLE RESPONSE

```
{
  "success": true,
  "statusCode": 200,
  "message": "Operation successful",
  "data": { /* requested data */ },
  "timestamp": "2026-07-25T10:00:00.000Z"
}
```

PATCH /utilities/system-settings/{key}

Update global system setting

UPDATES DATA Modifies an existing record. Sending a field overwrites its stored value. *Auth: Bearer JWT required.*

PARAMETERS

Name	In	Required	Description
key	path	yes	—

EXAMPLE REQUEST

```
curl -X PATCH "http://<server-ip>:3001/api/v1/utilities/system-settings/{key}" \
-H "Authorization: Bearer $TOKEN"
```

EXAMPLE RESPONSE

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Operation successful",  
  "data": { /* affected record */ },  
  "timestamp": "2026-07-25T10:00:00.000Z"  
}
```