

Paperless
business

infinite

IT Solutions

Infinite IT Solutions SRL


DESADV TECHNICAL SPECIFICATION
DEDICATED FOR DEDEMAN PROJECT
VERSION 4.1 - EDInet XML



Filed name	Type	Format	Description
<Desadv>	M		
<DesadvHeader>	M		
<DesadvNumber></DesadvNumber>	M	AN(50)	Document number
<DesadvDate></DesadvDate>	M	YYYY-MM-DD	Document date
<PlannedDeliveryDate></PlannedDeliveryDate>	M	YYYY-MM-DD	Planned date delivery
<Comment></Comment>	O	AN(2000)	Comment
<DeliveryDetails>	O		Delivery terms
<TermsOfDelivery></TermsOfDelivery>	O	AN(3)	Codes INCOTERMS
<Description></Description>	O	AN(2000)	Description of the conditions of delivery
</DeliveryDetails>			
<TransportDetails>	O		Transport Details
<TransportModeCode></TransportModeCode>	O	AN(3)	Mode of transport: 10 = see; 20 = Railway ; 30 = road ; 40 = air; 60 = multimodal
<MeansOfTransport>	O		Information about transport means
<Identyfication></Identyfication>	O	AN(50)	Identyfication number means of transport
<Ownership></Ownership>	O	AN(3)	Owner code means of transport: 1 – Owner of the goods is the owner of the center of transportation; 2 – Owner of the goods does not own the means of transport
<Nationality></Nationality>	O	AN(3)	Code of the country in which the registered means of transport
</MeansOfTransport>			
</TransportDetails>			
<ReferenceDocs>	O		Reference Document - associated with DESADV
<OrderAtBuyer>	O		Order in the system the buyer
<DocID></DocID>	M	AN(50)	Document number
<DocDate></DocDate>	O	YYYY-MM-DD	Document date
</OrderAtBuyer>			



<DeliveryDocument>	O		Data delivery
<DocID></DocID>	M	AN(50)	Document number (number WZ)
<DocDate></DocDate>	O	YYYY-MM-DD	Document date
</DeliveryDocument>			
<TransportDocument>	O		Waybill data
<DocID></DocID>	M	AN(50)	Document number
<DocDate></DocDate>	O	YYYY-MM-DD	Document date
</TransportDocument>			
</ReferenceDocs>			
</DesadvHeader>			
<DesadvParty>	M		
<BuyerParty>	M		Party communication – Buyer
<Name></Name>	M	AN(500)	Name of the party involved in the communication
<ILN></ILN>	M	AN(50)	Code GLN
<TaxID></TaxID>	O	AN(50)	Tax identification number
<IDInSupplierSys></IDInSupplierSys>	O	AN(100)	Code page on your system vendor/deliver
<AddressDetails>	O		
<City></City>	O	AN(500)	City
<PostalCode></PostalCode>	O	AN(50)	Postal Code
<Street></Street>	O	AN(100)	Street
<HouseNumber></HouseNumber>	O	AN(50)	House Number/ local
<CountryCode></CountryCode>	O	AN(3)	Country
</AddressDetails>			
</BuyerParty>			
<ShipToParty>	M		Party communication – delivery location
<Name></Name>	M	AN(500)	Name of the party involved in the communication



<ILN></ILN>	M	AN(50)	Code GLN
<TaxID></TaxID>	O	AN(50)	Tax identification number
<IDInSupplierSys></IDInSupplierSys>	O	AN(100)	Code page on your system vendor/deliver
<AddressDetails>	O		
<City></City>	O	AN(500)	City
<PostalCode></PostalCode>	O	AN(50)	Postal code
<Street></Street>	O	AN(100)	Street
<HouseNumber></HouseNumber>	O	AN(50)	House number/local
<CountryCode></CountryCode>	O	AN(3)	Country
</AddressDetails>			
</ShipToParty>			
<SellerParty>	M		Party communication – Seller
<Name></Name>	M	AN(500)	Name of the parties involved in the communication
<ILN></ILN>	M	AN(50)	Code GLN
<TaxID></TaxID>	O	AN(50)	Tax identification number
<IDInBuyerSys></IDInBuyerSys>	M	AN(100)	Code pages in the system the buyer
<AddressDetails>	O		
<City></City>	O	AN(500)	City
<PostalCode></PostalCode>	O	AN(50)	Postal Code
<Street></Street>	O	AN(100)	Street
<HouseNumber></HouseNumber>	O	AN(50)	House number/local
<CountryCode></CountryCode>	O	AN(3)	Country
</AddressDetails>			
</SellerParty>			
<ShipFromParty>	O/M*		Party communication – The point of export - * mandatory when supplier have more than one branch
<Name></Name>	M	AN(500)	Name the parties to the communication



<ILN></ILN>	M	AN(50)	Code GLN
<TaxID></TaxID>	O	AN(50)	Tax identification number
<IDInSupplierSys></IDInSupplierSys>	O	AN(100)	Code pages in the system seller/deliver
<IDInBuyerSys></IDInBuyerSys>	O	AN(100)	Code pages in the system purchase
<AddressDetails>	O		
<City></City>	O	AN(500)	City
<PostalCode></PostalCode>	O	AN(50)	Postal Code
<Street></Street>	O	AN(100)	Street
<HouseNumber></HouseNumber>	O	AN(50)	House number/ local
<CountryCode></CountryCode>	O	AN(3)	Country
</AddressDetails>			
</ShipFromParty>			
<ForwarderParty>	O		Party communication – Freight forwarder
<Name></Name>	M	AN(500)	Name the parties to the communication
<ILN></ILN>	M	AN(50)	Code GLN
<IDInSupplierSys></IDInSupplierSys>	O	AN(100)	Code pages in the system seller/deliver
<IDInBuyerSys></IDInBuyerSys>	O	AN(100)	Code pages in the system buyer
</ForwarderParty>			
<SellerHeadquartersParty>	O		The seat of the seller
<Name></Name>	M	AN(500)	Name the parties to the communication
<ILN></ILN>	M	AN(50)	Code GLN
<TaxID></TaxID>	O	AN(50)	Tax identification number
<IDInSupplierSys></IDInSupplierSys>	O	AN(100)	Code pages in the system the seller/deliver
<IDInBuyerSys></IDInBuyerSys>	O	AN(100)	Code pages in the system the buyer
<AddressDetails>	O		
<City></City>	O	AN(500)	City



<PostalCode></PostalCode>	O	AN(50)	Postal code
<Street></Street>	O	AN(100)	Street
<HouseNumber></HouseNumber>	O	AN(50)	House number/local
<CountryCode></CountryCode>	O	AN(3)	Country
</AddressDetails>			
<DefaultContact>	O		The basic contact details for the party communication
<Person></Person>	O	AN(500)	Communication person
<Tel></Tel>	O	AN(50)	Phone number
<Fax></Fax>	O	AN(50)	Fax
<EMail></EMail>	O	AN(100)	E-mail
</DefaultContact>			
</SellerHeadquartersParty>			
<ConsigneeParty>	O		The final recipient
<ILN></ILN>	M	AN(50)	Code GLN
</ConsigneeParty>			
</DesadvParty>			
<DesadvDetail>	M		
<Packaging>	M*		
<StructureLevelId></StructureLevelId>	M	N	Packing level identification
<ParentStructureLevelId></ParentStructureLevelId>	O	N	ID of the parent structure
<PackageIdentification>	O*		
<PackageQuantity></PackageQuantity>	O	R(3)	Number of packages given level
<PackageType></PackageType>	O	AN(3)	Packet type
<Description></Description>	O	AN(2000)	Packet Description
<GTIN></GTIN>	O	AN(50)	Global Trade Item Number
<SSCC></SSCC>	O	AN(50)	The serial number of the order



</PackageIdentification>			
<LineItems>	M		
<Item>	M*		
<ItemNum></ItemNum>	M	N	Position number
<EAN></EAN>	O	AN(50)	European commodity code
<BuyerItemID></BuyerItemID>	O	AN(50)	Product code in the system buyer
<SellerItemID></SellerItemID>	O	AN(50)	Product code in the system seller
<BatchNumber></BatchNumber>	O	AN(200)	Batch number
<PacketContentQuantity></PacketContentQuantity>	O	R(3)	Number of units in carton
<QuantityValue></QuantityValue>	M	R(3)	The amount realized/sent
<UnitOfMeasure></UnitOfMeasure>	M	AN(3)	Unit of measurement for the above unit
<ChangeReasonCode></ChangeReasonCode>	O	AN(2)	Reason to change the quantity supplied: AB- Discontinued; AC- too much; AD- lack of goods in the warehouse. Seller; AE- no information was provided; AF- goods damaged; AG- delivered after the time.
<Name></Name>	M	AN(500)	Products name
<Description></Description>	O	AN(2000)	Description of the items DESADVa
<OrderedQuantity></OrderedQuantity>	M	R(3)	The amount ordered
<DeliveryDate></DeliveryDate>	M	YYYY-MM-DD	Delivery date
<Comment></Comment>	O	AN(2000)	Comment of the items
<ActionRequestCode></ActionRequestCode>	O	AN(50)	Label (for backwards compatibility)
<BestBeforeDate></BestBeforeDate>	O	YYYY-MM-DD	Term suitability
<HandlingInstructions></HandlingInstructions>	O	AN(2000)	Manual storage
<ReferenceDocs>	O		Reference document – associated with DESADV
<OrderAtBuyer>	O		Order in the system the buyer
<DocID></DocID>	M	AN(50)	Document number
<DocDate></DocDate>	O	YYYY-MM-DD	Document date
</OrderAtBuyer>			



<DeliveryDocument>	O		Delivery number (Delivery note)
<DocID></DocID>	M	AN(50)	Document number
<DocDate></DocDate>	O	YYYY-MM-DD	Document number
</DeliveryDocument>			
</ReferenceDocs>			
</Item>			
</LineItems>			
</Packaging>			
</DesadvDetail>			
<DesadvSummary>	O		
<TotalShippedQuantity></TotalShippedQuantity>	O	R(3)	The number of units shipped
<TotalGrossWeight></TotalGrossWeight>	O	R(3)	Gross weight of the entire delivery
<TotalWeightUnitOfMeasure></TotalWeightUnitOfMeasure>	O	AN(3)	Unit weights for summary
</DesadvSummary>			
</Desadv>			

Field type:

M – Mandatory field

M* – Mandatory field, segment can occur repeatedly

O – Optional field

O* – Optional field, segment may occur repeatedly

Field formats:

AN(X)	A string of alphanumeric characters in length max x
-------	---



YYYY-MM-DD	Date field
YYYY-MM-DDThh:mm:ss	Date and hours field
N	Natural number
R(X)	Real number with precision to the x position of the decimal point separator „.” dot

Unit of measures:

COL	coli
SET	set
ROL	rola
L	litru
PAL	palet
PAC	pachet
M3	mentru cub
M2	metru patrat
M	metru
BUC	bucata
PUN	bag
ML	militer
KGM	kilogramm
CUT	cutie

Attention:

1/ Obligatory, the length and format of the fields are variable and depend on the findings of the parties exchanging messages.

2/ Fields: order number, order date, delivery number, date of document delivery, place of delivery can be transmitted on the lines or in the header. The principle of transfer in / data in the header for the case where all goods sold refers to the same order number, order date, delivery number, date, document delivery and place of delivery.

