

Imp Language Extension in Haskell

Calinov Cosmin

March 7, 2026

1 Introduction

This project implements an interpreter for an extended version of the IMP toy language using Haskell. The goal is to define the language formally (Syntax and Semantics) and verify its properties using property-based testing (QuickCheck).

The language builds upon the standard IMP imperative language by adding:

- **Rich Arithmetic:** Support for Modulo (%) and Power (^) operators.
- **Boolean Logic:** Full boolean expression support including comparison and logical operators.
- **Scoping:** A `Block` construct to group statements.
- **Concurrency:** A `Par` construct for the parallel execution of statements, which merges the resulting states deterministically.

The interpreter relies on Big-Step Operational Semantics (Natural Semantics) to define the execution rules.

2 Abstract Syntax Tree

2.1 Formal Grammar

What programs look like

$$\begin{aligned} \langle Exp \rangle ::= & \langle Integer \rangle \mid \langle Variable \rangle \\ & \mid \langle Exp \rangle \text{ '+' } \langle Exp \rangle \mid \langle Exp \rangle \text{ '*' } \langle Exp \rangle \\ & \mid \langle Exp \rangle \text{ '-' } \langle Exp \rangle \mid \langle Exp \rangle \text{ '/' } \langle Exp \rangle \\ & \mid \langle Exp \rangle \text{ '%' } \langle Exp \rangle \mid \langle Exp \rangle \text{ '^' } \langle Exp \rangle \\ & \mid \text{'true'} \mid \text{'false'} \\ & \mid \langle Exp \rangle \text{ '==' } \langle Exp \rangle \mid \langle Exp \rangle \text{ '<=' } \langle Exp \rangle \\ & \mid \langle Exp \rangle \text{ '>=' } \langle Exp \rangle \mid \langle Exp \rangle \text{ '<' } \langle Exp \rangle \\ & \mid \langle Exp \rangle \text{ '>' } \langle Exp \rangle \mid \text{'not'} \langle Exp \rangle \\ & \mid \langle Exp \rangle \text{ '&&' } \langle Exp \rangle \mid \langle Exp \rangle \text{ '||' } \langle Exp \rangle \end{aligned}$$

$$\langle StmtList \rangle ::= \langle Stmt \rangle \mid \langle Stmt \rangle \text{ ';' } \langle StmtList \rangle$$

$$\begin{aligned} \langle Stmt \rangle ::= & \text{'skip'} \\ & \mid \langle Variable \rangle \text{' := ' } \langle Exp \rangle \\ & \mid \langle Stmt \rangle \text{' ; ' } \langle Stmt \rangle \\ & \mid \text{'if' } \langle Exp \rangle \text{' then' } \langle Stmt \rangle \text{' else' } \langle Stmt \rangle \\ & \mid \text{'while' } \langle Exp \rangle \text{' do' } \langle Stmt \rangle \\ & \mid \text{'{' } \langle StmtList \rangle \text{' } \text{'}} \\ & \mid \text{'par' '{' } \langle StmtList \rangle \text{' } \text{'}} \end{aligned}$$

2.2 Data Types

Common Data Types

```

1      newtype Variable = Var String deriving (Eq,
2      Ord, Show)
3
4      data Value = VInt Int | VBool Bool deriving
5      (Eq, Show)
6
7      newtype MyState = List [(Variable, Value)]
8      deriving (Eq, Show)

```

Expression

```

1      data Exp = EVar Variable
2      | EInt Int
3      | EAdd Exp Exp
4      | EMul Exp Exp
5      | ESub Exp Exp
6      | EDiv Exp Exp
7      | EMod Exp Exp
8      | EPow Exp Exp
9      | BExp Bool
10     | BEq Exp Exp
11     | BLt Exp Exp
12     | BGt Exp Exp
13     | BLte Exp Exp
14     | BGte Exp Exp
15     | BAnd Exp Exp
16     | BOr Exp Exp
17     | BNot Exp
18     deriving Show

```

Note: EMod and EPow correspond to the % operator and ^ operator, respectively.

Statement

```
1      data Stmt = Assign Variable Exp
2      | Seq Stmt Stmt
3      | If Exp Stmt Stmt
4      | While Exp Stmt
5      | Skip
6      | Block [Stmt]
7      | Par [Stmt]
8      deriving Show
```

3 State

The state in the extended language is just a function that takes a Variable and returns its assigned Value.

$$\sigma : Var \rightarrow Val$$

4 Formal Semantics

What programs do.

4.1 Skip

$$\overline{\langle \text{skip}, \sigma \rangle} \Downarrow \sigma$$

4.2 Evaluation of Expressions

The evaluation of expressions relies on the state σ to retrieve variable values.

Constants and Variables:

$$\overline{\langle n, \sigma \rangle} \Downarrow n \quad (n \in \mathbb{Z}) \quad \overline{\langle b, \sigma \rangle} \Downarrow b \quad (b \in \{\text{true}, \text{false}\}) \quad \frac{x \in \text{Dom}(\sigma)}{\overline{\langle x, \sigma \rangle} \Downarrow \sigma(x)}$$

Binary Operations: For any binary operator $\oplus$ (e.g., $+$, $-$, $*$, $\leq$, $\wedge$):

$$\frac{\overline{\langle e_1, \sigma \rangle} \Downarrow v_1 \quad \overline{\langle e_2, \sigma \rangle} \Downarrow v_2}{\overline{\langle e_1 \oplus e_2, \sigma \rangle} \Downarrow v_1 \oplus_{val} v_2}$$

4.3 Assignment

$$\frac{\overline{\langle e, \sigma \rangle} \Downarrow v}{\overline{\langle x := e, \sigma \rangle} \Downarrow \sigma[x \mapsto v]}$$

4.4 Sequencing

$$\frac{\overline{\langle S_1, \sigma \rangle} \Downarrow \sigma' \quad \overline{\langle S_2, \sigma' \rangle} \Downarrow \sigma''}{\overline{\langle S_1; S_2, \sigma \rangle} \Downarrow \sigma''}$$

4.5 Conditional (If)

True Branch

$$\frac{\langle b, \sigma \rangle \Downarrow \text{true} \quad \langle S_1, \sigma \rangle \Downarrow \sigma'}{\langle \text{if } b \text{ then } S_1 \text{ else } S_2, \sigma \rangle \Downarrow \sigma'}$$

False Branch

$$\frac{\langle b, \sigma \rangle \Downarrow \text{false} \quad \langle S_2, \sigma \rangle \Downarrow \sigma'}{\langle \text{if } b \text{ then } S_1 \text{ else } S_2, \sigma \rangle \Downarrow \sigma'}$$

4.6 While

True

$$\frac{\langle b, \sigma \rangle \Downarrow \text{true} \quad \langle S, \sigma \rangle \Downarrow \sigma' \quad \langle \text{while } b \text{ do } S, \sigma' \rangle \Downarrow \sigma''}{\langle \text{while } b \text{ do } S, \sigma \rangle \Downarrow \sigma''}$$

False

$$\frac{\langle b, \sigma \rangle \Downarrow \text{false}}{\langle \text{while } b \text{ do } S, \sigma \rangle \Downarrow \sigma}$$

4.7 Block

A block of statements behaves like a recursive sequence.

$$\frac{}{\langle \text{block } [], \sigma \rangle \Downarrow \sigma} \quad \frac{\langle S, \sigma \rangle \Downarrow \sigma' \quad \langle \text{block } Ss, \sigma' \rangle \Downarrow \sigma''}{\langle \text{block } (S : Ss), \sigma \rangle \Downarrow \sigma''}$$

4.8 Parallel Execution (Par)

Parallel execution evaluates a list of statements $[S_1, \dots, S_n]$ concurrently, all starting from the initial state σ . The final state is obtained by merging the resulting states.

$$\frac{\forall i \in \{1..n\}, \langle S_i, \sigma \rangle \Downarrow \sigma_i \quad \sigma' = \text{merge}(\sigma_n, \dots, \sigma_1)}{\langle \text{par } [S_1, \dots, S_n], \sigma \rangle \Downarrow \sigma'}$$

Where *merge* resolves conflicts by prioritizing the last statement (Last Writer Wins):

$$\text{merge}(\sigma_n, \dots, \sigma_1)(x) = \begin{cases} \sigma_n(x) & \text{if } x \in \text{Dom}(\sigma_n) \\ \sigma_{n-1}(x) & \text{if } x \notin \text{Dom}(\sigma_n) \text{ and } x \in \text{Dom}(\sigma_{n-1}) \\ \dots & \\ \sigma_1(x) & \text{otherwise} \end{cases}$$

5 Property-based Testing using QuickCheck

5.1 Skip doesn't modify the state of the program

Skip statement's usefulness is shown in this property.

$$\text{stmt}(\sigma, \text{Skip}) = \sigma$$

5.2 Sequential execution is compositional

A staple for all programming languages that are deterministic.

$$\text{stmt}(\sigma, \text{Seq } s_1 s_2) = \text{stmt}(\text{stmt}(\sigma, s_1), s_2)$$

5.3 Assigning a variable and then getting its value returns the assigned value

Basic testing for state's functionality.

$$\text{get}(\text{stmt}(\sigma, \text{Assign } x \ v), x) = v$$

5.4 Sequencing statements is associative

Doesn't matter in which order you run the operation, the end result is the same.

$$\text{stmt}(\sigma, \text{Seq}(\text{Seq}(s_1, s_2), s_3)) = \text{stmt}(\sigma, \text{Seq}(s_1, \text{Seq}(s_2, s_3)))$$

5.5 Program execution is deterministic

This property illustrates that the rules of the language are consistent i.e. running the same statement at two different times doesn't change its outcome. This is especially useful when it comes to the Par statement, which is specifically designed to be deterministic. Other possible implementations could have chosen more stochastic approaches, the test failing in those particular cases. Another challenge was that While loops could run indefinitely. This was caused by the fact that the generated condition of the While loop would sometimes evaluate to True, thus running forever. I chose the simplest fix: I removed the the While statement from the Arbitrary instance of Stmt. The other possible fix would have been to add a "fuel" limit for every evaluation of each statement, but this would have required to change the the signature and consequently a significant part of the evaluation function's logic.

$$\text{stmt}(\sigma, s) = \text{stmt}(\sigma, s)$$

6 Usage Examples

6.1 Example 1: Loop and Arithmetic

```
1      main :: IO ()
2      main = do
3          let x = Var "x"
4          y = Var "y"
5          example = Seq
6              (Assign x (EInt 0))
7              (While (BLt (EVar x) (EInt 3)) (Block
8                  [ Assign y (EAdd (EVar x) (EInt 1))
9                    , Assign x (EAdd (EVar x) (EInt 1))
10                  ]))
11
12      final = stmt (List []) example
13      (val, _) = get final y
14
15      putStrLn $ "Result of program (value of y):
16                  " ++ show val
```

Output: Result of program (value of y): VInt 3

6.2 Example 2: Parallel Assignment

```
1      stmt5 = Par
2          [ Assign (Var "x") (EInt 1)
3            , Assign (Var "y") (EInt 2) ]
4      finalState3 = stmt (List []) stmt5
5      valX = fst (get finalState3 (Var "x"))
6      valY = fst (get finalState3 (Var "y"))
```

Result: valX is VInt 1, valY is VInt 2.

7 Conclusion

This project successfully extended the IMP language with arithmetic operators, local scoping, and deterministic parallelism. The implementation was verified using the QuickCheck library, ensuring adherence to the formal semantics defined using Big-Step operational rules. The use of property-based testing proved effective in identifying edge cases, particularly in non-terminating loops and state consistency during parallel execution.

8 References

- Chalmers University of Technology. *QuickCheck: A Lightweight Tool for Random Testing of Haskell Programs* <https://dl.acm.org/doi/epdf/>

10.1145/351240.351266

- Hackage. *QuickCheck: Automatic testing of Haskell programs* <https://hackage.haskell.org/package/QuickCheck>
- sulzmann.github.io. *QuickCheck: Automatic Testing* <https://sulzmann.github.io/ProgrammingParadigms/lec-haskell-testing.html>
- University of Nottingham. *Programming language semantics: It's easy as 1,2,3* <https://people.cs.nott.ac.uk/pszgmh/123.pdf>)