

# Deploying and Debugging

After [creating your C-Apps and deployable archives](#), you are ready to deploy them to one or more Carbon servers (that is, servers for products based on WSO2 Carbon). You can then test them and debug your applications and artifacts as needed.

**i** If you are running products in a cluster, you can use [Deployment Synchronizer](#) to keep the configurations on all nodes in the cluster in synch.

- [Deploying a C-App using the management console](#)
- [Deploying a C-App to a running server inside Eclipse](#)
- [Redeploying a C-App to a running server inside Eclipse](#)
- [Deploying a C-App to multiple servers using the Maven plug-in](#)
  - [Adding the plug-in to the POM file](#)
  - [Generating and deploying the CAR file](#)
- [Debugging your application](#)

## Deploying a C-App using the management console

To deploy the CAR file for the C-App to a Carbon server, start the server, log in to the management console for that product, go to **Application -> Add**, and browse for the CAR file that you have created.

**WSO2 Enterprise Service Bus (WSO2...)**

**Management Console**

Signed-in as: admin@10.100.3.31:9443 | [Sign-out](#) | [Docs](#) | [About](#)

**WSO2 ESB Home** [? Help](#)


Welcome to the WSO2 ESB Management Console

Server	
Host	10.100.3.31
Server URL	https://10.100.3.31:9443/services/
Server Start Time	2012-02-10 14:05:42
System Up Time	0 day(s) 0 hr(s) 1 min(s) 36 sec(s)
Version	4.0.0
Repository Location	file:/C:/wso2/WSO2ESB~1.0/bin/..repository/deployment/server/

Operating System	
OS Name	Windows 7
OS Version	6.1

Operating System User

https://localhost:9443/carbon/carbonapps/app\_upload.jsp?region=region1&item=apps\_add\_menu



Once you click **Upload**, you will be asked to **Refresh** the browser. Once you refresh, you will see that the **CAR** file has been deployed.

## Deploying a C-App to a running server inside Eclipse

Before you deploy the created C-App project, you have to choose the artifacts you need to deploy. For that, double click on the **pom.xml** and select artifacts you need to deploy and save the changes.

MyCompositeApplication/pom.xml

### MyCompositeApplication

Group Id: com.example.MyCompositeApplic

Artifact Id: MyCompositeApplication

Version: 1.0.0

Description: MyCompositeApplication

**Dependencies**

Artifact	Server Role	Version
<input type="checkbox"/> MyRegistryResources	--	1.0.0
<input checked="" type="checkbox"/> SynapseConfigs	--	1.0.0
<input checked="" type="checkbox"/> com.example.CustomerDS_._CustomerDS	DataServicesServer	1.0.0
<input type="checkbox"/> com.example.MyHandlerProject_._MyHandlerProject	GovernanceRegistry	1.0.0
<input type="checkbox"/> com.example.WebApp_._WebApp	ApplicationServer	1.0.0
<input checked="" type="checkbox"/> org.wso2.sample.CardAxis2Service_._CardAxis2Service	ApplicationServer	1.0.0
<input checked="" type="checkbox"/> org.wso2.sample.MyRegistryFilterProject_._MyRegistryFilterProject	GovernanceRegistry	1.0.0
<input checked="" type="checkbox"/> wso2.hcc.MainframePojoService_._MainframePojoService	ApplicationServer	1.0.0

Select All    Deselect All

Go to **Servers** view, right click and select **New -> Server**.

MyCompositeApplication/pom.xml

### MyCompositeApplication

Group Id: com.example.MyCompositeApplic

Artifact Id: MyCompositeApplication

Version: 1.0.0

Description: MyCompositeApplication

**Dependencies**

Artifact	Server Role	Version
<input type="checkbox"/> MyRegistryResources	--	1.0.0
<input checked="" type="checkbox"/> SynapseConfigs	--	1.0.0
<input checked="" type="checkbox"/> com.example.CustomerDS_._CustomerDS	DataServicesServer	1.0.0
<input type="checkbox"/> com.example.MyHandlerProject_._MyHandlerProject	GovernanceRegistry	1.0.0
<input type="checkbox"/> com.example.WebApp_._WebApp	ApplicationServer	1.0.0
<input checked="" type="checkbox"/> org.wso2.sample.CardAxis2Service_._CardAxis2Service	ApplicationServer	1.0.0
<input checked="" type="checkbox"/> org.wso2.sample.MyRegistryFilterProject_._MyRegistryFilterProject	GovernanceRegistry	1.0.0
<input checked="" type="checkbox"/> wso2.hcc.MainframePojoService_._MainframePojoService	ApplicationServer	1.0.0

Select All    Deselect All

Design    Source


Markers    Properties    Servers    Data Source Explorer


No servers available. Define a new server from the [new server wizard...](#)

New    Server


Properties

Select the relevant version of the server under the **WSO2** category. For example, **WSO2 Carbon 4.2 based server**.

 To see the relevant version of the Carbon based server, refer to the [Release Matrix](#).



If you have not added WSO2 Server instances before, you will need to specify the location of the downloaded WSO2 Server instance.



**New Server**

**New WSO2 Carbon 4.2 based server Runtime**

Define a new WSO2 Carbon 4.2 based server runtime


You can use [Installed JRE preferences](#) to create a new JRE

JRE: Default JRE


Runtime Name WSO2 Carbon 4.2 based server

CARBON\_HOME /Users/USER03/Downloads/wso2carbon-4.2.0

Now you will see your version of the server (for example **WSO2 Carbon 4.2 based server**) added to the **Server Runtime Environments**. Click **OK**.




You can change ports if you want. If the default ports are not used by any other application, you can keep them as they are. After setting the ports click **Next**.


A screenshot of a 'New Server' dialog box in WSO2 Developer Studio. The dialog has a title bar with standard Mac OS window controls. Below the title bar, the text 'New WSO2 Carbon 4.2 based server Server' is displayed, followed by the instruction 'Create a new WSO2 Carbon 4.2 based server server'. To the right of this text is a small icon of a server rack. The main area of the dialog contains several configuration options, each with a text input field or a checkbox. The options are: 'Carbon service port (HTTP)' with the value '9763', 'Carbon web console port (HTTPS)' with the value '9443', 'Carbon Server Offset' with the value '0', 'Carbon server debug port' with the value '5001', 'Synapse transport HTTP port(change only if applicable)' with the value '9763', 'Synapse transport HTTPS port(change only if applicable)' with the value '9443', 'Bring up the CARBON\_HOME in the browser when this server starts.' with a checked checkbox, 'Enable hot update of published server modules' with a checked checkbox, and 'Enable OSGi console' with an unchecked checkbox. At the bottom of the dialog are four buttons: '< Back', 'Next >', 'Cancel', and 'Finish'.

Add the C-App project and click **Finish**.





Now you will see the newly added server listed in the **Servers** view. Right click on the **WSO2 Carbon x.x.x based server at localhost** and select **Start** from the menu.




## Redeploying a C-App to a running server inside Eclipse

After you have deployed your C-App to a running server inside Eclipse, you may want to change the content of your C-App. In that case you do not need to remove the deployed C-App from the server and deploy again to the server. Instead you can re-deploy an already deployed C-App. Deploy the C-App project according to the instructions given above and then do the necessary changes to your C-App project.

Open the **Servers** view in Eclipse using **Window => Show View => Servers**.

Click on the expandable icon of the Server you are running inside Eclipse. (This expandable icons available only if you have deployed a project in that server). Right-click on the project and click **Re-deploy**.



Then you will see that your Eclipse console is updated and you can notice that your C-App project is deployed again.

## Deploying a C-App to multiple servers using the Maven plug-in

The WSO2 CAR Deploy plug-in for Maven allows you to generate the CAR file for a C-App and then deploy it (or undeploy it) on multiple local and remote Carbon servers, including StratosLive. To use this plug-in, you add it to the `pom.xml` file for your C-App and then use the `mvn clean deploy` command to generate and deploy the CAR.

### Adding the plug-in to the POM file

1. Under the C-App you want to deploy, double-click the `pom.xml` file to open it in the editor.
2. Click the Source tab and navigate to the `maven-car-deploy-plugin` under `<build> -> <plugins>`.
3. Modify the `maven-car-deploy-plugin` properties as follows:
  - a. Under `<carbonServers>`, create one `<CarbonServer>` for each Carbon server where you want to deploy the CAR file.
  - b. Specify the following properties for each Carbon server:
    - If you are using a custom certificate with your Carbon server, import the public key of the custom certificate to your trust store, and then set the `<trustStorePath>`, `<trustStorePassword>`, and `<trustStoreType>` properties to the location, password, and type of your trust store.
    - Set the `<serverUrl>`, `<userName>`, and `<password>` properties to the URL (such as `https://localhost:9443`), user name, and password for the Carbon server.
    - In the `<operation>` element, specify whether to deploy or undeploy the CAR file for this Carbon server.
4. In the `<properties>` section at the end of the POM file, do the following:
  - a. Add the following line to ensure that the CAR will be deployed:
 

```
<maven.car.deploy.skip>false</maven.car.deploy.skip>
```
  - b. If you want to deploy the CAR file to a remote Maven repository in addition to the Carbon servers, add the following line:
 

```
<maven.deploy.skip>false</maven.deploy.skip>
```

**Note:** You will be able to override both of these settings when you run the Maven command.
5. Save the file.

You are now ready to generate and deploy the CAR file for this C-App.

### Generating and deploying the CAR file

You now run the `mvn clean deploy` command to generate the CAR file and deploy it to the Carbon servers in a single step. You can add parameters to the command to override the configuration. For example, to deploy the CAR file to the Carbon servers but not to the remote Maven repository, add the `-Dmaven.deploy.skip=true` parameter.

er, as follows:

```
mvn clean deploy -Dmaven.deploy.skip=true
```

If you want to deploy to the remote Maven repository but not the Carbon servers, add the `-Dmaven.car.deploy.skip=true` parameter, as follows:

```
mvn clean deploy -Dmaven.car.deploy.skip=true
```


You can also skip deployment to both the remote repository AND the Carbon servers:

```
mvn clean deploy -Dmaven.deploy.skip=true -Dmaven.car.deploy.skip=true
```


## Debugging your application

Suppose you want to develop a simple Apache Axis2 Service and want to debug your service when you invoke it. Let's see how to achieve this using WSO2 Developer Studio.


First, create a simple GreetingService.




Then create a Composite Application Project to group it.




Now add a WSO2 Application Server instance to your Eclipse workspace. Steps to add a Carbon Server is described in the [Deploy a C-App to a running Server inside Eclipse](#) section. After adding the server, start the server in the **debug** mode.




After the server is successfully started, add the **GreetingServiceCApp** project.



When your application has deployed successfully, you will see the following messages in your console.




Now go to your web browser and check whether your application is being deployed under the **Web Services Listing** page.




Now click on the **Try This Service** option at the right hand corner. Once you click it, it will go to a separate page where it lists all the operations related to the web service you choose.







Before you invoke the service, go back to your **Eclipse Workspace** and put a debug point inside your method.




Now go back to your web console and invoke the service. Once you invoke the service, it will ask whether to change in to the **Debug Perspective** in Eclipse.




Click **Yes**. If your Eclipse instance could not find the relevant source for the class, it will show a blank page as below.




Click **Edit Source Lookup Path**.




Click **Add** and select the **Java Project**.



Select the **GreetingService** project from the list and click **OK**.



Now you will see the source being attached and you will see the debug point being hit.



In a similar manner, you can debug any application which will be associated with **Java Sources**.