

# CET2012 - Programming Paradigms: Advanced Java - Practicum 02

**Topics Covered:** Files I/O, Regular Expressions, Collections, OOP

## Learning Objectives:

- Familiarize working with files in Java
- Familiarize with the usage of regular expressions
- Familiarize with the usages of some Java Collection Framework classes
- Learn and implement the Command Design Pattern

## Deliverables:

- Submit a single zip file called `CET2012_P02_<Your_Name>.zip` (e.g. `CET2012_P02_John_Doe.zip`) containing your Java codes, include your driver class (aka class with the `main` method).
- Note that a non-working submission will result in a zero

## Background

### About the Task

A company wants to develop a small tool that is able to store some employee data into a file. This tool allows users to **add, list, update, delete** and **undo the previous instruction**. In addition, this tool is able to load from a saved file at startup (if any) and store its content to a file after all commands have been executed, analogous to a cashier entering items to an Point of Sales machine or calling up a previous transaction then generating a receipt.

The payload are all made up of all **ASCII based characters only**, however they are entered using the format detailed below. Depending on the command, the data items in the payload may differ. However, **there is a restriction for `<data3>`**. It is only able to accept **a single email address or Latin letters (case insensitive), digits 0 to 9 and underscores**. Each data item is to have **Title Case** (aka first letter is always in capitals) except emails.

after all commands have been executed not after EACH command have been executed.

```
1 # Payload 1
2 <data1> <data2> <data3>
3 # Payload 2
4 <index> <data1> <data2> <data3>
```

when they say depending on command, the data items in the payload may differ they are referring to whether it is in payload 1 style or payload 2 style.

Although the email address syntax has a very wide range of allowable characters as detail in [this](#) Wikipedia article, the company has chosen to restrict the allowable characters to the following:

- **Local part:**

- uppercase and lowercase Latin letters A to Z and a to z
- digits 0 to 9
- printable characters `._-` (dot, underscore & dash). Note that for the printable characters, they must not be present as either the first or last character and also do not appear consecutively. **The underscore character is the exception to this rule.**

- **Domain part (2 parts):** format `yyyy.xxx`

- uppercase and lowercase Latin letters A to Z and a to z
- digits 0 to 9
- printable characters `.-` (dot & dash). Note that for the printable characters, they must not be present as either the first or last character and also do not appear consecutively
- the `".xxx"` part of the domain is allowed to have a range of minimum 2 to a maximum of 3 characters. In addition, only lowercase Latin letters a to z are allowed.

As stated above, there are 5 commands: `add`, `update`, `delete`, `list` and `undo`. Each command uses either a variation of the structure of *Payload 1* or *Payload 2* or none at all. The following table details the structure for each command.


Command	Payload Structure
Add	<code>&lt;data1&gt; &lt;data2&gt; &lt;data3&gt;</code> Other than the rules listed for <code>&lt;data3&gt;</code> above, <code>&lt;data1&gt;</code> and <code>&lt;data2&gt;</code> <b>do not require error checking</b> . <b>All 3 data items are required to be filled</b> when this command is used.
Update	<code>&lt;index&gt; &lt;data1&gt; &lt;data2&gt; &lt;data3&gt;</code> The <code>&lt;index&gt;</code> and at least 1 data item is required. Order of the data item matters, i.e. <code>&lt;data1&gt;</code> value will update <code>&lt;data1&gt;</code> value added from the <i>Add</i> command.
Delete	<code>&lt;index&gt;</code> Numerical index based off the index shown using the <i>List</i> command.
List	No inputs required. Lists out the current items stored in the data store.
Undo	No inputs required. Undo the previous command. <b>Applicable to the <code>add</code>, <code>update</code> &amp; <code>delete</code> commands only.</b>

so these should be things you put inside your stack, add, update, delete.

## Command Design Pattern in Brief

The command design pattern is a behavioural design pattern that turns a request/command into a standalone object that contains all information about the request/command. This pattern allows commands to be delayed or queued before execution, in addition, it supports undo operations.

The base structure of the Command Design Pattern is shown in figure 1 below.



- The **Invoker** class is responsible for initiating the commands. It must have a field to store the reference to a command object. The Invoker **triggers** the commands instead of sending the request directly to the receiver. The invoker is not responsible for creating the command object, it usually gets a pre-created command from the client.
- The **Command** interface usually declares just a single method for executing the command.
- **Concrete Commands** implements the various kinds of commands. A concrete command isn't supposed to perform the work on its own, but rather to pass the call to one of the business logic objects. Parameters required to execute a method on a receiving object can be declared as fields in the concrete command.
- The **Receiver** class contains some business logic. Almost any object may act as a receiver. Most commands only handle the details of how a request is passed to the receiver, while the receiver itself does the actual work.
- The **Client** creates and configures the concrete command objects. The client must pass all of the command parameters, including a receiver instance, into the command's constructor. After that, the resulting command may be associated with one or multiple senders.

### Real World Example

Word editors such as Microsoft Office or Notepad++ all have commands that result in the change in the state of the editor for example, cutting and pasting of text. Taking the Cut and Paste function from those editors, cut removes the selected text from the editor and places it in some memory (called the clipboard) whereas paste takes the text from the clipboard and places it at the location of the text cursor.


After any command is executed, it's placed into the command history (a stack of command objects) along with the backup copy of the editor's state at that point. Thus, if the user needs to revert an operation, the application can take the most recent command from the history, read the associated backup of the editor's state, and restore it.

The client code (GUI elements, command history, etc.) isn't coupled to concrete command classes because it works with commands via the command interface. This approach enables us to introduce new commands into an application without breaking any existing code.

## Task

Your task is to develop this tool using the Command Design Pattern (from the previous section) and the following requirements.

- You are to use `java.util.Stack` to store your command history and `java.util.ArrayList` for your data store.
- For long-term storage of the entered data, you are to store the data in a text file called `dataStore.txt`. The location of the file should be created or read from the `src` folder of your project. **DO NOT submit this text file.**
- You are to use regular expressions for checking the values for data item `<data3>`.
- You are to implement a single custom exception class to for all non `Throwable` error messages. **implement it from the Exception class.**
- Include a `storeToFile()` method in your class that handles the data store.
- Concrete commands are to have the following classnames:**
  - `AddCommand`
  - `UpdateCommand`
  - `DeleteCommand`
  - `ListCommand`
  - `UndoCommand`
- Include any other methods that you may require.
- Using the Javadoc tool, you are to include the documentation of your program to allow users to understand and be able to incorporate your tool to their own projects. **You are to ensure that your Javadoc of your project is generable.**
- The class diagram of the `Invoker` class is given below



cannot add any other things to Invoker class, must follow the UML

You may refer to an example of the behaviour of the program shown below

```

1  add
2  add
3  add
4  add
5  List

```

ArrayList will store all your data for your first then when ready then it will write to dataStore.txt

use relative path for dataStore.txt

Stack <>  
ArrayList <>

you can put int or String etc in the <> or you can put a user-defined class also can.

could probably use this to throw an error that the email address is not correct.

the purpose of the storeToFile() method is just to store all your things in your array list to your dataStore.txt

```

6  01. First_name Last_name Email
7  02. John Doe simple@example.com
8  03. Hanna Moon tetter.tots@potatoesarelife.com
9  04. Ah Boon green-tea@teaforlife.com
10 update # 3 Adam
11 List
12 01. First_name Last_name Email
13 02. John Doe simple@example.com
14 03. Adam Moon tetter.tots@potatoesarelife.com
15 04. Ah Boon green-tea@teaforlife.com
16 update # 1 blue bell ice-cream@alaskaFields.org
17 List
18 01. Blue Bell ice-cream@alaskaFields.org
19 02. John Doe simple@example.com
20 03. Adam Moon tetter.tots@potatoesarelife.com
21 04. Ah Boon green-tea@teaforlife.com
22 Delete # 1
23 List
24 01. John Doe simple@example.com
25 02. Adam Moon tetter.tots@potatoesarelife.com
26 03. Ah Boon green-tea@teaforlife.com
27 Undo
28 List
29 01. Blue Bell ice-cream@alaskaFields.org
30 02. John Doe simple@example.com
31 03. Adam Moon tetter.tots@potatoesarelife.com
32 04. Ah Boon green-tea@teaforlife.com

```

undo can do as many  
times as you want.

For the maximum allocation of marks, refer to the table below.

Description	Marks (%)
Successful implementation of program using the Command Design Pattern (passes instructor's test case, no bugs, does not crash)	65
Proper implementation of the regular expression	5
Proper implementation and usage of the Java Collection Framework	10
Successful read from and write to file	10
Proper and generable documentation using Javadoc tool	10

Once you have completed, save your file in the following format `CET2012_P02_<Your_Name>.zip`  
e.g. `CET2012_P02_John_Doe.zip`.