

DE4xxSolarSystemEphemerides

5.1

Generated by Doxygen 1.8.5

Mon Jul 31 2023 11:40:41

Contents

1	Module Index	1
1.1	Modules	1
2	Namespace Index	3
2.1	Namespace List	3
3	Hierarchical Index	5
3.1	Class Hierarchy	5
4	Data Structure Index	7
4.1	Data Structures	7
5	File Index	9
5.1	File List	9
6	Module Documentation	13
6.1	Models	13
6.1.1	Detailed Description	13
6.2	Environment	14
6.2.1	Detailed Description	14
6.3	Ephemerides	15
6.3.1	Detailed Description	15
6.4	De4xxEphem	16
6.4.1	Detailed Description	16
6.4.2	Macro Definition Documentation	16
6.4.2.1	__STDC_LIMIT_MACROS	16
6.5	EphemInterface	17
6.5.1	Detailed Description	17
6.6	EphemItem	18
6.6.1	Detailed Description	18
6.6.2	Macro Definition Documentation	18
6.6.2.1	EPSILON_TIME	18
6.6.2.2	TAYLOR_CUTOFF	18

6.7	EphemManager	19
6.7.1	Detailed Description	19
6.8	PropagatedPlanet	20
6.8.1	Detailed Description	20
7	Namespace Documentation	21
7.1	jeod Namespace Reference	21
7.1.1	Detailed Description	22
7.1.2	Function Documentation	23
7.1.2.1	l1_point	23
7.1.2.2	process_mem_usage	23
7.2	jeod::De4xxBase Namespace Reference	23
7.2.1	Detailed Description	24
7.2.2	Enumeration Type Documentation	24
7.2.2.1	De4xxEphemBodies	24
7.2.2.2	De4xxEphemConsts	25
7.2.2.3	De4xxFileEntries	25
7.2.3	Function Documentation	26
7.2.3.1	__attribute__	26
7.2.3.2	number_grav_models	26
7.2.3.3	number_jeod_items	26
7.2.3.4	number_physical_bodies	26
7.2.3.5	number_trans_points	26
8	Data Structure Documentation	27
8.1	jeod::BaseEphemeridesManager Class Reference	27
8.1.1	Detailed Description	28
8.1.2	Constructor & Destructor Documentation	28
8.1.2.1	~BaseEphemeridesManager	28
8.1.3	Member Function Documentation	28
8.1.3.1	add_ephem_item	28
8.1.3.2	add_ephemeris	29
8.1.3.3	add_integ_frame	29
8.1.3.4	add_planet	29
8.1.3.5	add_planet	29
8.1.3.6	clear_added_ephemerides	29
8.1.3.7	disable_add_ephemeris	29
8.1.3.8	ephem_note_tree_status_change	30
8.1.3.9	find_base_planet	30
8.1.3.10	find_ephem_angle	30
8.1.3.11	find_ephem_item	30

8.1.3.12	find_ephem_point	30
8.1.3.13	find_integ_frame	31
8.1.3.14	find_integ_frame_index	31
8.1.3.15	find_planet	31
8.1.3.16	get_integ_frames	31
8.1.3.17	get_num_planets	32
8.1.3.18	is_integ_frame	32
8.1.4	Friends And Related Function Documentation	32
8.1.4.1	init_attrjeod_BaseEphemeridesManager	32
8.1.4.2	InputProcessor	32
8.2	jeod::De4xxEphemeris Class Reference	32
8.2.1	Detailed Description	35
8.2.2	Constructor & Destructor Documentation	35
8.2.2.1	De4xxEphemeris	35
8.2.2.2	~De4xxEphemeris	35
8.2.2.3	De4xxEphemeris	35
8.2.3	Member Function Documentation	36
8.2.3.1	activate	36
8.2.3.2	activate_em_nodes	36
8.2.3.3	activate_nodes	36
8.2.3.4	deactivate	36
8.2.3.5	determine_root_node	37
8.2.3.6	ephem_activate	37
8.2.3.7	ephem_build_tree	37
8.2.3.8	ephem_initialize	37
8.2.3.9	ephem_update	38
8.2.3.10	get_header_data	38
8.2.3.11	get_model_number	38
8.2.3.12	get_name	38
8.2.3.13	initialize_file	39
8.2.3.14	initialize_items	39
8.2.3.15	initialize_model	39
8.2.3.16	initialize_model	39
8.2.3.17	initialize_time	40
8.2.3.18	operator=	40
8.2.3.19	propagate_lunar_rnp	40
8.2.3.20	set_model_number	40
8.2.3.21	shutdown	40
8.2.3.22	time_is_in_range	40
8.2.3.23	timestamp	41

8.2.4	Friends And Related Function Documentation	41
8.2.4.1	init_attrjeod__De4xxEphemeris	41
8.2.4.2	InputProcessor	41
8.2.5	Field Documentation	41
8.2.5.1	active	41
8.2.5.2	body_to_file_idx	41
8.2.5.3	earth_moon_barycenter_frame	42
8.2.5.4	file	42
8.2.5.5	force_update	42
8.2.5.6	ident	42
8.2.5.7	item_data	42
8.2.5.8	lunar_orientation	42
8.2.5.9	nactive_items	43
8.2.5.10	points	43
8.2.5.11	root_item	43
8.2.5.12	selected_items	43
8.2.5.13	solar_system_barycenter_frame	43
8.2.5.14	time_dyn	43
8.2.5.15	time_tt	44
8.2.5.16	update_time	44
8.3	jeod::De4xxEphemItem Class Reference	44
8.3.1	Detailed Description	45
8.3.2	Member Enumeration Documentation	45
8.3.2.1	Status	45
8.3.3	Constructor & Destructor Documentation	46
8.3.3.1	De4xxEphemItem	46
8.3.3.2	~De4xxEphemItem	46
8.3.3.3	De4xxEphemItem	46
8.3.4	Member Function Documentation	46
8.3.4.1	operator=	46
8.3.5	Friends And Related Function Documentation	46
8.3.5.1	De4xxEphemeris	46
8.3.5.2	init_attrjeod__De4xxEphemItem	46
8.3.5.3	InputProcessor	46
8.3.6	Field Documentation	46
8.3.6.1	enabled_item	46
8.3.6.2	frame	46
8.3.6.3	index	47
8.3.6.4	item	47
8.3.6.5	name	47

8.3.6.6	status	47
8.4	jeod::De4xxFile Class Reference	47
8.4.1	Detailed Description	49
8.4.2	Constructor & Destructor Documentation	49
8.4.2.1	De4xxFile	49
8.4.2.2	~De4xxFile	49
8.4.2.3	De4xxFile	49
8.4.3	Member Function Documentation	49
8.4.3.1	capture_mem_stats	49
8.4.3.2	close	50
8.4.3.3	initialize	50
8.4.3.4	interpolate	50
8.4.3.5	open	51
8.4.3.6	operator=	51
8.4.3.7	pre_initialize	51
8.4.3.8	reopen	52
8.4.3.9	shutdown	52
8.4.3.10	time_is_in_range	52
8.4.3.11	update	52
8.4.4	Friends And Related Function Documentation	53
8.4.4.1	De4xxFileRestart	53
8.4.4.2	init_attrjeod__De4xxFile	54
8.4.4.3	InputProcessor	54
8.4.5	Field Documentation	54
8.4.5.1	coef	54
8.4.5.2	file_spec	54
8.4.5.3	header	54
8.4.5.4	io	54
8.4.5.5	item	54
8.4.5.6	logMemoryStats	55
8.4.5.7	ref_time	55
8.4.5.8	resident_set	55
8.4.5.9	restart	55
8.4.5.10	update_time	55
8.4.5.11	vm_usage	55
8.5	jeod::De4xxFileCoef Class Reference	56
8.5.1	Detailed Description	56
8.5.2	Constructor & Destructor Documentation	56
8.5.2.1	De4xxFileCoef	56
8.5.2.2	De4xxFileCoef	56

8.5.3	Member Function Documentation	57
8.5.3.1	operator=	57
8.5.4	Friends And Related Function Documentation	57
8.5.4.1	De4xxFile	57
8.5.4.2	init_attrjeod__De4xxFileCoef	57
8.5.4.3	InputProcessor	57
8.5.5	Field Documentation	57
8.5.5.1	chebyderiv	57
8.5.5.2	chebypoly	57
8.5.5.3	chebyterms	57
8.5.5.4	chebyx	57
8.5.5.5	coef	58
8.6	jeod::De4xxFileHeader Class Reference	58
8.6.1	Detailed Description	59
8.6.2	Constructor & Destructor Documentation	59
8.6.2.1	De4xxFileHeader	59
8.6.2.2	De4xxFileHeader	59
8.6.2.3	~De4xxFileHeader	59
8.6.3	Member Function Documentation	59
8.6.3.1	operator=	59
8.6.4	Friends And Related Function Documentation	59
8.6.4.1	De4xxFile	59
8.6.4.2	init_attrjeod__De4xxFileHeader	59
8.6.4.3	InputProcessor	59
8.6.5	Field Documentation	59
8.6.5.1	au	59
8.6.5.2	b1_em_dist_ratio	60
8.6.5.3	be_em_dist_ratio	60
8.6.5.4	bm_em_dist_ratio	60
8.6.5.5	e1_em_dist_ratio	60
8.6.5.6	em_mass_ratio	60
8.6.5.7	gmbody	60
8.6.5.8	vlight	61
8.7	jeod::De4xxFileIO Class Reference	61
8.7.1	Detailed Description	62
8.7.2	Constructor & Destructor Documentation	62
8.7.2.1	De4xxFileIO	62
8.7.2.2	De4xxFileIO	62
8.7.3	Member Function Documentation	62
8.7.3.1	operator=	62

8.7.4	Friends And Related Function Documentation	62
8.7.4.1	De4xxFile	62
8.7.4.2	init_attrjeod__De4xxFileIO	62
8.7.4.3	InputProcessor	62
8.7.5	Field Documentation	63
8.7.5.1	coeffs_segment_starting_addr	63
8.7.5.2	current_record_starting_addr	63
8.7.5.3	file	63
8.7.5.4	itemData	63
8.7.5.5	max_terms	63
8.7.5.6	metaData	63
8.7.5.7	recno	64
8.7.5.8	segment_index	64
8.7.5.9	segment_recno	64
8.7.5.10	segmentData	64
8.7.5.11	total_num_recs	64
8.8	jeod::De4xxFileItem Class Reference	64
8.8.1	Detailed Description	65
8.8.2	Constructor & Destructor Documentation	65
8.8.2.1	De4xxFileItem	65
8.8.2.2	De4xxFileItem	65
8.8.3	Member Function Documentation	66
8.8.3.1	operator=	66
8.8.4	Friends And Related Function Documentation	66
8.8.4.1	De4xxFile	66
8.8.4.2	init_attrjeod__De4xxFileItem	66
8.8.4.3	InputProcessor	66
8.8.5	Field Documentation	66
8.8.5.1	active	66
8.8.5.2	avail	66
8.8.5.3	item_idx	66
8.8.5.4	nitems	66
8.8.5.5	pscale	67
8.8.5.6	state	67
8.8.5.7	update_time	67
8.9	jeod::De4xxFileRefTime Class Reference	67
8.9.1	Detailed Description	68
8.9.2	Constructor & Destructor Documentation	68
8.9.2.1	De4xxFileRefTime	68
8.9.2.2	De4xxFileRefTime	68

8.9.3	Member Function Documentation	68
8.9.3.1	operator=	68
8.9.4	Friends And Related Function Documentation	68
8.9.4.1	De4xxFile	68
8.9.4.2	init_attrjeod__De4xxFileRefTime	68
8.9.4.3	InputProcessor	68
8.9.5	Field Documentation	68
8.9.5.1	block_no	68
8.9.5.2	epoch_date	69
8.9.5.3	fdate	69
8.9.5.4	init_time	69
8.9.5.5	time_offset	69
8.10	jeod::De4xxFileRestart Class Reference	69
8.10.1	Detailed Description	70
8.10.2	Constructor & Destructor Documentation	70
8.10.2.1	De4xxFileRestart	70
8.10.2.2	~De4xxFileRestart	70
8.10.2.3	De4xxFileRestart	70
8.10.3	Member Function Documentation	70
8.10.3.1	operator=	70
8.10.3.2	simple_restore	70
8.10.4	Field Documentation	71
8.10.4.1	de4xx_file	71
8.11	jeod::De4xxFileSpec Class Reference	71
8.11.1	Detailed Description	72
8.11.2	Constructor & Destructor Documentation	72
8.11.2.1	De4xxFileSpec	72
8.11.2.2	De4xxFileSpec	72
8.11.3	Member Function Documentation	72
8.11.3.1	get_model_number	72
8.11.3.2	operator=	72
8.11.3.3	set_model_number	72
8.11.4	Friends And Related Function Documentation	72
8.11.4.1	De4xxFile	72
8.11.4.2	init_attrjeod__De4xxFileSpec	73
8.11.4.3	InputProcessor	73
8.11.5	Field Documentation	73
8.11.5.1	denum	73
8.11.5.2	ephem_file_dir	73
8.11.5.3	ephem_file_name	73

8.11.5.4	pathname	73
8.12	jeod::EmptySpaceEphemeris Class Reference	73
8.12.1	Detailed Description	75
8.12.2	Constructor & Destructor Documentation	75
8.12.2.1	EmptySpaceEphemeris	75
8.12.2.2	~EmptySpaceEphemeris	75
8.12.2.3	EmptySpaceEphemeris	75
8.12.3	Member Function Documentation	75
8.12.3.1	ephem_activate	75
8.12.3.2	ephem_build_tree	75
8.12.3.3	ephem_initialize	75
8.12.3.4	initialize_model	76
8.12.3.5	operator=	76
8.12.3.6	set_name	76
8.12.4	Friends And Related Function Documentation	76
8.12.4.1	init_attrjeod__EmptySpaceEphemeris	76
8.12.4.2	InputProcessor	76
8.12.5	Field Documentation	76
8.12.5.1	central_frame	77
8.12.5.2	central_point	77
8.13	jeod::EphemeridesManager Class Reference	77
8.13.1	Detailed Description	79
8.13.2	Constructor & Destructor Documentation	79
8.13.2.1	EphemeridesManager	79
8.13.2.2	~EphemeridesManager	80
8.13.2.3	EphemeridesManager	80
8.13.3	Member Function Documentation	80
8.13.3.1	activate_ephemerides	80
8.13.3.2	add_ephem_item	80
8.13.3.3	add_ephemeris	81
8.13.3.4	add_integ_frame	81
8.13.3.5	add_planet	81
8.13.3.6	add_planet	82
8.13.3.7	add_ref_frame	83
8.13.3.8	clear_added_ephemerides	83
8.13.3.9	disable_add_ephemeris	83
8.13.3.10	ephem_note_tree_status_change	83
8.13.3.11	find_base_planet	84
8.13.3.12	find_ephem_angle	84
8.13.3.13	find_ephem_item	84

8.13.3.14	find_ephem_point	85
8.13.3.15	find_integ_frame	85
8.13.3.16	find_integ_frame_index	85
8.13.3.17	find_planet	86
8.13.3.18	get_integ_frames	86
8.13.3.19	get_num_planets	86
8.13.3.20	initialize_ephemerides	87
8.13.3.21	is_integ_frame	87
8.13.3.22	operator=	87
8.13.3.23	ref_frame_tree_needs_rebuild	87
8.13.3.24	set_target_frame	87
8.13.3.25	update_ephemerides	88
8.13.4	Friends And Related Function Documentation	88
8.13.4.1	init_attrjeod__EphemeridesManager	88
8.13.4.2	InputProcessor	88
8.13.5	Field Documentation	88
8.13.5.1	ephem_items	88
8.13.5.2	ephemerides	88
8.13.5.3	integ_frames	88
8.13.5.4	planets	88
8.13.5.5	regenerate_ref_frame_tree	89
8.13.5.6	single_ephem_mode	89
8.13.5.7	update_time	89
8.14	jeod::EphemeridesMessages Class Reference	89
8.14.1	Detailed Description	90
8.14.2	Constructor & Destructor Documentation	90
8.14.2.1	EphemeridesMessages	90
8.14.2.2	EphemeridesMessages	90
8.14.3	Member Function Documentation	91
8.14.3.1	operator=	91
8.14.4	Friends And Related Function Documentation	91
8.14.4.1	init_attrjeod__EphemeridesMessages	91
8.14.4.2	InputProcessor	91
8.14.5	Field Documentation	91
8.14.5.1	debug	91
8.14.5.2	duplicate_entry	91
8.14.5.3	file_error	91
8.14.5.4	garbage_file	91
8.14.5.5	inconsistent_setup	92
8.14.5.6	internal_error	92

8.14.5.7	invalid_item	92
8.14.5.8	invalid_name	92
8.14.5.9	item_not_in_file	92
8.14.5.10	null_pointer	93
8.14.5.11	single_ephem_mode	93
8.14.5.12	time_not_in_range	93
8.14.5.13	unsupported_architecture	93
8.15	jeod::EphemerisDataItemMeta Struct Reference	93
8.15.1	Detailed Description	94
8.15.2	Field Documentation	94
8.15.2.1	npoly	94
8.15.2.2	nterms	94
8.15.2.3	offset	94
8.16	jeod::EphemerisDataSegmentMeta Struct Reference	94
8.16.1	Detailed Description	95
8.16.2	Field Documentation	95
8.16.2.1	num_recs	95
8.16.2.2	start_epoch	95
8.16.2.3	stop_epoch	95
8.17	jeod::EphemerisDataSetMeta Struct Reference	95
8.17.1	Detailed Description	96
8.17.2	Field Documentation	96
8.17.2.1	de_constants	96
8.17.2.2	delta_epoch	96
8.17.2.3	ncoeff	96
8.17.2.4	number_file_items	96
8.17.2.5	number_segments	97
8.17.2.6	start_epoch	97
8.17.2.7	stop_epoch	97
8.18	jeod::EphemerisInterface Class Reference	97
8.18.1	Detailed Description	98
8.18.2	Constructor & Destructor Documentation	98
8.18.2.1	~EphemerisInterface	98
8.18.3	Member Function Documentation	98
8.18.3.1	ephem_activate	98
8.18.3.2	ephem_build_tree	98
8.18.3.3	ephem_initialize	99
8.18.3.4	ephem_update	100
8.18.3.5	get_name	100
8.18.3.6	timestamp	100

8.18.4	Friends And Related Function Documentation	100
8.18.4.1	init_attrjeod__EphemerisInterface	100
8.18.4.2	InputProcessor	100
8.19	jeod::EphemerisItem Class Reference	100
8.19.1	Detailed Description	103
8.19.2	Member Enumeration Documentation	103
8.19.2.1	TargetAspect	103
8.19.3	Constructor & Destructor Documentation	103
8.19.3.1	EphemerisItem	103
8.19.3.2	~EphemerisItem	104
8.19.3.3	EphemerisItem	104
8.19.4	Member Function Documentation	104
8.19.4.1	activate	104
8.19.4.2	deactivate	104
8.19.4.3	default_suffix	104
8.19.4.4	disable	104
8.19.4.5	disconnect_from_tree	104
8.19.4.6	enable	105
8.19.4.7	get_enabled_item	105
8.19.4.8	get_head	105
8.19.4.9	get_manager	105
8.19.4.10	get_name	106
8.19.4.11	get_next	106
8.19.4.12	get_owner	106
8.19.4.13	get_target_frame	106
8.19.4.14	is_activatable	107
8.19.4.15	is_active	107
8.19.4.16	is_enabled	107
8.19.4.17	operator=	107
8.19.4.18	set_head	107
8.19.4.19	set_manager	108
8.19.4.20	set_name	109
8.19.4.21	set_name	109
8.19.4.22	set_name_internal	109
8.19.4.23	set_next	109
8.19.4.24	set_owner	110
8.19.4.25	set_target_frame	110
8.19.4.26	set_timestamp	110
8.19.4.27	timestamp	110
8.19.4.28	updates_what	110

8.19.4.29	validate_name	111
8.19.5	Friends And Related Function Documentation	111
8.19.5.1	init_attrjeod__EphemerisItem	111
8.19.5.2	InputProcessor	111
8.19.6	Field Documentation	111
8.19.6.1	active	111
8.19.6.2	enabled	111
8.19.6.3	head	112
8.19.6.4	manager	112
8.19.6.5	name	112
8.19.6.6	next	112
8.19.6.7	owner	112
8.19.6.8	target_frame	113
8.19.6.9	update_time	113
8.20	jeod::EphemerisOrientation Class Reference	113
8.20.1	Detailed Description	114
8.20.2	Constructor & Destructor Documentation	114
8.20.2.1	EphemerisOrientation	114
8.20.2.2	~EphemerisOrientation	114
8.20.2.3	EphemerisOrientation	115
8.20.3	Member Function Documentation	115
8.20.3.1	default_suffix	115
8.20.3.2	disconnect_from_tree	115
8.20.3.3	enable	115
8.20.3.4	note_frame_status_change	115
8.20.3.5	operator=	115
8.20.3.6	updates_what	116
8.20.4	Friends And Related Function Documentation	116
8.20.4.1	init_attrjeod__EphemerisOrientation	116
8.20.4.2	InputProcessor	116
8.20.5	Field Documentation	116
8.20.5.1	subscribed_to_inertial	116
8.21	jeod::EphemerisPoint Class Reference	116
8.21.1	Detailed Description	117
8.21.2	Constructor & Destructor Documentation	118
8.21.2.1	EphemerisPoint	118
8.21.2.2	~EphemerisPoint	118
8.21.2.3	EphemerisPoint	118
8.21.3	Member Function Documentation	118
8.21.3.1	default_suffix	118

8.21.3.2	disconnect_from_tree	118
8.21.3.3	initialize_state	118
8.21.3.4	note_frame_status_change	118
8.21.3.5	operator=	119
8.21.3.6	update	119
8.21.3.7	update_scaled	119
8.21.3.8	updates_what	119
8.21.4	Friends And Related Function Documentation	120
8.21.4.1	init_attrjeod__EphemerisPoint	120
8.21.4.2	InputProcessor	120
8.22	jeod::EphemerisRefFrame Class Reference	120
8.22.1	Detailed Description	121
8.22.2	Constructor & Destructor Documentation	121
8.22.2.1	EphemerisRefFrame	121
8.22.2.2	~EphemerisRefFrame	121
8.22.2.3	EphemerisRefFrame	121
8.22.3	Member Function Documentation	122
8.22.3.1	operator=	122
8.22.3.2	set_active_status	122
8.22.3.3	set_ephem_manager	122
8.22.4	Friends And Related Function Documentation	122
8.22.4.1	init_attrjeod__EphemerisRefFrame	122
8.22.4.2	InputProcessor	122
8.22.5	Field Documentation	122
8.22.5.1	ephem_manager	122
8.23	jeod::EphemerisZXZOrientation Class Reference	123
8.23.1	Detailed Description	124
8.23.2	Constructor & Destructor Documentation	124
8.23.2.1	EphemerisZXZOrientation	124
8.23.2.2	~EphemerisZXZOrientation	124
8.23.2.3	EphemerisZXZOrientation	124
8.23.3	Member Function Documentation	124
8.23.3.1	get_euler_angles	124
8.23.3.2	get_euler_angles	124
8.23.3.3	get_euler_rates	125
8.23.3.4	get_euler_rates	125
8.23.3.5	operator=	125
8.23.3.6	propagate	125
8.23.3.7	update	126
8.23.4	Friends And Related Function Documentation	127

8.23.4.1	init_attrjeod__EphemerisZXZOrientation	127
8.23.4.2	InputProcessor	127
8.23.5	Field Documentation	127
8.23.5.1	euler_angle_313	127
8.23.5.2	euler_rate_313	127
8.24	jeod::PropagatedEphemerisOrientation Class Reference	127
8.24.1	Detailed Description	128
8.24.2	Constructor & Destructor Documentation	129
8.24.2.1	PropagatedEphemerisOrientation	129
8.24.2.2	~PropagatedEphemerisOrientation	129
8.24.2.3	PropagatedEphemerisOrientation	129
8.24.3	Member Function Documentation	129
8.24.3.1	operator=	129
8.24.3.2	update	129
8.24.4	Friends And Related Function Documentation	129
8.24.4.1	init_attrjeod__PropagatedEphemerisOrientation	129
8.24.4.2	InputProcessor	129
8.24.5	Field Documentation	130
8.24.5.1	body	130
8.24.5.2	body_ref_frame	130
8.25	jeod::PropagatedEphemerisPlanet Class Reference	130
8.25.1	Detailed Description	131
8.25.2	Constructor & Destructor Documentation	131
8.25.2.1	PropagatedEphemerisPlanet	131
8.25.2.2	~PropagatedEphemerisPlanet	132
8.25.2.3	PropagatedEphemerisPlanet	132
8.25.3	Member Function Documentation	132
8.25.3.1	operator=	132
8.25.3.2	update	132
8.25.4	Friends And Related Function Documentation	132
8.25.4.1	init_attrjeod__PropagatedEphemerisPlanet	132
8.25.4.2	InputProcessor	132
8.25.5	Field Documentation	132
8.25.5.1	body	132
8.25.5.2	body_ref_frame	133
8.26	jeod::PropagatedPlanet Class Reference	133
8.26.1	Detailed Description	135
8.26.2	Member Enumeration Documentation	135
8.26.2.1	Mode	135
8.26.3	Constructor & Destructor Documentation	136

8.26.3.1	PropagatedPlanet	136
8.26.3.2	~PropagatedPlanet	136
8.26.3.3	PropagatedPlanet	136
8.26.4	Member Function Documentation	136
8.26.4.1	activate	136
8.26.4.2	deactivate	136
8.26.4.3	ephem_activate	136
8.26.4.4	ephem_build_tree	137
8.26.4.5	ephem_initialize	137
8.26.4.6	ephem_update	137
8.26.4.7	get_name	137
8.26.4.8	initialize_model	138
8.26.4.9	operator=	138
8.26.4.10	set_commanded_mode	138
8.26.4.11	set_mode	138
8.26.4.12	shutdown	138
8.26.4.13	timestamp	139
8.26.5	Friends And Related Function Documentation	139
8.26.5.1	init_attrjeod__PropagatedPlanet	139
8.26.5.2	InputProcessor	139
8.26.6	Field Documentation	139
8.26.6.1	active	139
8.26.6.2	body	139
8.26.6.3	commanded_mode	139
8.26.6.4	dyn_manager	139
8.26.6.5	ephem_orient	140
8.26.6.6	ephem_planet	140
8.26.6.7	ident	140
8.26.6.8	initialized	140
8.26.6.9	mode	140
8.26.6.10	parent_frame	140
8.26.6.11	parent_name	141
8.26.6.12	planet	141
8.26.6.13	planet_name	141
8.26.6.14	time_dyn	141
8.26.6.15	update_time	141
8.27	jeod::SinglePlanetEphemeris Class Reference	141
8.27.1	Detailed Description	143
8.27.2	Constructor & Destructor Documentation	143
8.27.2.1	SinglePlanetEphemeris	143

8.27.2.2	~SinglePlanetEphemeris	143
8.27.2.3	SinglePlanetEphemeris	143
8.27.3	Member Function Documentation	143
8.27.3.1	ephem_activate	143
8.27.3.2	ephem_build_tree	143
8.27.3.3	ephem_initialize	144
8.27.3.4	initialize_model	145
8.27.3.5	operator=	145
8.27.3.6	set_name	145
8.27.4	Friends And Related Function Documentation	145
8.27.4.1	init_attrjeod__SinglePlanetEphemeris	145
8.27.4.2	InputProcessor	145
8.27.5	Field Documentation	145
8.27.5.1	central_point	146
8.28	jeod::SinglePointEphemeris Class Reference	146
8.28.1	Detailed Description	147
8.28.2	Constructor & Destructor Documentation	147
8.28.2.1	SinglePointEphemeris	147
8.28.2.2	~SinglePointEphemeris	147
8.28.2.3	SinglePointEphemeris	147
8.28.3	Member Function Documentation	148
8.28.3.1	activate	148
8.28.3.2	deactivate	148
8.28.3.3	ephem_activate	148
8.28.3.4	ephem_build_tree	148
8.28.3.5	ephem_initialize	148
8.28.3.6	ephem_update	149
8.28.3.7	get_name	149
8.28.3.8	initialize_model	149
8.28.3.9	operator=	149
8.28.3.10	set_name	149
8.28.3.11	timestamp	149
8.28.4	Friends And Related Function Documentation	150
8.28.4.1	init_attrjeod__SinglePointEphemeris	150
8.28.4.2	InputProcessor	150
8.28.5	Field Documentation	150
8.28.5.1	active	150
8.28.5.2	identifier	150
8.28.5.3	update_time	150

9	File Documentation	151
9.1	base_ephem_manager.hh File Reference	151
9.1.1	Detailed Description	151
9.2	class_declarations.hh File Reference	151
9.2.1	Detailed Description	152
9.3	class_declarations.hh File Reference	152
9.3.1	Detailed Description	152
9.4	class_declarations.hh File Reference	152
9.4.1	Detailed Description	152
9.5	de405_0.cc File Reference	152
9.5.1	Variable Documentation	153
9.5.1.1	itemData	153
9.5.1.2	metaData	153
9.5.1.3	segment_coeffs_0	153
9.5.1.4	segmentData	153
9.6	de405_1.cc File Reference	153
9.6.1	Variable Documentation	153
9.6.1.1	segment_coeffs_1	153
9.7	de405_10.cc File Reference	154
9.7.1	Variable Documentation	154
9.7.1.1	segment_coeffs_10	154
9.8	de405_11.cc File Reference	154
9.8.1	Variable Documentation	154
9.8.1.1	segment_coeffs_11	154
9.9	de405_12.cc File Reference	154
9.9.1	Variable Documentation	154
9.9.1.1	segment_coeffs_12	154
9.10	de405_13.cc File Reference	155
9.10.1	Variable Documentation	155
9.10.1.1	segment_coeffs_13	155
9.11	de405_14.cc File Reference	155
9.11.1	Variable Documentation	155
9.11.1.1	segment_coeffs_14	155
9.12	de405_15.cc File Reference	155
9.12.1	Variable Documentation	155
9.12.1.1	segment_coeffs_15	155
9.13	de405_16.cc File Reference	156
9.13.1	Variable Documentation	156
9.13.1.1	segment_coeffs_16	156
9.14	de405_17.cc File Reference	156

9.14.1	Variable Documentation	156
9.14.1.1	segment_coeffs_17	156
9.15	de405_18.cc File Reference	156
9.15.1	Variable Documentation	156
9.15.1.1	segment_coeffs_18	156
9.16	de405_19.cc File Reference	157
9.16.1	Variable Documentation	157
9.16.1.1	segment_coeffs_19	157
9.17	de405_2.cc File Reference	157
9.17.1	Variable Documentation	157
9.17.1.1	segment_coeffs_2	157
9.18	de405_20.cc File Reference	157
9.18.1	Variable Documentation	157
9.18.1.1	segment_coeffs_20	157
9.19	de405_21.cc File Reference	158
9.19.1	Variable Documentation	158
9.19.1.1	segment_coeffs_21	158
9.20	de405_22.cc File Reference	158
9.20.1	Variable Documentation	158
9.20.1.1	segment_coeffs_22	158
9.21	de405_23.cc File Reference	158
9.21.1	Variable Documentation	158
9.21.1.1	segment_coeffs_23	158
9.22	de405_24.cc File Reference	159
9.22.1	Variable Documentation	159
9.22.1.1	segment_coeffs_24	159
9.23	de405_25.cc File Reference	159
9.23.1	Variable Documentation	159
9.23.1.1	segment_coeffs_25	159
9.24	de405_26.cc File Reference	159
9.24.1	Variable Documentation	159
9.24.1.1	segment_coeffs_26	159
9.25	de405_27.cc File Reference	160
9.25.1	Variable Documentation	160
9.25.1.1	segment_coeffs_27	160
9.26	de405_28.cc File Reference	160
9.26.1	Variable Documentation	160
9.26.1.1	segment_coeffs_28	160
9.27	de405_29.cc File Reference	160
9.27.1	Variable Documentation	160

9.27.1.1	segment_coeffs_29	160
9.28	de405_3.cc File Reference	161
9.28.1	Variable Documentation	161
9.28.1.1	segment_coeffs_3	161
9.29	de405_30.cc File Reference	161
9.29.1	Variable Documentation	161
9.29.1.1	segment_coeffs_30	161
9.30	de405_4.cc File Reference	161
9.30.1	Variable Documentation	161
9.30.1.1	segment_coeffs_4	161
9.31	de405_5.cc File Reference	162
9.31.1	Variable Documentation	162
9.31.1.1	segment_coeffs_5	162
9.32	de405_6.cc File Reference	162
9.32.1	Variable Documentation	162
9.32.1.1	segment_coeffs_6	162
9.33	de405_7.cc File Reference	162
9.33.1	Variable Documentation	162
9.33.1.1	segment_coeffs_7	162
9.34	de405_8.cc File Reference	163
9.34.1	Variable Documentation	163
9.34.1.1	segment_coeffs_8	163
9.35	de405_9.cc File Reference	163
9.35.1	Variable Documentation	163
9.35.1.1	segment_coeffs_9	163
9.36	de421_0.cc File Reference	163
9.36.1	Variable Documentation	163
9.36.1.1	itemData	163
9.36.1.2	metaData	164
9.36.1.3	segment_coeffs_0	164
9.36.1.4	segmentData	164
9.37	de421_1.cc File Reference	164
9.37.1	Variable Documentation	165
9.37.1.1	segment_coeffs_1	165
9.38	de440_0.cc File Reference	165
9.38.1	Variable Documentation	165
9.38.1.1	itemData	165
9.38.1.2	metaData	165
9.38.1.3	segment_coeffs_0	165
9.38.1.4	segmentData	166

9.39	de440_1.cc File Reference	166
9.39.1	Variable Documentation	166
9.39.1.1	segment_coeffs_1	166
9.40	de440_10.cc File Reference	166
9.40.1	Variable Documentation	166
9.40.1.1	segment_coeffs_10	166
9.41	de440_2.cc File Reference	166
9.41.1	Variable Documentation	166
9.41.1.1	segment_coeffs_2	166
9.42	de440_3.cc File Reference	167
9.42.1	Variable Documentation	167
9.42.1.1	segment_coeffs_3	167
9.43	de440_4.cc File Reference	167
9.43.1	Variable Documentation	167
9.43.1.1	segment_coeffs_4	167
9.44	de440_5.cc File Reference	167
9.44.1	Variable Documentation	167
9.44.1.1	segment_coeffs_5	167
9.45	de440_6.cc File Reference	168
9.45.1	Variable Documentation	168
9.45.1.1	segment_coeffs_6	168
9.46	de440_7.cc File Reference	168
9.46.1	Variable Documentation	168
9.46.1.1	segment_coeffs_7	168
9.47	de440_8.cc File Reference	168
9.47.1	Variable Documentation	168
9.47.1.1	segment_coeffs_8	168
9.48	de440_9.cc File Reference	169
9.48.1	Variable Documentation	169
9.48.1.1	segment_coeffs_9	169
9.49	de4xx_base.hh File Reference	169
9.49.1	Detailed Description	170
9.50	de4xx_ephem.cc File Reference	170
9.50.1	Detailed Description	171
9.51	de4xx_ephem.hh File Reference	171
9.51.1	Detailed Description	171
9.52	de4xx_ephem_dynmanager.cc File Reference	171
9.52.1	Detailed Description	172
9.53	de4xx_file.cc File Reference	172
9.53.1	Detailed Description	173

9.54	de4xx_file.hh File Reference	173
9.54.1	Detailed Description	174
9.55	de4xx_file_init.cc File Reference	174
9.55.1	Detailed Description	174
9.56	de4xx_file_update.cc File Reference	174
9.56.1	Detailed Description	175
9.57	ephem_interface.hh File Reference	175
9.57.1	Detailed Description	175
9.58	ephem_item.cc File Reference	175
9.58.1	Detailed Description	176
9.59	ephem_item.hh File Reference	176
9.59.1	Detailed Description	176
9.60	ephem_item_inline.hh File Reference	177
9.60.1	Detailed Description	177
9.61	ephem_manager.cc File Reference	177
9.61.1	Detailed Description	177
9.62	ephem_manager.hh File Reference	177
9.62.1	Detailed Description	178
9.63	ephem_messages.cc File Reference	178
9.63.1	Detailed Description	178
9.63.2	Macro Definition Documentation	178
9.63.2.1	MAKE_EPHEMERIDES_MESSAGE_CODE	178
9.64	ephem_messages.hh File Reference	179
9.64.1	Detailed Description	179
9.65	ephem_orient.cc File Reference	179
9.65.1	Detailed Description	179
9.66	ephem_orient.hh File Reference	180
9.66.1	Detailed Description	180
9.67	ephem_orient_zxz.cc File Reference	180
9.67.1	Detailed Description	181
9.68	ephem_orient_zxz.hh File Reference	181
9.68.1	Detailed Description	181
9.69	ephem_point.cc File Reference	181
9.69.1	Detailed Description	182
9.70	ephem_point.hh File Reference	182
9.70.1	Detailed Description	182
9.71	ephem_ref_frame.cc File Reference	182
9.71.1	Detailed Description	183
9.72	ephem_ref_frame.hh File Reference	183
9.72.1	Detailed Description	183

9.73 find_planet.cc File Reference	183
9.73.1 Detailed Description	184
9.74 propagated_planet.cc File Reference	184
9.74.1 Detailed Description	184
9.75 propagated_planet.hh File Reference	185
9.75.1 Detailed Description	185
9.76 simple_ephemerides.cc File Reference	185
9.76.1 Detailed Description	186
9.77 simple_ephemerides.hh File Reference	186
9.77.1 Detailed Description	186

Index**187**

Chapter 1

Module Index

1.1 Modules

Here is a list of all modules:

Models	13
Environment	14
Ephemerides	15
De4xxEphem	16
EphemInterface	17
EphemItem	18
EphemManager	19
PropagatedPlanet	20

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

jeod	Namespace jeod	21
jeod::De4xxBase	Defines enumerations used in the DE4xx ephemeris model	23

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

ActivateInterface	
jeod::EphemerisInterface	97
jeod::De4xxEphemeris	32
jeod::PropagatedPlanet	133
jeod::SinglePointEphemeris	146
jeod::EmptySpaceEphemeris	73
jeod::SinglePlanetEphemeris	141
BaseRefFrameManager	
jeod::BaseEphemeridesManager	27
jeod::EphemeridesManager	77
jeod::De4xxEphemItem	44
jeod::De4xxFile	47
jeod::De4xxFileCoef	56
jeod::De4xxFileHeader	58
jeod::De4xxFileIO	61
jeod::De4xxFileItem	64
jeod::De4xxFileRefTime	67
jeod::De4xxFileSpec	71
jeod::EphemeridesMessages	89
jeod::EphemerisDataItemMeta	93
jeod::EphemerisDataSegmentMeta	94
jeod::EphemerisDataSetMeta	95
RefFrame	
jeod::EphemerisRefFrame	120
RefFrameManager	
jeod::EphemeridesManager	77
RefFrameOwner	
jeod::De4xxEphemeris	32
jeod::EphemerisItem	100
jeod::EphemerisOrientation	113
jeod::EphemerisZXZOrientation	123
jeod::PropagatedEphemerisOrientation	127
jeod::EphemerisPoint	116
jeod::PropagatedEphemerisPlanet	130
SimpleCheckpointable	
jeod::De4xxFileRestart	69

Chapter 4

Data Structure Index

4.1 Data Structures

Here are the data structures with brief descriptions:

jeod::BaseEphemeridesManager	The EphemManager class augments the RefFrameManager with ephemeris-related items . . .	27
jeod::De4xxEphemeris	The S_define-level class that provides planetary ephemerides	32
jeod::De4xxEphemItem	Describes a point modeled in a DE4xx ephemeris file	44
jeod::De4xxFile	Provides the ability to read and interpret a DE4xx ephemeris file	47
jeod::De4xxFileCoef	Contains Chebychev polynomial coefficients and terms	56
jeod::De4xxFileHeader	Contains data extracted from the ephemeris file header	58
jeod::De4xxFileIO	Contains data used directly for reading the ephemeris file	61
jeod::De4xxFileItem	Contains data regarding one of the items in a DE ephemeris file	64
jeod::De4xxFileRefTime	Contains timing reference data	67
jeod::De4xxFileRestart	The FILE pointer in a De4xxFileIO cannot be restored by Trick	69
jeod::De4xxFileSpec	Specifies which file to use (user input initialization-time data)	71
jeod::EmptySpaceEphemeris	Empty space has one ephemeris point	73
jeod::EphemeridesManager	Manages the ephemeris models in a simulation	77
jeod::EphemeridesMessages	Specifies the message IDs used in the Ephemerides model	89
jeod::EphemerisDataItemMeta	Structure containing the header metadata for sizing/locating the data entries with the data segments	93
jeod::EphemerisDataSegmentMeta	Metadata implied from each data segment	94
jeod::EphemerisDataSetMeta	Container for the metadata from the DE model header	95
jeod::EphemerisInterface	Interface class that specifies minimal functionality of an ephemeris model	97

jeod::EphemerisItem	Base class for representing an item that is modeled in an ephemeris model	100
jeod::EphemerisOrientation	An EphemerisOrientation object updates the rotational state of an ephemeris reference frame . .	113
jeod::EphemerisPoint	An EphemerisPoint object updates the translational state of an ephemeris reference frame . .	116
jeod::EphemerisRefFrame	An EphemerisRefFrame is a RefFrame whose state is set by an ephemeris model	120
jeod::EphemerisZXZOrientation	The EphemerisZXZOrientation is an EphemerisOrientation subclass that updates orientation based on an Z-X-Z Euler sequence and the time derivatives of this sequence	123
jeod::PropagatedEphemerisOrientation	A PropagatedEphemerisOrientation is an EphemerisOrientation whose state is coupled with the rotational state of a DynBody reference frame	127
jeod::PropagatedEphemerisPlanet	A PropagatedEphemerisPlanet is an EphemerisPoint whose state is coupled with the translational state of a DynBody reference frame	130
jeod::PropagatedPlanet	The PropagatedPlanet ephemeris model provides planetary state via a DynBody object whose state is propagated using the JEOD state integration techniques	133
jeod::SinglePlanetEphemeris	A space with one gravitation body has one ephemeris point	141
jeod::SinglePointEphemeris	A SinglePointEphemeris has one ephemeris point	146

Chapter 5

File Index

5.1 File List

Here is a list of all files with brief descriptions:

base_ephem_manager.hh	Define the BaseEphemManager class, which defines the interfaces to the class EphemManager	151
de4xx_ephem/include/class_declarations.hh	Forward declarations of classes defined in the DE4xx model	151
ephem_interface/include/class_declarations.hh	Forward declarations of classes defined in models/environment/ephemerides/ephem_interface files	152
ephem_item/include/class_declarations.hh	Forward declarations of classes defined in models/environment/ephemerides/ephem_item files	152
de405_0.cc		152
de405_1.cc		153
de405_10.cc		154
de405_11.cc		154
de405_12.cc		154
de405_13.cc		155
de405_14.cc		155
de405_15.cc		155
de405_16.cc		156
de405_17.cc		156
de405_18.cc		156
de405_19.cc		157
de405_2.cc		157
de405_20.cc		157
de405_21.cc		158
de405_22.cc		158
de405_23.cc		158
de405_24.cc		159
de405_25.cc		159
de405_26.cc		159
de405_27.cc		160
de405_28.cc		160
de405_29.cc		160
de405_3.cc		161
de405_30.cc		161
de405_4.cc		161
de405_5.cc		162
de405_6.cc		162
de405_7.cc		162

de405_8.cc	163
de405_9.cc	163
de421_0.cc	163
de421_1.cc	164
de440_0.cc	165
de440_1.cc	166
de440_10.cc	166
de440_2.cc	166
de440_3.cc	167
de440_4.cc	167
de440_5.cc	167
de440_6.cc	168
de440_7.cc	168
de440_8.cc	168
de440_9.cc	169
de4xx_base.hh	
Define data types for JPL ephemeris model	169
de4xx_ephem.cc	
Define the methods of the classes defined in de4xx_ephem.hh	170
de4xx_ephem.hh	
Define class for the De4xx ephemeris model	171
de4xx_ephem_dynmanager.cc	
Wall off dependencies on the dynamics manager	171
de4xx_file.cc	
This file defines several utility functions used to read a binary JPL DE405 ephemeris file	172
de4xx_file.hh	
Define the class responsible for reading the DE4xx ephemeris file	173
de4xx_file_init.cc	
Define De4xx initialization methods	174
de4xx_file_update.cc	
Define De4xxFile::update	174
ephem_interface.hh	
Define base class for all ephemeris interface models	175
ephem_item.cc	
Define member functions for the EphemerItem class and subclasses	175
ephem_item.hh	
Define classes for items represented in some ephemeris model	176
ephem_item_inline.hh	
Define inline methods for the EphemerisItem class	177
ephem_manager.cc	
Define EphemeridesManager methods	177
ephem_manager.hh	
Define the EphemManager class, which manages the ephemeris models in a JEOD-based simulation	177
ephem_messages.cc	
Implement the class EphemeridesMessages	178
ephem_messages.hh	
Define the class EphemeridesMessages, the class that specifies the message IDs used in the JEOD ephemerides model	179
ephem_orient.cc	
Define member functions for the EphemerItem class and subclasses	179
ephem_orient.hh	
Define class EphemerisOrientation	180
ephem_orient_zxz.cc	
Define member functions for the EphemerItem class and subclasses	180
ephem_orient_zxz.hh	
Define classes for items represented in some ephemeris model	181

ephem_point.cc	Define member functions for the EphemPoint class	181
ephem_point.hh	Define class EphemerisPoint	182
ephem_ref_frame.cc	Define non-inlined member functions for the EphemRefFrame class	182
ephem_ref_frame.hh	Define the class EphemerisRefFrame	183
find_planet.cc	Define EphemeridesManager::find_planet	183
propagated_planet.cc	Define the methods of the classes defined in propagated_planet.hh	184
propagated_planet.hh	Define the classes needed to propagate a planet	185
simple_ephemerides.cc	Define member functions for the SinglePointEphemeris class and subclasses	185
simple_ephemerides.hh	Define classes that define simple ephemeris models	186

Chapter 6

Module Documentation

6.1 Models

Modules

- [Environment](#)

6.1.1 Detailed Description

6.2 Environment

Modules

- [Ephemerides](#)

6.2.1 Detailed Description

6.3 Ephemerides

Modules

- [De4xxEphem](#)
- [EphemInterface](#)
- [EphemItem](#)
- [EphemManager](#)
- [PropagatedPlanet](#)

6.3.1 Detailed Description

6.4 De4xxEphem

Files

- file [de4xx_ephem/include/class_declarations.hh](#)
Forward declarations of classes defined in the DE4xx model.
- file [de4xx_base.hh](#)
Define data types for JPL ephemeris model.
- file [de4xx_ephem.hh](#)
Define class for the De4xx ephemeris model.
- file [de4xx_file.hh](#)
Define the class responsible for reading the DE4xx ephemeris file.
- file [de4xx_ephem.cc](#)
Define the methods of the classes defined in [de4xx_ephem.hh](#).
- file [de4xx_ephem_dynmanager.cc](#)
Wall off dependencies on the dynamics manager.
- file [de4xx_file.cc](#)
This file defines several utility functions used to read a binary JPL DE405 ephemeris file.
- file [de4xx_file_init.cc](#)
Define De4xx initialization methods.
- file [de4xx_file_update.cc](#)
Define De4xxFile::update.

Namespaces

- [jeod](#)
Namespace jeod.

Macros

- `#define __STDC_LIMIT_MACROS`

6.4.1 Detailed Description

6.4.2 Macro Definition Documentation

6.4.2.1 `#define __STDC_LIMIT_MACROS`

Definition at line 51 of file [de4xx_file.cc](#).

6.5 EphemerInterface

Files

- file [ephem_interface/include/class_declarations.hh](#)
Forward declarations of classes defined in models/environment/ephemerides/ephem_interface files.
- file [ephem_interface.hh](#)
Define base class for all ephemeris interface models.
- file [ephem_messages.hh](#)
Define the class EphemeridesMessages, the class that specifies the message IDs used in the JEOD ephemerides model.
- file [ephem_ref_frame.hh](#)
Define the class EphemerisRefFrame.
- file [simple_ephemerides.hh](#)
Define classes that define simple ephemeris models.
- file [ephem_messages.cc](#)
Implement the class EphemeridesMessages.
- file [ephem_ref_frame.cc](#)
Define non-inlined member functions for the EphemRefFrame class.
- file [simple_ephemerides.cc](#)
Define member functions for the SinglePointEphemeris class and subclasses.

Namespaces

- [jeod](#)
Namespace jeod.

6.5.1 Detailed Description

6.6 EphemItem

Files

- file [ephem_item/include/class_declarations.hh](#)
Forward declarations of classes defined in models/environment/ephemerides/ephem_item files.
- file [ephem_item.hh](#)
Define classes for items represented in some ephemeris model.
- file [ephem_item_inline.hh](#)
Define inline methods for the EphemerisItem class.
- file [ephem_orient.hh](#)
Define class EphemerisOrientation.
- file [ephem_orient_zxz.hh](#)
Define classes for items represented in some ephemeris model.
- file [ephem_point.hh](#)
Define class EphemerisPoint.
- file [ephem_item.cc](#)
Define member functions for the EphemItem class and subclasses.
- file [ephem_orient.cc](#)
Define member functions for the EphemItem class and subclasses.
- file [ephem_orient_zxz.cc](#)
Define member functions for the EphemItem class and subclasses.
- file [ephem_point.cc](#)
Define member functions for the EphemPoint class.

Namespaces

- [jeod](#)
Namespace jeod.

Macros

- `#define EPSILON_TIME 1e-12`
- `#define TAYLOR_CUTOFF 0.00786`

6.6.1 Detailed Description

6.6.2 Macro Definition Documentation

6.6.2.1 `#define EPSILON_TIME 1e-12`

Definition at line 60 of file `ephem_orient_zxz.cc`.

Referenced by `jeod::EphemerisZXZOrientation::propagate()`.

6.6.2.2 `#define TAYLOR_CUTOFF 0.00786`

Definition at line 70 of file `ephem_orient_zxz.cc`.

Referenced by `jeod::EphemerisZXZOrientation::propagate()`.

6.7 EphemManager

Files

- file [base_ephem_manager.hh](#)
Define the BaseEphemManager class, which defines the interfaces to the class EphemManager.
- file [ephem_manager.hh](#)
Define the EphemManager class, which manages the ephemeris models in a JEOD-based simulation.
- file [ephem_manager.cc](#)
Define EphemeridesManager methods.
- file [find_planet.cc](#)
Define EphemeridesManager::find_planet.

Namespaces

- [jeod](#)
Namespace jeod.

6.7.1 Detailed Description

6.8 PropagatedPlanet

Files

- file [propagated_planet.hh](#)
Define the classes needed to propagate a planet.
- file [propagated_planet.cc](#)
Define the methods of the classes defined in [propagated_planet.hh](#).

Namespaces

- [jeod](#)
Namespace jeod.

6.8.1 Detailed Description

Chapter 7

Namespace Documentation

7.1 jeod Namespace Reference

Namespace jeod.

Namespaces

- [De4xxBase](#)
Defines enumerations used in the DE4xx ephemeris model.

Data Structures

- class [De4xxEphemItem](#)
Describes a point modeled in a DE4xx ephemeris file.
- class [De4xxEphemeris](#)
The S_define-level class that provides planetary ephemerides.
- struct [EphemerisDataSetMeta](#)
Container for the metadata from the DE model header.
- struct [EphemerisDataItemMeta](#)
Structure containing the header metadata for sizing/locating the data entries with the data segments.
- struct [EphemerisDataSegmentMeta](#)
Metadata implied from each data segment.
- class [De4xxFileSpec](#)
Specifies which file to use (user input initialization-time data).
- class [De4xxFileIO](#)
Contains data used directly for reading the ephemeris file.
- class [De4xxFileHeader](#)
Contains data extracted from the ephemeris file header.
- class [De4xxFileItem](#)
Contains data regarding one of the items in a DE ephemeris file.
- class [De4xxFileRefTime](#)
Contains timing reference data.
- class [De4xxFileCoef](#)
Contains Chebychev polynomial coefficients and terms.
- class [De4xxFileRestart](#)
The FILE pointer in a [De4xxFileIO](#) cannot be restored by Trick.
- class [De4xxFile](#)

Provides the ability to read and interpret a DE4xx ephemeris file.

- class [EphemerisInterface](#)

Interface class that specifies minimal functionality of an ephemeris model.

- class [EphemeridesMessages](#)

Specifies the message IDs used in the Ephemerides model.

- class [EphemerisRefFrame](#)

An [EphemerisRefFrame](#) is a [RefFrame](#) whose state is set by an ephemeris model.

- class [SinglePointEphemeris](#)

A [SinglePointEphemeris](#) has one ephemeris point.

- class [EmptySpaceEphemeris](#)

Empty space has one ephemeris point.

- class [SinglePlanetEphemeris](#)

A space with one gravitation body has one ephemeris point.

- class [EphemerisItem](#)

The [EphemerisItem](#) class is the base class for representing an item that is modeled in an ephemeris model.

- class [EphemerisOrientation](#)

An [EphemerisOrientation](#) object updates the rotational state of an ephemeris reference frame.

- class [EphemerisZXZOrientation](#)

The [EphemerisZXZOrientation](#) is an [EphemerisOrientation](#) subclass that updates orientation based on an Z-X-Z Euler sequence and the time derivatives of this sequence.

- class [EphemerisPoint](#)

An [EphemerisPoint](#) object updates the translational state of an ephemeris reference frame.

- class [BaseEphemeridesManager](#)

The [EphemManager](#) class augments the [RefFrameManager](#) with ephemeris-related items.

- class [EphemeridesManager](#)

The [EphemeridesManager](#) class manages the ephemeris models in a simulation.

- class [PropagatedEphemerisPlanet](#)

A [PropagatedEphemerisPlanet](#) is an [EphemerisPoint](#) whose state is coupled with the translational state of a [DynBody](#) reference frame.

- class [PropagatedEphemerisOrientation](#)

A [PropagatedEphemerisOrientation](#) is an [EphemerisOrientation](#) whose state is coupled with the rotational state of a [DynBody](#) reference frame.

- class [PropagatedPlanet](#)

The [PropagatedPlanet](#) ephemeris model provides planetary state via a [DynBody](#) object whose state is propagated using the JEOD state integration techniques.

Functions

- void [process_mem_usage](#) (double &vm_usage, double &resident_set)
- static double [l1_point](#) (double b1b2_mass_ratio)

Calculate the location of the L1 point as a ratio.

7.1.1 Detailed Description

Namespace jeod.

7.1.2 Function Documentation

7.1.2.1 static double jeod::l1_point (double *b1b2_mass_ratio*) [static]

Calculate the location of the L1 point as a ratio.

Returns

Ratio of body1 to L1-point distance to body1 to body2 distance

Parameters

in	<i>b1b2_mass_ratio</i>	Body1 to body2 mass ratio
----	------------------------	---------------------------

Definition at line 276 of file `de4xx_file_init.cc`.

Referenced by `jeod::De4xxFile::initialize()`.

7.1.2.2 void jeod::process_mem_usage (double & *vm_usage*, double & *resident_set*)

Definition at line 495 of file `de4xx_file.cc`.

Referenced by `jeod::De4xxFile::capture_mem_stats()`.

7.2 jeod::De4xxBase Namespace Reference

Defines enumerations used in the DE4xx ephemeris model.

Enumerations

- enum [De4xxFileEntries](#) {
[De4xx_File_Mercury](#) = 0, [De4xx_File_Venus](#) = 1, [De4xx_File_EMbary](#) = 2, [De4xx_File_Mars](#) = 3,
[De4xx_File_Jupiter](#) = 4, [De4xx_File_Saturn](#) = 5, [De4xx_File_Uranus](#) = 6, [De4xx_File_Neptune](#) = 7,
[De4xx_File_Pluto](#) = 8, [De4xx_File_Moon](#) = 9, [De4xx_File_Sun](#) = 10, [De4xx_File_ENutation](#) = 11,
[De4xx_File_LLibration](#) = 12, [De4xx_File_LAngVel](#) = 13, [De4xx_File_tt_tdb](#) = 14, [De4xx_File_MaxEntries](#) }
Defines names for planetary body descriptors in the ephemeris file.
- enum [De4xxEphemConsts](#) {
[De4xx_Const_DENUM](#) = 0, [De4xx_Const_LENUM](#), [De4xx_Const_AU](#), [De4xx_Const_EMRA](#),
[De4xx_Const_CLIGHT](#), [De4xx_Const_GM1](#), [De4xx_Const_GM2](#), [De4xx_Const_GMB](#),
[De4xx_Const_GM4](#), [De4xx_Const_GM5](#), [De4xx_Const_GM6](#), [De4xx_Const_GM7](#),
[De4xx_Const_GM8](#), [De4xx_Const_GM9](#), [De4xx_Const_GMS](#), [De4xx_Const_MaxConsts](#) }
Index aliases for the constants listed in the DE header that are used by JEOD.
- enum [De4xxEphemBodies](#) {
[De4xx_Ephem_Sun](#) = 0, [De4xx_Ephem_Mercury](#) = 1, [De4xx_Ephem_Venus](#) = 2, [De4xx_Ephem_Earth](#) = 3,
[De4xx_Ephem_Mars](#) = 4, [De4xx_Ephem_Jupiter](#) = 5, [De4xx_Ephem_Saturn](#) = 6, [De4xx_Ephem_Uranus](#) =
7,
[De4xx_Ephem_Neptune](#) = 8, [De4xx_Ephem_Pluto](#) = 9, [De4xx_Ephem_Moon](#) = 10, [De4xx_Ephem_EMbary](#)
= 11,
[De4xx_Ephem_SSbary](#) = 12, [De4xx_Ephem_EML1](#) = 13, [De4xx_Ephem_ENutation](#) = 14, [De4xx_Ephem_-](#)
[LLibration](#) = 15,
[De4xx_Ephem_MaxBodies](#) }
Defines names for ephemeris items as represented in the JEOD DE4xx model.

Functions

- static const char *point_names[32] [__attribute__\(\(unused\)\)](#)
- static uint32_t [number_jeod_items](#) (int de_version_num [__attribute__\(\(unused\)\)](#))
Total number of items in the JEOD ephemeris.
- static uint32_t [number_trans_points](#) (int de_version_num [__attribute__\(\(unused\)\)](#))
Total number of translational states in the JEOD ephemeris.
- static uint32_t [number_grav_models](#) (int de_version_num [__attribute__\(\(unused\)\)](#))
Number of gravity models in the JEOD ephemeris (Mercury to Sun + implied Earth) Currently only one possibility, but written for extensibility.
- static uint32_t [number_physical_bodies](#) (int de_version_num [__attribute__\(\(unused\)\)](#))
Number of bodies in the JEOD ephemeris (Planets + Pluto + Moon + Sun) Currently only one possibility, but written for extensibility.

7.2.1 Detailed Description

Defines enumerations used in the DE4xx ephemeris model.

7.2.2 Enumeration Type Documentation

7.2.2.1 enum jeod::De4xxBase::De4xxEphemBodies

Defines names for ephemeris items as represented in the JEOD DE4xx model.

NOTA BENE: The Earth-moon barycenter follows the massive bodies as the barycenter is not itself a massive body.

Enumerator

De4xx_Ephem_Sun Sun.

De4xx_Ephem_Mercury Mercury.

De4xx_Ephem_Venus Venus.

De4xx_Ephem_Earth Earth.

De4xx_Ephem_Mars Mars.

De4xx_Ephem_Jupiter Jupiter.

De4xx_Ephem_Saturn Saturn.

De4xx_Ephem_Uranus Uranus.

De4xx_Ephem_Neptune Neptune.

De4xx_Ephem_Pluto Pluto.

De4xx_Ephem_Moon Moon.

De4xx_Ephem_EMbary Earth-moon barycenter.

De4xx_Ephem_SSbary Solar system barycenter.

De4xx_Ephem_EML1 Earth-moon L1 point (disabled)

De4xx_Ephem_ENutation Nutations (disabled)

De4xx_Ephem_LLibration Librations.

De4xx_Ephem_MaxBodies

Definition at line 148 of file de4xx_base.hh.

7.2.2.2 enum jeod::De4xxBase::De4xxEphemConsts

Index aliases for the constants listed in the DE header that are used by JEOD.

This is an incomplete subset of the constants provided by DE, but all of these constants must be present for JEOD ephemeris to perform.

Enumerator

De4xx_Const_DENUM
De4xx_Const_LENUM
De4xx_Const_AU
De4xx_Const_EMRAT
De4xx_Const_CLIGHT
De4xx_Const_GM1
De4xx_Const_GM2
De4xx_Const_GMB
De4xx_Const_GM4
De4xx_Const_GM5
De4xx_Const_GM6
De4xx_Const_GM7
De4xx_Const_GM8
De4xx_Const_GM9
De4xx_Const_GMS
De4xx_Const_MaxConsts

Definition at line 122 of file de4xx_base.hh.

7.2.2.3 enum jeod::De4xxBase::De4xxFileEntries

Defines names for planetary body descriptors in the ephemeris file.

This enum defines names for the bodies as they are represented in the ephemeris file.

Enumerator

De4xx_File_Mercury Mercury XYZ [km].
De4xx_File_Venus Venus XYZ.
De4xx_File_EMbary Earth-moon barycenter XYZ.
De4xx_File_Mars Mars XYZ.
De4xx_File_Jupiter Jupiter XYZ.
De4xx_File_Saturn Saturn XYZ.
De4xx_File_Uranus Uranus XYZ.
De4xx_File_Neptune Neptune XYZ.
De4xx_File_Pluto Pluto XYZ.
De4xx_File_Moon Moon, geocentric coords. XYZ.
De4xx_File_Sun Sun XYZ.
De4xx_File_ENutation Earth Nutations d(psi), d(eps) [rad].
De4xx_File_LLibration Lun mantle Libratns phi,tht,psi [rad].
De4xx_File_LAngVel Lun mantle ang vel omg_{xyz} [rad/day].
De4xx_File_tt_tdb TDB to TT offset @ geocenter [s].
De4xx_File_MaxEntries

Definition at line 95 of file de4xx_base.hh.

7.2.3 Function Documentation

7.2.3.1 `static const char* point_names [32] jeod::De4xxBase::__attribute__ ((unused)) [static]`

7.2.3.2 `static uint32_t jeod::De4xxBase::number_grav_models (int de_version_num __attribute__(unused)) [inline], [static]`

Number of gravity models in the JEOD ephemeris (Mercury to Sun + implied Earth) Currently only one possibility, but written for extensibility.

Definition at line 217 of file `de4xx_base.hh`.

Referenced by `jeod::De4xxFileHeader::De4xxFileHeader()`, and `jeod::De4xxFile::initialize()`.

7.2.3.3 `static uint32_t jeod::De4xxBase::number_jeod_items (int de_version_num __attribute__(unused)) [inline], [static]`

Total number of items in the JEOD ephemeris.

Refer to `De4xxEphemBodies` for identities of each item. Currently only one possibility, but written for extensibility

Definition at line 197 of file `de4xx_base.hh`.

Referenced by `jeod::De4xxEphemeris::activate_nodes()`, `jeod::De4xxEphemeris::De4xxEphemeris()`, `jeod::De4xxEphemeris::ephem_activate()`, `jeod::De4xxEphemeris::ephem_initialize()`, and `jeod::De4xxEphemeris::initialize_items()`.

7.2.3.4 `static uint32_t jeod::De4xxBase::number_physical_bodies (int de_version_num __attribute__(unused)) [inline], [static]`

Number of bodies in the JEOD ephemeris (Planets + Pluto + Moon + Sun) Currently only one possibility, but written for extensibility.

Definition at line 226 of file `de4xx_base.hh`.

7.2.3.5 `static uint32_t jeod::De4xxBase::number_trans_points (int de_version_num __attribute__(unused)) [inline], [static]`

Total number of translational states in the JEOD ephemeris.

(Sun, Mercury to Pluto, EMBary, SSbary) Currently excludes EML1 Currently only one possibility, but written for extensibility

Definition at line 207 of file `de4xx_base.hh`.

Referenced by `jeod::De4xxEphemeris::activate_nodes()`, `jeod::De4xxEphemeris::De4xxEphemeris()`, `jeod::De4xxEphemeris::determine_root_node()`, `jeod::De4xxEphemeris::ephem_build_tree()`, and `jeod::De4xxEphemeris::initialize_items()`.

Chapter 8


Data Structure Documentation

8.1 jeod::BaseEphemeridesManager Class Reference

The EphemManager class augments the RefFrameManager with ephemeris-related items.

```
#include <base_ephem_manager.hh>
```

Inheritance diagram for jeod::BaseEphemeridesManager:



Public Member Functions

- [~BaseEphemeridesManager](#) () override
Destructor.
- virtual void [ephem_note_tree_status_change](#) ()=0
Denote that the tree needs to be rebuilt.
- virtual void [add_planet](#) (BasePlanet &planet)=0
Add a planet to the list of such.
- virtual void [add_planet](#) (Planet &planet)=0
Add a planet to the list of such.
- virtual BasePlanet * [find_base_planet](#) (const char *name) const =0
Find a planet.
- virtual Planet * [find_planet](#) (const char *name) const =0
Find a planet.
- virtual unsigned int [get_num_planets](#) (void) const =0
Return number of registered planets.
- virtual void [add_ephemeris](#) (EphemerisInterface &ephem_if)=0
Add an ephemeris model to the list of such.
- virtual void [clear_added_ephemerides](#) (void)=0
Deactivate all registered ephemeris models.
- virtual void [disable_add_ephemeris](#) (void)=0

- Disable registration of new ephemeris models.*
- virtual void `add_ephem_item` (`EphemerisItem` &ephem_item)=0
Add an ephemeris item to the list of such.
- virtual `EphemerisItem` * `find_ephem_item` (const char *name) const =0
Find an ephemeris item.
- virtual `EphemerisOrientation` * `find_ephem_angle` (const char *name) const =0
Find an ephemeris orientation.
- virtual `EphemerisPoint` * `find_ephem_point` (const char *name) const =0
Find an ephemeris point.
- virtual void `add_integ_frame` (`EphemerisRefFrame` &ref_frame)=0
Add an integration frame to the list of such.
- virtual `EphemerisRefFrame` * `find_integ_frame` (const char *name) const =0
Find an integration frame.
- virtual bool `is_integ_frame` (const `RefFrame` &ref_frame) const =0
Check whether a reference frame is an integration frame.
- virtual unsigned int `find_integ_frame_index` (const `EphemerisRefFrame` &ref_frame) const =0
Find a reference frame's index in the list of integration frames.
- virtual const std::vector
 < `EphemerisRefFrame` * > & `get_integ_frames` (void) const =0
Get the vector of integration frames.

Friends

- class `InputProcessor`
- void `init_attrjeod__BaseEphemeridesManager` ()

8.1.1 Detailed Description

The EphemManager class augments the RefFrameManager with ephemeris-related items.

This class defines the external interfaces to that class.

Definition at line 91 of file base_ephem_manager.hh.

8.1.2 Constructor & Destructor Documentation

8.1.2.1 `jeod::BaseEphemeridesManager::~BaseEphemeridesManager ()` `[inline]`, `[override]`

Destructor.

Definition at line 105 of file base_ephem_manager.hh.

8.1.3 Member Function Documentation

8.1.3.1 `virtual void jeod::BaseEphemeridesManager::add_ephem_item (EphemerisItem & ephem_item)` `[pure virtual]`

Add an ephemeris item to the list of such.

Parameters

<i>ephem_item</i>	Item to be added.
-------------------	-------------------

Implemented in [jeod::EphemeridesManager](#).

8.1.3.2 `virtual void jeod::BaseEphemeridesManager::add_ephemeris (EphemerisInterface & ephem_if) [pure virtual]`

Add an ephemeris model to the list of such.

Parameters

<i>ephem_if</i>	Ephemeris model to be added.
-----------------	------------------------------

Implemented in [jeod::EphemeridesManager](#).

8.1.3.3 `virtual void jeod::BaseEphemeridesManager::add_integ_frame (EphemerisRefFrame & ref_frame) [pure virtual]`

Add an integration frame to the list of such.

Parameters

<i>ref_frame</i>	Frame to be added.
------------------	--------------------

Implemented in [jeod::EphemeridesManager](#).

8.1.3.4 `virtual void jeod::BaseEphemeridesManager::add_planet (BasePlanet & planet) [pure virtual]`

Add a planet to the list of such.

Parameters

<i>planet</i>	Planet to be added.
---------------	---------------------

Implemented in [jeod::EphemeridesManager](#).

8.1.3.5 `virtual void jeod::BaseEphemeridesManager::add_planet (Planet & planet) [pure virtual]`

Add a planet to the list of such.

Parameters

<i>planet</i>	Planet to be added.
---------------	---------------------

Implemented in [jeod::EphemeridesManager](#).

8.1.3.6 `virtual void jeod::BaseEphemeridesManager::clear_added_ephemerides (void) [pure virtual]`

Deactivate all registered ephemeris models.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.7 `virtual void jeod::BaseEphemeridesManager::disable_add_ephemeris (void) [pure virtual]`

Disable registration of new ephemeris models.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.8 `virtual void jeod::BaseEphemeridesManager::ephem_note_tree_status_change () [pure virtual]`

Denote that the tree needs to be rebuilt.

Implemented in [jeod::EphemeridesManager](#).

Referenced by `jeod::EphemerisItem::disable()`, `jeod::EphemerisItem::enable()`, and `jeod::EphemerisRefFrame::set_active_status()`.

8.1.3.9 `virtual BasePlanet* jeod::BaseEphemeridesManager::find_base_planet (const char * name) const [pure virtual]`

Find a planet.

Parameters

<i>name</i>	Planet name.
-------------	--------------

Returns

Pointer to found planet.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.10 `virtual EphemerisOrientation* jeod::BaseEphemeridesManager::find_ephem_angle (const char * name) const [pure virtual]`

Find an ephemeris orientation.

Parameters

<i>name</i>	Item to be found.
-------------	-------------------

Returns

Found item.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.11 `virtual EphemerisItem* jeod::BaseEphemeridesManager::find_ephem_item (const char * name) const [pure virtual]`

Find an ephemeris item.

Parameters

<i>name</i>	Item to be found.
-------------	-------------------

Returns

Found item.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.12 `virtual EphemerisPoint* jeod::BaseEphemeridesManager::find_ephem_point (const char * name) const [pure virtual]`

Find an ephemeris point.

Parameters

<i>name</i>	Item to be found.
-------------	-------------------

Returns

Found item.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.13 `virtual EphemerisRefFrame* jeod::BaseEphemeridesManager::find_integ_frame (const char * name) const`
`[pure virtual]`

Find an integration frame.

Parameters

<i>name</i>	Frame to be found.
-------------	--------------------

Returns

Found frame.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.14 `virtual unsigned int jeod::BaseEphemeridesManager::find_integ_frame_index (const EphemerisRefFrame & ref_frame) const`
`[pure virtual]`

Find a reference frame's index in the list of integration frames.

Parameters

<i>ref_frame</i>	Frame to be checked.
------------------	----------------------

Returns

Frame index.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.15 `virtual Planet* jeod::BaseEphemeridesManager::find_planet (const char * name) const` `[pure virtual]`

Find a planet.

Parameters

<i>name</i>	Planet name.
-------------	--------------

Returns

Pointer to found planet.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.16 `virtual const std::vector<EphemerisRefFrame*> & jeod::BaseEphemeridesManager::get_integ_frames (void) const`
`[pure virtual]`

Get the vector of integration frames.

Returns

Vector of reference frame pointers.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.17 `virtual unsigned int jeod::BaseEphemeridesManager::get_num_planets (void) const` `[pure virtual]`

Return number of registered planets.

Returns

Number of planets.

Implemented in [jeod::EphemeridesManager](#).

8.1.3.18 `virtual bool jeod::BaseEphemeridesManager::is_integ_frame (const RefFrame & ref_frame) const` `[pure virtual]`

Check whether a reference frame is an integration frame.

Parameters

<i>ref_frame</i>	Frame to be checked.
------------------	----------------------

Returns

True if *ref_frame* is an integration frame, false otherwise.

Implemented in [jeod::EphemeridesManager](#).

Referenced by [jeod::EphemerisItem::set_target_frame\(\)](#).

8.1.4 Friends And Related Function Documentation

8.1.4.1 `void init_attrjeod__BaseEphemeridesManager ()` `[friend]`

8.1.4.2 `friend class InputProcessor` `[friend]`

Definition at line 94 of file `base_ephem_manager.hh`.

The documentation for this class was generated from the following file:


- [base_ephem_manager.hh](#)

8.2 jeod::De4xxEphemeris Class Reference

The S_define-level class that provides planetary ephemerides.

```
#include <de4xx_ephem.hh>
```

Inheritance diagram for `jeod::De4xxEphemeris`:



Public Member Functions

- `De4xxEphemeris` (void)
De4xxEphemeris default constructor.
- `~De4xxEphemeris` (void) override
De4xxEphemeris destructor.
- void `initialize_model` (const TimeManager &time_manager, DynManager &dyn_manager, const std::string &time_type="TT")
Initialize the De4xxEphemeris model.
- void `initialize_model` (const TimeManager &time_manager, EphemeridesManager &ephem_manager, const std::string &time_type="TT")
Initialize the De4xxEphemeris model.
- void `propagate_lunar_rnp` (void)
Propagate the lunar orientation to the current time.
- void `shutdown` (void)
Free resources allocated by the De4xxEphemeris model.
- void `activate` (void) override
Nominally, activate the object.
- void `deactivate` (void) override
Deactivate the De4xxEphemeris object.
- double `timestamp` (void) const override
Return time of last update.
- const char * `get_name` (void) const override
Return model name.
- void `ephem_initialize` (EphemeridesManager &ephem_manager) override
Complete the initialization process.
- void `ephem_activate` (EphemeridesManager &ephem_manager) override
Mark appropriate items in the model as active.
- void `ephem_build_tree` (EphemeridesManager &ephem_manager) override
Construct the ephemeris model portions of the reference frame tree.
- void `ephem_update` (void) override
Update ephemerides for subscribed items.
- bool `time_is_in_range` (void) const
Check whether the specified time is represented in the JPL ephemeris file.
- void `set_model_number` (int denum_in)
Set ephemeris model number.
- uint32_t `get_model_number` ()
Get Ephemeris model number.
- const `De4xxFileHeader` & `get_header_data` ()

Data Fields

- bool [active](#)
Is the model active? This is set to true by the constructor.
- bool * [selected_items](#)
Used at initialization time only to selectively enable/disable portions of the model.

Protected Attributes

- [De4xxFile](#) file
The ephemeris file model.
- bool [force_update](#)
Is an update needed even if the time hasn't changed?
- unsigned int [nactive_items](#)
Number of items that are currently active.
- [De4xxEphemItem](#) * [item_data](#)
Data pertaining to the points for which translational states are calculated.
- char * [ident](#)
Identifier for this model, computed from the supplied file.
- double [update_time](#)
Time of last update, dynamic time seconds.
- [EphemerisPoint](#) * [points](#)
The planets and barycenter points, in De4xxEphemBodies FileBodies order.
- [EphemerisZXZOrientation](#) [lunar_orientation](#)
Lunar orientation.
- [EphemerisRefFrame](#) [earth_moon_barycenter_frame](#)
Earth-Moon barycenter reference frame.
- [EphemerisRefFrame](#) [solar_system_barycenter_frame](#)
Solar system barycenter reference frame.
- [De4xxEphemItem](#) * [root_item](#)
The root point in the reference frame tree.
- const TimeStandard * [time_tt](#)
The source of ephemeris time information.
- const TimeDyn * [time_dyn](#)
The source of dynamic time information.
- int * [body_to_file_idx](#)
Mapping from De4xxEphemBodies numbers to De4xxFileBodies numbers.

Private Member Functions

- void [initialize_time](#) (const TimeManager &time_manager, const std::string &time_type)
Initialize [De4xxEphemeris](#) timing.
- void [initialize_file](#) (void)
Initialize the [De4xxEphemeris](#) file.
- void [initialize_items](#) ([EphemeridesManager](#) &ephem_manager)
Initialize the [De4xxEphemeris](#) item data.
- unsigned int [activate_nodes](#) (void)
Mark appropriate items in the model as active.
- unsigned int [activate_em_nodes](#) (unsigned int tot_active)
Adjust Earth, Moon, and Earth-Moon barycenter activity.

- void [determine_root_node](#) (void)
Determine which item should be the root of the ref frame tree.
- [De4xxEphemeris](#) (const [De4xxEphemeris](#) &)
Not implemented.
- [De4xxEphemeris](#) & [operator=](#) (const [De4xxEphemeris](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__De4xxEphemeris](#) ()

8.2.1 Detailed Description

The S_define-level class that provides planetary ephemerides.

The [De4xxEphemeris](#) class constructs the ephemeris reference frame tree and updates the states of the planets based on data from a DE4xx ephemeris model.

Definition at line 196 of file `de4xx_ephem.hh`.

8.2.2 Constructor & Destructor Documentation

8.2.2.1 `jeod::De4xxEphemeris::De4xxEphemeris (void)`

[De4xxEphemeris](#) default constructor.

Definition at line 120 of file `de4xx_ephem.cc`.

References `body_to_file_idx`, `jeod::De4xxBase::De4xx_Ephem_Earth`, `jeod::De4xxBase::De4xx_Ephem_EMbary`, `jeod::De4xxBase::De4xx_Ephem_EML1`, `jeod::De4xxBase::De4xx_Ephem_ENutation`, `jeod::De4xxBase::De4xx_Ephem_Jupiter`, `jeod::De4xxBase::De4xx_Ephem_LLibration`, `jeod::De4xxBase::De4xx_Ephem_Mars`, `jeod::De4xxBase::De4xx_Ephem_Mercury`, `jeod::De4xxBase::De4xx_Ephem_Moon`, `jeod::De4xxBase::De4xx_Ephem_Neptune`, `jeod::De4xxBase::De4xx_Ephem_Pluto`, `jeod::De4xxBase::De4xx_Ephem_Saturn`, `jeod::De4xxBase::De4xx_Ephem_SSbary`, `jeod::De4xxBase::De4xx_Ephem_Sun`, `jeod::De4xxBase::De4xx_Ephem_Uranus`, `jeod::De4xxBase::De4xx_Ephem_Venus`, `jeod::De4xxBase::De4xx_File_EMbary`, `jeod::De4xxBase::De4xx_File_ENutation`, `jeod::De4xxBase::De4xx_File_Jupiter`, `jeod::De4xxBase::De4xx_File_LLibration`, `jeod::De4xxBase::De4xx_File_Mars`, `jeod::De4xxBase::De4xx_File_MaxEntries`, `jeod::De4xxBase::De4xx_File_Mercury`, `jeod::De4xxBase::De4xx_File_Moon`, `jeod::De4xxBase::De4xx_File_Neptune`, `jeod::De4xxBase::De4xx_File_Pluto`, `jeod::De4xxBase::De4xx_File_Saturn`, `jeod::De4xxBase::De4xx_File_Sun`, `jeod::De4xxBase::De4xx_File_Uranus`, `jeod::De4xxBase::De4xx_File_Venus`, `earth_moon_barycenter_frame`, `jeod::EphemerisOrientation::enable()`, `jeod::EphemerisItem::enable()`, `jeod::EphemerisItem::get_name()`, `jeod::De4xxEphemItem::index`, `jeod::De4xxEphemItem::item`, `item_data`, `lunar_orientation`, `jeod::De4xxEphemItem::name`, `jeod::De4xxBase::number_jeod_items()`, `jeod::De4xxBase::number_trans_points()`, `points`, `selected_items`, `jeod::EphemerisItem::set_name()`, `jeod::EphemerisItem::set_owner()`, and `solar_system_barycenter_frame`.

8.2.2.2 `jeod::De4xxEphemeris::~~De4xxEphemeris (void)` `[override]`

[De4xxEphemeris](#) destructor.

Definition at line 219 of file `de4xx_ephem.cc`.

References `body_to_file_idx`, `item_data`, `points`, `selected_items`, and `shutdown()`.

8.2.2.3 `jeod::De4xxEphemeris::De4xxEphemeris (const De4xxEphemeris &)` `[private]`

Not implemented.

8.2.3 Member Function Documentation

8.2.3.1 void jeod::De4xxEphemeris::activate (void) [override]

Nominally, activate the object.

In the case of a [De4xxEphemeris](#) object, an inactive object cannot be activated.

Definition at line 252 of file `de4xx_ephem.cc`.

References `active`, and `jeod::EphemeridesMessages::internal_error`.

8.2.3.2 unsigned int jeod::De4xxEphemeris::activate_em_nodes (unsigned int *tot_active*) [private]

Adjust Earth, Moon, and Earth-Moon barycenter activity.

Returns

Void

Parameters

<i>in</i>	<i>tot_active</i>	Number active translation nodes
-----------	-------------------	---------------------------------

Definition at line 578 of file `de4xx_ephem.cc`.

References `jeod::EphemerisItem::activate()`, `jeod::De4xxEphemItem::Active`, `jeod::De4xxBase::De4xx_Ephem_Earth`, `jeod::De4xxBase::De4xx_Ephem_EMbary`, `jeod::De4xxBase::De4xx_Ephem_Moon`, `jeod::De4xxEphemItem::Deselected`, `jeod::EphemerisItem::enable()`, `jeod::De4xxEphemItem::enabled_item`, `jeod::De4xxEphemItem::Inactive`, `jeod::EphemeridesMessages::inconsistent_setup`, `jeod::De4xxEphemItem::InTree`, `jeod::De4xxEphemItem::item`, `item_data`, `nactive_items`, `jeod::De4xxEphemItem::name`, and `jeod::De4xxEphemItem::status`.

Referenced by `ephem_activate()`.

8.2.3.3 unsigned int jeod::De4xxEphemeris::activate_nodes (void) [private]

Mark appropriate items in the model as active.

Returns

Void

Definition at line 534 of file `de4xx_ephem.cc`.

References `jeod::De4xxEphemItem::Active`, `jeod::De4xxEphemItem::Deselected`, `jeod::De4xxEphemItem::enabled_item`, `file`, `jeod::De4xxFile::file_spec`, `jeod::EphemerisItem::get_enabled_item()`, `jeod::De4xxFileSpec::get_model_number()`, `jeod::De4xxEphemItem::Inactive`, `jeod::De4xxEphemItem::InTree`, `jeod::EphemerisItem::is_active()`, `jeod::De4xxEphemItem::item`, `item_data`, `nactive_items`, `jeod::De4xxBase::number_jeod_items()`, `jeod::De4xxBase::number_trans_points()`, and `jeod::De4xxEphemItem::status`.

Referenced by `ephem_activate()`.

8.2.3.4 void jeod::De4xxEphemeris::deactivate (void) [override]

Deactivate the [De4xxEphemeris](#) object.

Definition at line 269 of file `de4xx_ephem.cc`.

References `active`.

8.2.3.5 void jeod::De4xxEphemeris::determine_root_node (void) [private]

Determine which item should be the root of the ref frame tree.

Definition at line 646 of file de4xx_ephem.cc.

References jeod::De4xxBase::De4xx_Ephem_Earth, jeod::De4xxBase::De4xx_Ephem_EMbary, jeod::De4xxBase::De4xx_Ephem_Moon, jeod::De4xxBase::De4xx_Ephem_SSbary, jeod::De4xxEphemItem::enabled_item, file, jeod::De4xxFile::file_spec, jeod::De4xxFileSpec::get_model_number(), jeod::De4xxEphemItem::Inactive, jeod::De4xxEphemItem::IsRoot, jeod::De4xxEphemItem::item, item_data, nactive_items, jeod::De4xxBase::number_trans_points(), root_item, and jeod::De4xxEphemItem::status.

Referenced by ephemer_activate().

8.2.3.6 void jeod::De4xxEphemeris::ephemer_activate (EphemeridesManager & ephemer_manager) [override], [virtual]

Mark appropriate items in the model as active.

Parameters

in, out	ephemer_manager	Ephemerides manager
---------	-----------------	---------------------

Implements [jeod::EphemerisInterface](#).

Definition at line 712 of file de4xx_ephem.cc.

References activate_em_nodes(), activate_nodes(), jeod::De4xxEphemItem::Active, active, jeod::De4xxFileItem::active, body_to_file_idx, jeod::De4xxBase::De4xx_Ephem_EMbary, jeod::De4xxBase::De4xx_Ephem_LLibration, jeod::De4xxBase::De4xx_Ephem_Sun, jeod::De4xxBase::De4xx_File_ENutation, jeod::De4xxBase::De4xx_File_LLibration, determine_root_node(), file, jeod::De4xxFile::file_spec, force_update, jeod::De4xxFileSpec::get_model_number(), jeod::De4xxFile::item, item_data, nactive_items, jeod::De4xxBase::number_jeod_items(), and jeod::De4xxEphemItem::status.

8.2.3.7 void jeod::De4xxEphemeris::ephemer_build_tree (EphemeridesManager & ephemer_manager) [override], [virtual]

Construct the ephemeris model portions of the reference frame tree.

Parameters

in, out	ephemer_manager	Ephemerides manager
---------	-----------------	---------------------

Implements [jeod::EphemerisInterface](#).

Definition at line 771 of file de4xx_ephem.cc.

References jeod::De4xxEphemItem::Active, active, jeod::De4xxBase::De4xx_Ephem_Earth, jeod::De4xxBase::De4xx_Ephem_EMbary, jeod::De4xxBase::De4xx_Ephem_Moon, jeod::De4xxBase::De4xx_Ephem_SSbary, jeod::De4xxEphemItem::Deselected, jeod::De4xxEphemItem::enabled_item, file, jeod::De4xxFile::file_spec, jeod::De4xxEphemItem::frame, jeod::De4xxFileSpec::get_model_number(), jeod::EphemeridesMessages::inconsistent_setup, jeod::De4xxEphemItem::item, item_data, jeod::De4xxEphemItem::name, jeod::De4xxBase::number_trans_points(), root_item, and jeod::De4xxEphemItem::status.

8.2.3.8 void jeod::De4xxEphemeris::ephemer_initialize (EphemeridesManager & ephemer_manager) [override], [virtual]

Complete the initialization process.

This method should be called after all other ephemeris models have completed their basic initialization and after all planets have registered themselves with the ephemeris manager.

Parameters

<code>in, out</code>	<code>ephem_manager</code>	Ephemerides manager
----------------------	----------------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Definition at line 494 of file `de4xx_ephem.cc`.

References `active`, `jeod::De4xxEphemItem::Deselected`, `file`, `jeod::De4xxFile::file_spec`, `jeod::De4xxEphemItem::frame`, `jeod::De4xxFileSpec::get_model_number()`, `jeod::EphemerisItem::get_target_frame()`, `jeod::De4xxEphemItem::item`, `item_data`, `jeod::De4xxBase::number_jeod_items()`, and `jeod::De4xxEphemItem::status`.

8.2.3.9 void jeod::De4xxEphemeris::ephem_update (void) [override],[virtual]

Update ephemerides for subscribed items.

Implements [jeod::EphemerisInterface](#).

Definition at line 831 of file `de4xx_ephem.cc`.

References `jeod::De4xxEphemItem::Active`, `active`, `jeod::De4xxFileHeader::be_em_dist_ratio`, `jeod::De4xxFileHeader::bm_em_dist_ratio`, `body_to_file_idx`, `jeod::De4xxBase::De4xx_Ephem_Earth`, `jeod::De4xxBase::De4xx_Ephem_EMbary`, `jeod::De4xxBase::De4xx_Ephem_LLibration`, `jeod::De4xxBase::De4xx_Ephem_Moon`, `jeod::De4xxBase::De4xx_Ephem_Sun`, `jeod::De4xxBase::De4xx_File_LLibration`, `jeod::De4xxEphemItem::enabled_item`, `file`, `force_update`, `jeod::De4xxFile::header`, `jeod::De4xxEphemItem::item`, `jeod::De4xxFile::item`, `item_data`, `lunar_orientation`, `nactive_items`, `points`, `root_item`, `jeod::De4xxFileItem::state`, `time_dyn`, `time_tt`, `jeod::EphemerisPoint::update()`, `jeod::EphemerisZXZOrientation::update()`, `jeod::De4xxFile::update()`, `jeod::EphemerisPoint::update_scaled()`, and `update_time`.

8.2.3.10 const De4xxFileHeader& jeod::De4xxEphemeris::get_header_data () [inline]

Definition at line 268 of file `de4xx_ephem.hh`.

References `file`, and `jeod::De4xxFile::header`.

8.2.3.11 uint32_t jeod::De4xxEphemeris::get_model_number () [inline]

Get Ephemeris model number.

This number is used to specify the de file to use the pathname is of the form `PWD/build/de4xx_lib/libde<denum-ln>.so`

Definition at line 264 of file `de4xx_ephem.hh`.

References `file`, `jeod::De4xxFile::file_spec`, and `jeod::De4xxFileSpec::get_model_number()`.

8.2.3.12 const char * jeod::De4xxEphemeris::get_name (void) const [override],[virtual]

Return model name.

Returns

Name

Implements [jeod::EphemerisInterface](#).

Definition at line 296 of file `de4xx_ephem.cc`.

References `ident`.

8.2.3.13 void jeod::De4xxEphemeris::initialize_file (void) [private]

Initialize the [De4xxEphemeris](#) file.

Definition at line 384 of file de4xx_ephem.cc.

References jeod::De4xxBase::De4xx_Const_DENUM, jeod::De4xxBase::De4xx_Const_LENUM, jeod::Ephemeris-DataSetMeta::de_constants, file, ident, jeod::De4xxFile::initialize(), jeod::De4xxFile::io, jeod::De4xxFileIO::meta-Data, and time_tt.

Referenced by initialize_model().

8.2.3.14 void jeod::De4xxEphemeris::initialize_items (EphemeridesManager & *ephem_manager*) [private]

Initialize the [De4xxEphemeris](#) item data.

Parameters

in, out	<i>ephem_manager</i>	Ephemerides manager
---------	----------------------	---------------------

Definition at line 419 of file de4xx_ephem.cc.

References jeod::EphemeridesManager::add_ephem_item(), jeod::EphemeridesManager::add_integ_frame(), jeod::De4xxBase::De4xx_Ephem_Earth, jeod::De4xxBase::De4xx_Ephem_EMbary, jeod::De4xxBase::De4xx_Ephem_LLibration, jeod::De4xxBase::De4xx_Ephem_Moon, jeod::De4xxBase::De4xx_Ephem_SSbary, jeod::De4xxEphemItem::Deselected, jeod::EphemerisItem::disable(), earth_moon_barycenter_frame, file, jeod::De4xxFile::file_spec, jeod::De4xxFileSpec::get_model_number(), jeod::De4xxEphemItem::Inactive, jeod::EphemeridesMessages::inconsistent_setup, jeod::De4xxEphemItem::item, item_data, lunar_orientation, jeod::De4xxBase::number_jeod_items(), jeod::De4xxBase::number_trans_points(), points, selected_items, solar_system_barycenter_frame, and jeod::De4xxEphemItem::status.

Referenced by initialize_model().

8.2.3.15 void jeod::De4xxEphemeris::initialize_model (const TimeManager & *time_manager*, DynManager & *dyn_manager*, const std::string & *time_type* = "TT")

Initialize the [De4xxEphemeris](#) model.

Parameters

in	<i>time_manager</i>	Time manager
in, out	<i>dyn_manager</i>	Dynamics manager
in	<i>time_type</i>	time type

Definition at line 50 of file de4xx_ephem_dynmanager.cc.

8.2.3.16 void jeod::De4xxEphemeris::initialize_model (const TimeManager & *time_manager*, EphemeridesManager & *ephem_manager*, const std::string & *time_type* = "TT")

Initialize the [De4xxEphemeris](#) model.

This method is called before the planets have been registered with the reference frame manager, so we don't know whether the ephemeris items should be enabled or disabled.

Parameters

in	<i>time_manager</i>	Time manager
in, out	<i>ephem_manager</i>	Ephemerides manager

<i>in</i>	<i>time_type</i>	optional "tt" "tdb" "tt" default manager
-----------	------------------	--

Definition at line 314 of file de4xx_ephem.cc.

References active, jeod::EphemeridesManager::add_ephemeris(), initialize_file(), initialize_items(), and initialize_time().

8.2.3.17 void jeod::De4xxEphemeris::initialize_time (const TimeManager & *time_manager*, const std::string & *time_type*)
[private]

Initialize [De4xxEphemeris](#) timing.

Parameters

<i>in</i>	<i>time_manager</i>	Time manager
<i>in</i>	<i>time_type</i>	time type

Definition at line 345 of file de4xx_ephem.cc.

References jeod::EphemeridesMessages::inconsistent_setup, time_dyn, and time_tt.

Referenced by initialize_model().

8.2.3.18 De4xxEphemeris& jeod::De4xxEphemeris::operator= (const De4xxEphemeris &) [private]

Not implemented.

8.2.3.19 void jeod::De4xxEphemeris::propagate_lunar_rnp (void)

Propagate the lunar orientation to the current time.

Definition at line 933 of file de4xx_ephem.cc.

References jeod::De4xxEphemItem::Active, active, jeod::De4xxBase::De4xx_Ephem_LLibration, item_data, lunar_orientation, jeod::EphemerisZXZOrientation::propagate(), and time_dyn.

8.2.3.20 void jeod::De4xxEphemeris::set_model_number (int *denum_in*) [inline]

Set ephemeris model number.

This number is used to specify the de file to use the pathname is of the form PWD/build/de4xx_lib/libde<denum-ln>.so

Definition at line 255 of file de4xx_ephem.hh.

References file, jeod::De4xxFile::file_spec, and jeod::De4xxFileSpec::set_model_number().

8.2.3.21 void jeod::De4xxEphemeris::shutdown (void)

Free resources allocated by the [De4xxEphemeris](#) model.

Definition at line 234 of file de4xx_ephem.cc.

References file, ident, and jeod::De4xxFile::shutdown().

Referenced by ~De4xxEphemeris().

8.2.3.22 bool jeod::De4xxEphemeris::time_is_in_range (void) const

Check whether the specified time is represented in the JPL ephemeris file.

Assumptions and Limitations

- Ephemeris file is open for input
- Ephemeris file is blocked per value set in the ephemeris_file structure

Returns

True if time is in file

Definition at line 921 of file de4xx_ephem.cc.

References file, jeod::De4xxFile::time_is_in_range(), and time_tt.

8.2.3.23 `double jeod::De4xxEphemeris::timestamp (void) const` `[override], [virtual]`

Return time of last update.

Returns

Timestamp

Units: day

Implements [jeod::EphemerisInterface](#).

Definition at line 283 of file de4xx_ephem.cc.

References update_time.

8.2.4 Friends And Related Function Documentation

8.2.4.1 `void init_attrjeod__De4xxEphemeris ()` `[friend]`

8.2.4.2 `friend class InputProcessor` `[friend]`

Definition at line 198 of file de4xx_ephem.hh.

8.2.5 Field Documentation

8.2.5.1 `bool jeod::De4xxEphemeris::active`

Is the model active? This is set to true by the constructor.

Setting this flag to false prior to initialization time will result in the model never doing anything. Setting this flag to false after the model has been active for some time is not supported. `trick_units(-)`

Definition at line 282 of file de4xx_ephem.hh.

Referenced by `activate()`, `deactivate()`, `ephem_activate()`, `ephem_build_tree()`, `ephem_initialize()`, `ephem_update()`, `initialize_model()`, and `propagate_lunar_rnp()`.

8.2.5.2 `int* jeod::De4xxEphemeris::body_to_file_idx` `[protected]`

Mapping from De4xxEphemBodies numbers to De4xxFileBodies numbers.

`trick_units(-)`

Definition at line 376 of file de4xx_ephem.hh.

Referenced by `De4xxEphemeris()`, `ephem_activate()`, `ephem_update()`, and `~De4xxEphemeris()`.

8.2.5.3 EphemerisRefFrame jeod::De4xxEphemeris::earth_moon_barycenter_frame [protected]

Earth-Moon barycenter reference frame.

trick_units(-)

Definition at line 351 of file de4xx_ephem.hh.

Referenced by De4xxEphemeris(), and initialize_items().

8.2.5.4 De4xxFile jeod::De4xxEphemeris::file [protected]

The ephemeris file model.

The items of interest to the typical user are the data members file.file_spec.ephem_file_name and file.file_spec.denum. The former specifies the name of the file while the latter serves as a sanity check that the right file is being read.trick_units(-)

Definition at line 310 of file de4xx_ephem.hh.

Referenced by activate_nodes(), determine_root_node(), ephemer_activate(), ephemer_build_tree(), ephemer_initialize(), ephemer_update(), get_header_data(), get_model_number(), initialize_file(), initialize_items(), set_model_number(), shutdown(), and time_is_in_range().

8.2.5.5 bool jeod::De4xxEphemeris::force_update [protected]

Is an update needed even if the time hasn't changed?

trick_units(-)

Definition at line 315 of file de4xx_ephem.hh.

Referenced by ephemer_activate(), and ephemer_update().

8.2.5.6 char* jeod::De4xxEphemeris::ident [protected]

Identifier for this model, computed from the supplied file.

trick_units(-)

Definition at line 331 of file de4xx_ephem.hh.

Referenced by get_name(), initialize_file(), and shutdown().

8.2.5.7 De4xxEphemItem* jeod::De4xxEphemeris::item_data [protected]

Data pertaining to the points for which translational states are calculated.

trick_units(-)

Definition at line 326 of file de4xx_ephem.hh.

Referenced by activate_em_nodes(), activate_nodes(), De4xxEphemeris(), determine_root_node(), ephemer_activate(), ephemer_build_tree(), ephemer_initialize(), ephemer_update(), initialize_items(), propagate_lunar_rnp(), and ~De4xxEphemeris().

8.2.5.8 EphemerisZXZOrientation jeod::De4xxEphemeris::lunar_orientation [protected]

Lunar orientation.

trick_units(-)

Definition at line 346 of file de4xx_ephem.hh.

Referenced by De4xxEphemeris(), ephemeris_update(), initialize_items(), and propagate_lunar_rnp().

8.2.5.9 unsigned int jeod::De4xxEphemeris::nactive_items [protected]

Number of items that are currently active.

trick_units(–)

Definition at line 320 of file de4xx_ephem.hh.

Referenced by activate_em_nodes(), activate_nodes(), determine_root_node(), ephemeris_activate(), and ephemeris_update().

8.2.5.10 EphemerisPoint* jeod::De4xxEphemeris::points [protected]

The planets and barycenter points, in De4xxEphemBodies FileBodies order.

trick_units(–)

Definition at line 341 of file de4xx_ephem.hh.

Referenced by De4xxEphemeris(), ephemeris_update(), initialize_items(), and ~De4xxEphemeris().

8.2.5.11 De4xxEphemItem* jeod::De4xxEphemeris::root_item [protected]

The root point in the reference frame tree.

trick_units(–)

Definition at line 361 of file de4xx_ephem.hh.

Referenced by determine_root_node(), ephemeris_build_tree(), and ephemeris_update().

8.2.5.12 bool* jeod::De4xxEphemeris::selected_items

Used at initialization time only to selectively enable/disable portions of the model.

The constructor initializes all elements of this array to true. Users can set selected elements to false to disable the corresponding ephemeris items. The intent is to enable the use of multiple ephemeris models. Typical users of the model can leave this member as-is. NOTE: while the container is of length 16, Nutations and lunar librations are not currently supported by JEODtrick_units(–)

Definition at line 294 of file de4xx_ephem.hh.

Referenced by De4xxEphemeris(), initialize_items(), and ~De4xxEphemeris().

8.2.5.13 EphemerisRefFrame jeod::De4xxEphemeris::solar_system_barycenter_frame [protected]

Solar system barycenter reference frame.

trick_units(–)

Definition at line 356 of file de4xx_ephem.hh.

Referenced by De4xxEphemeris(), and initialize_items().

8.2.5.14 const TimeDyn* jeod::De4xxEphemeris::time_dyn [protected]

The source of dynamic time information.

trick_units(–)

Definition at line 371 of file de4xx_ephem.hh.

Referenced by `ephem_update()`, `initialize_time()`, and `propagate_lunar_rnp()`.

8.2.5.15 `const TimeStandard* jeod::De4xxEphemeris::time_tt` `[protected]`

The source of ephemeris time information.

`trick_units(-)`

Definition at line 366 of file `de4xx_ephem.hh`.

Referenced by `ephem_update()`, `initialize_file()`, `initialize_time()`, and `time_is_in_range()`.

8.2.5.16 `double jeod::De4xxEphemeris::update_time` `[protected]`

Time of last update, dynamic time seconds.

`trick_units(s)`

Definition at line 336 of file `de4xx_ephem.hh`.

Referenced by `ephem_update()`, and `timestamp()`.

The documentation for this class was generated from the following files:

- [de4xx_ephem.hh](#)
- [de4xx_ephem.cc](#)
- [de4xx_ephem_dynmanager.cc](#)

8.3 `jeod::De4xxEphemItem` Class Reference

Describes a point modeled in a DE4xx ephemeris file.

```
#include <de4xx_ephem.hh>
```

Public Types

- enum `Status` {
`Deselected` = 0, `Inactive` = 1, `IsRoot` = 2, `InTree` = 3,
`Active` = 4 }

Enumerates the status values of a `De4xxEphemItem`.

Public Member Functions

- `De4xxEphemItem` (void)
`De4xxEphemItem` default constructor.
- `~De4xxEphemItem` (void)
`De4xxEphemItem` destructor.

Protected Attributes

- `EphemerisItem * item`
The ephemeris item for this item from this model.
- `EphemerisItem * enabled_item`
The enabled ephemeris item for this item, not necessarily from this model.
- `EphemerisRefFrame * frame`

The reference frame whose state is set by this item.

- const char * [name](#)

Item name; used for reporting errors.

- [Status status](#)

The status for this item.

- unsigned int [index](#)

The node index number, per the De4xxEphemBodies numbering scheme.

Private Member Functions

- [De4xxEphemItem](#) (const [De4xxEphemItem](#) &)

Not implemented.

- [De4xxEphemItem](#) & [operator=](#) (const [De4xxEphemItem](#) &)

Not implemented.

Friends

- class [InputProcessor](#)
- class [De4xxEphemeris](#)
- void [init_attrjeod__De4xxEphemItem](#) ()

8.3.1 Detailed Description

Describes a point modeled in a DE4xx ephemeris file.

This class is only used inside the [De4xxEphemeris](#) class as the type of the protected item_data data member.

Definition at line 97 of file de4xx_ephem.hh.

8.3.2 Member Enumeration Documentation

8.3.2.1 enum jeod::De4xxEphemItem::Status

Enumerates the status values of a De4xEphemItem.

Enumerator

Deselected The item is marked as deselected or the corresponding reference frame is not present in the simulation. The corresponding ephemeris item is permanently disabled under such circumstances.

Inactive The item has not been deselected and the corresponding reference frame is present but is inactive.

IsRoot The item has not been deselected and the corresponding reference frame is present and active. However, the item in question is the root of the reference frame tree and hence its state is the trivial state.

InTree The item has not been deselected and the corresponding reference frame is present and active. However, the ephemeris item that updates this frame is not a part of this model.

Active The item has not been deselected, the corresponding reference frame is present and active, and the ephemeris item that updates this frame belongs to this model.

Definition at line 109 of file de4xx_ephem.hh.

8.3.3 Constructor & Destructor Documentation

8.3.3.1 `jeod::De4xxEphemItem::De4xxEphemItem (void)`

[De4xxEphemItem](#) default constructor.

Definition at line 92 of file `de4xx_ephem.cc`.

8.3.3.2 `jeod::De4xxEphemItem::~~De4xxEphemItem (void)`

[De4xxEphemItem](#) destructor.

Definition at line 109 of file `de4xx_ephem.cc`.

8.3.3.3 `jeod::De4xxEphemItem::De4xxEphemItem (const De4xxEphemItem &)` `[private]`

Not implemented.

8.3.4 Member Function Documentation

8.3.4.1 `De4xxEphemItem& jeod::De4xxEphemItem::operator= (const De4xxEphemItem &)` `[private]`

Not implemented.

8.3.5 Friends And Related Function Documentation

8.3.5.1 `friend class De4xxEphemeris` `[friend]`

Definition at line 100 of file `de4xx_ephem.hh`.

8.3.5.2 `void init_attrjeod__De4xxEphemItem ()` `[friend]`

8.3.5.3 `friend class InputProcessor` `[friend]`

Definition at line 98 of file `de4xx_ephem.hh`.

8.3.6 Field Documentation

8.3.6.1 `EphemerisItem* jeod::De4xxEphemItem::enabled_item` `[protected]`

The enabled ephemeris item for this item, not necessarily from this model.

`trick_units(-)`

Definition at line 153 of file `de4xx_ephem.hh`.

Referenced by `jeod::De4xxEphemeris::activate_em_nodes()`, `jeod::De4xxEphemeris::activate_nodes()`, `jeod::De4xxEphemeris::determine_root_node()`, `jeod::De4xxEphemeris::ephem_build_tree()`, and `jeod::De4xxEphemeris::ephem_update()`.

8.3.6.2 `EphemerisRefFrame* jeod::De4xxEphemItem::frame` `[protected]`

The reference frame whose state is set by this item.

`trick_units(-)`

Definition at line 158 of file de4xx_ephem.hh.

Referenced by jeod::De4xxEphemeris::ephem_build_tree(), and jeod::De4xxEphemeris::ephem_initialize().

8.3.6.3 unsigned int jeod::De4xxEphemItem::index [protected]

The node index number, per the De4xxEphemBodies numbering scheme.

trick_units(-)

Definition at line 173 of file de4xx_ephem.hh.

Referenced by jeod::De4xxEphemeris::De4xxEphemeris().

8.3.6.4 EphemerisItem* jeod::De4xxEphemItem::item [protected]

The ephemeris item for this item from this model.

trick_units(-)

Definition at line 147 of file de4xx_ephem.hh.

Referenced by jeod::De4xxEphemeris::activate_em_nodes(), jeod::De4xxEphemeris::activate_nodes(), jeod::De4xxEphemeris::De4xxEphemeris(), jeod::De4xxEphemeris::determine_root_node(), jeod::De4xxEphemeris::ephem_build_tree(), jeod::De4xxEphemeris::ephem_initialize(), jeod::De4xxEphemeris::ephem_update(), and jeod::De4xxEphemeris::initialize_items().

8.3.6.5 const char* jeod::De4xxEphemItem::name [protected]

Item name; used for reporting errors.

trick_units(-)

Definition at line 163 of file de4xx_ephem.hh.

Referenced by jeod::De4xxEphemeris::activate_em_nodes(), jeod::De4xxEphemeris::De4xxEphemeris(), and jeod::De4xxEphemeris::ephem_build_tree().

8.3.6.6 Status jeod::De4xxEphemItem::status [protected]

The status for this item.

trick_units(-)

Definition at line 168 of file de4xx_ephem.hh.

Referenced by jeod::De4xxEphemeris::activate_em_nodes(), jeod::De4xxEphemeris::activate_nodes(), jeod::De4xxEphemeris::determine_root_node(), jeod::De4xxEphemeris::ephem_activate(), jeod::De4xxEphemeris::ephem_build_tree(), jeod::De4xxEphemeris::ephem_initialize(), and jeod::De4xxEphemeris::initialize_items().

The documentation for this class was generated from the following files:

- [de4xx_ephem.hh](#)
- [de4xx_ephem.cc](#)

8.4 jeod::De4xxFile Class Reference

Provides the ability to read and interpret a DE4xx ephemeris file.

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFile](#) (void)
Construct the JPL ephemeris file.
- [~De4xxFile](#) (void)
Destroy the JPL ephemeris file.
- void [pre_initialize](#) (void)
Pre-initialize a DE4xxFile instance.
- void [initialize](#) (double epoch_time, double del_day, double time_offset, double init_time)
Initialize a DE4xxFile instance.
- bool [time_is_in_range](#) (double time) const
Check whether the specified time is represented in the JPL ephemeris file.
- void [update](#) (double time)
Calculate the position and velocity states of selected planetary bodies at some point in time.
- void [shutdown](#) ()
Shutdown the JPL ephemeris file.

Data Fields

- [De4xxFileSpec](#) file_spec
File specification.
- [De4xxFileHeader](#) header
File header.
- [De4xxFileItem](#) * item
Item data.
- [De4xxFileIO](#) io
File descriptor.
- [De4xxFileRefTime](#) ref_time
Reference time.
- [De4xxFileCoef](#) coef
Chebyshev coeffs.
- [De4xxFileRestart](#) restart
Restart handler.
- double [update_time](#)
Time of last update.
- double [vm_usage](#)
trick_units(-)
- double [resident_set](#)
trick_units(-)
- bool [logMemoryStats](#)
trick_units(-)

Private Member Functions

- void [open](#) (void)
Open the JPL ephemeris file.
- void [reopen](#) (void)
Open the JPL ephemeris file on restart.
- void [close](#) (void)
Close the JPL ephemeris file.

- void [interpolate](#) (double time, double fblk)
Calculate the position and velocity states of selected planetary bodies at some point in time.
- [De4xxFile](#) (const [De4xxFile](#) &)
Not implemented.
- [De4xxFile](#) & [operator=](#) (const [De4xxFile](#) &)
Not implemented.
- void [capture_mem_stats](#) ()

Friends

- class [InputProcessor](#)
- class [De4xxFileRestart](#)
- void [init_attrjeod__De4xxFile](#) ()

8.4.1 Detailed Description

Provides the ability to read and interpret a DE4xx ephemeris file.

Definition at line 617 of file `de4xx_file.hh`.

8.4.2 Constructor & Destructor Documentation

8.4.2.1 `jeod::De4xxFile::De4xxFile (void)`

Construct the JPL ephemeris file.

Definition at line 252 of file `de4xx_file.cc`.

References `jeod::De4xxBase::De4xx_File_ENutation`, `jeod::De4xxBase::De4xx_File_LLibration`, `jeod::De4xxBase::De4xx_File_MaxEntries`, `jeod::De4xxBase::De4xx_File_tt_tdb`, `item`, `jeod::De4xxFileItem::nitems`, `jeod::De4xxFileItem::pscale`, and `restart`.

8.4.2.2 `jeod::De4xxFile::~~De4xxFile (void)`

Destroy the JPL ephemeris file.

Definition at line 292 of file `de4xx_file.cc`.

References `close()`, `item`, and `restart`.

8.4.2.3 `jeod::De4xxFile::De4xxFile (const De4xxFile &) [private]`

Not implemented.

8.4.3 Member Function Documentation

8.4.3.1 `void jeod::De4xxFile::capture_mem_stats () [private]`

Definition at line 532 of file `de4xx_file.cc`.

References `logMemoryStats`, `jeod::process_mem_usage()`, `resident_set`, and `vm_usage`.

8.4.3.2 void jeod::De4xxFile::close (void) [private]

Close the JPL ephemeris file.

Assumptions and Limitations

- Ephemeris file is open for input
- Errors are fatal

Definition at line 433 of file de4xx_file.cc.

References jeod::De4xxFileCoef::chebyderiv, jeod::De4xxFileCoef::chebypoly, coef, jeod::De4xxFileIO::file, jeod::EphemeridesMessages::file_error, io, and jeod::De4xxFileIO::metaData.

Referenced by shutdown(), and ~De4xxFile().

8.4.3.3 void jeod::De4xxFile::initialize (double epoch_time, double del_day, double time_offset, double init_time)

Initialize a DE4xxFile instance.

Parameters

in	<i>epoch_time</i>	Julian date Units: day
in	<i>del_day</i>	Days from epoch Units: day
in	<i>time_offset</i>	Terrestrial Time offset Units: s
in	<i>init_time</i>	Seconds from epoch Units: s

Definition at line 178 of file de4xx_file_init.cc.

References jeod::De4xxFileHeader::au, jeod::De4xxFileHeader::b1_em_dist_ratio, jeod::De4xxFileHeader::be_em_dist_ratio, jeod::De4xxFileRefTime::block_no, jeod::De4xxFileHeader::bm_em_dist_ratio, jeod::De4xxFileCoef::chebyderiv, jeod::De4xxFileCoef::chebypoly, coef, jeod::De4xxBase::De4xx_Const_AU, jeod::De4xxBase::De4xx_Const_CLIGHT, jeod::De4xxBase::De4xx_Const_EMERAT, jeod::De4xxBase::De4xx_Const_GM1, jeod::De4xxBase::De4xx_Const_GM2, jeod::De4xxBase::De4xx_Const_GM4, jeod::De4xxBase::De4xx_Const_GM5, jeod::De4xxBase::De4xx_Const_GM6, jeod::De4xxBase::De4xx_Const_GM7, jeod::De4xxBase::De4xx_Const_GM8, jeod::De4xxBase::De4xx_Const_GM9, jeod::De4xxBase::De4xx_Const_GMB, jeod::De4xxBase::De4xx_Const_GMS, jeod::De4xxBase::De4xx_Ephem_Earth, jeod::De4xxBase::De4xx_Ephem_EMBary, jeod::De4xxBase::De4xx_Ephem_Jupiter, jeod::De4xxBase::De4xx_Ephem_Mars, jeod::De4xxBase::De4xx_Ephem_Mercury, jeod::De4xxBase::De4xx_Ephem_Moon, jeod::De4xxBase::De4xx_Ephem_Neptune, jeod::De4xxBase::De4xx_Ephem_Pluto, jeod::De4xxBase::De4xx_Ephem_Saturn, jeod::De4xxBase::De4xx_Ephem_Sun, jeod::De4xxBase::De4xx_Ephem_Uranus, jeod::De4xxBase::De4xx_Ephem_Venus, jeod::EphemerisDataSetMeta::de_constants, jeod::EphemerisDataSetMeta::delta_epoch, jeod::De4xxFileSpec::denum, jeod::De4xxFileHeader::e1_em_dist_ratio, jeod::De4xxFileHeader::em_mass_ratio, jeod::De4xxFileRefTime::epoch_date, jeod::De4xxFileRefTime::fdate, file_spec, jeod::De4xxFileHeader::gmbody, header, jeod::De4xxFileRefTime::init_time, io, jeod::l1_point(), jeod::De4xxFileIO::max_terms, jeod::De4xxFileIO::metaData, jeod::De4xxBase::number_grav_models(), pre_initialize(), ref_time, jeod::De4xxFileIO::segmentData, jeod::EphemerisDataSegmentMeta::start_epoch, jeod::EphemeridesMessages::time_not_in_range, jeod::De4xxFileIO::total_num_recs, update_time, and jeod::De4xxFileHeader::vlight.

Referenced by jeod::De4xxEphemeris::initialize_file().

8.4.3.4 void jeod::De4xxFile::interpolate (double time, double fblk) [private]

Calculate the position and velocity states of selected planetary bodies at some point in time.

Parameters

<i>in</i>	<i>time</i>	Time since reference Units: s
<i>in</i>	<i>fblk</i>	Fractional block

Definition at line 260 of file `de4xx_file_update.cc`.

References `jeod::De4xxFileItem::active`, `jeod::De4xxFileCoef::chebyderiv`, `jeod::De4xxFileCoef::chebypoly`, `jeod::De4xxFileCoef::chebyterms`, `jeod::De4xxFileCoef::chebyx`, `jeod::De4xxFileCoef::coef`, `coef`, `jeod::EphemerisDataSetMeta::delta_epoch`, `io`, `item`, `jeod::De4xxFileItem::item_idx`, `itemData`, `jeod::De4xxFileIO::itemData`, `jeod::De4xxFileIO::metaData`, `jeod::De4xxFileItem::nitems`, `jeod::EphemerisDataItemMeta::npoly`, `jeod::EphemerisDataItemMeta::nterms`, `jeod::EphemerisDataSetMeta::number_file_items`, `jeod::EphemerisDataItemMeta::offset`, `jeod::De4xxFileItem::pscale`, `jeod::De4xxFileItem::state`, and `jeod::De4xxFileItem::update_time`.

Referenced by `update()`.

8.4.3.5 void jeod::De4xxFile::open (void) [private]

Open the JPL ephemeris file.

Assumptions and Limitations

- Errors are fatal

Returns

Void

Definition at line 321 of file `de4xx_file.cc`.

References `jeod::De4xxBase::De4xx_File_MaxEntries`, `jeod::EphemeridesMessages::debug`, `jeod::De4xxFileSpec::ephem_file_dir`, `jeod::De4xxFileSpec::ephem_file_name`, `jeod::De4xxFileIO::file`, `jeod::EphemeridesMessages::file_error`, `file_spec`, `io`, `jeod::De4xxFileIO::itemData`, `jeod::De4xxFileIO::metaData`, `jeod::EphemerisDataSetMeta::number_file_items`, `jeod::De4xxFileSpec::pathname`, and `jeod::De4xxFileIO::segmentData`.

Referenced by `pre_initialize()`.

8.4.3.6 De4xxFile& jeod::De4xxFile::operator= (const De4xxFile &) [private]

Not implemented.

8.4.3.7 void jeod::De4xxFile::pre_initialize (void)

Pre-initialize a `De4xxFile` instance.

Definition at line 71 of file `de4xx_file_init.cc`.

References `jeod::De4xxFileItem::avail`, `jeod::De4xxFileCoef::coef`, `coef`, `jeod::De4xxFileIO::coeffs_segment_starting_addr`, `jeod::De4xxFileIO::current_record_starting_addr`, `jeod::De4xxBase::De4xx_Const_DENUM`, `jeod::De4xxBase::De4xx_File_MaxEntries`, `jeod::EphemerisDataSetMeta::de_constants`, `jeod::De4xxFileSpec::denum`, `jeod::De4xxFileIO::file`, `jeod::EphemeridesMessages::file_error`, `file_spec`, `jeod::EphemeridesMessages::garbage_file`, `jeod::EphemeridesMessages::internal_error`, `io`, `item`, `jeod::De4xxFileItem::item_idx`, `itemData`, `jeod::De4xxFileIO::itemData`, `jeod::De4xxFileIO::max_terms`, `jeod::De4xxFileIO::metaData`, `jeod::EphemerisDataItemMeta::nterms`, `jeod::EphemerisDataSegmentMeta::num_recs`, `jeod::EphemerisDataSetMeta::number_file_items`, `jeod::EphemerisDataSetMeta::number_segments`, `jeod::EphemerisDataItemMeta::offset`, `open()`, `jeod::De4xxFileSpec::pathname`, `jeod::De4xxFileIO::recno`, `jeod::De4xxFileIO::segment_index`, `jeod::De4xxFileIO::segment_recno`, `jeod::De4xxFileIO::segmentData`, `jeod::EphemerisDataSegmentMeta::start_epoch`, `jeod::EphemerisDataSegmentMeta::stop_epoch`, and `jeod::De4xxFileIO::total_num_recs`.

Referenced by `initialize()`, and `reopen()`.

8.4.3.8 void jeod::De4xxFile::reopen (void) [private]

Open the JPL ephemeris file on restart.

Assumptions and Limitations

- File spec has been reloaded.
- Data has been allocated
- Errors are fatal

Definition at line 411 of file de4xx_file.cc.

References jeod::De4xxFileIO::file, io, and pre_initialize().

Referenced by jeod::De4xxFileRestart::simple_restore().

8.4.3.9 void jeod::De4xxFile::shutdown (void)

Shutdown the JPL ephemeris file.

Definition at line 306 of file de4xx_file.cc.

References close().

Referenced by jeod::De4xxEphemeris::shutdown().

8.4.3.10 bool jeod::De4xxFile::time_is_in_range (double time) const

Check whether the specified time is represented in the JPL ephemeris file.

Assumptions and Limitations

- Ephemeris file is open for input
- Ephemeris file is blocked per value set in the ephem_file structure

Returns

True if time is in file

Parameters

in	time	Time since reference Units: s
----	------	----------------------------------

Definition at line 476 of file de4xx_file.cc.

References jeod::De4xxFileRefTime::block_no, jeod::EphemerisDataSetMeta::delta_epoch, jeod::De4xxFileRefTime::init_time, io, jeod::De4xxFileIO::metaData, ref_time, and jeod::De4xxFileIO::total_num_recs.

Referenced by jeod::De4xxEphemeris::time_is_in_range().

8.4.3.11 void jeod::De4xxFile::update (double time)

Calculate the position and velocity states of selected planetary bodies at some point in time.

The EphemeridesState structure embedded in the Ephemerides structure contains an update indicator and state for each body. The state for a body is updated if the body's indicator indicates that a state update is needed.

Body selection – The 'active_bodies' array in the EphemeridesState structure indicates which planets' states are to be updated. The function updates the position and velocity for the selected bodies.

Time specification – Four input variables are available for specifying the time.

- `tt_offset` is the offset between the remaining input times and Terrestrial Time (aka Terrestrial Dynamic Time, or TDT). Set this to zero if the other input times are already expressed in Terrestrial Time.
- For highest precision, set `epoch_time` to the Julian date at midnight of the time point of interest and set either `del_day` or `del_time` to the difference between the time point of interest and the `epoch_time`.
- An alternative that retains full precession is to pass the time at the start of the simulation in `epoch_time` and `del_day` and the time into the simulation in `del_time`. In this approach, `epoch_time` represents the Julian date at the midnight preceding the start of the simulation and `del_day` represents the time between the epoch time and simulation start.
- For ease of use, set `epoch_time` to the Julian date representing the the time point of interest and set both `del_day` and `del_time` to 0.0. Note that this approach has a machine granularity of about 0.2 msec.
- An intermediate alternative is to set the `epoch_time` to the start time of the simulation, `del_day` to zero and `del_time` to the simulation time in seconds. This approach will result in a small temporal bias due to the precision loss in the epoch time.

Outputs – Positions and velocities are expressed in the ICRF coordinate system. The states of the Sun and planets, including Earth-Moon barycenter, are expressed with respect to the solar system barycenter. Lunar states are expressed with respect to the center of the Earth.

NOTA BENE – The states of unselected bodies may or may not be changed.

Assumptions and Limitations

- Assumption 1. Ephemeris file is open.
- Assumption 2. Offset times in `del_day` and `del_time` are small. See description above.
- Assumption 3. The caller will not reference the states of bodies not requested in the `active_bodies` array. The unselected body states are fair game and may or may not be modified by this function.
- Limitation 1. No light speed time-of-travel corrections. Such corrections must be made by the caller if needed.
- Limitation 2. No relativistic time corrections for the difference between Terrestrial and Barycenter Dynamic Time.
- Limitation 3. The states of the sun and the major planets are expressed in ICRF coordinates relative to the Solar System barycenter. The state of the Moon is expressed in ICRF coordinates relative to the center of the Earth.

Parameters

<code>in</code>	<code>time</code>	Time since reference Units: s
-----------------	-------------------	----------------------------------

Definition at line 115 of file `de4xx_file_update.cc`.

References `jeod::De4xxFileItem::active`, `jeod::De4xxFileItem::avail`, `jeod::De4xxFileRefTime::block_no`, `jeod::De4xxFileCoef::coef`, `coef`, `jeod::De4xxFileIO::coeffs_segment_starting_addr`, `jeod::De4xxFileIO::current_record_starting_addr`, `jeod::EphemerisDataSetMeta::delta_epoch`, `jeod::De4xxFileIO::file`, `jeod::EphemeridesMessages::file_error`, `file_spec`, `jeod::De4xxFileRefTime::init_time`, `jeod::EphemeridesMessages::internal_error`, `interpolate()`, `io`, `item`, `jeod::EphemeridesMessages::item_not_in_file`, `jeod::De4xxFileIO::metaData`, `jeod::EphemerisDataSetMeta::ncoeff`, `jeod::EphemerisDataSegmentMeta::num_recs`, `jeod::EphemerisDataSetMeta::number_file_items`, `jeod::EphemerisDataSetMeta::number_segments`, `jeod::De4xxFileSpec::pathname`, `jeod::De4xxFileIO::recno`, `ref_time`, `jeod::De4xxFileIO::segment_index`, `jeod::De4xxFileIO::segment_recno`, `jeod::De4xxFileIO::segmentData`, `jeod::De4xxFileIO::total_num_recs`, and `update_time`.

Referenced by `jeod::De4xxEphemeris::ephem_update()`.

8.4.4 Friends And Related Function Documentation

8.4.4.1 friend class `De4xxFileRestart` [`friend`]

Definition at line 620 of file `de4xx_file.hh`.

8.4.4.2 `void init_attrjeod__De4xxFile () [friend]`

8.4.4.3 `friend class InputProcessor [friend]`

Definition at line 618 of file `de4xx_file.hh`.

8.4.5 Field Documentation

8.4.5.1 `De4xxFileCoef jeod::De4xxFile::coef`

Chebyshev coeffs.

`trick_units(-)`

Definition at line 680 of file `de4xx_file.hh`.

Referenced by `close()`, `initialize()`, `interpolate()`, `pre_initialize()`, and `update()`.

8.4.5.2 `De4xxFileSpec jeod::De4xxFile::file_spec`

File specification.

`trick_units(-)`

Definition at line 655 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxEphemeris::activate_nodes()`, `jeod::De4xxEphemeris::determine_root_node()`, `jeod::De4xxEphemeris::ephem_activate()`, `jeod::De4xxEphemeris::ephem_build_tree()`, `jeod::De4xxEphemeris::ephem_initialize()`, `jeod::De4xxEphemeris::get_model_number()`, `initialize()`, `jeod::De4xxEphemeris::initialize_items()`, `open()`, `pre_initialize()`, `jeod::De4xxEphemeris::set_model_number()`, and `update()`.

8.4.5.3 `De4xxFileHeader jeod::De4xxFile::header`

File header.

`trick_units(-)`

Definition at line 660 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxEphemeris::ephem_update()`, `jeod::De4xxEphemeris::get_header_data()`, and `initialize()`.

8.4.5.4 `De4xxFileIO jeod::De4xxFile::io`

File descriptor.

`trick_units(-)`

Definition at line 670 of file `de4xx_file.hh`.

Referenced by `close()`, `initialize()`, `jeod::De4xxEphemeris::initialize_file()`, `interpolate()`, `open()`, `pre_initialize()`, `reopen()`, `time_is_in_range()`, and `update()`.

8.4.5.5 `De4xxFileItem* jeod::De4xxFile::item`

Item data.

Sized to fit number of entries in most recent DE4xx release `trick_units(-)`

Definition at line 665 of file `de4xx_file.hh`.

Referenced by `De4xxFile()`, `jeod::De4xxEphemeris::ephem_activate()`, `jeod::De4xxEphemeris::ephem_update()`, `interpolate()`, `pre_initialize()`, `update()`, and `~De4xxFile()`.

8.4.5.6 `bool jeod::De4xxFile::logMemoryStats`

`trick_units(-)`

Definition at line 705 of file `de4xx_file.hh`.

Referenced by `capture_mem_stats()`.

8.4.5.7 `De4xxFileRefTime jeod::De4xxFile::ref_time`

Reference time.

`trick_units(-)`

Definition at line 675 of file `de4xx_file.hh`.

Referenced by `initialize()`, `time_is_in_range()`, and `update()`.

8.4.5.8 `double jeod::De4xxFile::resident_set`

`trick_units(-)`

Definition at line 700 of file `de4xx_file.hh`.

Referenced by `capture_mem_stats()`.

8.4.5.9 `De4xxFileRestart jeod::De4xxFile::restart`

Restart handler.

`trick_io(**)`

Definition at line 685 of file `de4xx_file.hh`.

Referenced by `De4xxFile()`, and `~De4xxFile()`.

8.4.5.10 `double jeod::De4xxFile::update_time`

Time of last update.

`trick_units(s)`

Definition at line 690 of file `de4xx_file.hh`.

Referenced by `initialize()`, and `update()`.

8.4.5.11 `double jeod::De4xxFile::vm_usage`

`trick_units(-)`

Definition at line 695 of file `de4xx_file.hh`.

Referenced by `capture_mem_stats()`.

The documentation for this class was generated from the following files:

- [de4xx_file.hh](#)
- [de4xx_file.cc](#)
- [de4xx_file_init.cc](#)

- [de4xx_file_update.cc](#)

8.5 jeod::De4xxFileCoef Class Reference

Contains Chebychev polynomial coefficients and terms.

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFileCoef](#) (void)
Construct a De4xxFileFileCoef object.

Protected Attributes

- `size_t` [chebyterms](#)
No.
- `double` [chebyx](#)
Chebychev x value.
- `double *` [chebypoly](#)
Chebychev polynomial coeffs.
- `double *` [chebyderiv](#)
Derivative of chebypoly.
- `double *` [coef](#)
Current block contents.

Private Member Functions

- [De4xxFileCoef](#) (const [De4xxFileCoef](#) &)
- [De4xxFileCoef](#) & [operator=](#) (const [De4xxFileCoef](#) &)

Friends

- class [InputProcessor](#)
- class [De4xxFile](#)
- void [init_attrjeod__De4xxFileCoef](#) ()

8.5.1 Detailed Description

Contains Chebychev polynomial coefficients and terms.

Definition at line 540 of file [de4xx_file.hh](#).

8.5.2 Constructor & Destructor Documentation

8.5.2.1 `jeod::De4xxFileCoef::De4xxFileCoef (const De4xxFileCoef &)` [private]

8.5.2.2 `jeod::De4xxFileCoef::De4xxFileCoef (void)`

Construct a [De4xxFileFileCoef](#) object.

Definition at line 201 of file [de4xx_file.cc](#).

8.5.3 Member Function Documentation

8.5.3.1 `De4xxFileCoef& jeod::De4xxFileCoef::operator=(const De4xxFileCoef &)` `[private]`

8.5.4 Friends And Related Function Documentation

8.5.4.1 `friend class De4xxFile` `[friend]`

Definition at line 544 of file `de4xx_file.hh`.

8.5.4.2 `void init_attrjeod__De4xxFileCoef()` `[friend]`

8.5.4.3 `friend class InputProcessor` `[friend]`

Definition at line 542 of file `de4xx_file.hh`.

8.5.5 Field Documentation

8.5.5.1 `double* jeod::De4xxFileCoef::chebyderiv` `[protected]`

Derivative of chebypoly.

`trick_units(-)`

Definition at line 568 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::close()`, `jeod::De4xxFile::initialize()`, and `jeod::De4xxFile::interpolate()`.

8.5.5.2 `double* jeod::De4xxFileCoef::chebypoly` `[protected]`

Chebyshev polynomial coeffs.

`trick_units(-)`

Definition at line 563 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::close()`, `jeod::De4xxFile::initialize()`, and `jeod::De4xxFile::interpolate()`.

8.5.5.3 `size_t jeod::De4xxFileCoef::chebyterms` `[protected]`

No.

Chebyshev polynomials termstrick_units(-)

Definition at line 553 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`.

8.5.5.4 `double jeod::De4xxFileCoef::chebyx` `[protected]`

Chebyshev x value.

`trick_units(-)`

Definition at line 558 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`.

8.5.5.5 `double* jeod::De4xxFileCoef::coef` [protected]

Current block contents.

`trick_units(-)` `trick_io(**)`

Definition at line 573 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`, `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

The documentation for this class was generated from the following files:

- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.6 `jeod::De4xxFileHeader` Class Reference

Contains data extracted from the ephemeris file header.

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFileHeader](#) (void)
Construct a [De4xxFileHeader](#) object.
- [~De4xxFileHeader](#) (void)
Destruct a [De4xxFileHeader](#) object.

Data Fields

- double [au](#)
Astronomical unit in meters.
- double [vlight](#)
Speed of light.
- double [em_mass_ratio](#)
Earth: Moon mass ratio.
- double [be_em_dist_ratio](#)
Ratio of Earth-to-barycenter and Earth-to-Moon distances Note: Also equal to the ratio of Moon and Earth+Moon masses.
- double [bm_em_dist_ratio](#)
Ratio of Barycenter-to-Moon and Earth-to-Moon distances Note: Also equal to the ratio of Earth and Earth+Moon masses.
- double [e1_em_dist_ratio](#)
Ratio of Earth to Earth-moon L1 point and Earth-to-Moon distances.
- double [b1_em_dist_ratio](#)
Ratio of Earth-Moon barycenter to L1 point and Earth-to-Moon distances.
- double * [gmbody](#)
Body gravitational constants.

Private Member Functions

- [De4xxFileHeader](#) (const [De4xxFileHeader](#) &)
- [De4xxFileHeader](#) & operator= (const [De4xxFileHeader](#) &)

Friends

- class [InputProcessor](#)
- class [De4xxFile](#)
- void [init_attrjeod__De4xxFileHeader](#) ()

8.6.1 Detailed Description

Contains data extracted from the ephemeris file header.

Definition at line 358 of file `de4xx_file.hh`.

8.6.2 Constructor & Destructor Documentation

8.6.2.1 `jeod::De4xxFileHeader::De4xxFileHeader (const De4xxFileHeader &) [private]`

8.6.2.2 `jeod::De4xxFileHeader::De4xxFileHeader (void)`

Construct a [De4xxFileHeader](#) object.

Definition at line 130 of file `de4xx_file.cc`.

References `gmbody`, and `jeod::De4xxBase::number_grav_models()`.

8.6.2.3 `jeod::De4xxFileHeader::~De4xxFileHeader (void)`

Destruct a [De4xxFileHeader](#) object.

Definition at line 151 of file `de4xx_file.cc`.

References `gmbody`.

8.6.3 Member Function Documentation

8.6.3.1 `De4xxFileHeader& jeod::De4xxFileHeader::operator= (const De4xxFileHeader &) [private]`

8.6.4 Friends And Related Function Documentation

8.6.4.1 `friend class De4xxFile [friend]`

Definition at line 362 of file `de4xx_file.hh`.

8.6.4.2 `void init_attrjeod__De4xxFileHeader () [friend]`

8.6.4.3 `friend class InputProcessor [friend]`

Definition at line 360 of file `de4xx_file.hh`.

8.6.5 Field Documentation

8.6.5.1 `double jeod::De4xxFileHeader::au`

Astronomical unit in meters.

`trick_units(m)`

Definition at line 370 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize().

8.6.5.2 double jeod::De4xxFileHeader::b1_em_dist_ratio

Ratio of Earth-Moon barycenter to L1 point and Earth-to-Moon distances.

trick_units(—)

Definition at line 402 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize().

8.6.5.3 double jeod::De4xxFileHeader::be_em_dist_ratio

Ratio of Earth-to-barycenter and Earth-to-Moon distances Note: Also equal to the ratio of Moon and Earth+Moon masses.

trick_units(—)

Definition at line 386 of file de4xx_file.hh.

Referenced by jeod::De4xxEphemeris::ephem_update(), and jeod::De4xxFile::initialize().

8.6.5.4 double jeod::De4xxFileHeader::bm_em_dist_ratio

Ratio of Barycenter-to-Moon and Earth-to-Moon distances Note: Also equal to the ratio of Earth and Earth+Moon masses.

trick_units(—)

Definition at line 392 of file de4xx_file.hh.

Referenced by jeod::De4xxEphemeris::ephem_update(), and jeod::De4xxFile::initialize().

8.6.5.5 double jeod::De4xxFileHeader::e1_em_dist_ratio

Ratio of Earth to Earth-moon L1 point and Earth-to-Moon distances.

trick_units(—)

Definition at line 397 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize().

8.6.5.6 double jeod::De4xxFileHeader::em_mass_ratio

Earth: Moon mass ratio.

trick_units(—)

Definition at line 380 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize().

8.6.5.7 double* jeod::De4xxFileHeader::gmbody

Body gravitational constants.

trick_units(m3/s2)

Definition at line 407 of file de4xx_file.hh.

Referenced by `De4xxFileHeader()`, `jeod::De4xxFile::initialize()`, and `~De4xxFileHeader()`.

8.6.5.8 double jeod::De4xxFileHeader::vlight

Speed of light.

`trick_units(m/s)`

Definition at line 375 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::initialize()`.

The documentation for this class was generated from the following files:

- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.7 jeod::De4xxFileIO Class Reference

Contains data used directly for reading the ephemeris file.

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFileIO](#) (void)
Construct a [De4xxFileIO](#) object.

Data Fields

- [EphemerisDataSetMeta](#) * [metaData](#)
Metadata (e.g., sizing) regarding the selected DE ephemeris data set.
- [EphemerisDataItemMeta](#) * [itemData](#)
Metadata (e.g., number of terms) regarding each ephemeris item (e.g., Mercury) contained in the JPL data.
- [EphemerisDataSegmentMeta](#) * [segmentData](#)
Metadata (e.g., number of records) regarding each polynomial segment of the JPL data.
- double * [coeffs_segment_starting_addr](#)
Pointer to first value in the segment.
- double * [current_record_starting_addr](#)
Pointer to first value in the record.
- uint32_t [recno](#)
The current record number.
- uint32_t [segment_index](#)
The current segment number.
- uint32_t [segment_recno](#)
The current segment record number.
- uint32_t [total_num_recs](#)
The number of records in the dataset.
- uint32_t [max_terms](#)
The maximum number of Chebychev terms in the file.

Protected Attributes

- void * [file](#)

The dl handle for the ephemeris shared object.

Private Member Functions

- [De4xxFileIO](#) (const [De4xxFileIO](#) &)
- [De4xxFileIO](#) & operator= (const [De4xxFileIO](#) &)

Friends

- class [InputProcessor](#)
- class [De4xxFile](#)
- void [init_attrjeod__De4xxFileIO](#) ()

8.7.1 Detailed Description

Contains data used directly for reading the ephemeris file.

Definition at line 271 of file [de4xx_file.hh](#).

8.7.2 Constructor & Destructor Documentation

8.7.2.1 [jeod::De4xxFileIO::De4xxFileIO](#) (const [De4xxFileIO](#) &) [[private](#)]

8.7.2.2 [jeod::De4xxFileIO::De4xxFileIO](#) (void)

Construct a [De4xxFileIO](#) object.

Definition at line 108 of file [de4xx_file.cc](#).

8.7.3 Member Function Documentation

8.7.3.1 [De4xxFileIO& jeod::De4xxFileIO::operator=](#) (const [De4xxFileIO](#) &) [[private](#)]

8.7.4 Friends And Related Function Documentation

8.7.4.1 friend class [De4xxFile](#) [[friend](#)]

Definition at line 275 of file [de4xx_file.hh](#).

8.7.4.2 void [init_attrjeod__De4xxFileIO](#) () [[friend](#)]

8.7.4.3 friend class [InputProcessor](#) [[friend](#)]

Definition at line 273 of file [de4xx_file.hh](#).

8.7.5 Field Documentation

8.7.5.1 `double* jeod::De4xxFileO::coeffs_segment_starting_addr`

Pointer to first value in the segment.

`trick_units(-) trick_io(**)`

Definition at line 300 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

8.7.5.2 `double* jeod::De4xxFileO::current_record_starting_addr`

Pointer to first value in the record.

`trick_units(-) trick_io(**)`

Definition at line 305 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

8.7.5.3 `void* jeod::De4xxFileO::file` `[protected]`

The dl handle for the ephemeris shared object.

`trick_units(-) trick_io(**)`

Definition at line 337 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::close()`, `jeod::De4xxFile::open()`, `jeod::De4xxFile::pre_initialize()`, `jeod::De4xxFile::reopen()`, and `jeod::De4xxFile::update()`.

8.7.5.4 `EphemerisDataItemMeta* jeod::De4xxFileO::itemData`

Metadata (e.g., number of terms) regarding each ephemeris item (e.g., Mercury) contained in the JPL data.

`trick_units(-) trick_io(**)`

Definition at line 289 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`, `jeod::De4xxFile::open()`, and `jeod::De4xxFile::pre_initialize()`.

8.7.5.5 `uint32_t jeod::De4xxFileO::max_terms`

The maximum number of Chebychev terms in the file.

`trick_units(-)`

Definition at line 331 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::initialize()`, and `jeod::De4xxFile::pre_initialize()`.

8.7.5.6 `EphemerisDataSetMeta* jeod::De4xxFileO::metaData`

Metadata (e.g., sizing) regarding the selected DE ephemeris data set.

`trick_units(-) trick_io(**)`

Definition at line 283 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::close()`, `jeod::De4xxFile::initialize()`, `jeod::De4xxEphemeris::initialize_file()`, `jeod::De4xxFile::interpolate()`, `jeod::De4xxFile::open()`, `jeod::De4xxFile::pre_initialize()`, `jeod::De4xxFile::time_is_in_range()`, and `jeod::De4xxFile::update()`.

8.7.5.7 uint32_t jeod::De4xxFileIO::recno

The current record number.

trick_units(-)

Definition at line 311 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::pre_initialize(), and jeod::De4xxFile::update().

8.7.5.8 uint32_t jeod::De4xxFileIO::segment_index

The current segment number.

trick_units(-)

Definition at line 316 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::pre_initialize(), and jeod::De4xxFile::update().

8.7.5.9 uint32_t jeod::De4xxFileIO::segment_recno

The current segment record number.

trick_units(-)

Definition at line 321 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::pre_initialize(), and jeod::De4xxFile::update().

8.7.5.10 EphemerisDataSegmentMeta* jeod::De4xxFileIO::segmentData

Metadata (e.g., number of records) regarding each polynomial segment of the JPL data.

trick_units(-) trick_io(**)

Definition at line 295 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize(), jeod::De4xxFile::open(), jeod::De4xxFile::pre_initialize(), and jeod::De4xxFile::update().

8.7.5.11 uint32_t jeod::De4xxFileIO::total_num_recs

The number of records in the dataset.

trick_units(-)

Definition at line 326 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize(), jeod::De4xxFile::pre_initialize(), jeod::De4xxFile::time_is_in_range(), and jeod::De4xxFile::update().

The documentation for this class was generated from the following files:

- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.8 jeod::De4xxFileItem Class Reference

Contains data regarding one of the items in a DE ephemeris file.

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFileItem](#) (void)
Construct a [De4xxFileItem](#) object.

Data Fields

- bool [active](#)
Is this item's state to be computed? (external input)
- bool [avail](#)
Is this item represented in the ephemeris file?
- uint32_t [item_idx](#)
trick_units(-)
- int32_t [nitems](#)
Vector size.
- double [pscale](#)
Zeroth derivative scale factor.
- double [update_time](#)
Update time (simulation time)
- double [state](#) [2][3]
State data (zeroth, first derivative)

Private Member Functions

- [De4xxFileItem](#) (const [De4xxFileItem](#) &)
- [De4xxFileItem](#) & [operator=](#) (const [De4xxFileItem](#) &)

Friends

- class [InputProcessor](#)
- class [De4xxFile](#)
- void [init_attrjeod__De4xxFileItem](#) ()

8.8.1 Detailed Description

Contains data regarding one of the items in a DE ephemeris file.

Definition at line 428 of file `de4xx_file.hh`.

8.8.2 Constructor & Destructor Documentation

8.8.2.1 `jeod::De4xxFileItem::De4xxFileItem (const De4xxFileItem &) [private]`

8.8.2.2 `jeod::De4xxFileItem::De4xxFileItem (void)`

Construct a [De4xxFileItem](#) object.

As most ephemeris file items are position vectors in kilometers, this constructor sets the scale to 1000 and the number of items to three.

Definition at line 164 of file `de4xx_file.cc`.

References [state](#).

8.8.3 Member Function Documentation

8.8.3.1 `De4xxFileItem& jeod::De4xxFileItem::operator= (const De4xxFileItem &)` [private]

8.8.4 Friends And Related Function Documentation

8.8.4.1 `friend class De4xxFile` [friend]

Definition at line 432 of file `de4xx_file.hh`.

8.8.4.2 `void init_attrjeod__De4xxFileItem ()` [friend]

8.8.4.3 `friend class InputProcessor` [friend]

Definition at line 430 of file `de4xx_file.hh`.

8.8.5 Field Documentation

8.8.5.1 `bool jeod::De4xxFileItem::active`

Is this item's state to be computed? (external input)

`trick_units(-)`

Definition at line 440 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxEphemeris::ephem_activate()`, `jeod::De4xxFile::interpolate()`, and `jeod::De4xxFile::update()`.

8.8.5.2 `bool jeod::De4xxFileItem::avail`

Is this item represented in the ephemeris file?

`trick_units(-)`

Definition at line 445 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

8.8.5.3 `uint32_t jeod::De4xxFileItem::item_idx`

`trick_units(-)`

Definition at line 448 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`, and `jeod::De4xxFile::pre_initialize()`.

8.8.5.4 `int32_t jeod::De4xxFileItem::nitems`

Vector size.

`trick_units(-)`

Definition at line 453 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::De4xxFile()`, and `jeod::De4xxFile::interpolate()`.

8.8.5.5 double jeod::De4xxFileItem::pscale

Zeroth derivative scale factor.

trick_units(—)

Definition at line 458 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::De4xxFile(), and jeod::De4xxFile::interpolate().

8.8.5.6 double jeod::De4xxFileItem::state[2][3]

State data (zeroth, first derivative)

trick_units(—)

Definition at line 468 of file de4xx_file.hh.

Referenced by De4xxFileItem(), jeod::De4xxEphemeris::ephem_update(), and jeod::De4xxFile::interpolate().

8.8.5.7 double jeod::De4xxFileItem::update_time

Update time (simulation time)

trick_units(s)

Definition at line 463 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::interpolate().

The documentation for this class was generated from the following files:

- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.9 jeod::De4xxFileRefTime Class Reference

Contains timing reference data.

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFileRefTime](#) (void)
Construct a [De4xxFileRefTime](#) object.

Data Fields

- double [epoch_date](#)
Julian date of midnight preceding reference time point.
- double [fdate](#)
Fractional days past epoch date of reference time point.
- double [time_offset](#)
Time offset, Typically, Terrestrial Time offset.
- double [init_time](#)
Initialization time (seconds from reference, typically zero).
- double [block_no](#)
File block number corresponding to reference time.

Private Member Functions

- [De4xxFileRefTime](#) (const [De4xxFileRefTime](#) &)
- [De4xxFileRefTime](#) & operator= (const [De4xxFileRefTime](#) &)

Friends

- class [InputProcessor](#)
- class [De4xxFile](#)
- void [init_attrjeod__De4xxFileRefTime](#) ()

8.9.1 Detailed Description

Contains timing reference data.

Definition at line 488 of file [de4xx_file.hh](#).

8.9.2 Constructor & Destructor Documentation

8.9.2.1 `jeod::De4xxFileRefTime::De4xxFileRefTime (const De4xxFileRefTime &)` `[private]`

8.9.2.2 `jeod::De4xxFileRefTime::De4xxFileRefTime (void)`

Construct a [De4xxFileRefTime](#) object.

Definition at line 185 of file [de4xx_file.cc](#).

8.9.3 Member Function Documentation

8.9.3.1 `De4xxFileRefTime& jeod::De4xxFileRefTime::operator= (const De4xxFileRefTime &)` `[private]`

8.9.4 Friends And Related Function Documentation

8.9.4.1 `friend class De4xxFile` `[friend]`

Definition at line 492 of file [de4xx_file.hh](#).

8.9.4.2 `void init_attrjeod__De4xxFileRefTime ()` `[friend]`

8.9.4.3 `friend class InputProcessor` `[friend]`

Definition at line 490 of file [de4xx_file.hh](#).

8.9.5 Field Documentation

8.9.5.1 `double jeod::De4xxFileRefTime::block_no`

File block number corresponding to reference time.

`trick_units(-)`

Definition at line 520 of file [de4xx_file.hh](#).

Referenced by `jeod::De4xxFile::initialize()`, `jeod::De4xxFile::time_is_in_range()`, and `jeod::De4xxFile::update()`.

8.9.5.2 double jeod::De4xxFileRefTime::epoch_date

Julian date of midnight preceding reference time point.

trick_units(day)

Definition at line 500 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize().

8.9.5.3 double jeod::De4xxFileRefTime::fdate

Fractional days past epoch date of reference time point.

trick_units(day)

Definition at line 505 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize().

8.9.5.4 double jeod::De4xxFileRefTime::init_time

Initialization time (seconds from reference, typically zero).

trick_units(s)

Definition at line 513 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::initialize(), jeod::De4xxFile::time_is_in_range(), and jeod::De4xxFile::update().

8.9.5.5 double jeod::De4xxFileRefTime::time_offset

Time offset, Typically, Terrestrial Time offset.

trick_units(s)

Definition at line 509 of file de4xx_file.hh.

The documentation for this class was generated from the following files:


- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.10 jeod::De4xxFileRestart Class Reference

The FILE pointer in a [De4xxFileIO](#) cannot be restored by Trick.

```
#include <de4xx_file.hh>
```

Inheritance diagram for jeod::De4xxFileRestart:

**Public Member Functions**

- [De4xxFileRestart](#) ([De4xxFile](#) &in)

- Construct a [De4xxFileRestart](#) object.
- [~De4xxFileRestart](#) (void) override
- Destroy a [De4xxFileRestart](#) object.
- void [simple_restore](#) (void) override
- Reopen the [De4xx](#) file for a restart.

Protected Attributes

- [De4xxFile](#) & [de4xx_file](#)
- The [De4xxFile](#) object to be restored.

Private Member Functions

- [De4xxFileRestart](#) (const [De4xxFileRestart](#) &)
- [De4xxFileRestart](#) & [operator=](#) (const [De4xxFileRestart](#) &)

8.10.1 Detailed Description

The FILE pointer in a [De4xxFileIO](#) cannot be restored by Trick.

This class provides that essential restart mechanism.

Definition at line 594 of file [de4xx_file.hh](#).

8.10.2 Constructor & Destructor Documentation

8.10.2.1 `jeod::De4xxFileRestart::De4xxFileRestart (De4xxFile & in) [explicit]`

Construct a [De4xxFileRestart](#) object.

Parameters

<code>in, out</code>	<code>in</code>	The De4xxFile object
----------------------	-----------------	--------------------------------------

Definition at line 219 of file [de4xx_file.cc](#).

8.10.2.2 `jeod::De4xxFileRestart::~~De4xxFileRestart (void) [override]`

Destroy a [De4xxFileRestart](#) object.

Definition at line 231 of file [de4xx_file.cc](#).

8.10.2.3 `jeod::De4xxFileRestart::De4xxFileRestart (const De4xxFileRestart &) [private]`

8.10.3 Member Function Documentation

8.10.3.1 `De4xxFileRestart& jeod::De4xxFileRestart::operator= (const De4xxFileRestart &) [private]`

8.10.3.2 `void jeod::De4xxFileRestart::simple_restore (void) [override]`

Reopen the [De4xx](#) file for a restart.

Definition at line 242 of file [de4xx_file.cc](#).

References [de4xx_file](#), and [jeod::De4xxFile::reopen\(\)](#).

8.10.4 Field Documentation

8.10.4.1 De4xxFile& jeod::De4xxFileRestart::de4xx_file [protected]

The [De4xxFile](#) object to be restored.

trick_io(**)

Definition at line 606 of file [de4xx_file.hh](#).

Referenced by [simple_restore\(\)](#).

The documentation for this class was generated from the following files:

- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.11 jeod::De4xxFileSpec Class Reference

Specifies which file to use (user input initialization-time data).

```
#include <de4xx_file.hh>
```

Public Member Functions

- [De4xxFileSpec](#) (void)
Construct a [De4xxFileSpec](#) object.
- void [set_model_number](#) (int denum_in)
Set ephemeris model number.
- uint32_t [get_model_number](#) ()
Get Ephemeris model number.

Protected Attributes

- uint32_t [denum](#)
Ephemeris model number.
- std::string [ephem_file_dir](#)
Ephemeris file directory.
- std::string [ephem_file_name](#)
Ephemeris file name.
- std::string [pathname](#)
Ephemeris file path name.

Private Member Functions

- [De4xxFileSpec](#) (const [De4xxFileSpec](#) &)
Not implemented.
- [De4xxFileSpec](#) & [operator=](#) (const [De4xxFileSpec](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- class [De4xxFile](#)
- void [init_attrjeod__De4xxFileSpec](#) ()

8.11.1 Detailed Description

Specifies which file to use (user input initialization-time data).

Definition at line 193 of file `de4xx_file.hh`.

8.11.2 Constructor & Destructor Documentation

8.11.2.1 `jeod::De4xxFileSpec::De4xxFileSpec (void)`

Construct a `De4xxFileSpec` object.

Definition at line 87 of file `de4xx_file.cc`.

References `set_model_number()`.

8.11.2.2 `jeod::De4xxFileSpec::De4xxFileSpec (const De4xxFileSpec &) [private]`

Not implemented.

8.11.3 Member Function Documentation

8.11.3.1 `uint32_t jeod::De4xxFileSpec::get_model_number () [inline]`

Get Ephemeris model number.

This number is used to specify the de file to use the pathname is of the form `PWD/build/de4xx_lib/libde<denum-In>.so`

Definition at line 218 of file `de4xx_file.hh`.

References `denum`.

Referenced by `jeod::De4xxEphemeris::activate_nodes()`, `jeod::De4xxEphemeris::determine_root_node()`, `jeod::De4xxEphemeris::ephem_activate()`, `jeod::De4xxEphemeris::ephem_build_tree()`, `jeod::De4xxEphemeris::ephem_initialize()`, `jeod::De4xxEphemeris::get_model_number()`, and `jeod::De4xxEphemeris::initialize_items()`.

8.11.3.2 `De4xxFileSpec& jeod::De4xxFileSpec::operator= (const De4xxFileSpec &) [private]`

Not implemented.

8.11.3.3 `void jeod::De4xxFileSpec::set_model_number (int denum_in)`

Set ephemeris model number.

This number is used to specify the de file to use the pathname is of the form `PWD/build/de4xx_lib/libde<denum-In>.so`

Definition at line 97 of file `de4xx_file.cc`.

References `denum`, `ephem_file_dir`, `ephem_file_name`, and `pathname`.

Referenced by `De4xxFileSpec()`, and `jeod::De4xxEphemeris::set_model_number()`.

8.11.4 Friends And Related Function Documentation

8.11.4.1 `friend class De4xxFile [friend]`

Definition at line 196 of file `de4xx_file.hh`.

8.11.4.2 `void init_attrjeod__De4xxFileSpec () [friend]`

8.11.4.3 `friend class InputProcessor [friend]`

Definition at line 194 of file `de4xx_file.hh`.

8.11.5 Field Documentation

8.11.5.1 `uint32_t jeod::De4xxFileSpec::denum [protected]`

Ephemeris model number.

This must match the DE number in the data file; a sanity check `trick_units(-)`

Definition at line 231 of file `de4xx_file.hh`.

Referenced by `get_model_number()`, `jeod::De4xxFile::initialize()`, `jeod::De4xxFile::pre_initialize()`, and `set_model_number()`.

8.11.5.2 `std::string jeod::De4xxFileSpec::ephem_file_dir [protected]`

Ephemeris file directory.

`trick_units(-)`

Definition at line 236 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::open()`, and `set_model_number()`.

8.11.5.3 `std::string jeod::De4xxFileSpec::ephem_file_name [protected]`

Ephemeris file name.

`trick_units(-)`

Definition at line 241 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::open()`, and `set_model_number()`.

8.11.5.4 `std::string jeod::De4xxFileSpec::pathname [protected]`

Ephemeris file path name.

`trick_io(*o) trick_units(-)`

Definition at line 247 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::open()`, `jeod::De4xxFile::pre_initialize()`, `set_model_number()`, and `jeod::De4xxFile::update()`.

The documentation for this class was generated from the following files:


- [de4xx_file.hh](#)
- [de4xx_file.cc](#)

8.12 jeod::EmptySpaceEphemeris Class Reference

Empty space has one ephemeris point.

```
#include <simple_ephemerides.hh>
```

Inheritance diagram for jeod::EmptySpaceEphemeris:



Public Member Functions

- [EmptySpaceEphemeris](#) (void)
Construct an *EmptySpaceEphemeris* object.
- [~EmptySpaceEphemeris](#) (void) override
Destruct an *EmptySpaceEphemeris* object.
- void [set_name](#) (const char *frame_name) override
Set the name of an *EmptySpaceEphemeris* object.
- void [initialize_model](#) (EphemeridesManager &ephem_manager) override
Initialize an *EmptySpaceEphemeris* object.
- void [ephem_initialize](#) (EphemeridesManager &ephem_manager) override
Initialize an *EmptySpaceEphemeris* object.
- void [ephem_activate](#) (EphemeridesManager &ephem_manager) override
Activate an *EmptySpaceEphemeris* object.
- void [ephem_build_tree](#) (EphemeridesManager &ephem_manager) override
Build the reference frame tree with the central frame as the root.

Protected Attributes

- [EphemerisPoint](#) central_point
The *EphemerisPoint* that represents the center of an empty universe.
- [EphemerisRefFrame](#) central_frame
The sole ephemeris frame for this model.

Private Member Functions

- [EmptySpaceEphemeris](#) (const [EmptySpaceEphemeris](#) &)
Not implemented.
- [EmptySpaceEphemeris](#) & operator= (const [EmptySpaceEphemeris](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EmptySpaceEphemeris](#) ()

8.12.1 Detailed Description

Empty space has one ephemeris point.

Definition at line 203 of file simple_ephemerides.hh.

8.12.2 Constructor & Destructor Documentation

8.12.2.1 jeod::EmptySpaceEphemeris::EmptySpaceEphemeris (void)

Construct an [EmptySpaceEphemeris](#) object.

Definition at line 152 of file simple_ephemerides.cc.

References [central_point](#), [jeod::EphemerisItem::enable\(\)](#), and [jeod::EphemerisItem::set_owner\(\)](#).

8.12.2.2 jeod::EmptySpaceEphemeris::~~EmptySpaceEphemeris (void) [override]

Destruct an [EmptySpaceEphemeris](#) object.

Definition at line 163 of file simple_ephemerides.cc.

8.12.2.3 jeod::EmptySpaceEphemeris::EmptySpaceEphemeris (const EmptySpaceEphemeris &) [private]

Not implemented.

8.12.3 Member Function Documentation

8.12.3.1 void jeod::EmptySpaceEphemeris::ephem_activate (EphemeridesManager & *ephem_manager*) [override], [virtual]

Activate an [EmptySpaceEphemeris](#) object.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 247 of file simple_ephemerides.cc.

8.12.3.2 void jeod::EmptySpaceEphemeris::ephem_build_tree (EphemeridesManager & *ephem_manager*) [override], [virtual]

Build the reference frame tree with the central frame as the root.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 259 of file simple_ephemerides.cc.

References [jeod::SinglePointEphemeris::active](#), and [central_frame](#).

8.12.3.3 void jeod::EmptySpaceEphemeris::ephem_initialize (EphemeridesManager & *ephem_manager*) [override], [virtual]

Initialize an [EmptySpaceEphemeris](#) object.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 224 of file simple_ephemerides.cc.

References [central_point](#), [jeod::SinglePointEphemeris::deactivate\(\)](#), [jeod::EphemerisItem::disable\(\)](#), [jeod::EphemerisItem::get_target_frame\(\)](#), [jeod::SinglePointEphemeris::identifier](#), and [jeod::EphemeridesMessages::inconsistent_setup](#).

8.12.3.4 `void jeod::EmptySpaceEphemeris::initialize_model (EphemeridesManager & ephem_manager)`
`[override],[virtual]`

Initialize an [EmptySpaceEphemeris](#) object.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 204 of file simple_ephemerides.cc.

References [jeod::SinglePointEphemeris::active](#), [jeod::EphemeridesManager::add_ephem_item\(\)](#), [jeod::EphemeridesManager::add_ephemeris\(\)](#), [jeod::EphemeridesManager::add_integ_frame\(\)](#), [central_frame](#), and [central_point](#).

8.12.3.5 `EmptySpaceEphemeris& jeod::EmptySpaceEphemeris::operator= (const EmptySpaceEphemeris &)`
`[private]`

Not implemented.

8.12.3.6 `void jeod::EmptySpaceEphemeris::set_name (const char * new_name)` `[override],[virtual]`

Set the name of an [EmptySpaceEphemeris](#) object.

Parameters

<i>in, out</i>	<i>new_name</i>	Ephemeris name
----------------	-----------------	----------------

Reimplemented from [jeod::SinglePointEphemeris](#).

Definition at line 175 of file simple_ephemerides.cc.

References [central_frame](#), [central_point](#), [jeod::SinglePointEphemeris::set_name\(\)](#), and [jeod::EphemerisItem::set_name\(\)](#).

8.12.4 Friends And Related Function Documentation

8.12.4.1 `void init_attrjeod_EmptySpaceEphemeris ()` `[friend]`

8.12.4.2 `friend class InputProcessor` `[friend]`

Definition at line 205 of file simple_ephemerides.hh.

8.12.5 Field Documentation

8.12.5.1 EphemerisRefFrame jeod::EmptySpaceEphemeris::central_frame [protected]

The sole ephemeris frame for this model.

trick_units(-)

Definition at line 239 of file simple_ephemerides.hh.

Referenced by ephem_build_tree(), initialize_model(), and set_name().

8.12.5.2 EphemerisPoint jeod::EmptySpaceEphemeris::central_point [protected]

The [EphemerisPoint](#) that represents the center of an empty universe.

trick_units(-)

Definition at line 234 of file simple_ephemerides.hh.

Referenced by EmptySpaceEphemeris(), ephem_initialize(), initialize_model(), and set_name().

The documentation for this class was generated from the following files:


- [simple_ephemerides.hh](#)
- [simple_ephemerides.cc](#)

8.13 jeod::EphemeridesManager Class Reference

The [EphemeridesManager](#) class manages the ephemeris models in a simulation.

```
#include <ephem_manager.hh>
```

Inheritance diagram for jeod::EphemeridesManager:



Public Member Functions

- [EphemeridesManager](#) ()
EphemeridesManager default constructor.
- [~EphemeridesManager](#) () override
EphemeridesManager destructor.
- bool [ref_frame_tree_needs_rebuild](#) () const
Query if the reference frame tree needs to be rebuilt.
- void [ephem_note_tree_status_change](#) () override
Denote that the reference frame tree needs to be rebuilt.
- void [add_planet](#) (BasePlanet &planet) override
Add a planet to the planets registry.
- void [add_planet](#) (Planet &planet) override
Add a planet to the registry.
- BasePlanet * [find_base_planet](#) (const char *name) const override

- Find the planet with the given name.*

 - Planet * [find_planet](#) (const char *name) const override
- Find the planet with the given name.*

 - unsigned int [get_num_planets](#) (void) const override
- Return number of registered planets.*

 - void [add_ephemeris](#) (EphemerisInterface &ephem_if) override
- Add an ephemeris model to the list of managed models.*

 - void [clear_added_ephemerides](#) (void) override
- Deactivate any registered ephemeris items and remove them from the list.*

 - void [disable_add_ephemeris](#) (void) override
- Make subsequent calls to add_ephemeris deactivate the specified ephemeris model instead of adding it to the list of managed models.*

 - void [add_ephem_item](#) (EphemerisItem &ephem_item) override
- Add an ephemeris item to the set of ephemeris items known to the ephemerides manager.*

 - EphemerisItem * [find_ephem_item](#) (const char *name) const override
- Find the first registered EphemerisItem with the given name.*

 - EphemerisOrientation * [find_ephem_angle](#) (const char *name) const override
- Find the EphemerisOrientation with the given name.*

 - EphemerisPoint * [find_ephem_point](#) (const char *name) const override
- Find the EphemerisPoint with the given name.*

 - void [add_integ_frame](#) (EphemerisRefFrame &ref_frame) override
- Add a frame to the reference frame and integration frame lists.*

 - EphemerisRefFrame * [find_integ_frame](#) (const char *name) const override
- Find the integration frame with the given name.*

 - bool [is_integ_frame](#) (const RefFrame &ref_frame) const override
- Determine if supplied frame is an integration frame.*

 - unsigned int [find_integ_frame_index](#) (const EphemerisRefFrame &ref_frame) const override
- Find the index of provided frame in the integration frames vector.*

 - const std::vector
 - < EphemerisRefFrame * > & [get_integ_frames](#) (void) const override
- Get a copy of the vector of integration frames.*

 - void [add_ref_frame](#) (RefFrame &ref_frame) override
- Add a reference frame to the reference frame registry.*

 - void [set_target_frame](#) (RefFrame &ref_frame)
- Set the target-frame reference for the ref-frame and all known EphemlItems with similar target-frame names.*

 - void [initialize_ephemerides](#) (void)
- Initialize the ephemeris models.*

 - void [activate_ephemerides](#) (void)
- Activate ephemeris items based on frame subscription status, activate ephemeris models, and build the reference frame tree.*

 - void [update_ephemerides](#) (void)
- Update each ephemeris model.*

Protected Attributes

- bool [single_ephem_mode](#)

Set via a call to disable_add_ephemeris, typically to allow a simple ephemeris model to be active with all other models made inactive.
- bool [regenerate_ref_frame_tree](#)

Set when the reference frame tree needs to be regenerated.
- double [update_time](#)

Time of last update.

- JeodPointerVector< BasePlanet >
::type [planets](#)

The planets in a simulation, typically defined at the S_define level.

- JeodPointerVector
< [EphemerisInterface](#) >::type [ephemerides](#)

The ephemerides models managed by this [EphemeridesManager](#).

- JeodPointerVector
< [EphemerisItem](#) >::type [ephem_items](#)

The heads of the ephemeris item lists.

- JeodPointerVector
< [EphemerisRefFrame](#) >::type [integ_frames](#)

List of reference frames that are not rotating with respect to the root node of the reference frame tree.

Private Member Functions

- [EphemeridesManager](#) (const [EphemeridesManager](#) &)
Not implemented.
- [EphemeridesManager](#) & operator= (const [EphemeridesManager](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemeridesManager](#) ()

8.13.1 Detailed Description

The [EphemeridesManager](#) class manages the ephemeris models in a simulation.

The primary functions of a [EphemeridesManager](#) are to:

- Maintain lists of planets, ephemeris models, ephemeris items, and integration frames, and to provide lookup methods for these lists.
- Dynamically determine which ephemerides are needed in a simulation.
- Initialize ephemeris models and keep them in sync with the rest of the simulation.

Definition at line 91 of file [ephem_manager.hh](#).

8.13.2 Constructor & Destructor Documentation

8.13.2.1 jeod::EphemeridesManager::EphemeridesManager (void)

[EphemeridesManager](#) default constructor.

Definition at line 59 of file [ephem_manager.cc](#).

References [ephem_items](#), [ephemerides](#), [integ_frames](#), and [planets](#).

8.13.2.2 `jeod::EphemeridesManager::~EphemeridesManager (void) [override]`

[EphemeridesManager](#) destructor.

Definition at line 83 of file `ephem_manager.cc`.

References `ephem_items`, `ephemerides`, `integ_frames`, and `planets`.

8.13.2.3 `jeod::EphemeridesManager::EphemeridesManager (const EphemeridesManager &) [private]`

Not implemented.

8.13.3 Member Function Documentation

8.13.3.1 `void jeod::EphemeridesManager::activate_ephemerides (void)`

Activate ephemeris items based on frame subscription status, activate ephemeris models, and build the reference frame tree.

Definition at line 707 of file `ephem_manager.cc`.

References `jeod::EphemerisItem::disconnect_from_tree()`, `jeod::EphemerisInterface::ephem_activate()`, `jeod::EphemerisInterface::ephem_build_tree()`, `ephem_items`, `ephemerides`, and `regenerate_ref_frame_tree`.

Referenced by `update_ephemerides()`.

8.13.3.2 `void jeod::EphemeridesManager::add_ephem_item (EphemerisItem & ephem_item) [override], [virtual]`

Add an ephemeris item to the set of ephemeris items known to the ephemerides manager.

Each ephemeris model calls this method for each ephemeris item represented by that ephemeris model. The provided item is added to

- The `ephem_items` list if the provided item's name is unique or
- The tail of the list of items with the same name if an item with the provided item's name is already in the `ephem_items` list.

Multiple ephemerides models might represent the same conceptual item. The `ephem_items` list contains only items with unique names. These head items link to other items with the same name via the items' next data members, which form a singly-linked list of commonly-named items.

Assumptions and limitations:

- The item must have a valid name.
- Only one item with a given name can be enabled.

Parameters

<i>ephem_item</i>	Ephemeris item to be added to the registry.
-------------------	---

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 296 of file `ephem_manager.cc`.

References `jeod::EphemerisItem::disable()`, `jeod::EphemeridesMessages::duplicate_entry`, `ephem_items`, `find_ephem_item()`, `jeod::EphemerisItem::get_enabled_item()`, `jeod::EphemerisInterface::get_name()`, `jeod::EphemerisItem::get_name()`, `jeod::EphemerisItem::get_next()`, `jeod::EphemerisItem::get_owner()`, `jeod::EphemeridesMessages::inconsistent_setup`, `jeod::EphemeridesMessages::internal_error`, `jeod::EphemerisItem::is_enabled()`,

jeod::EphemerisItem::set_head(), jeod::EphemerisItem::set_manager(), jeod::EphemerisItem::set_next(), jeod::EphemerisItem::set_target_frame(), jeod::EphemeridesMessages::single_ephem_mode, single_ephem_mode, jeod::EphemerisItem::Translation, and jeod::EphemerisItem::updates_what().

Referenced by jeod::De4xxEphemeris::initialize_items(), jeod::EmptySpaceEphemeris::initialize_model(), and jeod::SinglePlanetEphemeris::initialize_model().

8.13.3.3 void jeod::EphemeridesManager::add_ephemeris (EphemerisInterface & *ephem_if*) [override], [virtual]

Add an ephemeris model to the list of managed models.

Assumptions and limitations:

- Ephemeris models must be registered with the ephemerides manager in dependency order: Models with no dependencies are registered first, followed by models that depend on these base models, and so on.

Parameters

<i>ephem_if</i>	Ephemeris model to be added to the registry.
-----------------	--

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 232 of file ephem_manager.cc.

References ephemerides.

Referenced by jeod::De4xxEphemeris::initialize_model(), jeod::EmptySpaceEphemeris::initialize_model(), and jeod::SinglePlanetEphemeris::initialize_model().

8.13.3.4 void jeod::EphemeridesManager::add_integ_frame (EphemerisRefFrame & *ref_frame*) [override], [virtual]

Add a frame to the reference frame and integration frame lists.

Parameters

<i>ref_frame</i>	Integration frame to be added to the registries
------------------	---

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 467 of file ephem_manager.cc.

References add_ref_frame(), and integ_frames.

Referenced by jeod::De4xxEphemeris::initialize_items(), and jeod::EmptySpaceEphemeris::initialize_model().

8.13.3.5 void jeod::EphemeridesManager::add_planet (BasePlanet & *planet*) [override], [virtual]

Add a planet to the planets registry.

Parameters

<i>planet</i>	Planet to be added to the registry.
---------------	-------------------------------------

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 120 of file ephem_manager.cc.

References jeod::EphemeridesMessages::duplicate_entry, find_base_planet(), and planets.

Referenced by add_planet().

8.13.3.6 `void jeod::EphemeridesManager::add_planet (Planet & planet)` `[override], [virtual]`

Add a planet to the registry.

Parameters

<i>planet</i>	Planet to be added to the registry.
---------------	-------------------------------------

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 87 of file `find_planet.cc`.

References `add_planet()`.

8.13.3.7 void jeod::EphemeridesManager::add_ref_frame (RefFrame & ref_frame) [override]

Add a reference frame to the reference frame registry.

Parameters

<i>ref_frame</i>	Reference frame to be added to the registry
------------------	---

Definition at line 594 of file `ephem_manager.cc`.

References `set_target_frame()`.

Referenced by `add_integ_frame()`.

8.13.3.8 void jeod::EphemeridesManager::clear_added_ephemerides (void) [override],[virtual]

Deactivate any registered ephemeris items and remove them from the list.

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 245 of file `ephem_manager.cc`.

References `jeod::EphemerisItem::disable()`, `ephem_items`, `ephemerides`, and `jeod::EphemeridesMessages::single_ephem_mode`.

8.13.3.9 void jeod::EphemeridesManager::disable_add_ephemeris (void) [override],[virtual]

Make subsequent calls to `add_ephemeris` deactivate the specified ephemeris model instead of adding it to the list of managed models.

Note

This is an irrevocable act.

Assumptions and limitations:

- This method is typically used after clearing the ephemerides model list and then adding the one allowed ephemerides model:

```
EphemeridesManager::clear_added_ephemerides();
EphemeridesManager::add_ephemeris (model);
EphemeridesManager::add_ephem_item (item);
EphemeridesManager::disable_add_ephemeris ();
```

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 214 of file `ephem_manager.cc`.

References `single_ephem_mode`.

8.13.3.10 void jeod::EphemeridesManager::ephem_note_tree_status_change (void) [override],[virtual]

Denote that the reference frame tree needs to be rebuilt.

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 102 of file ephemer_manager.cc.

References regenerate_ref_frame_tree.

8.13.3.11 `BasePlanet * jeod::EphemeridesManager::find_base_planet (const char * name) const` `[override]`,
`[virtual]`

Find the planet with the given name.

Parameters

<i>name</i>	Planet name.
-------------	--------------

Returns

Found planet; NULL if not found.

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 159 of file ephemer_manager.cc.

References planets.

Referenced by add_planet(), jeod::SinglePlanetEphemeris::ephemer_initialize(), jeod::PropagatedPlanet::ephemer_initialize(), and find_planet().

8.13.3.12 `EphemerisOrientation * jeod::EphemeridesManager::find_ephem_angle (const char * name) const` `[override]`,
`[virtual]`

Find the [EphemerisOrientation](#) with the given name.

Parameters

<i>name</i>	Ephemeris angle name
-------------	----------------------

Returns

Found ephemeris angle

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 413 of file ephemer_manager.cc.

References find_ephem_item(), and jeod::EphemeridesMessages::invalid_item.

8.13.3.13 `EphemerisItem * jeod::EphemeridesManager::find_ephem_item (const char * name) const` `[override]`,
`[virtual]`

Find the first registered [EphemerisItem](#) with the given name.

Parameters

<i>name</i>	Ephemeris item name
-------------	---------------------

Returns

Found ephemeris item

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 388 of file ephem_manager.cc.

References `ephem_items`, and `jeod::EphemerisItem::get_name()`.

Referenced by `add_ephem_item()`, `find_ephem_angle()`, `find_ephem_point()`, and `set_target_frame()`.

8.13.3.14 `EphemerisPoint * jeod::EphemeridesManager::find_ephem_point (const char * name) const` `[override]`, `[virtual]`

Find the [EphemerisPoint](#) with the given name.

Parameters

<i>name</i>	Ephemeris point name
-------------	----------------------

Returns

Found ephemeris point

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 438 of file ephem_manager.cc.

References `find_ephem_item()`, and `jeod::EphemeridesMessages::invalid_item`.

8.13.3.15 `EphemerisRefFrame * jeod::EphemeridesManager::find_integ_frame (const char * name) const` `[override]`, `[virtual]`

Find the integration frame with the given name.

Parameters

<i>name</i>	Integration frame name
-------------	------------------------

Returns

Found integration frame

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 486 of file ephem_manager.cc.

References `integ_frames`.

8.13.3.16 `unsigned int jeod::EphemeridesManager::find_integ_frame_index (const EphemerisRefFrame & ref_frame) const` `[override]`, `[virtual]`

Find the index of provided frame in the integration frames vector.

Parameters

<i>ref_frame</i>	Reference to be found
------------------	-----------------------

Returns

Index of found frame

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 551 of file ephem_manager.cc.

References integ_frames, and jeod::EphemeridesMessages::invalid_item.

8.13.3.17 Planet * jeod::EphemeridesManager::find_planet (const char * *name*) const [override],[virtual]

Find the planet with the given name.

Parameters

<i>name</i>	Planet name
-------------	-------------

Returns

Found planet, as a Planet rather than a BasePlanet

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 51 of file find_planet.cc.

References find_base_planet(), and jeod::EphemeridesMessages::invalid_item.

8.13.3.18 const std::vector< EphemerisRefFrame * > & jeod::EphemeridesManager::get_integ_frames (void) const [override],[virtual]

Get a copy of the vector of integration frames.

Returns

Copy of integration frames vector

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 511 of file ephem_manager.cc.

References integ_frames.

8.13.3.19 unsigned int jeod::EphemeridesManager::get_num_planets (void) const [override],[virtual]

Return number of registered planets.

Returns

: Number of registered planets.

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 186 of file ephem_manager.cc.

References planets.

Referenced by jeod::SinglePlanetEphemeris::ephem_initialize().

8.13.3.20 void jeod::EphemeridesManager::initialize_ephemerides (void)

Initialize the ephemeris models.

Definition at line 660 of file ephem_manager.cc.

References jeod::EphemerisInterface::ephem_initialize(), ephemerides, and regenerate_ref_frame_tree.

8.13.3.21 bool jeod::EphemeridesManager::is_integ_frame (const RefFrame & ref_frame) const [override], [virtual]

Determine if supplied frame is an integration frame.

Parameters

<i>ref_frame</i>	Reference frame to test
------------------	-------------------------

Returns

True if the frame is a registered integration frame, false otherwise

Implements [jeod::BaseEphemeridesManager](#).

Definition at line 525 of file ephem_manager.cc.

References integ_frames.

8.13.3.22 EphemeridesManager& jeod::EphemeridesManager::operator= (const EphemeridesManager &) [private]

Not implemented.

8.13.3.23 bool jeod::EphemeridesManager::ref_frame_tree_needs_rebuild () const [inline]

Query if the reference frame tree needs to be rebuilt.

Returns

regenerate_ref_frame_tree data member.

Definition at line 116 of file ephem_manager.hh.

References regenerate_ref_frame_tree.

8.13.3.24 void jeod::EphemeridesManager::set_target_frame (RefFrame & ref_frame)

Set the target-frame reference for the ref-frame and all known EphemItems with similar target-frame names.

Parameters

<i>ref_frame</i>	Reference frame to be used as the target-frame.
------------------	---

Definition at line 609 of file ephem_manager.cc.

References find_ephem_item(), jeod::EphemeridesMessages::inconsistent_setup, jeod::EphemerisRefFrame::set_ephem_manager(), and jeod::EphemerisItem::set_target_frame().

Referenced by add_ref_frame(), and jeod::PropagatedPlanet::ephem_initialize().

8.13.3.25 void jeod::EphemeridesManager::update_ephemerides (void)

Update each ephemeris model.

Definition at line 681 of file ephem_manager.cc.

References activate_ephemerides(), jeod::EphemerisInterface::ephem_update(), ephemerides, and regenerate_ref_frame_tree.

8.13.4 Friends And Related Function Documentation

8.13.4.1 void init_attrjeod__EphemeridesManager () [friend]

8.13.4.2 friend class InputProcessor [friend]

Definition at line 95 of file ephem_manager.hh.

8.13.5 Field Documentation

8.13.5.1 JeodPointerVector<EphemerisItem>::type jeod::EphemeridesManager::ephem_items [protected]

The heads of the ephemeris item lists.

All items in one of these sublists share the same name. The members of the ephem_items list have distinct names.-
trick_io(**)

Definition at line 246 of file ephem_manager.hh.

Referenced by activate_ephemerides(), add_ephem_item(), clear_added_ephemerides(), EphemeridesManager(), find_ephem_item(), and ~EphemeridesManager().

8.13.5.2 JeodPointerVector<EphemerisInterface>::type jeod::EphemeridesManager::ephemerides [protected]

The ephemerides models managed by this [EphemeridesManager](#).

trick_io(**)

Definition at line 239 of file ephem_manager.hh.

Referenced by activate_ephemerides(), add_ephemeris(), clear_added_ephemerides(), EphemeridesManager(), initialize_ephemerides(), update_ephemerides(), and ~EphemeridesManager().

8.13.5.3 JeodPointerVector<EphemerisRefFrame>::type jeod::EphemeridesManager::integ_frames [protected]

List of reference frames that are not rotating with respect to the root node of the reference frame tree.

trick_io(**)

Definition at line 252 of file ephem_manager.hh.

Referenced by add_integ_frame(), EphemeridesManager(), find_integ_frame(), find_integ_frame_index(), get_integ_frames(), is_integ_frame(), and ~EphemeridesManager().

8.13.5.4 JeodPointerVector<BasePlanet>::type jeod::EphemeridesManager::planets [protected]

The planets in a simulation, typically defined at the S_define level.

trick_io(**)

Definition at line 234 of file ephem_manager.hh.

Referenced by `add_planet()`, `EphemeridesManager()`, `find_base_planet()`, `get_num_planets()`, and `~EphemeridesManager()`.

8.13.5.5 `bool jeod::EphemeridesManager::regenerate_ref_frame_tree` [protected]

Set when the reference frame tree needs to be regenerated.

`trick_units(-)`

Definition at line 224 of file `ephem_manager.hh`.

Referenced by `activate_ephemerides()`, `ephem_note_tree_status_change()`, `initialize_ephemerides()`, `ref_frame_tree_needs_rebuild()`, and `update_ephemerides()`.

8.13.5.6 `bool jeod::EphemeridesManager::single_ephem_mode` [protected]

Set via a call to `disable_add_ephemeris`, typically to allow a simple ephemeris model to be active with all other models made inactive.

`trick_units(-)`

Definition at line 219 of file `ephem_manager.hh`.

Referenced by `add_ephem_item()`, and `disable_add_ephemeris()`.

8.13.5.7 `double jeod::EphemeridesManager::update_time` [protected]

Time of last update.

`trick_units(s)`

Definition at line 229 of file `ephem_manager.hh`.

The documentation for this class was generated from the following files:

- [ephem_manager.hh](#)
- [ephem_manager.cc](#)
- [find_planet.cc](#)

8.14 jeod::EphemeridesMessages Class Reference

Specifies the message IDs used in the Ephemerides model.

```
#include <ephem_messages.hh>
```

Static Public Attributes

- static char const * `inconsistent_setup` = "environment/ephemerides/" "inconsistent_setup"
Error issued when the ephemeris model configuration is inconsistent.
- static char const * `file_error` = "environment/ephemerides/" "file_error"
Error issued when the ephemeris file cannot be opened for input.
- static char const * `unsupported_architecture` = "environment/ephemerides/" "unsupported_architecture"
Error issued for machine architectures that do not conform to the architecture assumptions:
- static char const * `garbage_file` = "environment/ephemerides/" "garbage_file"
Error issued when the ephemeris file appears to be garbage.
- static char const * `time_not_in_range` = "environment/ephemerides/" "time_not_in_range"
Error issued when the ephemeris file does not contain data for the requested time.

- static char const * [item_not_in_file](#) = "environment/ephemerides/" "item_not_in_file"
Error issued when the ephemeris file does not contain data for the requested item.
- static char const * [null_pointer](#) = "environment/ephemerides/" "null_pointer"
Issued when a pointer should be non-NULL but isn't.
- static char const * [duplicate_entry](#) = "environment/ephemerides/" "duplicate_entry"
Issued on request to add a pointer to a list a second time.
- static char const * [invalid_name](#) = "environment/ephemerides/" "invalid_name"
Issued when a name is invalid – empty, a duplicate, ...
- static char const * [invalid_item](#) = "environment/ephemerides/" "invalid_item"
Issued when something other than a name is invalid.
- static char const * [single_ephem_mode](#) = "environment/ephemerides/" "single_ephem_mode"
Issued when the ephemeris manager is rejecting add_ephemeris calls.
- static char const * [internal_error](#) = "environment/ephemerides/" "internal_error"
Issued when some internal error occurred.
- static char const * [debug](#) = "environment/ephemerides/" "debug"
Used to send a message about a non-error condition.

Private Member Functions

- [EphemeridesMessages](#) (void)
Not implemented.
- [EphemeridesMessages](#) (const [EphemeridesMessages](#) &)
Not implemented.
- [EphemeridesMessages](#) & operator= (const [EphemeridesMessages](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemeridesMessages](#) ()

8.14.1 Detailed Description

Specifies the message IDs used in the Ephemerides model.

Assumptions and Limitations

- This is a complete catalog of the messages sent by the ephemerides model.
- This is not an exhaustive list of all the things that can go awry.

Definition at line 85 of file `ephem_messages.hh`.

8.14.2 Constructor & Destructor Documentation

8.14.2.1 `jeod::EphemeridesMessages::EphemeridesMessages (void) [private]`

Not implemented.

8.14.2.2 `jeod::EphemeridesMessages::EphemeridesMessages (const EphemeridesMessages &) [private]`

Not implemented.

8.14.3 Member Function Documentation

8.14.3.1 EphemeridesMessages& jeod::EphemeridesMessages::operator= (const EphemeridesMessages &) [private]

Not implemented.

8.14.4 Friends And Related Function Documentation

8.14.4.1 void init_attrjeod__EphemeridesMessages () [friend]

8.14.4.2 friend class InputProcessor [friend]

Definition at line 86 of file ephem_messages.hh.

8.14.5 Field Documentation

8.14.5.1 char const * jeod::EphemeridesMessages::debug = "environment/ephemerides/" "debug" [static]

Used to send a message about a non-error condition.

trick_units(–)

Definition at line 163 of file ephem_messages.hh.

Referenced by jeod::De4xxFile::open().

8.14.5.2 char const * jeod::EphemeridesMessages::duplicate_entry = "environment/ephemerides/" "duplicate_entry" [static]

Issued on request to add a pointer to a list a second time.

trick_units(–)

Definition at line 136 of file ephem_messages.hh.

Referenced by jeod::EphemeridesManager::add_ephem_item(), and jeod::EphemeridesManager::add_planet().

8.14.5.3 char const * jeod::EphemeridesMessages::file_error = "environment/ephemerides/" "file_error" [static]

Error issued when the ephemeris file cannot be opened for input.

trick_units(–)

Definition at line 100 of file ephem_messages.hh.

Referenced by jeod::De4xxFile::close(), jeod::De4xxFile::open(), jeod::De4xxFile::pre_initialize(), and jeod::De4xxFile::update().

8.14.5.4 char const * jeod::EphemeridesMessages::garbage_file = "environment/ephemerides/" "garbage_file" [static]

Error issued when the ephemeris file appears to be garbage.

trick_units(–)

Definition at line 114 of file ephem_messages.hh.

Referenced by jeod::De4xxFile::pre_initialize().

8.14.5.5 `char const * jeod::EphemeridesMessages::inconsistent_setup = "environment/ephemerides/" "inconsistent_setup"`
`[static]`

Error issued when the ephemeris model configuration is inconsistent.

`trick_units(-)`

Definition at line 95 of file `ephem_messages.hh`.

Referenced by `jeod::De4xxEphemeris::activate_em_nodes()`, `jeod::EphemeridesManager::add_ephem_item()`, `jeod::De4xxEphemeris::ephem_build_tree()`, `jeod::EmptySpaceEphemeris::ephem_initialize()`, `jeod::SinglePlanetEphemeris::ephem_initialize()`, `jeod::PropagatedPlanet::ephem_initialize()`, `jeod::De4xxEphemeris::initialize_items()`, `jeod::PropagatedPlanet::initialize_model()`, `jeod::De4xxEphemeris::initialize_time()`, `jeod::EphemerisReferenceFrame::set_active_status()`, `jeod::PropagatedPlanet::set_mode()`, `jeod::SinglePointEphemeris::set_name()`, and `jeod::EphemeridesManager::set_target_frame()`.

8.14.5.6 `char const * jeod::EphemeridesMessages::internal_error = "environment/ephemerides/" "internal_error"`
`[static]`

Issued when some internal error occurred.

These errors should never happen. `trick_units(-)`

Definition at line 157 of file `ephem_messages.hh`.

Referenced by `jeod::SinglePointEphemeris::activate()`, `jeod::De4xxEphemeris::activate()`, `jeod::PropagatedPlanet::activate()`, `jeod::EphemeridesManager::add_ephem_item()`, `jeod::EphemerisOrientation::note_frame_status_change()`, `jeod::EphemerisPoint::note_frame_status_change()`, `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

8.14.5.7 `char const * jeod::EphemeridesMessages::invalid_item = "environment/ephemerides/" "invalid_item"` `[static]`

Issued when something other than a name is invalid.

`trick_units(-)`

Definition at line 146 of file `ephem_messages.hh`.

Referenced by `jeod::EphemerisItem::activate()`, `jeod::EphemeridesManager::find_ephem_angle()`, `jeod::EphemeridesManager::find_ephem_point()`, `jeod::EphemeridesManager::find_integ_frame_index()`, `jeod::EphemeridesManager::find_planet()`, and `jeod::EphemerisItem::set_target_frame()`.

8.14.5.8 `char const * jeod::EphemeridesMessages::invalid_name = "environment/ephemerides/" "invalid_name"` `[static]`

Issued when a name is invalid – empty, a duplicate, ...

`trick_units(-)`

Definition at line 141 of file `ephem_messages.hh`.

Referenced by `jeod::EphemerisItem::set_name()`, and `jeod::EphemerisItem::validate_name()`.

8.14.5.9 `char const * jeod::EphemeridesMessages::item_not_in_file = "environment/ephemerides/" "item_not_in_file"`
`[static]`

Error issued when the ephemeris file does not contain data for the requested item.

`trick_units(-)`

Definition at line 126 of file `ephem_messages.hh`.

Referenced by `jeod::De4xxFile::update()`.

8.14.5.10 `char const * jeod::EphemeridesMessages::null_pointer = "environment/ephemerides/" "null_pointer" [static]`

Issued when a pointer should be non-NULL but isn't.

trick_units(-)

Definition at line 131 of file ephem_messages.hh.

8.14.5.11 `char const * jeod::EphemeridesMessages::single_ephem_mode = "environment/ephemerides/" "single_ephem_mode" [static]`

Issued when the ephemeris manager is rejecting add_ephemeris calls.

trick_units(-)

Definition at line 151 of file ephem_messages.hh.

Referenced by jeod::EphemeridesManager::add_ephem_item(), and jeod::EphemeridesManager::clear_added_ephemerides().

8.14.5.12 `char const * jeod::EphemeridesMessages::time_not_in_range = "environment/ephemerides/" "time_not_in_range" [static]`

Error issued when the ephemeris file does not contain data for the requested time.

trick_units(-)

Definition at line 120 of file ephem_messages.hh.

Referenced by jeod::De4xxFile::initialize().

8.14.5.13 `char const * jeod::EphemeridesMessages::unsupported_architecture = "environment/ephemerides/" "unsupported_architecture" [static]`

Error issued for machine architectures that do not conform to the architecture assumptions:

- char = 8 bits
- int32_t = 4 bytes (32 bits)
- double = 8 bytes (64 bits)trick_units(-)

Definition at line 109 of file ephem_messages.hh.

The documentation for this class was generated from the following files:

- [ephem_messages.hh](#)
- [ephem_messages.cc](#)

8.15 jeod::EphemerisDataItemMeta Struct Reference

Structure containing the header metadata for sizing/locating the data entries with the data segments.

```
#include <de4xx_file.hh>
```

Data Fields

- [uint32_t offset](#)
Offsets into coeffs array.

- `uint32_t nterms`
Chebyshev polynomial terms.
- `uint32_t npoly`
Number polynomials per data block.

8.15.1 Detailed Description

Structure containing the header metadata for sizing/locating the data entries with the data segments.

Definition at line 145 of file `de4xx_file.hh`.

8.15.2 Field Documentation

8.15.2.1 `uint32_t jeod::EphemerisDataItemMeta::npoly`

Number polynomials per data block.

`trick_units(-)`

Definition at line 160 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`.

8.15.2.2 `uint32_t jeod::EphemerisDataItemMeta::nterms`

Chebyshev polynomial terms.

`trick_units(-)`

Definition at line 155 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`, and `jeod::De4xxFile::pre_initialize()`.

8.15.2.3 `uint32_t jeod::EphemerisDataItemMeta::offset`

Offsets into coeffs array.

`trick_units(-)`

Definition at line 150 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`, and `jeod::De4xxFile::pre_initialize()`.

The documentation for this struct was generated from the following file:

- [de4xx_file.hh](#)

8.16 `jeod::EphemerisDataSegmentMeta` Struct Reference

Metadata implied from each data segment.

```
#include <de4xx_file.hh>
```

Data Fields

- `uint32_t num_recs`
The number of records in the file.
- `double start_epoch`

- Julian date of start of file.*
 • double [stop_epoch](#)
Julian date of end of file.

8.16.1 Detailed Description

Metadata implied from each data segment.

Definition at line 167 of file `de4xx_file.hh`.

8.16.2 Field Documentation

8.16.2.1 `uint32_t jeod::EphemerisDataSegmentMeta::num_recs`

The number of records in the file.

`trick_units(-)`

Definition at line 172 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

8.16.2.2 `double jeod::EphemerisDataSegmentMeta::start_epoch`

Julian date of start of file.

`trick_units(day)`

Definition at line 177 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::initialize()`, and `jeod::De4xxFile::pre_initialize()`.

8.16.2.3 `double jeod::EphemerisDataSegmentMeta::stop_epoch`

Julian date of end of file.

`trick_units(day)`

Definition at line 182 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::pre_initialize()`.

The documentation for this struct was generated from the following file:

- [de4xx_file.hh](#)

8.17 jeod::EphemerisDataSetMeta Struct Reference

Container for the metadata from the DE model header.

```
#include <de4xx_file.hh>
```

Data Fields

- `uint32_t` [number_file_items](#)
Return the number of ephemeris items provided in DE data.
- `double` [start_epoch](#)
Julian date of start of dataset.

- double `stop_epoch`
Julian date of end of dataset.
- double `delta_epoch`
Julian period length of each segment.
- uint32_t `number_segments`
Number of ascp files (segments) provided by DE model.
- uint32_t `ncoeff`
Size of each data record throughout the dataset.
- double `de_constants` [`De4xxBase::De4xx_Const_MaxConsts`]
Array of supplied constants required by JEOD.

8.17.1 Detailed Description

Container for the metadata from the DE model header.

Definition at line 101 of file `de4xx_file.hh`.

8.17.2 Field Documentation

8.17.2.1 double `jeod::EphemerisDataSetMeta::de_constants[De4xxBase::De4xx_Const_MaxConsts]`

Array of supplied constants required by JEOD.

Definition at line 137 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::initialize()`, `jeod::De4xxEphemeris::initialize_file()`, and `jeod::De4xxFile::pre_initialize()`.

8.17.2.2 double `jeod::EphemerisDataSetMeta::delta_epoch`

Julian period length of each segment.

`trick_units(day)`

Definition at line 122 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::initialize()`, `jeod::De4xxFile::interpolate()`, `jeod::De4xxFile::time_is_in_range()`, and `jeod::De4xxFile::update()`.

8.17.2.3 uint32_t `jeod::EphemerisDataSetMeta::ncoeff`

Size of each data record throughout the dataset.

`trick_units(-)`

Definition at line 132 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::update()`.

8.17.2.4 uint32_t `jeod::EphemerisDataSetMeta::number_file_items`

Return the number of ephemeris items provided in DE data.

(e.g., 13 for DE405/421, 15 for DE440)

Definition at line 107 of file `de4xx_file.hh`.

Referenced by `jeod::De4xxFile::interpolate()`, `jeod::De4xxFile::open()`, `jeod::De4xxFile::pre_initialize()`, and `jeod::De4xxFile::update()`.

8.17.2.5 uint32_t jeod::EphemerisDataSetMeta::number_segments

Number of ascp files (segments) provided by DE model.

trick_units(-)

Definition at line 127 of file de4xx_file.hh.

Referenced by jeod::De4xxFile::pre_initialize(), and jeod::De4xxFile::update().

8.17.2.6 double jeod::EphemerisDataSetMeta::start_epoch

Julian date of start of dataset.

trick_units(day)

Definition at line 112 of file de4xx_file.hh.

8.17.2.7 double jeod::EphemerisDataSetMeta::stop_epoch

Julian date of end of dataset.

trick_units(day)

Definition at line 117 of file de4xx_file.hh.

The documentation for this struct was generated from the following file:


- [de4xx_file.hh](#)

8.18 jeod::EphemerisInterface Class Reference

Interface class that specifies minimal functionality of an ephemeris model.

```
#include <ephem_interface.hh>
```

Inheritance diagram for jeod::EphemerisInterface:



Public Member Functions

- [~EphemerisInterface](#) (void) override
Destructor; there is nothing to destroy here.
- virtual double [timestamp](#) (void) const =0
Indicates when class was last updated.
- virtual const char * [get_name](#) (void) const =0
Identify the model.
- virtual void [ephem_initialize](#) (EphemeridesManager &manager)=0
Initialize the model.
- virtual void [ephem_activate](#) (EphemeridesManager &manager)=0

Activate the model.

- virtual void [ephem_build_tree](#) ([EphemeridesManager](#) &manager)=0

Build the model's contribution to the reference frame tree.

- virtual void [ephem_update](#) (void)=0

Update the model.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemerisInterface](#) ()

8.18.1 Detailed Description

Interface class that specifies minimal functionality of an ephemeris model.

Definition at line 81 of file [ephem_interface.hh](#).

8.18.2 Constructor & Destructor Documentation

8.18.2.1 [jeod::EphemerisInterface::~~EphemerisInterface](#) (void) [inline], [override]

Destructor; there is nothing to destroy here.

Definition at line 163 of file [ephem_interface.hh](#).

8.18.3 Member Function Documentation

8.18.3.1 virtual void [jeod::EphemerisInterface::ephem_activate](#) ([EphemeridesManager](#) & *manager*) [pure virtual]

Activate the model.

Parameters

<i>in, out</i>	<i>manager</i>	Ephemerides manager
----------------	----------------	---------------------

Implemented in [jeod::PropagatedPlanet](#), [jeod::SinglePlanetEphemeris](#), [jeod::De4xxEphemeris](#), [jeod::EmptySpaceEphemeris](#), and [jeod::SinglePointEphemeris](#).

Referenced by [jeod::EphemeridesManager::activate_ephemerides](#)().

8.18.3.2 virtual void [jeod::EphemerisInterface::ephem_build_tree](#) ([EphemeridesManager](#) & *manager*) [pure virtual]

Build the model's contribution to the reference frame tree.

Parameters

<i>in, out</i>	<i>manager</i>	Ephemerides manager
----------------	----------------	---------------------

Implemented in [jeod::PropagatedPlanet](#), [jeod::SinglePlanetEphemeris](#), [jeod::De4xxEphemeris](#), [jeod::EmptySpaceEphemeris](#), and [jeod::SinglePointEphemeris](#).

Referenced by [jeod::EphemeridesManager::activate_ephemerides](#)().

8.18.3.3 virtual void jeod::EphemerisInterface::ephem_initialize (EphemeridesManager & *manager*) [pure virtual]

Initialize the model.

Parameters

<code>in, out</code>	<code>manager</code>	Ephemerides manager
----------------------	----------------------	---------------------

Implemented in [jeod::PropagatedPlanet](#), [jeod::SinglePlanetEphemeris](#), [jeod::De4xxEphemeris](#), [jeod::EmptySpaceEphemeris](#), and [jeod::SinglePointEphemeris](#).

Referenced by [jeod::EphemeridesManager::initialize_ephemerides\(\)](#).

8.18.3.4 `virtual void jeod::EphemerisInterface::ephem_update (void) [pure virtual]`

Update the model.

Implemented in [jeod::PropagatedPlanet](#), [jeod::De4xxEphemeris](#), and [jeod::SinglePointEphemeris](#).

Referenced by [jeod::EphemeridesManager::update_ephemerides\(\)](#).

8.18.3.5 `virtual const char* jeod::EphemerisInterface::get_name (void) const [pure virtual]`

Identify the model.

Returns

Model name

Implemented in [jeod::PropagatedPlanet](#), [jeod::De4xxEphemeris](#), and [jeod::SinglePointEphemeris](#).

Referenced by [jeod::EphemeridesManager::add_ephem_item\(\)](#).

8.18.3.6 `virtual double jeod::EphemerisInterface::timestamp (void) const [pure virtual]`

Indicates when class was last updated.

Returns

Time of last update

Units: s

Implemented in [jeod::PropagatedPlanet](#), [jeod::De4xxEphemeris](#), and [jeod::SinglePointEphemeris](#).

8.18.4 Friends And Related Function Documentation

8.18.4.1 `void init_attrjeod__EphemerisInterface () [friend]`

8.18.4.2 `friend class InputProcessor [friend]`

Definition at line 82 of file `ephem_interface.hh`.

The documentation for this class was generated from the following file:


- [ephem_interface.hh](#)

8.19 jeod::EphemerisItem Class Reference

The [EphemerisItem](#) class is the base class for representing an item that is modeled in an ephemeris model.

```
#include <ephem_item.hh>
```

Inheritance diagram for jeod::EphemerisItem:



Public Types

- enum [TargetAspect](#) { [Translation](#) = 0, [Rotation](#) = 1 }
- Defines the aspect of the target frame that will be modified by the [EphemerisItem](#) object.*

Public Member Functions

- [EphemerisItem](#) ()
Construct an ephemeris item.
- [~EphemerisItem](#) () override
Destroy an ephemeris item.
- virtual void [set_name](#) (const char *new_name)
Name an ephemeris item.
- virtual void [set_name](#) (const char *pname, const char *fname)
Name an ephemeris item.
- const char * [get_name](#) () const
Return the name.
- virtual void [set_timestamp](#) (double time)
Set the update time of this item.
- double [timestamp](#) (void) const
Return the update time of this item.
- virtual void [set_owner](#) ([EphemerisInterface](#) *new_owner)
Set the owner of this item.
- [EphemerisInterface](#) * [get_owner](#) () const
Return the owner of this item.
- virtual void [set_manager](#) ([BaseEphemeridesManager](#) *new_manager)
Set the manager of this item.
- [BaseEphemeridesManager](#) * [get_manager](#) () const
Return the manager of this item.
- virtual void [set_next](#) ([EphemerisItem](#) *next_item)
Set the next item.
- [EphemerisItem](#) * [get_next](#) () const
Get the next item.
- virtual void [set_head](#) ([EphemerisItem](#) *head_item)
Set the head item.
- [EphemerisItem](#) * [get_head](#) () const
Get the head item.
- virtual void [set_target_frame](#) ([EphemerisRefFrame](#) &frame)
Set the target frame.
- [EphemerisRefFrame](#) * [get_target_frame](#) () const

- Get the target frame.*
- virtual void **enable** ()
 - Enable an **EphemerisItem** object.*
- virtual void **disable** ()
 - Disable an **EphemerisItem** object.*
- bool **is_enabled** () const
 - Return enabled status.*
- **EphemerisItem** * **get_enabled_item** (void) const
 - Get the item marked as enabled, if any.*
- virtual void **activate** ()
 - Activate a **EphemerisItem** object.*
- virtual void **deactivate** ()
 - Deactivate a **EphemerisItem** object.*
- bool **is_active** () const
 - Return activity status.*
- bool **is_activatable** () const
 - Is the item activatable?*
- void **validate_name** (const char *file, unsigned int line, const char *new_value, const char *old_value, const char *variable_name)
 - Name an ephemeris item.*
- virtual **TargetAspect** **updates_what** (void) const =0
 - Identifies which part of the target frame does the object updates.*
- virtual const char * **default_suffix** (void) const =0
 - The default suffix for the item.*
- virtual void **disconnect_from_tree** (void)=0
 - Disconnect the item from the reference frame tree.*

Protected Member Functions

- virtual void **set_name_internal** (char *new_name)
 - Name an ephemeris item.*

Protected Attributes

- char * **name**
 - The name of the item.*
- **EphemerisInterface** * **owner**
 - The ephemeris model that owns this object.*
- **BaseEphemeridesManager** * **manager**
 - The ephemeris manager that manages this object.*
- **EphemerisRefFrame** * **target_frame**
 - The reference frame whose non-constant state is set by this object.*
- **EphemerisItem** * **head**
 - The first ephemeris item with the same name as this item.*
- **EphemerisItem** * **next**
 - The next ephemeris item with the same name as this item.*
- double **update_time**
 - Time of last update, dynamic time seconds.*
- bool **enabled**
 - Is the item enabled?*
- bool **active**
 - Is the item active?*

Private Member Functions

- [EphemerisItem](#) (const [EphemerisItem](#) &)
Not implemented.
- [EphemerisItem](#) & operator= (const [EphemerisItem](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemerisItem](#) ()

8.19.1 Detailed Description

The [EphemerisItem](#) class is the base class for representing an item that is modeled in an ephemeris model.

Ephemeris items form the bridge between the reference frame model and the ephemeris models. An [EphemerisItem](#)

- Has a name, which is not necessarily unique. Ephemeris items with the same name are linked to one another to form a linked list.
- Has a target reference frame. This is the ephemeris reference frame which has the same name as the ephemeris item.
- Can be enabled or disabled. At most one item of a set of commonly-named items can be enabled, and only if a correspondingly-named ephemeris reference frame exists. Ownership of the correspondingly-named ephemeris reference frame transfers to the enabled ephemeris item. When an ephemeris item is disabled, the ephemeris model that owns the ephemeris item should not operate on the correspondingly-named reference frame.
- Can be active or inactive. Disabled items must always be inactive. The activity level of the enabled item for a set of commonly-named items is automatically maintained to be the same as that of the target frame.

The ephemeris model that owns an active ephemeris item is responsible for ensuring that the correspondingly-named ephemeris reference frame is a part of the active reference frame tree and for updating that reference frame's state.

Definition at line 106 of file `ephem_item.hh`.

8.19.2 Member Enumeration Documentation

8.19.2.1 enum `jeod::EphemerisItem::TargetAspect`

Defines the aspect of the target frame that will be modified by the [EphemerisItem](#) object.

Enumerator

Translation

Rotation

Definition at line 117 of file `ephem_item.hh`.

8.19.3 Constructor & Destructor Documentation

8.19.3.1 `jeod::EphemerisItem::EphemerisItem (void)`

Construct an ephemeris item.

Definition at line 62 of file `ephem_item.cc`.

8.19.3.2 `jeod::EphemerisItem::~~EphemerisItem (void) [override]`

Destroy an ephemeris item.

Definition at line 83 of file `ephem_item.cc`.

References name.

8.19.3.3 `jeod::EphemerisItem::EphemerisItem (const EphemerisItem &) [private]`

Not implemented.

8.19.4 Member Function Documentation

8.19.4.1 `void jeod::EphemerisItem::activate (void) [virtual]`

Activate a [EphemerisItem](#) object.

Definition at line 345 of file `ephem_item.cc`.

References active, `jeod::EphemeridesMessages::invalid_item`, `is_activatable()`, and name.

Referenced by `jeod::De4xxEphemeris::activate_em_nodes()`, `jeod::EphemerisOrientation::note_frame_status_change()`, `jeod::EphemerisPoint::note_frame_status_change()`, and `set_target_frame()`.

8.19.4.2 `void jeod::EphemerisItem::deactivate (void) [inline],[virtual]`

Deactivate a [EphemerisItem](#) object.

Definition at line 130 of file `ephem_item_inline.hh`.

References active.

Referenced by `jeod::EphemerisOrientation::note_frame_status_change()`, and `jeod::EphemerisPoint::note_frame_status_change()`.

8.19.4.3 `virtual const char* jeod::EphemerisItem::default_suffix (void) const [pure virtual]`

The default suffix for the item.

Implemented in [jeod::EphemerisOrientation](#), and [jeod::EphemerisPoint](#).

Referenced by `set_name()`.

8.19.4.4 `void jeod::EphemerisItem::disable (void) [inline],[virtual]`

Disable an [EphemerisItem](#) object.

Definition at line 316 of file `ephem_item.cc`.

References active, enabled, `jeod::BaseEphemeridesManager::ephem_note_tree_status_change()`, manager, and target_frame.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`, `jeod::EphemeridesManager::clear_added_ephemerides()`, `enable()`, `jeod::EmptySpaceEphemeris::ephem_initialize()`, `jeod::SinglePlanetEphemeris::ephem_initialize()`, `jeod::De4xxEphemeris::initialize_items()`, and `jeod::PropagatedPlanet::set_mode()`.

8.19.4.5 `virtual void jeod::EphemerisItem::disconnect_from_tree (void) [pure virtual]`

Disconnect the item from the reference frame tree.

Implemented in [jeod::EphemerisOrientation](#), and [jeod::EphemerisPoint](#).

Referenced by [jeod::EphemeridesManager::activate_ephemerides\(\)](#).

8.19.4.6 void jeod::EphemerisItem::enable (void) [virtual]

Enable an [EphemerisItem](#) object.

Reimplemented in [jeod::EphemerisOrientation](#).

Definition at line 279 of file `ephem_item.cc`.

References `active`, `disable()`, `enabled`, `jeod::BaseEphemeridesManager::ephem_note_tree_status_change()`, `get_enabled_item()`, `manager`, and `target_frame`.

Referenced by `jeod::De4xxEphemeris::activate_em_nodes()`, `jeod::De4xxEphemeris::De4xxEphemeris()`, `jeod::EmptySpaceEphemeris::EmptySpaceEphemeris()`, `jeod::EphemerisOrientation::enable()`, `jeod::PropagatedPlanet::set_mode()`, and `jeod::SinglePlanetEphemeris::SinglePlanetEphemeris()`.

8.19.4.7 EphemerisItem * jeod::EphemerisItem::get_enabled_item (void) const [inline]

Get the item marked as enabled, if any.

Returns

Enabled item

Definition at line 272 of file `ephem_item_inline.hh`.

References `enabled`, `head`, and `next`.

Referenced by `jeod::De4xxEphemeris::activate_nodes()`, `jeod::EphemeridesManager::add_ephem_item()`, `jeod::EphemerisOrientation::enable()`, `enable()`, and `set_target_frame()`.

8.19.4.8 EphemerisItem * jeod::EphemerisItem::get_head (void) const [inline]

Get the head item.

Returns

Root item

Definition at line 220 of file `ephem_item_inline.hh`.

References `head`.

8.19.4.9 BaseEphemeridesManager * jeod::EphemerisItem::get_manager (void) const [inline]

Return the manager of this item.

Returns

Object manager

Definition at line 194 of file `ephem_item_inline.hh`.

References `manager`.

8.19.4.10 `const char * jeod::EphemerisItem::get_name (void) const [inline]`

Return the name.

Returns

Void

Definition at line 79 of file `ephem_item_inline.hh`.

References `name`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`, `jeod::De4xxEphemeris::De4xxEphemeris()`, and `jeod::EphemeridesManager::find_ephem_item()`.

8.19.4.11 `EphemerisItem * jeod::EphemerisItem::get_next (void) const [inline]`

Get the next item.

Returns

Next item

Definition at line 246 of file `ephem_item_inline.hh`.

References `next`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`.

8.19.4.12 `EphemerisInterface * jeod::EphemerisItem::get_owner (void) const [inline]`

Return the owner of this item.

Returns

Frame owner

Definition at line 168 of file `ephem_item_inline.hh`.

References `owner`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`.

8.19.4.13 `EphemerisRefFrame * jeod::EphemerisItem::get_target_frame (void) const [inline]`

Get the target frame.

Returns

Target frame

Definition at line 259 of file `ephem_item_inline.hh`.

References `target_frame`.

Referenced by `jeod::SinglePlanetEphemeris::ephem_build_tree()`, `jeod::EmptySpaceEphemeris::ephem_initialize()`, `jeod::De4xxEphemeris::ephem_initialize()`, `jeod::SinglePlanetEphemeris::ephem_initialize()`, and `jeod::PropagatedPlanet::ephem_initialize()`.

8.19.4.14 `bool jeod::EphemerisItem::is_activatable (void) const`

Is the item activatable?

Returns

True if item can be activated.

Definition at line 365 of file `ephem_item.cc`.

References `active`, `enabled`, `head`, and `next`.

Referenced by `activate()`.

8.19.4.15 `bool jeod::EphemerisItem::is_active (void) const` `[inline]`

Return activity status.

Returns

Is item active?

Definition at line 143 of file `ephem_item_inline.hh`.

References `active`.

Referenced by `jeod::De4xxEphemeris::activate_nodes()`.

8.19.4.16 `bool jeod::EphemerisItem::is_enabled (void) const` `[inline]`

Return enabled status.

Returns

Is item enabled?

Definition at line 118 of file `ephem_item_inline.hh`.

References `enabled`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`.

8.19.4.17 `EphemerisItem& jeod::EphemerisItem::operator= (const EphemerisItem &)` `[private]`

Not implemented.

8.19.4.18 `void jeod::EphemerisItem::set_head (EphemerisItem * head_item)` `[inline],[virtual]`

Set the head item.

Parameters

<code>in, out</code>	<code>head_item</code>	Root item
----------------------	------------------------	-----------

Definition at line 207 of file `ephem_item_inline.hh`.

References `head`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`.

8.19.4.19 `void jeod::EphemerisItem::set_manager (BaseEphemeridesManager * new_manager)` `[inline]`,
`[virtual]`

Set the manager of this item.

Parameters

<i>in</i>	<i>new_manager</i>	New owner
-----------	--------------------	-----------

Definition at line 181 of file `ephem_item_inline.hh`.

References `manager`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`.

8.19.4.20 void jeod::EphemerisItem::set_name (const char * *new_name*) [virtual]

Name an ephemeris item.

Parameters

<i>in</i>	<i>new_name</i>	New name
-----------	-----------------	----------

Definition at line 151 of file `ephem_item.cc`.

References `default_suffix()`, `jeod::EphemeridesMessages::invalid_name`, `name`, `set_name_internal()`, and `validate_name()`.

Referenced by `jeod::De4xxEphemeris::De4xxEphemeris()`, `jeod::PropagatedPlanet::initialize_model()`, `jeod::EmptySpaceEphemeris::set_name()`, and `jeod::SinglePlanetEphemeris::set_name()`.

8.19.4.21 void jeod::EphemerisItem::set_name (const char * *pname*, const char * *fname*) [virtual]

Name an ephemeris item.

Parameters

<i>in</i>	<i>pname</i>	Planet name
<i>in</i>	<i>fname</i>	Frame name

Definition at line 132 of file `ephem_item.cc`.

References `name`, `set_name_internal()`, and `validate_name()`.

8.19.4.22 void jeod::EphemerisItem::set_name_internal (char * *new_name*) [protected],[virtual]

Name an ephemeris item.

Parameters

<i>in</i>	<i>new_name</i>	New name
-----------	-----------------	----------

Definition at line 183 of file `ephem_item.cc`.

References `name`.

Referenced by `set_name()`.

8.19.4.23 void jeod::EphemerisItem::set_next (EphemerisItem * *next_item*) [inline],[virtual]

Set the next item.

Parameters

<i>in, out</i>	<i>next_item</i>	Next item
----------------	------------------	-----------

Definition at line 233 of file `ephem_item_inline.hh`.

References `next`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`.

8.19.4.24 `void jeod::EphemerisItem::set_owner (EphemerisInterface * new_owner) [inline],[virtual]`

Set the owner of this item.

Parameters

<i>in</i>	<i>new_owner</i>	New owner
-----------	------------------	-----------

Definition at line 156 of file `ephem_item_inline.hh`.

References owner.

Referenced by `jeod::De4xxEphemeris::De4xxEphemeris()`, `jeod::EmptySpaceEphemeris::EmptySpaceEphemeris()`, `jeod::PropagatedPlanet::PropagatedPlanet()`, and `jeod::SinglePlanetEphemeris::SinglePlanetEphemeris()`.

8.19.4.25 `void jeod::EphemerisItem::set_target_frame (EphemerisRefFrame & frame) [virtual]`

Set the target frame.

All ephemeris items that share a common name must point to the same target frame.

Parameters

<i>in</i>	<i>frame</i>	Target frame
-----------	--------------	--------------

Definition at line 204 of file `ephem_item.cc`.

References `activate()`, `get_enabled_item()`, `head`, `jeod::EphemeridesMessages::invalid_item`, `jeod::BaseEphemeridesManager::is_integ_frame()`, `manager`, `name`, `next`, `set_target_frame()`, `target_frame`, `Translation`, and `updates_what()`.

Referenced by `jeod::EphemeridesManager::add_ephem_item()`, `set_target_frame()`, and `jeod::EphemeridesManager::set_target_frame()`.

8.19.4.26 `void jeod::EphemerisItem::set_timestamp (double time) [inline],[virtual]`

Set the update time of this item.

Parameters

<i>in</i>	<i>time</i>	Time Units: s
-----------	-------------	------------------

Definition at line 92 of file `ephem_item_inline.hh`.

References `update_time`.

8.19.4.27 `double jeod::EphemerisItem::timestamp (void) const [inline]`

Return the update time of this item.

Returns

Time of last update
Units: s

Definition at line 105 of file `ephem_item_inline.hh`.

References `update_time`.

8.19.4.28 `virtual TargetAspect jeod::EphemerisItem::updates_what (void) const [pure virtual]`

Identifies which part of the target frame does the object updates.

Implemented in [jeod::EphemerisOrientation](#), and [jeod::EphemerisPoint](#).

Referenced by [jeod::EphemeridesManager::add_ephem_item\(\)](#), and [set_target_frame\(\)](#).

8.19.4.29 `void jeod::EphemerisItem::validate_name (const char * file, unsigned int line, const char * new_value, const char * old_value, const char * variable_name)`

Name an ephemeris item.

Parameters

in	<i>file</i>	Usually FILE
in	<i>line</i>	Usually LINE
in	<i>new_value</i>	Value to check
in	<i>old_value</i>	Current value
in	<i>variable_name</i>	Variable name

Definition at line 102 of file `ephem_item.cc`.

References [jeod::EphemeridesMessages::invalid_name](#), and [manager](#).

Referenced by [set_name\(\)](#).

8.19.5 Friends And Related Function Documentation

8.19.5.1 `void init_attrjeod__EphemerisItem ()` [[friend](#)]

8.19.5.2 `friend class InputProcessor` [[friend](#)]

Definition at line 107 of file `ephem_item.hh`.

8.19.6 Field Documentation

8.19.6.1 `bool jeod::EphemerisItem::active` [[protected](#)]

Is the item active?

- An item can be activated only if it is enabled. The `enable` and `activate` methods assure that this is the case.
- Activity is determined by the activity of the target frame, which is in turn determined by the reference frame subscription `model.trick_units(-)`

Definition at line 272 of file `ephem_item.hh`.

Referenced by [activate\(\)](#), [deactivate\(\)](#), [disable\(\)](#), [jeod::EphemerisPoint::disconnect_from_tree\(\)](#), [enable\(\)](#), [is_activatable\(\)](#), and [is_active\(\)](#).

8.19.6.2 `bool jeod::EphemerisItem::enabled` [[protected](#)]

Is the item enabled?

- An item can be enabled only if the data associated with the item such as the translational state of a planet exist somewhere in the simulation.
- Only one of a set of ephemeris items that share the same name can be enabled. The `enable` method ensures that this is the case.

- Exactly one of a set of ephemeris items that share same name should be enabled if some other simulation agent depends on the data associated with an ephemeris item. Ensuring that this is the case is the responsibility of the ephemeris models and the users of those models.`trick_units(-)`

Definition at line 263 of file `ephem_item.hh`.

Referenced by `disable()`, `jeod::EphemerisOrientation::enable()`, `enable()`, `get_enabled_item()`, `is_activatable()`, `is_enabled()`, `jeod::PropagatedEphemerisPlanet::update()`, and `jeod::PropagatedEphemerisOrientation::update()`.

8.19.6.3 `EphemerisItem*` `jeod::EphemerisItem::head` `[protected]`

The first ephemeris item with the same name as this item.

`trick_units(-)`

Definition at line 240 of file `ephem_item.hh`.

Referenced by `get_enabled_item()`, `get_head()`, `is_activatable()`, `set_head()`, and `set_target_frame()`.

8.19.6.4 `BaseEphemeridesManager*` `jeod::EphemerisItem::manager` `[protected]`

The ephemeris manager that manages this object.

`trick_units(-)`

Definition at line 230 of file `ephem_item.hh`.

Referenced by `disable()`, `enable()`, `get_manager()`, `set_manager()`, `set_target_frame()`, and `validate_name()`.

8.19.6.5 `char*` `jeod::EphemerisItem::name` `[protected]`

The name of the item.

`trick_units(-)`

Definition at line 220 of file `ephem_item.hh`.

Referenced by `activate()`, `get_name()`, `set_name()`, `set_name_internal()`, `set_target_frame()`, and `~EphemerisItem()`.

8.19.6.6 `EphemerisItem*` `jeod::EphemerisItem::next` `[protected]`

The next ephemeris item with the same name as this item.

`trick_units(-)`

Definition at line 245 of file `ephem_item.hh`.

Referenced by `get_enabled_item()`, `get_next()`, `is_activatable()`, `set_next()`, and `set_target_frame()`.

8.19.6.7 `EphemerisInterface*` `jeod::EphemerisItem::owner` `[protected]`

The ephemeris model that owns this object.

`trick_units(-)`

Definition at line 225 of file `ephem_item.hh`.

Referenced by `get_owner()`, and `set_owner()`.

8.19.6.8 EphemerisRefFrame* jeod::EphemerisItem::target_frame [protected]

The reference frame whose non-constant state is set by this object.

trick_units(-)

Definition at line 235 of file ephemeris_item.hh.

Referenced by `disable()`, `jeod::EphemerisPoint::disconnect_from_tree()`, `enable()`, `get_target_frame()`, `jeod::EphemerisPoint::initialize_state()`, `jeod::EphemerisOrientation::note_frame_status_change()`, `jeod::EphemerisPoint::note_frame_status_change()`, `jeod::EphemerisZXZOrientation::propagate()`, `set_target_frame()`, `jeod::EphemerisPoint::update()`, `jeod::EphemerisZXZOrientation::update()`, `jeod::PropagatedEphemerisPlanet::update()`, `jeod::PropagatedEphemerisOrientation::update()`, and `jeod::EphemerisPoint::update_scaled()`.

8.19.6.9 double jeod::EphemerisItem::update_time [protected]

Time of last update, dynamic time seconds.

trick_units(s)

Definition at line 250 of file ephemeris_item.hh.

Referenced by `jeod::EphemerisZXZOrientation::propagate()`, `set_timestamp()`, `timestamp()`, `jeod::EphemerisPoint::update()`, `jeod::EphemerisZXZOrientation::update()`, `jeod::PropagatedEphemerisPlanet::update()`, `jeod::PropagatedEphemerisOrientation::update()`, and `jeod::EphemerisPoint::update_scaled()`.

The documentation for this class was generated from the following files:


- [ephemeris_item.hh](#)
- [ephemeris_item_inline.hh](#)
- [ephemeris_item.cc](#)

8.20 jeod::EphemerisOrientation Class Reference

An [EphemerisOrientation](#) object updates the rotational state of an ephemeris reference frame.

```
#include <ephemeris_orient.hh>
```

Inheritance diagram for `jeod::EphemerisOrientation`:



Public Member Functions

- [EphemerisOrientation](#) ()
Construct an ephemeris angle.
- [~EphemerisOrientation](#) () override
Destroy an ephemeris angle.
- [TargetAspect updates_what](#) (void) const override

Specify the aspect of the target frame updated by the object.

- void [enable](#) () override

Enable a [EphemerisItem](#) object.

- void [note_frame_status_change](#) (RefFrame *frame) override

Null implementation.

- const char * [default_suffix](#) () const override

Return the default suffix for this item class, i.e., "pfix".

- void [disconnect_from_tree](#) () override

Disconnect the item from the tree; this is a no-op for an [EphemerisOrientation](#).

Protected Attributes

- bool [subscribed_to_inertial](#)

A subscription to the planet's inertial frame is issued whenever the planet's planet-fixed frame is active to ensure that the planet-fixed frame is a part of the ref frame tree.

Private Member Functions

- [EphemerisOrientation](#) (const [EphemerisOrientation](#) &)

Not implemented.

- [EphemerisOrientation](#) & [operator=](#) (const [EphemerisOrientation](#) &)

Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemerisOrientation](#) ()

Additional Inherited Members

8.20.1 Detailed Description

An [EphemerisOrientation](#) object updates the rotational state of an ephemeris reference frame.

Definition at line 89 of file `ephem_orient.hh`.

8.20.2 Constructor & Destructor Documentation

8.20.2.1 `jeod::EphemerisOrientation::EphemerisOrientation (void)`

Construct an ephemeris angle.

Definition at line 59 of file `ephem_orient.cc`.

8.20.2.2 `jeod::EphemerisOrientation::~~EphemerisOrientation (void)` `[override]`

Destroy an ephemeris angle.

Definition at line 71 of file `ephem_orient.cc`.

8.20.2.3 `jeod::EphemerisOrientation::EphemerisOrientation (const EphemerisOrientation &)` [private]

Not implemented.

8.20.3 Member Function Documentation

8.20.3.1 `const char * jeod::EphemerisOrientation::default_suffix (void) const` [override],[virtual]

Return the default suffix for this item class, i.e., "pfix".

Returns

Default suffix

Implements [jeod::EphemerisItem](#).

Definition at line 166 of file `ephem_orient.cc`.

8.20.3.2 `void jeod::EphemerisOrientation::disconnect_from_tree (void)` [override],[virtual]

Disconnect the item from the tree; this is a no-op for an [EphemerisOrientation](#).

Implements [jeod::EphemerisItem](#).

Definition at line 179 of file `ephem_orient.cc`.

8.20.3.3 `void jeod::EphemerisOrientation::enable (void)` [override],[virtual]

Enable a [EphemerisItem](#) object.

Reimplemented from [jeod::EphemerisItem](#).

Definition at line 96 of file `ephem_orient.cc`.

References [jeod::EphemerisItem::enable\(\)](#), [jeod::EphemerisItem::enabled](#), [jeod::EphemerisItem::get_enabled_item\(\)](#), and [subscribed_to_inertial](#).

Referenced by [jeod::De4xxEphemeris::De4xxEphemeris\(\)](#), and [jeod::PropagatedPlanet::set_mode\(\)](#).

8.20.3.4 `void jeod::EphemerisOrientation::note_frame_status_change (RefFrame * frame)` [override]

Null implementation.

Parameters

<i>in</i>	<i>frame</i>	Frame whose status has changed
-----------	--------------	--------------------------------

Definition at line 122 of file `ephem_orient.cc`.

References [jeod::EphemerisItem::activate\(\)](#), [jeod::EphemerisItem::deactivate\(\)](#), [jeod::EphemeridesMessages::internal_error](#), [subscribed_to_inertial](#), and [jeod::EphemerisItem::target_frame](#).

8.20.3.5 `EphemerisOrientation& jeod::EphemerisOrientation::operator= (const EphemerisOrientation &)`
[private]

Not implemented.

8.20.3.6 `EphemerisItem::TargetAspect` `jeod::EphemerisOrientation::updates_what (void) const` `[override]`,
`[virtual]`

Specify the aspect of the target frame updated by the object.

[EphemerisOrientation](#) objects update the rotational state.

Returns

Target of object

Implements [jeod::EphemerisItem](#).

Definition at line 84 of file `ephem_orient.cc`.

References `jeod::EphemerisItem::Rotation`.

8.20.4 Friends And Related Function Documentation

8.20.4.1 `void init_attrjeod__EphemerisOrientation ()` `[friend]`

8.20.4.2 `friend class InputProcessor` `[friend]`

Definition at line 90 of file `ephem_orient.hh`.

8.20.5 Field Documentation

8.20.5.1 `bool jeod::EphemerisOrientation::subscribed_to_inertial` `[protected]`

A subscription to the planet's inertial frame is issued whenever the planet's planet-fixed frame is active to ensure that the the planet-fixed frame is a part of the ref frame tree.

This flag is set when such a subscription is made. `trick_units(-)`

Definition at line 127 of file `ephem_orient.hh`.

Referenced by `enable()`, and `note_frame_status_change()`.

The documentation for this class was generated from the following files:


- [ephem_orient.hh](#)
- [ephem_orient.cc](#)

8.21 `jeod::EphemerisPoint` Class Reference

An [EphemerisPoint](#) object updates the translational state of an ephemeris reference frame.

```
#include <ephem_point.hh>
```

Inheritance diagram for `jeod::EphemerisPoint`:



Public Member Functions

- [EphemerisPoint](#) ()
Construct an ephemeris point.
- [~EphemerisPoint](#) () override
Destroy an ephemeris point.
- [TargetAspect updates_what](#) (void) const override
Specify the aspect of the target frame updated by the object.
- const char * [default_suffix](#) () const override
Return the default suffix for this item class, i.e., "inertial".
- void [disconnect_from_tree](#) () override
Disconnect the associated inertial frame from the tree.
- void [note_frame_status_change](#) (RefFrame *frame) override
Set active status to correspond with that of the inertial frame.
- virtual void [initialize_state](#) ()
Zero-out the inertial frame's translational state.
- virtual void [update](#) (const double *pos, const double *vel, double time)
Update the inertial frame's translational state.
- virtual void [update_scaled](#) (const double *pos, const double *vel, double scale, double time)
Update the inertial frame's translational state.

Private Member Functions

- [EphemerisPoint](#) (const [EphemerisPoint](#) &)
Not implemented.
- [EphemerisPoint](#) & [operator=](#) (const [EphemerisPoint](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemerisPoint](#) ()

Additional Inherited Members

8.21.1 Detailed Description

An [EphemerisPoint](#) object updates the translational state of an ephemeris reference frame.

Definition at line 86 of file `ephem_point.hh`.

8.21.2 Constructor & Destructor Documentation

8.21.2.1 `jeod::EphemerisPoint::EphemerisPoint (void)`

Construct an ephemeris point.

Definition at line 59 of file `ephem_point.cc`.

8.21.2.2 `jeod::EphemerisPoint::~~EphemerisPoint (void)` `[override]`

Destroy an ephemeris point.

Definition at line 71 of file `ephem_point.cc`.

8.21.2.3 `jeod::EphemerisPoint::EphemerisPoint (const EphemerisPoint &)` `[private]`

Not implemented.

8.21.3 Member Function Documentation

8.21.3.1 `const char * jeod::EphemerisPoint::default_suffix (void) const` `[override]`, `[virtual]`

Return the default suffix for this item class, i.e., "inertial".

Returns

Default suffix

Implements [jeod::EphemerisItem](#).

Definition at line 110 of file `ephem_point.cc`.

8.21.3.2 `void jeod::EphemerisPoint::disconnect_from_tree (void)` `[override]`, `[virtual]`

Disconnect the associated inertial frame from the tree.

Implements [jeod::EphemerisItem](#).

Definition at line 122 of file `ephem_point.cc`.

References [jeod::EphemerisItem::active](#), and [jeod::EphemerisItem::target_frame](#).

8.21.3.3 `void jeod::EphemerisPoint::initialize_state (void)` `[inline]`, `[virtual]`

Zero-out the inertial frame's translational state.

Definition at line 137 of file `ephem_point.cc`.

References [jeod::EphemerisItem::target_frame](#).

8.21.3.4 `void jeod::EphemerisPoint::note_frame_status_change (RefFrame * frame)` `[override]`

Set active status to correspond with that of the inertial frame.

Parameters

in	<i>frame</i>	Frame whose status has changed
----	--------------	--------------------------------

Definition at line 83 of file ephem_point.cc.

References `jeod::EphemerisItem::activate()`, `jeod::EphemerisItem::deactivate()`, `jeod::EphemeridesMessages::internal_error`, and `jeod::EphemerisItem::target_frame`.

8.21.3.5 EphemerisPoint& jeod::EphemerisPoint::operator= (const EphemerisPoint &) [private]

Not implemented.

8.21.3.6 void jeod::EphemerisPoint::update (const double * *position*, const double * *velocity*, double *time*) [virtual]

Update the inertial frame's translational state.

Parameters

in	<i>position</i>	Position wrt parent Units: M
in	<i>velocity</i>	Velocity wrt parent Units: M/s
in	<i>time</i>	Timestamp Units: s

Definition at line 154 of file ephem_point.cc.

References `jeod::EphemerisItem::target_frame`, and `jeod::EphemerisItem::update_time`.

Referenced by `jeod::De4xxEphemeris::ephem_update()`.

8.21.3.7 void jeod::EphemerisPoint::update_scaled (const double * *position*, const double * *velocity*, double *scale*, double *time*) [virtual]

Update the inertial frame's translational state.

Parameters

in	<i>position</i>	Position wrt parent Units: M
in	<i>velocity</i>	Velocity wrt parent Units: M/s
in	<i>scale</i>	Scale factor
in	<i>time</i>	Timestamp Units: s

Definition at line 176 of file ephem_point.cc.

References `jeod::EphemerisItem::target_frame`, and `jeod::EphemerisItem::update_time`.

Referenced by `jeod::De4xxEphemeris::ephem_update()`.

8.21.3.8 EphemerisItem::TargetAspect jeod::EphemerisPoint::updates_what (void) const [override], [virtual]

Specify the aspect of the target frame updated by the object.

[EphemerisPoint](#) objects update the translational state.

Returns

Target of object

Implements [jeod::EphemerisItem](#).

Definition at line 197 of file `ephem_point.cc`.

References [jeod::EphemerisItem::Translation](#).

8.21.4 Friends And Related Function Documentation

8.21.4.1 `void init_attrjeod__EphemerisPoint ()` [[friend](#)]

8.21.4.2 `friend class InputProcessor` [[friend](#)]

Definition at line 87 of file `ephem_point.hh`.

The documentation for this class was generated from the following files:


- [ephem_point.hh](#)
- [ephem_point.cc](#)

8.22 jeod::EphemerisRefFrame Class Reference

An [EphemerisRefFrame](#) is a [RefFrame](#) whose state is set by an ephemeris model.

```
#include <ephem_ref_frame.hh>
```

Inheritance diagram for `jeod::EphemerisRefFrame`:

**Public Member Functions**

- [EphemerisRefFrame](#) ()
Construct an [EphemerisRefFrame](#).
- [~EphemerisRefFrame](#) () override
Destruct an [EphemerisRefFrame](#).
- virtual void [set_ephem_manager](#) ([BaseEphemeridesManager](#) *manager)
Set the [EphemerisRefFrame](#)'s owner.

Protected Member Functions

- void [set_active_status](#) (bool new_status) override
Augment [RefFrame::set_active_status](#) by notifying the ephemerides manager that the tree might need to be rebuilt.

Protected Attributes

- [BaseEphemeridesManager](#) * [ephem_manager](#)
The ephemerides manager to which notifications of changes in ephemeris reference frame activity status are sent.

Private Member Functions

- [EphemerisRefFrame](#) (const [EphemerisRefFrame](#) &)
Not implemented.
- [EphemerisRefFrame](#) & operator= (const [EphemerisRefFrame](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemerisRefFrame](#) ()

8.22.1 Detailed Description

An [EphemerisRefFrame](#) is a [RefFrame](#) whose state is set by an ephemeris model.

Ephemeris reference frames come in three basic flavors:

- Planet-centered inertial frames. These are non-rotating frames whose origin is the center of mass of some planet (the Sun is a planet) and whose translational motion is (for now) assumed to be due to gravitation only. The orientation with respect to inertial is the identity transformation.
- Barycenter inertial frames. These are non-rotating frames whose origin is the center of mass of two or more planets.
- Planet-fixed frames. These are rotating frames whose origin is the center of mass of some planet (see ISSUE) and that rotate with the planet in question. The parent is always a planet-centered inertial frame with a zero translation offset between the planet-centered inertial and planet-fixed frames.

Only planet-centered inertial and barycenter inertial frames can serve as integration frames or as the root of the reference frame tree.

Definition at line 99 of file `ephem_ref_frame.hh`.

8.22.2 Constructor & Destructor Documentation

8.22.2.1 jeod::EphemerisRefFrame::EphemerisRefFrame (void)

Construct an [EphemerisRefFrame](#).

Definition at line 50 of file `ephem_ref_frame.cc`.

8.22.2.2 jeod::EphemerisRefFrame::~~EphemerisRefFrame (void) [override]

Destruct an [EphemerisRefFrame](#).

Definition at line 60 of file `ephem_ref_frame.cc`.

8.22.2.3 jeod::EphemerisRefFrame::EphemerisRefFrame (const EphemerisRefFrame &) [private]

Not implemented.

8.22.3 Member Function Documentation

8.22.3.1 `EphemerisRefFrame& jeod::EphemerisRefFrame::operator= (const EphemerisRefFrame &)` [private]

Not implemented.

8.22.3.2 `void jeod::EphemerisRefFrame::set_active_status (bool new_status)` [override],[protected]

Augment `RefFrame::set_active_status` by notifying the ephemerides manager that the tree might need to be rebuilt.

Parameters

in	<i>new_status</i>	Active status
----	-------------------	---------------

Definition at line 83 of file `ephem_ref_frame.cc`.

References `ephem_manager`, `jeod::BaseEphemeridesManager::ephem_note_tree_status_change()`, and `jeod::EphemeridesMessages::inconsistent_setup`.

8.22.3.3 `void jeod::EphemerisRefFrame::set_ephem_manager (BaseEphemeridesManager * manager)` [virtual]

Set the [EphemerisRefFrame](#)'s owner.

Parameters

in, out	<i>manager</i>	Ephemeris manager
---------	----------------	-------------------

Definition at line 70 of file `ephem_ref_frame.cc`.

References `ephem_manager`.

Referenced by `jeod::EphemeridesManager::set_target_frame()`.

8.22.4 Friends And Related Function Documentation

8.22.4.1 `void init_attrjeod__EphemerisRefFrame ()` [friend]

8.22.4.2 `friend class InputProcessor` [friend]

Definition at line 100 of file `ephem_ref_frame.hh`.

8.22.5 Field Documentation

8.22.5.1 `BaseEphemeridesManager* jeod::EphemerisRefFrame::ephem_manager` [protected]

The ephemerides manager to which notifications of changes in ephemeris reference frame activity status are sent.

`trick_units(-)`

Definition at line 128 of file `ephem_ref_frame.hh`.

Referenced by `set_active_status()`, and `set_ephem_manager()`.

The documentation for this class was generated from the following files:


- [ephem_ref_frame.hh](#)
- [ephem_ref_frame.cc](#)

8.23 jeod::EphemerisZXZOrientation Class Reference

The [EphemerisZXZOrientation](#) is an [EphemerisOrientation](#) subclass that updates orientation based on an Z-X-Z Euler sequence and the time derivatives of this sequence.

```
#include <ephem_orient_zxz.hh>
```

Inheritance diagram for jeod::EphemerisZXZOrientation:



Public Member Functions

- [EphemerisZXZOrientation](#) ()
Construct an ephemeris angle.
- [~EphemerisZXZOrientation](#) () override
Destroy an ephemeris angle.
- const double * [get_euler_angles](#) () const
Return the Euler angles.
- void [get_euler_angles](#) (double *angles) const
Return the Euler angles.
- const double * [get_euler_rates](#) () const
Return the Euler rates.
- void [get_euler_rates](#) (double *rates) const
Return the Euler angles.
- virtual void [update](#) (const double *angles, const double *derivs, double time)
Compute a JEOD rotational state given a 3-1-3 inertial-to-planet-fixed Euler sequence and the time derivatives of the Euler angles.
- virtual void [propagate](#) (double to_time)
Propagate the orientation to the current time.

Protected Attributes

- double [euler_angle_313](#) [3]
Astronomical (zxz) Euler angles.
- double [euler_rate_313](#) [3]
Time derivatives of the zyz Euler angles.

Private Member Functions

- [EphemerisZXZOrientation](#) (const [EphemerisZXZOrientation](#) &)
Not implemented.
- [EphemerisZXZOrientation](#) & operator= (const [EphemerisZXZOrientation](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__EphemerisZXZOrientation](#) ()

Additional Inherited Members

8.23.1 Detailed Description

The [EphemerisZXZOrientation](#) is an [EphemerisOrientation](#) subclass that updates orientation based on an Z-X-Z Euler sequence and the time derivatives of this sequence.

Definition at line 90 of file `ephem_orient_zxz.hh`.

8.23.2 Constructor & Destructor Documentation

8.23.2.1 `jeod::EphemerisZXZOrientation::EphemerisZXZOrientation (void)`

Construct an ephemeris angle.

Definition at line 80 of file `ephem_orient_zxz.cc`.

References `euler_angle_313`, and `euler_rate_313`.

8.23.2.2 `jeod::EphemerisZXZOrientation::~~EphemerisZXZOrientation (void)` [override]

Destroy an ephemeris angle.

Definition at line 93 of file `ephem_orient_zxz.cc`.

8.23.2.3 `jeod::EphemerisZXZOrientation::EphemerisZXZOrientation (const EphemerisZXZOrientation &)` [private]

Not implemented.

8.23.3 Member Function Documentation

8.23.3.1 `const double * jeod::EphemerisZXZOrientation::get_euler_angles (void) const`

Return the Euler angles.

Returns

Euler angles

Definition at line 105 of file `ephem_orient_zxz.cc`.

References `euler_angle_313`.

8.23.3.2 `void jeod::EphemerisZXZOrientation::get_euler_angles (double * angles) const`

Return the Euler angles.

Parameters

out	angles	Euler angles Units: r
-----	--------	--------------------------

Definition at line 118 of file ephem_orient_zxz.cc.

References euler_angle_313.

8.23.3.3 const double * jeod::EphemerisZXZOrientation::get_euler_rates (void) const

Return the Euler rates.

Returns

Euler rates

Definition at line 135 of file ephem_orient_zxz.cc.

References euler_rate_313.

8.23.3.4 void jeod::EphemerisZXZOrientation::get_euler_rates (double * rates) const

Return the Euler angles.

Parameters

out	rates	Euler rates Units: r/s
-----	-------	---------------------------

Definition at line 148 of file ephem_orient_zxz.cc.

References euler_rate_313.

8.23.3.5 EphemerisZXZOrientation& jeod::EphemerisZXZOrientation::operator= (const EphemerisZXZOrientation &) [private]

Not implemented.

8.23.3.6 void jeod::EphemerisZXZOrientation::propagate (double to_time) [virtual]

Propagate the orientation to the current time.

Assumptions and Limitations

- The orientation has been computed.
- Rotation is constant during the update interval.

Parameters

in	to_time	Target dynamic time Units: s
----	---------	---------------------------------

Definition at line 167 of file ephem_orient_zxz.cc.

References EPSILON_TIME, jeod::EphemerisItem::target_frame, TAYLOR_CUTOFF, and jeod::EphemerisItem::update_time.

Referenced by jeod::De4xxEphemeris::propagate_lunar_rnp().

8.23.3.7 `void jeod::EphemerisZXZOrientation::update (const double * angles, const double * derivs, double time)`
`[virtual]`

Compute a JEOD rotational state given a 3-1-3 inertial-to-planet-fixed Euler sequence and the time derivatives of the Euler angles.

Parameters

in	<i>angles</i>	zxz Euler angles Units: r
in	<i>derivs</i>	zxz Euler angle time derivatives Units: r/s
in	<i>time</i>	Update time Units: s

Definition at line 230 of file `ephem_orient_zxz.cc`.

References `euler_angle_313`, `euler_rate_313`, `jeod::EphemerisItem::target_frame`, and `jeod::EphemerisItem::update_time`.

Referenced by `jeod::De4xxEphemeris::ephem_update()`.

8.23.4 Friends And Related Function Documentation

8.23.4.1 `void init_attrjeod__EphemerisZXZOrientation ()` `[friend]`

8.23.4.2 `friend class InputProcessor` `[friend]`

Definition at line 91 of file `ephem_orient_zxz.hh`.

8.23.5 Field Documentation

8.23.5.1 `double jeod::EphemerisZXZOrientation::euler_angle_313[3]` `[protected]`

Astronomical (zxz) Euler angles.

`trick_units(rad)`

Definition at line 130 of file `ephem_orient_zxz.hh`.

Referenced by `EphemerisZXZOrientation()`, `get_euler_angles()`, and `update()`.

8.23.5.2 `double jeod::EphemerisZXZOrientation::euler_rate_313[3]` `[protected]`

Time derivatives of the zyz Euler angles.

`trick_units(rad/s)`

Definition at line 135 of file `ephem_orient_zxz.hh`.

Referenced by `EphemerisZXZOrientation()`, `get_euler_rates()`, and `update()`.

The documentation for this class was generated from the following files:


- [ephem_orient_zxz.hh](#)
- [ephem_orient_zxz.cc](#)

8.24 jeod::PropagatedEphemerisOrientation Class Reference

A [PropagatedEphemerisOrientation](#) is an [EphemerisOrientation](#) whose state is coupled with the rotational state of a `DynBody` reference frame.

```
#include <propagated_planet.hh>
```

Inheritance diagram for `jeod::PropagatedEphemerisOrientation`:



Public Member Functions

- [PropagatedEphemerisOrientation](#) (DynBody &dyn_body, BodyRefFrame &frame)
[PropagatedEphemerisOrientation](#) non-default constructor.
- [~PropagatedEphemerisOrientation](#) (void) override
[PropagatedEphemerisOrientation](#) destructor.
- virtual void [update](#) (double time)
Copy rotational state from/to the body reference frame.

Protected Attributes

- DynBody & [body](#)
The dynamic body whose state is tied to that of the planet.
- BodyRefFrame & [body_ref_frame](#)
The body reference frame whose rotational state is coupled with that of the planet's planet-fixed frame.

Private Member Functions

- [PropagatedEphemerisOrientation](#) (const [PropagatedEphemerisOrientation](#) &)
Not implemented.
- [PropagatedEphemerisOrientation](#) & operator= (const [PropagatedEphemerisOrientation](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__PropagatedEphemerisOrientation](#) ()

Additional Inherited Members

8.24.1 Detailed Description

A [PropagatedEphemerisOrientation](#) is an [EphemerisOrientation](#) whose state is coupled with the rotational state of a DynBody reference frame.

This class is intended for use by the [PropagatedPlanet](#) class. Use outside of the [PropagatedPlanet](#) is not sanctioned.

The class acts analogously to the class [PropagatedEphemerisPlanet](#), but for rotation rather than translation. See [PropagatedEphemerisPlanet](#) for a description of the behavior of the class.

Definition at line 179 of file `propagated_planet.hh`.

8.24.2 Constructor & Destructor Documentation

8.24.2.1 `jeod::PropagatedEphemerisOrientation::PropagatedEphemerisOrientation (DynBody & dyn_body, BodyRefFrame & frame)`

[PropagatedEphemerisOrientation](#) non-default constructor.

Parameters

<i>in, out</i>	<i>dyn_body</i>	The DynBody that represents the planet
<i>in, out</i>	<i>frame</i>	The body reference frame

Definition at line 127 of file `propagated_planet.cc`.

8.24.2.2 `jeod::PropagatedEphemerisOrientation::~~PropagatedEphemerisOrientation (void)` `[override]`

[PropagatedEphemerisOrientation](#) destructor.

Definition at line 142 of file `propagated_planet.cc`.

8.24.2.3 `jeod::PropagatedEphemerisOrientation::PropagatedEphemerisOrientation (const PropagatedEphemerisOrientation &)` `[private]`

Not implemented.

8.24.3 Member Function Documentation

8.24.3.1 `PropagatedEphemerisOrientation& jeod::PropagatedEphemerisOrientation::operator= (const PropagatedEphemerisOrientation &)` `[private]`

Not implemented.

8.24.3.2 `void jeod::PropagatedEphemerisOrientation::update (double dyn_time)` `[virtual]`

Copy rotational state from/to the body reference frame.

Parameters

<i>in</i>	<i>dyn_time</i>	Dynamic time seconds Units: s
-----------	-----------------	----------------------------------

Definition at line 154 of file `propagated_planet.cc`.

References `body`, `body_ref_frame`, `jeod::EphemerisItem::enabled`, `jeod::EphemerisItem::target_frame`, and `jeod::EphemerisItem::update_time`.

Referenced by `jeod::PropagatedPlanet::ephem_update()`.

8.24.4 Friends And Related Function Documentation

8.24.4.1 `void init_attrjeod__PropagatedEphemerisOrientation ()` `[friend]`

8.24.4.2 `friend class InputProcessor` `[friend]`

Definition at line 180 of file `propagated_planet.hh`.

8.24.5 Field Documentation

8.24.5.1 DynBody& jeod::PropagatedEphemerisOrientation::body [protected]

The dynamic body whose state is tied to that of the planet.

trick_units(–)

Definition at line 208 of file propagated_planet.hh.

Referenced by update().

8.24.5.2 BodyRefFrame& jeod::PropagatedEphemerisOrientation::body_ref_frame [protected]

The body reference frame whose rotational state is coupled with that of the planet's planet-fixed frame.

trick_units(–)

Definition at line 214 of file propagated_planet.hh.

Referenced by update().

The documentation for this class was generated from the following files:


- [propagated_planet.hh](#)
- [propagated_planet.cc](#)

8.25 jeod::PropagatedEphemerisPlanet Class Reference

A [PropagatedEphemerisPlanet](#) is an [EphemerisPoint](#) whose state is coupled with the translational state of a Dyn-Body reference frame.

```
#include <propagated_planet.hh>
```

Inheritance diagram for jeod::PropagatedEphemerisPlanet:



Public Member Functions

- [PropagatedEphemerisPlanet](#) (DynBody &dyn_body, BodyRefFrame &frame)
PropagatedEphemerisPlanet non-default constructor.
- [~PropagatedEphemerisPlanet](#) (void) override
PropagatedEphemerisPlanet destructor.
- virtual void [update](#) (double time)
Copy rotational state from/to the body reference frame.

Protected Attributes

- DynBody & [body](#)
The dynamic body whose state is tied to that of the planet.
- BodyRefFrame & [body_ref_frame](#)
The body reference frame whose translational state is coupled with that of the planet's inertial frame.

Private Member Functions

- [PropagatedEphemerisPlanet](#) (const [PropagatedEphemerisPlanet](#) &)
Not implemented.
- [PropagatedEphemerisPlanet](#) & operator= (const [PropagatedEphemerisPlanet](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__PropagatedEphemerisPlanet](#) ()

Additional Inherited Members

8.25.1 Detailed Description

A [PropagatedEphemerisPlanet](#) is an [EphemerisPoint](#) whose state is coupled with the translational state of a DynBody reference frame.

This class is intended for use by the [PropagatedPlanet](#) class. Use outside of the [PropagatedPlanet](#) is not sanctioned.

The inherited enabled flag takes on an additional meaning in this derived class. The base class meaning of this flag is that the ephemeris item, or the ephemeris model that owns the item, is responsible for maintaining the translational state of the target frame when the item is enabled but not when the item is disabled.

For this class, when the enabled flag is set still means that the item is responsible for maintaining the translational state of the target ephemeris reference frame. The dynamic body serves as the source of this state. When the enabled flag is clear, some other model is assumed to be responsible for maintaining the target frame state. The target frame state serves as the source of the dynamic body's state when the enabled flag is clear. A [PropagatedEphemerisPlanet](#) is an [EphemerisPoint](#) whose state is coupled with the translational state of a DynBody reference frame.

This class is intended for use by the [PropagatedPlanet](#) class. Use outside of the [PropagatedPlanet](#) is not sanctioned.

The class acts analogously to the class [PropagatedEphemerisOrientation](#), but for translation rather than rotation. See [PropagatedEphemerisOrientation](#) for a description of the behavior of the class.

Definition at line 119 of file `propagated_planet.hh`.

8.25.2 Constructor & Destructor Documentation

8.25.2.1 `jeod::PropagatedEphemerisPlanet::PropagatedEphemerisPlanet (DynBody & dyn_body, BodyRefFrame & frame)`

[PropagatedEphemerisPlanet](#) non-default constructor.

Parameters

<i>in, out</i>	<i>dyn_body</i>	The DynBody that represents the planet
<i>in, out</i>	<i>frame</i>	The body reference frame

Definition at line 188 of file propagated_planet.cc.

8.25.2.2 `jeod::PropagatedEphemerisPlanet::~~PropagatedEphemerisPlanet (void)` `[override]`

[PropagatedEphemerisPlanet](#) destructor.

Definition at line 81 of file propagated_planet.cc.

8.25.2.3 `jeod::PropagatedEphemerisPlanet::PropagatedEphemerisPlanet (const PropagatedEphemerisPlanet &)`
`[private]`

Not implemented.

8.25.3 Member Function Documentation

8.25.3.1 `PropagatedEphemerisPlanet& jeod::PropagatedEphemerisPlanet::operator= (const PropagatedEphemerisPlanet &)` `[private]`

Not implemented.

8.25.3.2 `void jeod::PropagatedEphemerisPlanet::update (double dyn_time)` `[virtual]`

Copy rotational state from/to the body reference frame.

Parameters

<i>in</i>	<i>dyn_time</i>	Dynamic time seconds Units: s
-----------	-----------------	----------------------------------

Definition at line 93 of file propagated_planet.cc.

References `body`, `body_ref_frame`, `jeod::EphemerisItem::enabled`, `jeod::EphemerisItem::target_frame`, and `jeod::EphemerisItem::update_time`.

Referenced by `jeod::PropagatedPlanet::ephem_update()`.

8.25.4 Friends And Related Function Documentation

8.25.4.1 `void init_attrjeod__PropagatedEphemerisPlanet ()` `[friend]`

8.25.4.2 `friend class InputProcessor` `[friend]`

Definition at line 120 of file propagated_planet.hh.

8.25.5 Field Documentation

8.25.5.1 `DynBody& jeod::PropagatedEphemerisPlanet::body` `[protected]`

The dynamic body whose state is tied to that of the planet.

`trick_units(-)`

Definition at line 157 of file propagated_planet.hh.

Referenced by update().

8.25.5.2 BodyRefFrame& jeod::PropagatedEphemerisPlanet::body_ref_frame [protected]

The body reference frame whose translational state is coupled with that of the planet's inertial frame.

trick_units(–)

Definition at line 163 of file propagated_planet.hh.

Referenced by update().

The documentation for this class was generated from the following files:


- [propagated_planet.hh](#)
- [propagated_planet.cc](#)

8.26 jeod::PropagatedPlanet Class Reference

The [PropagatedPlanet](#) ephemeris model provides planetary state via a DynBody object whose state is propagated using the JEOD state integration techniques.

```
#include <propagated_planet.hh>
```

Inheritance diagram for jeod::PropagatedPlanet:



Public Types

- enum [Mode](#) { [TransFromPlanet_RotFromPlanet](#) = 0, [TransFromPlanet_RotFromBody](#) = 1, [TransFromBody_RotFromPlanet](#) = 2, [TransFromBody_RotFromBody](#) = 3 }

Defines the modes in which an active [PropagatedPlanet](#) object operates.

Public Member Functions

- [PropagatedPlanet](#) (void)
[PropagatedPlanet](#) default constructor.
- [~PropagatedPlanet](#) (void) override
[PropagatedPlanet](#) destructor.
- void [initialize_model](#) (const TimeManager &time_manager, DynManager &dyn_manager)
Initialize a [PropagatedPlanet](#) model.
- void [shutdown](#) (void)
Free resources allocated by the [PropagatedPlanet](#) model.
- void [activate](#) (void) override
Nominally, activate the object.
- void [deactivate](#) (void) override

- Deactivate the [PropagatedPlanet](#) object.
- double [timestamp](#) (void) const override
Return time of last update.
- const char * [get_name](#) (void) const override
Return model name.
- void [ephem_initialize](#) ([EphemeridesManager](#) &ephem_manager) override
Mark appropriate items in the model as active.
- void [ephem_activate](#) ([EphemeridesManager](#) &ephem_manager) override
Activate ephemerides.
- void [ephem_build_tree](#) ([EphemeridesManager](#) &ephem_manager) override
Construct the ephemeris model portions of the reference frame tree.
- void [ephem_update](#) (void) override
Update ephemerides for subscribed items.
- void [set_commanded_mode](#) ([Mode](#) new_mode)
Setter for the commanded mode.

Data Fields

- char * [planet_name](#)
The name of the planet.
- char * [parent_name](#)
The name of the parent frame.
- DynBody [body](#)
The dynamic body whose state is tied to that of the planet.
- [Mode](#) [commanded_mode](#)
The mode in which the model should operate.

Protected Member Functions

- void [set_mode](#) (void)
Change the behavior of a [PropagatedPlanet](#).

Protected Attributes

- bool [initialized](#)
Has the model been initialized?
- [Mode](#) [mode](#)
The mode in which the model is operating.
- char * [ident](#)
Model name; used for reporting errors.
- bool [active](#)
Is the planet present and marked as active?
- double [update_time](#)
Time of last update, dynamic time seconds.
- BasePlanet * [planet](#)
The planet tied to the body.
- [EphemerisRefFrame](#) * [parent_frame](#)
The parent of the planet.
- DynManager * [dyn_manager](#)
The dynamics manager.

- const TimeDyn * [time_dyn](#)
The source of dynamic time information.
- [PropagatedEphemerisPlanet](#) [ephem_planet](#)
The ephemeris item that couples the translational states of the body's composite body frame and the planet's inertial frame.
- [PropagatedEphemerisOrientation](#) [ephem_orient](#)
The ephemeris item that couples the rotational states of the body's composite body frame and the planet's planet-fixed frame.

Private Member Functions

- [PropagatedPlanet](#) (const [PropagatedPlanet](#) &)
Not implemented.
- [PropagatedPlanet](#) & [operator=](#) (const [PropagatedPlanet](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__PropagatedPlanet](#) ()

8.26.1 Detailed Description

The [PropagatedPlanet](#) ephemeris model provides planetary state via a DynBody object whose state is propagated using the JEOD state integration techniques.

Scenarios in which a simulation will use a [PropagatedPlanet](#) object include:

- An object such as an asteroid for which an ephemeris model is not readily available.
- An object such as a planet that is represented in some other ephemeris model but the simulation developer wants the planet to be propagated to ensure that the planet and the vehicles operating in the vicinity of the planet obey the same laws of physics.

The [PropagatedPlanet](#) model provides mechanisms that accommodate these scenarios. The class defines multiple modes in which a propagated planet object operates. In all modes, the model ensures consistency between the translational states of the dynamic body's composite frame and the planet's planet-centered frame and between the rotational states of the dynamic body's composite frame and the planet's planet-fixed frame.

Definition at line 246 of file [propagated_planet.hh](#).

8.26.2 Member Enumeration Documentation

8.26.2.1 enum jeod::PropagatedPlanet::Mode

Defines the modes in which an active [PropagatedPlanet](#) object operates.

A [PropagatedPlanet](#) contains a BasePlanet pointer [PropagatedPlanet::planet](#) and a DynBody [PropagatedPlanet::body](#). The translational states of the planet-centered inertial frame and the body's composite_body frame are tied to one another, as are the rotational states of the planet-fixed frame and the the body's composite_body frame. This enum identifies which of the planet or the body is the source of translational and the the rotational parts of the state.

Enumerator

TransFromPlanet_RotFromPlanet
TransFromPlanet_RotFromBody

TransFromBody_RotFromPlanet

TransFromBody_RotFromBody

Definition at line 263 of file propagated_planet.hh.

8.26.3 Constructor & Destructor Documentation

8.26.3.1 jeod::PropagatedPlanet::PropagatedPlanet (void)

[PropagatedPlanet](#) default constructor.

Definition at line 203 of file propagated_planet.cc.

References `ephem_orient`, `ephem_planet`, and `jeod::EphemerisItem::set_owner()`.

8.26.3.2 jeod::PropagatedPlanet::~~PropagatedPlanet (void) [override]

[PropagatedPlanet](#) destructor.

Definition at line 230 of file propagated_planet.cc.

References `shutdown()`.

8.26.3.3 jeod::PropagatedPlanet::PropagatedPlanet (const PropagatedPlanet &) [private]

Not implemented.

8.26.4 Member Function Documentation

8.26.4.1 void jeod::PropagatedPlanet::activate (void) [override]

Nominally, activate the object.

In the case of a [PropagatedPlanet](#) object, an inactive object cannot be activated.

Definition at line 258 of file propagated_planet.cc.

References `active`, and `jeod::EphemeridesMessages::internal_error`.

8.26.4.2 void jeod::PropagatedPlanet::deactivate (void) [override]

Deactivate the [PropagatedPlanet](#) object.

Definition at line 275 of file propagated_planet.cc.

References `active`.

8.26.4.3 void jeod::PropagatedPlanet::ephem_activate (EphemeridesManager & ephem_manager) [override], [virtual]

Activate ephemerides.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Definition at line 512 of file propagated_planet.cc.

References `body`, `mode`, `TransFromBody_RotFromBody`, `TransFromBody_RotFromPlanet`, and `TransFromPlanet_RotFromBody`.

8.26.4.4 `void jeod::PropagatedPlanet::ephem_build_tree (EphemeridesManager & ephem_manager)` `[override]`, `[virtual]`

Construct the ephemeris model portions of the reference frame tree.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Definition at line 534 of file propagated_planet.cc.

References `active`, `parent_frame`, and `planet`.

8.26.4.5 `void jeod::PropagatedPlanet::ephem_initialize (EphemeridesManager & ephem_manager)` `[override]`, `[virtual]`

Mark appropriate items in the model as active.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Definition at line 396 of file propagated_planet.cc.

References `active`, `ephem_orient`, `ephem_planet`, `jeod::EphemeridesManager::find_base_planet()`, `jeod::EphemerisItem::get_target_frame()`, `jeod::EphemeridesMessages::inconsistent_setup`, `planet`, `planet_name`, `set_mode()`, and `jeod::EphemeridesManager::set_target_frame()`.

8.26.4.6 `void jeod::PropagatedPlanet::ephem_update (void)` `[override]`, `[virtual]`

Update ephemerides for subscribed items.

Implements [jeod::EphemerisInterface](#).

Definition at line 555 of file propagated_planet.cc.

References `active`, `body`, `commanded_mode`, `dyn_manager`, `ephem_orient`, `ephem_planet`, `initialized`, `mode`, `set_mode()`, `time_dyn`, `TransFromBody_RotFromBody`, `jeod::PropagatedEphemerisPlanet::update()`, `jeod::PropagatedEphemerisOrientation::update()`, and `update_time`.

8.26.4.7 `const char * jeod::PropagatedPlanet::get_name (void) const` `[override]`, `[virtual]`

Return model name.

Returns

Name

Implements [jeod::EphemerisInterface](#).

Definition at line 302 of file propagated_planet.cc.

References ident.

8.26.4.8 `void jeod::PropagatedPlanet::initialize_model (const TimeManager & time_manager, DynManager & dyn_manager_ref)`

Initialize a [PropagatedPlanet](#) model.

Assumptions and Limitations

- This method must be called after the ephemeris model that defines the parent frame has been initialized.

Parameters

in	<i>time_manager</i>	Time manager
in, out	<i>dyn_manager_ref</i>	Dynamics manager

Definition at line 320 of file propagated_planet.cc.

References active, body, dyn_manager, ephemeris_orient, ephemeris_planet, ident, jeod::EphemeridesMessages::inconsistent_setup, parent_frame, parent_name, planet_name, jeod::EphemerisItem::set_name(), and time_dyn.

8.26.4.9 `PropagatedPlanet& jeod::PropagatedPlanet::operator= (const PropagatedPlanet &) [private]`

Not implemented.

8.26.4.10 `void jeod::PropagatedPlanet::set_commanded_mode (PropagatedPlanet::Mode new_mode)`

Setter for the commanded mode.

Parameters

in	<i>new_mode</i>	New commanded mode
----	-----------------	--------------------

Definition at line 453 of file propagated_planet.cc.

References commanded_mode.

8.26.4.11 `void jeod::PropagatedPlanet::set_mode (void) [protected]`

Change the behavior of a [PropagatedPlanet](#).

Definition at line 464 of file propagated_planet.cc.

References commanded_mode, jeod::EphemerisItem::disable(), dyn_manager, jeod::EphemerisOrientation::enable(), jeod::EphemerisItem::enable(), ephemeris_orient, ephemeris_planet, jeod::EphemeridesMessages::inconsistent_setup, mode, TransFromBody_RotFromBody, TransFromBody_RotFromPlanet, TransFromPlanet_RotFromBody, and TransFromPlanet_RotFromPlanet.

Referenced by ephemeris_initialize(), and ephemeris_update().

8.26.4.12 `void jeod::PropagatedPlanet::shutdown (void)`

Free resources allocated by the [PropagatedPlanet](#) model.

Definition at line 241 of file propagated_planet.cc.

References ident.

Referenced by ~PropagatedPlanet().

8.26.4.13 `double jeod::PropagatedPlanet::timestamp (void) const` `[override],[virtual]`

Return time of last update.

Returns

Timestamp
Units: day

Implements [jeod::EphemerisInterface](#).

Definition at line 289 of file `propagated_planet.cc`.

References `update_time`.

8.26.5 Friends And Related Function Documentation

8.26.5.1 `void init_attrjeod__PropagatedPlanet ()` `[friend]`

8.26.5.2 `friend class InputProcessor` `[friend]`

Definition at line 247 of file `propagated_planet.hh`.

8.26.6 Field Documentation

8.26.6.1 `bool jeod::PropagatedPlanet::active` `[protected]`

Is the planet present and marked as active?

`trick_units(-)`

Definition at line 378 of file `propagated_planet.hh`.

Referenced by `activate()`, `deactivate()`, `ephem_build_tree()`, `ephem_initialize()`, `ephem_update()`, and `initialize_model()`.

8.26.6.2 `DynBody jeod::PropagatedPlanet::body`

The dynamic body whose state is tied to that of the planet.

`trick_units(-)`

Definition at line 342 of file `propagated_planet.hh`.

Referenced by `ephem_activate()`, `ephem_update()`, and `initialize_model()`.

8.26.6.3 `Mode jeod::PropagatedPlanet::commanded_mode`

The mode in which the model should operate.

`trick_units(-)`

Definition at line 347 of file `propagated_planet.hh`.

Referenced by `ephem_update()`, `set_commanded_mode()`, and `set_mode()`.

8.26.6.4 `DynManager* jeod::PropagatedPlanet::dyn_manager` `[protected]`

The dynamics manager.

trick_units(–)

Definition at line 398 of file propagated_planet.hh.

Referenced by ephem_update(), initialize_model(), and set_mode().

8.26.6.5 **PropagatedEphemerisOrientation** jeod::PropagatedPlanet::ephem_orient [protected]

The ephemeris item that couples the rotational states of the body's composite body frame and the planet's planet-fixed frame.

trick_units(–)

Definition at line 415 of file propagated_planet.hh.

Referenced by ephem_initialize(), ephem_update(), initialize_model(), PropagatedPlanet(), and set_mode().

8.26.6.6 **PropagatedEphemerisPlanet** jeod::PropagatedPlanet::ephem_planet [protected]

The ephemeris item that couples the translational states of the body's composite body frame and the planet's inertial frame.

trick_units(–)

Definition at line 409 of file propagated_planet.hh.

Referenced by ephem_initialize(), ephem_update(), initialize_model(), PropagatedPlanet(), and set_mode().

8.26.6.7 **char*** jeod::PropagatedPlanet::ident [protected]

Model name; used for reporting errors.

trick_units(–)

Definition at line 373 of file propagated_planet.hh.

Referenced by get_name(), initialize_model(), and shutdown().

8.26.6.8 **bool** jeod::PropagatedPlanet::initialized [protected]

Has the model been initialized?

trick_units(–)

Definition at line 363 of file propagated_planet.hh.

Referenced by ephem_update().

8.26.6.9 **Mode** jeod::PropagatedPlanet::mode [protected]

The mode in which the model is operating.

trick_units(–)

Definition at line 368 of file propagated_planet.hh.

Referenced by ephem_activate(), ephem_update(), and set_mode().

8.26.6.10 **EphemerisRefFrame*** jeod::PropagatedPlanet::parent_frame [protected]

The parent of the planet.

trick_units(–)

Definition at line 393 of file propagated_planet.hh.

Referenced by ephem_build_tree(), and initialize_model().

8.26.6.11 char* jeod::PropagatedPlanet::parent_name

The name of the parent frame.

This is used at initialization time only.trick_units(–)

Definition at line 337 of file propagated_planet.hh.

Referenced by initialize_model().

8.26.6.12 BasePlanet* jeod::PropagatedPlanet::planet [protected]

The planet tied to the body.

trick_units(–)

Definition at line 388 of file propagated_planet.hh.

Referenced by ephem_build_tree(), and ephem_initialize().

8.26.6.13 char* jeod::PropagatedPlanet::planet_name

The name of the planet.

This is used at initialization time only.trick_units(–)

Definition at line 331 of file propagated_planet.hh.

Referenced by ephem_initialize(), and initialize_model().

8.26.6.14 const TimeDyn* jeod::PropagatedPlanet::time_dyn [protected]

The source of dynamic time information.

trick_units(–)

Definition at line 403 of file propagated_planet.hh.

Referenced by ephem_update(), and initialize_model().

8.26.6.15 double jeod::PropagatedPlanet::update_time [protected]

Time of last update, dynamic time seconds.

trick_units(s)

Definition at line 383 of file propagated_planet.hh.

Referenced by ephem_update(), and timestamp().

The documentation for this class was generated from the following files:


- [propagated_planet.hh](#)
- [propagated_planet.cc](#)

8.27 jeod::SinglePlanetEphemeris Class Reference

A space with one gravitation body has one ephemeris point.

```
#include <simple_ephemerides.hh>
```

Inheritance diagram for jeod::SinglePlanetEphemeris:



Public Member Functions

- [SinglePlanetEphemeris](#) (void)
Construct an [SinglePlanetEphemeris](#) object.
- [~SinglePlanetEphemeris](#) (void) override
Destruct an [SinglePlanetEphemeris](#) object.
- void [set_name](#) (const char *frame_name) override
Set the name of a [SinglePlanetEphemeris](#) object.
- void [initialize_model](#) ([EphemeridesManager](#) &ephem_manager) override
Initialize a [SinglePlanetEphemeris](#) object.
- void [ephem_initialize](#) ([EphemeridesManager](#) &ephem_manager) override
Initialize a [SinglePlanetEphemeris](#) object.
- void [ephem_activate](#) ([EphemeridesManager](#) &ephem_manager) override
Activate a [SinglePlanetEphemeris](#) object.
- void [ephem_build_tree](#) ([EphemeridesManager](#) &ephem_manager) override
Build the reference frame tree with the central frame as the root.

Protected Attributes

- [EphemerisPoint](#) central_point
The [EphemerisPoint](#) that represents the center of a simple universe.

Private Member Functions

- [SinglePlanetEphemeris](#) (const [SinglePlanetEphemeris](#) &)
Not implemented.
- [SinglePlanetEphemeris](#) & operator= (const [SinglePlanetEphemeris](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__SinglePlanetEphemeris](#) ()

8.27.1 Detailed Description

A space with one gravitation body has one ephemeris point.

Note well: A [SinglePlanetEphemeris](#) does not contain a Planet object. The planet must be specified elsewhere.

Definition at line 257 of file simple_ephemerides.hh.

8.27.2 Constructor & Destructor Documentation

8.27.2.1 jeod::SinglePlanetEphemeris::SinglePlanetEphemeris (void)

Construct an [SinglePlanetEphemeris](#) object.

Definition at line 286 of file simple_ephemerides.cc.

References `central_point`, `jeod::EphemerisItem::enable()`, and `jeod::EphemerisItem::set_owner()`.

8.27.2.2 jeod::SinglePlanetEphemeris::~~SinglePlanetEphemeris (void) [override]

Destruct an [SinglePlanetEphemeris](#) object.

Definition at line 297 of file simple_ephemerides.cc.

8.27.2.3 jeod::SinglePlanetEphemeris::SinglePlanetEphemeris (const SinglePlanetEphemeris &) [private]

Not implemented.

8.27.3 Member Function Documentation

8.27.3.1 void jeod::SinglePlanetEphemeris::ephem_activate (EphemeridesManager & *ephem_manager*) [override], [virtual]

Activate a [SinglePlanetEphemeris](#) object.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 400 of file simple_ephemerides.cc.

8.27.3.2 void jeod::SinglePlanetEphemeris::ephem_build_tree (EphemeridesManager & *ephem_manager*) [override], [virtual]

Build the reference frame tree with the central frame as the root.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 412 of file simple_ephemerides.cc.

References `jeod::SinglePointEphemeris::active`, `central_point`, and `jeod::EphemerisItem::get_target_frame()`.

8.27.3.3 `void jeod::SinglePlanetEphemeris::ephem_initialize (EphemeridesManager & ephem_manager)`
[`override`], [`virtual`]

Initialize a [SinglePlanetEphemeris](#) object.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 355 of file `simple_ephemerides.cc`.

References `jeod::SinglePointEphemeris::active`, `central_point`, `jeod::SinglePointEphemeris::deactivate()`, `jeod::EphemerisItem::disable()`, `jeod::EphemeridesManager::find_base_planet()`, `jeod::EphemeridesManager::get_num_planets()`, `jeod::EphemerisItem::get_target_frame()`, `jeod::SinglePointEphemeris::identifier`, and `jeod::EphemeridesMessages::inconsistent_setup`.

8.27.3.4 `void jeod::SinglePlanetEphemeris::initialize_model (EphemeridesManager & ephem_manager)`
`[override], [virtual]`

Initialize a [SinglePlanetEphemeris](#) object.

Parameters

<i>in, out</i>	<i>ephem_manager</i>	Ephemerides manager
----------------	----------------------	---------------------

Implements [jeod::SinglePointEphemeris](#).

Definition at line 336 of file `simple_ephemerides.cc`.

References `jeod::SinglePointEphemeris::active`, `jeod::EphemeridesManager::add_ephem_item()`, `jeod::EphemeridesManager::add_ephemeris()`, and `central_point`.

8.27.3.5 `SinglePlanetEphemeris& jeod::SinglePlanetEphemeris::operator= (const SinglePlanetEphemeris &)`
`[private]`

Not implemented.

8.27.3.6 `void jeod::SinglePlanetEphemeris::set_name (const char * new_name)` `[override], [virtual]`

Set the name of a [SinglePlanetEphemeris](#) object.

Parameters

<i>in, out</i>	<i>new_name</i>	Central point name
----------------	-----------------	--------------------

Reimplemented from [jeod::SinglePointEphemeris](#).

Definition at line 309 of file `simple_ephemerides.cc`.

References `central_point`, `jeod::SinglePointEphemeris::set_name()`, and `jeod::EphemerisItem::set_name()`.

8.27.4 Friends And Related Function Documentation

8.27.4.1 `void init_attrjeod_SinglePlanetEphemeris ()` `[friend]`

8.27.4.2 `friend class InputProcessor` `[friend]`

Definition at line 259 of file `simple_ephemerides.hh`.

8.27.5 Field Documentation

8.27.5.1 EphemerisPoint jeod::SinglePlanetEphemeris::central_point [protected]

The [EphemerisPoint](#) that represents the center of a simple universe.

trick_units(-)

Definition at line 288 of file simple_ephemerides.hh.

Referenced by `ephem_build_tree()`, `ephem_initialize()`, `initialize_model()`, `set_name()`, and `SinglePlanetEphemeris()`.

The documentation for this class was generated from the following files:


- [simple_ephemerides.hh](#)
- [simple_ephemerides.cc](#)

8.28 jeod::SinglePointEphemeris Class Reference

A [SinglePointEphemeris](#) has one ephemeris point.

```
#include <simple_ephemerides.hh>
```

Inheritance diagram for `jeod::SinglePointEphemeris`:



Public Member Functions

- [SinglePointEphemeris](#) (void)
Construct a [SinglePointEphemeris](#) object.
- [~SinglePointEphemeris](#) (void) override
Destruct a [SinglePointEphemeris](#) object.
- virtual void [set_name](#) (const char *new_name)
Set the name of a [SinglePointEphemeris](#) object.
- void [activate](#) (void) override
Nominally, activate the model.
- void [deactivate](#) (void) override
Deactivate the model.
- double [timestamp](#) (void) const override
Retrieve the timestamp.
- const char * [get_name](#) (void) const override
Retrieve the identifier.
- void [ephem_update](#) (void) override
Update the ephemerides, which in this case is a no-op.
- virtual void [initialize_model](#) ([EphemeridesManager](#) &manager)=0
Register the model and its ephemeris points.

- void [ephem_initialize](#) ([EphemeridesManager](#) &manager) override=0
Initialize the ephemerides.
- void [ephem_activate](#) ([EphemeridesManager](#) &manager) override=0
Activate the model.
- void [ephem_build_tree](#) ([EphemeridesManager](#) &manager) override=0
Build the model's contribution to the reference frame tree.

Protected Attributes

- char * [identifier](#)
Identifier for this model.
- double [update_time](#)
Time of last update, dynamic time seconds.
- bool [active](#)
Is the model active?

Private Member Functions

- [SinglePointEphemeris](#) (const [SinglePointEphemeris](#) &)
Not implemented.
- [SinglePointEphemeris](#) & [operator=](#) (const [SinglePointEphemeris](#) &)
Not implemented.

Friends

- class [InputProcessor](#)
- void [init_attrjeod__SinglePointEphemeris](#) ()

8.28.1 Detailed Description

A [SinglePointEphemeris](#) has one ephemeris point.
Definition at line 85 of file `simple_ephemerides.hh`.

8.28.2 Constructor & Destructor Documentation

8.28.2.1 `jeod::SinglePointEphemeris::SinglePointEphemeris (void)`

Construct a [SinglePointEphemeris](#) object.
Definition at line 63 of file `simple_ephemerides.cc`.

8.28.2.2 `jeod::SinglePointEphemeris::~~SinglePointEphemeris (void)` `[override]`

Destruct a [SinglePointEphemeris](#) object.
Definition at line 77 of file `simple_ephemerides.cc`.
References `identifier`.

8.28.2.3 `jeod::SinglePointEphemeris::SinglePointEphemeris (const SinglePointEphemeris &)` `[private]`

Not implemented.

8.28.3 Member Function Documentation

8.28.3.1 `void jeod::SinglePointEphemeris::activate (void) [override]`

Nominally, activate the model.

Here, reject the request.

Definition at line 90 of file `simple_ephemerides.cc`.

References `active`, and `jeod::EphemeridesMessages::internal_error`.

8.28.3.2 `void jeod::SinglePointEphemeris::deactivate (void) [override]`

Deactivate the model.

Definition at line 105 of file `simple_ephemerides.cc`.

References `active`.

Referenced by `jeod::EmptySpaceEphemeris::ephem_initialize()`, and `jeod::SinglePlanetEphemeris::ephem_initialize()`.

8.28.3.3 `void jeod::SinglePointEphemeris::ephem_activate (EphemeridesManager & manager) [override], [pure virtual]`

Activate the model.

Parameters

<code>in, out</code>	<code>manager</code>	Ephemerides manager
----------------------	----------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Implemented in [jeod::SinglePlanetEphemeris](#), and [jeod::EmptySpaceEphemeris](#).

8.28.3.4 `void jeod::SinglePointEphemeris::ephem_build_tree (EphemeridesManager & manager) [override], [pure virtual]`

Build the model's contribution to the reference frame tree.

Parameters

<code>in, out</code>	<code>manager</code>	Ephemerides manager
----------------------	----------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Implemented in [jeod::SinglePlanetEphemeris](#), and [jeod::EmptySpaceEphemeris](#).

8.28.3.5 `void jeod::SinglePointEphemeris::ephem_initialize (EphemeridesManager & manager) [override], [pure virtual]`

Initialize the ephemerides.

Parameters

<code>in, out</code>	<code>manager</code>	Ephemerides manager
----------------------	----------------------	---------------------

Implements [jeod::EphemerisInterface](#).

Implemented in [jeod::SinglePlanetEphemeris](#), and [jeod::EmptySpaceEphemeris](#).

8.28.3.6 `void jeod::SinglePointEphemeris::ephem_update (void)` `[inline]`, `[override]`, `[virtual]`

Update the ephemerides, which in this case is a no-op.

Implements [jeod::EphemerisInterface](#).

Definition at line 331 of file `simple_ephemerides.hh`.

8.28.3.7 `const char * jeod::SinglePointEphemeris::get_name (void) const` `[inline]`, `[override]`, `[virtual]`

Retrieve the identifier.

Returns

Identifier

Implements [jeod::EphemerisInterface](#).

Definition at line 319 of file `simple_ephemerides.hh`.

References identifier.

8.28.3.8 `virtual void jeod::SinglePointEphemeris::initialize_model (EphemeridesManager & manager)` `[pure virtual]`

Register the model and its ephemeris points.

Parameters

<code>in, out</code>	<code>manager</code>	Ephemerides manager
----------------------	----------------------	---------------------

Implemented in [jeod::SinglePlanetEphemeris](#), and [jeod::EmptySpaceEphemeris](#).

8.28.3.9 `SinglePointEphemeris& jeod::SinglePointEphemeris::operator= (const SinglePointEphemeris &)` `[private]`

Not implemented.

8.28.3.10 `void jeod::SinglePointEphemeris::set_name (const char * new_name)` `[virtual]`

Set the name of a [SinglePointEphemeris](#) object.

Parameters

<code>in, out</code>	<code>new_name</code>	Central point name
----------------------	-----------------------	--------------------

Reimplemented in [jeod::SinglePlanetEphemeris](#), and [jeod::EmptySpaceEphemeris](#).

Definition at line 118 of file `simple_ephemerides.cc`.

References identifier, and `jeod::EphemeridesMessages::inconsistent_setup`.

Referenced by `jeod::EmptySpaceEphemeris::set_name()`, and `jeod::SinglePlanetEphemeris::set_name()`.

8.28.3.11 `double jeod::SinglePointEphemeris::timestamp (void) const` `[inline]`, `[override]`, `[virtual]`

Retrieve the timestamp.

Returns

Timestamp

Units: s

Implements [jeod::EphemerisInterface](#).

Definition at line 306 of file simple_ephemerides.hh.

References [update_time](#).

8.28.4 Friends And Related Function Documentation

8.28.4.1 `void init_attrjeod__SinglePointEphemeris ()` [[friend](#)]

8.28.4.2 `friend class InputProcessor` [[friend](#)]

Definition at line 87 of file simple_ephemerides.hh.

8.28.5 Field Documentation

8.28.5.1 `bool jeod::SinglePointEphemeris::active` [[protected](#)]

Is the model active?

[trick_units\(-\)](#)

Definition at line 187 of file simple_ephemerides.hh.

Referenced by [activate\(\)](#), [deactivate\(\)](#), [jeod::EmptySpaceEphemeris::ephem_build_tree\(\)](#), [jeod::SinglePlanetEphemeris::ephem_build_tree\(\)](#), [jeod::SinglePlanetEphemeris::ephem_initialize\(\)](#), [jeod::EmptySpaceEphemeris::initialize_model\(\)](#), and [jeod::SinglePlanetEphemeris::initialize_model\(\)](#).

8.28.5.2 `char* jeod::SinglePointEphemeris::identifier` [[protected](#)]

Identifier for this model.

[trick_units\(-\)](#)

Definition at line 177 of file simple_ephemerides.hh.

Referenced by [jeod::EmptySpaceEphemeris::ephem_initialize\(\)](#), [jeod::SinglePlanetEphemeris::ephem_initialize\(\)](#), [get_name\(\)](#), [set_name\(\)](#), and [~SinglePointEphemeris\(\)](#).

8.28.5.3 `double jeod::SinglePointEphemeris::update_time` [[protected](#)]

Time of last update, dynamic time seconds.

[trick_units\(s\)](#)

Definition at line 182 of file simple_ephemerides.hh.

Referenced by [timestamp\(\)](#).

The documentation for this class was generated from the following files:

- [simple_ephemerides.hh](#)
- [simple_ephemerides.cc](#)

Chapter 9

File Documentation

9.1 `base_ephem_manager.hh` File Reference

Define the BaseEphemManager class, which defines the interfaces to the class EphemManager.

```
#include <vector>
#include "utils/ref_frames/include/base_ref_frame_manager.hh"
#include "utils/sim_interface/include/jeod_class.hh"
```

Data Structures

- class [jeod::BaseEphemeridesManager](#)

The EphemManager class augments the RefFrameManager with ephemeris-related items.

Namespaces

- [jeod](#)

Namespace jeod.

9.1.1 Detailed Description

Define the BaseEphemManager class, which defines the interfaces to the class EphemManager.

Definition in file [base_ephem_manager.hh](#).

9.2 `class_declarations.hh` File Reference

Forward declarations of classes defined in the DE4xx model.

Namespaces

- [jeod](#)

Namespace jeod.

9.2.1 Detailed Description

Forward declarations of classes defined in the DE4xx model.

Definition in file [de4xx_ephem/include/class_declarations.hh](#).

9.3 class_declarations.hh File Reference

Forward declarations of classes defined in models/environment/ephemerides/ephem_interface files.

Namespaces

- [jeod](#)

Namespace jeod.

9.3.1 Detailed Description

Forward declarations of classes defined in models/environment/ephemerides/ephem_interface files.

Definition in file [ephem_interface/include/class_declarations.hh](#).

9.4 class_declarations.hh File Reference

Forward declarations of classes defined in models/environment/ephemerides/ephem_item files.

Namespaces

- [jeod](#)

Namespace jeod.

9.4.1 Detailed Description

Forward declarations of classes defined in models/environment/ephemerides/ephem_item files.

Definition in file [ephem_item/include/class_declarations.hh](#).

9.5 de405_0.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- [jeod::EphemerisDataSetMeta metaData](#)
- [jeod::EphemerisDataItemMeta itemData](#) [13]
- [jeod::EphemerisDataSegmentMeta segmentData](#) [31]
- double [segment_coeffs_0](#) [229][1018]

9.5.1 Variable Documentation

9.5.1.1 jeod::EphemerisDataItemMeta itemData[13]

Definition at line 44 of file de405_0.cc.

Referenced by jeod::De4xxFile::interpolate(), and jeod::De4xxFile::pre_initialize().

9.5.1.2 jeod::EphemerisDataSetMeta metaData

Initial value:

```
= {
    .number_file_items = 13,
    .start_epoch = 2305424.50,
    .stop_epoch = 2525008.50,
    .delta_epoch = 32,
    .number_segments = 31,
    .ncoeff = 1018,
    .de_constants = {
        0.405000000000000000E+03,
        0.405000000000000000E+03,
        0.149597870691000015E+09,
        0.813005600000000004E+02,
        0.299792457999999984E+06,
        0.491254745145081187E-10,
        0.724345248616270270E-09,
        0.899701134671249882E-09,
        0.954953510577925806E-10,
        0.282534590952422643E-06,
        0.845971518568065874E-07,
        0.129202491678196939E-07,
        0.152435890078427628E-07,
        0.218869976542596968E-11,
        0.295912208285591095E-03
    }
}
```

Definition at line 17 of file de405_0.cc.

9.5.1.3 double segment_coeffs_0[229][1018]

Definition at line 275 of file de405_0.cc.

9.5.1.4 jeod::EphemerisDataSegmentMeta segmentData[31]

Definition at line 112 of file de405_0.cc.

9.6 de405_1.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_1](#) [229][1018]

9.6.1 Variable Documentation

9.6.1.1 double segment_coeffs_1[229][1018]

Definition at line 17 of file de405_1.cc.

9.7 de405_10.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_10](#) [229][1018]

9.7.1 Variable Documentation

9.7.1.1 double segment_coeffs_10[229][1018]

Definition at line 17 of file de405_10.cc.

9.8 de405_11.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_11](#) [230][1018]

9.8.1 Variable Documentation

9.8.1.1 double segment_coeffs_11[230][1018]

Definition at line 17 of file de405_11.cc.

9.9 de405_12.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_12](#) [229][1018]

9.9.1 Variable Documentation

9.9.1.1 double segment_coeffs_12[229][1018]

Definition at line 17 of file de405_12.cc.

9.10 de405_13.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_13](#) [229][1018]

9.10.1 Variable Documentation

9.10.1.1 double [segment_coeffs_13](#)[229][1018]

Definition at line 17 of file de405_13.cc.

9.11 de405_14.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_14](#) [229][1018]

9.11.1 Variable Documentation

9.11.1.1 double [segment_coeffs_14](#)[229][1018]

Definition at line 17 of file de405_14.cc.

9.12 de405_15.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_15](#) [230][1018]

9.12.1 Variable Documentation

9.12.1.1 double [segment_coeffs_15](#)[230][1018]

Definition at line 17 of file de405_15.cc.

9.13 de405_16.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_16](#) [229][1018]

9.13.1 Variable Documentation

9.13.1.1 double [segment_coeffs_16](#)[229][1018]

Definition at line 17 of file de405_16.cc.

9.14 de405_17.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_17](#) [229][1018]

9.14.1 Variable Documentation

9.14.1.1 double [segment_coeffs_17](#)[229][1018]

Definition at line 17 of file de405_17.cc.

9.15 de405_18.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_18](#) [229][1018]

9.15.1 Variable Documentation

9.15.1.1 double [segment_coeffs_18](#)[229][1018]

Definition at line 17 of file de405_18.cc.

9.16 de405_19.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_19](#) [230][1018]

9.16.1 Variable Documentation

9.16.1.1 double [segment_coeffs_19](#)[230][1018]

Definition at line 17 of file de405_19.cc.

9.17 de405_2.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_2](#) [229][1018]

9.17.1 Variable Documentation

9.17.1.1 double [segment_coeffs_2](#)[229][1018]

Definition at line 17 of file de405_2.cc.

9.18 de405_20.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_20](#) [229][1018]

9.18.1 Variable Documentation

9.18.1.1 double [segment_coeffs_20](#)[229][1018]

Definition at line 17 of file de405_20.cc.

9.19 de405_21.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_21](#) [229][1018]

9.19.1 Variable Documentation

9.19.1.1 double [segment_coeffs_21](#)[229][1018]

Definition at line 17 of file de405_21.cc.

9.20 de405_22.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_22](#) [230][1018]

9.20.1 Variable Documentation

9.20.1.1 double [segment_coeffs_22](#)[230][1018]

Definition at line 17 of file de405_22.cc.

9.21 de405_23.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_23](#) [229][1018]

9.21.1 Variable Documentation

9.21.1.1 double [segment_coeffs_23](#)[229][1018]

Definition at line 17 of file de405_23.cc.

9.22 de405_24.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_24](#) [229][1018]

9.22.1 Variable Documentation

9.22.1.1 double [segment_coeffs_24](#)[229][1018]

Definition at line 17 of file de405_24.cc.

9.23 de405_25.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_25](#) [229][1018]

9.23.1 Variable Documentation

9.23.1.1 double [segment_coeffs_25](#)[229][1018]

Definition at line 17 of file de405_25.cc.

9.24 de405_26.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_26](#) [230][1018]

9.24.1 Variable Documentation

9.24.1.1 double [segment_coeffs_26](#)[230][1018]

Definition at line 17 of file de405_26.cc.

9.25 de405_27.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_27](#) [229][1018]

9.25.1 Variable Documentation

9.25.1.1 double [segment_coeffs_27](#)[229][1018]

Definition at line 17 of file de405_27.cc.

9.26 de405_28.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_28](#) [229][1018]

9.26.1 Variable Documentation

9.26.1.1 double [segment_coeffs_28](#)[229][1018]

Definition at line 17 of file de405_28.cc.

9.27 de405_29.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_29](#) [230][1018]

9.27.1 Variable Documentation

9.27.1.1 double [segment_coeffs_29](#)[230][1018]

Definition at line 17 of file de405_29.cc.

9.28 de405_3.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_3](#) [229][1018]

9.28.1 Variable Documentation

9.28.1.1 double [segment_coeffs_3](#)[229][1018]

Definition at line 17 of file de405_3.cc.

9.29 de405_30.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_30](#) [13][1018]

9.29.1 Variable Documentation

9.29.1.1 double [segment_coeffs_30](#)[13][1018]

Definition at line 17 of file de405_30.cc.

9.30 de405_4.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_4](#) [230][1018]

9.30.1 Variable Documentation

9.30.1.1 double [segment_coeffs_4](#)[230][1018]

Definition at line 17 of file de405_4.cc.

9.31 de405_5.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_5](#) [229][1018]

9.31.1 Variable Documentation

9.31.1.1 double [segment_coeffs_5](#)[229][1018]

Definition at line 17 of file de405_5.cc.

9.32 de405_6.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_6](#) [229][1018]

9.32.1 Variable Documentation

9.32.1.1 double [segment_coeffs_6](#)[229][1018]

Definition at line 17 of file de405_6.cc.

9.33 de405_7.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_7](#) [229][1018]

9.33.1 Variable Documentation

9.33.1.1 double [segment_coeffs_7](#)[229][1018]

Definition at line 17 of file de405_7.cc.

9.34 de405_8.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_8](#) [230][1018]

9.34.1 Variable Documentation

9.34.1.1 double [segment_coeffs_8](#)[230][1018]

Definition at line 17 of file de405_8.cc.

9.35 de405_9.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_9](#) [229][1018]

9.35.1 Variable Documentation

9.35.1.1 double [segment_coeffs_9](#)[229][1018]

Definition at line 17 of file de405_9.cc.

9.36 de421_0.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- [jeod::EphemerisDataSetMeta](#) [metaData](#)
- [jeod::EphemerisDataItemMeta](#) [itemData](#) [13]
- [jeod::EphemerisDataSegmentMeta](#) [segmentData](#) [2]
- double [segment_coeffs_0](#) [1713][1018]

9.36.1 Variable Documentation

9.36.1.1 [jeod::EphemerisDataItemMeta](#) [itemData](#)[13]

Definition at line 44 of file de421_0.cc.

9.36.1.2 jeod::EphemerisDataSetMeta metaData

Initial value:

```
= {
    .number_file_items = 13,
    .start_epoch = 2414992.50,
    .stop_epoch = 2524624.50,
    .delta_epoch = 32,
    .number_segments = 2,
    .ncoeff = 1018,
    .de_constants = {
        0.421000000000000000E+03,
        0.421000000000000000E+03,
        0.149597870699626200E+09,
        0.813005690699153000E+02,
        0.299792458000000000E+06,
        0.491254957186794000E-10,
        0.724345233269844100E-09,
        0.899701140826804900E-09,
        0.954954869562239000E-10,
        0.282534584085505000E-06,
        0.845970607330847800E-07,
        0.129202482579265000E-07,
        0.152435910924974000E-07,
        0.217844105199052000E-11,
        0.295912208285591100E-03
    }
}
```

Definition at line 17 of file de421_0.cc.

9.36.1.3 double segment_coeffs_0[1713][1018]

Definition at line 130 of file de421_0.cc.

9.36.1.4 jeod::EphemerisDataSegmentMeta segmentData[2]

Initial value:

```
= {
    {
        .num_recs = 1713,
        .start_epoch = 2.414992500000000000E+06,
        .stop_epoch = 2.469808500000000000E+06
    },
    {
        .num_recs = 1714,
        .start_epoch = 0.246977650000000000E+07,
        .stop_epoch = 0.252462450000000000E+07
    }
}
```

Definition at line 112 of file de421_0.cc.

9.37 de421_1.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_1](#) [1714][1018]

9.37.1 Variable Documentation

9.37.1.1 double segment_coeffs_1[1714][1018]

Definition at line 17 of file de421_1.cc.

9.38 de440_0.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- [jeod::EphemerisDataSetMeta metaData](#)
- [jeod::EphemerisDataItemMeta itemData \[15\]](#)
- [jeod::EphemerisDataSegmentMeta segmentData \[11\]](#)
- double [segment_coeffs_0 \[1142\]\[1018\]](#)

9.38.1 Variable Documentation

9.38.1.1 jeod::EphemerisDataItemMeta itemData[15]

Definition at line 44 of file de440_0.cc.

9.38.1.2 jeod::EphemerisDataSetMeta metaData

Initial value:

```
= {
    .number_file_items = 15,
    .start_epoch = 2287184.50,
    .stop_epoch = 2688976.50,
    .delta_epoch = 32,
    .number_segments = 11,
    .ncoeff = 1018,
    .de_constants = {
        0.44000000000000000000E+03,
        0.44000000000000000000E+03,
        0.1495978706999999988E+09,
        0.813005682214972154E+02,
        0.2997924579999999984E+06,
        0.491250019488931818E-10,
        0.724345233264411869E-09,
        0.899701139294734660E-09,
        0.954954882972581189E-10,
        0.282534582522579175E-06,
        0.845970599337629027E-07,
        0.129202656496823994E-07,
        0.152435734788519386E-07,
        0.217509646489335811E-11,
        0.295912208284119561E-03
    }
}
```

Definition at line 17 of file de440_0.cc.

9.38.1.3 double segment_coeffs_0[1142][1018]

Definition at line 185 of file de440_0.cc.

9.38.1.4 jeod::EphemerisDataSegmentMeta segmentData[11]

Definition at line 122 of file de440_0.cc.

9.39 de440_1.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coefs_1](#) [1142][1018]

9.39.1 Variable Documentation

9.39.1.1 double segment_coefs_1[1142][1018]

Definition at line 17 of file de440_1.cc.

9.40 de440_10.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coefs_10](#) [1143][1018]

9.40.1 Variable Documentation

9.40.1.1 double segment_coefs_10[1143][1018]

Definition at line 17 of file de440_10.cc.

9.41 de440_2.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coefs_2](#) [1143][1018]

9.41.1 Variable Documentation

9.41.1.1 double segment_coefs_2[1143][1018]

Definition at line 17 of file de440_2.cc.

9.42 de440_3.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_3](#) [1142][1018]

9.42.1 Variable Documentation

9.42.1.1 double [segment_coeffs_3](#)[1142][1018]

Definition at line 17 of file de440_3.cc.

9.43 de440_4.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_4](#) [1142][1018]

9.43.1 Variable Documentation

9.43.1.1 double [segment_coeffs_4](#)[1142][1018]

Definition at line 17 of file de440_4.cc.

9.44 de440_5.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_5](#) [1143][1018]

9.44.1 Variable Documentation

9.44.1.1 double [segment_coeffs_5](#)[1143][1018]

Definition at line 17 of file de440_5.cc.

9.45 de440_6.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_6](#) [1142][1018]

9.45.1 Variable Documentation

9.45.1.1 double [segment_coeffs_6](#)[1142][1018]

Definition at line 17 of file de440_6.cc.

9.46 de440_7.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_7](#) [1143][1018]

9.46.1 Variable Documentation

9.46.1.1 double [segment_coeffs_7](#)[1143][1018]

Definition at line 17 of file de440_7.cc.

9.47 de440_8.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_8](#) [1142][1018]

9.47.1 Variable Documentation

9.47.1.1 double [segment_coeffs_8](#)[1142][1018]

Definition at line 17 of file de440_8.cc.

9.48 de440_9.cc File Reference

```
#include "environment/ephemerides/de4xx_ephem/include/de4xx_file.hh"
```

Variables

- double [segment_coeffs_9](#) [1142][1018]

9.48.1 Variable Documentation

9.48.1.1 double segment_coeffs_9[1142][1018]

Definition at line 17 of file de440_9.cc.

9.49 de4xx_base.hh File Reference

Define data types for JPL ephemeris model.

```
#include <stdint>
#include "utils/sim_interface/include/jeod_class.hh"
```

Namespaces

- [jeod](#)
Namespace jeod.
- [jeod::De4xxBase](#)
Defines enumerations used in the DE4xx ephemeris model.

Enumerations

- enum [jeod::De4xxBase::De4xxFileEntries](#) {
[jeod::De4xxBase::De4xx_File_Mercury](#) = 0, [jeod::De4xxBase::De4xx_File_Venus](#) = 1, [jeod::De4xxBase::De4xx_File_EMbary](#) = 2, [jeod::De4xxBase::De4xx_File_Mars](#) = 3,
[jeod::De4xxBase::De4xx_File_Jupiter](#) = 4, [jeod::De4xxBase::De4xx_File_Saturn](#) = 5, [jeod::De4xxBase::De4xx_File_Uranus](#) = 6, [jeod::De4xxBase::De4xx_File_Neptune](#) = 7,
[jeod::De4xxBase::De4xx_File_Pluto](#) = 8, [jeod::De4xxBase::De4xx_File_Moon](#) = 9, [jeod::De4xxBase::De4xx_File_Sun](#) = 10, [jeod::De4xxBase::De4xx_File_ENutation](#) = 11,
[jeod::De4xxBase::De4xx_File_LLibration](#) = 12, [jeod::De4xxBase::De4xx_File_LAngVel](#) = 13, [jeod::De4xxBase::De4xx_File_tt_tdb](#) = 14, [jeod::De4xxBase::De4xx_File_MaxEntries](#) }
Defines names for planetary body descriptors in the ephemeris file.
- enum [jeod::De4xxBase::De4xxEphemConsts](#) {
[jeod::De4xxBase::De4xx_Const_DENUM](#) = 0, [jeod::De4xxBase::De4xx_Const_LENUM](#), [jeod::De4xxBase::De4xx_Const_AU](#), [jeod::De4xxBase::De4xx_Const_EMRAT](#),
[jeod::De4xxBase::De4xx_Const_CLIGHT](#), [jeod::De4xxBase::De4xx_Const_GM1](#), [jeod::De4xxBase::De4xx_Const_GM2](#), [jeod::De4xxBase::De4xx_Const_GMB](#),
[jeod::De4xxBase::De4xx_Const_GM4](#), [jeod::De4xxBase::De4xx_Const_GM5](#), [jeod::De4xxBase::De4xx_Const_GM6](#), [jeod::De4xxBase::De4xx_Const_GM7](#),
[jeod::De4xxBase::De4xx_Const_GM8](#), [jeod::De4xxBase::De4xx_Const_GM9](#), [jeod::De4xxBase::De4xx_Const_GMS](#), [jeod::De4xxBase::De4xx_Const_MaxConsts](#) }
Index aliases for the constants listed in the DE header that are used by JEOD.

- enum `jeod::De4xxBase::De4xxEphemBodies` {
`jeod::De4xxBase::De4xx_Ephem_Sun` = 0, `jeod::De4xxBase::De4xx_Ephem_Mercury` = 1, `jeod::De4xxBase::De4xx_Ephem_Venus` = 2, `jeod::De4xxBase::De4xx_Ephem_Earth` = 3,
`jeod::De4xxBase::De4xx_Ephem_Mars` = 4, `jeod::De4xxBase::De4xx_Ephem_Jupiter` = 5, `jeod::De4xxBase::De4xx_Ephem_Saturn` = 6, `jeod::De4xxBase::De4xx_Ephem_Uranus` = 7,
`jeod::De4xxBase::De4xx_Ephem_Neptune` = 8, `jeod::De4xxBase::De4xx_Ephem_Pluto` = 9, `jeod::De4xxBase::De4xx_Ephem_Moon` = 10, `jeod::De4xxBase::De4xx_Ephem_EMBary` = 11,
`jeod::De4xxBase::De4xx_Ephem_SSbary` = 12, `jeod::De4xxBase::De4xx_Ephem_EML1` = 13, `jeod::De4xxBase::De4xx_Ephem_ENutation` = 14, `jeod::De4xxBase::De4xx_Ephem_LLibration` = 15,
`jeod::De4xxBase::De4xx_Ephem_MaxBodies` }

Defines names for ephemeris items as represented in the JEOD DE4xx model.

Functions

- static const char *point_names[32] `jeod::De4xxBase::__attribute__((unused))`
- static uint32_t `jeod::De4xxBase::number_jeod_items` (int de_version_num __attribute__((unused)))
Total number of items in the JEOD ephemeris.
- static uint32_t `jeod::De4xxBase::number_trans_points` (int de_version_num __attribute__((unused)))
Total number of translational states in the JEOD ephemeris.
- static uint32_t `jeod::De4xxBase::number_grav_models` (int de_version_num __attribute__((unused)))
Number of gravity models in the JEOD ephemeris (Mercury to Sun + implied Earth) Currently only one possibility, but written for extensibility.
- static uint32_t `jeod::De4xxBase::number_physical_bodies` (int de_version_num __attribute__((unused)))
Number of bodies in the JEOD ephemeris (Planets + Pluto + Moon + Sun) Currently only one possibility, but written for extensibility.

9.49.1 Detailed Description

Define data types for JPL ephemeris model.

Definition in file [de4xx_base.hh](#).

9.50 de4xx_ephem.cc File Reference

Define the methods of the classes defined in [de4xx_ephem.hh](#).

```
#include <cstdlib>
#include <cstdio>
#include <climits>
#include <sstream>
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "environment/planet/include/base_planet.hh"
#include "environment/time/include/time_manager.hh"
#include "environment/time/include/time_tt.hh"
#include "environment/time/include/time_dyn.hh"
#include "utils/named_item/include/named_item.hh"
#include "utils/math/include/vector3.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "utils/math/include/numerical.hh"
#include "../include/de4xx_ephem.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.50.1 Detailed Description

Define the methods of the classes defined in [de4xx_ephem.hh](#).

Definition in file [de4xx_ephem.cc](#).

9.51 de4xx_ephem.hh File Reference

Define class for the De4xx ephemeris model.

```
#include <string>
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_ref_frame.-
hh"
#include "environment/ephemerides/ephem_item/include/ephem_item.hh"
#include "environment/ephemerides/ephem_item/include/ephem_orient_zxz.hh"
#include "environment/ephemerides/ephem_item/include/ephem_point.hh"
#include "environment/time/include/class_declarations.hh"
#include "utils/ref_frames/include/ref_frame_interface.hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "class_declarations.hh"
#include "de4xx_base.hh"
#include "de4xx_file.hh"
```

Data Structures

- class [jeod::De4xxEphemItem](#)
Describes a point modeled in a DE4xx ephemeris file.
- class [jeod::De4xxEphemeris](#)
The S_define-level class that provides planetary ephemerides.

Namespaces

- [jeod](#)

Namespace jeod.

9.51.1 Detailed Description

Define class for the De4xx ephemeris model.

Definition in file [de4xx_ephem.hh](#).

9.52 de4xx_ephem_dynmanager.cc File Reference

Wall off dependencies on the dynamics manager.

```
#include "dynamics/dyn_manager/include/dyn_manager.hh"
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "environment/time/include/time_manager.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/de4xx_ephem.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.52.1 Detailed Description

Wall off dependencies on the dynamics manager.

Definition in file [de4xx_ephem_dynmanager.cc](#).

9.53 de4xx_file.cc File Reference

This file defines several utility functions used to read a binary JPL DE405 ephemeris file.

```
#include <cerrno>
#include <cstdint>
#include <cstdlib>
#include <cstdio>
#include <cstring>
#include <limits>
#include <unistd.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <dlfcn.h>
#include <ios>
#include <iostream>
#include <fstream>
#include <string>
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/de4xx_file.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

Macros

- [#define __STDC_LIMIT_MACROS](#)

Functions

- void [jeod::process_mem_usage](#) (double &vm_usage, double &resident_set)

9.53.1 Detailed Description

This file defines several utility functions used to read a binary JPL DE405 ephemeris file. The functions are

open - Open an ephemeris file for input
 close - Close a previously open ephemeris file
 read_record - Read a record from the ephemeris file
 get_string - Get a string from the current data record
 get_int - Get integer array from the current data record
 get_double - Get double array from the current data record

NOTA BENE – The functions defined in this file are intended for use by the top-level ephemeris functions only.

Definition in file [de4xx_file.cc](#).

9.54 de4xx_file.hh File Reference

Define the class responsible for reading the DE4xx ephemeris file.

```
#include <cstdio>
#include <cstdlib>
#include <stdint.h>
#include "utils/container/include/simple_checkpointable.hh"
#include "utils/sim_interface/include/config.hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "de4xx_base.hh"
```

Data Structures

- struct [jeod::EphemerisDataSetMeta](#)
Container for the metadata from the DE model header.
- struct [jeod::EphemerisDataItemMeta](#)
Structure containing the header metadata for sizing/locating the data entries with the data segments.
- struct [jeod::EphemerisDataSegmentMeta](#)
Metadata implied from each data segment.
- class [jeod::De4xxFileSpec](#)
Specifies which file to use (user input initialization-time data).
- class [jeod::De4xxFileIO](#)
Contains data used directly for reading the ephemeris file.
- class [jeod::De4xxFileHeader](#)
Contains data extracted from the ephemeris file header.
- class [jeod::De4xxFileItem](#)
Contains data regarding one of the items in a DE ephemeris file.
- class [jeod::De4xxFileRefTime](#)
Contains timing reference data.
- class [jeod::De4xxFileCoef](#)
Contains Chebychev polynomial coefficients and terms.
- class [jeod::De4xxFileRestart](#)
The FILE pointer in a [De4xxFileIO](#) cannot be restored by Trick.
- class [jeod::De4xxFile](#)
Provides the ability to read and interpret a DE4xx ephemeris file.

Namespaces

- [jeod](#)

Namespace jeod.

9.54.1 Detailed Description

Define the class responsible for reading the DE4xx ephemeris file.

Definition in file [de4xx_file.hh](#).

9.55 de4xx_file_init.cc File Reference

Define De4xx initialization methods.

```
#include <cerrno>
#include <climits>
#include <cmath>
#include <cstddef>
#include <cstring>
#include <sys/types.h>
#include <sys/stat.h>
#include <unistd.h>
#include <dlfcn.h>
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/de4xx_file.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

Functions

- static double [jeod::l1_point](#) (double b1b2_mass_ratio)

Calculate the location of the L1 point as a ratio.

9.55.1 Detailed Description

Define De4xx initialization methods.

Definition in file [de4xx_file_init.cc](#).

9.56 de4xx_file_update.cc File Reference

Define De4xxFile::update.


```
#include <cstdint>
#include <limits>
#include <stdint>
#include <dlfcn.h>
#include <sstream>
#include "environment/ephemerides/ephemer_interface/include/ephemer_messages.-
hh"
#include "utils/message/include/message_handler.hh"
#include "utils/math/include/numerical.hh"
#include "../include/de4xx_file.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.56.1 Detailed Description

Define De4xxFile::update.

Definition in file [de4xx_file_update.cc](#).

9.57 ephemer_interface.hh File Reference

Define base class for all ephemeris interface models.

```
#include "utils/ref_frames/include/subscription.hh"
#include "utils/sim_interface/include/jeod_class.hh"
```

Data Structures

- class [jeod::EphemerisInterface](#)

Interface class that specifies minimal functionality of an ephemeris model.

Namespaces

- [jeod](#)

Namespace jeod.

9.57.1 Detailed Description

Define base class for all ephemeris interface models.

Definition in file [ephemer_interface.hh](#).

9.58 ephemer_item.cc File Reference

Define member functions for the EphemerItem class and subclasses.

```
#include <cstdint>
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/ephemerides/ephem_manager/include/base_ephem_manager.-
hh"
#include "environment/planet/include/base_planet.hh"
#include "utils/math/include/vector3.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "utils/named_item/include/named_item.hh"
#include "../include/ephem_item.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.58.1 Detailed Description

Define member functions for the EphemItem class and subclasses.

Definition in file [ephem_item.cc](#).

9.59 ephem_item.hh File Reference

Define classes for items represented in some ephemeris model.

```
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_ref_frame.-
hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "class_declarations.hh"
#include "ephem_item_inline.hh"
```

Data Structures

- class [jeod::EphemerisItem](#)

The [EphemerisItem](#) class is the base class for representing an item that is modeled in an ephemeris model.

Namespaces

- [jeod](#)

Namespace jeod.

9.59.1 Detailed Description

Define classes for items represented in some ephemeris model.

Definition in file [ephem_item.hh](#).

9.60 `ephem_item_inline.hh` File Reference

Define inline methods for the `EphemerisItem` class.

```
#include "ephem_item.hh"
```

Namespaces

- [jeod](#)
Namespace `jeod`.

9.60.1 Detailed Description

Define inline methods for the `EphemerisItem` class.

Definition in file [ephem_item_inline.hh](#).

9.61 `ephem_manager.cc` File Reference

Define `EphemeridesManager` methods.

```
#include <algorithm>
#include <cstdlib>
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_ref_frame.-
hh"
#include "environment/ephemerides/ephem_item/include/ephem_item.hh"
#include "environment/ephemerides/ephem_item/include/ephem_orient.hh"
#include "environment/ephemerides/ephem_item/include/ephem_point.hh"
#include "environment/planet/include/base_planet.hh"
#include "utils/message/include/message_handler.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/ref_frames/include/ref_frame.hh"
#include "../include/ephem_manager.hh"
```

Namespaces

- [jeod](#)
Namespace `jeod`.

9.61.1 Detailed Description

Define `EphemeridesManager` methods.

Definition in file [ephem_manager.cc](#).

9.62 `ephem_manager.hh` File Reference

Define the `EphemManager` class, which manages the ephemeris models in a JEOD-based simulation.

```
#include "utils/ref_frames/include/ref_frame_manager.hh"
#include "utils/container/include/pointer_vector.hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "base_ephem_manager.hh"
```

Data Structures

- class [jeod::EphemeridesManager](#)

The [EphemeridesManager](#) class manages the ephemeris models in a simulation.

Namespaces

- [jeod](#)

Namespace [jeod](#).

9.62.1 Detailed Description

Define the EphemManager class, which manages the ephemeris models in a JEOD-based simulation.

Definition in file [ephem_manager.hh](#).

9.63 ephem_messages.cc File Reference

Implement the class EphemeridesMessages.

```
#include "utils/message/include/make_message_code.hh"
#include "../include/ephem_messages.hh"
```

Namespaces

- [jeod](#)

Namespace [jeod](#).

Macros

- #define [MAKE_EPHEMERIDES_MESSAGE_CODE](#)(id) JEOD_MAKE_MESSAGE_CODE(EphemeridesMessages, "environment/ephemerides/", id)

9.63.1 Detailed Description

Implement the class EphemeridesMessages.

Definition in file [ephem_messages.cc](#).

9.63.2 Macro Definition Documentation

9.63.2.1 #define [MAKE_EPHEMERIDES_MESSAGE_CODE](#)(id) JEOD_MAKE_MESSAGE_CODE(EphemeridesMessages, "environment/ephemerides/", id)

Definition at line 39 of file [ephem_messages.cc](#).

9.64 `ephem_messages.hh` File Reference

Define the class `EphemeridesMessages`, the class that specifies the message IDs used in the JEOD ephemerides model.

```
#include "utils/sim_interface/include/jeod_class.hh"
```

Data Structures

- class [jeod::EphemeridesMessages](#)
Specifies the message IDs used in the Ephemerides model.

Namespaces

- [jeod](#)
Namespace `jeod`.

9.64.1 Detailed Description

Define the class `EphemeridesMessages`, the class that specifies the message IDs used in the JEOD ephemerides model.

Definition in file [ephem_messages.hh](#).

9.65 `ephem_orient.cc` File Reference

Define member functions for the `EphemItem` class and subclasses.

```
#include <cstdint>
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "environment/planet/include/base_planet.hh"
#include "utils/math/include/vector3.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "utils/named_item/include/named_item.hh"
#include "../include/ephem_orient.hh"
```

Namespaces

- [jeod](#)
Namespace `jeod`.

9.65.1 Detailed Description

Define member functions for the `EphemItem` class and subclasses.

Definition in file [ephem_orient.cc](#).

9.66 ephemeris.orient.hh File Reference

Define class EphemerisOrientation.

```
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_ref_frame.-
hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "class_declarations.hh"
#include "ephem_item.hh"
```

Data Structures

- class [jeod::EphemerisOrientation](#)

An [EphemerisOrientation](#) object updates the rotational state of an ephemeris reference frame.

Namespaces

- [jeod](#)

Namespace [jeod](#).

9.66.1 Detailed Description

Define class EphemerisOrientation.

Definition in file [ephemeris.orient.hh](#).

9.67 ephemeris.orient_zxz.cc File Reference

Define member functions for the EphemerisItem class and subclasses.

```
#include <cmath>
#include <cstdlib>
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "environment/planet/include/base_planet.hh"
#include "utils/math/include/vector3.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "utils/named_item/include/named_item.hh"
#include "utils/quaternion/include/quat.hh"
#include "../include/ephemeris.orient_zxz.hh"
```

Namespaces

- [jeod](#)

Namespace [jeod](#).

Macros

- `#define EPSILON_TIME 1e-12`
- `#define TAYLOR_CUTOFF 0.00786`

9.67.1 Detailed Description

Define member functions for the EphemerItem class and subclasses.

Definition in file [ephemer_orient_zxz.cc](#).

9.68 ephemer_orient_zxz.hh File Reference

Define classes for items represented in some ephemeris model.

```
#include "environment/ephemerides/ephemer_interface/include/ephemer_interface.-
hh"
#include "environment/ephemerides/ephemer_interface/include/ephemer_ref_frame.-
hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "class_declarations.hh"
#include "ephemer_orient.hh"
```

Data Structures

- class [jeod::EphemerisZXZOrientation](#)

The [EphemerisZXZOrientation](#) is an [EphemerisOrientation](#) subclass that updates orientation based on an Z-X-Z Euler sequence and the time derivatives of this sequence.

Namespaces

- [jeod](#)

Namespace jeod.

9.68.1 Detailed Description

Define classes for items represented in some ephemeris model.

Definition in file [ephemer_orient_zxz.hh](#).

9.69 ephemer_point.cc File Reference

Define member functions for the EphemerPoint class.

```
#include <cstdint>
#include "environment/ephemerides/ephemer_interface/include/ephemer_interface.-
hh"
#include "environment/ephemerides/ephemer_interface/include/ephemer_messages.-
```

```
hh"
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "environment/planet/include/base_planet.hh"
#include "utils/math/include/vector3.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "utils/named_item/include/named_item.hh"
#include "../include/ephem_point.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.69.1 Detailed Description

Define member functions for the EphemPoint class.

Definition in file [ephem_point.cc](#).

9.70 [ephem_point.hh](#) File Reference

Define class EphemerisPoint.

```
#include "utils/sim_interface/include/jeod_class.hh"
#include "class_declarations.hh"
#include "ephem_item.hh"
```

Data Structures

- class [jeod::EphemerisPoint](#)

An [EphemerisPoint](#) object updates the translational state of an ephemeris reference frame.

Namespaces

- [jeod](#)

Namespace jeod.

9.70.1 Detailed Description

Define class EphemerisPoint.

Definition in file [ephem_point.hh](#).

9.71 [ephem_ref_frame.cc](#) File Reference

Define non-inlined member functions for the EphemRefFrame class.


```
#include <cstdint>
#include "environment/ephemerides/ephem_manager/include/base_ephem_manager.-
hh"
#include "utils/message/include/message_handler.hh"
#include "../include/ephem_interface.hh"
#include "../include/ephem_messages.hh"
#include "../include/ephemer_ref_frame.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.71.1 Detailed Description

Define non-inlined member functions for the EphemerRefFrame class.

Definition in file [ephemer_ref_frame.cc](#).

9.72 ephemer_ref_frame.hh File Reference

Define the class EphemerisRefFrame.

```
#include <cstdint>
#include "utils/ref_frames/include/ref_frame.hh"
#include "utils/ref_frames/include/ref_frame_interface.hh"
#include "utils/sim_interface/include/jeod_class.hh"
```

Data Structures

- class [jeod::EphemerisRefFrame](#)

An [EphemerisRefFrame](#) is a [RefFrame](#) whose state is set by an ephemeris model.

Namespaces

- [jeod](#)

Namespace jeod.

9.72.1 Detailed Description

Define the class EphemerisRefFrame.

Definition in file [ephemer_ref_frame.hh](#).

9.73 find_planet.cc File Reference

Define EphemeridesManager::find_planet.

```
#include <cstddef>
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/planet/include/base_planet.hh"
#include "environment/planet/include/planet.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/ephem_manager.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.73.1 Detailed Description

Define EphemeridesManager::find_planet. This method is isolated from the other EphemeridesManager methods because the object file drags in a whole lot of stuff.

Definition in file [find_planet.cc](#).

9.74 propagated_planet.cc File Reference

Define the methods of the classes defined in [propagated_planet.hh](#).

```
#include <cstddef>
#include <cstdio>
#include <climits>
#include "dynamics/dyn_manager/include/dyn_manager.hh"
#include "environment/ephemerides/ephem_interface/include/ephem_messages.-
hh"
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "environment/planet/include/base_planet.hh"
#include "environment/time/include/time_manager.hh"
#include "environment/time/include/time_tt.hh"
#include "environment/time/include/time_dyn.hh"
#include "utils/named_item/include/named_item.hh"
#include "utils/math/include/vector3.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/propagated_planet.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

9.74.1 Detailed Description

Define the methods of the classes defined in [propagated_planet.hh](#).

Definition in file [propagated_planet.cc](#).

9.75 propagated_planet.hh File Reference

Define the classes needed to propagate a planet.

```
#include "dynamics/dyn_body/include/dyn_body.hh"
#include "environment/ephemerides/ephem_interface/include/ephem_interface.-
hh"
#include "environment/ephemerides/ephem_item/include/ephem_item.hh"
#include "environment/ephemerides/ephem_item/include/ephem_orient.hh"
#include "environment/ephemerides/ephem_item/include/ephem_point.hh"
#include "utils/sim_interface/include/jeod_class.hh"
```

Data Structures

- class [jeod::PropagatedEphemerisPlanet](#)
A [PropagatedEphemerisPlanet](#) is an [EphemerisPoint](#) whose state is coupled with the translational state of a *DynBody* reference frame.
- class [jeod::PropagatedEphemerisOrientation](#)
A [PropagatedEphemerisOrientation](#) is an [EphemerisOrientation](#) whose state is coupled with the rotational state of a *DynBody* reference frame.
- class [jeod::PropagatedPlanet](#)
The [PropagatedPlanet](#) ephemeris model provides planetary state via a *DynBody* object whose state is propagated using the JEOD state integration techniques.

Namespaces

- [jeod](#)
Namespace *jeod*.

9.75.1 Detailed Description

Define the classes needed to propagate a planet.

Definition in file [propagated_planet.hh](#).

9.76 simple_ephemerides.cc File Reference

Define member functions for the SinglePointEphemeris class and subclasses.

```
#include <cstdint>
#include "environment/ephemerides/ephem_manager/include/ephem_manager.hh"
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/ephem_messages.hh"
#include "../include/simple_ephemerides.hh"
```

Namespaces

- [jeod](#)
Namespace *jeod*.

9.76.1 Detailed Description

Define member functions for the SinglePointEphemeris class and subclasses.

Definition in file [simple_ephemerides.cc](#).

9.77 simple_ephemerides.hh File Reference

Define classes that define simple ephemeris models.

```
#include "environment/ephemerides/ephem_item/include/ephem_point.hh"
#include "utils/sim_interface/include/jeod_class.hh"
#include "ephem_interface.hh"
#include "ephem_ref_frame.hh"
```

Data Structures

- class [jeod::SinglePointEphemeris](#)
A [SinglePointEphemeris](#) has one ephemeris point.
- class [jeod::EmptySpaceEphemeris](#)
Empty space has one ephemeris point.
- class [jeod::SinglePlanetEphemeris](#)
A space with one gravitation body has one ephemeris point.

Namespaces

- [jeod](#)
Namespace jeod.

9.77.1 Detailed Description

Define classes that define simple ephemeris models.

Definition in file [simple_ephemerides.hh](#).

Index

- ~BaseEphemeridesManager
 - jeod::BaseEphemeridesManager, 28
- ~De4xxEphemItem
 - jeod::De4xxEphemItem, 46
- ~De4xxEphemeris
 - jeod::De4xxEphemeris, 35
- ~De4xxFile
 - jeod::De4xxFile, 49
- ~De4xxFileHeader
 - jeod::De4xxFileHeader, 59
- ~De4xxFileRestart
 - jeod::De4xxFileRestart, 70
- ~EmptySpaceEphemeris
 - jeod::EmptySpaceEphemeris, 75
- ~EphemeridesManager
 - jeod::EphemeridesManager, 79
- ~EphemerisInterface
 - jeod::EphemerisInterface, 98
- ~EphemerisItem
 - jeod::EphemerisItem, 103
- ~EphemerisOrientation
 - jeod::EphemerisOrientation, 114
- ~EphemerisPoint
 - jeod::EphemerisPoint, 118
- ~EphemerisRefFrame
 - jeod::EphemerisRefFrame, 121
- ~EphemerisZXZOrientation
 - jeod::EphemerisZXZOrientation, 124
- ~PropagatedEphemerisOrientation
 - jeod::PropagatedEphemerisOrientation, 129
- ~PropagatedEphemerisPlanet
 - jeod::PropagatedEphemerisPlanet, 132
- ~PropagatedPlanet
 - jeod::PropagatedPlanet, 136
- ~SinglePlanetEphemeris
 - jeod::SinglePlanetEphemeris, 143
- ~SinglePointEphemeris
 - jeod::SinglePointEphemeris, 147
- __attribute__
 - jeod::De4xxBase, 26
- activate
 - jeod::De4xxEphemeris, 36
 - jeod::EphemerisItem, 104
 - jeod::PropagatedPlanet, 136
 - jeod::SinglePointEphemeris, 148
- activate_em_nodes
 - jeod::De4xxEphemeris, 36
- activate_ephemerides
 - jeod::EphemeridesManager, 80
- activate_nodes
 - jeod::De4xxEphemeris, 36
- Active
 - jeod::De4xxEphemItem, 45
- active
 - jeod::De4xxEphemeris, 41
 - jeod::De4xxFileItem, 66
 - jeod::EphemerisItem, 111
 - jeod::PropagatedPlanet, 139
 - jeod::SinglePointEphemeris, 150
- add_ephem_item
 - jeod::BaseEphemeridesManager, 28
 - jeod::EphemeridesManager, 80
- add_ephemeris
 - jeod::BaseEphemeridesManager, 29
 - jeod::EphemeridesManager, 81
- add_integ_frame
 - jeod::BaseEphemeridesManager, 29
 - jeod::EphemeridesManager, 81
- add_planet
 - jeod::BaseEphemeridesManager, 29
 - jeod::EphemeridesManager, 81
- add_ref_frame
 - jeod::EphemeridesManager, 83
- au
 - jeod::De4xxFileHeader, 59
- avail
 - jeod::De4xxFileItem, 66
- b1_em_dist_ratio
 - jeod::De4xxFileHeader, 60
- base_ephem_manager.hh, 151
- be_em_dist_ratio
 - jeod::De4xxFileHeader, 60
- block_no
 - jeod::De4xxFileRefTime, 68
- bm_em_dist_ratio
 - jeod::De4xxFileHeader, 60
- body
 - jeod::PropagatedEphemerisOrientation, 130
 - jeod::PropagatedEphemerisPlanet, 132
 - jeod::PropagatedPlanet, 139
- body_ref_frame
 - jeod::PropagatedEphemerisOrientation, 130
 - jeod::PropagatedEphemerisPlanet, 133
- body_to_file_idx
 - jeod::De4xxEphemeris, 41
- capture_mem_stats
 - jeod::De4xxFile, 49

central_frame
 jeod::EmptySpaceEphemeris, 76
 central_point
 jeod::EmptySpaceEphemeris, 77
 jeod::SinglePlanetEphemeris, 145
 chebyderiv
 jeod::De4xxFileCoef, 57
 chebypoly
 jeod::De4xxFileCoef, 57
 chebyterms
 jeod::De4xxFileCoef, 57
 chebyx
 jeod::De4xxFileCoef, 57
 class_declarations.hh, 151, 152
 clear_added_ephemerides
 jeod::BaseEphemeridesManager, 29
 jeod::EphemeridesManager, 83
 close
 jeod::De4xxFile, 49
 coef
 jeod::De4xxFile, 54
 jeod::De4xxFileCoef, 57
 coeffs_segment_starting_addr
 jeod::De4xxFileIO, 63
 commanded_mode
 jeod::PropagatedPlanet, 139
 current_record_starting_addr
 jeod::De4xxFileIO, 63

 de405_0.cc, 152
 itemData, 153
 metaData, 153
 segment_coeffs_0, 153
 segmentData, 153
 de405_1.cc, 153
 segment_coeffs_1, 153
 de405_10.cc, 154
 segment_coeffs_10, 154
 de405_11.cc, 154
 segment_coeffs_11, 154
 de405_12.cc, 154
 segment_coeffs_12, 154
 de405_13.cc, 155
 segment_coeffs_13, 155
 de405_14.cc, 155
 segment_coeffs_14, 155
 de405_15.cc, 155
 segment_coeffs_15, 155
 de405_16.cc, 156
 segment_coeffs_16, 156
 de405_17.cc, 156
 segment_coeffs_17, 156
 de405_18.cc, 156
 segment_coeffs_18, 156
 de405_19.cc, 157
 segment_coeffs_19, 157
 de405_2.cc, 157
 segment_coeffs_2, 157
 de405_20.cc, 157
 segment_coeffs_20, 157
 de405_21.cc, 158
 segment_coeffs_21, 158
 de405_22.cc, 158
 segment_coeffs_22, 158
 de405_23.cc, 158
 segment_coeffs_23, 158
 de405_24.cc, 159
 segment_coeffs_24, 159
 de405_25.cc, 159
 segment_coeffs_25, 159
 de405_26.cc, 159
 segment_coeffs_26, 159
 de405_27.cc, 160
 segment_coeffs_27, 160
 de405_28.cc, 160
 segment_coeffs_28, 160
 de405_29.cc, 160
 segment_coeffs_29, 160
 de405_3.cc, 161
 segment_coeffs_3, 161
 de405_30.cc, 161
 segment_coeffs_30, 161
 de405_4.cc, 161
 segment_coeffs_4, 161
 de405_5.cc, 162
 segment_coeffs_5, 162
 de405_6.cc, 162
 segment_coeffs_6, 162
 de405_7.cc, 162
 segment_coeffs_7, 162
 de405_8.cc, 163
 segment_coeffs_8, 163
 de405_9.cc, 163
 segment_coeffs_9, 163
 de421_0.cc, 163
 itemData, 163
 metaData, 163
 segment_coeffs_0, 164
 segmentData, 164
 de421_1.cc, 164
 segment_coeffs_1, 165
 de440_0.cc, 165
 itemData, 165
 metaData, 165
 segment_coeffs_0, 165
 segmentData, 165
 de440_1.cc, 166
 segment_coeffs_1, 166
 de440_10.cc, 166
 segment_coeffs_10, 166
 de440_2.cc, 166
 segment_coeffs_2, 166
 de440_3.cc, 167
 segment_coeffs_3, 167
 de440_4.cc, 167
 segment_coeffs_4, 167
 de440_5.cc, 167

- segment_coeffs_5, [167](#)
- de440_6.cc, [168](#)
 - segment_coeffs_6, [168](#)
- de440_7.cc, [168](#)
 - segment_coeffs_7, [168](#)
- de440_8.cc, [168](#)
 - segment_coeffs_8, [168](#)
- de440_9.cc, [169](#)
 - segment_coeffs_9, [169](#)
- De4xx_Const_AU
 - jeod::De4xxBase, [25](#)
- De4xx_Const_CLIGHT
 - jeod::De4xxBase, [25](#)
- De4xx_Const_DENUM
 - jeod::De4xxBase, [25](#)
- De4xx_Const_EM RAT
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM1
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM2
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM4
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM5
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM6
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM7
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM8
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GM9
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GMB
 - jeod::De4xxBase, [25](#)
- De4xx_Const_GMS
 - jeod::De4xxBase, [25](#)
- De4xx_Const_LENUM
 - jeod::De4xxBase, [25](#)
- De4xx_Const_MaxConsts
 - jeod::De4xxBase, [25](#)
- De4xx_Ephem_EML1
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_EMbary
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_ENutation
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Earth
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Jupiter
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_LLibration
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Mars
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_MaxBodies
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Mercury
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Moon
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Neptune
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Pluto
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_SSbary
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Saturn
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Sun
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Uranus
 - jeod::De4xxBase, [24](#)
- De4xx_Ephem_Venus
 - jeod::De4xxBase, [24](#)
- De4xx_File_EMbary
 - jeod::De4xxBase, [25](#)
- De4xx_File_ENutation
 - jeod::De4xxBase, [25](#)
- De4xx_File_Jupiter
 - jeod::De4xxBase, [25](#)
- De4xx_File_LAngVel
 - jeod::De4xxBase, [25](#)
- De4xx_File_LLibration
 - jeod::De4xxBase, [25](#)
- De4xx_File_Mars
 - jeod::De4xxBase, [25](#)
- De4xx_File_MaxEntries
 - jeod::De4xxBase, [25](#)
- De4xx_File_Mercury
 - jeod::De4xxBase, [25](#)
- De4xx_File_Moon
 - jeod::De4xxBase, [25](#)
- De4xx_File_Neptune
 - jeod::De4xxBase, [25](#)
- De4xx_File_Pluto
 - jeod::De4xxBase, [25](#)
- De4xx_File_Saturn
 - jeod::De4xxBase, [25](#)
- De4xx_File_Sun
 - jeod::De4xxBase, [25](#)
- De4xx_File_Uranus
 - jeod::De4xxBase, [25](#)
- De4xx_File_Venus
 - jeod::De4xxBase, [25](#)
- De4xx_File_tt_tdb
 - jeod::De4xxBase, [25](#)
- de4xx_base.hh, [169](#)
- de4xx_ephem.cc, [170](#)
- de4xx_ephem.hh, [171](#)
- de4xx_ephem_dynmanager.cc, [171](#)
- de4xx_file
 - jeod::De4xxFileRestart, [71](#)
- de4xx_file.cc, [172](#)
- de4xx_file.hh, [173](#)
- de4xx_file_init.cc, [174](#)

- de4xx_file_update.cc, 174
- De4xxEphem, 16
- De4xxEphemBodies
 - jeod::De4xxBase, 24
- De4xxEphemConsts
 - jeod::De4xxBase, 24
- De4xxEphemItem
 - jeod::De4xxEphemItem, 46
- De4xxEphemeris
 - jeod::De4xxEphemeris, 35
 - jeod::De4xxEphemItem, 46
- De4xxFile
 - jeod::De4xxFile, 49
 - jeod::De4xxFileCoef, 57
 - jeod::De4xxFileHeader, 59
 - jeod::De4xxFileIO, 62
 - jeod::De4xxFileItem, 66
 - jeod::De4xxFileRefTime, 68
 - jeod::De4xxFileSpec, 72
- De4xxFileCoef
 - jeod::De4xxFileCoef, 56
- De4xxFileEntries
 - jeod::De4xxBase, 25
- De4xxFileHeader
 - jeod::De4xxFileHeader, 59
- De4xxFileIO
 - jeod::De4xxFileIO, 62
- De4xxFileItem
 - jeod::De4xxFileItem, 65
- De4xxFileRefTime
 - jeod::De4xxFileRefTime, 68
- De4xxFileRestart
 - jeod::De4xxFile, 53
 - jeod::De4xxFileRestart, 70
- De4xxFileSpec
 - jeod::De4xxFileSpec, 72
- de_constants
 - jeod::EphemerisDataSetMeta, 96
- deactivate
 - jeod::De4xxEphemeris, 36
 - jeod::EphemerisItem, 104
 - jeod::PropagatedPlanet, 136
 - jeod::SinglePointEphemeris, 148
- debug
 - jeod::EphemeridesMessages, 91
- default_suffix
 - jeod::EphemerisItem, 104
 - jeod::EphemerisOrientation, 115
 - jeod::EphemerisPoint, 118
- delta_epoch
 - jeod::EphemerisDataSetMeta, 96
- denum
 - jeod::De4xxFileSpec, 73
- Deselected
 - jeod::De4xxEphemItem, 45
- determine_root_node
 - jeod::De4xxEphemeris, 36
- disable
 - jeod::EphemerisItem, 104
- disable_add_ephemeris
 - jeod::BaseEphemeridesManager, 29
 - jeod::EphemeridesManager, 83
- disconnect_from_tree
 - jeod::EphemerisItem, 104
 - jeod::EphemerisOrientation, 115
 - jeod::EphemerisPoint, 118
- duplicate_entry
 - jeod::EphemeridesMessages, 91
- dyn_manager
 - jeod::PropagatedPlanet, 139
- e1_em_dist_ratio
 - jeod::De4xxFileHeader, 60
- EPSILON_TIME
 - EphemItem, 18
- earth_moon_barycenter_frame
 - jeod::De4xxEphemeris, 41
- em_mass_ratio
 - jeod::De4xxFileHeader, 60
- EmptySpaceEphemeris
 - jeod::EmptySpaceEphemeris, 75
- enable
 - jeod::EphemerisItem, 105
 - jeod::EphemerisOrientation, 115
- enabled
 - jeod::EphemerisItem, 111
- enabled_item
 - jeod::De4xxEphemItem, 46
- Environment, 14
- ephem_activate
 - jeod::De4xxEphemeris, 37
 - jeod::EmptySpaceEphemeris, 75
 - jeod::EphemerisInterface, 98
 - jeod::PropagatedPlanet, 136
 - jeod::SinglePlanetEphemeris, 143
 - jeod::SinglePointEphemeris, 148
- ephem_build_tree
 - jeod::De4xxEphemeris, 37
 - jeod::EmptySpaceEphemeris, 75
 - jeod::EphemerisInterface, 98
 - jeod::PropagatedPlanet, 137
 - jeod::SinglePlanetEphemeris, 143
 - jeod::SinglePointEphemeris, 148
- ephem_file_dir
 - jeod::De4xxFileSpec, 73
- ephem_file_name
 - jeod::De4xxFileSpec, 73
- ephem_initialize
 - jeod::De4xxEphemeris, 37
 - jeod::EmptySpaceEphemeris, 75
 - jeod::EphemerisInterface, 98
 - jeod::PropagatedPlanet, 137
 - jeod::SinglePlanetEphemeris, 143
 - jeod::SinglePointEphemeris, 148
- ephem_interface.hh, 175
- ephem_item.cc, 175
- ephem_item.hh, 176

- ephem_item_inline.hh, 177
- ephem_items
 - jeod::EphemeridesManager, 88
- ephem_manager
 - jeod::EphemerisRefFrame, 122
- ephem_manager.cc, 177
- ephem_manager.hh, 177
- ephem_messages.cc, 178
- ephem_messages.hh, 179
- ephem_note_tree_status_change
 - jeod::BaseEphemeridesManager, 29
 - jeod::EphemeridesManager, 83
- ephem_orient
 - jeod::PropagatedPlanet, 140
- ephem_orient.cc, 179
- ephem_orient.hh, 180
- ephem_orient_zxz.cc, 180
- ephem_orient_zxz.hh, 181
- ephem_planet
 - jeod::PropagatedPlanet, 140
- ephem_point.cc, 181
- ephem_point.hh, 182
- ephem_ref_frame.cc, 182
- ephem_ref_frame.hh, 183
- ephem_update
 - jeod::De4xxEphemeris, 38
 - jeod::EphemerisInterface, 100
 - jeod::PropagatedPlanet, 137
 - jeod::SinglePointEphemeris, 148
- EphemInterface, 17
- EphemItem, 18
 - EPSILON_TIME, 18
 - TAYLOR_CUTOFF, 18
- EphemManager, 19
- Ephemerides, 15
- ephemerides
 - jeod::EphemeridesManager, 88
- EphemeridesManager
 - jeod::EphemeridesManager, 79, 80
- EphemeridesMessages
 - jeod::EphemeridesMessages, 90
- EphemerisItem
 - jeod::EphemerisItem, 103, 104
- EphemerisOrientation
 - jeod::EphemerisOrientation, 114
- EphemerisPoint
 - jeod::EphemerisPoint, 118
- EphemerisRefFrame
 - jeod::EphemerisRefFrame, 121
- EphemerisZXZOrientation
 - jeod::EphemerisZXZOrientation, 124
- epoch_date
 - jeod::De4xxFileRefTime, 68
- euler_angle_313
 - jeod::EphemerisZXZOrientation, 127
- euler_rate_313
 - jeod::EphemerisZXZOrientation, 127
- fdate
 - jeod::De4xxFileRefTime, 69
- file
 - jeod::De4xxEphemeris, 42
 - jeod::De4xxFileIO, 63
- file_error
 - jeod::EphemeridesMessages, 91
- file_spec
 - jeod::De4xxFile, 54
- find_base_planet
 - jeod::BaseEphemeridesManager, 30
 - jeod::EphemeridesManager, 84
- find_ephem_angle
 - jeod::BaseEphemeridesManager, 30
 - jeod::EphemeridesManager, 84
- find_ephem_item
 - jeod::BaseEphemeridesManager, 30
 - jeod::EphemeridesManager, 84
- find_ephem_point
 - jeod::BaseEphemeridesManager, 30
 - jeod::EphemeridesManager, 85
- find_integ_frame
 - jeod::BaseEphemeridesManager, 31
 - jeod::EphemeridesManager, 85
- find_integ_frame_index
 - jeod::BaseEphemeridesManager, 31
 - jeod::EphemeridesManager, 85
- find_planet
 - jeod::BaseEphemeridesManager, 31
 - jeod::EphemeridesManager, 86
- find_planet.cc, 183
- force_update
 - jeod::De4xxEphemeris, 42
- frame
 - jeod::De4xxEphemItem, 46
- garbage_file
 - jeod::EphemeridesMessages, 91
- get_enabled_item
 - jeod::EphemerisItem, 105
- get_euler_angles
 - jeod::EphemerisZXZOrientation, 124
- get_euler_rates
 - jeod::EphemerisZXZOrientation, 125
- get_head
 - jeod::EphemerisItem, 105
- get_header_data
 - jeod::De4xxEphemeris, 38
- get_integ_frames
 - jeod::BaseEphemeridesManager, 31
 - jeod::EphemeridesManager, 86
- get_manager
 - jeod::EphemerisItem, 105
- get_model_number
 - jeod::De4xxEphemeris, 38
 - jeod::De4xxFileSpec, 72
- get_name
 - jeod::De4xxEphemeris, 38
 - jeod::EphemerisInterface, 100
 - jeod::EphemerisItem, 105

- jeod::PropagatedPlanet, 137
- jeod::SinglePointEphemeris, 149
- get_next
 - jeod::EphemerisItem, 106
- get_num_planets
 - jeod::BaseEphemeridesManager, 32
 - jeod::EphemeridesManager, 86
- get_owner
 - jeod::EphemerisItem, 106
- get_target_frame
 - jeod::EphemerisItem, 106
- gmbody
 - jeod::De4xxFileHeader, 60
- head
 - jeod::EphemerisItem, 112
- header
 - jeod::De4xxFile, 54
- ident
 - jeod::De4xxEphemeris, 42
 - jeod::PropagatedPlanet, 140
- identifier
 - jeod::SinglePointEphemeris, 150
- InTree
 - jeod::De4xxEphemItem, 45
- Inactive
 - jeod::De4xxEphemItem, 45
- inconsistent_setup
 - jeod::EphemeridesMessages, 91
- index
 - jeod::De4xxEphemItem, 47
- init_attrjeod__BaseEphemeridesManager
 - jeod::BaseEphemeridesManager, 32
- init_attrjeod__De4xxEphemItem
 - jeod::De4xxEphemItem, 46
- init_attrjeod__De4xxEphemeris
 - jeod::De4xxEphemeris, 41
- init_attrjeod__De4xxFile
 - jeod::De4xxFile, 53
- init_attrjeod__De4xxFileCoef
 - jeod::De4xxFileCoef, 57
- init_attrjeod__De4xxFileHeader
 - jeod::De4xxFileHeader, 59
- init_attrjeod__De4xxFileIO
 - jeod::De4xxFileIO, 62
- init_attrjeod__De4xxFileItem
 - jeod::De4xxFileItem, 66
- init_attrjeod__De4xxFileRefTime
 - jeod::De4xxFileRefTime, 68
- init_attrjeod__De4xxFileSpec
 - jeod::De4xxFileSpec, 72
- init_attrjeod__EmptySpaceEphemeris
 - jeod::EmptySpaceEphemeris, 76
- init_attrjeod__EphemeridesManager
 - jeod::EphemeridesManager, 88
- init_attrjeod__EphemeridesMessages
 - jeod::EphemeridesMessages, 91
- init_attrjeod__EphemerisInterface
 - jeod::EphemerisInterface, 100
- init_attrjeod__EphemerisItem
 - jeod::EphemerisItem, 111
- init_attrjeod__EphemerisOrientation
 - jeod::EphemerisOrientation, 116
- init_attrjeod__EphemerisPoint
 - jeod::EphemerisPoint, 120
- init_attrjeod__EphemerisRefFrame
 - jeod::EphemerisRefFrame, 122
- init_attrjeod__EphemerisZXZOrientation
 - jeod::EphemerisZXZOrientation, 127
- init_attrjeod__PropagatedEphemerisOrientation
 - jeod::PropagatedEphemerisOrientation, 129
- init_attrjeod__PropagatedEphemerisPlanet
 - jeod::PropagatedEphemerisPlanet, 132
- init_attrjeod__PropagatedPlanet
 - jeod::PropagatedPlanet, 139
- init_attrjeod__SinglePlanetEphemeris
 - jeod::SinglePlanetEphemeris, 145
- init_attrjeod__SinglePointEphemeris
 - jeod::SinglePointEphemeris, 150
- init_time
 - jeod::De4xxFileRefTime, 69
- initialize
 - jeod::De4xxFile, 50
- initialize_ephemerides
 - jeod::EphemeridesManager, 86
- initialize_file
 - jeod::De4xxEphemeris, 38
- initialize_items
 - jeod::De4xxEphemeris, 39
- initialize_model
 - jeod::De4xxEphemeris, 39
 - jeod::EmptySpaceEphemeris, 76
 - jeod::PropagatedPlanet, 138
 - jeod::SinglePlanetEphemeris, 145
 - jeod::SinglePointEphemeris, 149
- initialize_state
 - jeod::EphemerisPoint, 118
- initialize_time
 - jeod::De4xxEphemeris, 40
- initialized
 - jeod::PropagatedPlanet, 140
- InputProcessor
 - jeod::BaseEphemeridesManager, 32
 - jeod::De4xxEphemeris, 41
 - jeod::De4xxEphemItem, 46
 - jeod::De4xxFile, 54
 - jeod::De4xxFileCoef, 57
 - jeod::De4xxFileHeader, 59
 - jeod::De4xxFileIO, 62
 - jeod::De4xxFileItem, 66
 - jeod::De4xxFileRefTime, 68
 - jeod::De4xxFileSpec, 73
 - jeod::EmptySpaceEphemeris, 76
 - jeod::EphemeridesManager, 88
 - jeod::EphemeridesMessages, 91
 - jeod::EphemerisInterface, 100

- jeod::EphemerisItem, 111
- jeod::EphemerisOrientation, 116
- jeod::EphemerisPoint, 120
- jeod::EphemerisRefFrame, 122
- jeod::EphemerisZXZOrientation, 127
- jeod::PropagatedEphemerisOrientation, 129
- jeod::PropagatedEphemerisPlanet, 132
- jeod::PropagatedPlanet, 139
- jeod::SinglePlanetEphemeris, 145
- jeod::SinglePointEphemeris, 150
- integ_frames
 - jeod::EphemeridesManager, 88
- internal_error
 - jeod::EphemeridesMessages, 92
- interpolate
 - jeod::De4xxFile, 50
- invalid_item
 - jeod::EphemeridesMessages, 92
- invalid_name
 - jeod::EphemeridesMessages, 92
- io
 - jeod::De4xxFile, 54
- IsRoot
 - jeod::De4xxEphemItem, 45
- is_activatable
 - jeod::EphemerisItem, 106
- is_active
 - jeod::EphemerisItem, 107
- is_enabled
 - jeod::EphemerisItem, 107
- is_integ_frame
 - jeod::BaseEphemeridesManager, 32
 - jeod::EphemeridesManager, 87
- item
 - jeod::De4xxEphemItem, 47
 - jeod::De4xxFile, 54
- item_data
 - jeod::De4xxEphemeris, 42
- item_idx
 - jeod::De4xxFileItem, 66
- item_not_in_file
 - jeod::EphemeridesMessages, 92
- itemData
 - de405_0.cc, 153
 - de421_0.cc, 163
 - de440_0.cc, 165
 - jeod::De4xxFileIO, 63
- jeod, 21
 - l1_point, 23
 - process_mem_usage, 23
- jeod::De4xxBase
 - De4xx_Const_AU, 25
 - De4xx_Const_CLIGHT, 25
 - De4xx_Const_DENUM, 25
 - De4xx_Const_EMERAT, 25
 - De4xx_Const_GM1, 25
 - De4xx_Const_GM2, 25
 - De4xx_Const_GM4, 25
 - De4xx_Const_GM5, 25
 - De4xx_Const_GM6, 25
 - De4xx_Const_GM7, 25
 - De4xx_Const_GM8, 25
 - De4xx_Const_GM9, 25
 - De4xx_Const_GMB, 25
 - De4xx_Const_GMS, 25
 - De4xx_Const_LENUM, 25
 - De4xx_Const_MaxConsts, 25
 - De4xx_Ephem_EML1, 24
 - De4xx_Ephem_EMBary, 24
 - De4xx_Ephem_ENutation, 24
 - De4xx_Ephem_Earth, 24
 - De4xx_Ephem_Jupiter, 24
 - De4xx_Ephem_LLibration, 24
 - De4xx_Ephem_Mars, 24
 - De4xx_Ephem_MaxBodies, 24
 - De4xx_Ephem_Mercury, 24
 - De4xx_Ephem_Moon, 24
 - De4xx_Ephem_Neptune, 24
 - De4xx_Ephem_Pluto, 24
 - De4xx_Ephem_SSbary, 24
 - De4xx_Ephem_Saturn, 24
 - De4xx_Ephem_Sun, 24
 - De4xx_Ephem_Uranus, 24
 - De4xx_Ephem_Venus, 24
 - De4xx_File_EMBary, 25
 - De4xx_File_ENutation, 25
 - De4xx_File_Jupiter, 25
 - De4xx_File_LAngVel, 25
 - De4xx_File_LLibration, 25
 - De4xx_File_Mars, 25
 - De4xx_File_MaxEntries, 25
 - De4xx_File_Mercury, 25
 - De4xx_File_Moon, 25
 - De4xx_File_Neptune, 25
 - De4xx_File_Pluto, 25
 - De4xx_File_Saturn, 25
 - De4xx_File_Sun, 25
 - De4xx_File_Uranus, 25
 - De4xx_File_Venus, 25
 - De4xx_File_tt_tdb, 25
- jeod::De4xxEphemItem
 - Active, 45
 - Deselected, 45
 - InTree, 45
 - Inactive, 45
 - IsRoot, 45
- jeod::EphemerisItem
 - Rotation, 103
 - Translation, 103
- jeod::PropagatedPlanet
 - TransFromBody_RotFromBody, 136
 - TransFromBody_RotFromPlanet, 135
 - TransFromPlanet_RotFromBody, 135
 - TransFromPlanet_RotFromPlanet, 135
- jeod::BaseEphemeridesManager, 27
 - ~BaseEphemeridesManager, 28

- add_ephem_item, 28
- add_ephemeris, 29
- add_integ_frame, 29
- add_planet, 29
- clear_added_ephemerides, 29
- disable_add_ephemeris, 29
- ephem_note_tree_status_change, 29
- find_base_planet, 30
- find_ephem_angle, 30
- find_ephem_item, 30
- find_ephem_point, 30
- find_integ_frame, 31
- find_integ_frame_index, 31
- find_planet, 31
- get_integ_frames, 31
- get_num_planets, 32
- init_attrjeod__BaseEphemeridesManager, 32
- InputProcessor, 32
- is_integ_frame, 32
- jeod::De4xxBase, 23
 - __attribute__, 26
 - De4xxEphemBodies, 24
 - De4xxEphemConsts, 24
 - De4xxFileEntries, 25
 - number_grav_models, 26
 - number_jeod_items, 26
 - number_physical_bodies, 26
 - number_trans_points, 26
- jeod::De4xxEphemItem, 44
 - ~De4xxEphemItem, 46
 - De4xxEphemItem, 46
 - De4xxEphemeris, 46
 - enabled_item, 46
 - frame, 46
 - index, 47
 - init_attrjeod__De4xxEphemItem, 46
 - InputProcessor, 46
 - item, 47
 - name, 47
 - operator=, 46
 - Status, 45
 - status, 47
- jeod::De4xxEphemeris, 32
 - ~De4xxEphemeris, 35
 - activate, 36
 - activate_em_nodes, 36
 - activate_nodes, 36
 - active, 41
 - body_to_file_idx, 41
 - De4xxEphemeris, 35
 - deactivate, 36
 - determine_root_node, 36
 - earth_moon_barycenter_frame, 41
 - ephem_activate, 37
 - ephem_build_tree, 37
 - ephem_initialize, 37
 - ephem_update, 38
 - file, 42
 - force_update, 42
 - get_header_data, 38
 - get_model_number, 38
 - get_name, 38
 - ident, 42
 - init_attrjeod__De4xxEphemeris, 41
 - initialize_file, 38
 - initialize_items, 39
 - initialize_model, 39
 - initialize_time, 40
 - InputProcessor, 41
 - item_data, 42
 - lunar_orientation, 42
 - nactive_items, 43
 - operator=, 40
 - points, 43
 - propagate_lunar_rnp, 40
 - root_item, 43
 - selected_items, 43
 - set_model_number, 40
 - shutdown, 40
 - solar_system_barycenter_frame, 43
 - time_dyn, 43
 - time_is_in_range, 40
 - time_tt, 44
 - timestamp, 41
 - update_time, 44
- jeod::De4xxFile, 47
 - ~De4xxFile, 49
 - capture_mem_stats, 49
 - close, 49
 - coef, 54
 - De4xxFile, 49
 - De4xxFileRestart, 53
 - file_spec, 54
 - header, 54
 - init_attrjeod__De4xxFile, 53
 - initialize, 50
 - InputProcessor, 54
 - interpolate, 50
 - io, 54
 - item, 54
 - logMemoryStats, 55
 - open, 51
 - operator=, 51
 - pre_initialize, 51
 - ref_time, 55
 - reopen, 51
 - resident_set, 55
 - restart, 55
 - shutdown, 52
 - time_is_in_range, 52
 - update, 52
 - update_time, 55
 - vm_usage, 55
- jeod::De4xxFileCoef, 56
 - chebyderiv, 57
 - chebypoly, 57

- chebyterms, 57
- chebyx, 57
- coef, 57
- De4xxFile, 57
- De4xxFileCoef, 56
- init_attrjeod__De4xxFileCoef, 57
- InputProcessor, 57
- operator=, 57
- jeod::De4xxFileHeader, 58
 - ~De4xxFileHeader, 59
 - au, 59
 - b1_em_dist_ratio, 60
 - be_em_dist_ratio, 60
 - bm_em_dist_ratio, 60
 - De4xxFile, 59
 - De4xxFileHeader, 59
 - e1_em_dist_ratio, 60
 - em_mass_ratio, 60
 - gmbdy, 60
 - init_attrjeod__De4xxFileHeader, 59
 - InputProcessor, 59
 - operator=, 59
 - vlight, 61
- jeod::De4xxFileIO, 61
 - coeffs_segment_starting_addr, 63
 - current_record_starting_addr, 63
 - De4xxFile, 62
 - De4xxFileIO, 62
 - file, 63
 - init_attrjeod__De4xxFileIO, 62
 - InputProcessor, 62
 - itemData, 63
 - max_terms, 63
 - metaData, 63
 - operator=, 62
 - recno, 63
 - segment_index, 64
 - segment_recno, 64
 - segmentData, 64
 - total_num_recs, 64
- jeod::De4xxFileItem, 64
 - active, 66
 - avail, 66
 - De4xxFile, 66
 - De4xxFileItem, 65
 - init_attrjeod__De4xxFileItem, 66
 - InputProcessor, 66
 - item_idx, 66
 - nitems, 66
 - operator=, 66
 - pscale, 66
 - state, 67
 - update_time, 67
- jeod::De4xxFileRefTime, 67
 - block_no, 68
 - De4xxFile, 68
 - De4xxFileRefTime, 68
 - epoch_date, 68
 - fdate, 69
 - init_attrjeod__De4xxFileRefTime, 68
 - init_time, 69
 - InputProcessor, 68
 - operator=, 68
 - time_offset, 69
- jeod::De4xxFileRestart, 69
 - ~De4xxFileRestart, 70
 - de4xx_file, 71
 - De4xxFileRestart, 70
 - operator=, 70
 - simple_restore, 70
- jeod::De4xxFileSpec, 71
 - De4xxFile, 72
 - De4xxFileSpec, 72
 - denum, 73
 - ephem_file_dir, 73
 - ephem_file_name, 73
 - get_model_number, 72
 - init_attrjeod__De4xxFileSpec, 72
 - InputProcessor, 73
 - operator=, 72
 - pathname, 73
 - set_model_number, 72
- jeod::EmptySpaceEphemeris, 73
 - ~EmptySpaceEphemeris, 75
 - central_frame, 76
 - central_point, 77
 - EmptySpaceEphemeris, 75
 - ephem_activate, 75
 - ephem_build_tree, 75
 - ephem_initialize, 75
 - init_attrjeod__EmptySpaceEphemeris, 76
 - initialize_model, 76
 - InputProcessor, 76
 - operator=, 76
 - set_name, 76
- jeod::EphemeridesManager, 77
 - ~EphemeridesManager, 79
 - activate_ephemerides, 80
 - add_ephem_item, 80
 - add_ephemeris, 81
 - add_integ_frame, 81
 - add_planet, 81
 - add_ref_frame, 83
 - clear_added_ephemerides, 83
 - disable_add_ephemeris, 83
 - ephem_items, 88
 - ephem_note_tree_status_change, 83
 - ephemerides, 88
 - EphemeridesManager, 79, 80
 - find_base_planet, 84
 - find_ephem_angle, 84
 - find_ephem_item, 84
 - find_ephem_point, 85
 - find_integ_frame, 85
 - find_integ_frame_index, 85
 - find_planet, 86

- get_integ_frames, 86
- get_num_planets, 86
- init_attrjeod__EphemeridesManager, 88
- initialize_ephemerides, 86
- InputProcessor, 88
- integ_frames, 88
- is_integ_frame, 87
- operator=, 87
- planets, 88
- ref_frame_tree_needs_rebuild, 87
- regenerate_ref_frame_tree, 89
- set_target_frame, 87
- single_ephem_mode, 89
- update_ephemerides, 87
- update_time, 89
- jeod::EphemeridesMessages, 89
 - debug, 91
 - duplicate_entry, 91
 - EphemeridesMessages, 90
 - file_error, 91
 - garbage_file, 91
 - inconsistent_setup, 91
 - init_attrjeod__EphemeridesMessages, 91
 - InputProcessor, 91
 - internal_error, 92
 - invalid_item, 92
 - invalid_name, 92
 - item_not_in_file, 92
 - null_pointer, 92
 - operator=, 91
 - single_ephem_mode, 93
 - time_not_in_range, 93
 - unsupported_architecture, 93
- jeod::EphemerisDataItemMeta, 93
 - npoly, 94
 - nterms, 94
 - offset, 94
- jeod::EphemerisDataSegmentMeta, 94
 - num_recs, 95
 - start_epoch, 95
 - stop_epoch, 95
- jeod::EphemerisDataSetMeta, 95
 - de_constants, 96
 - delta_epoch, 96
 - ncoeff, 96
 - number_file_items, 96
 - number_segments, 96
 - start_epoch, 97
 - stop_epoch, 97
- jeod::EphemerisInterface, 97
 - ~EphemerisInterface, 98
 - ephem_activate, 98
 - ephem_build_tree, 98
 - ephem_initialize, 98
 - ephem_update, 100
 - get_name, 100
 - init_attrjeod__EphemerisInterface, 100
 - InputProcessor, 100
 - timestamp, 100
- jeod::EphemerisItem, 100
 - ~EphemerisItem, 103
 - activate, 104
 - active, 111
 - deactivate, 104
 - default_suffix, 104
 - disable, 104
 - disconnect_from_tree, 104
 - enable, 105
 - enabled, 111
 - EphemerisItem, 103, 104
 - get_enabled_item, 105
 - get_head, 105
 - get_manager, 105
 - get_name, 105
 - get_next, 106
 - get_owner, 106
 - get_target_frame, 106
 - head, 112
 - init_attrjeod__EphemerisItem, 111
 - InputProcessor, 111
 - is_activatable, 106
 - is_active, 107
 - is_enabled, 107
 - manager, 112
 - name, 112
 - next, 112
 - operator=, 107
 - owner, 112
 - set_head, 107
 - set_manager, 107
 - set_name, 109
 - set_name_internal, 109
 - set_next, 109
 - set_owner, 109
 - set_target_frame, 110
 - set_timestamp, 110
 - target_frame, 112
 - TargetAspect, 103
 - timestamp, 110
 - update_time, 113
 - updates_what, 110
 - validate_name, 111
- jeod::EphemerisOrientation, 113
 - ~EphemerisOrientation, 114
 - default_suffix, 115
 - disconnect_from_tree, 115
 - enable, 115
 - EphemerisOrientation, 114
 - init_attrjeod__EphemerisOrientation, 116
 - InputProcessor, 116
 - note_frame_status_change, 115
 - operator=, 115
 - subscribed_to_inertial, 116
 - updates_what, 115
- jeod::EphemerisPoint, 116
 - ~EphemerisPoint, 118

- default_suffix, 118
- disconnect_from_tree, 118
- EphemerisPoint, 118
- init_attrjeod__EphemerisPoint, 120
- initialize_state, 118
- InputProcessor, 120
- note_frame_status_change, 118
- operator=, 119
- update, 119
- update_scaled, 119
- updates_what, 119
- jeod::EphemerisRefFrame, 120
 - ~EphemerisRefFrame, 121
 - ephem_manager, 122
 - EphemerisRefFrame, 121
 - init_attrjeod__EphemerisRefFrame, 122
 - InputProcessor, 122
 - operator=, 122
 - set_active_status, 122
 - set_ephem_manager, 122
- jeod::EphemerisZXZOrientation, 123
 - ~EphemerisZXZOrientation, 124
 - EphemerisZXZOrientation, 124
 - euler_angle_313, 127
 - euler_rate_313, 127
 - get_euler_angles, 124
 - get_euler_rates, 125
 - init_attrjeod__EphemerisZXZOrientation, 127
 - InputProcessor, 127
 - operator=, 125
 - propagate, 125
 - update, 125
- jeod::PropagatedEphemerisOrientation, 127
 - ~PropagatedEphemerisOrientation, 129
 - body, 130
 - body_ref_frame, 130
 - init_attrjeod__PropagatedEphemerisOrientation, 129
 - InputProcessor, 129
 - operator=, 129
 - PropagatedEphemerisOrientation, 129
 - update, 129
- jeod::PropagatedEphemerisPlanet, 130
 - ~PropagatedEphemerisPlanet, 132
 - body, 132
 - body_ref_frame, 133
 - init_attrjeod__PropagatedEphemerisPlanet, 132
 - InputProcessor, 132
 - operator=, 132
 - PropagatedEphemerisPlanet, 131, 132
 - update, 132
- jeod::PropagatedPlanet, 133
 - ~PropagatedPlanet, 136
 - activate, 136
 - active, 139
 - body, 139
 - commanded_mode, 139
 - deactivate, 136
 - dyn_manager, 139
 - ephem_activate, 136
 - ephem_build_tree, 137
 - ephem_initialize, 137
 - ephem_orient, 140
 - ephem_planet, 140
 - ephem_update, 137
 - get_name, 137
 - ident, 140
 - init_attrjeod__PropagatedPlanet, 139
 - initialize_model, 138
 - initialized, 140
 - InputProcessor, 139
 - Mode, 135
 - mode, 140
 - operator=, 138
 - parent_frame, 140
 - parent_name, 141
 - planet, 141
 - planet_name, 141
 - PropagatedPlanet, 136
 - set_commanded_mode, 138
 - set_mode, 138
 - shutdown, 138
 - time_dyn, 141
 - timestamp, 138
 - update_time, 141
- jeod::SinglePlanetEphemeris, 141
 - ~SinglePlanetEphemeris, 143
 - central_point, 145
 - ephem_activate, 143
 - ephem_build_tree, 143
 - ephem_initialize, 143
 - init_attrjeod__SinglePlanetEphemeris, 145
 - initialize_model, 145
 - InputProcessor, 145
 - operator=, 145
 - set_name, 145
 - SinglePlanetEphemeris, 143
- jeod::SinglePointEphemeris, 146
 - ~SinglePointEphemeris, 147
 - activate, 148
 - active, 150
 - deactivate, 148
 - ephem_activate, 148
 - ephem_build_tree, 148
 - ephem_initialize, 148
 - ephem_update, 148
 - get_name, 149
 - identifier, 150
 - init_attrjeod__SinglePointEphemeris, 150
 - initialize_model, 149
 - InputProcessor, 150
 - operator=, 149
 - set_name, 149
 - SinglePointEphemeris, 147
 - timestamp, 149
 - update_time, 150

- l1_point
 - jeod, [23](#)
- logMemoryStats
 - jeod::De4xxFile, [55](#)
- lunar_orientation
 - jeod::De4xxEphemeris, [42](#)
- manager
 - jeod::EphemerisItem, [112](#)
- max_terms
 - jeod::De4xxFileIO, [63](#)
- metaData
 - de405_0.cc, [153](#)
 - de421_0.cc, [163](#)
 - de440_0.cc, [165](#)
 - jeod::De4xxFileIO, [63](#)
- Mode
 - jeod::PropagatedPlanet, [135](#)
- mode
 - jeod::PropagatedPlanet, [140](#)
- Models, [13](#)
- nactive_items
 - jeod::De4xxEphemeris, [43](#)
- name
 - jeod::De4xxEphemItem, [47](#)
 - jeod::EphemerisItem, [112](#)
- ncoeff
 - jeod::EphemerisDataSetMeta, [96](#)
- next
 - jeod::EphemerisItem, [112](#)
- nitems
 - jeod::De4xxFileItem, [66](#)
- note_frame_status_change
 - jeod::EphemerisOrientation, [115](#)
 - jeod::EphemerisPoint, [118](#)
- npoly
 - jeod::EphemerisDataItemMeta, [94](#)
- nterms
 - jeod::EphemerisDataItemMeta, [94](#)
- null_pointer
 - jeod::EphemeridesMessages, [92](#)
- num_recs
 - jeod::EphemerisDataSegmentMeta, [95](#)
- number_file_items
 - jeod::EphemerisDataSetMeta, [96](#)
- number_grav_models
 - jeod::De4xxBase, [26](#)
- number_jeod_items
 - jeod::De4xxBase, [26](#)
- number_physical_bodies
 - jeod::De4xxBase, [26](#)
- number_segments
 - jeod::EphemerisDataSetMeta, [96](#)
- number_trans_points
 - jeod::De4xxBase, [26](#)
- offset
 - jeod::EphemerisDataItemMeta, [94](#)
- open
 - jeod::De4xxFile, [51](#)
- operator=
 - jeod::De4xxEphemeris, [40](#)
 - jeod::De4xxEphemItem, [46](#)
 - jeod::De4xxFile, [51](#)
 - jeod::De4xxFileCoef, [57](#)
 - jeod::De4xxFileHeader, [59](#)
 - jeod::De4xxFileIO, [62](#)
 - jeod::De4xxFileItem, [66](#)
 - jeod::De4xxFileRefTime, [68](#)
 - jeod::De4xxFileRestart, [70](#)
 - jeod::De4xxFileSpec, [72](#)
 - jeod::EmptySpaceEphemeris, [76](#)
 - jeod::EphemeridesManager, [87](#)
 - jeod::EphemeridesMessages, [91](#)
 - jeod::EphemerisItem, [107](#)
 - jeod::EphemerisOrientation, [115](#)
 - jeod::EphemerisPoint, [119](#)
 - jeod::EphemerisRefFrame, [122](#)
 - jeod::EphemerisZXZOrientation, [125](#)
 - jeod::PropagatedEphemerisOrientation, [129](#)
 - jeod::PropagatedEphemerisPlanet, [132](#)
 - jeod::PropagatedPlanet, [138](#)
 - jeod::SinglePlanetEphemeris, [145](#)
 - jeod::SinglePointEphemeris, [149](#)
- owner
 - jeod::EphemerisItem, [112](#)
- parent_frame
 - jeod::PropagatedPlanet, [140](#)
- parent_name
 - jeod::PropagatedPlanet, [141](#)
- pathname
 - jeod::De4xxFileSpec, [73](#)
- planet
 - jeod::PropagatedPlanet, [141](#)
- planet_name
 - jeod::PropagatedPlanet, [141](#)
- planets
 - jeod::EphemeridesManager, [88](#)
- points
 - jeod::De4xxEphemeris, [43](#)
- pre_initialize
 - jeod::De4xxFile, [51](#)
- process_mem_usage
 - jeod, [23](#)
- propagate
 - jeod::EphemerisZXZOrientation, [125](#)
- propagate_lunar_rnp
 - jeod::De4xxEphemeris, [40](#)
- propagated_planet.cc, [184](#)
- propagated_planet.hh, [185](#)
- PropagatedEphemerisOrientation
 - jeod::PropagatedEphemerisOrientation, [129](#)
- PropagatedEphemerisPlanet
 - jeod::PropagatedEphemerisPlanet, [131](#), [132](#)
- PropagatedPlanet, [20](#)
- jeod::PropagatedPlanet, [136](#)

pscale
 jeod::De4xxFileItem, [66](#)

 recno
 jeod::De4xxFileIO, [63](#)
 ref_frame_tree_needs_rebuild
 jeod::EphemeridesManager, [87](#)
 ref_time
 jeod::De4xxFile, [55](#)
 regenerate_ref_frame_tree
 jeod::EphemeridesManager, [89](#)
 reopen
 jeod::De4xxFile, [51](#)
 resident_set
 jeod::De4xxFile, [55](#)
 restart
 jeod::De4xxFile, [55](#)
 root_item
 jeod::De4xxEphemeris, [43](#)
 Rotation
 jeod::EphemerisItem, [103](#)

 segment_coeffs_0
 de405_0.cc, [153](#)
 de421_0.cc, [164](#)
 de440_0.cc, [165](#)
 segment_coeffs_1
 de405_1.cc, [153](#)
 de421_1.cc, [165](#)
 de440_1.cc, [166](#)
 segment_coeffs_10
 de405_10.cc, [154](#)
 de440_10.cc, [166](#)
 segment_coeffs_11
 de405_11.cc, [154](#)
 segment_coeffs_12
 de405_12.cc, [154](#)
 segment_coeffs_13
 de405_13.cc, [155](#)
 segment_coeffs_14
 de405_14.cc, [155](#)
 segment_coeffs_15
 de405_15.cc, [155](#)
 segment_coeffs_16
 de405_16.cc, [156](#)
 segment_coeffs_17
 de405_17.cc, [156](#)
 segment_coeffs_18
 de405_18.cc, [156](#)
 segment_coeffs_19
 de405_19.cc, [157](#)
 segment_coeffs_2
 de405_2.cc, [157](#)
 de440_2.cc, [166](#)
 segment_coeffs_20
 de405_20.cc, [157](#)
 segment_coeffs_21
 de405_21.cc, [158](#)
 segment_coeffs_22
 de405_22.cc, [158](#)
 segment_coeffs_23
 de405_23.cc, [158](#)
 segment_coeffs_24
 de405_24.cc, [159](#)
 segment_coeffs_25
 de405_25.cc, [159](#)
 segment_coeffs_26
 de405_26.cc, [159](#)
 segment_coeffs_27
 de405_27.cc, [160](#)
 segment_coeffs_28
 de405_28.cc, [160](#)
 segment_coeffs_29
 de405_29.cc, [160](#)
 segment_coeffs_3
 de405_3.cc, [161](#)
 de440_3.cc, [167](#)
 segment_coeffs_30
 de405_30.cc, [161](#)
 segment_coeffs_4
 de405_4.cc, [161](#)
 de440_4.cc, [167](#)
 segment_coeffs_5
 de405_5.cc, [162](#)
 de440_5.cc, [167](#)
 segment_coeffs_6
 de405_6.cc, [162](#)
 de440_6.cc, [168](#)
 segment_coeffs_7
 de405_7.cc, [162](#)
 de440_7.cc, [168](#)
 segment_coeffs_8
 de405_8.cc, [163](#)
 de440_8.cc, [168](#)
 segment_coeffs_9
 de405_9.cc, [163](#)
 de440_9.cc, [169](#)
 segment_index
 jeod::De4xxFileIO, [64](#)
 segment_recno
 jeod::De4xxFileIO, [64](#)
 segmentData
 de405_0.cc, [153](#)
 de421_0.cc, [164](#)
 de440_0.cc, [165](#)
 jeod::De4xxFileIO, [64](#)
 selected_items
 jeod::De4xxEphemeris, [43](#)
 set_active_status
 jeod::EphemerisRefFrame, [122](#)
 set_commanded_mode
 jeod::PropagatedPlanet, [138](#)
 set_ephem_manager
 jeod::EphemerisRefFrame, [122](#)
 set_head
 jeod::EphemerisItem, [107](#)
 set_manager

- jeod::EphemerisItem, 107
- set_mode
 - jeod::PropagatedPlanet, 138
- set_model_number
 - jeod::De4xxEphemeris, 40
 - jeod::De4xxFileSpec, 72
- set_name
 - jeod::EmptySpaceEphemeris, 76
 - jeod::EphemerisItem, 109
 - jeod::SinglePlanetEphemeris, 145
 - jeod::SinglePointEphemeris, 149
- set_name_internal
 - jeod::EphemerisItem, 109
- set_next
 - jeod::EphemerisItem, 109
- set_owner
 - jeod::EphemerisItem, 109
- set_target_frame
 - jeod::EphemeridesManager, 87
 - jeod::EphemerisItem, 110
- set_timestamp
 - jeod::EphemerisItem, 110
- shutdown
 - jeod::De4xxEphemeris, 40
 - jeod::De4xxFile, 52
 - jeod::PropagatedPlanet, 138
- simple_ephemerides.cc, 185
- simple_ephemerides.hh, 186
- simple_restore
 - jeod::De4xxFileRestart, 70
- single_ephem_mode
 - jeod::EphemeridesManager, 89
 - jeod::EphemeridesMessages, 93
- SinglePlanetEphemeris
 - jeod::SinglePlanetEphemeris, 143
- SinglePointEphemeris
 - jeod::SinglePointEphemeris, 147
- solar_system_barycenter_frame
 - jeod::De4xxEphemeris, 43
- start_epoch
 - jeod::EphemerisDataSegmentMeta, 95
 - jeod::EphemerisDataSetMeta, 97
- state
 - jeod::De4xxFileItem, 67
- Status
 - jeod::De4xxEphemItem, 45
- status
 - jeod::De4xxEphemItem, 47
- stop_epoch
 - jeod::EphemerisDataSegmentMeta, 95
 - jeod::EphemerisDataSetMeta, 97
- subscribed_to_inertial
 - jeod::EphemerisOrientation, 116
- TAYLOR_CUTOFF
 - EphemItem, 18
- target_frame
 - jeod::EphemerisItem, 112
- TargetAspect
 - jeod::EphemerisItem, 103
- time_dyn
 - jeod::De4xxEphemeris, 43
 - jeod::PropagatedPlanet, 141
- time_is_in_range
 - jeod::De4xxEphemeris, 40
 - jeod::De4xxFile, 52
- time_not_in_range
 - jeod::EphemeridesMessages, 93
- time_offset
 - jeod::De4xxFileRefTime, 69
- time_tt
 - jeod::De4xxEphemeris, 44
- timestamp
 - jeod::De4xxEphemeris, 41
 - jeod::EphemerisInterface, 100
 - jeod::EphemerisItem, 110
 - jeod::PropagatedPlanet, 138
 - jeod::SinglePointEphemeris, 149
- total_num_recs
 - jeod::De4xxFileIO, 64
- TransFromBody_RotFromBody
 - jeod::PropagatedPlanet, 136
- TransFromBody_RotFromPlanet
 - jeod::PropagatedPlanet, 135
- TransFromPlanet_RotFromBody
 - jeod::PropagatedPlanet, 135
- TransFromPlanet_RotFromPlanet
 - jeod::PropagatedPlanet, 135
- Translation
 - jeod::EphemerisItem, 103
- unsupported_architecture
 - jeod::EphemeridesMessages, 93
- update
 - jeod::De4xxFile, 52
 - jeod::EphemerisPoint, 119
 - jeod::EphemerisZXZOrientation, 125
 - jeod::PropagatedEphemerisOrientation, 129
 - jeod::PropagatedEphemerisPlanet, 132
- update_ephemerides
 - jeod::EphemeridesManager, 87
- update_scaled
 - jeod::EphemerisPoint, 119
- update_time
 - jeod::De4xxEphemeris, 44
 - jeod::De4xxFile, 55
 - jeod::De4xxFileItem, 67
 - jeod::EphemeridesManager, 89
 - jeod::EphemerisItem, 113
 - jeod::PropagatedPlanet, 141
 - jeod::SinglePointEphemeris, 150
- updates_what
 - jeod::EphemerisItem, 110
 - jeod::EphemerisOrientation, 115
 - jeod::EphemerisPoint, 119
- validate_name
 - jeod::EphemerisItem, 111

vlight
 jeod::De4xxFileHeader, [61](#)
vm_usage
 jeod::De4xxFile, [55](#)