

# Package ‘rneos’

July 26, 2012

**Version** 0.2-7

**Date** 2012-07-22

**Title** rneos: XML-RPC Interface to NEOS

**Depends** R (>= 2.10.0), methods, XMLRPC, RCurl, XML, stats

**LazyLoad** yes

**Description** Within this package the XML-RPC API to NEOS is implemented. This enables the user to pass optimization problems to NEOS and retrieve results within R.

**License** GPL (>= 2)

**Author** Bernhard Pfaff [aut, cre]

**Maintainer** Bernhard Pfaff <bernhard@pfaffikus.de>

**Repository** CRAN

**Repository/R-Forge/Project** rneos

**Repository/R-Forge/Revision** 224

**Date/Publication** 2012-07-26 21:32:19

## R topics documented:

CreateNeosComm . . . . .	2
CreateXmlString . . . . .	3
NemailHelp . . . . .	4
NeosAns-class . . . . .	5
NeosComm-class . . . . .	6
NeosJob-class . . . . .	7
NeosOff-class . . . . .	8
NeosXml-class . . . . .	9
NgetFinalResults . . . . .	11

NgetFinalResultsNonBlocking . . . . .	12
NgetIntermediateResults . . . . .	13
NgetIntermediateResultsNonBlocking . . . . .	15
NgetJobInfo . . . . .	16
NgetJobStatus . . . . .	17
NgetSolverTemplate . . . . .	19
Nhelp . . . . .	20
NkillJob . . . . .	21
NlistAllSolvers . . . . .	22
NlistCategories . . . . .	23
NlistSolversInCategory . . . . .	24
Nping . . . . .	25
NprintQueue . . . . .	26
NsubmitJob . . . . .	27
Nversion . . . . .	28
Nwelcome . . . . .	29
<b>Index</b>	<b>30</b>

CreateNeosComm

*Creating an object for communications with NEOS*

## Description

This function creates an object of class NeosComm that will contain all necessary information for dealing with HTTP requests to NEOS. This object will be needed in all requests to NEOS and hence must be created in advance of XML-RPC requests.

## Usage

```
CreateNeosComm(curlopts = list(httpheader = c('Content-Type' =
"text/xml", 'User-Agent' = "R"), port = 3332), curlhandle =
getCurlHandle())
```

## Arguments

curlopts	A named list of elements that are passed as options to curl. By default, the httpheader and the port options are preset.
curlhandle	An object of class CURLHandle. By default the returned object of getCurlHandle() is employed.

## Details

A list of valid curl options can be retrieved from listCurlOptions(). Please note, that the relevant HTTP-bodies within the requests will be created directly in the API-functions provided in this package and must not be provided as list elements in curloptions. However, if one accesses NEOS *via* a Proxy-Server, for instance, than the values for the relevant options must be set within the list-argument curlopts. The values of the returned object will be passed down to the function

`xml.rpc()` which is utilised for all calls to the function `Nfoo` contained in this package. Hereby, `foo` signify the name of NEOS-API.

**Value**

An object of class `NeosComm`.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for R Curl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>,  
libcurl web site: <http://curl.haxx.se>

**See Also**

[NeosComm](#)

**Examples**

```
## Not run:  
  
nc <- CreateNeosComm()  
nc  
  
## End(Not run)
```

---

CreateXmlString

*Inserting CDATA into XML-templates of NEOS*

---

**Description**

With this function the information for XML-templates can be inserted. Ordinarily, one creates an object with the function `NgetSolverTemplate()` first and then inserts the requested CDATA fields of this XML-form with this function.

**Usage**

```
CreateXmlString(neosxml, cdataList)
```

**Arguments**

<code>neosxml</code>	An object of class <code>NeosXml</code> created with the function <code>NgetSolverTemplate()</code> .
<code>cdataList</code>	A named list object with the CDATA tags to be filled.

**Value**

A character string containing the specified optimization problem, which can then be used in a call to `NsubmitJob()`.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosXml](#) and [NgetSolverTemplate](#)

**Examples**

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
  inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
cat(modc)
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
cat(datc)
## create list object
argslst <- list(model = modc, data = datc, commands = "",
  comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslst)
xmls

## End(Not run)
```

**Description**

This functions calls the XML-RPC method “emailHelp()” of NEOS and returns general help message for email users.

**Usage**

```
NemailHelp(convert = TRUE, nc = CreateNeosComm())
```

**Arguments**

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:

NemailHelp()

## End(Not run)
```

---

NeosAns-class

---

Class "NeosAns"

---

**Description**

Objects of this class contain the returned results from NEOS as well as information on which kind of query has been sent and how it was sent.

**Objects from the Class**

Objects can be created by calls of the form `new("NeosAns", ...)` or more conveniently by calling the relevant R API functions.

**Slots**

**ans:** Object of class "character": The returned XML-RPC of NEOS as character string.  
**method:** Object of class "character": The name of the called API function.  
**call:** Object of class "call": The call to the generating function of the object.  
**nc:** Object of class "NeosComm": The NeosComm object that has been used in the request to NEOS.

**Methods**

**show signature(object = "NeosAns"):** Returns the converted slot ans from an object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for Rcurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosComm](#)

**Examples**

```
showClass("NeosAns")
```

---

NeosComm-class

*Class "NeosComm"*

---

**Description**

The purpose of this class is to gather the relevant information needed for HTTP requests that is passed to NEOS.

**Objects from the Class**

Objects can be created by calls of the form `new("NeosComm", ...)` or more conveniently by creating an object from `CreateNeosComm()`.

**Slots**

**url:** Object of class "character": The URL to NEOS, *i.e.*, <http://www.neos-server.org>  
**curlopts:** Object of class "list": A named list of valid Curl options.  
**curlhandle:** Object of class "CURLHandle": Objects of this class can be created and altered with `getCurlHandle()`

**Methods**

No methods defined with class "NeosComm" in the signature.

**Author(s)**

Bernhard Pfaff

**References**

Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>, and  
libcurl web site: <http://curl.haxx.se>

**See Also**

[CreateNeosComm](#), [getCurlHandle](#) and [CURLHandle-class](#)

**Examples**

```
showClass("NeosComm")
## Not run:

nc <- CreateNeosComm()
nc

## End(Not run)
```

---

NeosJob-class

*Class "NeosJob"*


---

**Description**

Objects of this class contain among other slots the returned jobnumber and password for jobs submitted to NEOS. Objects of this class can then be used for retrieving the optimization results.

**Objects from the Class**

Objects can be created by calls of the form `new("NeosJob", ...)` or more conveniently by calling the relevant R API function `NsubmitJob`.

**Slots**

**jobnumber:** Object of class "numeric": The returned job number.  
**password:** Object of class "character": The returned pass word.  
**method:** Object of class "character": The name of the called API function.  
**call:** Object of class "call": The call to the generating function of the object.  
**nc:** Object of class "NeosComm": The NeosComm object that has been used in the request to NEOS.

## Methods

**show** signature(object = "NeosJob"): Displays the slots jobnumber and password from an object of class NeosJob.

## Author(s)

Bernhard Pfaff

## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

## Examples

```
showClass("NeosJob")
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
NsubmitJob(xmlstring = xmls, user = "rneos", interface = "", id = 0)

## End(Not run)
```

---

NeosOff-class

*Class "NeosOff"*

---

## Description

Objects of this class contain among other slots the partial result and the offset.

## Objects from the Class

Objects can be created by calls of the form `new("NeosOff", ...)`.



**Slots**

ans: Object of class "character": The partial result returned from NEOS.  
 offset: Object of class "integer": The integer offset until the results have been returned.  
 jobnumber: Object of class "numeric": The returned job number.  
 password: Object of class "character": The returned pass word.  
 method: Object of class "character": The name of the called API function.  
 call: Object of class "call": The call to the generating function of the object.  
 nc: Object of class "NeosComm": The NeosComm object that has been used in the request to NEOS.

**Methods**

**update** Updates an object of class NeosOff.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://neos.mcs.anl.gov/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**Examples**

```
showClass("NeosOff")
```

---

 NeosXml-class

---

*Class "NeosXml"*


---

**Description**

Objects of this class contain the returned results from NEOS as well as information on which kind of query has been sent and how it was sent.

**Objects from the Class**

Objects can be created by calls of the form `new("NeosXml", ...)` or more conveniently by calling the relevant R API functions.

**Slots**

xml: Object of class "XMLNode": The returned and converted XML-template of NEOS.  
 method: Object of class "character": The name of the called API function.  
 call: Object of class "call": The call to the generating function of the object.  
 nc: Object of class "NeosComm": The NeosComm object that has been used in the request to NEOS.

## Methods

**show** signature(object = "NeosXml"): Returns the converted slot xml from an object of class NeosXml.

## Author(s)

Bernhard Pfaff

## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

## See Also

[NeosComm](#)

## Examples

```
showClass("NeosXml")
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
id = 0)
NgetJobStatus(obj = test, convert = TRUE)
NgetJobInfo(obj = test, convert = TRUE)
NgetFinalResults(obj = test, convert = TRUE)

## End(Not run)
```

---

NgetFinalResults	<i>XML-RPC method getFinalResults of Neos</i>
------------------	-----------------------------------------------

---

## Description

This functions calls the XML-RPC method “getFinalResults()” of NEOS, which gets results of a job submitted to NEOS. If the job is still running, then this function will hang until the job is finished.

## Usage

```
NgetFinalResults(obj, convert = TRUE)
```

## Arguments

obj	NeosJob, an object of class NeosJob as returned by the function NsubmitJob.
convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned (base-64 encoded).

## Value

An object of class NeosAns.

## Author(s)

Bernhard Pfaff

## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

## See Also

[NeosAns](#) and [NsubmitJob](#)

## Examples

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
```

```

datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
id = 0)
NgetFinalResults(obj = test, convert = TRUE)

## End(Not run)

```

---

NgetFinalResultsNonBlocking

*XML-RPC method getFinalResultsNonBlocking of Neos*

---

## Description

This functions calls the XML-RPC method “getFinalResultsNonBlocking()” of NEOS, which gets results of a job submitted to NEOS. If the job is still running, then this function will return an empty string (base-64 encoded).

## Usage

```
NgetFinalResultsNonBlocking(obj, convert = TRUE)
```

## Arguments

obj	NeosJob, an object of class NeosJob as returned by the function NsubmitJob.
convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned (base-64 encoded).

## Value

An object of class NeosAns.

## Author(s)

Bernhard Pfaff

## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [NsubmitJob](#)

**Examples**

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
  inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
  comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
  id = 0)
NgetFinalResultsNonBlocking(obj = test, convert = TRUE)

## End(Not run)
```

---

NgetIntermediateResults

*XML-RPC method getIntermediateResults of Neos*

---

**Description**

This functions calls the XML-RPC method “getIntermediateResults()” of NEOS, which returns intermediate results of a job submitted to NEOS, starting at the character offset up to the last received data. Intermediate results are usually the standard output of the solver daemon. If the job is still running, then this function will hang until another packet of output is sent to NEOS or the job is finished. This function will return a tuple of thebase-64 encoded object and the new offset (object, newoffset). The offset refers to uncoded characters.

**Usage**

```
NgetIntermediateResults(obj, offset = NULL, convert = TRUE)
```

**Arguments**

obj	NeosJob, an object of class NeosJob as returned by the function NsubmitJob.
offset	Integer, the offset from which on the results are returned. In a first run this is set to integer(0).

convert            Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned (base-64 encoded).

### Value

An object of class NeosOff.

### Author(s)

Bernhard Pfaff

### References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for R Curl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

### See Also

[NeosOff](#) and [NsubmitJob](#)

### Examples

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
id = 0)
NgetIntermediateResults(obj = test, convert = TRUE)

## End(Not run)
```

---

`NgetIntermediateResultsNonBlocking`*XML-RPC method getIntermediateResultsNonBlocking of Neos*

---

## Description

This functions calls the XML-RPC method “getIntermediateResultsNonBlocking()” of NEOS, which returns intermediate results of a job submitted to NEOS, starting at the character offset up to the last received data. Intermediate results are usually the standard output of the solver daemon. If the job is still running, then this function will hang until another packet of output is sent to NEOS or the job is finished. This function will return a tuple of thebase-64 encoded object and the new offset (object, newoffset). The offset refers to uncoded characters.

## Usage

```
NgetIntermediateResultsNonBlocking(obj, offset = NULL,  
                                   convert = TRUE)
```

## Arguments

<code>obj</code>	NeosJob, an object of class NeosJob as returned by the function <code>NsubmitJob</code> .
<code>offset</code>	Integer, the offset from which on the results are returned. In a first run this is set to <code>integer(0)</code> .
<code>convert</code>	Logical, if <code>convert = TRUE</code> (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned (base-64 encoded).

## Value

An object of class `NeosOff`.

## Author(s)

Bernhard Pfaff

## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

## See Also

[NeosOff](#) and [NsubmitJob](#)

## Examples

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
id = 0)
NgetIntermediateResultsNonBlocking(obj = test, convert = TRUE)

## End(Not run)
```

---

NgetJobInfo

XML-RPC method getJobInfo of Neos

---

## Description

This functions calls the XML-RPC method “getJobInfo()” of NEOS and returns a four-tuple (category, solver name, input, status).

## Usage

```
NgetJobInfo(obj, convert = TRUE)
```

## Arguments

obj	Object of class NeosJob, as returned by the function NsubmitJob.
convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.

## Value

An object of class NeosAns.

## Author(s)

Bernhard Pfaff



## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

## See Also

[NeosAns](#), [NeosJob](#) and [NgetJobStatus](#)

## Examples

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
  inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
  comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdatalist = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
  id = 0)
NgetJobInfo(obj = test, convert = TRUE)

## End(Not run)
```

---

NgetJobStatus

*XML-RPC method getJobStatus of Neos*

---

## Description

This functions calls the XML-RPC method “getJobStatus()” of NEOS and returns an object of class NeosAns. The functions returns the current job status (either “Done”, “Running”, “Waiting”, “Unknown Job” or “Bad Password”).

## Usage

```
NgetJobStatus(obj, convert = TRUE)
```

**Arguments**

obj	NeosJob, an object of class NeosJob as returned by the function NsubmitJob.
convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [NsubmitJob](#)

**Examples**

```
## Not run:

tmp <- NgetSolverTemplate(category = "go", solvername = "ASA",
  inputMethod = "AMPL")
## setting path to example model and data file
modf <- system.file("ExAMPL", "diet.mod", package = "rneos")
datf <- system.file("ExAMPL", "diet.dat", package = "rneos")
## import of file contents
modc <- paste(paste(readLines(modf), collapse = "\n"), "\n")
datc <- paste(paste(readLines(datf), collapse = "\n"), "\n")
## create list object
argslist <- list(model = modc, data = datc, commands = "",
  comments = "")
## create XML string
xmls <- CreateXmlString(neosxml = template, cdataList = argslist)
test <- NsubmitJob(xmlstring = xmls, user = "rneos", interface = "",
  id = 0)
NgetJobStatus(obj = test, convert = TRUE)

## End(Not run)
```

---

NgetSolverTemplate	<i>XML-RPC method getSolverTemplate of Neos</i>
--------------------	-------------------------------------------------

---

**Description**

This functions calls the XML-RPC method “getSolverTemplate()” of NEOS. If the solver category:solvername:inputMethod exists on NEOS, then an XML template is returned as an object of class NeosXml.

**Usage**

```
NgetSolverTemplate(category, solvername, inputMethod,  
                  nc = CreateNeosComm())
```

**Arguments**

category	Character, the abbreviation of a category
solvername	Character, the name of the solver to be used.
inputMethod	Character, the name of the solver for which the xml-template shall be returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosXml.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosXml](#), [NlistAllSolvers](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:  
  
NgetSolverTemplate(category = "go", solvername = "ASA", inputMethod = "AMPL")  
  
## End(Not run)
```

Nhelp

*XML-RPC method help of Neos*

---

**Description**

This functions calls the XML-RPC method “help()” of NEOS and returns an object of class NeosAns.

**Usage**

```
Nhelp(convert = TRUE, nc = CreateNeosComm())
```

**Arguments**

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:  
  
Nhelp()  
  
## End(Not run)
```

---

NkillJob	<i>XML-RPC method killJob of Neos</i>
----------	---------------------------------------

---

### Description

This method is used to cancel a job submission running on NEOS (or waiting to run on NEOS). The job password is required to prevent abuse of this function (extracted from relevant slot of obj). This functions calls the XML-RPC method “killJob()” of NEOS and returns an object of class NeosAns.

### Usage

```
NkillJob(obj, killmsg = NULL, convert = TRUE)
```

### Arguments

obj	Object of class NeosJob, as returned by the function NsubmitJob.
killmsg	Character, optional description.
convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.

### Value

An object of class NeosAns containing the returned message from NEOS.

### Author(s)

Bernhard Pfaff

### References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

### See Also

[NeosAns](#) and [NeosJob](#)

---

NlistAllSolvers	<i>XML-RPC method listAllSolvers of Neos</i>
-----------------	----------------------------------------------

---

### Description

This functions calls the XML-RPC method “listAllSolvers()” of NEOS and returns an object of class NeosAns; a list of category:solver:inputMethod.

### Usage

```
NlistAllSolvers(convert = TRUE, nc = CreateNeosComm())
```

### Arguments

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

### Value

An object of class NeosAns.

### Author(s)

Bernhard Pfaff

### References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

### See Also

[NeosAns](#) and [CreateNeosComm](#)

### Examples

```
## Not run:  
  
NlistAllSolvers()  
  
## End(Not run)
```

---

NlistCategories	<i>XML-RPC method listCategories of Neos</i>
-----------------	----------------------------------------------

---

### Description

This functions calls the XML-RPC method “listCategories()” of NEOS and returns an object of class NeosAns; a dictionary with entries (‘abbreviated name’:‘full name’,...).

### Usage

```
NlistCategories(convert = TRUE, nc = CreateNeosComm())
```

### Arguments

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

### Value

An object of class NeosAns.

### Author(s)

Bernhard Pfaff

### References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

### See Also

[NeosAns](#) and [CreateNeosComm](#)

### Examples

```
## Not run:  
  
NlistCategories()  
  
## End(Not run)
```

---

`NlistSolversInCategory`*XML-RPC method listSolversInCategory of Neos*

---

## Description

This functions calls the XML-RPC method “listSolversInCategory()” of NEOS and returns an object of class NeosAns. The returned content is a list of solver:input for every solver in the category (category can be abbreviation or full\\_name).

## Usage

```
NlistSolversInCategory(category, convert = TRUE,  
                      nc = CreateNeosComm())
```

## Arguments

category	Character, the abbreviation of a category
convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

## Value

An object of class NeosAns.

## Author(s)

Bernhard Pfaff

## References

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

## See Also

[NeosAns](#), [NlistCategories](#) and [CreateNeosComm](#)



**Examples**

```
## Not run:  
  
NlistSolversInCategory(category = "go")  
  
## End(Not run)
```

---

Nping	<i>XML-RPC method ping of Neos</i>
-------	------------------------------------

---

**Description**

This functions calls the XML-RPC method “ping()” of NEOS and returns an object of class NeosAns. It is verified that this NeosServer is running and a message ‘NeosServer is alive’ is returned.

**Usage**

```
Nping(convert = TRUE, nc = CreateNeosComm())
```

**Arguments**

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#), [NlistCategories](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:

Nping()

## End(Not run)
```

---

NprintQueue

*XML-RPC method printQueue of Neos*


---

**Description**

This functions calls the XML-RPC method “printQueue()” of NEOS and returns an object of class NeosAns, which is a string containing the current NEOS jobs.

**Usage**

```
NprintQueue(convert = TRUE, nc = CreateNeosComm())
```

**Arguments**

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for Rcurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:

NprintQueue()

## End(Not run)
```

---

NsubmitJob

*XML-RPC method submitJob of Neos*


---

**Description**

This functions calls the XML-RPC method “submitJob()” of NEOS and returns an object of class NeosJob.

**Usage**

```
NsubmitJob(xmlstring, user = "rneos", interface = "",
           id = 0, nc = CreateNeosComm())
```

**Arguments**

xmlstring	Character, the xml string according to the solver’s template and filled with the user’s optimisation data.
user	Character, the name of the user
interface	Character, the name of the interface.
id	Integer, an identifier for the submitted job.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosJob.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
 Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
 Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosJob](#), [CreateXmlString](#) and [NgetSolverTemplate](#)

Nversion

*XML-RPC method version of Neos*

---

**Description**

This functions calls the XML-RPC method “version()” of NEOS and returns an object of class NeosAns, which is a string containing the version number of the NEOS server.

**Usage**

```
Nversion(convert = TRUE, nc = CreateNeosComm())
```

**Arguments**

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:  
  
Nversion()  
  
## End(Not run)
```

---

**Nwelcome***XML-RPC method welcome of Neos*

---

**Description**

This functions calls the XML-RPC method “welcome()” of NEOS and returns an object of class NeosAns, which is a welcome message (string).

**Usage**

```
Nwelcome(convert = TRUE, nc = CreateNeosComm())
```

**Arguments**

convert	Logical, if convert = TRUE (the default) the value of the returned XML-RPC result is extracted and returned as character, otherwise the XML-RPC string is returned.
nc	Object of class NeosComm: By default, this argument is set by calling CreateNeosComm() and thereby using the default values of this function.

**Value**

An object of class NeosAns.

**Author(s)**

Bernhard Pfaff

**References**

NEOS API: <http://www.neos-server.org/neos/NEOS-API.html>,  
Omegahat web site for RCurl: <http://www.omegahat.org/RCurl>,  
Omegahat web site for XMLRPC: <http://www.omegahat.org/XMLRPC>

**See Also**

[NeosAns](#) and [CreateNeosComm](#)

**Examples**

```
## Not run:  
  
Nwelcome()  
  
## End(Not run)
```

# Index

## \*Topic **IO**

CreateNeosComm, [2](#)  
CreateXmlString, [3](#)  
NemailHelp, [4](#)  
NeosAns-class, [5](#)  
NeosComm-class, [6](#)  
NeosJob-class, [7](#)  
NeosOff-class, [8](#)  
NeosXml-class, [9](#)  
NgetFinalResults, [11](#)  
NgetFinalResultsNonBlocking, [12](#)  
NgetIntermediateResults, [13](#)  
NgetIntermediateResultsNonBlocking, [15](#)  
NgetJobInfo, [16](#)  
NgetJobStatus, [17](#)  
NgetSolverTemplate, [19](#)  
Nhelp, [20](#)  
NkillJob, [21](#)  
NlistAllSolvers, [22](#)  
NlistCategories, [23](#)  
NlistSolversInCategory, [24](#)  
Nping, [25](#)  
NprintQueue, [26](#)  
NsubmitJob, [27](#)  
Nversion, [28](#)  
Nwelcome, [29](#)

## \*Topic **classes**

NeosAns-class, [5](#)  
NeosComm-class, [6](#)  
NeosJob-class, [7](#)  
NeosOff-class, [8](#)  
NeosXml-class, [9](#)

CreateNeosComm, [2](#), [5](#), [7](#), [19](#), [20](#), [22–26](#), [28](#), [29](#)  
CreateXmlString, [3](#), [27](#)

getCurlHandle, [7](#)

NemailHelp, [4](#)

NeosAns, [5](#), [11](#), [13](#), [17](#), [18](#), [20–26](#), [28](#), [29](#)  
NeosAns-class, [5](#)  
NeosComm, [3](#), [6](#), [10](#)  
NeosComm-class, [6](#)  
NeosJob, [17](#), [21](#), [27](#)  
NeosJob-class, [7](#)  
NeosOff, [14](#), [15](#)  
NeosOff-class, [8](#)  
NeosXml, [4](#), [19](#)  
NeosXml-class, [9](#)  
NgetFinalResults, [11](#)  
NgetFinalResultsNonBlocking, [12](#)  
NgetIntermediateResults, [13](#)  
NgetIntermediateResultsNonBlocking, [15](#)  
NgetJobInfo, [16](#)  
NgetJobStatus, [17](#), [17](#)  
NgetSolverTemplate, [4](#), [19](#), [27](#)  
Nhelp, [20](#)  
NkillJob, [21](#)  
NlistAllSolvers, [19](#), [22](#)  
NlistCategories, [23](#), [24](#), [25](#)  
NlistSolversInCategory, [24](#)  
Nping, [25](#)  
NprintQueue, [26](#)  
NsubmitJob, [11](#), [13–15](#), [18](#), [27](#)  
Nversion, [28](#)  
Nwelcome, [29](#)

show, NeosAns-method (NeosAns-class), [5](#)  
show, NeosJob-method (NeosJob-class), [7](#)  
show, NeosOff-method (NeosOff-class), [8](#)  
show, NeosXml-method (NeosXml-class), [9](#)

update, NeosOff-method (NeosOff-class), [8](#)