

Slomins DF511 Door Video Lock — Control4 Driver

Overview

Complete Control4 driver for Slomins DF511 Door Video Lock with full CldBus API integration, MQTT event streaming, RTSP video streaming, lock control, doorbell functionality, face recognition, and two-way audio support.

Model: DF511

Version: 9

Minimum Control4 OS: 3.3.2+

Device Type: Door Video Lock with Camera

Last Updated: August 18, 2026

Features

Automatic Camera Discovery

- Auto-populate IP Address and VID

Streaming Support

- H.264 (AVC)
- H.265 (HEVC)
- MJPEG
- Snapshot

PTZ Support

- No PTZ capabilities (fixed camera)

Lock Control

- Remote lock and unlock via CldBus API
- Full Control4 Lock Proxy integration
- Automatic lock status synchronization
- Auto-relock with configurable timer
- Lock/Unlock event triggers for Control4 automation

Doorbell Functionality

- Doorbell ring detection and notifications
- Visitor notification with snapshot attachment

Battery Management

- Battery level monitoring (0-100%)
- Low battery alerts

Two-Way Audio

- Microphone control (Mute/Unmute)
- Speaker volume control (1-10)

Motion Detection

- Adjustable sensitivity (1-10)
- Motion event notifications
- Face detection
- Stranger detection

Advanced Unlock Methods

- Password unlock
- Offline password unlock
- Duress password unlock
- Face recognition unlock
- NFC card unlock
- Mobile app unlock
- One-click unlock

- **Physical key unlock**
-

Available Actions

- **Take Snapshot** — Capture a still image from the camera
 - **Initialize Camera** — Initialize camera connection and authentication
 - **Mute Mic** — Mute the camera microphone
 - **Unmute Mic** — Unmute the camera microphone
 - **Turn up speaker volume** — Increase speaker volume by 1 level
 - **Turn down speaker volume** — Decrease speaker volume by 1 level
 - **Sensitivity =** — Set motion detection sensitivity (1-10)
 - **Show device information** — Display device information
 - **Lock** — Lock the door
 - **Unlock** — Unlock the door
-

Control4 Programming Events and Conditionals

Events

The driver triggers the following Control4 events:

- **Motion Detected** — When camera detects motion
- **Face Detected** — When camera detects a face
- **Stranger Detected** — When camera detects a stranger
- **Low Battery** — When battery level is low
- **Camera Online** — When camera comes online
- **Camera Offline** — When camera goes offline
- **Camera Restarted** — When camera reboots
- **Doorbell Ring** — When doorbell button is pressed
- **Unlock with Password** — When unlocked using a password
- **Offline Password Unlock** — When unlocked using an offline password
- **Duress Unlock** — When unlocked using a duress password

- **Face Recognition Unlock** — When unlocked using face recognition
- **NFC Unlock** — When unlocked using an NFC card
- **App Unlock** — When unlocked from the mobile app
- **One-Click Unlock** — When unlocked using one-click unlock
- **Key Unlock** — When unlocked using a physical key
- **One-Touch Lock** — When locked using one-touch lock
- **Lock Event** — When locked
- **Remote Lock** — When locked remotely
- **Locking Started** — When lock operation starts
- **Locked Outside** — When someone is locked outside
- **System Is Locked** — When system is locked

Conditionals

Use these conditionals in Control4 programming:

- **If Locked** — True/False
- **If Unlocked** — True/False
- **If in fault** — True/False
- **If sensing motion** — True/False
- **If not sensing motion** — True/False
- **If Mic is muted** — True/False
- **If Mic is unmuted** — True/False
- **If Speaker volume is** — 1 through 10
- **If battery level is** — 0 through 100
- **If Sensitivity is** — 1 through 10
- **If Stranger Detected** — True/False

Requirements

- **Control4 Composer Pro**
- **Control4 OS 3.3.2+**
- **Network access** to API endpoint and camera

- Camera accessible on LAN
-

Installation

1. Install Driver Package

1. Open **Control4 Composer Pro**
 2. Go to **Drivers** → **Add Driver** → **Install From File**
 3. Select `Slomins-doorvideolock-DF511.c4z`
 4. Click **Install**
 5. Driver will appear in the available drivers list
-

2. Add Device to Project

1. Open **Project View**
 2. Select a room
 3. Click **Add Device**
 4. Search for **Slomins DF511 Door Video Lock**
 5. Add to the room
-

3. Configure Properties

API Configuration

- **Base API URL:** `https://api.arpha-tech.com`
- **Account:** Your email or phone number

Camera Configuration

- **IP Address:** Camera IP (example `192.168.1.100`)
 - **HTTP Port:** 80
 - **RTSP Port:** 554
 - **Username:** Camera username
 - **Password:** Camera password
-

4. Enable Lock Tile in Control4 UI

To make the **DF511 Lock tile visible** in the Control4 interface:

1. Open **Composer Pro**
2. Navigate to the room where the device was added
3. Select the **Security** tab
4. Locate **DF511 Lock**
5. Enable **Show in Navigator**
6. Click **OK**

The lock control tile will now appear in the Control4 mobile app and touchscreens.

Quick Start Guide

Complete Setup Flow

1. Execute "Initialize"
 - Gets RSA public key from API
 - Stores in "Public Key" property
2. Execute "Login/Register"
 - Encrypts credentials with RSA-OAEP
 - Authenticates with API
 - Stores Auth Token
3. Execute "Test Main Stream"
 - Generates RTSP URL for streaming
4. Execute "Get Snapshot URL"

→ Generates HTTP snapshot URL

5. Test Lock Control

- Lock/Unlock using Control4 Navigator
- Driver sends commands to API
- Lock status updates automatically

▮ Dynamic IP Auto-Update (Online Event Handling)

The driver includes intelligent handling of camera connectivity to ensure the correct IP address is always used.

▮ How It Works

Whenever the camera comes online, the driver automatically:

- Detects the **Camera Online** event
- Calls the **Get Devices API**
- Matches the device using **VID (Virtual ID)**
- Retrieves the latest **local IP address**
- Updates the **IP Address** property in the driver
- Pushes the updated address to the **Control4 Camera Proxy**

▮ Real-Time Event Detection

The driver supports **MQTT-based real-time event streaming over SSL (port 8884)** and provides notifications for the following events:

- Doorbell ring notifications with snapshot
- Motion detection with snapshot attachment
- Human detection
- Stranger detection
- Camera online/offline status monitoring

MQTT Configuration

Default Behavior

MQTT is **enabled automatically by the driver after authentication**.

The driver will automatically:

- 1. Enable MQTT
- 2. Fetch MQTT credentials
- 3. Connect to the MQTT broker
- 4. Subscribe to camera event topics

You normally **do not need to enable MQTT manually**.

CldBus App Motion Detection Settings

To receive **Motion Detection** and **Human Detection** events, detection must be enabled in the **CldBus mobile app**.

Steps

- 1. Open the **CldBus App**
- 2. Select your **camera device**
- 3. Tap **Settings**
- 4. Navigate to:

Settings → Motion Detection

- 5. Under **Detection Type**, select one of the following:

Detection Type	Description
All Detections	All movement events will trigger notifications. This includes general motion detection.
Human Detection	Only human movement will trigger events. Non-human motion will be ignored.

Push Notification Configuration

1. Create Push Notification

- 1. Open **Composer Pro**
- 2. Navigate to:

Agents → Push Notification

- 3. Click **Add Notification** then enter a name for the notification.

Configure the following:

Setting	Value
Category	Cameras
Severity	Info / Critical
Subject	Camera Event

Click **Save**.

2. Enable Snapshot Attachment

Edit the created notification and set:

Attachment Type = Snapshot URL

This allows push notifications to include the **camera snapshot image**.

Mapping Push Notifications in Programming

- 1. In **Composer Pro**, open **Programming**.
- 2. Select the **Camera Driver** from the device list.
- 3. In the **Events** section, choose the event you want to trigger the notification (for example **Motion Detected**).

On the **right-side panel**:

- 4. Click **Push Notifications**.

- From the dropdown list, select the **notification you created earlier**.
- Drag and drop the notification into the programming area **or double-click the green arrow** to add it.

This maps the camera event to the push notification.

Example:

```
WHEN Motion Detected THEN Send Push Notification
```

Notification Flow

```
Camera Event (MQTT)
    ↓
Driver Receives Event
    ↓
Driver Processes Event
    ↓
Control4 Event Triggered
    ↓
Push Notification Agent
    ↓
Mobile Notification Sent
    ↓
Snapshot Image Attached
```

Available Actions

Accessible via **Device** → **Actions**

Authentication

- Initialize
- Login/Register
- Get Devices

Streaming

- Test Main Stream

- Test Sub Stream
- Get Snapshot URL

Lock Controls

- Lock
- Unlock

Properties

Input Properties

Property	Type	Default	Description
Base API URL	STRING	https://api.arpha-tech.com	API endpoint
Account	STRING	-	User email/phone
IP Address	STRING	192.168.1.100	Camera IP
HTTP Port	INTEGER	3333	HTTP port
RTSP Port	INTEGER	554	RTSP port
Username	STRING	-	Camera username
Password	STRING	-	Camera password
Snapshot Path	STRING	/wps-cgi/image.cgi	Snapshot path
Enable MQTT	LIST	True	Enable/disable MQTT event streaming

Output Properties

Property	Description
Status	Current driver status

Property	Description
Public Key	RSA public key
Client ID	Generated client ID
Auth Token	Authentication token
Main Stream URL	High quality RTSP URL
Sub Stream URL	Low quality RTSP URL
Lock State	Locked / Unlocked
Online	Camera online status

API Functions

1. Initialize Camera

Command: INITIALIZE_CAMERA

Endpoint: POST /api/v3/openapi/init

Purpose: Retrieve RSA public key for encryption

What it does:

- Generates client ID and request ID
- Creates HMAC-SHA256 signature
- Requests public key from API
- Stores key in "Public Key" property

Expected Output:

```
Camera initialization succeeded
Received public key: MIGfMA...
Public key stored successfully
```

2. Login/Register

Command: LOGIN_OR_REGISTER

Endpoint: POST /api/v3/openapi/auth/login-or-register

Purpose: Authenticate user with encrypted credentials

Prerequisites:

- Must run Initialize first (needs public key)
- Account must be set in properties

What it does:

- Encrypts credentials with RSA-OAEP + SHA256
- Sends authentication request
- Stores auth token and user ID
- Token used for subsequent API calls

Encryption Process:

1. Create crypto object: C4:Crypto("RSA")
2. Import public key
3. Encrypt JSON: {"country_code":"US", "account":"user@email.com"}
4. Generate HMAC-SHA256 signature
5. Send to API

Expected Output:

```
Using C4:Crypto for RSA-OAEP encryption...
Crypto object created successfully
Public key imported successfully
Encrypting data with RSA-OAEP + SHA256...
Encryption successful!
Login/Register succeeded
Auth token stored
User ID: 12345
```

3. Test Main Stream

Command: TEST_MAIN_STREAM

Purpose: Generate high quality RTSP stream URL

Format: `rtsp://<ip>:554/streamtype=1`

Prerequisites:

- IP Address set in properties
- RTSP Port (default: 554)

Example Output:

```
Main Stream RTSP URL: rtsp://192.168.1.100:554/streamtype=1
```

Result:

- URL stored in "Main Stream URL" property
 - Use URL in VMS or video player
-

4. Test Sub Stream

Command: `TEST_SUB_STREAM`

Purpose: Generate low quality RTSP stream URL

Format: `rtsp://<ip>:554/streamtype=0`

Prerequisites:

- IP Address set in properties
- RTSP Port (default: 554)

Example Output:

```
Sub Stream RTSP URL: rtsp://192.168.1.100:554/streamtype=0
```

Result:

- URL stored in "Sub Stream URL" property
 - Use URL in VMS or video player
-

5. Get Snapshot URL

Command: GET_SNAPSHOT_URL

Purpose: Generate HTTP snapshot URL

Format: http://<ip>:<port>/wps-cgi/image.cgi?resolution=640x480

Prerequisites:

- IP Address set in properties
- Optional: Username/Password for authentication

Example Output:

Snapshot URL: http://192.168.1.100:3333/wps-cgi/image.cgi?resolution=640x480

6. Lock Status & Control

Purpose: Control and monitor the door lock integrated in the DF511 device.

API Endpoint Example

GET /v1.0/devices/{deviceId}/status

What it does:

- Retrieves the device status from the cloud API
- Extracts the lock_motor_state value
- Updates Control4 lock proxy
- Synchronizes lock state with Control4 UI

Driver Behavior

When the driver receives lock status from the API:

API Value	Control4 State
true	Locked
false	Unlocked

The driver then updates the Control4 lock proxy:

```
C4:SendToProxy(5002, "LOCK_STATUS_CHANGED", { LOCK_STATUS = "locked" })
```

or

```
C4:SendToProxy(5002, "LOCK_STATUS_CHANGED", { LOCK_STATUS = "unlocked" })
```

This ensures the **Navigator lock icon updates correctly**.

Automation Events

The driver fires Control4 events when state changes:

- Lock
- Unlock
- Lock Error
- Unlock Error

Logging & Troubleshooting

View Logs

1. Open **Composer Pro**
2. Go to **Lua Output**
3. Execute driver actions
4. Review request and response logs

Common Issues

No public key available

- Run Initialize first
- Check API URL

Login failed

- Verify Account property
- Ensure Initialize ran successfully

IP Address not set

- Verify camera is reachable on LAN

No auth token available

- Run Login/Register first

MQTT not receiving events

- Verify **Enable MQTT = True**
- Confirm authentication completed
- Ensure motion detection enabled in CldBus app
- Verify outbound port **8884** is allowed

API Response Codes

- **200 / 20000** - Success
- **401** - Unauthorized (invalid token)
- **400** - Bad request (invalid parameters)
- **500** - Server error

Building the Driver

File Structure

```
Slomins-doorvideolock-DF511/  
├─ driver.lua  
├─ driver.xml  
├─ mqtt_manager.lua  
├─ README.md  
├─ CldBusApi/  
│   └─ auth.lua  
│   └─ dkjson.lua  
│   └─ http.lua  
│   └─ sha256.lua
```

```
| └─ transport_c4.lua
|   └─ util.lua
└─ build-c4z.ps1
```

Build Package

Run:

```
.\build-c4z.ps1
```

This generates:

```
Slomins-doorvideolock-DF511.c4z
```

Development Notes

Helper Libraries (CldBusApi/)

- **auth.lua** - Authentication utilities
- **dkjson.lua** - JSON encoding/decoding
- **http.lua** - HTTP request helpers
- **sha256.lua** - HMAC-SHA256 implementation
- **transport_c4.lua** - Control4 transport adapter
- **util.lua** - UUID generation, HMAC functions

Signature Generation

All API requests include HMAC-SHA256 signatures:

```
-- Message format
local message = "client_id=<uuid>&request_id=<uuid>&time=<timestamp>&version=0.0.1"

-- Generate signature
local signature = util.hmac_sha256_hex(message, app_secret)
```

```
-- App secret
local app_secret = "hg4IwDpf2tvbVdBGc6nwP5x2XGCi1Nv8"
```

UUID Generation

```
local client_id = util.uuid_v4()
-- Example: "0ffb133a-b03d-4cfd-82a9-d45220516199"
```

Version History

v9 (Current)

- Updated live stream url. Now uses /live instead of /streamtype.

v8

- Fixed the streaming path using streamtype 1.
- Added Face management feature.

v7

- Added device and firmware info.
- Added snapshot feature on preview ui.

v6

- Bug fixes and improvements

v5.0

- Auto-populate IP Address, VID and MAC Address

v4.0

- Implemented timestamp display support for recording logs and events
- Adjusted default volume to 4

- Implemented lock preview option

v3.0

- Implemented functionality to store all incoming events in the database.

v2.0

- Fixed version display showing 0 in Control4 Manage Drivers interface
- Fixed device specific conditionals labels not showing in Control4 Composer

v1.0.0

- Complete API integration
- RSA-OAEP encryption
- Authentication and token management
- Device listing
- RTSP streaming
- Snapshot support
- Lock proxy integration
- MQTT real-time event detection
- Push notification support

v1.0.1

- HTML Readme File
- Dynamic credentials retrieval

v1.0.2

- Manually Locking and locking trigger events/Scenes in Control4

v1.0.3

- Implemented real-time state synchronization for lock/unlock status to ensure the UI reflects changes instantly without requiring a refresh.

v1.0.4

- Bug Fixes : device hang when API is unreachable, MQTT connection stability improvements

v1.0.5

- Dynamic Cldbus API Id and App Secret retrieval from API when MAC address is provided

v1.0.6

- Added conditionals in composer pro for mapping lock and unlock events to push notifications, ensuring that notifications are only sent when the corresponding event occurs.
- Disabled ptz on the command panel of the composer pro as the camera does not support ptz, preventing confusion and improving usability for users configuring the driver in their Control4 system.

v1.0.7

- Improved device wake-up reliability by implementing a retry mechanism for API calls when the camera is offline.
- Bug Fixes: Reinitializes the device when account property changes to ensure the driver is fetching the latest authentication token.

v1.0.8

- Bug Fixes: Low Battery, Battery Warning, and Battery Critical events are now properly detected and logged in Lua Output.
- Bug Fixes: Lock and Unlock controls now working in Android and iOS Control4 apps.
- Bug Fixes: Offline password unlock, Motion Detection events are now properly triggering push notifications.

v1.0.9

- Fixed an issue with low battery notifications where MQTT was not re-enabled after VID changes.
- Minor bug fixes and improvements.

v1.0.10

- Updated Control4 Camera Programming Options
- **Device Events:** Added "System Is Locked"
- **Commands Removed:** Pan Left, Pan Right, Pan Scan, Tilt Up, Tilt Down, Tilt Scan, Zoom In, Zoom Out, Preset, Home
- **Commands Added:** Take Snapshot, Initialize Camera *, Unmute Mic, Mute Mic, Turn up speaker volume, Turn down speaker volume, Sensitivity =
- **DF511 Door Lock Commands Removed:** Toggle Door Lock

- **Conditions Added:** If Speaker volume is 1-10, If battery is <, > or =, If sensing motion, If not sensing motion, If Mic is muted, If Mic is unmuted, Sensitivity =

v1.0.11

- Updates- Added device variable to display **FaceName** in face detection notifications.
- How to Display Face Name in Push Notifications

1. Open **Control4 Composer Pro**
2. Navigate to **Agents** → **Notifications**
3. Select or create a notification for the **Face Detected** event
4. In the notification message body, click **Add Variable**
5. In the variable picker tree, expand your **DF511 Door Lock** device
6. Expand **Device Variables**
7. Select **FaceName** from the list
8. Click **OK**

- Fixes- Resolved issue where the **lock UI was taking time to load** in the updated Control4 app.

Support

Driver Version: 9

Manufacturer: Slomins

Model: DF511-SL

Control4 OS: 3.3.2+

For issues check **Lua Output logs** in Composer Pro.

License

