

-Call Center-

API Documentation Guide

INTRODUCTION

The API package enables common tasks of the call center to be performed programmatically by issuing an API request. The tasks may be such as: creating an agent, editing an agent, deleting a queue, originating a call between an agent and a supplied phone number etc.

In general, this API expects the request parameters to be sent in the POST method and can output the response in xml or json according to your choice. The response includes the following:

- The request parameters received
- Result status (whether the request succeeded or not)
- Optional additional information

THE APIS REQUESTS

1 Create Agent 9
2 Edit Agent 15
3 Delete Agent 21
4 Assign Agent 25
5 Release Agent 30
6 Login Agent 34
7 Logoff Agent 39
8 Set State of an Agent 44
9 Get Agent State 49
10 Get Agent Answered Calls 58
11 Send Message to an Agent 62
12 Screen Capture on an Agent 67
13 Create Queue 72
14 Edit Queue 77
15 Delete Queue 82
16 Queue Get Agents 88

17 Queue Members Update 93
18 Get Waiting time of queue 102
19 Get Incomings Calls 107
20 Get Outgoings Calls 114
21 Originate Call 120
22 Queue Dial 126
23 Get Call CDR 131
24 Start New Call Recording 138
25 Mute (stop) Call Recording 142
26 Unmute (start) Call Recording 146
27 Add Dialer Entry 150
28 Delete Dialer Entry By ID 156
29 Delete Dialer Entry By Number 161
30 Delete Dialer Entry by Customer ID 166
31 Get Dialer Entry Id 172
32 Edit Dialer Entry 177
33 Send CDR 183

OUTBOUND API SERVICE

Given a listener script in the client side, the outbound API can supply a service that reports call details of each incoming or outgoing call. The reporting can be done via the http get or http post in the format of : xml, json or key-value.

GENERAL RESPONSE STRUCTURE

The following applies for all the requests that may be sent to the API.

The response is structured as described here:

Response:

Response can be either in xml or in json.

XML and JSON

The following elements are returned:

Value	Description	Type
Data	Root element	data element

Data element:

Value	Description	Type
request	Contains the information about the request sent.	request element
status	The result status whether it succeeded or not.	status element
info	Contains response information	info element

Request element:

Value	Description	Type
request_id	An id the API system supplies the request. This string helps Identify the request within the log file.	String(1369813640.8711)
type	The type of the request	String (agent_create)
All possible input parameters	The same parameters sent	As described in the request Parameters table.

Status element:

Value	Description	Type
field_name	The field name the error is referring to. This field may be absent in case of an operational error.	String
Code	A numeric id of the result	Integer
description	A text description of the result.	String

Info element:

This element will hold any further information that the request is intended to return.

It will show up only upon requests that are meant to return information further than success/failure, and only on the successful among them.

Its structure is not fixed; it varies according to the request purpose.

For deeper understanding, look into the response examples given in the specific requests documentation.

Errors

General Errors:

When the URL sent for the request is wrong.

Status Code	Status Description	Status Field Name
300	Uri is wrong, no object as {object name sent}	NONE
301	Uri is wrong, no action as {action sent} for object {object name sent}	NONE

Syntactic Errors:

Syntactic errors occur when the parameters supplied in the request are missing or invalid.

The code range of these errors will start from 100.

Status Code	Status Description	Status Field Name
101	Missing parameter	Any one of the required fields of the request.
102	Invalid parameter, only digits are allowed.	Any of the numeric input fields.
103	Invalid parameter, use only alphabet characters, hyphens or spaces.	Any of the name input fields like name.
104	Invalid parameter: use only allowed values (%s)	For example, format should have only one of the values 'xml' or 'json' any other would be considered as wrong.
105	API key is wrong	api_key
106	Invalid parameter: value exceeds maximum limit (%s)	For example, wrapuptime > 60

107	Invalid parameter: value exceeds minimum limit (%s)	
108	Invalid unique id: The format should be two digital strings joined by a dot	
109	Wrong format of numeric list	
110	Invalid parameter: use only alphabet characters, punctuation characters, digits, hyphens or spaces	
111	Invalid parameter: use only alphabet characters, hyphens, spaces or digits	
112	Wrong format of pipes list	
113	Wrong date format, the date should be formatted like YYYY-MM-DD HH:MM:SS	
114	The date supplied is not a future date	
115	The input format is invalid, it does not follow the syntax indicated in the API guide	
116	The input string exceeds maximum length allowed.	

Operational Errors:

Operational errors occur when some resources used by the system fail or the action cannot be completed because the action completion will lead to an error. For example, trying to create an existing agent will trigger an operational error.

The code range of these errors will start from 200.

Status Code	Status Description	Status Field Name
200	O. K	NONE
201	System error, agent was not {xxx} (MySQL failure, asterisk failure	NONE

	) , Where xxx can be any of: created, edited, deleted, Assigned, released.	
202	Agent with the supplied id already exits.	Id (agent/create)
203	The department supplied does not exist	department
204	The queue supplied does not exist	Any of the fields carrying queue_id
205	The agent id supplied does not exist	Id
206	Nothing to update – no parameters to update were sent.	NONE (agent/edit, queue/edit)
207	Agent cannot be deleted while logged in	NONE (agent/delete)
208	The agent is already assigned to the queue	NONE (agent/assign)
209	The agent is not assigned to the supplied queue	NONE (agent/release)
210	License limit for agents' number has been reached	NONE (agent/create)
211	The agent must be logged in	NONE (call/originate)
212	You must send at least one of these: exten_num, agent_id, pbx_did	NONE (call/originate)
213	please send an agent OR extension OR pbx_did, and not more than 1!	NONE (call/originate)
214	The recording file was not found	NONE (call/get_recording)
215	The agent is inactive	id (agent/login)
216	The extension does not exist	ag_exten (agent/login)
217	The agent is not logged off	NONE (agent/login)
218	Extension {exten_num} is in use by {agent_id}	NONE (agent/login)
219	The agent is already logged off	NONE (agent/logoff)
220	The subtype id supplied does not exist for the department the agent belongs to.	NONE (agent/set_state)

221	For state 'online' there are no subtypes, subtype_id should not be supplied.	subtype_id (agent/set_state)
222	There are no agents available to receive the message.	NONE
223	The agent's CTI is not connected	NONE (agent/screen_capture)
224	A queue with the supplied id already exits.	id (queue/create)
225	A queue with the supplied id does not exit.	id (queue/delete,edit)
226	The queue is used by active agents	NONE (queue/delete)
227	The campaign does not exist	campaign_id (dialer_entry/add)
228	The dialer entry already exists for this campaign	number1 (dialer_entry/add)
229	The dialer entry does not exist	entry_id (dialer_entry/delete)
230	Some actions could not be completed	queue_members (queue/members_update)
231	No members update needed	queue/members_update
232	The did supplied does not exist	Call/originate
233	Xit	Call/originate
234	Please supply only one or zero parameters	Agent/get_state
235	When the since_method supplied is “given_timestamp”, you must supply the parameter since_timestamp as well	Agent/get_answered_calls
236	Please supply either id or queue_id, not both.	Agent/get_answered_calls
237	The dialer entry contains duplicates among number1, number2, number3	NONE

1 CREATE AGENT

Http Method:

POST

Url:

http://callcenter/api/agent/create

Request Parameters:

Parameter	Description	Required	Values
Id	The agent id to be used	required	Only digits are allowed. Example: 2016.
Name	The agent name to be used	required	Only letters,hyphens and spaces are allowed. Example: mira-israel
password	The password to be used by the agent	required	Only digits allowed. For example: 124456
out_q	The outgoing queue the agent will be associated to.	optional	Only digits are allowed. For example 2001. The queue must be an existing queue.
wrapuptime	The wrapup time the agent is allowed to	optional	Time in seconds like: 30 Should not exceed

			60 seconds
department	The agent's department.	optional	The department id, only digits allowed. Should be an existing department like: 12
mon1_queue	A monitored queue. For mon1_queue the CTI displays how many waiting calls are there.	optional	Only digits are allowed.
mon2_queue	A monitored queue. For mon2_queue the CTI displays how many waiting calls are there.	optional	Only digits are allowed.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_create</type>
                  <id>2012</id>
                  <name></name>
                 <password>1234</password>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>name</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_create</type>
                  <id>2012</id>
                  <name>bisly</name>
                 <password>1234</password>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                     "type":"agent_create",
                                     "id":"2012",
                                     "name":"",
                                     "password":"1234"
                  },
                  "status":  {
                                     "code":"101",
                                     "description": "Missing Parameter",
                                     "field_name":"name"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request": {
                                 "request_id": "1369813640.8711",
                                 "type":"agent_create",
                                 "id":"2012",
                                 "name":"bisly",
                                 "password":"1234"
                  } ,
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
          }
}
```

2 EDIT AGENT

Http Method:

POST, GET

Url:

http://callcenter/api/agent/edit

Request Parameters:

Parameter	Description	Required	Values
Id	The agent id to be used	required	Only digits are allowed. Example: 2016.
** Name	The agent name to be used	optional	Only letters,hyphens and spaces are allowed. Example: mira-israel
** password	The password to be used by the agent	optional	Only digits allowed. For example: 124456
** out_q	The outgoing queue the agent will be associated to.	optional	Only digits are allowed. For example 2001. The queue must be an existing queue.
** wrapuptime	The wrapup time the agent is allowed to	optional	Time in seconds like: 30, Should not exceed

			60 seconds
** department	The agent's department.	optional	The department id, only digits allowed. Should be an exiting department like: 12
** mon1_queue	A monitored queue. For mon1_queue the CTI displays how many waiting calls are there.	optional	Only digits are allowed.
** mon2_queue	A monitored queue. For mon2_queue the CTI displays how many waiting calls are there.	optional	Only digits are allowed.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the api. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

** name, password, out_q, wrapuptime, department, mon1_queue and mon2_queue is all optional, but at least one of them should be supplied, because obviously some information should be updated.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_edit </type>
                  <password>1234</password>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_edit</type>
                  <id>2012</id>
                  <name>bisly</name>
                 <password>1234</password>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"agent_edit",
                                    "password":"1234"
                  },
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"agent_id",
                                 "id":"2012",
                                 "name":"bisly",
                                 "password":"1234"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
          }
}
```

3 DELETE AGENT

Http Method:

POST, GET

Url:

http://callcenter/api/agent/delete/

Request Parameters:

Parameter	Description	Required	Values
id	The agent id to be used	required	Only digits are allowed. Example: 2016.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_delete </type>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_delete</type>
                  <id>2012</id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:

```
{
   "data": {
                "request":   {
                        "request_id": "1369813640.8711",
                            "type":"agent_delete"
                } ,
```

```
                "status": {
                                "code":"101",
                                "description": "Missing Parameter",
                                "field_name":"id"
                        }
        }
}
```


Successful Response:


```
{
   "data": {
                "request":  {
                                "request_id": "1369813640.8711",
                                "type":"agent_delete",
                                "id":"2012",
                },
                "status":  {
                                "code":"200",
                                "description": "O.K",
                                "field_name":"NONE"
                        }
        }
}
```

4 ASSIGN AGENT

Http Method:

POST

Url:

http://callcenter/api/agent/assign/

Request Parameters:

Parameter	Description	Required	Values
id	The agent id to be used	required	Only digits are allowed. Example: 2016.
queue_id	The queue to assign the agent to.	required	Only digits are allowed. Example: 3000
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_assign </type>
                 <queue_id>3000</queue_id>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_assign</type>
                  <id>2012</id>
                <queue_id>3000</queue_id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"agent_assign",
                                 "queue_id":"3000"
                  },
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"agent_assign",
                                 "id":"2012",
                               "queue_id":"3000"
                  },
                  "status": {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
          }
}
```

5 RELEASE AGENT

Http Method:

POST

Url:

http://callcenter/api/agent/release/

Request Parameters:

Parameter	Description	Required	Values
id	The agent id to release	required	Only digits are allowed. Example: 2016.
queue_id	The queue to release the agent from.	required	Only digits are allowed. Example: 3000
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_release </type>
                 <queue_id>3000</queue_id>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                 <request_id>1369813640.8711</request_id>
```

```
                <type>agent_assign</type>
                <id>2012</id>
               <queue_id>3000</queue_id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
              <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:

```
{
   "data": {
                "request":   {
                        "request_id": "1369813640.8711",
                            "type":"agent_release ",
                        "queue_id":"3000"
                } ,
                "status":  {
                            "code":"101",
                            "description": "Missing Parameter",
```

```
                    "field_name":"id"
                }
        }
}
```


Successful Response:


```
{
   "data": {
            "request":  {
                    "request_id": "1369813640.8711",
                    "type":"agent_release",
                    "id":"2012",
                "queue_id":"3000"
            },
            "status":  {
                    "code":"200",
                    "description": "O.K",
                    "field_name":"NONE"
                }
        }
}
```

6 LOGIN AGENT

Http Method:

POST

Url:

http://callcenter/api/agent/login/

Request Parameters:

Parameter	Description	Required	Values
id	The agent to login	required	Only digits are allowed. Example: 2016.
ag_exten	The extension of the agent to login with	required	Only digits are allowed. Example: 2000
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_login></type>
                 < id>2016</ id>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>ag_exten</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
```



```
                <request_id>1369813640.8711</request_id>
                  <type>agent_login </type>
                  <id>2016</id>
                <ag_exten >3000</ag_exten >
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
              <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"agent_login ",
                                 "id":"2016"
                  },
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"ag_exten"
                           }
         }
}
```


Successful Response:


```
{
   "data": {
                  "request":  {
                                    "request_id": "1369813640.8711",
```

```
                    "type":"agent_login",
                    "id":"2016",
                "ag_exten":"2000"
            },
            "status": {
                    "code":"200",
                    "description": "O.K",
                    "field_name":"NONE"
                }
        }
}
```

7 LOGOFF AGENT

Http Method:

POST

Url:

http://callcenter/api/agent/logoff/

Request Parameters:

Parameter	Description	Required	Values
id	The agent to logoff	required	Only digits are allowed. Example: 2016.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_logoff ></type>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
```

```
                <request_id>1369813640.8711</request_id>
                  <type>agent_logoff</type>
                  <id>2016</id>
          </request>
          <status>
                  <code>200</code>
                  <description>O.K</code>
                <field_name>NONE</field_name>
          </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"agent_logoff ",
                                 "id":"2016"
                  } ,
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                "request":  {
                                "request_id": "1369813640.8711",
                                "type":"agent_logoff",
                                "id":"2016"
                },
                "status":  {
                                "code":"200",
                                "description": "O.K",
                                "field_name":"NONE"
                        }
        }
}
```

8 SET STATE OF AN AGENT

Http Method:

POST

Url:

http://callcenter/api/agent/set_state/

Request Parameters:

Parameter	Description	Required	Values
id	The agent whom state is going to be set.	required	Only digits are allowed. Example: 2016.
state	The new state of the agent.	required	One of the following values: mission, pause,online
subtype_id	The pause type or the mission type	optional	Only digits are allowed. The subtype id should be one of the existing subtypes in the agent's department.
format	The desired format of the response	required	json or xml

api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Subtype ids can be obtained from the call center GUI, inside the department manager section under the .Pause and Mission subtypes tab

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_set_state ></type>
                 <state>mission</state>
        </request>
         <status>
```

```
                <code>101</code>
                <description>Missing Parameter </code>
              <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_set_state</type>
                  <id>2016</id>
                <state>mission</state>
                <subytype_id>3 </subtype_id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
              <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"agent_set_state ",
                                 "state":"mission"
                  } ,
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                    "request_id": "1369813640.8711",
                                    "type":"agent_set_state",
                                    "id":"2016",
                                "state":"mission",
                                "subtype_id":"3"
                  },
                  "status":  {
                                    "code":"200",
                                    "description": "O.K",
                                    "field_name":"NONE"
                              }
         }
}
```

9 GET AGENT STATE

Purpose:

This request will return the agent state (online, offline, mission, pause, FORCEPAUSEALL) , the duration the agent is in this state and if relevant, the subtype id and subtype name (for pause and mission).

If the agent id is supplied, the information returned will hold data relevant for this agent alone.

If the queue id is supplied, the information returned will hold data for all the queue assigned agents.

If no parameters (agent id, queue id) are supplied, the information returned will hold data

for all online agents.

Http Method:

POST

Url:

http://callcenter/api/agent/get_state/

Request Parameters:

Parameter	Description	Required	Values
id	The agent whom state is going to be read.	optional **	Only digits are allowed. Example: 2016.
queue_id	The queue for which the associated agents' state will be read.	optional **	One of the following values: mission, pause,online

format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

** The request should be sent with either agent_id or queue_id and not both.

It is possible to send the request with no parameters, then the whole list of online

agents will be returned.

Response

The duration returned is a string of 6 segments in the format of yy:mm:dd:hh:ii:ss .

For example, 02:02:21:06:47:38 means two years, 2 months, 21 days, 6 hours, 47 minutes and 38 seconds.

Online state – When the agent's state is "online" he may be talking or idle. This is why the response also contain an element: sub_state , to indicate "active" for talking or "idle".

FORCEPAUSE state - for backward compatibility, when state="FORCEPAUSEALL", we add a sub_state element which value is forcepause.

See examples below.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                 < id>2016</agent_ id>
        </request>
        <status>
                <code>205</code>
                <description> The agent id supplied does not exist </code>
               <field_name> id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  < id>2016</agent_id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
        <info>
            <agents>
                <agent>
                        <id>2016</id>
                        <state>mission</status>
                      <subtype_id>26</subtype_id>
                        <subtype_name>paperwork</subtype>
                        <duration>00:00:00:00:35:20</duration>
                </agent>
            </agents>
      </info>
```

</data>

Json example:

Failed Response:


```
{
   "data": {
                  "request":   {
                                 "request_id": "1369813640.8711",
                                    " id": "2016"
                  } ,
                  "status":  {
                                    "code":"205",
                                    "description": " The agent id supplied does not exist ",
                                    "field_name":" id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 " id":"2016"
                  } ,
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                         } ,
                  "info": {
                                 "agents":[
                                 {"id":"2000","state":"offline","subtype_id":0,"subtype_name":"none"},
                                 {"id":"2009","state":"offline","subtype_id":0,"subtype_name":"none"},
                                 {"id":"2016","state":"mission","subtype_id":"0","subtype_name":"gene
                         ral"}
                                 ]
                  }
          }
}
```

Example of Successful response for FORCEPAUSE

```
<data>
  <request>
    <request_id>1487753493.8397</request_id>
    <type>agent_get_state</type>
    <id>2016</id>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
  <info>
    <agents>
      <agent>
        <id>2016</id>
        <state>FORCEPAUSEALL</state>
        <sub_state>forcepause</sub_state>
        <subtype_id>0</subtype_id>
        <subtype_name>none</subtype_name>
        <duration>00:00:00:00:01:30</duration>
      </agent>
    </agents>
  </info>
</data>
```

Notice the <state> element contains “FORCEPAUSEALL” for backward compatibility and the element <sub_state> contains “forcepause” .

Example of Successful response for idle agent:

```
<data>
  <request>
    <request_id>1487753708.5451</request_id>
    <type>agent_get_state</type>
    <id>2016</id>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
  <info>
    <agents>
      <agent>
        <id>2016</id>
        <state>online</state>
        <sub_state>idle</sub_state>
        <subtype_id>0</subtype_id>
        <subtype_name>none</subtype_name>
        <duration>00:00:11</duration>
      </agent>
    </agents>
  </info>
</data>
```

Notice the element <state> contains the term “online” to indicate the general status of agent is logged, while the <sub_state> element is “idle” .

Example of Successful response for a talking agent:

```
<data>
  <request>
    <request_id>1487753992.2865</request_id>
    <type>agent_get_state</type>
    <id>2016</id>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
  <info>
    <agents>
      <agent>
        <id>2016</id>
        <state>online</state>
        <sub_state>active</sub_state>
        <subtype_id>0</subtype_id>
        <subtype_name>none</subtype_name>
        <duration>00:01:04</duration>
      </agent>
    </agents>
  </info>
</data>
```

Notice the element <state> contains the term “online” to indicate the general status of agent is logged, while the <sub_state> element is “active”.

10 GET AGENT ANSWERED CALLS

Purpose:

This request will return the amount of answered calls.

If the agent id is supplied, the information returned will hold data relevant for this agent alone.

If the queue id is supplied, the information returned will hold data for all the queue assigned agents.

If no parameters (agent id, queue id) are supplied, the information returned will hold data

for all online agents.

Http Method:

POST

Url:

http://callcenter/api/agent/get_answered_calls/

Parameter	Description	Required	Values
id	The agent whose	optional **	Only digits are allowed. Example: 2016.
queue_id	The queue for which the associated agents' state will be read.	optional **	Only digits are allowed. Example: 3000.
since_method	since method can be one of the following: last_login , given_timestamp,	Required	one of the following: last_login , given_timestamp,

	midnight		midnight
since_timestamp	A parameter given as a timestamp , indicating the calls were answered since this value onwards .	Optional – If the since_method is “given_timestamp” It is required. If the since_method is last_login, it can be sent (but not a must). If the method is midnight , it should not be sent.	For example: 1417690388
filter_inactive	Filter inactive agents – yes or no.	Optional , Default value is “no”	yes,no
format	The desired format of the response	Required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

** The request should be sent with either agent_id or queue_id and not both.

It is possible to send the request with no parameters, then the whole list of online

agents will be returned.

since_method:

last_login – The count of answered calls would apply on calls performed since the agent last login. This method can be combined with the parameter since_timestamp, to further limit results (the counted answered calls are later to the agent last login time, and later to the since_timestamp).

given_timestamp –

If this method is chosen, the parameter since_timestamp is required.

The count of answered calls would apply on calls performed since the value supplied in "since_timestamp".

Example of Successful response for single agent:

```
<data>
  <request>
    <request_id>1487753708.5451</request_id>
    <type>agent_get_answered_calls</type>
     <since_method>last_login</since_method>

    <id>2016</id>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
  <info>
    <agents>
```

```
        <agent>
          <id>2016</id>
          <answered_incoming_calls>50</answered_incoming_calls>
          <answered_outgoing_calls>20</answered_outgoing_calls>
          <answered_total_calls>70</answered_total_calls>
        </agent>
      </agents>
    </info>
</data>
```

Example of failed response for a single agent:

```
<data>
  <request>
    <request_id>1488097871.7712</request_id>
    <type>agent_get_answered_calls</type>
    <id>2099</id>
    <since_timestamp>1417690388</since_timestamp>
    <filter_inactive>yes</filter_inactive>
    <format>xml</format>
  </request>
  <status>
    <code>101</code>
    <description>Missing parameter</description>
    <field_name>since_method</field_name>
  </status>
</data>
```

11 Send Message to an Agent

Http Method:

POST

Url:

http://callcenter/api/agent/send_msg/

Request Parameters:

Parameter	Description	Required	Values
ag_list	A comma separated list of agent ids to send the message to.	required	A comma separated list of numbers. Can be a single agent id too.
msg	The message to be sent.	required	Only characters, digits and spaces are allowed.
from	From whom the message is sent	required	Only characters, digits and spaces are allowed.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Successful Response

Since it is possible to pass a few agents to send the message to, some may fail to receive it as they are offline. The successful response may contain an info element stating which agents failed to receive the message along with the reason. See json and xml examples for clarification.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_send_msg ></type>
                 <msg>Hello</msg>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>ag_list</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_send_msg </type>
                  <ag_list>2016,7000</ag_list >
                <from >Admin</from >
                <msg >Do your homework now</msg >
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
              <field_name>NONE</field_name>
        </status>
       <info>
            <agent_7000>The agent id supplied does not exist</agent_7000>
        </info>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                     "type":"agent_send_msg ",
                                 "msg":"Hello"
                  } ,
                  "status":  {
                                     "code":"101",
                                     "description": "Missing Parameter",
                                     "field_name":"ag_list"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"agent_send_msg ",
                                 "ag_list":"2016",
                               "msg":"Go do your homework now",
                               "from":"Admin"
                  } ,
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
          }
}
```

12 Screen Capture on an Agent

Http Method:

POST

Url:

http://callcenter/api/agent/screen_capture/

Request Parameters:

Parameter	Description	Required	Values
id	The agent id whose screen is going to be captured.	required	Only digits are allowed. Example: 2016.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_screen_capture ></type>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>agent_screen_capture </type>
                  <id>2016</id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
        <info>
           <file_url>http://dana/cc3/screen_captures/upload/myScreen2016.jpg </file_url>
        </info>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"agent_screen_capture "
                  },
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"agent_screen_capture",
                                 "id":"2016"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                        },
                        "info": {
"file_url":"http://dana/cc3/screen_captures/upload/myScreen2016.jpg"
                        }
         }
}
```

13 CREATE QUEUE

Http Method:

POST

Url:

http://callcenter/api/queue/create/

Request Parameters:

Parameter	Description	Required	Values
id	The queue id	required	Only digits are allowed. Example: 2016.
name	The queue name	required	Only letters,hyphens and spaces are allowed. Example: support
out_clid	Outbound caller id	optional	Only digits are allowed. For example: 732209191
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer.	required	The predefined value agreed upon.

	This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.		

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue _create</type>
                  <id>3000</id>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>name</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue _create</type>
                  <id>3000</id>
                  <name>support </name>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request": {
                                 "request_id": "1369813640.8711",
                                    "type":"queue _create",
                                    "id":"3000"
                  } ,
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"name"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"queue_create",
                                 "id":"300",
                                 "name":"support"
                              },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                              }
          }
}
```

14 EDIT QUEUE

Http Method:

POST

Url:

http://callcenter/api/queue/edit/

Request Parameters:

Parameter	Description	Required	Values
id	The queue id	required	Only digits are allowed. Example: 2016.
name	The queue name	optional	Only letters,hyphens and spaces are allowed. Example: support
out_clid	Outbound caller id	optional	Only digits are allowed. For example: 732209191
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

.At least one of the fields: name or out_clid must be supplied, otherwise there is nothing to update **

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue _edit</type>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue _edit</type>
                  <id>3000</id>
                  <name>support </name>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request": {
                                 "request_id": "1369813640.8711",
                                    "type":"queue _edit"
                  } ,
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request": {
                                 "request_id": "1369813640.8711",
                                 "type":"queue_edit",
                                 "id":"300",
                                 "name":"support"
                              },
                  "status": {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
         }
}
```

15 DELETE QUEUE

Http Method:

POST

Url:

http://callcenter/api/queue/delete/

Request Parameters:

Parameter	Description	Required	Values
id	The queue id	required	Only digits are allowed. Example: 2016.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

A queue that is used by active agents will not be deleted.

Before deleting a queue, please make sure no agents are members of this queue, no agents are using the queue as their outgoing queue and no agents are monitoring this queue .

Upon trying to delete a queue that is still in use, an error status code is returned a long with information regarding how and by whom it is used .

Please see the failed response examples for clarification.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue _delete</type>
                <id>3000</id>
        </request>
        <status>
                <code>225</code>
                <description>The queue is used by active agents</description>
               <field_name>NONE</field_name>
        </status>
       <info>
            <out_queue>
                <agents_list>2016,2026,2032</agents_list>
             </out_queue>
            <mon1_queue>
                <agents_list>2020,2030</agents_list>
             </mon1_queue>
             <mon2_queue>
```



```
                <agents_list>2040,2050</agents_list>
            </mon2_queue>
            <members>
                <agents_list>2016,2020,2040</agents_list>
            </members>
        </info>

</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                <type>queue _delete </type>
                <id>3000</id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
            <field_name>NONE</field_name>
        </status>
data/>
```

Json example:

Failed Response:


```
{
        "request":
        {
                "request_id":"1372337334.5207",
                "type":"queue_delete",
                "format":"json",
                "id":"3000"
        },
        "status":
        {
                "code":"226",
                "description":"The queue is used by active agents",
                "field_name":"NONE"
        },
        "info":
        {
        "members":
                {
                        "agents_list":"4000,2021,2009,2625,2529,2530,2000,2024,2023,2025,2030,2018,2525,2008,2029,2003,2016"
                },
        "out_queue":
```

```
        {
                "agents_list":"2000,2001,2002,2003,2004,2009,2018,2023,2024,2025,2030,2509,2525,2529,2530,2625,4000"
        },
        "mon1_queue":
        {
                "agents_list":"2000,2002,2017,2018,2023,2029,2030,2525,2530"
        },
      "mon2_queue":
        {
                "agents_list":"2018"
        }
   }
}
```

Successful Response:


```
{
   "data": {
                  "request": {
                                 "request_id": "1369813640.8711",
                                 "type":"queue_delete",
                                 "id":"3000"
                              },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }

         }
}
```

16 QUEUE GET AGENTS

Http Method:

POST

Url:

http://callcenter/api/queue/get_agents/

Request Parameters:

Parameter	Description	Required	Values
id	The queue id	required	Only digits are allowed. Example: 2016.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>get_agents</type>
                 <id>4000</id>
        </request>
        <status>
                <code>225</code>
                <description> The queue supplied does not exist </description>
               <field_name>id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                 <request_id>1369813640.8711</request_id>
```

```
                <type>get_agents </type>
                <id>3000</id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
              <field_name>NONE</field_name>
        </status>
       <info>
            <assigned_agents>2016,2017,2018</assigned_agents>
      </info>
</data>
```

Json example:

Failed Response:


```
{
        "request":
        {
                "request_id":"1372337334.5207",
                "type":"get_agents",
                "format":"json",
                "id":"4000"
        },
        "status":
        {
                "code":"225",
                "description":"The queue supplied does not exist ",
                "field_name":"id"
        }
}
```


Successful Response:


```
{
   "data": {
                "request": {
                                "request_id": "1369813640.8711",
```

```
                    "type":"queue_delete",
                    "id":"3000"
                },
            "status": {
                    "code":"200",
                    "description": "O.K",
                    "field_name":"NONE"
                },
            "info": {
                    "assigned_agents": "2016,2017,2018"
                }

        }
}
```

17 QUEUE MEMBERS UPDATE

Http Method:

POST

Url:

http://callcenter/api/queue/members_update /

Request Parameters:

Parameter	Description	Required	Values
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.
queue_members_xml	An xml string that indicates for each queue, which agents should be assigned	required	Only digits allowed for the queue ids and agents ids .

	and which agents should be released. See more detailed description below.		

Example of the queue_members input parameter

```
<queues>
    <queue id="3000">
        <assign>1001, 1002, 1003</assign>
        <release>1005,1006,1007</ release >
    </queue>
    <queue id="3001">
        <assign>2001, 2002,,2009</assign>
        <release>2005,2006,2007</ release >
    </queue>
</queues>
```

Output Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue_members_update</type>
                <queue_members_xml>
                        <![CDATA[
                        <queues>
                                        <queue id=”3000”>
                                                <assign>1001, 1002, 1003</assign>
                                                <release>1005,1006,1007</ release >
                                        </queue>
                                        <queue id=”3001”>
                                                <assign>2001, 2002,2009</assign>
                                                <release>2005,2006,2007</ release >
                                        </queue>
                        </queues>
                        ]]>
                </queue_members_xml>
```



```
        </request>
        <status>
                <code>230</code>
                <description> Request failed</description>
               <field_name>queue_members</field_name>
        </status>
       <info>
                <queue id="3000" >
                        <agent id="1001" >Agent does not exist</agent>
                </queue>
      </info>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>queue_members_update</type>
                  <queue_members_xml>
                        <![CDATA[
                                <queues>
                                        <queue id=”3000”>
                                                <assign>1001, 1002, 1003</assign>
                                                <release>1005,1006,1007</ release >
                                        </queue>
                                        <queue id=”3001”>
                                                <assign>2001, 2002,2009</assign>
                                                <release>2005,2006,2007</ release >
                                        </queue>
                                </queues>
                        ]]>
                 </queue_members_xml>
        </request>
        <status>
                <code>200</code>
```

```
                <description>O.K</code>
                <field_name>NONE</field_name>
            </status>
</data>
```

Json example:

Failed Response:


```
{
        "request":
        {
                "request_id":"1372337334.5207",
                "type":"queue_members_update",
                "format":"json",
                "queue_members":{
                                                "queues": [
                                                { "id":"3000", "assign":"1001, 1002, 1003",
                                                  "release":"1005,1006,1007"},
                                                { "id":"3001", "assign":"2001, 2002,2009",
                                                  "release":"2005,2006,2007"}
                                                ]
                                        }
        },
        "status":
        {
                "code":"230",
                "description":" Request failed ",
                "field_name":"queue_members"
```

```
        },
        "info":
        {
                {
                        "queue":{
                        "attributes":{"id":"3000"},
                        "agent":{"attributes":{"id":"1001"},"content":"Agent does not exist"}
                         }
                }


        }
}
```


Successful Response:

```
{
   "data": {
                "request": {
                                "request_id": "1369813640.8711",
                                "type":"queue_members_update",
                                "format":"json",
                "queue_members":{
                                        "queues": [
                                                { "id":"3000", "assign":"1001, 1002, 1003",
                                                  "release":"1005,1006,1007"},
                                                { "id":"3001", "assign":"2001, 2002,2009",
                                                  "release":"2005,2006,2007"}
                                                ]
                                    }

                            },
                "status":  {
                                "code":"200",
                                "description": "O.K",
                                "field_name":"NONE"
                            }
        }
}
```

18 GET WAITING TIME OF QUEUE

Http Method:

POST

Url:

http://callcenter/api/queue/get_waiting_time/

Request Parameters:

Parameter	Description	Required	Values
id	The queue id	required	Only digits are allowed. Example: 2016.
in_seconds	If passed as yes, the waiting time will be returned in seconds. Otherwise it will be returned in the format mm:ss	Optional	yes/no
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer.	required	The predefined value agreed upon.

	This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.		

Output Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <id>555</id>
                   <type>queue_get_waiting_time </type>
                <format>xml</format>
        </request>
        <status>
                <code>225</code>
                <description>A queue with the supplied id does not exit</description>
               <field_name>id </field_name>
        </status>
```

</data>

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <id>3000</id>
                   <type>queue_get_waiting_time </type>
                <format>xml</format>
        </request>
        <status>
                <code>200</code>
                <description>O.K </description>
               <field_name>NONE</field_name>
        </status>
       <info>
                <waiting_time>01:45</waiting_time>
      </info>
</data>
```

Json example:

Failed Response:


```
{
        "request":
        {
                "request_id":"1372337334.5207",
                "type":"queue_get_waiting_time",
                "format":"json",
                "id":"4000"
        },
        "status":
        {
                "code":"225",
                "description":"The queue supplied does not exist ",
                "field_name":"id"
        }
}
```


Successful Response:


```
{
   "data": {
                "request": {
```

```
                    "request_id": "1369813640.8711",
                    "type":"queue_get_waiting_time",
                    "id":"3000",
                    "in_seconds":"yes"
                },
            "status": {
                    "code":"200",
                    "description": "O.K",
                    "field_name":"NONE"
                },
            "info": {
                    "waiting_time": "105"
                }

        }
}
```

19 GET INCOMINGS CALLS

Http Method:

POST

Url:

http://callcenter/api/call/get_incoming

Parameter	Description	Required	Values
queue_id	The queue to dial from	Optional **	Only digits are allowed. Example: 3000
call_type	Which calls: waiting or answered calls	** Optional	One of the values: waiting, answered, all default: waiting.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during	required	The predefined value agreed upon.

	installation of the API. It is a combination of internal server IP and a predefined random string.		

.queue_id is optional. If supplied, only calls associated with the supplied queue will be returned

.If queue id is omitted, all icoming calls , on all queues will be returned

.call_type is optional, if not supplied , by default it will retrieve all the calls : waiting and answered

Examples xml

Failed Response:

<?xml version="1.0" encoding="utf-8"?>

<data>

```
<request>
        <request_id>1369813640.8711</request_id>
          <type>call_get_incoming /type>
         <queue_id>4000</queue_id>
</request>
<status>
        <code>225</code>
        <description> The queue supplied does not exist </description>
       <field_name>queue_id</field_name>
</status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
          <request_id>1369813640.8711</request_id>
            <type>call_get_incoming </type>
            <queue_id>3000</queue_id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
```

```
        <field_name>NONE</field_name>
    </status>
    <info>
        <calls>
            <call>
                <order>1</order>
                <uniqueid> 1395065321.354</uniqueid>
                <queue>3000</queue>
                <start_time> 1395065322</start_time>
                <number> 732209084</number>
                <state>waiting</state>
                <agent_id>NONE</agent_id>
                <wait_time>120</wait_time>
                <duration>0</duration>
            </call>
            <call>
                <order>2</order>
                <uniqueid> 1395065322.355</uniqueid>
                <queue>4000</queue>
                <start_time> 1395065455</start_time>
                <number> 732109085</number>
                <state>answered</state>
                <agent_id>NONE</agent_id>
```

```
                    <wait_time>154</wait_time>
                    <duration>0</duration>


                </call>
            </calls>
            </info>
</data>
```


Json example:

Failed Response:


```
{
        "request":
        {
                "request_id":"1372337334.5207",
                "type":"call_get_incoming ",
                "format":"json",
                "queue_id":"4000"
        },
        "status":
        {
                "code":"225",
                "description":"The queue supplied does not exist ",
                "field_name":"queue_id"
```

```
        }
}
```

Successful Response:


```
{
  "data": {
            "request": {
                        "request_id": "1369813640.8711",
                        "type":"call_get_incoming ",
                        "queue_id":"3000"
                      },
            "status": {
                        "code":"200",
                        "description": "O.K",
                        "field_name":"NONE"
                      },
           "info": {
                      "calls":[
                                {
                                  "order":"1",
                                  "uniqueid":"1395065321.354",
                                  "queue":"3000",
```

```
                    "start_time":"1395065322",
                    "wait_time":"120",
                    "number":"732209084" ,
                "agent_id":"NONE",
                    "duration":"0",
                    "state":"waiting"
                },
                {
                    "order":"2",
                    "uniqueid":"1395065431.354",
                    "queue":"4000",
                    "start_time":"1395065452",
                    "wait_time":"154",
                    "number":"7322091111",
                    "agent_id":"NONE",
                    "duration":"0",
                    "state":"answered"
                }
            ]
            }

        }
}
```

20 GET OUTGOINGS CALLS

Http Method:

POST

Url:

http://callcenter/api/call/get_outgoing

Parameter	Description	Required	Values
queue_id	The queue to dial from	Optional **	Only digits are allowed. Example: 3000
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

.queue_id is optional. If supplied, only calls associated with the supplied queue will be returned

.If queue id is omitted, all outgoing calls , on all queues will be returned

Examples xml

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
	<request>
		<request_id>1369813640.8711</request_id>
		  <type>call_get_outgoing</type>
		 <queue_id>4000</queue_id>
	</request>
	<status>
		<code>225</code>
		<description> The queue supplied does not exist </description>
		<field_name>queue_id</field_name>
	</status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
	<request>
		<request_id>1369813640.8711</request_id>
		  <type>call_get_outgoing </type>
```

```
            <queue_id>3000</queue_id>
    </request>
    <status>
            <code>200</code>
            <description>O.K</code>
           <field_name>NONE</field_name>
    </status>
  <info>
       <calls>
            <call>
                    <order>1</order>
                    <uniqueid> 1395065321.354</uniqueid>
                    <queue>3000</queue>
                    <start_time> 1395065322</start_time>
                    <number> 732209084</number>
                    <agent_id>2016 </agent_id>
            </call>
            <call>
                    <order>2</order>
                    <uniqueid> 1395065322.355</uniqueid>
                    <queue>4000</queue>
                    <start_time> 1395065455</start_time>
                    <number> 732109085</number>
```

```
                    <agent_id>2027 </agent_id>
                </call>
        </calls>
        </info>
</data>
```

Json example:

Failed Response:

```
{
        "request":
        {
                "request_id":"1372337334.5207",
                "type":"call_get_outgoing ",
                "format":"json",
                "queue_id":"4000"
        },
        "status":
        {
                "code":"225",
                "description":"The queue supplied does not exist ",
                "field_name":"queue_id"
        }
}
```

Successful Response:


```
{
   "data": {
                  "request": {
                                 "request_id": "1369813640.8711",
                                 "type":"call_get_outgoing ",
                                 "queue_id":"3000"
                              },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           },
               "info":  {
                           "calls":[
                                    {
                                       "order":"1",
                                       "uniqueid":"1395065321.354",
                                       "queue":"3000",
                                       "start_time":"1395065322",
                                       "number":"732209084" ,
                           "agent_id":"2016"
                                    },
```

```
                {
                    "order":"2",
                    "uniqueid":"1395065431.354",
                    "queue":"4000",
                    "start_time":"1395065452",
                    "number":"7322091111",
                    "agent_id":"2027"
                }
            ]
            }

        }
}
```

21 ORIGINATE CALL

Http Method:

POST

Url:

http://callcenter/api/call/originate

Request Parameters:

Parameter	Description	Required	Values
agent_id	The agent to receive the call	Optional **	Only digits are allowed. Example: 2016.
custom_field	The custom field identifying the agent	Optional **	Any string that is used as the agent identifier
exten_num	The extension to receive the call	Optional **	Only digits are allowed. Example: 2000
queue_id	The queue to dial from	Optional **	Only digits are allowed. Example: 3000
queue_id	The queue to dial from	Optional **	Only digits are allowed. Example: 3000
queue_id	The queue to dial from	Optional **	Only digits are allowed. Example: 3000
misc_app	The misc application to receive the call	Optional **	Only digits are allowed . Example: 9876
dest_num	Destination number	Required	Only digits are allowed.
caller_id	The caller ID which will be shown to the customer.	Optional	Any alphanumeric string is allowed.
timeout_dst	How long in seconds to dial the number.	Optional	Only digits are allowed. Should not exceed 60 seconds.

			Example: 30000 (for 30 seconds).
timeout_src	How long in seconds to dial the exten/agent.	Optional	Only digits are allowed. Should not exceed 60 seconds. Example: 30000 (for 30 seconds).
custom1	A custom variable	Optional	Alpha numeric characters, comma, equal sign. Like: name=John,id=1234
custom2	A custom variable	Optional	Alpha numeric characters, comma, equal sign. Like: name=John,id=1234
script	A script to run after the originate is performed. Should be a local php script given with an absolute path.	Optional	For example Script=/www/load_route/plugins/callbacks/rimon_update_callback.php|123.456
format	The desired format of the response	Required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	Required	The predefined value agreed upon.

** One of the parameters: agent_id,custom_field, exten,queue_id, misc_app must be sent as part of the request.

In addition, only one of them should be sent, sending more than one would yield an

error.

** The script parameter :

If such a parameter is supplied, the script is run after the originate is performed.

The parameter should be in the following syntax:

script_name|param1|param2|param3

where script name includes the absolute path.

For example:

/www/load_route/plugins/callbacks /rimon_update_callback.php|123.456

The script must be a local php script and must be given with an absolute path.

Successful Response

On a successful request, the response will return the unique id of the call on the PBX (for pulling the recording file).

This information will be held under : data->info->call_id elements.

See xml, json examples for clarification.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
```

<request_id>1369813640.8711</request_id>

<type>call_originate</type>

<agent _id>2016</agent _id>

</request>

<status>

<code>101</code>

<description>Missing Parameter </code>

<field_name>dest_num</field_name>

</status>

</data>

Successful Response:

<?xml version="1.0" encoding="utf-8"?>

<data>

<request>

<request_id>1369813640.8711</request_id>

<type>call_originate</type>

<agent_id>2016</agent_id>

<dest_num>050345111</dest_num >

<custom1>03337543</custom1>

</request>

<status>

<code>200</code>

```
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
        <info>
           <call_id>1331136500.1484</call_id>
        </info>
</data>
```


Json example:

Failed Response:


```
{
   "data": {
                "request":  {
                        "request_id": "1369813640.8711",
                            "type":"call_originate",
                        "agent_id":"2016"
                } ,
                "status":  {
                            "code":"101",
                            "description": "Missing Parameter",
                            "field_name":"dest_num"
                        }
          }
```

}

Successful Response:


```
{
   "data": {
                  "request":  {
                                    "request_id": "1369813640.8711",
                                    "type":"call_originate",
                                    "agent_id":"2016",
                                "dest_num":"050456111",
                                    "custom1":"03337543"
                  },
                  "status":  {
                                    "code":"200",
                                    "description": "O.K",
                                    "field_name":"NONE"
                            },
                "info": {
                                  "call_id":"1331136500.1484"
                        }
          }
}
```

22 QUEUE DIAL

Http Method:

POST

Url:

http://callcenter/api/call/queue_dial

Request Parameters:

Parameter	Description	Required	Values
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.
queue_id	The queue which will accept the call	required	Only digits are allowed. Example: 3000

dest_num	Destination number	required	Only digits are allowed.
custom1	A custom variable , may contain any additional data, for example: customer id .	optional	Alpha numeric characters, comma, equal sign. Like: name=John,id=1234

Output Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>call_queue_dial </type>
                 <queue _id>3000</queue _id>
                  <custom1>SAB123456</custom1 >
        </request>
        <status>
                <code>101</code>
```

<description>Missing Parameter </code>

<field_name>dest_num</field_name>

</status>

</data>

Successful Response:

<?xml version="1.0" encoding="utf-8"?>

<data>

<request>

<request_id>1369813640.8711</request_id>

<type>call_queue_dial </type>

<queue _id>3000</queue _id>

<dest_num>050345111</dest_num >

<custom1> SAB123456</customer1>

</request>

<status>

<code>200</code>

<description>O.K</code>

<field_name>NONE</field_name>

</status>

</data>

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                    "type":"call_queue_dial ",
                                 "queue _id":"3000",
                                    "custom1":"SAB123456"
                  } ,
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"dest_num"
                           }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"call_queue_dial ",
                                 "queue _id":"3000",
                               "dest_num":"050456111",
                                 "custom1":" SAB123456"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
          }
}
```

23 GET CALL CDR

Http Method:

POST

Url:

http://callcenter/api/call/get_cdr

Request Parameters:

Parameter	Description	Required	Values
unique_id	The unique id of the recorded call.	required	Two digital strings joined by a dot. Example: 1371114407.1070
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Successful Response

On a successful request, the response will return:

Agent id – The agent that participated in the call

Queue id - The queue the call belongs to .

Caller id – The caller id number.

Answer Time - Unix timestamp of the time the call was answered.

End Time – Unix timestamp of the time the call was hangup

Waiting Time – waiting time in seconds.

Duration - duration of the call in seconds

Direction – whether it is incoming call or outgoing call.

Recording Link – link to the recording of the call (saved for backward compatibility)

Recordings – all the relevant recordings of the call.

This information will be held under : data->info element.

See xml, json examples for clarification.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>call_get_cdr </type>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>unique_id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
```

```
<request>
        <request_id>1369813640.8711</request_id>
        <type>call_get_cdr </type>
          <unique_id>1367404914.28</unique_id>
</request>
<status>
        <code>200</code>
        <description>O.K</code>
       <field_name>NONE</field_name>
</status>
<info>
   <agent_id>2016</agent_id>
   <queue_id>3000</queue_id>
   <caller_id>050888555</caller_id>
   <answer_time>1325400427</answer_time>
     <end_time>1325400557</end_time>
   <waiting_time>59</waiting_time>
   <duration>56</duration>
     <direction>outgoing</direction>
     <recording_link>http://tikalpbx.tikal.center/cc3/execmodules/playmessage.php?path=L21u
dC9yZWMvMjAxOS0wOS0xMS8yMDE5MDkxMS0xNjUzNTEtMTU2ODIxMDAzMS4zNzYuV0FW</r
ecording_link>
     <recordings>
       <recording>http://tikalpbx.tikal.center/cc3/execmodules/playmessage.php?path=L21udC
9yZWMvMjAxOS0wOS0xMS8yMDE5MDkxMS0xNjUzNTEtMTU2ODIxMDAzMS4zNzYuV0FW</rec
```

ording>
<recording>http://tikalpbx.tikal.center/cc3/execmodules/playmessage.php?path=L21udC9yZWMvMjAxOS0wOS0xMS9xMzAwMS0wNzMyODMyMjE1LTIwMTkwOTExLTE2NTM0OS0xNTY4MjEwMDA0LjM3NC5XQVY=</recording>
</recordings>
</info>
</data>

Json example:

Failed Response:

{
"data": {
"request": {
"request_id": "1369813640.8711",
"type":"call_get_cdr ",
},
"status": {
"code":"101",
"description": "Missing Parameter",
"field_name":"unique_id"
}
}
}

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"call_get_cdr ",
                                 "unique_id":"1325404771.26",
                  } ,
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           } ,
                "info": {
                                 "agent_id":"2016",
                                 "queue_id":"3000",
                                 "caller_id":"050888555",
                                 "answer_time":"1325400427",
                                 "end_time":"1325400557",
                                 "waiting_time":"59",
                              "duration":"56",
                              "direction":"outgoing",

"recording_link": "http://tikalpbx.tikal.center/cc3/execmodules/playmessage.php?path=L21udC9yZWM
```

vMjAxOS0wOS0xMS8yMDE5MDkxMS0xNjUzNTEtMTU2ODIxMDAzMS4zNzYuV0FW",
"recordings": [
"http://tikalpbx.tikal.center/cc3/execmodules/playmessage.php?path=L21udC9yZWMvMjAxOS0wOS0xMS8yMDE5MDkxMS0xNjUzNTEtMTU2ODIxMDAzMS4zNzYuV0FW",
"http://tikalpbx.tikal.center/cc3/execmodules/playmessage.php?path=L21udC9yZWMvMjAxOS0wOS0xMS9xMzAwMS0wNzMyODMyMjE1LTIwMTkwOTExLTE2NTM0OS0xNTY4MjEwMDA0LjM3NC5XQVY="
],
}
}
}

24 START NEW CALL RECORDING

Http Method:

POST

Url:

http://callcenter/api/call/start_new_recording

Request Parameters:

Parameter	Description	Required	Values
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.
agent_id	The agent to receive the call	optional **	Only digits are allowed. Example: 2016.
custom_field	The custom field identifying the aget	** optional	Any string that is used as the agent identifier
exten_num	The extension to receive the call	optional **	Only digits are allowed. Example: 2000

** This request is intended to be used on queues that are configured to avoid recording, in case the agent

has succeeded convincing the customer to start recording.

** For now, the request supports only incoming answered queue calls.

** One of the parameters: agent_id,custom_field or exten_num must be sent as part of the request.

In addition, only one of them should be sent, sending more than one would yield an

error

** A call should already exist, when this request API is triggered. If no call exists, an error would be returned.

Output Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<data>
  <request>
    <request_id>1517737889.1210</request_id>
    <type>call_start_new_recording</type>
    <agent_id>2200</agent_id>
    <format>xml</format>
  </request>
  <status>
    <code>201</code>
    <description>No call exists</description>
    <field_name>NONE</field_name>
  </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<data>
  <request>
    <request_id>1517738164.4392</request_id>
    <type>call_start_new_recording</type>
    <agent_id>2200</agent_id>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
</data>
```

Json example:

Failed Response:


```
{
  "data": {
    "request": {
      "request_id": "1517738308.4325",
      "type": "call_start_new_recording",
      "agent_id": "11",
      "format": "json"
    },
    "status": {
      "code": "205",
      "description": "The agent id supplied does not exist",
      "field_name": "agent_id"
    }
  }
}
```


Successful Response:


```
{
  "data": {
    "request": {
      "request_id": "1517739676.5856",
      "type": "call_start_new_recording",
      "exten_num": "2000",
      "format": "json"
    },
    "status": {
      "code": "200",
      "description": "O.K",
      "field_name": "NONE"
    }
  }
}
```

25 MUTE (STOP) CALL RECORDING

Http Method:

POST

Url:

http://callcenter/api/call/stop_recording

Request Parameters:

Parameter	Description	Required	Values
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.
agent_id	The agent to receive the call	optional **	Only digits are allowed. Example: 2016.
custom_field	The custom field identifying the aget	** optional	Any string that is used as the agent identifier
exten_num	The extension to receive the call	optional **	Only digits are allowed. Example: 2000

** One of the parameters: agent_id,custom_field or exten_num must be sent as part of the request.

In addition, only one of them should be sent, sending more than one would yield an

error

** A call should already exist, when this request API is triggered. If no call exists, an error would be returned.

Output Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<data>
  <request>
    <request_id>1517745986.1844</request_id>
    <type>call_stop_recording</type>
    <agent_id>2200</agent_id>
    <custom_field>bla_custom1</custom_field>
    <format>xml</format>
  </request>
  <status>
    <code>213</code>
    <description>Please send an agent id OR extension number OR custom field, and not more than 1!<
/description>
    <field_name>NONE</field_name>
  </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<data>
  <request>
```

```
    <request_id>1517745801.4706</request_id>
    <type>call_stop_recording</type>
    <custom_field>bla_custom1</custom_field>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
</data>
```

Json example:

Failed Response:


```
{
  "data": {
    "request": {
      "request_id": "1517746211.1575",
      "type": "call_stop_recording",
      "agent_id": "11",
      "format": "json"
    },
    "status": {
      "code": "205",
      "description": "The agent id supplied does not exist",
      "field_name": "agent_id"
    }
  }
}
```


Successful Response:


```
{
  "data": {
    "request": {
      "request_id": "1517746279.5780",
      "type": "call_stop_recording",
      "agent_id": "2200",
      "format": "json"
    },
    "status": {
      "code": "200",
      "description": "O.K",
      "field_name": "NONE"
    }
  }
}
```

26 UNMUTE (START) CALL RECORDING

Http Method:

POST

Url:

http://callcenter/api/call/start_recording

Request Parameters:

Parameter	Description	Required	Values
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.
agent_id	The agent to receive the call	optional **	Only digits are allowed. Example: 2016.
custom_field	The custom field identifying the aget	** optional	Any string that is used as the agent identifier
exten_num	The extension to receive the call	optional **	Only digits are allowed. Example: 2000

** One of the parameters: agent_id, custom_field or exten_num must be sent as part of the request.

In addition, only one of them should be sent, sending more than one would yield an

error

** A call should already exist, when this request API is triggered. If no call exists, an error would be returned.

Output Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<data>
  <request>
    <request_id>1517737889.1210</request_id>
    <type>call_start_recording</type>
    <agent_id>2200</agent_id>
    <format>xml</format>
  </request>
  <status>
    <code>201</code>
    <description>No call exists</description>
    <field_name>NONE</field_name>
  </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<data>
  <request>
    <request_id>1517738164.4392</request_id>
    <type>call_start_recording</type>
    <agent_id>2200</agent_id>
    <format>xml</format>
  </request>
  <status>
    <code>200</code>
    <description>O.K</description>
    <field_name>NONE</field_name>
  </status>
</data>
```

Json example:

Failed Response:


```
{
  "data": {
    "request": {
      "request_id": "1517738308.4325",
      "type": "call_start_recording",
      "agent_id": "11",
      "format": "json"
    },
    "status": {
      "code": "205",
      "description": "The agent id supplied does not exist",
      "field_name": "agent_id"
    }
  }
}
```


Successful Response:


```
{
  "data": {
    "request": {
      "request_id": "1517739676.5856",
      "type": "call_start_recording",
      "exten_num": "2000",
      "format": "json"
    },
    "status": {
      "code": "200",
      "description": "O.K",
      "field_name": "NONE"
    }
  }
}
```

27 ADD DIALER ENTRY

Http Method:

POST

Url:

http://callcenter/api/dialer_entry/add

Request Parameters:

Parameter	Description	Required	Values
campaign_id	The campaign id	required	only digits. The campaign id should belong to an existing campaign.
name	The record name	required	letters, digits, spaces,hyphens
number1	phone number to dial	required	only digits, + sign is allowed at the beginning of the number
number2	additional phone	optional	only digits,+ sign is allowed at the beginning of the number
number3	additional phone	optional	only digits, + sign is allowed at the beginning of the number
customer_id	identifier of the customer	optional	a string up to 50 characters.
call_date	The date when the dialer will be allowed to start dialing to this entry	optional	Y-M-D H:I:S (MySQL date format)

			The date has to be a future date.
call_date_end	The date when the call won't be dialed anymore	optional	Y-M-D H:I:S (MySQL date format) The date has to be a future date.
custom_info	A string of custom key=value pairs joined by pipes	optional	key1=val1| key2=val2|key3=val3
priority	The priority for this entry – the higher the better	optional	Integer.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Comments

For number1, number2, number3:

number1 is required, it must be supplied.

+ sign is allowed, only at the beginning of the number.

Characters other than digits and + sign, will be cleared off the number.

Successful Response

On a successful request, the response will return the id of the new dialer entry.This information will be held under : data->info->entry_id element.

See xml, json examples for clarification.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>dialer_entry_add</type>
                <campaign_id>31</campaign_id>
                  <number1>073456890</number1>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>name</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                <type>dial_entry_add</type>
                  <campaign_id>31</campaign_id>
                  <number1>073456890</number1>
                  <name>Moshe Cohen</name>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
              <field_name>NONE</field_name>
        </status>
       <info>
          <entry_id>256</entry_id>
       </info>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                  "type":"dial_entry_add",
                                  "campaign_id":"31",
                                     "number1":"073456890"
                  },
                  "status":  {
                                     "code":"101",
                                     "description": "Missing Parameter",
                                     "field_name":"name"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                    "request_id": "1369813640.8711",
                                    "type":"call_get_cdr ",
                                    "campaign_id":"31",
                                    "number1":"073456890",
                                    "name":"Moshe Cohen"
                  },
                  "status":  {
                                    "code":"200",
                                    "description": "O.K",
                                    "field_name":"NONE"
                        },
                "info": {
                                    "entry_id":"256"
                      }
          }
}
```

28 DELETE DIALER ENTRY BY ID

Http Method:

POST

Url:

http://callcenter/api/dialer_entry/delete_by_id

Request Parameters:

Parameter	Description	Required	Values
entry_id	The id of the entry to be deleted	required	only digits. The entry_id shoud be of an existing entry.
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
	<request>
		<request_id>1369813640.8711</request_id>
		  <type>dialer_entry_delete_by_id</type>
	</request>
	<status>
		<code>101</code>
		<description>Missing Parameter </code>
		<field_name>entry_id</field_name>
	</status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                <type>dial_entry_delete_by_id </type>
                  <entry_id>31</entry _id>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                  "type":"dial_entry_delete_by_id "
                  },
                  "status":  {
                                    "code":"101",
                                    "description": "Missing Parameter",
                                    "field_name":"entry_id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"call_get_cdr ",
                                 "entry _id":"31"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
         }
}
```

29 DELETE DIALER ENTRY BY NUMBER

Http Method:

POST

Url:

http://callcenter/api/dialer_entry/delete_by_number

Request Parameters:

Parameter	Description	Required	Values
campaign_id	The campaign the entry belongs to.	required	only digits
number1	The phone number to call	required	only digits
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>dialer_entry_delete_by_number</type>
<campaign_id>6</campaign_id>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>number</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                <type>dial_entry_delete_by_id </type>
                  <campaign _id>31</campaign _id>
                  <number1>073444555</number1>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                  "type":"dial_entry_delete_by_number ",
                                     "campaign_id":"6"
                  } ,
                  "status":  {
                                     "code":"101",
                                     "description": "Missing Parameter",
                                     "field_name":"number1"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"dial_entry_delete_by_number ",
                                 "campaign_id":"6",
                                 "number1":"073444555"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           }
          }
}
```

30 DELETE DIALER ENTRY BY CUSTOMER ID

Http Method:

POST

Url:

http://callcenter/api/dialer_entry/delete_by_customer_id

Request Parameters:

Parameter	Description	Required	Values
campaign_id	The campaign the entry belongs to.	required	only digits
customer_id	The customer identifier	required	string up to 50 characters
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and	required	The predefined value agreed upon.

	a predefined random string.		

Examples

Xml example:

Failed Response:

<?xml version="1.0" encoding="utf-8"?>

<data>

<request>

<request_id>1369813640.8711</request_id>

<type>dialer_entry_delete_by_customer_id</type>
<campaign_id>6</campaign_id>

</request>

<status>

<code>101</code>

<description>Missing Parameter </code>

<field_name>customer_id</field_name>

</status>

</data>

Successful Response:

<?xml version="1.0" encoding="utf-8"?>

<data>

<request>

<request_id>1369813640.8711</request_id>

<type>dial_entry_delete_by_customer_id </type>

<campaign _id>31</campaign _id>

<customer_id >ABC11234GMP</customer_id >



```
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:

{

```
  "data": {
                "request":  {
                            "request_id": "1369813640.8711",
                             "type":"dial_entry_delete_by_customer_id ",
                               "campaign_id":"6"
                } ,
                "status":  {
                               "code":"101",
                               "description": "Missing Parameter",
                               "field_name":"customer_id"
                          }
        }
}
```


Successful Response:


```
{
  "data": {
                "request":  {
                               "request_id": "1369813640.8711",
                               "type":"dial_entry_delete_by_customer_id ",
                               "campaign_id":"6",
                               "number1":"073444555"
```

```
                },
                "status": {
                                "code":"200",
                                "description": "O.K",
                                "field_name":"NONE"
                        }
        }
}
```

31 GET DIALER ENTRY ID

Http Method:

POST

Url:

http://callcenter/api/dialer_entry/get_entry_id

Request Parameters

Parameter	Description	Required	Values
campaign_id	The campaign the entry belongs to.	required	only digits
number1	The phone number to call	required	only digits
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Successful Response

On a successful request, the response will return:

entry_id – The id of the record with campaign_id and number1 as supplied.

The entry_id will be placed under the info element.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>dialer_entry_get_entry_id</type>
<campaign_id>6</campaign_id>
        </request>
        <status>
                <code>101</code>
                <description>Missing Parameter </code>
               <field_name>number</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                <type>dial_entry_get_entry_id</type>
                  <campaign _id>31</campaign _id>
                  <number1>073444555</number1>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
       <info>
                <entry_id>27</entry_id>
        </info>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                  "type":"dial_entry_get_entry_id ",
                                     "campaign_id":"6"
                  } ,
                  "status":  {
                                     "code":"101",
                                     "description": "Missing Parameter",
                                     "field_name":"number1"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"dial_entry_get_entry_id ",
                                 "campaign_id":"6",
                                 "number1":"073444555"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           },
                  "info": {
                           "entry_id": "27"
                           }
          }
}
```

32 EDIT DIALER ENTRY

Http Method:

POST

Url:

http://callcenter/api/dialer_entry/edit

Request Parameters:

Parameter	Description	Required	Values
entry_id	The entry id	required	Only digits.
campaign_id	The campaign id	optional	only digits. The campaign id should belong to an existing campaign.
name	The record name	optional	letters, digits, spaces,hyphens
number1	phone number to dial	optional	only digits
number2	additional phone	optional	only digits
number3	additional phone	optional	only digits
customer_id	customer identifier	optional	up to 50 characters

call_date	The dial time	optional	Y-M-D H:I:S (Mysql date format) The date has to be a future date.
custom_info	A string of custom key=value pairs joined by pipes	optional	key1=val1|key2=val2|key3=val3
format	The desired format of the response	required	json or xml
api_key	The special key that was supplied to the customer. This will be set during installation of the API. It is a combination of internal server IP and a predefined random string.	required	The predefined value agreed upon.

Examples

Xml example:

Failed Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                  <type>dialer_entry_edit </type>
                  <entry_id>5</entry_id>
                  <campaign_id>700</campaign_id>
        </request>
        <status>
                <code>227</code>
                <description>The campaign does not exist</code>
               <field_name>campaign_id</field_name>
        </status>
</data>
```

Successful Response:

```
<?xml version="1.0" encoding="utf-8"?>
<data>
        <request>
                <request_id>1369813640.8711</request_id>
                <type>dial_entry_edit </type>
                  <entry _id>31</entry _id>
                  <number1>073444555</number1>
        </request>
        <status>
                <code>200</code>
                <description>O.K</code>
               <field_name>NONE</field_name>
        </status>
</data>
```

Json example:

Failed Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                  "type":"dial_entry_edit ",
                                     "entry_id":"5",
                                     "campaign_id":"700"
                  } ,
                  "status":  {
                                     "code":"227",
                                     "description": "The campaign does not exist",
                                     "field_name":"campaign_id"
                              }
          }
}
```

Successful Response:


```
{
   "data": {
                  "request":  {
                                 "request_id": "1369813640.8711",
                                 "type":"dial_entry_edit ",
                                 "entry_id":"7",
                                 "campaign_id":"6"
                  },
                  "status":  {
                                 "code":"200",
                                 "description": "O.K",
                                 "field_name":"NONE"
                           },


         }
}
```

33 SEND CDR

This service enables you to get notified about every incoming or outgoing call in the call center. In order to have this service, the customer should supply a URL leading to a script that knows how to handle the reported data. The supplied URL should be given at the time of the API installation.

The reported data maybe formatted in xml or json or key-value pairs via post or get according to your preference. The reported data is passed as a string (an xml or json string) in a field named: data.

After parsing the 'data' field into xml or json, the following fields are available:

agent_id - The agent number.

queue_id -The queue number.

caller_id - The phone number of the caller.

answer_time - The time the call was answered.

end_time – The time the call was finished.

waiting_time – The waiting time.

duration – Duration of the call.

direction – incoming or outgoing.

recording_link - A link to the call recording.

call_status – answered or unanswered or asterisk status

custom1, custom2 -

The originate API enables passing custom1, custom2 parameters. These are values of the customer's choice. If the call arrived from the originate API service, the custom1, custom2 fields will be reported back by the Send Cdr.

An Example of A listener script

There should be a script located on the client machine that is listening for reports coming from the send CDR service. The script should be something like the following:

```
<?php

$xml_str  = $_REQUEST['data'];     // the 'data' key of the request array holds the xml string

$xml_obj = new SimpleXMLElement($xml_str);  // convert the string to an xml object

 // accessing the xml object fields :

log_me("agent_id=".$xml_obj->agent_id);

log_me("queue_id=".$xml_obj->queue_id);

log_me("caller_id=".$xml_obj->caller_id);

log_me("answer_time=".$xml_obj->answer_time);

log_me("end_time=".$xml_obj->end_time);

log_me("waiting_time=".$xml_obj->waiting_time);

log_me("duration=".$xml_obj->duration);

log_me("direction=".$xml_obj->direction);

log_me("recording_link=".$xml_ojb->recording_link);

log_me("call_status=".$xml_obj->call_status);

echo "Success!";  // returning some response to the send_cdr script
```

```
function log_me($str)
{
	$fh = fopen("/var/log/listener/listener.txt","a");
	fwrite($fh,"Start:".date("Y-m-d H:i:s")."\n");
	fwrite($fh,$str."\n");
	fwrite($fh,"End:".date("Y-m-d H:i:s")."\n");
	fclose($fh);
}

?>
```

Examples of call output

The examples below show the output of the send CDR service for each possible output format.

Each example displays the contents of the $_REQUEST of the listening script.

An Example of xml call output:

```
array (
	'data' =>
	 '<?xml version="1.0" encoding="utf-8"?>
	<info>
		<agent_id>2016</agent_id>
		<queue_id>3000</queue_id>
		<caller_id>0527367812</caller_id>
```

<answer_time>1373201867</answer_time>

<end_time>1373201885</end_time>

<waiting_time>3</waiting_time>

<duration>18</duration>

<direction>incoming</direction>

<recording_link>http://dana/api/legacy/get_rec_by_uid.php?uid=1373201860.136</recording_link>

<unique_id>1373201860.136</unique_id>

<cust1>CUSTOM1</cust1>

<cust2>CUSTOM2</cust2>

</info>',

)

An Example of json call output:

```
array (
        'data' => '{
                        "info":{
                                "agent_id":"2029",
                                "queue_id":"",
                                "caller_id":"0503300273",
                                "answer_time":"1325403767",
                                "end_time":1373204902,
                                "waiting_time":"411",
                                "duration":47801135,
```

```
                    "direction":"outgoing",
                    "recording_link":"http:\\/\\/dana\\/api\\/legacy\\/get_rec_by_uid.php
                ?uid=1325403767.329",
                    "unique_id":"1325403767.329",
                    "cust1":"hello",
                    "cust2":"world"
                }
            }',
)
```


An Example of key-value call output:


```
array (
  'agent_id' => '2029',
  'queue_id' => '',
  'caller_id' => '0503300273',
  'answer_time' => '1325403767',
  'end_time' => '1373205123',
  'waiting_time' => '411',
  'duration' => '47801356',
  'direction' => 'outgoing',
  'recording_link' => 'http://dana/api/legacy/get_rec_by_uid.php?uid=1325403767.329',
  'unique_id' => '1325403767.329',
  'cust1' => 'hello',
  'cust2' => 'world',
)
```