Politecnico di Milano

Department of Electronics, Information and Bioengineering

Master Degree course in Computer Science Engineering



Project Plan (PD)

myTaxiService



Instructor: Prof. Elisabetta Di Nitto

Authors: Code:
Luca Luciano Costanzo 789038
Simone Disabato 852863

Document version 1.0, released on January 21, 2016

Contents

1	Intr	duction	1
	1.1	Purpose	1
	1.2	List of Definitions and Abbreviations	1
	1.3	List of Reference Documents	2
	1.4	Overall Description	2
2	Proj	ect Estimations	3
	2.1	Project Size (Function Points)	3
		2.1.1 Internal Logic Files	6
		2.1.2 External Logic Files	6
		2.1.3 External Inputs	7
		2.1.4 External Inquiries	7
		2.1.5 External Outputs	7
	2.2	Effort Estimation (COCOMO II)	7
3	Proj	ect Schedule	8
4	Proj	ect Risks	9
5	Oth	er Info	10
	5.1	Working hours	10
	E 2		10

Abstract

The global scope of the project follows, as it has been explained in the previous documents, to make the document easy to understand.

Users, once registered, are able to ask for an immediate ride or to book one of them.

The system provides the user with a complete map of the city and its suburbs within the taxi service is available. The current position of the user is obtained by localization services of the user's smartphone if it's possible, otherwise the user notifies his position directly on the map with a marker or by a searching box. The destination is also chosen either graphically or by a research. The user can view the suggested path and then he must confirm the request.

When a user asks for a ride, the system checks the availability of a taxi driver near the current position, by splitting the city in several areas and using a FIFO (First In First Out) policy to manage the assignment of the ride's driver. The selected driver can accept or decline the ride. In the former case the system informs the user about waiting time, estimated travelling time, prices and cab car-code.

The system gives also the possibility to book a ride with at least two hours in advance. As the user does when he asks for a ride, he selects the desired starting venue and the destination. Afterwards, the system gives a calendar where the customer can choose the date (at most 30 days in advance) and the starting hour. Ten minutes before the meeting time the system starts all the operations described before in order to assign a taxi-driver.

A reservation from the app or the website can be undone until the system confirmation of the availability of a taxi, while a booking can be cancelled at most fifteen minutes before the meeting hour.

After those deadlines the ride is considered bought by the customers and an eventual absence on the established venue forbids other possibilities to book or to take a ride.

Introduction

In this chapter the purpose of the document will be presented in the section 1.1. Then, other useful information are made available, for instance the list of definitions and abbreviations and the reference documents. Finally, in the section 1.4 an overall description of the document structure will be presented.

1.1 Purpose

The purposes of this document are principally two. The first one is to estimate the project size, the effort and the cost, by using some algorithmic procedures. Second, a schedule and a plan for the document (partially retroactive, since this section should have been written in parallel with the Requirements Analysis and Specification Document), having a detailed analysis of team's member availability, the risks associated to the project and the associated recovery actions.

1.2 List of Definitions and Abbreviations

Up to now, no definitions or acronyms or abbreviation have been used in the document. Hence, this section is empty.

1.3 List of Reference Documents

The reference documents are now listed. Note that, all the documents related on the *myTaxyService* project are written by the same authors of this one, whereas the other documents have a reference of their author when this information is available.

- Software Engineering 2 Project, AA 2015-2016 Assignments 4 Test plan (available on beep platform only for registered students of Politecnico of Milan);
- The Requirements Analysis and Specification Document (RASD) for *my-TaxiService* v1.2, released on 6th November 2015;
- The Design Document (DD) for *myTaxiService* v1.0, released on 4th December 2015;
- The Integration Test Plan Document (ITPD) for *myTaxiService* v1.01, released on 21th January 2016.
- COCOMO II Model Definition Manual, available at http://csse.usc. edu/csse/research/COCOMOII/cocomo2000.0/CII_modelman2000. 0.pdf

1.4 Overall Description

The estimations concerning the project are presented in the chapter 2, with two algorithmic techniques: the Function Points (FP) to (typically under-) evaluate the project size and the COnstructive COst MOdel (COCOMO) to estimate the project effort and the costs.

The chapter 3 is reserved to the project schedule presentation and to the assignment of each task to a project's developer.

Finally, the chapter 4 the risks of the project and the related actions will be presented.

Project Estimations

In this chapter we are going to estimate the main features of *myTaxiService* project, by using COCOMO II. Reading from the reference manual:

The COCOMO II model is part of a suite of Constructive Cost Models. This suite is an effort to update and extend the well-known COCOMO (Constructive Cost Model) software cost estimation model originally published in Software Engineering Economics by Barry Boehm in 1981.

In the section 2.1 we focus on the project's size in term of lines of code, whereas in the section 2.2 other metrics, such the required time and the costs will be analysed.

2.1 Project Size (Function Points)

Reading from the reference manual:

The function point cost estimation approach is based on the amount of functionality in a software project and a set of individual project factors [Behrens 1983; Kunkler 1985; IFPUG 1994]. Function points are useful estimators since they are based on information that is available early in the project life-cycle. A brief summary of function points and their calculation in support of COCOMO II follows.

The function types are five, described in the table¹.

Function Point	Description
External Input (EI)	Count each unique user data or user control
	input type that enters the external boundary
	of the software system being measured.
External Output (EO)	Count each unique user data or control output
	type that leaves the external boundary of the
	software system being measured.
Internal Logical File (ILF)	Count each major logical group of user data or
	control information in the software system as
	a logical internal file type. Include each logi-
	cal file (e.g., each logical group of data) that
	is generated, used, or maintained by the soft-
	ware system.
External Interface Files (EIF)	Files passed or shared between software sys-
	tems should be counted as external interface
	file types within each system.
External Inquiry (EQ)	Count each unique input-output combina-
	tion, where input causes and generates an im-
	mediate output, as an external inquiry type.

Finally, to perform the analysis we have to present other two tables from the same reference manual of the other one. The first one will be used to classify each function on three level of complexity (high, medium and low).

The second one shows the weights to be used into the estimation formulas².

¹The table is given by the COCOMO II reference manual.

²The UFP acronym means Unadjusted Function Points

Table 2. FP Counting Weights

For Internal Logical Files and External Interface Files **Data Elements Record Elements** <u>20 - 50</u> <u>1 - 19</u> <u>51+</u> 1 2 - 5 Low Low Avg. Low Avg. High 6+ Avg. High High

For External Output and External Inquiry

	Data Elements		
File Types	<u>1 - 5</u>	<u>6 - 19</u>	<u>20+</u>
0 or 1	Low	Low	Avg.
2 - 3	Low	Avg.	High
4+	Ava.	High	High

For External Input

	Data Elements		
File Types	<u>1 - 4</u>	<u>5 - 15</u>	<u>16+</u>
0 or 1	Low	Low	Avg.
2 - 3	Low	Avg.	High
3+	Avg.	High	High

Table 3. UFP Complexity Weights

	Complexity-Weight		
Function Type	Low	Average	High
Internal Logical Files	7	10	15
External Interfaces Files	5	7	10
External Inputs	3	4	6
External Outputs	4	5	7
External Inquiries	3	4	6

Up to now, we have presented the Function Points technique. Now, we are going to start our analysis, split by the function type.

2.1.1 Internal Logic Files

The system has to manage Internal Logic Files to store information related to the users (both *normal* and drivers), the *historical* rides, the areas and the driver workshifts³

The users have from 12 to 16 fields to be stored (the second number is referred to the drivers case) and only the alerts and the zerotime or future rides have to be stored, thus the complexity is low. The areas and the workshifts can also be considered as low complexity type. In fact they have a few fields and less than six extra records.

The rides have 10 fields, including two positions, the driver and the passenger, all saved in separate entities. They can be considered as an average complexity type, since we have about seven records per ride (in fact in addition to the five presented, the positions requires additional records).

In the table the analysis is summarize:

ILF	Complexity	FP
User	Low	7
Area	Low	7
Workshift	Low	7
Ride	Average	10
Total		31

2.1.2 External Logic Files

The system acquires data from te GPS interface. A GPS position is essentially a tuple of type Position, described in our database. Hence, we have a low complexity type and 7 FP.

³See the logic schema at the page 10 of the Design Document to have a detailed description of each part of the database.

- 2.1.3 External Inputs
- 2.1.4 External Inquiries
- 2.1.5 External Outputs
- 2.2 Effort Estimation (COCOMO II)

Project Schedule

Project Risks

Other Info

This chapter contains information about the used tools and the hours of work by the members of the working group.

5.1 Working hours

Date	Costanzo's hours	Disabato's hours
2016/1/21	-	3h
Total Project Plan	0h	3h
Global	71h	76h

5.2 Tools

For this assignment the following tools were used:

• LaTeX and TexStudio editor