

**APPENDIX J — KITS, ACCESSORIES, PACKAGING, AND DEPLOYMENT MODES
(NON-LIMITING)**

A. Overview

This appendix provides non-limiting examples of kits, accessories, packaging, and deployment modes that may be used with any node described herein. Any accessory or deployment element described herein may be omitted, substituted, combined, or modified while maintaining the functional intent of privacy-preserving measurement, validity gating, and user-safe operation.

B. Example Kits (Non-Limiting)

In various embodiments, the system may be provided as one or more kits, including: 1. Single-node kit comprising one sensing node and a charging dock. 2. Two-node kit comprising an intimate-region node and an upper-body context node. 3. Baseline kit comprising one or more session-based baseline nodes (geometry and/or compliance) with alignment aids. 4. Multi-node kit comprising three or more nodes with a unified computing application for cross-device correlation. 5. Professional/clinical kit variant comprising one or more nodes with professional-facing reporting outputs.

C. Accessories and Consumables (Non-Limiting)

In various embodiments, accessories may include one or more of: removable sleeves, liners, or covers configured for hygiene and repeatable coupling; alignment aids for session-based scanning (e.g., positioning guides, orientation cues, docking-alignment features); docking bases configured for charging and storage; cleaning/storage cases and drying cradles; replacement consumables (e.g., single-use barriers, removable coupling interfaces) where desired; and calibration accessories configured to support sensor checks or reference measurements. Accessories may be configured to avoid explicit anatomical depiction and may be described in functional, non-limiting terms.

D. Packaging and User Guidance (Non-Limiting)

In various embodiments, packaging includes: 1. a device enclosure and protective foam or molded inserts, 2. a quick-start guide configured to describe privacy-preserving outputs and validity requirements, 3. safety and cleaning guidance consistent with materials and sealing approaches, and 4. optional QR-based onboarding to assist pairing and consent configuration. In certain embodiments, packaging includes labels and indicators for device orientation, charging alignment, and accessory identification.

E. Deployment Modes (Non-Limiting)

In various embodiments, the system supports one or more deployment modes, including: 1. consumer mode, emphasizing privacy-preserving indices, trends, and confidence indicators; 2. professional review mode, emphasizing session validity labels, quality indices, and exportable abstract summaries; 3. local-only mode, wherein data processing and storage occur locally and sharing is disabled; 4. derived-only exchange mode, wherein only privacy-preserving derived metrics may be shared under consent; and 5. consent-gated correlation mode, enabling cross-user correlation under explicit authorization scopes and revocation controls.

F. Provisioning, Pairing, and Device Management (Non-Limiting)

In various embodiments, the system includes: device provisioning and pairing flows, node naming and management, firmware update mechanisms, calibration and self-check flows, and access control configuration for cross-user correlation. In certain embodiments, device authenticity checks prevent unauthorized hardware from contributing to reportable outputs.

G. Variations

Any kit configuration, accessory set, packaging element, or deployment mode described herein may be substituted or rearranged. The system may be distributed as a modular kit that expands over time by adding additional nodes, and the computing system may update to support new node types while maintaining privacy-preserving output formats and validity gating.