

APPENDIX M — FIGURES, DRAWINGS, AND REFERENCE LABELS (OPTIONAL, NON-LIMITING)

A. Overview

This appendix provides an optional framework for organizing figures and reference labels that may be included with this provisional filing. Figures are not required, but can strengthen disclosure by illustrating node form factors, sensor placements, workflows, and data-flow architectures. Any figure numbers and labels herein are exemplary and may be renumbered or revised without limiting the disclosure.

B. Exemplary Figure List (Non-Limiting)

FIG. 1 — System overview showing a plurality of sensing nodes and a computing system, with privacy-preserving outputs. FIG. 2 — External longitudinal node example (ring or C-shaped wearable), showing non-limiting sensor regions (pressure/strain, magnetic displacement, optical, temperature, IMU). FIG. 3 — Intraluminal longitudinal node example, showing non-limiting sensor regions (impedance electrodes, dielectric sensing region, pH sensor region, temperature sensors, pressure zones, IMU). FIG. 4 — External geometry node example, showing scan-path concept, optical flow region, time-of-flight/distance regions, IMU region, and validity gating. FIG. 5 — Intraluminal geometry/compliance node example, showing endpoint sensing, controlled radial stimulus element, circumferential contact ring(s), stimulus pressure transducer, and validation gating. FIG. 6 — Upper-body context node example (chest, wrist, or ring), showing ECG/PPG/IMU/EDA/temperature regions and wear integrity checks. FIG. 7 — Data pipeline block diagram (acquisition → preprocessing → quality gating → feature extraction → metric generation → correlation → reporting). FIG. 8 — Consent-gated cross-user correlation flow, showing pairing, scope selection, derived-metric exchange, correlation computation, and revocation/expiration. FIG. 9 — Privacy-preserving UI examples illustrating indices, zones, curves, confidence indicators, and consent/scope status displays.

C. Exemplary Reference Labels (Non-Limiting)

In various embodiments, figures may use reference labels including: 100 computing system; 110 mobile device; 120 server environment; 200 plurality of sensing nodes; 210 external longitudinal node; 220 intraluminal longitudinal node; 230 external geometry node; 240 intraluminal geometry/compliance node; 250 context node; 300 communications link; 310 time synchronization module; 400 preprocessing module; 410 quality index module; 420 artifact rejection module; 430 feature extraction module; 440 metric generation module; 450 correlation module; 460 privacy-preserving output module; 500 consent manager; 510 scope selector; 520 token/key manager; 530 audit metadata module.

D. Non-Limiting Notes on Figures

1. Figures may be schematic, conceptual, or illustrative, and are not required to be to scale. 2. Sensor placements may be generalized as regions to allow substitution and variation. 3. Any node form factor shown in a figure may represent external, intraluminal, wearable, session-based, or hybrid embodiments.