

**APPENDIX N — DEFINITIONS, TERMINOLOGY, AND INTERPRETATION RULES
(NON-LIMITING)**

A. Overview

This appendix provides non-limiting definitions and interpretation rules to clarify terms used throughout this specification. These definitions are provided for convenience and do not limit the scope of the disclosure.

B. Definitions (Non-Limiting)

1. Node: a device, module, or subsystem configured to acquire one or more sensor signals and provide data to a computing system. 2. Sensing node / sensing device: a node containing one or more sensors, associated electronics, and a housing configured for wearable, intraluminal, session-based, or context collection. 3. Computing system: one or more processors and memory (e.g., mobile device, embedded processor, server environment) configured to receive data, process data, and generate outputs. 4. Longitudinal: measurements collected across time windows over hours, nights, days, weeks, or longer. 5. Session-based: measurements collected during a discrete user-performed workflow intended to produce a baseline reference and/or validation-scored acquisition. 6. Intraluminal: configured to operate at least partially within an internal bodily lumen (including vaginal and/or anal contexts in certain embodiments). 7. External: configured to operate outside the body and/or adjacent to external tissue. 8. Quality index (QI): a computed measure representing signal validity and/or confidence derived from contact integrity, motion gating, sensor saturation, continuity checks, and/or multi-sensor agreement. 9. Validity gating: accepting, down-weighting, or excluding data windows based on quality index thresholds and plausibility checks. 10. Artifact rejection: signal processing and classification steps configured to reduce or remove motion artifacts, contact artifacts, drift artifacts, thermal artifacts, and/or environmental artifacts. 11. Derived metric: an output computed from one or more sensor signals, which may be privacy-preserving and normalized. 12. Privacy-preserving output: an output configured to avoid explicit anatomical imagery and avoid explicit anatomical labeling, typically presented as indices, zones, ranges, curves, distributions, and confidence indicators. 13. Cross-device correlation: correlation or alignment computations performed between derived metrics originating from two or more nodes. 14. Cross-user correlation: correlation or alignment computations performed between two user profiles under consent gating, preferably using derived metrics without sharing raw signals between users. 15. Consent gating: a permission and scope control mechanism controlling whether, how, and for how long cross-user sharing and correlation may occur.

C. Interpretation Rules (Non-Limiting)

1. Open-ended terms: including, comprising, and having are open-ended and do not exclude additional elements. 2. Configured to: indicates capability, not strict requirement of use in every instance. 3. Approximate values: about indicates reasonable tolerances given device constraints and practical measurement variability. 4. Substitution principle: any sensor modality may be replaced by an equivalent modality providing substantially similar function. 5. Combination principle: any feature described in one embodiment may be combined with any feature described in another embodiment unless expressly stated otherwise. 6. Ordering: process steps may be reordered, repeated, omitted, or combined unless a particular order is explicitly required.

D. Non-Limiting Closing Notes

These definitions and rules are intended to clarify disclosure language and support broad coverage of variations, substitutions, and combinations consistent with the described systems and methods.