

DETAILED DESCRIPTION OF THE INVENTION

Distinction Over Conventional Techniques (Non-Admission)

The following discussion is provided for contextual clarity and shall not be construed as an admission regarding the scope, content, or applicability of any prior art. The disclosed systems and methods differ materially from conventional measurement approaches that rely on manual rulers, flexible tapes, visual estimation, static calipers, or isolated single-point proximity sensing.

Conventional measurement techniques typically produce discrete scalar values without spatial indexing, surface reconstruction, or standardized digital encoding. Such approaches lack synchronized correlation between radial depth acquisition and longitudinal positional tracking sufficient to generate a structured anatomical geometry profile.

Existing proximity or distance-measuring devices that capture isolated depth values do not, to the inventor's knowledge, combine multi-axis displacement tracking with temporally synchronized radial sampling to reconstruct a continuous indexed three-dimensional anatomical model as described herein. Furthermore, conventional sizing devices do not incorporate integrated encryption, anti-spoofing physiological validation, encoded structural signature generation, or modular interoperability pathways within distributed biometric ecosystems.

To the extent that depth sensing technologies, optical motion sensors, lidar systems, structured light modules, or displacement tracking components are known individually, the inventive architecture disclosed herein resides in the coordinated synchronization, spatial indexing, reconstruction modeling, encoded profile generation, and system-level integration of such components for penile anatomical geometry profiling.

Nothing in this section shall be interpreted as limiting the inventive concepts to distinctions expressly articulated above. The inventive scope is defined by the disclosed coordinated architecture for generating user-specific penile anatomical geometry profiles through synchronized spatial acquisition, reconstruction, encoding, and secure deployment frameworks, irrespective of whether individual sensing elements were previously known in isolation.