

HNCO

0.7

Generated by Doxygen 1.8.13

Contents

1	Namespace Index	1
1.1	Namespace List	1
2	Hierarchical Index	3
2.1	Class Hierarchy	3
3	Class Index	7
3.1	Class List	7
4	Namespace Documentation	11
4.1	hnco Namespace Reference	11
4.1.1	Detailed Description	14
4.1.2	Typedef Documentation	14
4.1.2.1	bit_t	14
4.1.2.2	sparse_bit_matrix_t	14
4.1.2.3	sparse_bit_vector_t	15
4.1.3	Function Documentation	15
4.1.3.1	bm_add_rows()	15
4.1.3.2	bm_identity()	15
4.1.3.3	bm_invert()	15
4.1.3.4	bm_multiply()	16
4.1.3.5	bm_solve()	16
4.1.3.6	bm_solve_upper_triangular()	17
4.1.3.7	sbm_multiply()	18
4.2	hnco::algorithm Namespace Reference	18

4.2.1	Detailed Description	20
4.3	hnco::algorithm::bm_pbil Namespace Reference	20
4.3.1	Detailed Description	20
4.4	hnco::algorithm::hea Namespace Reference	21
4.4.1	Detailed Description	21
4.5	hnco::exception Namespace Reference	21
4.5.1	Detailed Description	21
4.6	hnco::function Namespace Reference	22
4.6.1	Detailed Description	23
4.7	hnco::neighborhood Namespace Reference	23
4.7.1	Detailed Description	24
4.8	hnco::random Namespace Reference	24
4.8.1	Detailed Description	24
5	Class Documentation	25
5.1	AdditiveGaussianNoise Class Reference	25
5.1.1	Detailed Description	26
5.1.2	Member Function Documentation	26
5.1.2.1	get_maximum()	26
5.1.2.2	has_known_maximum()	26
5.2	AffineMap Class Reference	27
5.2.1	Detailed Description	28
5.3	Algorithm Class Reference	28
5.3.1	Detailed Description	30
5.3.2	Member Data Documentation	30
5.3.2.1	_functions	30
5.4	BernoulliProcess Class Reference	31
5.4.1	Detailed Description	32
5.4.2	Constructor & Destructor Documentation	32
5.4.2.1	BernoulliProcess() [1/2]	32
5.4.2.2	BernoulliProcess() [2/2]	32

5.4.3	Member Function Documentation	33
5.4.3.1	set_allow_stay()	33
5.4.3.2	set_probability()	33
5.5	BiasedCrossover Class Reference	34
5.5.1	Detailed Description	34
5.5.2	Member Function Documentation	34
5.5.2.1	breed()	34
5.6	BinaryHerding Class Reference	35
5.6.1	Detailed Description	36
5.6.2	Member Enumeration Documentation	36
5.6.2.1	anonymous enum	36
5.7	BinaryMoment Struct Reference	37
5.7.1	Detailed Description	38
5.8	BmPbil Class Reference	38
5.8.1	Detailed Description	40
5.8.2	Member Enumeration Documentation	40
5.8.2.1	anonymous enum	40
5.8.2.2	anonymous enum	41
5.8.2.3	anonymous enum	41
5.8.3	Member Function Documentation	41
5.8.3.1	set_selection_size()	41
5.9	Cache Class Reference	42
5.9.1	Detailed Description	43
5.9.2	Constructor & Destructor Documentation	43
5.9.2.1	Cache()	43
5.9.3	Member Function Documentation	43
5.9.3.1	provides_incremental_evaluation()	44
5.10	CallCounter Class Reference	44
5.10.1	Detailed Description	45
5.11	CompactGa Class Reference	45

5.11.1 Detailed Description	47
5.12 CompleteSearch Class Reference	47
5.12.1 Detailed Description	48
5.13 Crossover Class Reference	48
5.13.1 Detailed Description	48
5.13.2 Member Function Documentation	49
5.13.2.1 breed()	49
5.14 DeceptiveJump Class Reference	49
5.14.1 Detailed Description	50
5.14.2 Member Function Documentation	50
5.14.2.1 get_maximum()	50
5.14.2.2 has_known_maximum()	51
5.15 EqualProducts Class Reference	51
5.15.1 Detailed Description	52
5.15.2 Member Function Documentation	52
5.15.2.1 random()	52
5.16 Error Class Reference	53
5.16.1 Detailed Description	54
5.17 ProgressTracker::Event Struct Reference	54
5.17.1 Detailed Description	54
5.18 Exception Class Reference	54
5.18.1 Detailed Description	55
5.19 Factorization Class Reference	55
5.19.1 Detailed Description	56
5.19.2 Constructor & Destructor Documentation	56
5.19.2.1 Factorization()	56
5.20 FourPeaks Class Reference	57
5.20.1 Detailed Description	58
5.20.2 Member Function Documentation	58
5.20.2.1 get_maximum()	59

5.20.2.2	has_known_maximum()	59
5.21	Function Class Reference	59
5.21.1	Detailed Description	61
5.21.2	Member Function Documentation	61
5.21.2.1	get_maximum()	61
5.21.2.2	incremental_eval()	62
5.21.2.3	provides_incremental_evaluation()	62
5.21.2.4	safe_eval()	62
5.22	FunctionController Class Reference	63
5.22.1	Detailed Description	64
5.22.2	Member Function Documentation	64
5.22.2.1	provides_incremental_evaluation()	64
5.23	FunctionDecorator Class Reference	64
5.23.1	Detailed Description	65
5.24	FunctionMapComposition Class Reference	65
5.24.1	Detailed Description	66
5.24.2	Constructor & Destructor Documentation	66
5.24.2.1	FunctionMapComposition()	66
5.24.3	Member Function Documentation	67
5.24.3.1	get_maximum()	67
5.24.3.2	has_known_maximum()	67
5.25	FunctionModifier Class Reference	68
5.25.1	Detailed Description	68
5.26	FunctionPlugin Class Reference	69
5.26.1	Detailed Description	70
5.26.2	Constructor & Destructor Documentation	70
5.26.2.1	FunctionPlugin()	70
5.27	GeneticAlgorithm Class Reference	70
5.27.1	Detailed Description	72
5.27.2	Constructor & Destructor Documentation	72

5.27.2.1	GeneticAlgorithm()	72
5.27.3	Member Function Documentation	73
5.27.3.1	set_allow_stay()	73
5.28	HammingBall Class Reference	73
5.28.1	Detailed Description	74
5.28.2	Constructor & Destructor Documentation	74
5.28.2.1	HammingBall()	74
5.29	HammingBallIterator Class Reference	75
5.29.1	Detailed Description	76
5.29.2	Constructor & Destructor Documentation	76
5.29.2.1	HammingBallIterator()	76
5.30	HammingSphere Class Reference	76
5.30.1	Detailed Description	77
5.30.2	Constructor & Destructor Documentation	78
5.30.2.1	HammingSphere()	78
5.31	Hea< Moment, Herding > Class Template Reference	78
5.31.1	Detailed Description	80
5.31.2	Member Enumeration Documentation	81
5.31.2.1	anonymous enum	81
5.31.2.2	anonymous enum	81
5.31.3	Constructor & Destructor Documentation	81
5.31.3.1	Hea()	81
5.31.4	Member Function Documentation	82
5.31.4.1	set_reset_period()	82
5.31.4.2	set_selection_size()	82
5.32	Hiff Class Reference	83
5.32.1	Detailed Description	83
5.32.2	Member Function Documentation	84
5.32.2.1	get_maximum()	84
5.32.2.2	has_known_maximum()	84

5.33 Hypercubeliterator Class Reference	84
5.33.1 Detailed Description	85
5.33.2 Member Function Documentation	85
5.33.2.1 next()	85
5.34 IterativeAlgorithm Class Reference	86
5.34.1 Detailed Description	87
5.34.2 Constructor & Destructor Documentation	87
5.34.2.1 IterativeAlgorithm()	87
5.34.3 Member Function Documentation	87
5.34.3.1 maximize()	87
5.34.3.2 set_num_iterations()	88
5.35 Iterator Class Reference	88
5.35.1 Detailed Description	89
5.36 Jump Class Reference	90
5.36.1 Detailed Description	90
5.36.2 Member Function Documentation	91
5.36.2.1 get_maximum()	91
5.36.2.2 has_known_maximum()	91
5.37 Labs Class Reference	91
5.37.1 Detailed Description	92
5.38 LastEvaluation Class Reference	92
5.38.1 Detailed Description	93
5.39 LeadingOnes Class Reference	93
5.39.1 Detailed Description	94
5.39.2 Member Function Documentation	94
5.39.2.1 get_maximum()	94
5.39.2.2 has_known_maximum()	94
5.40 LinearFunction Class Reference	95
5.40.1 Detailed Description	96
5.40.2 Member Function Documentation	96

5.40.2.1	has_known_maximum()	96
5.40.2.2	random()	96
5.41	LinearMap Class Reference	97
5.41.1	Detailed Description	98
5.42	LocalMaximum Class Reference	98
5.42.1	Detailed Description	99
5.43	LongPath Class Reference	99
5.43.1	Detailed Description	100
5.44	Map Class Reference	100
5.44.1	Detailed Description	101
5.44.2	Member Function Documentation	101
5.44.2.1	is_surjective()	101
5.45	MapComposition Class Reference	102
5.45.1	Detailed Description	102
5.45.2	Constructor & Destructor Documentation	103
5.45.2.1	MapComposition()	103
5.45.3	Member Function Documentation	103
5.45.3.1	is_surjective()	103
5.46	MaximumReached Class Reference	104
5.46.1	Detailed Description	104
5.47	MaxSat Class Reference	105
5.47.1	Detailed Description	106
5.47.2	Member Function Documentation	106
5.47.2.1	load()	106
5.47.2.2	random() [1/2]	106
5.47.2.3	random() [2/2]	107
5.47.3	Member Data Documentation	107
5.47.3.1	_expression	107
5.48	Mmas Class Reference	108
5.48.1	Detailed Description	109

5.49 Model Class Reference	109
5.49.1 Detailed Description	110
5.50 ModelParameters Class Reference	110
5.50.1 Detailed Description	111
5.51 MuCommaLambdaEa Class Reference	111
5.51.1 Detailed Description	112
5.51.2 Constructor & Destructor Documentation	112
5.51.2.1 MuCommaLambdaEa()	112
5.51.3 Member Function Documentation	113
5.51.3.1 set_allow_stay()	113
5.52 MultiBitFlip Class Reference	113
5.52.1 Detailed Description	114
5.52.2 Constructor & Destructor Documentation	114
5.52.2.1 MultiBitFlip()	114
5.52.3 Member Function Documentation	114
5.52.3.1 bernoulli_trials()	114
5.52.3.2 reservoir_sampling()	115
5.53 MuPlusLambdaEa Class Reference	115
5.53.1 Detailed Description	116
5.53.2 Constructor & Destructor Documentation	117
5.53.2.1 MuPlusLambdaEa()	117
5.53.3 Member Function Documentation	117
5.53.3.1 set_allow_stay()	117
5.54 Needle Class Reference	118
5.54.1 Detailed Description	118
5.54.2 Member Function Documentation	119
5.54.2.1 get_maximum()	119
5.54.2.2 has_known_maximum()	119
5.55 Negation Class Reference	120
5.55.1 Detailed Description	121

5.55.2	Member Function Documentation	121
5.55.2.1	get_maximum()	121
5.55.2.2	has_known_maximum()	121
5.55.2.3	provides_incremental_evaluation()	122
5.56	Neighborhood Class Reference	122
5.56.1	Detailed Description	124
5.56.2	Constructor & Destructor Documentation	124
5.56.2.1	Neighborhood()	124
5.56.3	Member Function Documentation	124
5.56.3.1	map()	124
5.56.3.2	mutate()	125
5.57	NeighborhoodIterator Class Reference	125
5.57.1	Detailed Description	126
5.57.2	Constructor & Destructor Documentation	126
5.57.2.1	NeighborhoodIterator()	126
5.58	NkLandscape Class Reference	126
5.58.1	Detailed Description	127
5.58.2	Member Function Documentation	128
5.58.2.1	random()	128
5.59	NpsPbil Class Reference	128
5.59.1	Detailed Description	130
5.60	OnBudgetFunction Class Reference	130
5.60.1	Detailed Description	132
5.60.2	Member Function Documentation	132
5.60.2.1	eval()	132
5.60.2.2	incremental_eval()	132
5.60.2.3	update()	133
5.61	OneMax Class Reference	133
5.61.1	Detailed Description	134
5.61.2	Member Function Documentation	134

5.61.2.1	get_maximum()	134
5.61.2.2	has_known_maximum()	135
5.61.2.3	provides_incremental_evaluation()	135
5.62	OnePlusLambdaCommaLambdaGa Class Reference	135
5.62.1	Detailed Description	136
5.62.2	Constructor & Destructor Documentation	137
5.62.2.1	OnePlusLambdaCommaLambdaGa()	137
5.63	OnePlusOneEa Class Reference	137
5.63.1	Detailed Description	138
5.63.2	Constructor & Destructor Documentation	139
5.63.2.1	OnePlusOneEa()	139
5.63.3	Member Function Documentation	139
5.63.3.1	set_allow_stay()	139
5.63.3.2	set_num_iterations()	139
5.64	Pbil Class Reference	140
5.64.1	Detailed Description	141
5.65	Permutation Class Reference	141
5.65.1	Detailed Description	142
5.65.2	Member Function Documentation	142
5.65.2.1	is_surjective()	143
5.66	Plateau Class Reference	143
5.66.1	Detailed Description	144
5.66.2	Member Function Documentation	144
5.66.2.1	get_maximum()	144
5.66.2.2	has_known_maximum()	144
5.67	PointValueException Class Reference	145
5.67.1	Detailed Description	145
5.68	Population Class Reference	146
5.68.1	Detailed Description	147
5.68.2	Member Function Documentation	147

5.68.2.1	comma_selection()	148
5.68.2.2	get_best_bv() [1/2]	148
5.68.2.3	get_best_bv() [2/2]	148
5.68.2.4	get_best_value() [1/2]	149
5.68.2.5	get_best_value() [2/2]	149
5.68.2.6	get_worst_bv()	149
5.68.2.7	plus_selection()	150
5.68.3	Member Data Documentation	150
5.68.3.1	_lookup	150
5.68.3.2	_operator	150
5.69	PriorNoise Class Reference	151
5.69.1	Detailed Description	152
5.69.2	Member Function Documentation	152
5.69.2.1	get_maximum()	152
5.69.2.2	has_known_maximum()	152
5.69.2.3	provides_incremental_evaluation()	153
5.70	ProgressTracker Class Reference	153
5.70.1	Detailed Description	154
5.70.2	Member Function Documentation	155
5.70.2.1	eval()	155
5.70.2.2	get_last_improvement()	155
5.70.2.3	incremental_eval()	155
5.70.2.4	update()	156
5.71	PvAlgorithm Class Reference	156
5.71.1	Detailed Description	157
5.71.2	Member Enumeration Documentation	157
5.71.2.1	anonymous enum	157
5.72	Qubo Class Reference	158
5.72.1	Detailed Description	159
5.72.2	Member Function Documentation	159

5.72.2.1	load()	159
5.72.3	Member Data Documentation	160
5.72.3.1	_q	160
5.73	Random Struct Reference	160
5.73.1	Detailed Description	160
5.74	RandomLocalSearch Class Reference	161
5.74.1	Detailed Description	162
5.74.2	Member Function Documentation	162
5.74.2.1	set_patience()	162
5.75	RandomSearch Class Reference	163
5.75.1	Detailed Description	164
5.76	Restart Class Reference	164
5.76.1	Detailed Description	165
5.77	Ridge Class Reference	165
5.77.1	Detailed Description	166
5.77.2	Member Function Documentation	166
5.77.2.1	get_maximum()	166
5.77.2.2	has_known_maximum()	167
5.78	SimulatedAnnealing Class Reference	167
5.78.1	Detailed Description	169
5.78.2	Member Function Documentation	169
5.78.2.1	init_beta()	169
5.79	SingleBitFlip Class Reference	169
5.79.1	Detailed Description	170
5.80	SingleBitFlipIteator Class Reference	170
5.80.1	Detailed Description	171
5.80.2	Constructor & Destructor Documentation	171
5.80.2.1	SingleBitFlipIteator()	171
5.81	SinusSummationCancellation Class Reference	172
5.81.1	Detailed Description	172

5.82 SixPeaks Class Reference	173
5.82.1 Detailed Description	174
5.82.2 Member Function Documentation	174
5.82.2.1 get_maximum()	174
5.82.2.2 has_known_maximum()	175
5.83 SpinHerdng Class Reference	175
5.83.1 Detailed Description	176
5.83.2 Member Enumeration Documentation	177
5.83.2.1 anonymous enum	177
5.83.3 Constructor & Destructor Documentation	177
5.83.3.1 SpinHerdng()	177
5.83.4 Member Function Documentation	177
5.83.4.1 q_variation()	177
5.84 SpinMoment Struct Reference	178
5.84.1 Detailed Description	179
5.85 SteepestAscentHillClimbing Class Reference	179
5.85.1 Detailed Description	180
5.86 StopOnMaximum Class Reference	180
5.86.1 Detailed Description	181
5.86.2 Constructor & Destructor Documentation	181
5.86.2.1 StopOnMaximum()	181
5.86.3 Member Function Documentation	182
5.86.3.1 eval()	182
5.86.3.2 incremental_eval()	182
5.86.3.3 update()	182
5.87 StopOnTarget Class Reference	183
5.87.1 Detailed Description	184
5.87.2 Constructor & Destructor Documentation	184
5.87.2.1 StopOnTarget()	184
5.87.3 Member Function Documentation	184

5.87.3.1	eval()	184
5.87.3.2	incremental_eval()	185
5.87.3.3	update()	185
5.88	SummationCancellation Class Reference	185
5.88.1	Detailed Description	187
5.88.2	Constructor & Destructor Documentation	187
5.88.2.1	SummationCancellation()	187
5.88.3	Member Function Documentation	187
5.88.3.1	has_known_maximum()	187
5.89	TargetReached Class Reference	188
5.89.1	Detailed Description	188
5.90	TournamentSelection Class Reference	189
5.90.1	Detailed Description	189
5.90.2	Member Function Documentation	190
5.90.2.1	select()	190
5.91	Translation Class Reference	190
5.91.1	Detailed Description	191
5.91.2	Member Function Documentation	191
5.91.2.1	is_surjective()	192
5.92	Trap Class Reference	192
5.92.1	Detailed Description	193
5.92.2	Constructor & Destructor Documentation	193
5.92.2.1	Trap()	193
5.92.3	Member Function Documentation	193
5.92.3.1	get_maximum()	194
5.92.3.2	has_known_maximum()	194
5.93	Umda Class Reference	194
5.93.1	Detailed Description	196
5.94	UniformCrossover Class Reference	196
5.94.1	Detailed Description	196

5.94.2	Member Function Documentation	197
5.94.2.1	breed()	197
5.95	WalshExpansion Class Reference	197
5.95.1	Detailed Description	198
5.95.2	Member Function Documentation	199
5.95.2.1	random()	199
5.96	WalshExpansion1 Class Reference	199
5.96.1	Detailed Description	200
5.96.2	Member Function Documentation	200
5.96.2.1	random()	200
5.97	WalshExpansion2 Class Reference	201
5.97.1	Detailed Description	202
5.97.2	Member Function Documentation	202
5.97.2.1	random()	202
5.97.3	Member Data Documentation	203
5.97.3.1	_quadratic	203
Index		205

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

hnco	Top-level HNCO namespace	11
hnco::algorithm	Algorithms	18
hnco::algorithm::bm_pbil	Boltzmann machine PBIL	20
hnco::algorithm::hea	Herding evolutionary algorithm	21
hnco::exception	Exceptions	21
hnco::function	Functions to be maximized	22
hnco::neighborhood	Neighborhoods for local search	23
hnco::random	Pseudo random numbers	24

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Algorithm	28
CompleteSearch	47
IterativeAlgorithm	86
BmPbil	38
GeneticAlgorithm	70
Hea< Moment, Herding >	78
MuCommaLambdaEa	111
MuPlusLambdaEa	115
OnePlusLambdaCommaLambdaGa	135
PvAlgorithm	156
CompactGa	45
Mmas	108
NpsPbil	128
Pbil	140
Umda	194
RandomLocalSearch	161
RandomSearch	163
Restart	164
SimulatedAnnealing	167
SteepestAscentHillClimbing	179
OnePlusOneEa	137
BinaryHerding	35
BinaryMoment	37
Crossover	48
BiasedCrossover	34
UniformCrossover	196
ProgressTracker::Event	54
Exception	54
Error	53
LastEvaluation	92
PointValueException	145
LocalMaximum	98
MaximumReached	104
TargetReached	188

Function	59
DeceptiveJump	49
EqualProducts	51
Factorization	55
FourPeaks	57
FunctionDecorator	64
FunctionController	63
Cache	42
CallCounter	44
OnBudgetFunction	130
ProgressTracker	153
StopOnMaximum	180
StopOnTarget	183
FunctionModifier	68
AdditiveGaussianNoise	25
FunctionMapComposition	65
Negation	120
PriorNoise	151
FunctionPlugin	69
Hiff	83
Jump	90
Labs	91
LeadingOnes	93
LinearFunction	95
LongPath	99
MaxSat	105
Needle	118
NkLandscape	126
OneMax	133
Plateau	143
Qubo	158
Ridge	165
SixPeaks	173
SummationCancellation	185
SinusSummationCancellation	172
Trap	192
WalshExpansion	197
WalshExpansion1	199
WalshExpansion2	201
Iterator	88
HypercubeIterator	84
NeighborhoodIterator	125
HammingBallIterator	75
SingleBitFlipIterator	170
Map	100
AffineMap	27
LinearMap	97
MapComposition	102
Permutation	141
Translation	190
Model	109
ModelParameters	110
Neighborhood	122
MultiBitFlip	113
BernoulliProcess	31
HammingBall	73
HammingSphere	76

SingleBitFlip	169
Population	146
TournamentSelection	189
Random	160
SpinHerding	175
SpinMoment	178

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

AdditiveGaussianNoise	
Additive Gaussian Noise	25
AffineMap	
Affine map	27
Algorithm	
Abstract search algorithm	28
BernoulliProcess	
Bernoulli process	31
BiasedCrossover	
Biased crossover	34
BinaryHerding	
Herding with binary variables	35
BinaryMoment	
Moment for binary variables	37
BmPbil	
Boltzmann machine PBIL	38
Cache	
Cache	42
CallCounter	
Call counter	44
CompactGa	
Compact genetic algorithm	45
CompleteSearch	
Complete search	47
Crossover	
Crossover	48
DeceptiveJump	
Deceptive jump	49
EqualProducts	
Equal products	51
Error	
Error	53
ProgressTracker::Event	
Event	54
Exception	
Basic exception	54

Factorization	
Factorization	55
FourPeaks	
Four Peaks	57
Function	
Function	59
FunctionController	
Function controller	63
FunctionDecorator	
Function decorator	64
FunctionMapComposition	
Composition of a function and a map	65
FunctionModifier	
Function modifier	68
FunctionPlugin	
Function plugin	69
GeneticAlgorithm	
Genetic algorithm	70
HammingBall	
Hamming ball	73
HammingBallIterator	
Hamming ball neighborhood iterator	75
HammingSphere	
Hamming sphere	76
Hea< Moment, Herding >	
Herding evolutionary algorithm	78
Hiff	
Hierarchical if and only if	83
HypercubeIterator	
Hypercube iterator	84
IterativeAlgorithm	
Iterative search	86
Iterator	
Iterator over bit vectors	88
Jump	
Jump	90
Labs	
Low autocorrelation binary sequences	91
LastEvaluation	
Last evaluation	92
LeadingOnes	
Leading ones	93
LinearFunction	
Linear function	95
LinearMap	
Linear map	97
LocalMaximum	
Local maximum	98
LongPath	
Long path	99
Map	
Map	100
MapComposition	
Map composition	102
MaximumReached	
Maximum reached	104
MaxSat	
MAX-SAT	105

Mmas	
Max-min ant system	108
Model	
Model of a Boltzmann machine	109
ModelParameters	
Parameters of a Boltzmann machine	110
MuCommaLambdaEa	
(mu, lambda) EA	111
MultiBitFlip	
Multi bit flip	113
MuPlusLambdaEa	
(mu+lambda) EA	115
Needle	
Needle in a haystack	118
Negation	
Negation	120
Neighborhood	
Neighborhood	122
NeighborhoodIterator	
Neighborhood iterator	125
NkLandscape	
NK landscape	126
NpsPbil	
Population-based incremental learning with negative and positive selection	128
OnBudgetFunction	
CallCounter with a limited number of evaluations	130
OneMax	
OneMax	133
OnePlusLambdaCommaLambdaGa	
(1+(lambda, lambda)) genetic algorithm	135
OnePlusOneEa	
(1+1) EA	137
Pbil	
Population-based incremental learning	140
Permutation	
Permutation	141
Plateau	
Plateau	143
PointValueException	
Point-value exception	145
Population	
Population	146
PriorNoise	
Prior noise	151
ProgressTracker	
ProgressTracker	153
PvAlgorithm	
Probability vector algorithm	156
Qubo	
Quadratic unconstrained binary optimization	158
Random	
Random numbers	160
RandomLocalSearch	
Random local search	161
RandomSearch	
Random search	163
Restart	
Restart	164

Ridge	
Ridge	165
SimulatedAnnealing	
Simulated annealing	167
SingleBitFlip	
One bit neighborhood	169
SingleBitFlipIterator	
Single bit flip neighborhood iterator	170
SinusSummationCancellation	
Summation cancellation with sinus	172
SixPeaks	
Six Peaks	173
SpinHerdin	
Herdin with spin variables	175
SpinMoment	
Moment for spin variables	178
SteepestAscentHillClimbing	
Steepest ascent hill climbing	179
StopOnMaximum	
Stop on maximum	180
StopOnTarget	
Stop on target	183
SummationCancellation	
Summation cancellation	185
TargetReached	
Target reached	188
TournamentSelection	
Population with tournament selection	189
Translation	
Translation	190
Trap	
Trap	192
Umda	
Univariate marginal distribution algorithm	194
UniformCrossover	
Uniform crossover	196
WalshExpansion	
Walsh expansion	197
WalshExpansion1	
Walsh expansion of degree 1	199
WalshExpansion2	
Walsh expansion of degree 2	201

Chapter 4

Namespace Documentation

4.1 hnco Namespace Reference

top-level HNCO namespace

Namespaces

- [algorithm](#)
Algorithms.
- [exception](#)
Exceptions.
- [function](#)
Functions to be maximized.
- [neighborhood](#)
Neighborhoods for local search.
- [random](#)
Pseudo random numbers.

Classes

- class [AffineMap](#)
Affine map.
- class [HypercubeIterator](#)
Hypercube iterator.
- class [Iterator](#)
[Iterator](#) over bit vectors.
- class [LinearMap](#)
Linear map.
- class [Map](#)
Map.
- class [MapComposition](#)
Map composition.
- class [Permutation](#)
Permutation.
- class [Translation](#)
Translation.

Types and functions related to bit matrices

- typedef std::vector< [bit_vector_t](#) > [bit_matrix_t](#)
Bit matrix.
- void [bm_display](#) (const [bit_matrix_t](#) &M, std::ostream &stream)
Display bit matrix.
- bool [bm_is_valid](#) (const [bit_matrix_t](#) &M)
Check whether a bit matrix is valid.
- size_t [bm_num_rows](#) (const [bit_matrix_t](#) &M)
Number of rows.
- size_t [bm_num_columns](#) (const [bit_matrix_t](#) &M)
Number of columns.
- bool [bm_is_square](#) (const [bit_matrix_t](#) &M)
Check whether the matrix is a square matrix.
- bool [bm_is_identity](#) (const [bit_matrix_t](#) &M)
Check whether the matrix is the identity matrix.
- bool [bm_is_upper_triangular](#) (const [bit_matrix_t](#) &M)
Check whether the matrix is upper triangular.
- void [bm_resize](#) ([bit_matrix_t](#) &M, std::size_t num_rows, std::size_t num_columns)
Resize a bit matrix.
- void [bm_resize](#) ([bit_matrix_t](#) &M, std::size_t num_rows)
Resize a bit matrix and make it a square matrix.
- void [bm_clear](#) ([bit_matrix_t](#) &M)
Clear bit matrix.
- void [bm_identity](#) ([bit_matrix_t](#) &M)
Set the matrix to the identity matrix.
- void [bm_random](#) ([bit_matrix_t](#) &M)
Sample a random bit matrix.
- void [bm_swap_rows](#) ([bit_matrix_t](#) &M, std::size_t i, std::size_t j)
Swap two rows.
- void [bm_add_rows](#) ([bit_matrix_t](#) &M, std::size_t i, std::size_t j)
Add two rows.
- bool [bm_solve](#) ([bit_matrix_t](#) &A, [bit_vector_t](#) &b)
Solve a linear system.
- bool [bm_solve_upper_triangular](#) ([bit_matrix_t](#) &A, [bit_vector_t](#) &b)
Solve a linear system in upper triangular form.
- bool [bm_invert](#) ([bit_matrix_t](#) &M, [bit_matrix_t](#) &N)
Invert a bit matrix.
- void [bm_multiply](#) (const [bit_matrix_t](#) &M, const [bit_vector_t](#) &x, [bit_vector_t](#) &y)
Multiply a bit matrix and a bit vector.
- void [bm_transpose](#) (const [bit_matrix_t](#) &M, [bit_matrix_t](#) &N)
Transpose.

Types and functions related to bit vectors

- typedef char [bit_t](#)
Bit.
- typedef std::vector< [bit_t](#) > [bit_vector_t](#)
Bit vector.
- typedef std::pair< [bit_vector_t](#), double > [point_value_t](#)

- Type to represent point value pairs.*

 - [bit_t bit_flip](#) ([bit_t](#) b)

Flip bit.
- void [bv_display](#) (const [bit_vector_t](#) &v, std::ostream &stream)

Display bit vector.
- bool [bv_is_valid](#) (const [bit_vector_t](#) &x)

Check whether the bit vector is valid.
- bool [bv_is_zero](#) (const [bit_vector_t](#) &x)

Check whether the bit vector is zero.
- int [bv_hamming_weight](#) (const [bit_vector_t](#) &x)

Hamming weight.
- int [bv_hamming_distance](#) (const [bit_vector_t](#) &x, const [bit_vector_t](#) &y)

Hamming distance between two bit vectors.
- [bit_t bv_dot_product](#) (const [bit_vector_t](#) &x, const [bit_vector_t](#) &y)

Dot product.
- void [bv_clear](#) ([bit_vector_t](#) &x)

Clear bit vector.
- void [bv_flip](#) ([bit_vector_t](#) &x, std::size_t i)

Flip a single bit.
- void [bv_flip](#) ([bit_vector_t](#) &x, const [bit_vector_t](#) &mask)

Flip many bits.
- void [bv_random](#) ([bit_vector_t](#) &x)

Sample a random bit vector.
- void [bv_random](#) ([bit_vector_t](#) &x, int k)

Sample a random bit vector with given Hamming weight.
- void [bv_add](#) (const [bit_vector_t](#) &src, [bit_vector_t](#) &dest)

Add two bit vectors.
- void [bv_add](#) (const [bit_vector_t](#) &x, const [bit_vector_t](#) &y, [bit_vector_t](#) &dest)

Add two bit vectors.

Types and functions related to permutations

- typedef std::vector< std::size_t > [permutation_t](#)

Permutation type.
- bool [perm_is_valid](#) (const [permutation_t](#) &permutation)

Check that a vector represents a permutation.
- void [perm_random](#) ([permutation_t](#) &s)

Sample a random permutation.

Types and functions related to sparse bit matrices

- typedef std::vector< [sparse_bit_vector_t](#) > [sparse_bit_matrix_t](#)

Sparse bit matrix.
- void [sbm_display](#) (const [sparse_bit_matrix_t](#) &sbm, std::ostream &stream)

Display sparse bit matrix.
- void [bm_to_sbm](#) (const [bit_matrix_t](#) &bm, [sparse_bit_matrix_t](#) &sbm)

Convert a bit matrix to a sparse bit matrix.
- void [sbm_multiply](#) (const [sparse_bit_matrix_t](#) &M, const [bit_vector_t](#) &x, [bit_vector_t](#) &y)

Multiply a sparse bit matrix and a bit vector.

Types and functions related to sparse bit vectors

- `typedef std::vector< std::size_t > sparse_bit_vector_t`
Sparse bit vector.
- `void bv_flip (bit_vector_t &x, const sparse_bit_vector_t &sbv)`
Flip many bits.
- `void sbv_display (const sparse_bit_vector_t &v, std::ostream &stream)`
Display sparse bit vector.
- `void bv_to_sbv (const bit_vector_t &bv, sparse_bit_vector_t &sbv)`
Convert a bit vector to a sparse bit vector.

4.1.1 Detailed Description

top-level HNCO namespace

4.1.2 Typedef Documentation

4.1.2.1 bit_t

```
typedef char bit_t
```

Bit.

A single bit is represented by a char and the values 0 for false and 1 for true.

Definition at line 52 of file bit-vector.hh.

4.1.2.2 sparse_bit_matrix_t

```
typedef std::vector<sparse_bit_vector_t> sparse_bit_matrix_t
```

Sparse bit matrix.

A sparse bit matrix is represented as an array of sparse bit vectors. It knows its number of row, not its number of columns.

Definition at line 45 of file sparse-bit-matrix.hh.

4.1.2.3 sparse_bit_vector_t

```
typedef std::vector<std::size_t> sparse_bit_vector_t
```

Sparse bit vector.

A sparse bit vector is represented as an array containing the indices of its non-zero components. The indices must be sorted in ascending order.

A sparse bit vector does not know the dimension of the space it belongs to.

Definition at line 47 of file sparse-bit-vector.hh.

4.1.3 Function Documentation

4.1.3.1 bm_add_rows()

```
void bm_add_rows (
    bit_matrix_t & M,
    std::size_t i,
    std::size_t j )
```

Add two rows.

Row i is added to row j.

Definition at line 94 of file bit-matrix.cc.

4.1.3.2 bm_identity()

```
void bm_identity (
    bit_matrix_t & M )
```

Set the matrix to the identity matrix.

Precondition

bm_is_square(M)

Definition at line 29 of file bit-matrix.cc.

4.1.3.3 bm_invert()

```
bool bm_invert (
    bit_matrix_t & M,
    bit_matrix_t & N )
```

Invert a bit matrix.

Parameters

M	input matrix
N	inverse matrix

Precondition

`bm_is_square(M)`
`bm_is_square(N)`

Returns

true if M is invertible

Warning

M is modified by the function. Provided that M is invertible, after returning from the function, M is the identity matrix and N is the computed inverse matrix.

Definition at line 153 of file bit-matrix.cc.

4.1.3.4 `bm_multiply()`

```
void bm_multiply (
    const bit_matrix_t & M,
    const bit_vector_t & x,
    bit_vector_t & y )
```

Multiply a bit matrix and a bit vector.

The result is $y = Mx$.

Definition at line 195 of file bit-matrix.cc.

4.1.3.5 `bm_solve()`

```
bool bm_solve (
    bit_matrix_t & A,
    bit_vector_t & b )
```

Solve a linear system.

Solve the linear equation $Ax = b$.

Parameters

A	Matrix
b	Right hand side

Precondition

```
bm_is_square(A)
bm_num_rows(A) == b.size()
```

Returns

true if the system has a unique solution

Warning

Both A and b are modified by the function. Provided that A is invertible, after returning from the function, A is the identity matrix and b is the unique solution to the linear equation.

Definition at line 103 of file bit-matrix.cc.

4.1.3.6 `bm_solve_upper_triangular()`

```
bool bm_solve_upper_triangular (
    bit_matrix_t & A,
    bit_vector_t & b )
```

Solve a linear system in upper triangular form.

Solve the linear equation $Ax = b$.

Parameters

A	Upper triangular matrix
b	Right hand side

Precondition

```
bm_is_square(A)
bm_num_rows(A) == b.size()
bm_is_upper_triangular(A)
```

Returns

true if the system has a unique solution

Warning

Both A and b are modified by the function. Provided that A is invertible, after returning from the function, A is the identity matrix and b is the unique solution to the linear equation.

Definition at line 134 of file bit-matrix.cc.

4.1.3.7 sbm_multiply()

```
void hnco::sbm_multiply (
    const sparse_bit_matrix_t & M,
    const bit_vector_t & x,
    bit_vector_t & y ) [inline]
```

Multiply a sparse bit matrix and a bit vector.

The result is $y = Mx$.

Definition at line 68 of file sparse-bit-matrix.hh.

4.2 hnco::algorithm Namespace Reference

Algorithms.

Namespaces

- [bm_pbil](#)
Boltzmann machine PBIL.
- [hea](#)
Herding evolutionary algorithm.

Classes

- class [Algorithm](#)
Abstract search algorithm.
- class [BiasedCrossover](#)
Biased crossover.
- class [CompactGa](#)
Compact genetic algorithm.
- class [CompleteSearch](#)
Complete search.
- class [Crossover](#)
Crossover.
- class [GeneticAlgorithm](#)
Genetic algorithm.
- class [IterativeAlgorithm](#)
Iterative search.

- class [Mmas](#)
Max-min ant system.
- class [MuCommaLambdaEa](#)
(mu, lambda) EA.
- class [MuPlusLambdaEa](#)
(mu+lambda) EA.
- class [NpsPbil](#)
Population-based incremental learning with negative and positive selection.
- class [OnePlusLambdaCommaLambdaGa](#)
(1+(lambda, lambda)) genetic algorithm.
- class [OnePlusOneEa](#)
(1+1) EA.
- class [Pbil](#)
Population-based incremental learning.
- class [Population](#)
Population.
- class [PvAlgorithm](#)
Probability vector algorithm.
- class [RandomLocalSearch](#)
Random local search.
- class [RandomSearch](#)
Random search.
- class [Restart](#)
Restart.
- class [SimulatedAnnealing](#)
Simulated annealing.
- class [SteepestAscentHillClimbing](#)
Steepest ascent hill climbing.
- class [TournamentSelection](#)
Population with tournament selection.
- class [Umda](#)
Univariate marginal distribution algorithm.
- class [UniformCrossover](#)
Uniform crossover.

Functions

- template<class T >
bool [matrix_is_symmetric](#) (const std::vector< std::vector< T > > &A)
Check for symmetric matrix.
- template<class T >
bool [matrix_has_diagonal](#) (const std::vector< std::vector< T > > &A, T x)
Check for diagonal elements.
- template<class T >
bool [matrix_has_range](#) (const std::vector< std::vector< T > > &A, T inf, T sup)
Check for element range.
- template<class T >
bool [matrix_has_dominant_diagonal](#) (const std::vector< std::vector< T > > &A)
Check for element range.
- template<class T >
T [square](#) (T x)
Generic square function.
- double [logistic](#) (double x)
Logistic function (sigmoid)

Type and functions related to probability vectors

- typedef std::vector< double > [pv_t](#)
Probability vector type.
- double [pv_entropy](#) (const [pv_t](#) &pv)
Entropy of a probability vector.
- void [pv_sample](#) (const [pv_t](#) &pv, [bit_vector_t](#) &x)
Sample a bit vector.
- void [pv_uniform](#) ([pv_t](#) &pv)
Probability vector of the uniform distribution.
- void [pv_init](#) ([pv_t](#) &pv)
Initialize.
- void [pv_add](#) ([pv_t](#) &pv, const [bit_vector_t](#) &x)
Accumulate a bit vector.
- void [pv_add](#) ([pv_t](#) &pv, const [bit_vector_t](#) &x, double weight)
Accumulate a bit vector.
- void [pv_average](#) ([pv_t](#) &pv, int count)
Average.
- void [pv_update](#) ([pv_t](#) &pv, double rate, const [bit_vector_t](#) &x)
Update a probability vector toward a bit vector.
- void [pv_update](#) ([pv_t](#) &pv, double rate, const std::vector< double > &x)
Update a probability vector toward a probability vector.
- void [pv_update](#) ([pv_t](#) &pv, double rate, const std::vector< double > &x, const std::vector< double > &y)
Update a probability vector toward a probability vector and away from another one.
- void [pv_bound](#) ([pv_t](#) &pv, double lower_bound, double upper_bound)
Bound the components of a probability vector.

4.2.1 Detailed Description

Algorithms.

4.3 hnco::algorithm::bm_pbil Namespace Reference

Boltzmann machine PBIL.

Classes

- class [BmPbil](#)
Boltzmann machine PBIL.
- class [Model](#)
Model of a Boltzmann machine.
- class [ModelParameters](#)
Parameters of a Boltzmann machine.

4.3.1 Detailed Description

Boltzmann machine PBIL.

4.4 hnco::algorithm::hea Namespace Reference

Herding evolutionary algorithm.

Classes

- class [BinaryHerding](#)
Herding with binary variables.
- struct [BinaryMoment](#)
Moment for binary variables.
- class [Hea](#)
Herding evolutionary algorithm.
- class [SpinHerding](#)
Herding with spin variables.
- struct [SpinMoment](#)
Moment for spin variables.

4.4.1 Detailed Description

Herding evolutionary algorithm.

4.5 hnco::exception Namespace Reference

Exceptions.

Classes

- class [Error](#)
Error.
- class [Exception](#)
Basic exception.
- class [LastEvaluation](#)
Last evaluation.
- class [LocalMaximum](#)
Local maximum.
- class [MaximumReached](#)
Maximum reached.
- class [PointValueException](#)
Point-value exception.
- class [TargetReached](#)
target reached

4.5.1 Detailed Description

Exceptions.

4.6 hnco::function Namespace Reference

Functions to be maximized.

Classes

- class [AdditiveGaussianNoise](#)
Additive Gaussian Noise.
- class [Cache](#)
Cache.
- class [CallCounter](#)
Call counter.
- class [DeceptiveJump](#)
Deceptive jump.
- class [EqualProducts](#)
Equal products.
- class [Factorization](#)
Factorization.
- class [FourPeaks](#)
Four Peaks.
- class [Function](#)
Function.
- class [FunctionController](#)
Function controller.
- class [FunctionDecorator](#)
Function decorator.
- class [FunctionMapComposition](#)
Composition of a function and a map.
- class [FunctionModifier](#)
Function modifier.
- class [FunctionPlugin](#)
Function plugin.
- class [Hiff](#)
Hierarchical if and only if.
- class [Jump](#)
Jump.
- class [Labs](#)
Low autocorrelation binary sequences.
- class [LeadingOnes](#)
Leading ones.
- class [LinearFunction](#)
Linear function.
- class [LongPath](#)
Long path.
- class [MaxSat](#)
MAX-SAT.
- class [Needle](#)
Needle in a haystack.
- class [Negation](#)

- *Negation.*
- class [NkLandscape](#)
NK landscape.
- class [OnBudgetFunction](#)
CallCounter with a limited number of evaluations.
- class [OneMax](#)
OneMax.
- class [Plateau](#)
Plateau.
- class [PriorNoise](#)
Prior noise.
- class [ProgressTracker](#)
ProgressTracker.
- class [Qubo](#)
Quadratic unconstrained binary optimization.
- class [Ridge](#)
Ridge.
- class [SinusSummationCancellation](#)
Summation cancellation with sinus.
- class [SixPeaks](#)
Six Peaks.
- class [StopOnMaximum](#)
Stop on maximum.
- class [StopOnTarget](#)
Stop on target.
- class [SummationCancellation](#)
Summation cancellation.
- class [Trap](#)
Trap.
- class [WalshExpansion](#)
Walsh expansion.
- class [WalshExpansion1](#)
Walsh expansion of degree 1.
- class [WalshExpansion2](#)
Walsh expansion of degree 2.

Functions

- `std::ostream & operator<< (std::ostream &stream, const ProgressTracker::Event &event)`
Insert formatted output.

4.6.1 Detailed Description

Functions to be maximized.

4.7 hngo::neighborhood Namespace Reference

Neighborhoods for local search.

Classes

- class [BernoulliProcess](#)
Bernoulli process.
- class [HammingBall](#)
Hamming ball.
- class [HammingBallIterator](#)
Hamming ball neighborhood iterator.
- class [HammingSphere](#)
Hamming sphere.
- class [MultiBitFlip](#)
Multi bit flip.
- class [Neighborhood](#)
Neighborhood.
- class [NeighborhoodIterator](#)
Neighborhood iterator.
- class [SingleBitFlip](#)
One bit neighborhood.
- class [SingleBitFlipIterator](#)
Single bit flip neighborhood iterator.

4.7.1 Detailed Description

Neighborhoods for local search.

There are two unrelated kinds of neighborhoods, those for random local search and those for exhaustive local search.

4.8 `hnco::random` Namespace Reference

Pseudo random numbers.

Classes

- struct [Random](#)
Random numbers.

4.8.1 Detailed Description

Pseudo random numbers.

Chapter 5


Class Documentation

5.1 AdditiveGaussianNoise Class Reference

Additive Gaussian Noise.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for AdditiveGaussianNoise:



Public Member Functions

- [AdditiveGaussianNoise](#) ([Function](#) *function, double stddev)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &)

Evaluate a bit vector.

Information about the function

- `size_t` [get_bv_size](#) ()
Get bit vector size.
- `double` [get_maximum](#) ()
Get the global maximum.
- `bool` [has_known_maximum](#) ()
Check for a known maximum.

Private Attributes

- `std::normal_distribution< double >` [_dist](#)
Normal distribution.

Additional Inherited Members

5.1.1 Detailed Description

Additive Gaussian Noise.

Definition at line 166 of file `function-modifier.hh`.

5.1.2 Member Function Documentation

5.1.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Exceptions

<i>Error</i>	
--------------	--

Reimplemented from [Function](#).

Definition at line 188 of file `function-modifier.hh`.

5.1.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

false

Reimplemented from [Function](#).

Definition at line 192 of file function-modifier.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-modifier.hh
- lib/hnco/functions/decorators/function-modifier.cc

5.2 AffineMap Class Reference

Affine map.

```
#include <hnco/map.hh>
```

Inheritance diagram for AffineMap:

**Public Member Functions**

- void [random](#) (int n, int m)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.
- size_t [get_input_size](#) ()
Get input size.
- size_t [get_output_size](#) ()
Get output size.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_matrix_t_bm](#)
Bit matrix.
- [bit_vector_t_bv](#)
Translation vector.

Friends

- class **boost::serialization::access**

5.2.1 Detailed Description

Affine map.

An affine map f from Z_2^m to Z_2^n is defined by $f(x) = Ax + b$, where A is an $n \times m$ bit matrix and b is an n -dimensional bit vector.

Warning

The class does not reimplement the member function `is_surjective` hence a linear map is always considered not surjective.

Definition at line 258 of file `map.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/map.hh`
- `lib/hnco/map.cc`

5.3 Algorithm Class Reference

Abstract search algorithm.

```
#include <hnco/algorithms/algorithm.hh>
```

Inheritance diagram for Algorithm:



Public Member Functions

- `Algorithm ()`
Constructor.
- `Algorithm (int n)`
Constructor.
- `virtual ~Algorithm ()`
Destructor.
- `virtual void init ()`
Initialization.
- `virtual void maximize ()=0`
Maximize.
- `virtual const point_value_t & get_solution ()`
Solution.

Setters

- `virtual void set_function (function::Function *function)`
Set function.
- `virtual void set_functions (const std::vector< function::Function *> functions)`
Set functions.
- `void set_stream (std::ostream *x)`
Output stream.

Protected Member Functions

- void `random_solution` ()
Random solution.
- void `set_solution` (const `bit_vector_t` &x, double value)
Set solution.
- void `set_solution` (const `bit_vector_t` &x)
Set solution.
- void `update_solution` (const `bit_vector_t` &x, double value)
Update solution (strict)
- void `update_solution` (const `point_value_t` &pv)
Update solution (strict)
- void `update_solution` (const `bit_vector_t` &x)
Update solution (strict)

Protected Attributes

- `function::Function * _function`
Function.
- `std::vector< function::Function * > _functions`
Functions.
- `point_value_t _solution`
Solution.

Parameters

- `std::ostream * _stream` = &std::cout
Output stream.

5.3.1 Detailed Description

Abstract search algorithm.

All algorithms maximize some given function, sometimes called a fitness function or an objective function.

Definition at line 38 of file `algorithm.hh`.

5.3.2 Member Data Documentation

5.3.2.1 `_functions`

```
std::vector<function::Function *> _functions [protected]
```

Functions.

Each thread has its own function.

Definition at line 49 of file `algorithm.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/algorithm.hh`
- `lib/hnco/algorithms/algorithm.cc`

5.4 BernoulliProcess Class Reference

Bernoulli process.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for BernoulliProcess:



Public Member Functions

- [BernoulliProcess](#) (int n)
Constructor.
- [BernoulliProcess](#) (int n, double p)
Constructor.
- void [set_probability](#) (double p)
Set probability.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.
- void [bernoulli_process](#) ()
Bernoulli process.

Private Attributes

- std::bernoulli_distribution [_bernoulli_dist](#)
Bernoulli distribution (biased coin)
- std::binomial_distribution< int > [_binomial_dist](#)
Binomial distribution.
- bool [_reservoir_sampling](#) = false
Reservoir sampling.

Parameters

- bool `_allow_stay` = false
Allow stay.
- void `set_allow_stay` (bool x)
Set the flag `_allow_stay`.

Additional Inherited Members

5.4.1 Detailed Description

Bernoulli process.

Each component of the origin bit vector is flipped with some fixed probability. If no component has been flipped at the end, the process is started all over again. Thus the number of flipped bits follows a pseudo binomial law.

Definition at line 220 of file neighborhood.hh.

5.4.2 Constructor & Destructor Documentation

5.4.2.1 BernoulliProcess() [1/2]

```
BernoulliProcess (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

The Bernoulli probability is set to 1 / n.

Definition at line 255 of file neighborhood.hh.

5.4.2.2 BernoulliProcess() [2/2]

```
BernoulliProcess (
    int n,
    double p ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
p	Bernoulli probability

Definition at line 265 of file neighborhood.hh.

5.4.3 Member Function Documentation

5.4.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 292 of file neighborhood.hh.

5.4.3.2 set_probability()

```
void set_probability (
    double p ) [inline]
```

Set probability.

Sets `_reservoir_sampling` to true if $E(X) < \sqrt{n}$, where X is a random variable with a binomial distribution $B(n, p)$, that is if $np < \sqrt{n}$ or $p < 1 / \sqrt{n}$.

Definition at line 276 of file neighborhood.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.5 BiasedCrossover Class Reference

Biased crossover.

```
#include <hnco/algorithms/ea/crossover.hh>
```

Inheritance diagram for BiasedCrossover:



Public Member Functions

- [BiasedCrossover](#) ()
Constructor.
- void [breed](#) (const [bit_vector_t](#) &parent1, const [bit_vector_t](#) &parent2, [bit_vector_t](#) &offspring)
Breed.
- void [set_bias](#) (double b)
Set bias.

Private Attributes

- std::bernoulli_distribution [_bernoulli_dist](#)
Bernoulli distribution.

5.5.1 Detailed Description

Biased crossover.

Definition at line 75 of file crossover.hh.

5.5.2 Member Function Documentation

5.5.2.1 breed()

```
void breed (
    const bit\_vector\_t & parent1,
    const bit\_vector\_t & parent2,
    bit\_vector\_t & offspring ) [virtual]
```

Breed.

Each offspring's bit is copied from second parent with a fixed probability (the crossover bias), from first parent otherwise.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implements [Crossover](#).

Definition at line 45 of file crossover.cc.

The documentation for this class was generated from the following files:

- lib/hnco/algorithms/ea/crossover.hh
- lib/hnco/algorithms/ea/crossover.cc

5.6 BinaryHerding Class Reference

Herding with binary variables.

```
#include <hnco/algorithms/hea/herding-binary.hh>
```

Public Types

- enum { [DYNAMICS_MINIMIZE_NORM](#), [DYNAMICS_MAXIMIZE_INNER_PRODUCT](#) }

Public Member Functions

- [BinaryHerding](#) (int n)
Constructor.
- void [init](#) ()
Initialization.
- void [sample](#) (const [BinaryMoment](#) &target, [bit_vector_t](#) &x)
Sample a bit vector.
- double [error](#) (const [BinaryMoment](#) &target)
Compute the error.
- double [delta](#) (const [BinaryMoment](#) &target)
Compute the norm of delta.

Setters

- void [set_randomize_bit_order](#) (bool x)
Randomize bit order.
- void [set_dynamics](#) (int x)
Set the dynamics.
- void [set_weight](#) (double x)
Set the weight of second order moments.

Protected Member Functions

- void `compute_delta` (const `BinaryMoment` &target)
Compute delta.
- void `sample_minimize_norm` (const `BinaryMoment` &target, `bit_vector_t` &x)
Sample a bit vector.
- void `sample_maximize_inner_product` (const `BinaryMoment` &target, `bit_vector_t` &x)
Sample a bit vector.

Protected Attributes

- `BinaryMoment _count`
Counter moment.
- `BinaryMoment _delta`
Delta moment.
- `permutation_t _permutation`
Permutation.
- `std::uniform_int_distribution< int > _choose_bit`
Choose bit.
- `int _time`
Time.

Parameters

- `bool _randomize_bit_order` = false
Randomize bit order.
- `int _dynamics` = `DYNAMICS_MINIMIZE_NORM`
Dynamics.
- `double _weight` = 1
Weight of second order moments.

5.6.1 Detailed Description

Herding with binary variables.

Definition at line 38 of file herding-binary.hh.

5.6.2 Member Enumeration Documentation

5.6.2.1 anonymous enum

anonymous enum

Enumerator

<code>DYNAMICS_MINIMIZE_NORM</code>	Dynamics defined as minimization of a norm.
<code>DYNAMICS_MAXIMIZE_INNER_PRODUCT</code>	Dynamics defined as maximization of an inner product.

Definition at line 83 of file herding-binary.hh.

The documentation for this class was generated from the following files:

- lib/hnco/algorithms/hea/herding-binary.hh
- lib/hnco/algorithms/hea/herding-binary.cc

5.7 BinaryMoment Struct Reference

Moment for binary variables.

```
#include <hnco/algorithms/hea/moment-binary.hh>
```

Public Member Functions

- [BinaryMoment](#) (int n)
Constructor.
- void [uniform](#) ()
Set the moment to that of the uniform distribution.
- void [init](#) ()
Initialize.
- void [add](#) (const [bit_vector_t](#) &x)
Accumulate a bit vector.
- void [average](#) (int count)
Compute average.
- void [update](#) (const [BinaryMoment](#) &p, double rate)
Update moment.
- void [bound](#) (double margin)
Bound moment.
- double [distance](#) (const [BinaryMoment](#) &p) const
Distance.
- double [norm_2](#) () const
Compute the norm 2.
- double [diameter](#) () const
Compute the diameter.
- size_t [size](#) () const
Size.

Public Attributes

- std::vector< std::vector< double > > [_moment](#)
Moment.
- double [_weight](#) = 1
Weight of second order moments.

5.7.1 Detailed Description

Moment for binary variables.

Definition at line 37 of file moment-binary.hh.

The documentation for this struct was generated from the following files:


- lib/hnco/algorithms/hea/moment-binary.hh
- lib/hnco/algorithms/hea/moment-binary.cc

5.8 BmPbil Class Reference

Boltzmann machine PBIL.

```
#include <hnco/algorithms/bm-pbil/bm-pbil.hh>
```

Inheritance diagram for BmPbil:



Public Types

- enum { LOG_NORM_INFINITE, LOG_NORM_L1, **LAST_LOG** }
- enum { **SAMPLING_ASYNCHRONOUS**, **SAMPLING_ASYNCHRONOUS_FULL_SCAN**, **SAMPLING_SYNC_NCHRONOUS** }
- enum { **RESET_NO_RESET**, **RESET_ITERATION**, **RESET_BIT_VECTOR** }
- typedef std::bitset< LAST_LOG > **log_flags_t**

Public Member Functions

- **BmPbil** (int n, int population_size)
Constructor.
- void **init** ()
Initialization.

Private Member Functions

- void [iterate](#) ()
Single iteration.
- void [log](#) ()
Log.
- void [sample](#) (bit_vector_t &x)
Sample a bit vector.
- void [sample_asynchronous](#) ()
Asynchronous sampling.
- void [sample_asynchronous_full_scan](#) ()
Asynchronous sampling with full scan.
- void [sample_synchronous](#) ()
Synchronous sampling.

Private Attributes

- log_flags_t [_log_flags](#)
Log flags.
- Population [_population](#)
Population.
- Model [_model](#)
Model.
- ModelParameters [_parameters_all](#)
Parameters averaged over all individuals.
- ModelParameters [_parameters_best](#)
Parameters averaged over selected individuals.
- ModelParameters [_parameters_worst](#)
Parameters averaged over negatively selected individuals.
- std::uniform_int_distribution< size_t > [_choose_bit](#)
Uniform distribution on bit_vector_t components.
- permutation_t [_permutation](#)
Permutation.

Parameters

- int [_selection_size](#) = 1
Selection size (number of selected individuals in the population)
- double [_rate](#) = 1e-3
Learning rate.
- int [_num_gs_steps](#) = 100
Number of gibbs sampler steps.
- int [_num_gs_cycles](#) = 1
Number of gibbs sampler cycles.
- bool [_negative_positive_selection](#) = false
Negative and positive selection.
- int [_sampling](#) = SAMPLING_ASYNCHRONOUS
Sampling mode.
- int [_mc_reset_strategy](#) = RESET_NO_RESET

- MC reset strategy.*
 - void `set_selection_size` (int x)
Set the selection size.
 - void `set_rate` (double x)
Set the learning rate.
 - void `set_num_gs_steps` (int x)
Set the number of gibbs sampler steps.
 - void `set_num_gs_cycles` (int x)
Set the number of gibbs sampler cycles.
 - void `set_negative_positive_selection` (bool x)
Set negative and positive selection.
 - void `set_sampling` (int x)
Set the sampling mode.
 - void `set_mc_reset_strategy` (int x)
Set the MC reset strategy.
 - void `set_log_flags` (const log_flags_t &lf)
Set log flags.

Additional Inherited Members

5.8.1 Detailed Description

Boltzmann machine PBIL.

The BM model is slightly different from the one given in the reference below. More precisely, 0/1 variables are mapped to -1/+1 variables as in Walsh analysis.

Reference:

Arnaud Berny. 2002. Boltzmann machine for population-based incremental learning. In ECAI 2002. IOS Press, Lyon.

Definition at line 51 of file bm-pbil.hh.

5.8.2 Member Enumeration Documentation

5.8.2.1 anonymous enum

anonymous enum

Enumerator

LOG_NORM_INFINITE	Log infinite norm of the model parameters.
LOG_NORM_L1	Log 1-norm of the model parameters.

Definition at line 56 of file bm-pbil.hh.

5.8.2.2 anonymous enum

anonymous enum

Enumerator

SAMPLING_ASYNCHRONOUS	Asynchronous sampling. A single component of the internal state is randomly selected then updated by Gibbs sampling. This step is repeated <code>_num_gs_steps</code> times.
SAMPLING_ASYNCHRONOUS_FULL_SCAN	Asynchronous sampling with full scan. To sample a new bit vector, a random permutation is sampled and all components of the internal state are updated by Gibbs sampling in the order defined by the permutation.
SAMPLING_SYNCHRONOUS	Synchronous sampling. The full internal state is updated in one step from the probability vector made of the very marginal probabilities used in Gibbs sampling.

Definition at line 66 of file bm-pbil.hh.

5.8.2.3 anonymous enum

anonymous enum

Enumerator

RESET_NO_RESET	No reset.
RESET_ITERATION	Reset MC at the beginning of each iteration.
RESET_BIT_VECTOR	Reset MC before sampling each bit vector.

Definition at line 93 of file bm-pbil.hh.

5.8.3 Member Function Documentation

5.8.3.1 set_selection_size()

```
void set_selection_size (
    int x ) [inline]
```

Set the selection size.

The selection size is the number of selected individuals in the population.

Definition at line 210 of file bm-pbil.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/bm-pbil/bm-pbil.hh
- lib/hnco/algorithms/bm-pbil/bm-pbil.cc

5.9 Cache Class Reference

[Cache](#).

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for Cache:



Public Member Functions

- [Cache](#) ([Function](#) *function)
Constructor.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- `std::unordered_map< std::vector< bool >, double > _cache`
Cache.
- `std::vector< bool > _key`
Key.
- `int _num_evaluations`
Evaluation counter.
- `int _num_lookups`
Lookup counter.

Additional Inherited Members

5.9.1 Detailed Description

`Cache`.

This is a naive approach, in particular with respect to time complexity. Moreover, there is no control on the size of the database.

There is no default hash function for `std::vector<char>` hence the need to first copy a `bit_vector_t` into a `std::vector<bool>`, for which such a function exists, before inserting it or checking its existence in the map.

Definition at line 355 of file `function-controller.hh`.

5.9.2 Constructor & Destructor Documentation

5.9.2.1 `Cache()`

```
Cache (
    Function * function ) [inline]
```

Constructor.

Parameters

<code>function</code>	Decorated function
-----------------------	--------------------

Definition at line 374 of file `function-controller.hh`.

5.9.3 Member Function Documentation

5.9.3.1 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented from [FunctionController](#).

Definition at line 383 of file function-controller.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.10 CallCounter Class Reference

Call counter.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for CallCounter:



Public Member Functions

- [CallCounter](#) ([Function](#) *function)

Constructor.

- int [get_num_calls](#) ()

Get the number of calls.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)

Evaluate a bit vector.

- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↔
_bits)

Incremental evaluation.

- void [update](#) (const [bit_vector_t](#) &x, double value)

Update after a safe evaluation.

Protected Attributes

- int [_num_calls](#)

Number of calls.

5.10.1 Detailed Description

Call counter.

Definition at line 170 of file function-controller.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.11 CompactGa Class Reference

Compact genetic algorithm.

```
#include <hnco/algorithms/pv/compact-ga.hh>
```

Inheritance diagram for CompactGa:



Public Member Functions

- [CompactGa](#) (int n)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_rate](#) (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- std::vector< [bit_vector_t](#) > [_candidates](#)
Candidates.

Parameters

- double [_rate](#) = 1e-3
Learning rate.

Additional Inherited Members

5.11.1 Detailed Description

Compact genetic algorithm.

Reference:

Georges R. Harik, Fernando G. Lobo, and David E. Goldberg. 1999. The Compact Genetic Algorithm. IEEE Trans. on Evolutionary Computation 3, 4 (November 1999), 287–297.

Definition at line 43 of file compact-ga.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/pv/compact-ga.hh
- lib/hnco/algorithms/pv/compact-ga.cc

5.12 CompleteSearch Class Reference

Complete search.

```
#include <hnco/algorithms/complete-search.hh>
```

Inheritance diagram for CompleteSearch:



Public Member Functions

- [CompleteSearch](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.

Additional Inherited Members

5.12.1 Detailed Description

Complete search.

Definition at line 34 of file complete-search.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/complete-search.hh
- lib/hnco/algorithms/complete-search.cc

5.13 Crossover Class Reference

[Crossover](#).

```
#include <hnco/algorithms/ea/crossover.hh>
```

Inheritance diagram for Crossover:



Public Member Functions

- virtual [~Crossover](#) ()
Destructor.
- virtual void [breed](#) (const [bit_vector_t](#) &parent1, const [bit_vector_t](#) &parent2, [bit_vector_t](#) &offspring)=0
Breed.

5.13.1 Detailed Description

[Crossover](#).

Definition at line 35 of file crossover.hh.

5.13.2 Member Function Documentation

5.13.2.1 breed()

```
virtual void breed (
    const bit\_vector\_t & parent1,
    const bit\_vector\_t & parent2,
    bit\_vector\_t & offspring ) [pure virtual]
```

Breed.

The offspring is the crossover of two parents.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implemented in [BiasedCrossover](#), and [UniformCrossover](#).

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/ea/crossover.hh`

5.14 DeceptiveJump Class Reference

Deceptive jump.

```
#include <hnco/functions/jump.hh>
```

Inheritance diagram for DeceptiveJump:



Public Member Functions

- [DeceptiveJump](#) (int bv_size, int gap)
Constructor.
- [size_t get_bv_size](#) ()
Get bit vector size.
- [double eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- [bool has_known_maximum](#) ()
Check for a known maximum.
- [double get_maximum](#) ()
Get the global maximum.

Private Attributes

- [size_t _bv_size](#)
Bit vector size.
- [int _gap](#)
Gap.

5.14.1 Detailed Description

Deceptive jump.

This is a jump function with a deceptive gap as defined in "Analyzing evolutionary algorithms" by Thomas Jansen, where it is called Jump_k. Algorithms in the neighborhood of the maximizer (which is the all one bit vector) are taken away from it.

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 84 of file jump.hh.

5.14.2 Member Function Documentation

5.14.2.1 [get_maximum\(\)](#)

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

[_bv_size](#) + [_gap](#)

Reimplemented from [Function](#).

Definition at line 110 of file jump.hh.

5.14.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 106 of file jump.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/jump.hh
- lib/hnco/functions/jump.cc

5.15 EqualProducts Class Reference

Equal products.

```
#include <hnco/functions/equal-products.hh>
```

Inheritance diagram for EqualProducts:



Public Member Functions

- [EqualProducts](#) ()
Constructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- void [random](#) (int n, double upper_bound)
Random instance.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Member Functions

- `template<class Archive >`
`void serialize (Archive &ar, const unsigned int version)`
Serialize.

Private Attributes

- `std::vector< double > _numbers`
Numbers.

Friends

- class **`boost::serialization::access`**

5.15.1 Detailed Description

Equal products.

Partition a finite set of positive numbers into two subsets such that the product of numbers in the first subset is the closest to the product of numbers in the second subset. This is equivalent to the partition problem applied to the logarithms of the given numbers.

The function computes the negation of the distance between the product of numbers corresponding to ones in the bit vector and the product of those corresponding to zeros. The negation is a consequence of the fact that algorithms in HNCO maximize rather than minimize a function.

Reference:

S. Baluja and S. Davies. 1997. Using optimal dependency-trees for combinatorial optimization: learning the structure of the search space. Technical Report CMU- CS-97-107. Carnegie-Mellon University.

Definition at line 61 of file equal-products.hh.

5.15.2 Member Function Documentation

5.15.2.1 `random()`

```
void random (
    int n,
    double upper_bound )
```

Random instance.

Parameters

<i>n</i>	Size of bit vector
<i>upper_bound</i>	Upper bound of numbers

Definition at line 33 of file equal-products.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/equal-products.hh
- lib/hnco/functions/equal-products.cc

5.16 Error Class Reference

[Error](#).

```
#include <hnco/exception.hh>
```

Inheritance diagram for Error:



Public Member Functions

- [Error](#) ()
Constructor.
- [Error](#) (const std::string &s)
Constructor.
- virtual [~Error](#) ()
Destructor.
- virtual const char * [what](#) () const
Get message.

Protected Attributes

- std::string [_what](#)
Message.

5.16.1 Detailed Description

[Error](#).

Definition at line 83 of file exception.hh.

The documentation for this class was generated from the following file:

- lib/hnco/exception.hh

5.17 ProgressTracker::Event Struct Reference

[Event](#).

```
#include <hnco/functions/decorators/function-controller.hh>
```

Public Attributes

- int [time](#)
Time.
- double [value](#)
Value.

5.17.1 Detailed Description

[Event](#).

Definition at line 218 of file function-controller.hh.

The documentation for this struct was generated from the following file:


- lib/hnco/functions/decorators/function-controller.hh

5.18 Exception Class Reference

Basic exception.

```
#include <hnco/exception.hh>
```

Inheritance diagram for Exception:



5.18.1 Detailed Description

Basic exception.

Definition at line 35 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.19 Factorization Class Reference

[Factorization](#).

```
#include <hnco/functions/factorization.hh>
```

Inheritance diagram for Factorization:



Public Member Functions

- [Factorization](#) (std::string path)
Constructor.
- [~Factorization](#) ()
Destructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- void [display](#) (std::ostream &stream)
Display.
- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- void [convert](#) (const [bit_vector_t](#) &x)
Convert a bit vector into two numbers.

Private Attributes

- `mpz_t _number`
Number to factorize.
- `mpz_t _first_factor`
First factor.
- `mpz_t _second_factor`
Second factor.
- `mpz_t _product`
Product.
- `std::string _first_factor_string`
First factor in binary form.
- `std::string _second_factor_string`
Secon factor in binary form.
- `size_t _number_size`
Number size in bits.
- `size_t _first_factor_size`
First factor size in bits.
- `size_t _second_factor_size`
Second factor size in bits.
- `size_t _bv_size`
Bit vector size.

5.19.1 Detailed Description

[Factorization.](#)

Reference:

Torbjörn Granlund and the GMP development team. 2012. GNU MP: The GNU Multiple Precision Arithmetic Library (5.0.5 ed.).

<http://gmplib.org/>.

Definition at line 28 of file factorization.hh.

5.19.2 Constructor & Destructor Documentation

5.19.2.1 Factorization()

```
Factorization (
    std::string path )
```

Constructor.

Parameters

<i>path</i>	Path to a file containing a number to factorize
-------------	---

Warning

The file is a text file which contains exactly one natural number written in base 10 without any space.

Definition at line 16 of file factorization.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/factorization.hh
- lib/hnco/functions/factorization.cc

5.20 FourPeaks Class Reference

Four Peaks.

```
#include <hnco/functions/four-peaks.hh>
```

Inheritance diagram for FourPeaks:



Public Member Functions

- [FourPeaks](#) (int bv_size, int threshold)
Constructor.
- [size_t get_bv_size](#) ()
Get bit vector size.
- [double eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- [bool has_known_maximum](#) ()
Check for a known maximum.
- [double get_maximum](#) ()
Get the global maximum.

Private Attributes

- `size_t _bv_size`
Bit vector size.
- `int _threshold`
Threshold.
- `int _maximum`
Maximum.

5.20.1 Detailed Description

Four Peaks.

It is defined by

$$f(x) = \max\{\text{head}(x, 1) + \text{tail}(x, 0)\} + R(x)$$

where:

- $\text{head}(x, 1)$ is the length of the longest prefix of x made of ones;
- $\text{tail}(x, 0)$ is the length of the longest suffix of x made of zeros;
- $R(x)$ is the reward;
- $R(x) = n$ if $(\text{head}(x, 1) > t \text{ and } \text{tail}(x, 0) > t)$;
- $R(x) = 0$ otherwise;
- the threshold t is a parameter of the function.

This function has four maxima, of which exactly two are global ones.

For example, if $n = 6$ and $t = 1$:

- $f(111111) = 6$ (local maximum)
- $f(111110) = 5$
- $f(111100) = 10$ (global maximum)

Reference:

S. Baluja and R. Caruana. 1995. Removing the genetics from the standard genetic algorithm. In Proceedings of the 12th Annual Conference on Machine Learning. 38–46.

Definition at line 60 of file four-peaks.hh.

5.20.2 Member Function Documentation

5.20.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$2 * _bv_size - _threshold - 1$

Reimplemented from [Function](#).

Definition at line 91 of file four-peaks.hh.

5.20.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 87 of file four-peaks.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/four-peaks.hh
- lib/hnco/functions/four-peaks.cc

5.21 Function Class Reference

[Function](#).

```
#include <hnco/functions/function.hh>
```

Inheritance diagram for Function:



Public Member Functions

- virtual `~Function()`
Destructor.

Information about the function

- virtual `size_t get_bv_size()`=0
Get bit vector size.
- virtual `double get_maximum()`
Get the global maximum.
- virtual `bool has_known_maximum()`
Check for a known maximum.
- virtual `bool provides_incremental_evaluation()`

Check whether the function provides incremental evaluation.

Evaluation

- virtual double `eval` (const `bit_vector_t` &)=0
Evaluate a bit vector.
- virtual double `incremental_eval` (const `bit_vector_t` &x, double value, const `hnco::sparse_bit_vector_t` &flipped_bits)
Incremental evaluation.
- virtual double `safe_eval` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update after a safe evaluation.

Display

- virtual void `display` (std::ostream &stream)
Display.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

5.21.1 Detailed Description

[Function.](#)

Definition at line 35 of file `function.hh`.

5.21.2 Member Function Documentation

5.21.2.1 `get_maximum()`

```
virtual double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Exceptions

Error	
-------	--

Reimplemented in [Plateau](#), [Ridge](#), [Hiff](#), [AdditiveGaussianNoise](#), [SixPeaks](#), [Needle](#), [FunctionMapComposition](#), [LeadingOnes](#), [DeceptiveJump](#), [FourPeaks](#), [SummationCancellation](#), [Trap](#), [LinearFunction](#), [Negation](#), [PriorNoise](#), [Jump](#), [OneMax](#), and [FunctionController](#).

Definition at line 51 of file `function.hh`.

5.21.2.2 incremental_eval()

```
virtual double incremental_eval (
    const bit\_vector\_t & x,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [inline], [virtual]
```

Incremental evaluation.

Exceptions

<i>Error</i>	
--------------	--

Reimplemented in [OnBudgetFunction](#), [ProgressTracker](#), [CallCounter](#), [StopOnTarget](#), [StopOnMaximum](#), [Negation](#), and [OneMax](#).

Definition at line 75 of file function.hh.

5.21.2.3 provides_incremental_evaluation()

```
virtual bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented in [Cache](#), [Negation](#), [PriorNoise](#), [OneMax](#), and [FunctionController](#).

Definition at line 59 of file function.hh.

5.21.2.4 safe_eval()

```
virtual double safe_eval (
    const bit\_vector\_t & x ) [inline], [virtual]
```

Safely evaluate a bit vector.

Must be thread-safe, that is must avoid throwing exceptions and updating global states (e.g. maximum) in function decorators.

Reimplemented in [FunctionController](#).

Definition at line 85 of file function.hh.

The documentation for this class was generated from the following file:


- lib/hnco/functions/function.hh

5.22 FunctionController Class Reference

Function controller.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for FunctionController:



Public Member Functions

- **FunctionController** (**Function** *function)
Constructor.

Information about the function

- **size_t** **get_bv_size** ()
Get bit vector size.
- **double** **get_maximum** ()
Get the global maximum.
- **bool** **has_known_maximum** ()
Check for a known maximum.
- **bool** **provides_incremental_evaluation** ()
Check whether the function provides incremental evaluation.

Evaluation

- **double** **safe_eval** (const **bit_vector_t** &x)
Safely evaluate a bit vector.

Display

- **void** **display** (std::ostream &stream)
Display.
- **void** **describe** (const **bit_vector_t** &x, std::ostream &stream)
Describe a bit vector.

Additional Inherited Members

5.22.1 Detailed Description

[Function](#) controller.

Definition at line 38 of file function-controller.hh.

5.22.2 Member Function Documentation

5.22.2.1 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true if the decorated function does

Reimplemented from [Function](#).

Reimplemented in [Cache](#).

Definition at line 63 of file function-controller.hh.

The documentation for this class was generated from the following file:


- lib/hnco/functions/decorators/function-controller.hh

5.23 FunctionDecorator Class Reference

[Function](#) decorator.

```
#include <hnco/functions/decorators/function-decorator.hh>
```

Inheritance diagram for FunctionDecorator:



Public Member Functions

- [FunctionDecorator](#) ([Function](#) *function)
Constructor.

Protected Attributes

- [Function](#) * [_function](#)
Decorated function.

5.23.1 Detailed Description

[Function](#) decorator.

Definition at line 37 of file `function-decorator.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/functions/decorators/function-decorator.hh`

5.24 FunctionMapComposition Class Reference

Composition of a function and a map.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for FunctionMapComposition:



Public Member Functions

- [FunctionMapComposition](#) ([Function](#) *function, [Map](#) *map)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Information about the function

- size_t [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.

Private Attributes

- [Map](#) * [_map](#)
Map.
- [bit_vector_t](#) [_bv](#)
_bv

Additional Inherited Members

5.24.1 Detailed Description

Composition of a function and a map.

Definition at line 106 of file function-modifier.hh.

5.24.2 Constructor & Destructor Documentation

5.24.2.1 FunctionMapComposition()

```
FunctionMapComposition (
    Function * function,
    Map * map ) [inline]
```

Constructor.

Precondition

map->get_output_size() == function->[get_bv_size](#)()

Exceptions

Error

Definition at line 121 of file function-modifier.hh.

5.24.3 Member Function Documentation

5.24.3.1 get_maximum()

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Exceptions

Error

Reimplemented from [Function](#).

Definition at line 141 of file function-modifier.hh.

5.24.3.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true if the function has a known maximum and the map is bijective.

Reimplemented from [Function](#).

Definition at line 151 of file function-modifier.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-modifier.hh
- lib/hnco/functions/decorators/function-modifier.cc

5.25 FunctionModifier Class Reference

Function modifier.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for FunctionModifier:



Public Member Functions

- `FunctionModifier (Function *function)`
Constructor.

Additional Inherited Members

5.25.1 Detailed Description

Function modifier.

Definition at line 37 of file `function-modifier.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/functions/decorators/function-modifier.hh`

5.26 FunctionPlugin Class Reference

[Function](#) plugin.

```
#include <hnco/functions/plugin.hh>
```

Inheritance diagram for FunctionPlugin:



Public Member Functions

- [FunctionPlugin](#) (int bv_size, std::string path, std::string name)
Constructor.
- [~FunctionPlugin](#) ()
Destructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Types

- typedef double(* [extern_function_t](#)) (const char[], size_t)
Type of an extern function.

Private Attributes

- size_t [_bv_size](#)
Bit vector size.
- void * [_handle](#)
Handle returned by dlopen.
- [extern_function_t](#) [_extern_function](#)
Extern function.

5.26.1 Detailed Description

Function plugin.

Definition at line 34 of file plugin.hh.

5.26.2 Constructor & Destructor Documentation

5.26.2.1 FunctionPlugin()

```
FunctionPlugin (
    int bv_size,
    std::string path,
    std::string name )
```

Constructor.

Parameters

<i>bv_size</i>	Size of bit vectors
<i>path</i>	Path to a shared library
<i>name</i>	Name of a function of the shared library

Definition at line 35 of file plugin.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/plugin.hh
- lib/hnco/functions/plugin.cc

5.27 GeneticAlgorithm Class Reference

Genetic algorithm.

```
#include <hnco/algorithms/ea/genetic-algorithm.hh>
```


Inheritance diagram for GeneticAlgorithm:



Public Member Functions

- [GeneticAlgorithm](#) (int n, int mu)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_crossover_probability](#) (double x)
Set the crossover probability.
- void [set_tournament_size](#) (int x)
Set the tournament size.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [TournamentSelection _parents](#)
Parents.
- [TournamentSelection _offsprings](#)
Offsprings.
- [neighborhood::BernoulliProcess _mutation](#)

Mutation operator.

- `std::bernoulli_distribution _do_crossover`

Do crossover.

- `UniformCrossover _crossover`

Uniform crossover.

Parameters

- `double _mutation_probability`
Mutation probability.
- `double _crossover_probability = 0.5`
Crossover probability.
- `int _tournament_size = 10`
Tournament size.
- `bool _allow_stay = false`
Allow stay.

Additional Inherited Members

5.27.1 Detailed Description

Genetic algorithm.

- Tournament selection for reproduction
- Uniform crossover
- Mutation
- (mu, mu) selection (offspring population replaces parent population)

Reference:

J. H. Holland. 1975. Adaptation in natural and artificial systems. University of Michigan Press, Ann Arbor.

Definition at line 51 of file genetic-algorithm.hh.

5.27.2 Constructor & Destructor Documentation

5.27.2.1 GeneticAlgorithm()

```
GeneticAlgorithm (
    int n,
    int mu ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Population size

Definition at line 97 of file genetic-algorithm.hh.

5.27.3 Member Function Documentation

5.27.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 125 of file genetic-algorithm.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/genetic-algorithm.hh
- lib/hnco/algorithms/ea/genetic-algorithm.cc

5.28 HammingBall Class Reference

Hamming ball.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for HammingBall:



Public Member Functions

- [HammingBall](#) (int n, int r)
Constructor.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.

Private Attributes

- int [_radius](#)
Radius of the ball.
- `std::uniform_int_distribution< int > _choose_k`
Choose the distance to the center.

Additional Inherited Members

5.28.1 Detailed Description

Hamming ball.

Choose k uniformly on [1..r], where r is the radius of the ball, choose k bits uniformly among n and flip them.

Definition at line 304 of file neighborhood.hh.

5.28.2 Constructor & Destructor Documentation

5.28.2.1 HammingBall()

```
HammingBall (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>r</i>	Radius of the ball

Definition at line 323 of file neighborhood.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/neighborhoods/neighborhood.hh`
- `lib/hnco/neighborhoods/neighborhood.cc`

5.29 HammingBallIterator Class Reference

Hamming ball neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for HammingBallIterator:



Public Member Functions

- [HammingBallIterator](#) (int n, int r)
Constructor.
- void [init](#) ()
Initialization.
- bool [has_next](#) ()
Has next bit vector.
- void [next](#) ()
Next bit vector.

Private Attributes

- [bit_vector_t _mask](#)
Mutation mask.
- int [_radius](#)
Radius of the ball.
- int [_index](#)
Index of the next bit to shift to the right.
- int [_weight](#)
Partial Hamming weight.

Additional Inherited Members

5.29.1 Detailed Description

Hamming ball neighborhood iterator.

Definition at line 86 of file neighborhood-iterator.hh.

5.29.2 Constructor & Destructor Documentation

5.29.2.1 HammingBallIterator()

```
HammingBallIterator (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>r</i>	Radius of Hamming Ball

Definition at line 108 of file neighborhood-iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.30 HammingSphere Class Reference

Hamming sphere.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for HammingSphere:



Public Member Functions

- [HammingSphere](#) (int n, int r)
Constructor.
- void [set_radius](#) (int r)
Set radius.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.

Private Attributes

- int [_radius](#)
Radius of the sphere.

Additional Inherited Members

5.30.1 Detailed Description

Hamming sphere.

Uniformly choose r bits among n and flip them, where r is the radius of the sphere.

Definition at line 341 of file neighborhood.hh.

5.30.2 Constructor & Destructor Documentation

5.30.2.1 HammingSphere()

```
HammingSphere (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>r</i>	Radius of the sphere

Definition at line 357 of file neighborhood.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.31 Hea< Moment, Herding > Class Template Reference

Herding evolutionary algorithm.

```
#include <hnco/algorithms/hea/hea.hh>
```

Inheritance diagram for Hea< Moment, Herding >:



Public Types

- enum { [RATE_CONSTANT](#), [RATE_EXPONENTIAL](#), [RATE_INVERSE](#) }
- enum { [LOG_ERROR](#), [LOG_DTU](#), [LOG_DELTA](#), [LOG_SELECTION](#), [LAST_LOG](#) }
- typedef std::bitset< LAST_LOG > [log_flags_t](#)
Type for log flags.

Public Member Functions

- [Hea](#) (int n, int population_size)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_herding](#) (Herding *x)
Set the herding algorithm.
- void [set_margin](#) (double x)
Set the moment margin.
- void [set_selection_size](#) (int x)
Set the selection size.
- void [set_rate_strategy](#) (int x)
Set the rate strategy.
- void [set_reset_period](#) (int x)
Set the reset period.
- void [set_delay](#) (int x)
Set the delay.
- void [set_initial_rate](#) (double x)
Set the initial value of the learning rate.
- void [set_time_constant](#) (double x)
Set the time constant.
- void [set_bound_moment](#) (bool x)
Set the bound moment after update.
- void [set_weight](#) (double weight)
Set weight.
- void [set_log_flags](#) (const [log_flags_t](#) &lf)
Set log flags.

Private Member Functions

- void [iterate](#) ()
Single iteration.
- void [log](#) ()
Log.

Private Attributes

- `Moment _target`
Moment.
- `Moment _selection`
Moment of selected individuals.
- `Moment _uniform`
Uniform moment.
- `algorithm::Population _population`
Population.
- `Herding * _herding`
Herding.
- `double _error_cache`
Error cache.
- `double _dtu_cache`
Distance to uniform cache.
- `double _delta_cache`
Delta cache.
- `double _selection_cache`
Selection distance cache.
- `log_flags_t _log_flags`
Log flags.

Parameters

- `double _margin`
Moment margin.
- `int _selection_size = 1`
Selection size.
- `int _rate_strategy = RATE_CONSTANT`
Rate strategy.
- `int _reset_period = 0`
Reset period.
- `int _delay = 10000`
Delay.
- `double _initial_rate = 1e-4`
Initial value of the learning rate.
- `double _time_constant = 1000`
Time constant.
- `bool _bound_moment = false`
Bound moment after update.

Additional Inherited Members

5.31.1 Detailed Description

```
template<class Moment, class Herding>
class hnco::algorithm::hea::Hea< Moment, Herding >
```

Herding evolutionary algorithm.

Reference:

Arnaud Berny. 2015. Herding Evolutionary Algorithm. In Proceedings of the Companion Publication of the 2015 Annual Conference on Genetic and Evolutionary Computation (GECCO Companion '15). ACM, New York, NY, USA, 1355–1356.

Definition at line 49 of file hea.hh.

5.31.2 Member Enumeration Documentation

5.31.2.1 anonymous enum

anonymous enum

Enumerator

RATE_CONSTANT	Constant rate.
RATE_EXPONENTIAL	Exponential decay.
RATE_INVERSE	Inverse decay.

Definition at line 54 of file hea.hh.

5.31.2.2 anonymous enum

anonymous enum

Enumerator

LOG_ERROR	Log error.
LOG_DTU	Log distance to uniform.
LOG_DELTA	Log delta (moment increment)
LOG_SELECTION	Log the distance between the target and the selection moment.

Definition at line 65 of file hea.hh.

5.31.3 Constructor & Destructor Documentation

5.31.3.1 Hea()

```
Hea (
    int n,
    int population_size ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

`_margin` is initialized to $1 / n$.

Definition at line 234 of file `hea.hh`.

5.31.4 Member Function Documentation

5.31.4.1 `set_reset_period()`

```
void set_reset_period (
    int x ) [inline]
```

Set the reset period.

Parameters

x	Reset period
---	--------------

$x \leq 0$ means no reset.

Definition at line 281 of file `hea.hh`.

5.31.4.2 `set_selection_size()`

```
void set_selection_size (
    int x ) [inline]
```

Set the selection size.

The selection size is the number of selected individuals in the population.

Definition at line 270 of file `hea.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/hea/hea.hh`

5.32 Hiff Class Reference

Hierarchical if and only if.

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for Hiff:



Public Member Functions

- [Hiff](#) (int bv_size)
Constructor.
- [size_t get_bv_size](#) ()
Get bit vector size.
- [double eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- [bool has_known_maximum](#) ()
Check for a known maximum.
- [double get_maximum](#) ()
Get the global maximum.

Private Attributes

- [size_t _bv_size](#)
Bit vector size.
- [size_t _depth](#)
Tree depth.

5.32.1 Detailed Description

Hierarchical if and only if.

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 165 of file theory.hh.

5.32.2 Member Function Documentation

5.32.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$(i + 1) * 2^i$ where $2^i = _bv_size$

Reimplemented from [Function](#).

Definition at line 191 of file theory.hh.

5.32.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 187 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.33 Hypercubeliterator Class Reference

Hypercube iterator.

```
#include <hnco/iterator.hh>
```

Inheritance diagram for Hypercubeliterator:



Public Member Functions

- [Hypercubeliterator](#) (int n)
Constructor.
- void [init](#) ()
Initialization.
- bool [has_next](#) ()
Has next bit vector.
- void [next](#) ()
Next bit vector.

Additional Inherited Members

5.33.1 Detailed Description

Hypercube iterator.

Definition at line 71 of file iterator.hh.

5.33.2 Member Function Documentation

5.33.2.1 [next\(\)](#)

```
void next ( ) [virtual]
```

Next bit vector.

Implemented as a simple binary adder.

Implements [Iterator](#).

Definition at line 28 of file iterator.cc.

The documentation for this class was generated from the following files:


- lib/hnco/iterator.hh
- lib/hnco/iterator.cc

5.34 IterativeAlgorithm Class Reference

Iterative search.

```
#include <hnco/algorithms/algorithm.hh>
```

Inheritance diagram for IterativeAlgorithm:



Public Member Functions

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.

Setters

- void [set_num_iterations](#) (int x)
Set the number of iterations.

Protected Member Functions

- virtual void [iterate](#) ()=0
Single iteration.
- virtual void [log](#) ()
Log.

Protected Attributes

- `int _iteration`
Current iteration.
- `bool _something_to_log`
Something to log.

Parameters

- `int _num_iterations = 0`
Number of iterations.

5.34.1 Detailed Description

Iterative search.

Definition at line 130 of file `algorithm.hh`.

5.34.2 Constructor & Destructor Documentation

5.34.2.1 IterativeAlgorithm()

```
IterativeAlgorithm (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 160 of file `algorithm.hh`.

5.34.3 Member Function Documentation

5.34.3.1 maximize()

```
void maximize ( ) [virtual]
```

Maximize.

Inside the loop:

- call [iterate\(\)](#)
- call [log\(\)](#)

Warning

If an exception such as LocalMaximum is thrown by [iterate\(\)](#), [log\(\)](#) will not be called. However, hnco reports the maximum at the end of the search.

Implements [Algorithm](#).

Definition at line 77 of file algorithm.cc.

5.34.3.2 set_num_iterations()

```
void set_num_iterations (
    int x ) [inline]
```

Set the number of iterations.

Parameters

x	Number of iterations
---	----------------------

$x \leq 0$ means indefinite

Definition at line 184 of file algorithm.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/algorithm.hh
- lib/hnco/algorithms/algorithm.cc

5.35 Iterator Class Reference

[Iterator](#) over bit vectors.

```
#include <hnco/iterator.hh>
```

Inheritance diagram for Iterator:



Public Member Functions

- [Iterator](#) (int n)
Constructor.
- virtual [~Iterator](#) ()
Destructor.
- virtual const [bit_vector_t](#) & [get_current](#) ()
Current bit vector.
- virtual void [init](#) ()=0
Initialization.
- virtual bool [has_next](#) ()=0
Has next bit vector.
- virtual void [next](#) ()=0
Next bit vector.

Protected Attributes

- [bit_vector_t _current](#)
Current bit vector.

5.35.1 Detailed Description

[Iterator](#) over bit vectors.

Definition at line 40 of file iterator.hh.

The documentation for this class was generated from the following file:


- lib/hnco/iterator.hh

5.36 Jump Class Reference

[Jump](#).

```
#include <hnco/functions/jump.hh>
```

Inheritance diagram for Jump:



Public Member Functions

- [Jump](#) (int bv_size, int gap)
Constructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- size_t [_bv_size](#)
Bit vector size.
- int [_gap](#)
Gap.

5.36.1 Detailed Description

[Jump](#).

Reference:

H. Mühlenbein and T. Mahnig. 2001. Evolutionary Algorithms: From Recombination to Search Distributions. In Theoretical Aspects of Evolutionary Computing, Leila Kallel, Bart Naudts, and Alex Rogers (Eds.). Springer Berlin Heidelberg, 135–174.

Definition at line 40 of file jump.hh.

5.36.2 Member Function Documentation

5.36.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 66 of file `jump.hh`.

5.36.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 62 of file `jump.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/jump.hh`
- `lib/hnco/functions/jump.cc`

5.37 Labs Class Reference

Low autocorrelation binary sequences.

```
#include <hnco/functions/labs.hh>
```

Inheritance diagram for Labs:



Public Member Functions

- [Labs](#) (int n)
Constructor.
- `size_t` [get_bv_size](#) ()
Get bit vector size.
- `double` [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- `std::vector< int >` [_sequence](#)
Binary sequence written using 1 and -1.

5.37.1 Detailed Description

Low autocorrelation binary sequences.

Reference:

S Mertens. 1996. Exhaustive search for low-autocorrelation binary sequences. Journal of Physics A: Mathematical and General 29, 18 (1996), L473.

<http://stacks.iop.org/0305-4470/29/i=18/a=005>

Definition at line 43 of file labs.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/labs.hh
- lib/hnco/functions/labs.cc

5.38 LastEvaluation Class Reference

Last evaluation.

```
#include <hnco/exception.hh>
```

Inheritance diagram for LastEvaluation:



5.38.1 Detailed Description

Last evaluation.

Definition at line 79 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.39 LeadingOnes Class Reference

Leading ones.

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for LeadingOnes:



Public Member Functions

- [LeadingOnes](#) (int bv_size)
Constructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- size_t [_bv_size](#)
Bit vector size.

5.39.1 Detailed Description

Leading ones.

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 93 of file theory.hh.

5.39.2 Member Function Documentation

5.39.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 117 of file theory.hh.

5.39.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 113 of file theory.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/theory.hh`
- `lib/hnco/functions/theory.cc`

5.40 LinearFunction Class Reference

Linear function.

```
#include <hnco/functions/linear-function.hh>
```

Inheritance diagram for LinearFunction:



Public Member Functions

- [LinearFunction](#) ()
Constructor.
- void [random](#) (int n)
Random instance.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Member Functions

- template<class Archive >
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- std::vector< double > [_weights](#)
Weights.

Friends

- class **boost::serialization::access**

5.40.1 Detailed Description

Linear function.

Definition at line 40 of file linear-function.hh.

5.40.2 Member Function Documentation

5.40.2.1 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 76 of file linear-function.hh.

5.40.2.2 random()

```
void random (
    int n )
```

Random instance.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 34 of file linear-function.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/linear-function.hh
- lib/hnco/functions/linear-function.cc

5.41 LinearMap Class Reference

Linear map.

```
#include <hnco/map.hh>
```

Inheritance diagram for LinearMap:



Public Member Functions

- void `random` (int n, int m)
Random instance.
- void `map` (const `bit_vector_t` &input, `bit_vector_t` &output)
Map.
- size_t `get_input_size` ()
Get input size.
- size_t `get_output_size` ()
Get output size.

Private Member Functions

- template<class Archive >
void `save` (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void `load` (Archive &ar, const unsigned int version)
Load.

Private Attributes

- `bit_matrix_t _bm`
Bit matrix.

Friends

- class `boost::serialization::access`

5.41.1 Detailed Description

Linear map.

A linear map f from Z_2^m to Z_2^n is defined by $f(x) = Ax$, where A is an $m \times n$ bit matrix.

Warning

The class does not reimplement the member function `is_surjective` hence a linear map is always considered not surjective.

Definition at line 197 of file `map.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/map.hh`
- `lib/hnco/map.cc`

5.42 LocalMaximum Class Reference

Local maximum.

```
#include <hnco/exception.hh>
```

Inheritance diagram for `LocalMaximum`:



Public Member Functions

- `LocalMaximum` (const `point_value_t` &pv)
Const.

Additional Inherited Members

5.42.1 Detailed Description

Local maximum.

Definition at line 70 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.43 LongPath Class Reference

Long path.

```
#include <hnco/functions/long-path.hh>
```

Inheritance diagram for LongPath:



Public Member Functions

- [LongPath](#) (int bv_size, int prefix_length)
Constructor.
- [size_t get_bv_size](#) ()
Get bit vector size.
- [double eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- [size_t _bv_size](#)
Bit vector size.
- [int _prefix_length](#)
Prefix length.

5.43.1 Detailed Description

Long path.

Long paths have been introduced by Jeffrey Horn, David E. Goldberg, and Kalyanmoy Deb. Here we follow the definition given by Thomas Jansen (see references below).

As an example, here is the 2-long path of dimension 4:

- 0000
- 0001
- 0011
- 0111
- 1111
- 1101
- 1100

The fitness is increasing along the path. The fitness on the complementary of the path is defined as a linear function pointing to the beginning of the path.

References:

Jeffrey Horn, David E. Goldberg, and Kalyanmoy Deb, "Long Path Problems", PPSN III, 1994.

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 58 of file long-path.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/long-path.hh
- lib/hnco/functions/long-path.cc

5.44 Map Class Reference

[Map](#).

```
#include <hnco/map.hh>
```

Inheritance diagram for Map:



Public Member Functions

- virtual [~Map](#) ()
Destructor.
- virtual void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)=0
Map.
- virtual size_t [get_input_size](#) ()=0
Get input size.
- virtual size_t [get_output_size](#) ()=0
Get output size.
- virtual bool [is_surjective](#) ()
Check for surjective map.

5.44.1 Detailed Description

[Map](#).

Definition at line 39 of file map.hh.

5.44.2 Member Function Documentation

5.44.2.1 [is_surjective\(\)](#)

```
virtual bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

false

Reimplemented in [MapComposition](#), [Permutation](#), and [Translation](#).

Definition at line 59 of file map.hh.

The documentation for this class was generated from the following file:


- lib/hnco/map.hh

5.45 MapComposition Class Reference

Map composition.

```
#include <hnco/map.hh>
```

Inheritance diagram for MapComposition:



Public Member Functions

- [MapComposition](#) ()
Default constructor.
- [MapComposition](#) ([Map](#) *outer, [Map](#) *inner)
Constructor.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.
- size_t [get_input_size](#) ()
Get input size.
- size_t [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Attributes

- [Map](#) * [_outer](#)
Outer map.
- [Map](#) * [_inner](#)
Inner map.
- [bit_vector_t](#) [_bv](#)
Temporary bit vector.

5.45.1 Detailed Description

Map composition.

The resulting composition f is defined for all bit vector x by $f(x) = \text{outer}(\text{inner}(x))$.

Definition at line 326 of file map.hh.

5.45.2 Constructor & Destructor Documentation

5.45.2.1 MapComposition()

```
MapComposition (
    Map * outer,
    Map * inner ) [inline]
```

Constructor.

Parameters

<i>outer</i>	outer map
<i>inner</i>	inner map

Precondition

```
outer->get_input_size() == inner->get_output_size()
```

Definition at line 350 of file map.hh.

5.45.3 Member Function Documentation

5.45.3.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true if both maps are surjective

Reimplemented from [Map](#).

Definition at line 374 of file map.hh.

The documentation for this class was generated from the following file:


- lib/hnco/map.hh

5.46 MaximumReached Class Reference

Maximum reached.

```
#include <hnco/exception.hh>
```

Inheritance diagram for MaximumReached:



Public Member Functions

- [MaximumReached](#) (const [point_value_t](#) &pv)
Constructor.

Additional Inherited Members

5.46.1 Detailed Description

Maximum reached.

Definition at line 52 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.47 MaxSat Class Reference

MAX-SAT.

```
#include <hnco/functions/max-sat.hh>
```

Inheritance diagram for MaxSat:



Public Member Functions

- `MaxSat ()`
Default constructor.
- `void random (int n, int k, int c)`
Random instance.
- `void random (const bit_vector_t &solution, int k, int c)`
Random instance with satisfiable expression.
- `void load (std::istream &stream)`
Load an instance.
- `void save (std::ostream &stream)`
Save an instance.
- `size_t get_bv_size ()`
Get bit vector size.
- `double eval (const bit_vector_t &)`
Evaluate a bit vector.
- `void display (std::ostream &stream)`
Display the expression.

Private Attributes

- `std::vector< std::vector< int > > _expression`
Expression.
- `size_t _num_variables`
Number of variables.

5.47.1 Detailed Description

MAX-SAT.

Reference:

Christos M. Papadimitriou. 1994. Computational complexity. Addison-Wesley, Reading, Massachusetts.

Definition at line 42 of file max-sat.hh.

5.47.2 Member Function Documentation

5.47.2.1 load()

```
void load (
    std::istream & stream )
```

Load an instance.

Exceptions

Error	
-------	--

Definition at line 134 of file max-sat.cc.

5.47.2.2 random() [1/2]

```
void random (
    int n,
    int k,
    int c )
```

Random instance.

Parameters

<i>n</i>	Size of bit vectors
<i>k</i>	Number of literals per clause
<i>c</i>	Number of clauses

Definition at line 39 of file max-sat.cc.

5.47.2.3 random() [2/2]

```
void random (
    const bit_vector_t & solution,
    int k,
    int c )
```

Random instance with satisfiable expression.

Warning

Since the expression is satisfiable, the maximum of the function is equal to the number of clauses in the expression. However, this information is lost in the save and load cycle as the archive format only manages the expression itself.

Parameters

<i>solution</i>	Solution
<i>k</i>	Number of literals per clause
<i>c</i>	Number of clauses

Definition at line 67 of file max-sat.cc.

5.47.3 Member Data Documentation

5.47.3.1 _expression

```
std::vector<std::vector<int> > _expression [private]
```

Expression.

An expression is represented by a vector of clauses. A clause is represented by a vector of literals. A literal is represented by a non null integer; if the integer is positive then the literal is a variable; if it is negative then it is the logical negation of a variable.

Definition at line 52 of file max-sat.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/max-sat.hh
- lib/hnco/functions/max-sat.cc

5.48 Mmas Class Reference

Max-min ant system.

```
#include <hnco/algorithms/pv/mmas.hh>
```

Inheritance diagram for Mmas:



Public Member Functions

- [Mmas](#) (int n)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_operator](#) (std::function< bool(double, double)> x)
Set the binary operator for comparing evaluations.
- void [set_rate](#) (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- `bit_vector_t _x`
Candidate solution.

Parameters

- `std::function< bool(double, double)> _operator` = `std::greater_equal<double>()`
Binary operator for comparing evaluations.
- `double _rate` = `1e-3`
Learning rate.

Additional Inherited Members

5.48.1 Detailed Description

Max-min ant system.

Reference:

Thomas Stützle and Holger H. Hoos. 2000. MAX-MIN Ant System. *Future Generation Computer Systems* 16, 8 (2000), 889–914.

Definition at line 41 of file `mmas.hh`.

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/pv/mmas.hh`
- `lib/hnco/algorithms/pv/mmas.cc`

5.49 Model Class Reference

`Model` of a Boltzmann machine.

```
#include <hnco/algorithms/bm-pbil/model.hh>
```

Public Member Functions

- `Model` (int n)
Constructor.
- `void init` ()
Initialize.
- `void reset_mc` ()
Reset Markov chain.
- `void gibbs_sampler` (size_t i)
A Gibbs sampler cycle.
- `void gibbs_sampler_synchronous` ()
A synchronous Gibbs sampler.
- `const bit_vector_t & get_state` ()
Get the state of the Gibbs sampler.
- `void update` (const `ModelParameters` &p, const `ModelParameters` &q, double rate)
Update parameters in the direction of p and away from q.
- `double norm_infinite` ()
Infinite norm of the parameters.
- `double norm_l1` ()
l1 norm of the parameters

Private Attributes

- [ModelParameters _model_parameters](#)
Model parameters.
- [bit_vector_t _state](#)
State of the Gibbs sampler.
- [pv_t _pv](#)
Probability vector for synchronous Gibbs sampling.

5.49.1 Detailed Description

[Model](#) of a Boltzmann machine.

Definition at line 75 of file `model.hh`.

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/bm-pbil/model.hh`
- `lib/hnco/algorithms/bm-pbil/model.cc`

5.50 ModelParameters Class Reference

Parameters of a Boltzmann machine.

```
#include <hnco/algorithms/bm-pbil/model.hh>
```

Public Member Functions

- [ModelParameters](#) (int n)
Constructor.
- void [init](#) ()
Initialize.
- void [add](#) (const [bit_vector_t](#) &x)
Add a bit_vector_t.
- void [average](#) (int count)
Compute averages.
- void [update](#) (const [ModelParameters](#) &p, const [ModelParameters](#) &q, double rate)
Update parameters in the direction of p and away from q.
- double [norm_infinite](#) ()
Infinite norm of the parameters.
- double [norm_l1](#) ()
l1 norm of the parameters

Private Attributes

- `std::vector< std::vector< double > >` [_weight](#)
Weights.
- `std::vector< double >` [_bias](#)
Bias.

Friends

- class **Model**

5.50.1 Detailed Description

Parameters of a Boltzmann machine.

Definition at line 36 of file model.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/bm-pbil/model.hh
- lib/hnco/algorithms/bm-pbil/model.cc

5.51 MuCommaLambdaEa Class Reference

(mu, lambda) EA.

```
#include <hnco/algorithms/ea/mu-comma-lambda-ea.hh>
```

Inheritance diagram for MuCommaLambdaEa:



Public Member Functions

- [MuCommaLambdaEa](#) (int n, int mu, int lambda)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Private Member Functions

- void `iterate` ()
Single iteration.

Private Attributes

- `Population _parents`
Parents.
- `Population _offsprings`
Offsprings.
- `neighborhood::BernoulliProcess _mutation`
Mutation operator.
- `std::uniform_int_distribution< int > _select_parent`
Select parent.

Parameters

- double `_mutation_probability`
Mutation probability.
- bool `_allow_stay` = false
Allow stay.

Additional Inherited Members

5.51.1 Detailed Description

(mu, lambda) EA.

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 41 of file mu-comma-lambda-ea.hh.

5.51.2 Constructor & Destructor Documentation

5.51.2.1 MuCommaLambdaEa()

```
MuCommaLambdaEa (
    int n,
    int mu,
    int lambda ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Parent population size
<i>lambda</i>	Offspring population size

Definition at line 79 of file mu-comma-lambda-ea.hh.

5.51.3 Member Function Documentation

5.51.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 102 of file mu-comma-lambda-ea.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/mu-comma-lambda-ea.hh
- lib/hnco/algorithms/ea/mu-comma-lambda-ea.cc

5.52 MultiBitFlip Class Reference

Multi bit flip.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for MultiBitFlip:



Public Member Functions

- [MultiBitFlip](#) (int n)
Constructor.

Protected Member Functions

- void [bernoulli_trials](#) (int k)
Sample a given number of bits using Bernoulli trials.
- void [reservoir_sampling](#) (int k)
Sample a given number of bits using resevoir sampling.

Additional Inherited Members

5.52.1 Detailed Description

Multi bit flip.

Definition at line 183 of file neighborhood.hh.

5.52.2 Constructor & Destructor Documentation

5.52.2.1 MultiBitFlip()

```
MultiBitFlip (  
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 206 of file neighborhood.hh.

5.52.3 Member Function Documentation

5.52.3.1 bernoulli_trials()

```
void bernoulli_trials (  
    int k ) [protected]
```

Sample a given number of bits using Bernoulli trials.

Parameters

k	Number of bits to sample
-----	--------------------------

Definition at line 34 of file neighborhood.cc.

5.52.3.2 reservoir_sampling()

```
void reservoir_sampling (  
    int  $k$  ) [protected]
```

Sample a given number of bits using resevoir sampling.

Parameters

k	Number of bits to sample
-----	--------------------------

Definition at line 52 of file neighborhood.cc.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.53 MuPlusLambdaEa Class Reference

(mu+lambda) EA.

```
#include <hnco/algorithms/ea/mu-plus-lambda-ea.hh>
```

Inheritance diagram for MuPlusLambdaEa:



Public Member Functions

- [MuPlusLambdaEa](#) (int n, int mu, int lambda)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [Population _parents](#)
Parents.
- [Population _offsprings](#)
Offsprings.
- [neighborhood::BernoulliProcess _mutation](#)
Mutation operator.
- [std::uniform_int_distribution< int > _select_parent](#)
Select parent.

Parameters

- double [_mutation_probability](#)
Mutation probability.
- bool [_allow_stay](#) = false
Allow stay.

Additional Inherited Members

5.53.1 Detailed Description

(mu+lambda) EA.

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 40 of file mu-plus-lambda-ea.hh.

5.53.2 Constructor & Destructor Documentation

5.53.2.1 MuPlusLambdaEa()

```
MuPlusLambdaEa (
    int n,
    int mu,
    int lambda ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Parent population size
<i>lambda</i>	Offspring population size

Definition at line 78 of file mu-plus-lambda-ea.hh.

5.53.3 Member Function Documentation

5.53.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 101 of file mu-plus-lambda-ea.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/mu-plus-lambda-ea.hh
- lib/hnco/algorithms/ea/mu-plus-lambda-ea.cc

5.54 Needle Class Reference

[Needle](#) in a haystack.

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for Needle:



Public Member Functions

- [Needle](#) (int bv_size)
Constructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- size_t [_bv_size](#)
Bit vector size.

5.54.1 Detailed Description

[Needle](#) in a haystack.

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 129 of file theory.hh.

5.54.2 Member Function Documentation

5.54.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

1

Reimplemented from [Function](#).

Definition at line 153 of file theory.hh.

5.54.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 149 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.55 Negation Class Reference

[Negation](#).

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for Negation:



Public Member Functions

- [Negation](#) ([Function](#) *function)
Constructor.

Information about the function

- [size_t](#) [get_bv_size](#) ()
Get bit vector size.
- [double](#) [get_maximum](#) ()
Get the global maximum.
- [bool](#) [has_known_maximum](#) ()
Check for a known maximum.
- [bool](#) [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- [double](#) [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- [double](#) [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↔
_bits)
Incremental evaluation.

Additional Inherited Members

5.55.1 Detailed Description

[Negation](#).

Use cases:

- for algorithms which minimize rather than maximize a function
- for functions one wishes to minimize
- when minimization is needed inside an algorithm

Definition at line 58 of file function-modifier.hh.

5.55.2 Member Function Documentation

5.55.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Exceptions

<i>Error</i>	
--------------	--

Reimplemented from [Function](#).

Definition at line 76 of file function-modifier.hh.

5.55.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

false

Reimplemented from [Function](#).

Definition at line 80 of file function-modifier.hh.

5.55.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 85 of file function-modifier.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-modifier.hh
- lib/hnco/functions/decorators/function-modifier.cc

5.56 Neighborhood Class Reference

[Neighborhood](#).

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for Neighborhood:



Public Member Functions

- [Neighborhood](#) (int n)
Constructor.
- virtual [~Neighborhood](#) ()
Destructor.
- virtual void [set_origin](#) (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & [get_origin](#) ()
Get the origin.
- virtual const [bit_vector_t](#) & [get_candidate](#) ()
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & [get_flipped_bits](#) ()
Get flipped bits.
- virtual void [propose](#) ()
Propose a candidate bit vector.
- virtual void [keep](#) ()
Keep the candidate bit vector.
- virtual void [forget](#) ()
Forget the candidate bit vector.
- virtual void [mutate](#) ([bit_vector_t](#) &bv)
Mutate.
- virtual void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Protected Member Functions

- virtual void [sample_bits](#) ()=0
Sample bits.

Protected Attributes

- [bit_vector_t _origin](#)
Origin of the neighborhood.
- [bit_vector_t _candidate](#)
candidate bit vector
- `std::uniform_int_distribution< int > _uniform_index_dist`
Uniform index distribution.
- [sparse_bit_vector_t _flipped_bits](#)
Flipped bits.

5.56.1 Detailed Description

Neighborhood.

A neighborhood maintains two points, `_origin` and `_candidate`. They are initialized in the same state by `set_origin`. A `Neighborhood` class must implement the member function `sample_bits` which samples the bits to flip in `_origin` to get a `_candidate`. The following member functions take care of the modifications:

- `propose`: flip `_candidate`
- `keep`: flip `_origin`
- `forget`: flip `_candidate`

After `keep` or `forget`, `_origin` and `_candidate` are in the same state again.

A `Neighborhood` class can also behave as a mutation operator through the member functions `mutate` and `map`.

Definition at line 61 of file `neighborhood.hh`.

5.56.2 Constructor & Destructor Documentation

5.56.2.1 Neighborhood()

```
Neighborhood (
    int n ) [inline]
```

Constructor.

Parameters

<code>n</code>	Size of bit vectors
----------------	---------------------

Definition at line 86 of file `neighborhood.hh`.

5.56.3 Member Function Documentation

5.56.3.1 map()

```
virtual void map (
    const bit_vector_t & input,
    bit_vector_t & output ) [inline], [virtual]
```

Map.

The output bit vector is a mutated version of the input bit vector.

Parameters

<i>input</i>	Input bit vector
<i>output</i>	Output bit vector

Definition at line 148 of file neighborhood.hh.

5.56.3.2 mutate()

```
virtual void mutate (  
    bit_vector_t & bv ) [inline], [virtual]
```

Mutate.

In-place mutation of the bit vector.

Parameters

<i>bv</i>	Bit vector to mutate
-----------	----------------------

Definition at line 134 of file neighborhood.hh.

The documentation for this class was generated from the following file:


- lib/hnco/neighborhoods/neighborhood.hh

5.57 NeighborhoodIterator Class Reference

[Neighborhood](#) iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for NeighborhoodIterator:



Public Member Functions

- [NeighborhoodIterator](#) (int n)
Constructor.
- virtual void [set_origin](#) (const [bit_vector_t](#) &x)
Set origin.

Additional Inherited Members

5.57.1 Detailed Description

[Neighborhood](#) iterator.

Definition at line 38 of file neighborhood-iterator.hh.

5.57.2 Constructor & Destructor Documentation

5.57.2.1 NeighborhoodIterator()

```
NeighborhoodIterator (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 49 of file neighborhood-iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.58 NkLandscape Class Reference

NK landscape.

```
#include <hnco/functions/nk-landscape.hh>
```


Inheritance diagram for NkLandscape:



Public Member Functions

- `NkLandscape ()`
Default constructor.
- `size_t get_bv_size ()`
Get bit vector size.
- `void random (int n, int k, double stddev)`
Random instance.
- `double eval (const bit_vector_t &)`
Evaluate a bit vector.

Private Member Functions

- `template<class Archive >`
`void serialize (Archive &ar, const unsigned int version)`
Serialize.

Private Attributes

- `std::vector< std::vector< int > > _neighbors`
Bit neighbors.
- `std::vector< std::vector< double > > _partial_functions`
Partial functions.

Friends

- class `boost::serialization::access`

5.58.1 Detailed Description

NK landscape.

Reference:

S. A. Kauffman. 1993. The origins of order: self-organisation and selection in evolution. Oxford University Press.

Definition at line 47 of file `nk-landscape.hh`.

5.58.2 Member Function Documentation

5.58.2.1 random()

```
void random (
    int n,
    int k,
    double stddev )
```

Random instance.

Parameters

<i>n</i>	Size of bit vector
<i>k</i>	Number of neighbors of each bit
<i>stddev</i>	Standard deviation of the values of the partial functions

Definition at line 33 of file nk-landscape.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/nk-landscape.hh
- lib/hnco/functions/nk-landscape.cc

5.59 NpsPbil Class Reference

Population-based incremental learning with negative and positive selection.

```
#include <hnco/algorithms/pv/nps-pbil.hh>
```

Inheritance diagram for NpsPbil:



Public Member Functions

- [NpsPbil](#) (int n, int population_size)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_selection_size](#) (int x)
Set the selection size.
- void [set_rate](#) (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [Population _population](#)
Population.
- [pv_t _mean_best](#)
Mean of best individuals.
- [pv_t _mean_worst](#)

Mean of worst individuals.

Parameters

- `int _selection_size = 1`
Selection size.
- `double _rate = 1e-3`
Learning rate.

Additional Inherited Members

5.59.1 Detailed Description

Population-based incremental learning with negative and positive selection.

Reference:

Arnaud Berny. 2001. Extending selection learning toward fixed-length d-ary strings. In Artificial Evolution (Lecture Notes in Computer Science), P. Collet and others (Eds.). Springer, Le Creusot.

Definition at line 41 of file nps-pbil.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/pv/nps-pbil.hh`
- `lib/hnco/algorithms/pv/nps-pbil.cc`

5.60 OnBudgetFunction Class Reference

[CallCounter](#) with a limited number of evaluations.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for OnBudgetFunction:



Public Member Functions

- [OnBudgetFunction](#) ([Function](#) *function, int budget)

Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↔
_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Private Attributes

- int [_budget](#)
Budget.

Additional Inherited Members

5.60.1 Detailed Description

[CallCounter](#) with a limited number of evaluations.

Definition at line 310 of file function-controller.hh.

5.60.2 Member Function Documentation

5.60.2.1 eval()

```
double eval (
    const bit\_vector\_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 121 of file function-controller.cc.

5.60.2.2 incremental_eval()

```
double incremental_eval (
    const bit\_vector\_t & x,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 132 of file function-controller.cc.

5.60.2.3 update()

```
void update (
    const bit_vector_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 143 of file function-controller.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.61 OneMax Class Reference

[OneMax](#).

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for OneMax:



Public Member Functions

- [OneMax](#) (int bv_size)

Constructor.

Information about the function

- size_t [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double v, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.

Private Attributes

- size_t [_bv_size](#)
Bit vector size.

5.61.1 Detailed Description

[OneMax](#).

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 36 of file theory.hh.

5.61.2 Member Function Documentation

5.61.2.1 [get_maximum\(\)](#)

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

[_bv_size](#)

Reimplemented from [Function](#).

Definition at line 57 of file theory.hh.

5.61.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 61 of file theory.hh.

5.61.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 66 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.62 OnePlusLambdaCommaLambdaGa Class Reference

(1+(lambda, lambda)) genetic algorithm.

```
#include <hnco/algorithms/ea/one-plus-lambda-comma-lambda-ga.hh>
```

Inheritance diagram for OnePlusLambdaCommaLambdaGa:



Public Member Functions

- [OnePlusLambdaCommaLambdaGa](#) (int n, int lambda)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_crossover_bias](#) (double x)
Set the crossover bias.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [Population_offsprings](#)
Offsprings.
- std::binomial_distribution< int > [_radius_dist](#)
Radius distribution.
- [neighborhood::HammingSphere_mutation](#)
Mutation operator.
- [bit_vector_t_parent](#)
Parent.
- [BiasedCrossover_crossover](#)
Biased crossover.

Parameters

- double [_mutation_probability](#)
Mutation probability.
- double [_crossover_bias](#)
Crossover bias.

Additional Inherited Members

5.62.1 Detailed Description

(1+(lambda, lambda)) genetic algorithm.

Reference:

Benjamin Doerr, Carola Doerr, and Franziska Ebel. 2015. From black-box complexity to designing new genetic algorithms. Theoretical Computer Science 567 (2015), 87–104.

Definition at line 49 of file one-plus-lambda-comma-lambda-ga.hh.

5.62.2 Constructor & Destructor Documentation

5.62.2.1 OnePlusLambdaCommaLambdaGa()

```
OnePlusLambdaCommaLambdaGa (
    int n,
    int lambda ) [inline]
```

Constructor.

By default, `_mutation_probability` is set to `lambda / n` and `_crossover_bias` to `1 / lambda`.

Parameters

<i>n</i>	Size of bit vectors
<i>lambda</i>	Offspring population size

Definition at line 92 of file `one-plus-lambda-comma-lambda-ga.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ea/one-plus-lambda-comma-lambda-ga.hh`
- `lib/hnco/algorithms/ea/one-plus-lambda-comma-lambda-ga.cc`

5.63 OnePlusOneEa Class Reference

(1+1) EA.

```
#include <hnco/algorithms/ea/one-plus-one-ea.hh>
```

Inheritance diagram for OnePlusOneEa:



Public Member Functions

- [OnePlusOneEa](#) (int n)
Constructor.
- void [set_function](#) (function::Function *function)
Set function.
- void [init](#) ()
Initialization.
- void [maximize](#) ()
Maximize.
- const [point_value_t](#) & [get_solution](#) ()
Solution.

Setters

- void [set_num_iterations](#) (int x)
Set the number of iterations.
- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.
- void [set_incremental_evaluation](#) (bool x)
Set incremental evaluation.

Private Attributes

- [neighborhood::BernoulliProcess _neighborhood](#)
Neighborhood.
- [RandomLocalSearch _rls](#)
Random local search.

Parameters

- int [_num_iterations](#) = 0
Number of iterations.
- double [_mutation_probability](#)
Mutation probability.
- bool [_allow_stay](#) = false
Allow stay.
- bool [_incremental_evaluation](#) = false
Incremental evaluation.

Additional Inherited Members

5.63.1 Detailed Description

(1+1) EA.

(1+1) EA is implemented as a [RandomLocalSearch](#) with a [BernoulliProcess](#) neighborhood and infinite patience. Thus it does derive from [IterativeAlgorithm](#).

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 44 of file one-plus-one-ea.hh.

5.63.2 Constructor & Destructor Documentation

5.63.2.1 OnePlusOneEa()

```
OnePlusOneEa (  
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

_mutation_probability is initialized to 1 / n.

Definition at line 79 of file one-plus-one-ea.hh.

5.63.3 Member Function Documentation

5.63.3.1 set_allow_stay()

```
void set_allow_stay (  
    bool x ) [inline]
```

Set the flag _allow_stay.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 125 of file one-plus-one-ea.hh.

5.63.3.2 set_num_iterations()

```
void set_num_iterations (  
    int x ) [inline]
```

Set the number of iterations.

Parameters

<i>x</i>	Number of iterations
----------	----------------------

$x \leq 0$ means indefinite

Definition at line 115 of file one-plus-one-ea.hh.

The documentation for this class was generated from the following file:


- lib/hnco/algorithms/ea/one-plus-one-ea.hh

5.64 Pbil Class Reference

Population-based incremental learning.

```
#include <hnco/algorithms/pv/pbil.hh>
```

Inheritance diagram for Pbil:



Public Member Functions

- **Pbil** (int n, int population_size)
Constructor.
- void **init** ()
Initialization.

Setters

- void **set_selection_size** (int x)
Set the selection size.
- void **set_rate** (double x)
Set the learning rate.

Protected Member Functions

- void `iterate` ()
Single iteration.

Protected Attributes

- `Population _population`
Population.
- `pv_t _mean`
Mean of selected bit vectors.

Parameters

- int `_selection_size` = 1
Selection size.
- double `_rate` = 1e-3
Learning rate.

Additional Inherited Members

5.64.1 Detailed Description

Population-based incremental learning.

Reference:

S. Baluja and R. Caruana. 1995. Removing the genetics from the standard genetic algorithm. In Proceedings of the 12th Annual Conference on Machine Learning. 38–46.

Definition at line 40 of file `pbil.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/pv/pbil.hh`
- `lib/hnco/algorithms/pv/pbil.cc`

5.65 Permutation Class Reference

[Permutation](#).

```
#include <hnco/map.hh>
```

Inheritance diagram for `Permutation`:



Public Member Functions

- void [random](#) (int n)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.
- size_t [get_input_size](#) ()
Get input size.
- size_t [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [permutation_t _permutation](#)
Permutation.

Friends

- class **boost::serialization::access**

5.65.1 Detailed Description

[Permutation.](#)

A permutation is a linear map f from Z_2^n to itself defined by $f(x) = y$, where $y_i = x_{\sigma_i}$ and σ is a permutation of 0, 1, ..., n - 1.

Definition at line 132 of file map.hh.

5.65.2 Member Function Documentation

5.65.2.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 183 of file map.hh.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.66 Plateau Class Reference

[Plateau](#).

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for Plateau:



Public Member Functions

- [Plateau](#) (int bv_size)
Constructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- `size_t _bv_size`
Bit vector size.

5.66.1 Detailed Description

[Plateau](#).

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 239 of file theory.hh.

5.66.2 Member Function Documentation

5.66.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size + 2`

Reimplemented from [Function](#).

Definition at line 263 of file theory.hh.

5.66.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 259 of file theory.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/theory.hh`
- `lib/hnco/functions/theory.cc`

5.67 PointValueException Class Reference

Point-value exception.

```
#include <hnco/exception.hh>
```

Inheritance diagram for PointValueException:



Public Member Functions

- [PointValueException](#) (const [point_value_t](#) &pv)
Constructor.
- const [point_value_t](#) & [get_point_value](#) () const
Get point-value.

Protected Attributes

- [point_value_t _pv](#)
Point-value.

5.67.1 Detailed Description

Point-value exception.

Definition at line 38 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.68 Population Class Reference

[Population](#).

```
#include <hnco/algorithms/population.hh>
```

Inheritance diagram for Population:



Public Types

- typedef std::pair< size_t, double > [index_value_t](#)
Index-value type.

Public Member Functions

- [Population](#) (int population_size, int n)
Constructor.
- std::size_t [size](#) () const
Size.
- void [random](#) ()
Initialize the population with random bit vectors.
- [bit_vector_t](#) & [get_bv](#) (int i)
Get a bit vector.
- const [bit_vector_t](#) & [get_bv](#) (int i) const
Get a bit vector.

Get sorted bit vectors

- const [bit_vector_t](#) & [get_best_bv](#) (int i) const
Get best bit vector.
- const [bit_vector_t](#) & [get_best_bv](#) () const
Get best bit vector.
- const [bit_vector_t](#) & [get_worst_bv](#) (int i) const
Get worst bit vector.

Get sorted values

- double [get_best_value](#) (int i) const
Get best value.
- double [get_best_value](#) () const
Get best value.

Evaluation and sorting

- void [eval](#) (function::Function *function)
Evaluate the population.
- void [eval](#) (const std::vector< [function::Function](#) *> &functions)
Parallel evaluation of the population.
- void [sort](#) ()
Sort the lookup table.
- void [partial_sort](#) (int selection_size)
Partially sort the lookup table.

Selection

- void [plus_selection](#) (const [Population](#) &offsprings)
Plus selection.
- void [comma_selection](#) (const [Population](#) &offsprings)
Comma selection.

Public Attributes

- std::function< bool(const [index_value_t](#) &, const [index_value_t](#) &)> [_operator](#)
Binary operator for comparing index-value pairs.

Protected Attributes

- std::vector< [bit_vector_t](#) > [_bvs](#)
Bit vectors.
- std::vector< [index_value_t](#) > [_lookup](#)
Lookup table.

5.68.1 Detailed Description

[Population](#).

Definition at line 35 of file [population.hh](#).

5.68.2 Member Function Documentation

5.68.2.1 comma_selection()

```
void comma_selection (
    const Population & offsprings )
```

Comma selection.

Precondition

Offspring population must be sorted.

Warning

The function does not break ties randomly as it should.

Definition at line 108 of file population.cc.

5.68.2.2 get_best_bv() [1/2]

```
const bit_vector_t& get_best_bv (
    int i ) const [inline]
```

Get best bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 89 of file population.hh.

5.68.2.3 get_best_bv() [2/2]

```
const bit_vector_t& get_best_bv ( ) const [inline]
```

Get best bit vector.

Precondition

The population must be sorted.

Definition at line 95 of file population.hh.

5.68.2.4 `get_best_value()` [1/2]

```
double get_best_value (
    int i ) const [inline]
```

Get best value.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 118 of file population.hh.

5.68.2.5 `get_best_value()` [2/2]

```
double get_best_value ( ) const [inline]
```

Get best value.

Precondition

The population must be sorted.

Definition at line 124 of file population.hh.

5.68.2.6 `get_worst_bv()`

```
const bit_vector_t& get_worst_bv (
    int i ) const [inline]
```

Get worst bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 103 of file population.hh.

5.68.2.7 plus_selection()

```
void plus_selection (
    const Population & offsprings )
```

Plus selection.

Precondition

Both populations must be sorted.

Warning

The function does not break ties randomly as it should.

Definition at line 89 of file population.cc.

5.68.3 Member Data Documentation

5.68.3.1 _lookup

```
std::vector<index_value_t> _lookup [protected]
```

Lookup table.

Let p be of type `std::pair<size_t, double>`. Then p.first is the bv index in the unsorted population whereas p.second is the bv value.

Definition at line 57 of file population.hh.

5.68.3.2 _operator

```
std::function<bool(const index_value_t&, const index_value_t&)> _operator
```

Initial value:

```
=
    [](const index_value_t& a, const index_value_t& b) { return a.second > b.
        second; }
```

Binary operator for comparing index-value pairs.

Definition at line 43 of file population.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/population.hh
- lib/hnco/algorithms/population.cc

5.69 PriorNoise Class Reference

Prior noise.

```
#include <hnco/functions/decorators/prior-noise.hh>
```

Inheritance diagram for PriorNoise:



Public Member Functions

- [PriorNoise](#) ([Function](#) *fn, [neighborhood::Neighborhood](#) *nh)
Constructor.

Information about the function

- [size_t](#) [get_bv_size](#) ()
Get bit vector size.
- [double](#) [get_maximum](#) ()
Get the global maximum.
- [bool](#) [has_known_maximum](#) ()
Check for a known maximum.
- [bool](#) [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- [double](#) [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- [neighborhood::Neighborhood](#) * [_neighborhood](#)
Neighborhood.
- [bit_vector_t](#) [_noisy_bv](#)
Noisy bit vector.

Additional Inherited Members

5.69.1 Detailed Description

Prior noise.

Definition at line 35 of file prior-noise.hh.

5.69.2 Member Function Documentation

5.69.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Delegation is questionable here.

Reimplemented from [Function](#).

Definition at line 67 of file prior-noise.hh.

5.69.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Delegation is questionable here.

Reimplemented from [Function](#).

Definition at line 73 of file prior-noise.hh.

5.69.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented from [Function](#).

Definition at line 77 of file prior-noise.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/prior-noise.hh
- lib/hnco/functions/decorators/prior-noise.cc

5.70 ProgressTracker Class Reference

[ProgressTracker](#).

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for ProgressTracker:



Classes

- struct [Event](#)
Event.

Public Member Functions

- [ProgressTracker](#) ([Function](#) *function)
Constructor.
- const [Event](#) & [get_last_improvement](#) ()
Get the last improvement.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↔
_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Setters

- void [set_log_improvement](#) (bool x)
Log improvement.
- void [set_stream](#) (std::ostream *x)
Output stream.

Protected Member Functions

- void [update_last_improvement](#) (double value)
Update last improvement.

Protected Attributes

- [Event_last_improvement](#)
Last improvement.

Parameters

- bool [_log_improvement](#) = false
Log improvement.
- std::ostream * [_stream](#) = &std::cout
Output stream.

5.70.1 Detailed Description

[ProgressTracker](#).

A [ProgressTracker](#) is a [CallCounter](#) which records the last event, that is the time and value of the last improvement.

Definition at line 212 of file function-controller.hh.

5.70.2 Member Function Documentation

5.70.2.1 eval()

```
double eval (
    const bit_vector_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>MaximumReached</i>	
<i>TargetReached</i>	

Reimplemented from [CallCounter](#).

Definition at line 153 of file function-controller.cc.

5.70.2.2 get_last_improvement()

```
const Event& get_last_improvement ( ) [inline]
```

Get the last improvement.

Warning

If `_last_improvement.time` is zero then `_function` has never been called. The [Event](#) returned by `get_last_improvement` has therefore no meaning.

Definition at line 288 of file function-controller.hh.

5.70.2.3 incremental_eval()

```
double incremental_eval (
    const bit_vector_t & x,
    double value,
    const hnco::sparse_bit_vector_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>MaximumReached</i>	
<i>TargetReached</i>	

Reimplemented from [CallCounter](#).

Definition at line 172 of file function-controller.cc.

5.70.2.4 update()

```
void update (
    const bit\_vector\_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>MaximumReached</i>	
<i>TargetReached</i>	

Reimplemented from [CallCounter](#).

Definition at line 191 of file function-controller.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.71 PvAlgorithm Class Reference

Probability vector algorithm.

```
#include <hnco/algorithms/pv/pv-algorithm.hh>
```

Inheritance diagram for PvAlgorithm:



Public Types

- enum { [LOG_PV](#), [LOG_ENTROPY](#), [LAST_LOG](#) }
- typedef std::bitset< LAST_LOG > [log_flags_t](#)

Public Member Functions

- [PvAlgorithm](#) (int n)
Constructor.
- void [set_log_flags](#) (const [log_flags_t](#) &lf)
Set log flags.

Setters

- void [set_log_num_components](#) (int x)
Set the number of probability vector components to log.

Protected Member Functions

- void [log](#) ()
Log.

Protected Attributes

- [pv_t _pv](#)
Probability vector.
- double [_lower_bound](#)
Lower bound of probability.
- double [_upper_bound](#)
Upper bound of probability.
- [log_flags_t _log_flags](#)
Log flags.

Parameters

- int [_log_num_components](#) = 5
Number of probability vector components to log.

5.71.1 Detailed Description

Probability vector algorithm.

Definition at line 34 of file pv-algorithm.hh.

5.71.2 Member Enumeration Documentation

5.71.2.1 anonymous enum

anonymous enum

Enumerator

LOG_PV	Log probability vector.
LOG_ENTROPY	Log entropy.

Definition at line 39 of file pv-algorithm.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/pv/pv-algorithm.hh
- lib/hnco/algorithms/pv/pv-algorithm.cc

5.72 Qubo Class Reference

Quadratic unconstrained binary optimization.

```
#include <hnco/functions/qubo.hh>
```

Inheritance diagram for Qubo:



Public Member Functions

- [Qubo](#) ()
Constructor.
- void [load](#) (std::istream &stream)
Load an instance.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- std::vector< std::vector< double > > [_q](#)
Matrix.

5.72.1 Detailed Description

Quadratic unconstrained binary optimization.

Its expression is of the form $f(x) = \sum_i Q_{ii}x_i + \sum_{i < j} Q_{ij}x_ix_j = x^T Qx$, where Q is an n x n upper-triangular matrix.

[Qubo](#) is the problem addressed by qbsolv. Here is its description as given on github:

Qbsolv, a decomposing solver, finds a minimum value of a large quadratic unconstrained binary optimization (QUBO) problem by splitting it into pieces solved either via a D-Wave system or a classical tabu solver.

There are some differences between [WalshExpansion2](#) and [Qubo](#):

- [WalshExpansion2](#) maps 0/1 variables into -1/1 variables whereas [Qubo](#) directly deals with binary variables.
- Hence, there is a separate linear part in [WalshExpansion2](#) whereas the linear part in [Qubo](#) stems from the diagonal elements of the given matrix.

qbsolv aims at minimizing quadratic functions whereas hnco algorithms aim at maximizing them. Hence [Qubo::load](#) negates all elements so that maximizing the resulting function is equivalent to minimizing the original [Qubo](#).

References:

Michael Booth, Steven P. Reinhardt, and Aidan Roy. 2017. Partitioning Optimization Problems for Hybrid Classical/Quantum Execution. Technical Report. D-Wave.

<https://github.com/dwavesystems/qbsolv>

<http://people.brunel.ac.uk/~mastjjb/jeb/orlib/bqpinfo.html>

Definition at line 74 of file qubo.hh.

5.72.2 Member Function Documentation

5.72.2.1 load()

```
void load (
    std::istream & stream )
```

Load an instance.

Exceptions

<i>Error</i>	
--------------	--

Definition at line 36 of file qubo.cc.

5.72.3 Member Data Documentation

5.72.3.1 `_q`

```
std::vector<std::vector<double> > _q [private]
```

Matrix.

$n \times n$ upper triangular matrix.

Definition at line 83 of file qubo.hh.

The documentation for this class was generated from the following files:

- lib/hnco/functions/qubo.hh
- lib/hnco/functions/qubo.cc

5.73 Random Struct Reference

[Random](#) numbers.

```
#include <hnco/random.hh>
```

Static Public Member Functions

- static double [uniform](#) ()
Next uniformly distributed sample.
- static double [normal](#) ()
Next normally distributed sample.
- static bool [random_bit](#) ()
Next random bit.

Static Public Attributes

- static std::mt19937 [engine](#)
Engine.

5.73.1 Detailed Description

[Random](#) numbers.

Definition at line 33 of file random.hh.

The documentation for this struct was generated from the following files:


- lib/hnco/random.hh
- lib/hnco/random.cc

5.74 RandomLocalSearch Class Reference

Random local search.

```
#include <hnco/algorithms/ls/random-local-search.hh>
```

Inheritance diagram for RandomLocalSearch:



Public Member Functions

- [RandomLocalSearch](#) (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void [init](#) ()
Random initialization.
- void [init](#) (const [bit_vector_t](#) &x)
Explicit initialization.
- void [init](#) (const [bit_vector_t](#) &x, double value)
Explicit initialization.
- const [point_value_t](#) & [get_solution](#) ()
Solution.

Setters

- void [set_operator](#) (std::function< bool(double, double)> x)
Set the binary operator for comparing evaluations.
- void [set_patience](#) (int x)
Set patience.
- void [set_incremental_evaluation](#) (bool x)
Set incremental evaluation.

Protected Member Functions

- void `iterate` ()
Single iteration.
- void `iterate_full` ()
Single iteration with full evaluation.
- void `iterate_incremental` ()
Single iteration with incremental evaluation.

Protected Attributes

- `neighborhood::Neighborhood * _neighborhood`
Neighborhood.
- int `_num_failures`
Number of failure.

Parameters

- `std::function< bool(double, double)> _operator` = `std::greater_equal<double>()`
Binary operator for comparing evaluations.
- int `_patience` = 50
Patience.
- bool `_incremental_evaluation` = false
Incremental evaluation.

5.74.1 Detailed Description

Random local search.

Definition at line 39 of file random-local-search.hh.

5.74.2 Member Function Documentation

5.74.2.1 `set_patience()`

```
void set_patience (
    int x ) [inline]
```

Set patience.

Number of consecutive rejected moves before throwing a LocalMaximum exception

Parameters

<code>x</code>	Patience
----------------	----------

If $x \leq 0$ then patience is considered infinite, meaning that the algorithm will never throw any LocalMaximum exception.

Definition at line 110 of file random-local-search.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ls/random-local-search.hh
- lib/hnco/algorithms/ls/random-local-search.cc

5.75 RandomSearch Class Reference

Random search.

```
#include <hnco/algorithms/random-search.hh>
```

Inheritance diagram for RandomSearch:



Public Member Functions

- [RandomSearch](#) (int n)
Constructor.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [bit_vector_t _candidate](#)
Candidate.

Additional Inherited Members

5.75.1 Detailed Description

Random search.

Definition at line 30 of file random-search.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/random-search.hh
- lib/hnco/algorithms/random-search.cc

5.76 Restart Class Reference

[Restart](#).

```
#include <hnco/algorithms/restart.hh>
```

Inheritance diagram for Restart:



Public Member Functions

- [Restart](#) (int n, [Algorithm](#) *algorithm)
Constructor.
- void [set_function](#) (function::Function *function)
Set function.
- void [set_functions](#) (const std::vector< [function::Function](#) *> functions)
Set functions.

Private Member Functions

- void [iterate](#) ()
Optimize.

Private Attributes

- [Algorithm](#) * [_algorithm](#)
Algorithm.

Additional Inherited Members

5.76.1 Detailed Description

[Restart](#).

[Restart](#) an [Algorithm](#) an indefinite number of times. Should be used in conjunction with `OnBudgetFunction` or `StopOnMaximum`.

Definition at line 38 of file `restart.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/restart.hh`
- `lib/hnco/algorithms/restart.cc`

5.77 Ridge Class Reference

[Ridge](#).

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for [Ridge](#):



Public Member Functions

- [Ridge](#) (int bv_size)
Constructor.
- [size_t get_bv_size](#) ()
Get bit vector size.
- [double eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- [bool has_known_maximum](#) ()
Check for a known maximum.
- [double get_maximum](#) ()
Get the global maximum.

Private Attributes

- [size_t _bv_size](#)
Bit vector size.

5.77.1 Detailed Description

[Ridge](#).

Reference:

Thomas Jansen. 2013. Analyzing Evolutionary Algorithms. Springer.

Definition at line 203 of file theory.hh.

5.77.2 Member Function Documentation

5.77.2.1 [get_maximum\(\)](#)

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$2 * \text{_bv_size}$

Reimplemented from [Function](#).

Definition at line 227 of file theory.hh.

5.77.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 223 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.78 SimulatedAnnealing Class Reference

Simulated annealing.

```
#include <hnco/algorithms/ls/simulated-annealing.hh>
```

Inheritance diagram for SimulatedAnnealing:



Public Member Functions

- [SimulatedAnnealing](#) (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_num_transitions](#) (int x)
Set the number of accepted transitions before annealing.
- void [set_num_trials](#) (int x)
Set the Number of trials.
- void [set_initial_acceptance_probability](#) (double x)
Set the initial acceptance probability.
- void [set_beta_ratio](#) (double x)
Set ratio for beta.

Private Member Functions

- void [init_beta](#) ()
Initialize beta.
- void [iterate](#) ()
Single iteration.

Private Attributes

- [neighborhood::Neighborhood](#) * [_neighborhood](#)
Neighborhood.
- double [_beta](#)
Inverse temperature.
- double [_current_value](#)
Current value.
- int [_transitions](#)
Number of accepted transitions.

Parameters

- int [_num_transitions](#) = 50
Number of accepted transitions before annealing.
- int [_num_trials](#) = 100
Number of trials.
- double [_initial_acceptance_probability](#) = 0.6
Initial acceptance probability.
- double [_beta_ratio](#) = 1.2
Ratio for beta.

Additional Inherited Members

5.78.1 Detailed Description

Simulated annealing.

Reference:

S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. 1983. Optimization by simulated annealing. Science 220, 4598 (May 1983), 671–680.

Definition at line 44 of file simulated-annealing.hh.

5.78.2 Member Function Documentation

5.78.2.1 init_beta()

```
void init_beta ( ) [private]
```

Initialize beta.

Requires (2 * _num_trials) evaluations. This should be taken into account when using OnBudgetFunction.

Definition at line 34 of file simulated-annealing.cc.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ls/simulated-annealing.hh
- lib/hnco/algorithms/ls/simulated-annealing.cc

5.79 SingleBitFlip Class Reference

One bit neighborhood.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for SingleBitFlip:



Public Member Functions

- [SingleBitFlip](#) (int n)
Constructor.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.

Additional Inherited Members

5.79.1 Detailed Description

One bit neighborhood.

Definition at line 160 of file neighborhood.hh.

The documentation for this class was generated from the following file:


- lib/hnco/neighborhoods/neighborhood.hh

5.80 SingleBitFlipIterator Class Reference

Single bit flip neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for SingleBitFlipIterator:



Public Member Functions

- [SingleBitFlipIterator](#) (int n)
Constructor.
- void [init](#) ()
Initialization.
- bool [has_next](#) ()
Has next bit vector.
- void [next](#) ()
Next bit vector.

Private Attributes

- size_t [__index](#)
Index of the last flipped bit.

Additional Inherited Members

5.80.1 Detailed Description

Single bit flip neighborhood iterator.

Definition at line 58 of file neighborhood-iterator.hh.

5.80.2 Constructor & Destructor Documentation

5.80.2.1 SingleBitFlipIterator()

```
SingleBitFlipIterator (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 70 of file neighborhood-iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.81 SinusSummationCancellation Class Reference

Summation cancellation with sinus.

```
#include <hnco/functions/cancellation.hh>
```

Inheritance diagram for SinusSummationCancellation:



Public Member Functions

- [SinusSummationCancellation](#) (int n)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &x)
Evaluate a bit vector.

Additional Inherited Members

5.81.1 Detailed Description

Summation cancellation with sinus.

Reference:

M. Sebag and M. Schoenauer. 1997. A society of hill-climbers. In Proc. IEEE Int. Conf. on Evolutionary Computation. Indianapolis, 319–324.

Definition at line 103 of file cancellation.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/cancellation.hh
- lib/hnco/functions/cancellation.cc

5.82 SixPeaks Class Reference

Six Peaks.

```
#include <hnco/functions/four-peaks.hh>
```

Inheritance diagram for SixPeaks:



Public Member Functions

- `SixPeaks` (int bv_size, int threshold)
Constructor.
- `size_t get_bv_size ()`
Get bit vector size.
- `double eval` (const `bit_vector_t` &)
Evaluate a bit vector.
- `bool has_known_maximum ()`
Check for a known maximum.
- `double get_maximum ()`
Get the global maximum.

Private Attributes

- `size_t _bv_size`
Bit vector size.
- `int _threshold`
Threshold.
- `int _maximum`
Maximum.

5.82.1 Detailed Description

Six Peaks.

It is defined by

$$f(x) = \max\{\text{head}(x, 0) + \text{tail}(x, 1) + \text{head}(x, 1) + \text{tail}(x, 0)\} + R(x)$$

where:

- $\text{head}(x, 0)$ is the length of the longest prefix of x made of zeros;
- $\text{head}(x, 1)$ is the length of the longest prefix of x made of ones;
- $\text{tail}(x, 0)$ is the length of the longest suffix of x made of zeros;
- $\text{tail}(x, 1)$ is the length of the longest suffix of x made of ones;
- $R(x)$ is the reward;
- $R(x) = n$ if $(\text{head}(x, 0) > t \text{ and } \text{tail}(x, 1) > t) \text{ or } (\text{head}(x, 1) > t \text{ and } \text{tail}(x, 0) > t)$;
- $R(x) = 0$ otherwise;
- the threshold t is a parameter of the function.

This function has six maxima, of which exactly four are global ones.

For example, if $n = 6$ and $t = 1$:

- $f(111111) = 6$ (local maximum)
- $f(111110) = 5$
- $f(111100) = 10$ (global maximum)

Reference:

J. S. De Bonet, C. L. Isbell, and P. Viola. 1996. MIMIC: finding optima by estimating probability densities. In *Advances in Neural Information Processing Systems*. Vol. 9. MIT Press, Denver.

Definition at line 128 of file four-peaks.hh.

5.82.2 Member Function Documentation

5.82.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$2 * _bv_size - _threshold - 1$

Reimplemented from [Function](#).

Definition at line 159 of file four-peaks.hh.

5.82.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 155 of file four-peaks.hh.

The documentation for this class was generated from the following files:

- lib/hnco/functions/four-peaks.hh
- lib/hnco/functions/four-peaks.cc

5.83 SpinHerding Class Reference

Herding with spin variables.

```
#include <hnco/algorithms/hea/herding-spin.hh>
```

Public Types

- enum {
 [SAMPLE_GREEDY](#), [SAMPLE_RLS](#), [SAMPLE_DLS](#), [SAMPLE_NN](#),
 [LAST_SAMPLE](#) }

Public Member Functions

- [SpinHerding](#) (int n)
 Constructor.
- void [init](#) ()
 Initialization.
- void [sample](#) (const [SpinMoment](#) &target, [bit_vector_t](#) &x)
 Sample a bit vector.
- double [error](#) (const [SpinMoment](#) &target)
 Compute the error.
- double [delta](#) (const [SpinMoment](#) &target)
 Compute the norm of the moment increment.

Setters

- void [set_randomize_bit_order](#) (bool x)
 Randomize bit order.
- void [set_sampling_method](#) (int x)
 Set the sampling method.
- void [set_num_seq_updates](#) (int x)
 Set the number of sequential updates per sample.
- void [set_num_par_updates](#) (int x)
 Set the number of parallel updates per sample.
- void [set_weight](#) (double x)
 Set the weight of second order moments.

Protected Member Functions

- void `compute_delta` (const `SpinMoment` &target)
Compute delta.
- void `sample_greedy` (`bit_vector_t` &x)
Sample by means of a greedy algorithm.
- double `q_derivative` (const `bit_vector_t` &x, size_t i)
Derivative of q.
- double `q_variation` (const `bit_vector_t` &x, size_t i)
Variation of q.
- void `sample_rls` (`bit_vector_t` &x)
Sample by means of random local search.
- void `sample_dls` (`bit_vector_t` &x)
Sample by means of deterministic local search.
- void `sample_nn` (`bit_vector_t` &x)
Sample by means of a neural network.
- void `update_counters` (const `bit_vector_t` &x)
Update counters.

Protected Attributes

- `SpinMoment_delta`
Delta moment.
- `SpinMoment_count`
Counter moment.
- `bit_vector_t_state`
State.
- `permutation_t_permutation`
Permutation.
- `std::uniform_int_distribution< int > _choose_bit`
Choose bit.
- `int _time`
Time.

Parameters

- `bool _randomize_bit_order` = false
Randomize bit order.
- `int _sampling_method` = `SAMPLE_GREEDY`
Sampling method.
- `int _num_seq_updates`
Number of sequential updates per sample.
- `int _num_par_updates` = 1
Number of parallel updates per sample.
- `double _weight` = 1
Weight of second order moments.

5.83.1 Detailed Description

Herding with spin variables.

By spin variables, we mean variables taking values 1 or -1, instead of 0 or 1 in the case of binary variables.

Definition at line 37 of file `herding-spin.hh`.

5.83.2 Member Enumeration Documentation

5.83.2.1 anonymous enum

anonymous enum

Enumerator

SAMPLE_GREEDY	Greedy algorithm.
SAMPLE_RLS	Random local search.
SAMPLE_DLS	Deterministic local search.
SAMPLE_NN	Neural network.

Definition at line 109 of file herding-spin.hh.

5.83.3 Constructor & Destructor Documentation

5.83.3.1 SpinHerdng()

```
SpinHerdng (
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

_num_seq_updates is initialized to n.

Definition at line 131 of file herding-spin.hh.

5.83.4 Member Function Documentation

5.83.4.1 q_variation()

```
double q_variation (
    const bit_vector_t & x,
    size_t i ) [protected]
```

Variation of q .

Up to a positive multiplicative constant. Only the sign of the variation matters to local search.

Definition at line 155 of file herding-spin.cc.

The documentation for this class was generated from the following files:

- lib/hnco/algorithms/hea/herding-spin.hh
- lib/hnco/algorithms/hea/herding-spin.cc

5.84 SpinMoment Struct Reference

Moment for spin variables.

```
#include <hnco/algorithms/hea/moment-spin.hh>
```

Public Member Functions

- [SpinMoment](#) (int n)
Constructor.
- void [uniform](#) ()
Set the moment to that of the uniform distribution.
- void [init](#) ()
Initialize accumulators.
- void [add](#) (const [bit_vector_t](#) &x)
Update accumulators.
- void [average](#) (int count)
Compute average.
- void [update](#) (const [SpinMoment](#) &p, double rate)
Update moment.
- void [bound](#) (double margin)
Bound moment.
- double [distance](#) (const [SpinMoment](#) &p) const
Distance.
- double [norm_2](#) () const
Compute the norm 2.
- double [diameter](#) () const
Compute the diameter.
- [size_t](#) [size](#) () const
Size.

Public Attributes

- [std::vector< double > _first](#)
First moment.
- [std::vector< std::vector< double > > _second](#)
Second moment.
- double [_weight](#) = 1
Weight of second order moments.

5.84.1 Detailed Description

Moment for spin variables.

Definition at line 35 of file moment-spin.hh.

The documentation for this struct was generated from the following files:


- lib/hnco/algorithms/hea/moment-spin.hh
- lib/hnco/algorithms/hea/moment-spin.cc

5.85 SteepestAscentHillClimbing Class Reference

Steepest ascent hill climbing.

```
#include <hnco/algorithms/ls/steepest-ascent-hill-climbing.hh>
```

Inheritance diagram for SteepestAscentHillClimbing:



Public Member Functions

- [SteepestAscentHillClimbing](#) (int n, [neighborhood::NeighborhoodIterator](#) *neighborhood)
Constructor.
- void [init](#) ()
Random initialization.
- void [init](#) (const [bit_vector_t](#) &x)
Explicit initialization.
- void [init](#) (const [bit_vector_t](#) &x, double value)
Explicit initialization.

Protected Member Functions

- void `iterate()`
Single iteration.

Protected Attributes

- `std::vector< bit_vector_t > _candidates`
Potential candidate.
- `neighborhood::NeighborhoodIterator * _neighborhood`
Neighborhood.

5.85.1 Detailed Description

Steepest ascent hill climbing.

Definition at line 39 of file `steepest-ascent-hill-climbing.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ls/steepest-ascent-hill-climbing.hh`
- `lib/hnco/algorithms/ls/steepest-ascent-hill-climbing.cc`

5.86 StopOnMaximum Class Reference

Stop on maximum.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for StopOnMaximum:



Public Member Functions

- [StopOnMaximum](#) ([Function](#) *function)
Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↵_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Additional Inherited Members

5.86.1 Detailed Description

Stop on maximum.

The [eval\(\)](#) member function throws a MaximumReached exception when its argument maximizes the decorated function.

Definition at line 98 of file function-controller.hh.

5.86.2 Constructor & Destructor Documentation

5.86.2.1 StopOnMaximum()

```
StopOnMaximum (
    Function * function ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
-----------------	--------------------

Precondition

function->[has_known_maximum\(\)](#)

Definition at line 106 of file function-controller.hh.

5.86.3 Member Function Documentation

5.86.3.1 eval()

```
double eval (
    const bit\_vector\_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>MaximumReached</i>	
-----------------------	--

Implements [Function](#).

Definition at line 31 of file function-controller.cc.

5.86.3.2 incremental_eval()

```
double incremental_eval (
    const bit\_vector\_t & x,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>MaximumReached</i>	
-----------------------	--

Reimplemented from [Function](#).

Definition at line 43 of file function-controller.cc.

5.86.3.3 update()

```
void update (
    const bit\_vector\_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>MaximumReached</i>	
-----------------------	--

Reimplemented from [Function](#).

Definition at line 55 of file function-controller.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.87 StopOnTarget Class Reference

Stop on target.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for StopOnTarget:



Public Member Functions

- [StopOnTarget](#) ([Function](#) *function, double target)
Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped, [_bits](#))
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Private Attributes

- double `_target`
Target.

Additional Inherited Members

5.87.1 Detailed Description

Stop on target.

Definition at line 134 of file function-controller.hh.

5.87.2 Constructor & Destructor Documentation

5.87.2.1 StopOnTarget()

```
StopOnTarget (
    Function * function,
    double target ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
-----------------	--------------------

Definition at line 144 of file function-controller.hh.

5.87.3 Member Function Documentation

5.87.3.1 eval()

```
double eval (
    const bit_vector_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>TargetReached</i>	
----------------------	--

Implements [Function](#).

Definition at line 66 of file function-controller.cc.

5.87.3.2 incremental_eval()

```
double incremental_eval (
    const bit\_vector\_t & x,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>TargetReached</i>	
----------------------	--

Reimplemented from [Function](#).

Definition at line 76 of file function-controller.cc.

5.87.3.3 update()

```
void update (
    const bit\_vector\_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>TargetReached</i>	
----------------------	--

Reimplemented from [Function](#).

Definition at line 86 of file function-controller.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.88 SummationCancellation Class Reference

Summation cancellation.

```
#include <hnco/functions/cancellation.hh>
```

Inheritance diagram for SummationCancellation:



Public Member Functions

- [SummationCancellation](#) (int n)
Constructor.
- `size_t` [get_bv_size](#) ()
Get bit vector size.
- `double` [eval](#) (const `bit_vector_t` &x)
Evaluate a bit vector.
- `bool` [has_known_maximum](#) ()
Check for a known maximum.
- `double` [get_maximum](#) ()
Get the global maximum.

Protected Member Functions

- `void` [convert](#) (const `bit_vector_t` &x)
Convert a bit vector into a real vector.

Protected Attributes

- `size_t` [_bv_size](#)
Bit vector size.
- `std::vector< double >` [_buffer](#)
Buffer.

5.88.1 Detailed Description

Summation cancellation.

Encoding of a signed integer:

- bit 0: sign
- bits 1 to 8: two's complement representation

Reference:

S. Baluja and S. Davies. 1997. Using optimal dependency-trees for combinatorial optimization: learning the structure of the search space. Technical Report CMU- CS-97-107. Carnegie-Mellon University.

Definition at line 47 of file cancellation.hh.

5.88.2 Constructor & Destructor Documentation

5.88.2.1 SummationCancellation()

```
SummationCancellation (
    int n ) [inline]
```

Constructor.

The bit vector size n must be a multiple of 9. The size of `_buffer` is then $n / 9$.

Parameters

n	Size of the bit vector
-----	------------------------

Definition at line 70 of file cancellation.hh.

5.88.3 Member Function Documentation

5.88.3.1 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 86 of file cancellation.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/cancellation.hh
- lib/hnco/functions/cancellation.cc

5.89 TargetReached Class Reference

target reached

```
#include <hnco/exception.hh>
```

Inheritance diagram for TargetReached:

**Public Member Functions**

- [TargetReached](#) (const [point_value_t](#) &pv)
Constructor.

Additional Inherited Members

5.89.1 Detailed Description

target reached

Definition at line 61 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.90 TournamentSelection Class Reference

[Population](#) with tournament selection.

```
#include <hnco/algorithms/ea/tournament-selection.hh>
```

Inheritance diagram for TournamentSelection:



Public Member Functions

- [TournamentSelection](#) (int population_size, int n)
Constructor.
- const [bit_vector_t](#) & [select](#) ()
Selection.

Setters

- void [set_tournament_size](#) (int x)
Set the tournament size.

Private Attributes

- std::uniform_int_distribution< int > [_choose_individual](#)
Random index.

Parameters

- int [_tournament_size](#) = 10
Tournament size.

Additional Inherited Members

5.90.1 Detailed Description

[Population](#) with tournament selection.

Definition at line 34 of file tournament-selection.hh.

5.90.2 Member Function Documentation

5.90.2.1 select()

```
const bit_vector_t & select ( )
```

Selection.

The selection only requires that the population be evaluated, not necessarily sorted.

Precondition

The population must be evaluated.

Definition at line 33 of file tournament-selection.cc.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/tournament-selection.hh
- lib/hnco/algorithms/ea/tournament-selection.cc

5.91 Translation Class Reference

[Translation.](#)

```
#include <hnco/map.hh>
```

Inheritance diagram for Translation:



Public Member Functions

- void [random](#) (int n)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.
- [size_t](#) [get_input_size](#) ()
Get input size.
- [size_t](#) [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_vector_t](#) [_bv](#)
Translation vector.

Friends

- class **boost::serialization::access**

5.91.1 Detailed Description

[Translation](#).

A translation is an affine map f from Z_2^n to itself defined by $f(x) = x + b$, where b is an n -dimensional bit vector.

Definition at line 70 of file map.hh.

5.91.2 Member Function Documentation

5.91.2.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 121 of file map.hh.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.92 Trap Class Reference

[Trap](#).

```
#include <hnco/functions/trap.hh>
```

Inheritance diagram for Trap:



Public Member Functions

- [Trap](#) (int bv_size, int num_traps)
Constructor.
- size_t [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- `size_t _bv_size`
Bit vector size.
- `int _num_traps`
Number of traps.
- `int _trap_size`
Trap size.

5.92.1 Detailed Description

Trap.

Reference:

Kalyanmoy Deb and David E. Goldberg. 1993. Analyzing Deception in Trap Functions. In Foundations of Genetic Algorithms 2, L. Darrell Whitley (Ed.). Morgan Kaufmann, San Mateo, CA, 93–108.

Definition at line 43 of file trap.hh.

5.92.2 Constructor & Destructor Documentation

5.92.2.1 Trap()

```
Trap (
    int bv_size,
    int num_traps ) [inline]
```

Constructor.

Parameters

<i>bv_size</i>	Bit vector size
<i>num_traps</i>	Number of traps

Warning

`bv_size` must be a multiple of `num_traps`

Definition at line 64 of file trap.hh.

5.92.3 Member Function Documentation

5.92.3.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 88 of file trap.hh.

5.92.3.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 84 of file trap.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/trap.hh`
- `lib/hnco/functions/trap.cc`

5.93 Umda Class Reference

Univariate marginal distribution algorithm.

```
#include <hnco/algorithms/pv/umda.hh>
```

Inheritance diagram for Umda:



Public Member Functions

- [Umda](#) (int n, int population_size)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_selection_size](#) (int x)
Set the selection size.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [Population_population](#)
Population.
- [pv_t_mean](#)
Mean of selected bit vectors.

Parameters

- int [_selection_size](#) = 1
Selection size.

Additional Inherited Members

5.93.1 Detailed Description

Univariate marginal distribution algorithm.

Reference:

H. Mühlenbein. 1997. The equation for response to selection and its use for prediction. *Evolutionary Computation* 5, 3 (1997), 303–346.

Definition at line 40 of file `umda.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/pv/umda.hh`
- `lib/hnco/algorithms/pv/umda.cc`

5.94 UniformCrossover Class Reference

Uniform crossover.

```
#include <hnco/algorithms/ea/crossover.hh>
```

Inheritance diagram for `UniformCrossover`:



Public Member Functions

- void `breed` (const `bit_vector_t` &parent1, const `bit_vector_t` &parent2, `bit_vector_t` &offspring)
Breed.

5.94.1 Detailed Description

Uniform crossover.

Definition at line 56 of file `crossover.hh`.

5.94.2 Member Function Documentation

5.94.2.1 breed()

```
void breed (
    const bit\_vector\_t & parent1,
    const bit\_vector\_t & parent2,
    bit\_vector\_t & offspring ) [virtual]
```

Breed.

The offspring is the uniform crossover of two parents.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implements [Crossover](#).

Definition at line 30 of file `crossover.cc`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ea/crossover.hh`
- `lib/hnco/algorithms/ea/crossover.cc`

5.95 WalshExpansion Class Reference

Walsh expansion.

```
#include <hnco/functions/walsh/walsh-expansion.hh>
```

Inheritance diagram for WalshExpansion:



Public Member Functions

- [WalshExpansion](#) ()
Constructor.
- `size_t` [get_bv_size](#) ()
Get bit vector size.
- `void` [random](#) (int n, int num_features, double stddev)
Random instance.
- `double` [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- `void` [display](#) (std::ostream &stream)
Display.

Private Member Functions

- `template<class Archive >`
`void` [save](#) (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
`void` [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [hnco::bit_matrix_t_features](#)
Features.
- `std::vector< double >` [_coefficients](#)
Coefficients.
- [bit_vector_t_image](#)
Image of bit vectors under the feature matrix.

Friends

- `class` **boost::serialization::access**

5.95.1 Detailed Description

Walsh expansion.

Its expression is of the form

$$f(x) = \sum_u a_u (-1)^{x \cdot u}$$

where the sum is over a subset of $\{0, 1\}^n$ and $x \cdot u = \sum_i x_i u_i$ is mod 2. The real numbers a_u are the coefficients of the expansion and the bit vectors u are its feature vectors.

Definition at line 53 of file walsh-expansion.hh.

5.95.2 Member Function Documentation

5.95.2.1 random()

```
void random (
    int n,
    int num_features,
    double stddev )
```

Random instance.

Parameters

<i>n</i>	Size of bit vector
<i>num_features</i>	Number of feature vectors
<i>stddev</i>	Standard deviation of the coefficients

Definition at line 34 of file walsh-expansion.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/walsh/walsh-expansion.hh
- lib/hnco/functions/walsh/walsh-expansion.cc

5.96 WalshExpansion1 Class Reference

Walsh expansion of degree 1.

```
#include <hnco/functions/walsh/walsh-expansion-1.hh>
```

Inheritance diagram for WalshExpansion1:



Public Member Functions

- [WalshExpansion1](#) ()
Constructor.
- `size_t` [get_bv_size](#) ()
Get bit vector size.
- `void` [random](#) (int n, double stddev)
Random instance.
- `double` [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Member Functions

- `template<class Archive >`
`void` [serialize](#) (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- `std::vector< double >` [_linear](#)
Linear part.

Friends

- `class` **boost::serialization::access**

5.96.1 Detailed Description

Walsh expansion of degree 1.

Its expression is of the form

$$f(x) = \sum_i a_i (1 - 2x_i)$$

or equivalently

$$f(x) = \sum_i a_i (-1)^{x_i}$$

Definition at line 50 of file walsh-expansion-1.hh.

5.96.2 Member Function Documentation

5.96.2.1 random()

```
void random (
    int n,
    double stddev )
```

Random instance.

Parameters

<i>n</i>	Size of bit vector
<i>stddev</i>	Standard deviation of the coefficients

Definition at line 33 of file walsh-expansion-1.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/walsh/walsh-expansion-1.hh
- lib/hnco/functions/walsh/walsh-expansion-1.cc

5.97 WalshExpansion2 Class Reference

Walsh expansion of degree 2.

```
#include <hnco/functions/walsh/walsh-expansion-2.hh>
```

Inheritance diagram for WalshExpansion2:



Public Member Functions

- [WalshExpansion2](#) ()
Constructor.
- [size_t get_bv_size](#) ()
Get bit vector size.
- [void random](#) (int n, double stddev_lin, double stddev_quad)
Random instance.
- [double eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Member Functions

- `template<class Archive >`
`void serialize (Archive &ar, const unsigned int version)`
Serialize.

Private Attributes

- `std::vector< double > _linear`
Linear part.
- `std::vector< std::vector< double > > _quadratic`
Quadratic part.

Friends

- class `boost::serialization::access`

5.97.1 Detailed Description

Walsh expansion of degree 2.

Its expression is of the form

$$f(x) = \sum_i a_i (1 - 2x_i) + \sum_{i < j} a_{ij} (1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_i a_i (-1)^{x_i} + \sum_{i < j} a_{ij} (-1)^{x_i + x_j}$$

where the sum $x_i + x_j$ is mod 2 (xor).

Definition at line 52 of file `walsh-expansion-2.hh`.

5.97.2 Member Function Documentation

5.97.2.1 `random()`

```
void random (
    int n,
    double stddev_lin,
    double stddev_quad )
```

Random instance.

Parameters

<i>n</i>	Size of bit vector
<i>stddev_lin</i>	Standard deviation of the coefficients of the linear part
<i>stddev_quad</i>	Standard deviation of the coefficients of the quadratic part

Definition at line 33 of file `walsh-expansion-2.cc`.

5.97.3 Member Data Documentation

5.97.3.1 `_quadratic`

```
std::vector<std::vector<double> > _quadratic [private]
```

Quadratic part.

Represented as a lower triangular matrix (without its diagonal).

Definition at line 75 of file walsh-expansion-2.hh.

The documentation for this class was generated from the following files:

- lib/hnco/functions/walsh/walsh-expansion-2.hh
- lib/hnco/functions/walsh/walsh-expansion-2.cc

Index

- `_expression`
 - `hnco::function::MaxSat`, [107](#)
 - `_functions`
 - `hnco::algorithm::Algorithm`, [30](#)
 - `_lookup`
 - `hnco::algorithm::Population`, [150](#)
 - `_operator`
 - `hnco::algorithm::Population`, [150](#)
 - `_q`
 - `hnco::function::Qubo`, [160](#)
 - `_quadratic`
 - `hnco::function::WalshExpansion2`, [203](#)
- `AdditiveGaussianNoise`, [25](#)
- `AffineMap`, [27](#)
- `Algorithm`, [28](#)
- `bernoulli_trials`
 - `hnco::neighborhood::MultiBitFlip`, [114](#)
- `BernoulliProcess`, [31](#)
 - `hnco::neighborhood::BernoulliProcess`, [32](#)
- `BiasedCrossover`, [34](#)
- `BinaryHerding`, [35](#)
- `BinaryMoment`, [37](#)
- `bit_t`
 - `hnco`, [14](#)
- `bm_add_rows`
 - `hnco`, [15](#)
- `bm_identity`
 - `hnco`, [15](#)
- `bm_invert`
 - `hnco`, [15](#)
- `bm_multiply`
 - `hnco`, [16](#)
- `bm_solve`
 - `hnco`, [16](#)
- `bm_solve_upper_triangular`
 - `hnco`, [17](#)
- `BmPbil`, [38](#)
- `breed`
 - `hnco::algorithm::BiasedCrossover`, [34](#)
 - `hnco::algorithm::Crossover`, [49](#)
 - `hnco::algorithm::UniformCrossover`, [197](#)
- `Cache`, [42](#)
 - `hnco::function::Cache`, [43](#)
- `CallCounter`, [44](#)
- `comma_selection`
 - `hnco::algorithm::Population`, [147](#)
- `CompactGa`, [45](#)
- `CompleteSearch`, [47](#)
- `Crossover`, [48](#)
- `DeceptiveJump`, [49](#)
- `EqualProducts`, [51](#)
- `Error`, [53](#)
- `eval`
 - `hnco::function::OnBudgetFunction`, [132](#)
 - `hnco::function::ProgressTracker`, [155](#)
 - `hnco::function::StopOnMaximum`, [182](#)
 - `hnco::function::StopOnTarget`, [184](#)
- `Exception`, [54](#)
- `Factorization`, [55](#)
 - `hnco::function::Factorization`, [56](#)
- `FourPeaks`, [57](#)
- `Function`, [59](#)
- `FunctionController`, [63](#)
- `FunctionDecorator`, [64](#)
- `FunctionMapComposition`, [65](#)
 - `hnco::function::FunctionMapComposition`, [66](#)
- `FunctionModifier`, [68](#)
- `FunctionPlugin`, [69](#)
 - `hnco::function::FunctionPlugin`, [70](#)
- `GeneticAlgorithm`, [70](#)
 - `hnco::algorithm::GeneticAlgorithm`, [72](#)
- `get_best_bv`
 - `hnco::algorithm::Population`, [148](#)
- `get_best_value`
 - `hnco::algorithm::Population`, [148](#), [149](#)
- `get_last_improvement`
 - `hnco::function::ProgressTracker`, [155](#)
- `get_maximum`
 - `hnco::function::AdditiveGaussianNoise`, [26](#)
 - `hnco::function::DeceptiveJump`, [50](#)
 - `hnco::function::FourPeaks`, [58](#)
 - `hnco::function::Function`, [61](#)
 - `hnco::function::FunctionMapComposition`, [67](#)
 - `hnco::function::Hiff`, [84](#)
 - `hnco::function::Jump`, [91](#)
 - `hnco::function::LeadingOnes`, [94](#)
 - `hnco::function::Needle`, [119](#)
 - `hnco::function::Negation`, [121](#)
 - `hnco::function::OneMax`, [134](#)
 - `hnco::function::Plateau`, [144](#)
 - `hnco::function::PriorNoise`, [152](#)
 - `hnco::function::Ridge`, [166](#)
 - `hnco::function::SixPeaks`, [174](#)

- hnco::function::Trap, 193
- get_worst_bv
 - hnco::algorithm::Population, 149
- HammingBall, 73
 - hnco::neighborhood::HammingBall, 74
- HammingBallIterator, 75
 - hnco::neighborhood::HammingBallIterator, 76
- HammingSphere, 76
 - hnco::neighborhood::HammingSphere, 78
- has_known_maximum
 - hnco::function::AdditiveGaussianNoise, 26
 - hnco::function::DeceptiveJump, 50
 - hnco::function::FourPeaks, 59
 - hnco::function::FunctionMapComposition, 67
 - hnco::function::Hiff, 84
 - hnco::function::Jump, 91
 - hnco::function::LeadingOnes, 94
 - hnco::function::LinearFunction, 96
 - hnco::function::Needle, 119
 - hnco::function::Negation, 121
 - hnco::function::OneMax, 134
 - hnco::function::Plateau, 144
 - hnco::function::PriorNoise, 152
 - hnco::function::Ridge, 166
 - hnco::function::SixPeaks, 174
 - hnco::function::SummationCancellation, 187
 - hnco::function::Trap, 194
- Hea
 - hnco::algorithm::hea::Hea, 81
- Hea< Moment, Herding >, 78
- Hiff, 83
- hnco, 11
 - bit_t, 14
 - bm_add_rows, 15
 - bm_identity, 15
 - bm_invert, 15
 - bm_multiply, 16
 - bm_solve, 16
 - bm_solve_upper_triangular, 17
 - sbm_multiply, 18
 - sparse_bit_matrix_t, 14
 - sparse_bit_vector_t, 14
- hnco::Hypercubeliterator
 - next, 85
- hnco::Map
 - is_surjective, 101
- hnco::MapComposition
 - is_surjective, 103
 - MapComposition, 103
- hnco::Permutation
 - is_surjective, 142
- hnco::Translation
 - is_surjective, 191
- hnco::algorithm, 18
- hnco::algorithm::Algorithm
 - _functions, 30
- hnco::algorithm::BiasedCrossover
 - breed, 34
- hnco::algorithm::Crossover
 - breed, 49
- hnco::algorithm::GeneticAlgorithm
 - GeneticAlgorithm, 72
 - set_allow_stay, 73
- hnco::algorithm::IterativeAlgorithm
 - IterativeAlgorithm, 87
 - maximize, 87
 - set_num_iterations, 88
- hnco::algorithm::MuCommaLambdaEa
 - MuCommaLambdaEa, 112
 - set_allow_stay, 113
- hnco::algorithm::MuPlusLambdaEa
 - MuPlusLambdaEa, 117
 - set_allow_stay, 117
- hnco::algorithm::OnePlusLambdaCommaLambdaGa
 - OnePlusLambdaCommaLambdaGa, 137
- hnco::algorithm::OnePlusOneEa
 - OnePlusOneEa, 139
 - set_allow_stay, 139
 - set_num_iterations, 139
- hnco::algorithm::Population
 - _lookup, 150
 - _operator, 150
 - comma_selection, 147
 - get_best_bv, 148
 - get_best_value, 148, 149
 - get_worst_bv, 149
 - plus_selection, 149
- hnco::algorithm::RandomLocalSearch
 - set_patience, 162
- hnco::algorithm::SimulatedAnnealing
 - init_beta, 169
- hnco::algorithm::TournamentSelection
 - select, 190
- hnco::algorithm::UniformCrossover
 - breed, 197
- hnco::algorithm::bm_pbil, 20
- hnco::algorithm::bm_pbil::BmPbil
 - set_selection_size, 41
- hnco::algorithm::hea, 21
- hnco::algorithm::hea::Hea
 - Hea, 81
 - set_reset_period, 82
 - set_selection_size, 82
- hnco::algorithm::hea::SpinHerding
 - q_variation, 177
 - SpinHerding, 177
- hnco::exception, 21
- hnco::function, 22
- hnco::function::AdditiveGaussianNoise
 - get_maximum, 26
 - has_known_maximum, 26
- hnco::function::Cache
 - Cache, 43
 - provides_incremental_evaluation, 43
- hnco::function::DeceptiveJump
 - get_maximum, 50

- has_known_maximum, 50
- hnco::function::EqualProducts
 - random, 52
- hnco::function::Factorization
 - Factorization, 56
- hnco::function::FourPeaks
 - get_maximum, 58
 - has_known_maximum, 59
- hnco::function::Function
 - get_maximum, 61
 - incremental_eval, 61
 - provides_incremental_evaluation, 62
 - safe_eval, 62
- hnco::function::FunctionController
 - provides_incremental_evaluation, 64
- hnco::function::FunctionMapComposition
 - FunctionMapComposition, 66
 - get_maximum, 67
 - has_known_maximum, 67
- hnco::function::FunctionPlugin
 - FunctionPlugin, 70
- hnco::function::Hiff
 - get_maximum, 84
 - has_known_maximum, 84
- hnco::function::Jump
 - get_maximum, 91
 - has_known_maximum, 91
- hnco::function::LeadingOnes
 - get_maximum, 94
 - has_known_maximum, 94
- hnco::function::LinearFunction
 - has_known_maximum, 96
 - random, 96
- hnco::function::MaxSat
 - _expression, 107
 - load, 106
 - random, 106
- hnco::function::Needle
 - get_maximum, 119
 - has_known_maximum, 119
- hnco::function::Negation
 - get_maximum, 121
 - has_known_maximum, 121
 - provides_incremental_evaluation, 121
- hnco::function::NkLandscape
 - random, 128
- hnco::function::OnBudgetFunction
 - eval, 132
 - incremental_eval, 132
 - update, 132
- hnco::function::OneMax
 - get_maximum, 134
 - has_known_maximum, 134
 - provides_incremental_evaluation, 135
- hnco::function::Plateau
 - get_maximum, 144
 - has_known_maximum, 144
- hnco::function::PriorNoise
 - get_maximum, 152
 - has_known_maximum, 152
 - provides_incremental_evaluation, 152
- hnco::function::ProgressTracker
 - eval, 155
 - get_last_improvement, 155
 - incremental_eval, 155
 - update, 156
- hnco::function::Qubo
 - _q, 160
 - load, 159
- hnco::function::Ridge
 - get_maximum, 166
 - has_known_maximum, 166
- hnco::function::SixPeaks
 - get_maximum, 174
 - has_known_maximum, 174
- hnco::function::StopOnMaximum
 - eval, 182
 - incremental_eval, 182
 - StopOnMaximum, 181
 - update, 182
- hnco::function::StopOnTarget
 - eval, 184
 - incremental_eval, 185
 - StopOnTarget, 184
 - update, 185
- hnco::function::SummationCancellation
 - has_known_maximum, 187
 - SummationCancellation, 187
- hnco::function::Trap
 - get_maximum, 193
 - has_known_maximum, 194
 - Trap, 193
- hnco::function::WalshExpansion
 - random, 199
- hnco::function::WalshExpansion1
 - random, 200
- hnco::function::WalshExpansion2
 - _quadratic, 203
 - random, 202
- hnco::neighborhood, 23
- hnco::neighborhood::BernoulliProcess
 - BernoulliProcess, 32
 - set_allow_stay, 33
 - set_probability, 33
- hnco::neighborhood::HammingBall
 - HammingBall, 74
- hnco::neighborhood::HammingBallIterator
 - HammingBallIterator, 76
- hnco::neighborhood::HammingSphere
 - HammingSphere, 78
- hnco::neighborhood::MultiBitFlip
 - bernoulli_trials, 114
 - MultiBitFlip, 114
 - reservoir_sampling, 115
- hnco::neighborhood::Neighborhood
 - map, 124

- mutate, [125](#)
- Neighborhood, [124](#)
- hnco::neighborhood::NeighborhoodIterator
 - NeighborhoodIterator, [126](#)
- hnco::neighborhood::SingleBitFlipIterator
 - SingleBitFlipIterator, [171](#)
- hnco::random, [24](#)
- Hypercubeliterator, [84](#)
- incremental_eval
 - hnco::function::Function, [61](#)
 - hnco::function::OnBudgetFunction, [132](#)
 - hnco::function::ProgressTracker, [155](#)
 - hnco::function::StopOnMaximum, [182](#)
 - hnco::function::StopOnTarget, [185](#)
- init_beta
 - hnco::algorithm::SimulatedAnnealing, [169](#)
- is_surjective
 - hnco::Map, [101](#)
 - hnco::MapComposition, [103](#)
 - hnco::Permutation, [142](#)
 - hnco::Translation, [191](#)
- IterativeAlgorithm, [86](#)
 - hnco::algorithm::IterativeAlgorithm, [87](#)
- Iterator, [88](#)
- Jump, [90](#)
- Labs, [91](#)
- LastEvaluation, [92](#)
- LeadingOnes, [93](#)
- LinearFunction, [95](#)
- LinearMap, [97](#)
- load
 - hnco::function::MaxSat, [106](#)
 - hnco::function::Qubo, [159](#)
- LocalMaximum, [98](#)
- LongPath, [99](#)
- Map, [100](#)
- map
 - hnco::neighborhood::Neighborhood, [124](#)
- MapComposition, [102](#)
 - hnco::MapComposition, [103](#)
- MaxSat, [105](#)
- maximize
 - hnco::algorithm::IterativeAlgorithm, [87](#)
- MaximumReached, [104](#)
- Mmas, [108](#)
- Model, [109](#)
- ModelParameters, [110](#)
- MuCommaLambdaEa, [111](#)
 - hnco::algorithm::MuCommaLambdaEa, [112](#)
- MuPlusLambdaEa, [115](#)
 - hnco::algorithm::MuPlusLambdaEa, [117](#)
- MultiBitFlip, [113](#)
 - hnco::neighborhood::MultiBitFlip, [114](#)
- mutate
 - hnco::neighborhood::Neighborhood, [125](#)
- Needle, [118](#)
- Negation, [120](#)
- Neighborhood, [122](#)
 - hnco::neighborhood::Neighborhood, [124](#)
- NeighborhoodIterator, [125](#)
 - hnco::neighborhood::NeighborhoodIterator, [126](#)
- next
 - hnco::Hypercubeliterator, [85](#)
- NkLandscape, [126](#)
- NpsPbil, [128](#)
- OnBudgetFunction, [130](#)
- OneMax, [133](#)
- OnePlusLambdaCommaLambdaGa, [135](#)
 - hnco::algorithm::OnePlusLambdaCommaLambdaGa, [137](#)
- OnePlusOneEa, [137](#)
 - hnco::algorithm::OnePlusOneEa, [139](#)
- Pbil, [140](#)
- Permutation, [141](#)
- Plateau, [143](#)
- plus_selection
 - hnco::algorithm::Population, [149](#)
- PointValueException, [145](#)
- Population, [146](#)
- PriorNoise, [151](#)
- ProgressTracker, [153](#)
- ProgressTracker::Event, [54](#)
- provides_incremental_evaluation
 - hnco::function::Cache, [43](#)
 - hnco::function::Function, [62](#)
 - hnco::function::FunctionController, [64](#)
 - hnco::function::Negation, [121](#)
 - hnco::function::OneMax, [135](#)
 - hnco::function::PriorNoise, [152](#)
- PvAlgorithm, [156](#)
- q_variation
 - hnco::algorithm::hea::SpinHerding, [177](#)
- Qubo, [158](#)
- Random, [160](#)
- random
 - hnco::function::EqualProducts, [52](#)
 - hnco::function::LinearFunction, [96](#)
 - hnco::function::MaxSat, [106](#)
 - hnco::function::NkLandscape, [128](#)
 - hnco::function::WalshExpansion, [199](#)
 - hnco::function::WalshExpansion1, [200](#)
 - hnco::function::WalshExpansion2, [202](#)
- RandomLocalSearch, [161](#)
- RandomSearch, [163](#)
- reservoir_sampling
 - hnco::neighborhood::MultiBitFlip, [115](#)
- Restart, [164](#)
- Ridge, [165](#)
- safe_eval

- hnco::function::Function, [62](#)
- sbm_multiply
 - hnco, [18](#)
- select
 - hnco::algorithm::TournamentSelection, [190](#)
- set_allow_stay
 - hnco::algorithm::GeneticAlgorithm, [73](#)
 - hnco::algorithm::MuCommaLambdaEa, [113](#)
 - hnco::algorithm::MuPlusLambdaEa, [117](#)
 - hnco::algorithm::OnePlusOneEa, [139](#)
 - hnco::neighborhood::BernoulliProcess, [33](#)
- set_num_iterations
 - hnco::algorithm::IterativeAlgorithm, [88](#)
 - hnco::algorithm::OnePlusOneEa, [139](#)
- set_patience
 - hnco::algorithm::RandomLocalSearch, [162](#)
- set_probability
 - hnco::neighborhood::BernoulliProcess, [33](#)
- set_reset_period
 - hnco::algorithm::hea::Hea, [82](#)
- set_selection_size
 - hnco::algorithm::bm_pbil::BmPbil, [41](#)
 - hnco::algorithm::hea::Hea, [82](#)
- SimulatedAnnealing, [167](#)
- SingleBitFlip, [169](#)
- SingleBitFlipIterator, [170](#)
 - hnco::neighborhood::SingleBitFlipIterator, [171](#)
- SinusSummationCancellation, [172](#)
- SixPeaks, [173](#)
- sparse_bit_matrix_t
 - hnco, [14](#)
- sparse_bit_vector_t
 - hnco, [14](#)
- SpinHerdin, [175](#)
 - hnco::algorithm::hea::SpinHerdin, [177](#)
- SpinMoment, [178](#)
- SteepestAscentHillClimbing, [179](#)
- StopOnMaximum, [180](#)
 - hnco::function::StopOnMaximum, [181](#)
- StopOnTarget, [183](#)
 - hnco::function::StopOnTarget, [184](#)
- SummationCancellation, [185](#)
 - hnco::function::SummationCancellation, [187](#)
- TargetReached, [188](#)
- TournamentSelection, [189](#)
- Translation, [190](#)
- Trap, [192](#)
 - hnco::function::Trap, [193](#)
- Umda, [194](#)
- UniformCrossover, [196](#)
- update
 - hnco::function::OnBudgetFunction, [132](#)
 - hnco::function::ProgressTracker, [156](#)
 - hnco::function::StopOnMaximum, [182](#)
 - hnco::function::StopOnTarget, [185](#)
- WalshExpansion, [197](#)
 - WalshExpansion1, [199](#)
 - WalshExpansion2, [201](#)