

HNCO

0.26

Generated by Doxygen 1.9.8

1 Namespace Index	1
1.1 Namespace List	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	7
3.1 Class List	7
4 Namespace Documentation	15
4.1 hnco Namespace Reference	15
4.1.1 Detailed Description	20
4.1.2 Typedef Documentation	20
4.1.2.1 sparse_bit_vector_t	20
4.1.3 Function Documentation	20
4.1.3.1 bit_add()	20
4.1.3.2 bit_flip() [1/2]	20
4.1.3.3 bit_flip() [2/2]	21
4.1.3.4 bit_random()	21
4.1.3.5 bm_add_columns()	21
4.1.3.6 bm_add_rows()	22
4.1.3.7 bm_identity() [1/2]	22
4.1.3.8 bm_identity() [2/2]	22
4.1.3.9 bm_invert()	23
4.1.3.10 bm_multiply()	23
4.1.3.11 bm_rank()	24
4.1.3.12 bm_row_echelon_form()	24
4.1.3.13 bm_set_column()	24
4.1.3.14 bm_solve()	25
4.1.3.15 bm_solve_upper_triangular()	25
4.1.3.16 bm_transpose() [1/2]	26
4.1.3.17 bm_transpose() [2/2]	26
4.1.3.18 bv_add() [1/2]	27
4.1.3.19 bv_add() [2/2]	27
4.1.3.20 bv_flip()	27
4.1.3.21 bv_from_size_type()	28
4.1.3.22 bv_from_stream()	28
4.1.3.23 bv_from_string()	29
4.1.3.24 bv_from_vector_bool()	29
4.1.3.25 bv_to_size_type() [1/2]	29
4.1.3.26 bv_to_size_type() [2/2]	30
4.1.3.27 bv_to_vector_bool()	30
4.1.3.28 ensure()	31

4.1.3.29 fail_with()	31
4.1.3.30 is_in_range() [1/2]	31
4.1.3.31 is_in_range() [2/2]	32
4.1.3.32 load_from_archive()	32
4.1.3.33 perm_identity()	32
4.1.3.34 perm_random()	33
4.1.3.35 save_to_archive()	33
4.1.3.36 sbv_is_valid() [1/2]	33
4.1.3.37 sbv_is_valid() [2/2]	34
4.2 hnco::algorithm Namespace Reference	34
4.2.1 Detailed Description	37
4.2.2 Function Documentation	37
4.2.2.1 pv_add() [1/2]	37
4.2.2.2 pv_add() [2/2]	38
4.2.2.3 pv_average()	38
4.2.2.4 pv_bound()	38
4.2.2.5 pv_init()	39
4.2.2.6 pv_sample()	39
4.2.2.7 pv_uniform()	39
4.2.2.8 pv_update() [1/2]	40
4.2.2.9 pv_update() [2/2]	40
4.3 hnco::algorithm::fast_efficient_p3 Namespace Reference	40
4.3.1 Detailed Description	41
4.4 hnco::algorithm::gomea Namespace Reference	41
4.4.1 Detailed Description	41
4.5 hnco::algorithm::walsh_moment Namespace Reference	41
4.5.1 Detailed Description	42
4.6 hnco::app Namespace Reference	42
4.6.1 Detailed Description	43
4.6.2 Function Documentation	43
4.6.2.1 parse_representation()	43
4.6.2.2 parse_representations()	44
4.7 hnco::exception Namespace Reference	44
4.7.1 Detailed Description	45
4.8 hnco::function Namespace Reference	45
4.8.1 Detailed Description	47
4.8.2 Function Documentation	47
4.8.2.1 compute_fast_walsh_transform()	47
4.8.2.2 compute_walsh_transform()	48
4.9 hnco::function::controller Namespace Reference	48
4.9.1 Detailed Description	49
4.10 hnco::function::modifier Namespace Reference	49

4.10.1 Detailed Description	50
4.11 hnco::logging Namespace Reference	50
4.11.1 Detailed Description	50
4.12 hnco::map Namespace Reference	50
4.12.1 Detailed Description	51
4.12.2 Typedef Documentation	52
4.12.2.1 transvection_sequence_t	52
4.12.3 Function Documentation	52
4.12.3.1 ts_invert()	52
4.12.3.2 ts_is_valid() [1/2]	52
4.12.3.3 ts_is_valid() [2/2]	53
4.12.3.4 ts_multiply() [1/2]	53
4.12.3.5 ts_multiply() [2/2]	53
4.12.3.6 ts_random()	54
4.12.3.7 ts_random_commuting()	54
4.12.3.8 ts_random_disjoint()	55
4.12.3.9 ts_random_non_commuting()	55
4.12.3.10 ts_random_unique_destination()	56
4.12.3.11 ts_random_unique_source()	56
4.13 hnco::multiobjective Namespace Reference	58
4.13.1 Detailed Description	58
4.14 hnco::multiobjective::algorithm Namespace Reference	58
4.14.1 Detailed Description	59
4.14.2 Function Documentation	59
4.14.2.1 operator<()	59
4.15 hnco::multiobjective::app Namespace Reference	59
4.15.1 Detailed Description	60
4.16 hnco::multiobjective::function Namespace Reference	60
4.16.1 Detailed Description	60
4.16.2 Typedef Documentation	61
4.16.2.1 value_t	61
4.16.3 Function Documentation	61
4.16.3.1 dominates()	61
4.17 hnco::neighborhood Namespace Reference	61
4.17.1 Detailed Description	62
4.18 hnco::random Namespace Reference	62
4.18.1 Detailed Description	62
4.19 hnco::representation Namespace Reference	62
4.19.1 Detailed Description	63
4.19.2 Function Documentation	63
4.19.2.1 difference_is_safe()	63

5 Class Documentation	65
5.1 AbsoluteValue< T > Struct Template Reference	65
5.1.1 Detailed Description	65
5.2 AbstractMaxSat Class Reference	66
5.2.1 Detailed Description	67
5.2.2 Member Function Documentation	67
5.2.2.1 load()	67
5.2.2.2 load_()	68
5.2.2.3 save()	68
5.2.2.4 save_()	68
5.2.3 Member Data Documentation	69
5.2.3.1 _expression	69
5.3 AdditiveGaussianNoise Class Reference	69
5.3.1 Detailed Description	71
5.3.2 Member Function Documentation	71
5.3.2.1 get_bv_size()	71
5.4 AffineMap Class Reference	71
5.4.1 Detailed Description	72
5.4.2 Member Function Documentation	73
5.4.2.1 is_surjective()	73
5.4.2.2 load()	73
5.4.2.3 random()	73
5.4.2.4 save()	74
5.5 Algorithm Class Reference	74
5.5.1 Detailed Description	76
5.5.2 Member Function Documentation	76
5.5.2.1 finalize()	76
5.5.2.2 set_solution()	77
5.5.2.3 update_solution()	77
5.5.3 Member Data Documentation	77
5.5.3.1 _functions	77
5.6 Algorithm Class Reference	78
5.6.1 Detailed Description	79
5.6.2 Constructor & Destructor Documentation	79
5.6.2.1 Algorithm()	79
5.6.3 Member Data Documentation	79
5.6.3.1 _functions	79
5.7 AlgorithmFactory Class Reference	80
5.7.1 Detailed Description	80
5.7.2 Member Function Documentation	80
5.7.2.1 make()	80
5.8 AlgorithmFactory Class Reference	81

5.8.1 Detailed Description	81
5.8.2 Member Function Documentation	81
5.8.2.1 make()	81
5.9 BiasedCrossover Class Reference	82
5.9.1 Detailed Description	83
5.9.2 Member Function Documentation	83
5.9.2.1 recombine()	83
5.10 BmPbil< GibbsSampler > Class Template Reference	83
5.10.1 Detailed Description	87
5.10.2 Member Function Documentation	88
5.10.2.1 set_log_norm_infinite()	88
5.10.2.2 set_selection_size()	88
5.10.3 Member Data Documentation	88
5.10.3.1 _log_norm_infinite	88
5.10.3.2 _selection_size	88
5.11 BoltzmannSelection Class Reference	89
5.11.1 Detailed Description	90
5.11.2 Constructor & Destructor Documentation	90
5.11.2.1 BoltzmannSelection()	90
5.12 Cache Class Reference	91
5.12.1 Detailed Description	93
5.12.2 Constructor & Destructor Documentation	93
5.12.2.1 Cache()	93
5.12.3 Member Function Documentation	93
5.12.3.1 provides_incremental_evaluation()	93
5.13 CallCounter Class Reference	94
5.13.1 Detailed Description	96
5.14 CommandLineAlgorithmFactory Class Reference	96
5.14.1 Detailed Description	96
5.14.2 Member Function Documentation	97
5.14.2.1 make()	97
5.15 CommandLineAlgorithmFactory Class Reference	98
5.15.1 Detailed Description	99
5.15.2 Member Function Documentation	99
5.15.2.1 make()	99
5.16 CommandLineApplication Class Reference	99
5.16.1 Detailed Description	100
5.16.2 Constructor & Destructor Documentation	100
5.16.2.1 CommandLineApplication()	100
5.17 CommandLineApplication Class Reference	101
5.17.1 Detailed Description	102
5.17.2 Constructor & Destructor Documentation	102

5.17.2.1 CommandLineApplication()	102
5.18 CommandLineFunctionFactory Class Reference	102
5.18.1 Detailed Description	103
5.19 CommandLineFunctionFactory Class Reference	104
5.19.1 Detailed Description	104
5.20 CommaSelection Class Reference	104
5.20.1 Detailed Description	105
5.20.2 Constructor & Destructor Documentation	105
5.20.2.1 CommaSelection()	105
5.21 CompactGa Class Reference	105
5.21.1 Detailed Description	109
5.22 CompleteSearch Class Reference	110
5.22.1 Detailed Description	111
5.23 ComplexRepresentation< ScalarRep > Class Template Reference	112
5.23.1 Detailed Description	113
5.23.2 Constructor & Destructor Documentation	113
5.23.2.1 ComplexRepresentation() [1/2]	113
5.23.2.2 ComplexRepresentation() [2/2]	113
5.24 Controller Class Reference	114
5.24.1 Detailed Description	115
5.24.2 Member Function Documentation	115
5.24.2.1 provides_incremental_evaluation()	115
5.25 Crossover Class Reference	116
5.25.1 Detailed Description	116
5.25.2 Member Function Documentation	116
5.25.2.1 recombine()	116
5.26 DeceptiveJump Class Reference	117
5.26.1 Detailed Description	118
5.26.2 Member Function Documentation	119
5.26.2.1 get_maximum()	119
5.26.2.2 has_known_maximum()	119
5.27 DecoratedFunctionFactory Class Reference	119
5.27.1 Detailed Description	120
5.27.2 Member Function Documentation	120
5.27.2.1 make_function_controller()	120
5.28 Decorator Class Reference	121
5.28.1 Detailed Description	123
5.28.2 Constructor & Destructor Documentation	123
5.28.2.1 Decorator()	123
5.29 Decorator Class Reference	123
5.29.1 Detailed Description	124
5.30 DyadicFloatRepresentation< T > Class Template Reference	125

5.30.1 Detailed Description	126
5.30.2 Constructor & Destructor Documentation	126
5.30.2.1 DyadicFloatRepresentation() [1/2]	126
5.30.2.2 DyadicFloatRepresentation() [2/2]	126
5.30.3 Member Function Documentation	127
5.30.3.1 compute_lengths()	127
5.31 DyadicIntegerRepresentation< T > Class Template Reference	127
5.31.1 Detailed Description	128
5.31.2 Constructor & Destructor Documentation	129
5.31.2.1 DyadicIntegerRepresentation() [1/4]	129
5.31.2.2 DyadicIntegerRepresentation() [2/4]	129
5.31.2.3 DyadicIntegerRepresentation() [3/4]	129
5.31.2.4 DyadicIntegerRepresentation() [4/4]	130
5.32 EqualProducts Class Reference	130
5.32.1 Detailed Description	132
5.32.2 Member Function Documentation	132
5.32.2.1 generate()	132
5.32.2.2 load()	133
5.32.2.3 random()	133
5.32.2.4 save()	133
5.33 ProgressTracker::Event Struct Reference	134
5.33.1 Detailed Description	134
5.34 ExtendedHypercubeIterator Class Reference	134
5.34.1 Detailed Description	135
5.35 Factorization Class Reference	136
5.35.1 Detailed Description	138
5.35.2 Constructor & Destructor Documentation	138
5.35.2.1 Factorization()	138
5.35.3 Member Function Documentation	138
5.35.3.1 load()	138
5.36 FgenOptions Class Reference	139
5.36.1 Detailed Description	142
5.37 FirstAscentHillClimbing Class Reference	143
5.37.1 Detailed Description	146
5.38 FitnessProportionateSelection Class Reference	146
5.38.1 Detailed Description	147
5.38.2 Constructor & Destructor Documentation	147
5.38.2.1 FitnessProportionateSelection()	147
5.39 FourPeaks Class Reference	148
5.39.1 Detailed Description	149
5.39.2 Member Function Documentation	150
5.39.2.1 get_maximum()	150

5.39.2.2 has_known_maximum()	150
5.40 FrontDistancePair Struct Reference	151
5.40.1 Detailed Description	151
5.41 FullMoment Struct Reference	151
5.41.1 Detailed Description	152
5.41.2 Constructor & Destructor Documentation	152
5.41.2.1 FullMoment()	152
5.41.3 Member Function Documentation	152
5.41.3.1 average()	152
5.41.3.2 bound()	154
5.41.3.3 display()	154
5.41.3.4 scaled_difference()	154
5.41.3.5 update() [1/2]	155
5.41.3.6 update() [2/2]	155
5.42 FullMomentGibbsSampler Class Reference	156
5.42.1 Detailed Description	157
5.43 FullMomentHerding Class Reference	157
5.43.1 Detailed Description	158
5.43.2 Constructor & Destructor Documentation	158
5.43.2.1 FullMomentHerding()	158
5.43.3 Member Function Documentation	158
5.43.3.1 get_delta()	158
5.43.3.2 set_randomize_bit_order()	159
5.43.4 Member Data Documentation	159
5.43.4.1 _randomize_bit_order	159
5.44 Function Class Reference	159
5.44.1 Detailed Description	161
5.44.2 Member Function Documentation	161
5.44.2.1 describe()	161
5.44.2.2 evaluate()	162
5.44.2.3 evaluate_incrementally()	162
5.44.2.4 evaluate_safely()	162
5.44.2.5 get_maximum()	163
5.44.2.6 provides_incremental_evaluation()	164
5.44.2.7 update()	164
5.45 Function Class Reference	165
5.45.1 Detailed Description	166
5.45.2 Member Function Documentation	166
5.45.2.1 describe()	166
5.45.2.2 evaluate()	166
5.46 FunctionFactory Class Reference	167
5.46.1 Detailed Description	167

5.47 FunctionFactory Class Reference	167
5.47.1 Detailed Description	168
5.48 FunctionMapComposition Class Reference	168
5.48.1 Detailed Description	170
5.48.2 Constructor & Destructor Documentation	170
5.48.2.1 FunctionMapComposition()	170
5.48.3 Member Function Documentation	170
5.48.3.1 describe()	170
5.48.3.2 get_bv_size()	171
5.48.3.3 get_maximum()	171
5.48.3.4 has_known_maximum()	171
5.49 FunctionPlugin Class Reference	172
5.49.1 Detailed Description	173
5.49.2 Constructor & Destructor Documentation	173
5.49.2.1 FunctionPlugin()	173
5.50 Generator Struct Reference	173
5.50.1 Detailed Description	174
5.50.2 Member Function Documentation	174
5.50.2.1 reset()	174
5.50.2.2 set_seed()	174
5.51 GeneticAlgorithm Class Reference	175
5.51.1 Detailed Description	178
5.51.2 Constructor & Destructor Documentation	178
5.51.2.1 GeneticAlgorithm()	178
5.52 Gomea Class Reference	178
5.52.1 Detailed Description	180
5.53 HammingBall Class Reference	181
5.53.1 Detailed Description	182
5.53.2 Constructor & Destructor Documentation	183
5.53.2.1 HammingBall()	183
5.54 HammingSphere Class Reference	183
5.54.1 Detailed Description	185
5.54.2 Constructor & Destructor Documentation	185
5.54.2.1 HammingSphere()	185
5.55 HammingSphereliterator Class Reference	186
5.55.1 Detailed Description	187
5.55.2 Constructor & Destructor Documentation	187
5.55.2.1 HammingSphereliterator()	187
5.56 Hboa Class Reference	188
5.56.1 Detailed Description	190
5.56.2 Member Data Documentation	190
5.56.2.1 _implementation	190

5.57 Hea< Herding > Class Template Reference	190
5.57.1 Detailed Description	194
5.57.2 Constructor & Destructor Documentation	194
5.57.2.1 Hea()	194
5.57.3 Member Function Documentation	194
5.57.3.1 init()	194
5.57.3.2 set_log_herding_error()	195
5.57.3.3 set_margin()	195
5.57.3.4 set_reset_period()	195
5.57.3.5 set_selection_size()	195
5.57.4 Member Data Documentation	196
5.57.4.1 _log_herding_error	196
5.57.4.2 _margin	196
5.58 Hiff Class Reference	196
5.58.1 Detailed Description	197
5.58.2 Member Function Documentation	198
5.58.2.1 get_maximum()	198
5.58.2.2 has_known_maximum()	198
5.59 HncoEvaluator Class Reference	198
5.59.1 Detailed Description	199
5.60 HncoFitness Class Reference	199
5.60.1 Detailed Description	199
5.61 HncoOptions Class Reference	200
5.61.1 Detailed Description	213
5.62 HncoOptions Class Reference	214
5.62.1 Detailed Description	218
5.63 Human Class Reference	218
5.63.1 Detailed Description	221
5.64 Hypercubeliterator Class Reference	221
5.64.1 Detailed Description	222
5.65 Implementation Struct Reference	222
5.65.1 Detailed Description	222
5.66 InformationTheoreticEa Class Reference	223
5.66.1 Detailed Description	226
5.66.2 Member Function Documentation	226
5.66.2.1 init()	226
5.66.2.2 set_log_mutation_rate()	227
5.66.2.3 set_selection_size()	227
5.66.3 Member Data Documentation	227
5.66.3.1 _log_mutation_rate	227
5.66.3.2 _selection_size	227
5.67 Injection Class Reference	228

5.67.1 Detailed Description	229
5.67.2 Constructor & Destructor Documentation	229
5.67.2.1 Injection()	229
5.68 IntegerCategoricalRepresentation Class Reference	229
5.68.1 Detailed Description	230
5.68.2 Constructor & Destructor Documentation	230
5.68.2.1 IntegerCategoricalRepresentation()	230
5.69 IterativeAlgorithm Class Reference	231
5.69.1 Detailed Description	233
5.69.2 Constructor & Destructor Documentation	233
5.69.2.1 IterativeAlgorithm()	233
5.69.3 Member Function Documentation	234
5.69.3.1 loop()	234
5.69.3.2 maximize()	234
5.69.3.3 set_num_iterations()	234
5.70 IterativeAlgorithm Class Reference	235
5.70.1 Detailed Description	237
5.70.2 Constructor & Destructor Documentation	237
5.70.2.1 IterativeAlgorithm()	237
5.70.3 Member Function Documentation	237
5.70.3.1 loop()	237
5.70.3.2 minimize()	237
5.70.3.3 set_num_iterations()	237
5.71 Iterator Class Reference	238
5.71.1 Detailed Description	239
5.72 Jump Class Reference	239
5.72.1 Detailed Description	240
5.72.2 Member Function Documentation	240
5.72.2.1 get_maximum()	240
5.72.2.2 has_known_maximum()	241
5.73 Labs Class Reference	241
5.73.1 Detailed Description	242
5.74 LastEvaluation Class Reference	243
5.74.1 Detailed Description	243
5.75 LeadingOnes Class Reference	243
5.75.1 Detailed Description	244
5.75.2 Member Function Documentation	244
5.75.2.1 get_maximum()	244
5.75.2.2 has_known_maximum()	245
5.76 LinearCategoricalRepresentation Class Reference	245
5.76.1 Detailed Description	246
5.76.2 Constructor & Destructor Documentation	246

5.76.2.1 LinearCategoricalRepresentation()	246
5.77 LinearFunction Class Reference	246
5.77.1 Detailed Description	248
5.77.2 Member Function Documentation	248
5.77.2.1 generate()	248
5.77.2.2 has_known_maximum()	249
5.77.2.3 load()	249
5.77.2.4 provides_incremental_evaluation()	249
5.77.2.5 random()	250
5.77.2.6 save()	250
5.78 LinearMap Class Reference	250
5.78.1 Detailed Description	252
5.78.2 Member Function Documentation	252
5.78.2.1 is_surjective()	252
5.78.2.2 load()	252
5.78.2.3 random()	253
5.78.2.4 save()	253
5.79 LocalSearchAlgorithm< Neighborhood > Class Template Reference	253
5.79.1 Detailed Description	256
5.80 LogContext Class Reference	256
5.80.1 Detailed Description	257
5.81 Logger Class Reference	257
5.81.1 Detailed Description	257
5.81.2 Constructor & Destructor Documentation	258
5.81.2.1 Logger()	258
5.81.2.2 ~Logger()	259
5.82 LongPath Class Reference	259
5.82.1 Detailed Description	260
5.82.2 Member Function Documentation	261
5.82.2.1 get_maximum()	261
5.82.2.2 has_known_maximum()	261
5.83 Ltga Class Reference	262
5.83.1 Detailed Description	263
5.83.2 Member Data Documentation	264
5.83.2.1 _implementation	264
5.84 Map Class Reference	264
5.84.1 Detailed Description	265
5.84.2 Member Function Documentation	265
5.84.2.1 is_surjective()	265
5.85 MapComposition Class Reference	266
5.85.1 Detailed Description	267
5.85.2 Constructor & Destructor Documentation	267

5.85.2.1 MapComposition()	267
5.85.3 Member Function Documentation	267
5.85.3.1 is_surjective()	267
5.86 MapgenOptions Class Reference	268
5.86.1 Detailed Description	269
5.87 MaxNae3Sat Class Reference	270
5.87.1 Detailed Description	271
5.87.2 Member Function Documentation	271
5.87.2.1 load()	271
5.88 MaxSat Class Reference	272
5.88.1 Detailed Description	274
5.88.2 Member Function Documentation	274
5.88.2.1 random() [1/2]	274
5.88.2.2 random() [2/2]	274
5.89 Mimic Class Reference	275
5.89.1 Detailed Description	278
5.90 MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv > Class Template Reference	278
5.90.1 Detailed Description	280
5.90.2 Constructor & Destructor Documentation	280
5.90.2.1 MixedRepresentationMultivariateFunctionAdapter()	280
5.90.3 Member Function Documentation	281
5.90.3.1 display()	281
5.90.3.2 evaluate()	281
5.90.3.3 get_bv_size()	281
5.91 MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv > Class Template Reference	282
5.91.1 Detailed Description	283
5.91.2 Constructor & Destructor Documentation	284
5.91.2.1 MixedRepresentationMultivariateFunctionAdapter()	284
5.91.3 Member Function Documentation	284
5.91.3.1 display()	284
5.91.3.2 evaluate()	284
5.92 Mmas Class Reference	285
5.92.1 Detailed Description	288
5.93 Modifier Class Reference	289
5.93.1 Detailed Description	290
5.94 MuCommaLambdaEa Class Reference	290
5.94.1 Detailed Description	293
5.94.2 Constructor & Destructor Documentation	293
5.94.2.1 MuCommaLambdaEa()	293
5.95 MultiBitFlip Class Reference	294
5.95.1 Detailed Description	295

5.95.2 Constructor & Destructor Documentation	295
5.95.2.1 MultiBitFlip()	295
5.95.3 Member Function Documentation	296
5.95.3.1 bernoulli_trials()	296
5.95.3.2 rejection_sampling()	296
5.96 MultiobjectiveFunctionAdapter Class Reference	296
5.96.1 Detailed Description	298
5.96.2 Constructor & Destructor Documentation	298
5.96.2.1 MultiobjectiveFunctionAdapter()	298
5.96.3 Member Function Documentation	298
5.96.3.1 display()	298
5.96.3.2 evaluate()	299
5.96.3.3 get_bv_size()	299
5.97 MultivariateFunctionAdapter< Fn, Rep, Conv > Class Template Reference	299
5.97.1 Detailed Description	301
5.97.2 Constructor & Destructor Documentation	301
5.97.2.1 MultivariateFunctionAdapter()	301
5.97.3 Member Function Documentation	302
5.97.3.1 display()	302
5.97.3.2 evaluate()	302
5.97.3.3 get_bv_size()	302
5.98 MultivariateFunctionAdapter< Fn, Rep, Conv > Class Template Reference	303
5.98.1 Detailed Description	304
5.98.2 Constructor & Destructor Documentation	305
5.98.2.1 MultivariateFunctionAdapter()	305
5.98.3 Member Function Documentation	305
5.98.3.1 display()	305
5.98.3.2 evaluate()	305
5.98.3.3 get_bv_size()	306
5.99 MuPlusLambdaEa Class Reference	306
5.99.1 Detailed Description	309
5.99.2 Constructor & Destructor Documentation	309
5.99.2.1 MuPlusLambdaEa()	309
5.100 NearestNeighborsIsingModel1 Class Reference	310
5.100.1 Detailed Description	312
5.100.2 Member Function Documentation	312
5.100.2.1 evaluate()	312
5.100.2.2 generate()	312
5.100.2.3 load()	313
5.100.2.4 provides_incremental_evaluation()	313
5.100.2.5 random()	313
5.100.2.6 save()	314

5.101 NearestNeighborIsingModel2 Class Reference	314
5.101.1 Detailed Description	316
5.101.2 Member Function Documentation	317
5.101.2.1 evaluate()	317
5.101.2.2 generate()	317
5.101.2.3 load()	317
5.101.2.4 provides_incremental_evaluation()	318
5.101.2.5 random()	318
5.101.2.6 save()	318
5.102 Needle Class Reference	319
5.102.1 Detailed Description	320
5.102.2 Member Function Documentation	320
5.102.2.1 get_maximum()	320
5.102.2.2 has_known_maximum()	321
5.103 Neighborhood Class Reference	321
5.103.1 Detailed Description	323
5.103.2 Constructor & Destructor Documentation	323
5.103.2.1 Neighborhood()	323
5.103.3 Member Function Documentation	323
5.103.3.1 map()	323
5.103.3.2 mutate()	324
5.104 NeighborhoodIterator Class Reference	324
5.104.1 Detailed Description	325
5.104.2 Constructor & Destructor Documentation	325
5.104.2.1 NeighborhoodIterator()	325
5.105 NkLandscape Class Reference	326
5.105.1 Detailed Description	327
5.105.2 Member Function Documentation	328
5.105.2.1 generate()	328
5.105.2.2 load()	329
5.105.2.3 random()	329
5.105.2.4 random_structure()	329
5.105.2.5 save()	330
5.106 NpsPbil Class Reference	330
5.106.1 Detailed Description	334
5.107 Nsga2 Class Reference	335
5.107.1 Detailed Description	338
5.107.2 Constructor & Destructor Documentation	338
5.107.2.1 Nsga2()	338
5.107.3 Member Function Documentation	338
5.107.3.1 init()	338
5.107.3.2 set_tournament_size()	338

5.107.4 Member Data Documentation	339
5.107.4.1 _tournament_size	339
5.108 Nsga2ParetoFrontComputation Class Reference	339
5.108.1 Detailed Description	340
5.108.2 Member Function Documentation	340
5.108.2.1 compute()	340
5.108.2.2 is_non_dominated()	340
5.108.3 Member Data Documentation	340
5.108.3.1 _dominated	340
5.109 OnBudgetFunction Class Reference	341
5.109.1 Detailed Description	343
5.109.2 Member Function Documentation	343
5.109.2.1 evaluate()	343
5.109.2.2 evaluate_incrementally()	343
5.109.2.3 update()	343
5.110 OneMax Class Reference	344
5.110.1 Detailed Description	345
5.110.2 Member Function Documentation	345
5.110.2.1 get_maximum()	345
5.110.2.2 has_known_maximum()	346
5.110.2.3 provides_incremental_evaluation()	346
5.111 OnePlusLambdaCommaLambdaGa Class Reference	346
5.111.1 Detailed Description	349
5.111.2 Constructor & Destructor Documentation	349
5.111.2.1 OnePlusLambdaCommaLambdaGa()	349
5.112 OnePlusOneEa Class Reference	350
5.112.1 Detailed Description	352
5.112.2 Constructor & Destructor Documentation	352
5.112.2.1 OnePlusOneEa()	352
5.112.3 Member Function Documentation	352
5.112.3.1 set_num_iterations()	352
5.113 OppositeAbsoluteValue< T > Struct Template Reference	353
5.113.1 Detailed Description	353
5.114 OppositeFunction Class Reference	354
5.114.1 Detailed Description	355
5.114.2 Member Function Documentation	356
5.114.2.1 evaluate()	356
5.114.2.2 get_bv_size()	356
5.114.2.3 provides_incremental_evaluation()	356
5.115 OppositeSquaredMagnitude< T > Struct Template Reference	356
5.115.1 Detailed Description	357
5.116 ParameterLessPopulationPyramid Class Reference	357

5.116.1 Detailed Description	359
5.116.2 Member Data Documentation	359
5.116.2.1 <code>_implementation</code>	359
5.117 <code>ParsedModifier</code> Class Reference	360
5.117.1 Detailed Description	362
5.117.2 Constructor & Destructor Documentation	362
5.117.2.1 <code>ParsedModifier()</code>	362
5.118 <code>ParsedMultivariateFunction< Parser ></code> Class Template Reference	362
5.118.1 Detailed Description	363
5.118.2 Constructor & Destructor Documentation	363
5.118.2.1 <code>ParsedMultivariateFunction()</code>	363
5.119 <code>ParsedMultivariateFunction< Parser ></code> Class Template Reference	364
5.119.1 Detailed Description	365
5.119.2 Constructor & Destructor Documentation	365
5.119.2.1 <code>ParsedMultivariateFunction()</code>	365
5.119.3 Member Data Documentation	366
5.119.3.1 <code>_indices</code>	366
5.119.3.2 <code>_names</code>	366
5.119.3.3 <code>_ordered_names</code>	366
5.119.3.4 <code>_variables</code>	366
5.120 <code>Partition</code> Class Reference	367
5.120.1 Detailed Description	368
5.120.2 Member Function Documentation	368
5.120.2.1 <code>generate()</code>	368
5.120.2.2 <code>load()</code>	369
5.120.2.3 <code>random()</code>	369
5.120.2.4 <code>save()</code>	369
5.121 <code>Pbil</code> Class Reference	370
5.121.1 Detailed Description	373
5.122 <code>Permutation</code> Class Reference	374
5.122.1 Detailed Description	375
5.122.2 Member Function Documentation	375
5.122.2.1 <code>is_surjective()</code>	375
5.122.2.2 <code>load()</code>	375
5.122.2.3 <code>save()</code>	376
5.123 <code>PermutationFunctionAdapter< Fn ></code> Class Template Reference	376
5.123.1 Detailed Description	378
5.123.2 Constructor & Destructor Documentation	378
5.123.2.1 <code>PermutationFunctionAdapter()</code>	378
5.124 <code>PermutationRepresentation</code> Class Reference	379
5.124.1 Detailed Description	379
5.124.2 Constructor & Destructor Documentation	379

5.124.2.1 PermutationRepresentation()	379
5.125 Plateau Class Reference	380
5.125.1 Detailed Description	381
5.125.2 Member Function Documentation	381
5.125.2.1 get_maximum()	381
5.125.2.2 has_known_maximum()	382
5.126 PlusSelection Class Reference	382
5.126.1 Detailed Description	382
5.126.2 Constructor & Destructor Documentation	382
5.126.2.1 PlusSelection()	382
5.127 Population Struct Reference	383
5.127.1 Detailed Description	384
5.127.2 Constructor & Destructor Documentation	384
5.127.2.1 Population()	384
5.127.3 Member Function Documentation	385
5.127.3.1 evaluate()	385
5.127.3.2 get_best_bv() [1/2]	385
5.127.3.3 get_best_bv() [2/2]	385
5.127.3.4 get_best_index() [1/2]	385
5.127.3.5 get_best_index() [2/2]	386
5.127.3.6 get_best_value() [1/2]	386
5.127.3.7 get_best_value() [2/2]	386
5.127.3.8 get_equivalent_bvs()	387
5.127.3.9 get_size()	387
5.127.3.10 get_worst_bv()	387
5.127.3.11 partial_sort()	388
5.127.3.12 sort()	388
5.128 Population Struct Reference	388
5.128.1 Detailed Description	389
5.128.2 Constructor & Destructor Documentation	389
5.128.2.1 Population()	389
5.128.3 Member Function Documentation	390
5.128.3.1 resize()	390
5.128.3.2 shrink()	390
5.129 DyadicIntegerRepresentation< T >::Precision Struct Reference	391
5.129.1 Detailed Description	391
5.130 PriorNoise Class Reference	391
5.130.1 Detailed Description	393
5.130.2 Member Function Documentation	394
5.130.2.1 get_maximum()	394
5.130.2.2 has_known_maximum()	394
5.130.2.3 provides_incremental_evaluation()	394

5.131 ProgressTracker Class Reference	395
5.131.1 Detailed Description	397
5.131.2 Member Function Documentation	398
5.131.2.1 get_last_improvement()	398
5.131.3 Member Data Documentation	398
5.131.3.1 _record_evaluation_time	398
5.132 ProgressTrackerContext Class Reference	398
5.132.1 Detailed Description	399
5.132.2 Member Function Documentation	399
5.132.2.1 to_string()	399
5.133 Projection Class Reference	400
5.133.1 Detailed Description	401
5.133.2 Constructor & Destructor Documentation	401
5.133.2.1 Projection()	401
5.133.3 Member Function Documentation	401
5.133.3.1 is_surjective()	401
5.134 PvAlgorithm Class Reference	402
5.134.1 Detailed Description	404
5.135 PythonFunction Class Reference	405
5.135.1 Detailed Description	406
5.135.2 Constructor & Destructor Documentation	406
5.135.2.1 PythonFunction()	406
5.135.3 Member Function Documentation	406
5.135.3.1 get_maximum()	406
5.136 PythonFunction Class Reference	407
5.136.1 Detailed Description	408
5.136.2 Constructor & Destructor Documentation	408
5.136.2.1 PythonFunction()	408
5.137 Qubo Class Reference	408
5.137.1 Detailed Description	410
5.137.2 Member Function Documentation	410
5.137.2.1 load() [1/2]	410
5.137.2.2 load() [2/2]	411
5.137.3 Member Data Documentation	411
5.137.3.1 _q	411
5.138 RamUmda Class Reference	412
5.138.1 Detailed Description	416
5.138.2 Member Function Documentation	416
5.138.2.1 init()	416
5.138.2.2 set_selection_size()	417
5.138.3 Member Data Documentation	417
5.138.3.1 _selection_size	417

5.139 RamUmda2 Class Reference	417
5.139.1 Detailed Description	421
5.139.2 Member Function Documentation	422
5.139.2.1 init()	422
5.139.2.2 set_crossover_probability()	422
5.139.3 Member Data Documentation	422
5.139.3.1 _crossover_probability	422
5.140 RandomLocalSearch Class Reference	423
5.140.1 Detailed Description	426
5.140.2 Member Function Documentation	426
5.140.2.1 set_patience()	426
5.140.3 Member Data Documentation	427
5.140.3.1 _patience	427
5.141 RandomSearch Class Reference	427
5.141.1 Detailed Description	430
5.142 RandomSelection Class Reference	430
5.142.1 Detailed Description	431
5.142.2 Constructor & Destructor Documentation	431
5.142.2.1 RandomSelection()	431
5.143 RandomWalk Class Reference	431
5.143.1 Detailed Description	435
5.144 InformationTheoreticEa::Replacement Struct Reference	435
5.144.1 Detailed Description	436
5.144.2 Member Enumeration Documentation	436
5.144.2.1 anonymous enum	436
5.145 BmPbil< GibbsSampler >::ResetMode Struct Reference	436
5.145.1 Detailed Description	436
5.145.2 Member Enumeration Documentation	437
5.145.2.1 anonymous enum	437
5.146 Restart Class Reference	437
5.146.1 Detailed Description	439
5.146.2 Member Function Documentation	439
5.146.2.1 iterate()	439
5.146.2.2 set_num_iterations()	440
5.147 Ridge Class Reference	440
5.147.1 Detailed Description	441
5.147.2 Member Function Documentation	442
5.147.2.1 get_maximum()	442
5.147.2.2 has_known_maximum()	442
5.148 BmPbil< GibbsSampler >::SamplingMode Struct Reference	442
5.148.1 Detailed Description	442
5.148.2 Member Enumeration Documentation	442

5.148.2.1 anonymous enum	442
5.149 TsAffineMap::SamplingMode Struct Reference	443
5.149.1 Detailed Description	443
5.149.2 Member Enumeration Documentation	443
5.149.2.1 mode	443
5.150 ScalarToDouble< T > Struct Template Reference	444
5.150.1 Detailed Description	444
5.151 SelfAdjustingOnePlusOneEa Class Reference	445
5.151.1 Detailed Description	448
5.152 SimulatedAnnealing Class Reference	449
5.152.1 Detailed Description	452
5.152.2 Member Function Documentation	453
5.152.2.1 init_beta()	453
5.153 SingleBitFlip Class Reference	453
5.153.1 Detailed Description	454
5.154 SingleBitFlipIteator Class Reference	455
5.154.1 Detailed Description	456
5.154.2 Constructor & Destructor Documentation	456
5.154.2.1 SingleBitFlipIteator()	456
5.155 SinusSummationCancellation Class Reference	456
5.155.1 Detailed Description	458
5.156 SixPeaks Class Reference	459
5.156.1 Detailed Description	460
5.156.2 Member Function Documentation	461
5.156.2.1 get_maximum()	461
5.156.2.2 has_known_maximum()	461
5.157 SquaredMagnitude< T > Struct Template Reference	461
5.157.1 Detailed Description	462
5.158 StandardBitMutation Class Reference	462
5.158.1 Detailed Description	464
5.158.2 Constructor & Destructor Documentation	464
5.158.2.1 StandardBitMutation() [1/2]	464
5.158.2.2 StandardBitMutation() [2/2]	465
5.158.3 Member Function Documentation	465
5.158.3.1 set_mutation_rate()	465
5.159 SteepestAscentHillClimbing Class Reference	466
5.159.1 Detailed Description	469
5.160 StopOnMaximum Class Reference	469
5.160.1 Detailed Description	471
5.160.2 Constructor & Destructor Documentation	471
5.160.2.1 StopOnMaximum()	471
5.161 StopOnTarget Class Reference	472

5.161.1 Detailed Description	474
5.161.2 Constructor & Destructor Documentation	474
5.161.2.1 StopOnTarget()	474
5.161.3 Member Function Documentation	474
5.161.3.1 evaluate()	474
5.161.3.2 evaluate_incrementally()	475
5.161.3.3 update()	475
5.162 Stopwatch Class Reference	475
5.162.1 Detailed Description	476
5.163 Sudoku Class Reference	476
5.163.1 Detailed Description	477
5.163.2 Member Function Documentation	477
5.163.2.1 load()	477
5.163.2.2 load_()	478
5.163.2.3 random()	478
5.163.2.4 save()	478
5.164 SummationCancellation Class Reference	479
5.164.1 Detailed Description	480
5.164.2 Constructor & Destructor Documentation	480
5.164.2.1 SummationCancellation()	480
5.164.3 Member Function Documentation	481
5.164.3.1 has_known_maximum()	481
5.165 TargetReached Class Reference	481
5.165.1 Detailed Description	481
5.166 TournamentSelection Class Reference	482
5.166.1 Detailed Description	483
5.166.2 Constructor & Destructor Documentation	483
5.166.2.1 TournamentSelection()	483
5.166.3 Member Function Documentation	483
5.166.3.1 select()	483
5.166.3.2 set_tournament_size()	484
5.166.4 Member Data Documentation	484
5.166.4.1 _tournament_size	484
5.167 TournamentSelection< T, Compare > Class Template Reference	484
5.167.1 Detailed Description	485
5.168 Translation Class Reference	486
5.168.1 Detailed Description	487
5.168.2 Member Function Documentation	487
5.168.2.1 is_surjective()	487
5.168.2.2 load()	487
5.168.2.3 save()	488
5.169 Transvection Struct Reference	488

5.169.1 Detailed Description	489
5.169.2 Member Function Documentation	489
5.169.2.1 is_valid()	489
5.169.2.2 multiply() [1/2]	489
5.169.2.3 multiply() [2/2]	490
5.169.2.4 random()	490
5.169.2.5 random_non_commuting()	491
5.170 Trap Class Reference	491
5.170.1 Detailed Description	492
5.170.2 Constructor & Destructor Documentation	493
5.170.2.1 Trap()	493
5.170.3 Member Function Documentation	493
5.170.3.1 get_maximum()	493
5.170.3.2 has_known_maximum()	493
5.171 TriangularMoment Struct Reference	494
5.171.1 Detailed Description	494
5.171.2 Constructor & Destructor Documentation	494
5.171.2.1 TriangularMoment()	494
5.171.3 Member Function Documentation	495
5.171.3.1 average()	495
5.171.3.2 bound()	495
5.171.3.3 display()	495
5.171.3.4 scaled_difference()	496
5.171.3.5 update() [1/2]	496
5.171.3.6 update() [2/2]	497
5.172 TriangularMomentGibbsSampler Class Reference	498
5.172.1 Detailed Description	499
5.173 TriangularMomentHerding Class Reference	499
5.173.1 Detailed Description	500
5.173.2 Constructor & Destructor Documentation	500
5.173.2.1 TriangularMomentHerding()	500
5.173.3 Member Function Documentation	500
5.173.3.1 get_delta()	500
5.173.3.2 set_randomize_bit_order()	501
5.173.4 Member Data Documentation	501
5.173.4.1 _randomize_bit_order	501
5.174 TsAffineMap Class Reference	501
5.174.1 Detailed Description	503
5.174.2 Member Function Documentation	503
5.174.2.1 is_surjective()	503
5.174.2.2 load()	503
5.174.2.3 random()	503

5.174.2.4 save()	504
5.175 RamUmda::TsLengthMode Struct Reference	504
5.175.1 Detailed Description	505
5.175.2 Member Enumeration Documentation	505
5.175.2.1 anonymous enum	505
5.176 Tsp Class Reference	505
5.176.1 Detailed Description	506
5.176.2 Member Enumeration Documentation	506
5.176.2.1 EdgeWeightType	506
5.176.3 Member Function Documentation	507
5.176.3.1 generate()	507
5.176.3.2 load()	507
5.176.3.3 load_()	507
5.176.3.4 random()	508
5.176.3.5 save()	508
5.176.3.6 save_()	508
5.177 TwoRateOnePlusLambdaEa Class Reference	509
5.177.1 Detailed Description	512
5.177.2 Member Function Documentation	512
5.177.2.1 init()	512
5.177.2.2 set_log_mutation_rate()	512
5.177.2.3 set_mutation_rate_init()	513
5.177.3 Member Data Documentation	513
5.177.3.1 _log_mutation_rate	513
5.177.3.2 _mutation_rate_init	513
5.178 Umda Class Reference	513
5.178.1 Detailed Description	517
5.179 UniformCrossover Class Reference	518
5.179.1 Detailed Description	518
5.179.2 Member Function Documentation	518
5.179.2.1 recombine()	518
5.180 UniformSelection Class Reference	519
5.180.1 Detailed Description	520
5.180.2 Constructor & Destructor Documentation	520
5.180.2.1 UniformSelection()	520
5.181 UniversalFunction Class Reference	520
5.181.1 Detailed Description	521
5.182 UniversalFunction Class Reference	521
5.182.1 Detailed Description	522
5.183 UniversalFunctionAdapter Class Reference	522
5.183.1 Detailed Description	524
5.183.2 Constructor & Destructor Documentation	524

5.183.2.1 UniversalFunctionAdapter()	524
5.184 UniversalFunctionAdapter Class Reference	524
5.184.1 Detailed Description	526
5.184.2 Constructor & Destructor Documentation	526
5.184.2.1 UniversalFunctionAdapter()	526
5.185 ValueSetRepresentation< T > Class Template Reference	527
5.185.1 Detailed Description	528
5.185.2 Constructor & Destructor Documentation	528
5.185.2.1 ValueSetRepresentation()	528
5.186 WalshExpansion Class Reference	528
5.186.1 Detailed Description	530
5.186.2 Member Function Documentation	530
5.186.2.1 generate()	530
5.186.2.2 load()	530
5.186.2.3 random()	531
5.186.2.4 save()	531
5.187 WalshExpansion1 Class Reference	532
5.187.1 Detailed Description	533
5.187.2 Member Function Documentation	533
5.187.2.1 generate()	533
5.187.2.2 has_known_maximum()	534
5.187.2.3 load()	534
5.187.2.4 provides_incremental_evaluation()	534
5.187.2.5 random()	535
5.187.2.6 save()	535
5.188 WalshExpansion2 Class Reference	535
5.188.1 Detailed Description	537
5.188.2 Member Function Documentation	537
5.188.2.1 generate()	537
5.188.2.2 generate_ising1_long_range()	538
5.188.2.3 generate_ising1_long_range_periodic()	538
5.188.2.4 load()	539
5.188.2.5 random()	539
5.188.2.6 save()	540
5.188.3 Member Data Documentation	540
5.188.3.1 _quadratic	540
5.189 WalshTerm Struct Reference	540
5.189.1 Detailed Description	541
5.189.2 Member Data Documentation	541
5.189.2.1 feature	541

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

hnco	Top-level HNCO namespace	15
hnco::algorithm	Algorithms	34
hnco::algorithm::fast_efficient_p3	Algorithms from the FastEfficientP3 library	40
hnco::algorithm::gomea	GOMEA	41
hnco::algorithm::walsh_moment	Algorithms using Walsh moments	41
hnco::app	Classes for applications	42
hnco::exception	Exceptions	44
hnco::function	Functions defined on bit vectors	45
hnco::function::controller	Controllers	48
hnco::function::modifier	Modifiers	49
hnco::logging	Logging	50
hnco::map	Maps	50
hnco::multiobjective	Multiobjective optimization	58
hnco::multiobjective::algorithm	Multiobjective Algorithms	58
hnco::multiobjective::app	Classes for applications	59
hnco::multiobjective::function	Functions defined on bit vectors	60
hnco::neighborhood	Neighborhoods for local search	61
hnco::random	Random numbers	62
hnco::representation	Representations	62

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AbsoluteValue< T >	65
Algorithm	74
CompleteSearch	110
Decorator	121
Restart	437
IterativeAlgorithm	231
LocalSearchAlgorithm< neighborhood::NeighborhoodIterator >	253
FirstAscentHillClimbing	143
SteepestAscentHillClimbing	466
LocalSearchAlgorithm< neighborhood::Neighborhood >	253
RandomLocalSearch	423
RandomWalk	431
SimulatedAnnealing	449
GeneticAlgorithm	175
Human	218
InformationTheoreticEa	223
LocalSearchAlgorithm< Neighborhood >	253
Mimic	275
MuCommaLambdaEa	290
MuPlusLambdaEa	306
OnePlusLambdaCommaLambdaGa	346
PvAlgorithm	402
CompactGa	105
Mmas	285
NpsPbil	330
Pbil	370
RamUmda	412
RamUmda2	417
Umda	513
RandomSearch	427
SelfAdjustingOnePlusOneEa	445
TwoRateOnePlusLambdaEa	509
BmPbil< GibbsSampler >	83
Hea< Herding >	190

OnePlusOneEa	350
Hboa	188
Ltga	262
ParameterLessPopulationPyramid	357
Gomea	178
Algorithm	78
IterativeAlgorithm	235
Nsga2	335
AlgorithmFactory	80
CommandLineAlgorithmFactory	96
AlgorithmFactory	81
CommandLineAlgorithmFactory	98
CommandLineApplication	99
CommandLineApplication	101
CommaSelection	104
ComplexRepresentation< ScalarRep >	112
ComplexRepresentation< DyadicFloatRepresentation< double > >	112
Crossover	116
BiasedCrossover	82
UniformCrossover	518
DecoratedFunctionFactory	119
DyadicFloatRepresentation< T >	125
DyadicFloatRepresentation< double >	125
DyadicIntegerRepresentation< T >	127
DyadicIntegerRepresentation< int >	127
ProgressTracker::Event	134
exception	
std::runtime_error	
LastEvaluation	243
TargetReached	481
FfgenOptions	139
FrontDistancePair	151
FullMoment	151
FullMomentGibbsSampler	156
FullMomentHerding	157
Function	159
AbstractMaxSat	66
MaxNae3Sat	270
MaxSat	272
DeceptiveJump	117
Decorator	123
Controller	114
Cache	91
CallCounter	94
OnBudgetFunction	341
ProgressTracker	395
StopOnTarget	472
StopOnMaximum	469
Modifier	289
AdditiveGaussianNoise	69
FunctionMapComposition	168
OppositeFunction	354
ParsedModifier	360
PriorNoise	391
EqualProducts	130
Factorization	136

FourPeaks	148
FunctionPlugin	172
Hiff	196
Jump	239
Labs	241
LeadingOnes	243
LinearFunction	246
LongPath	259
MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >	278
MultiobjectiveFunctionAdapter	296
MultivariateFunctionAdapter< Fn, Rep, Conv >	299
NearestNeighborIsingModel1	310
NearestNeighborIsingModel2	314
Needle	319
NkLandscape	326
OneMax	344
Partition	367
PermutationFunctionAdapter< Fn >	376
Plateau	380
PythonFunction	405
Qubo	408
Ridge	440
SixPeaks	459
SummationCancellation	479
SinusSummationCancellation	456
Trap	491
UniversalFunctionAdapter	522
WalshExpansion	528
WalshExpansion1	532
WalshExpansion2	535
Function	165
MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >	282
MultivariateFunctionAdapter< Fn, Rep, Conv >	303
PythonFunction	407
UniversalFunctionAdapter	524
FunctionFactory	167
CommandLineFunctionFactory	102
FunctionFactory	167
CommandLineFunctionFactory	104
Generator	173
HncoEvaluator	198
HncoFitness	199
HncoOptions	200
HncoOptions	214
Implementation	222
IntegerCategoricalRepresentation	229
Iterator	238
ExtendedHypercubeIterator	134
HypercubeIterator	221
NeighborhoodIterator	324
HammingSphereIterator	186
SingleBitFlipIterator	455
LinearCategoricalRepresentation	245
LogContext	256
ProgressTrackerContext	398
Logger	257
Map	264

AffineMap	71
Injection	228
LinearMap	250
MapComposition	266
Permutation	374
Projection	400
Translation	486
TsAffineMap	501
MapgenOptions	268
Neighborhood	321
MultiBitFlip	294
HammingBall	181
HammingSphere	183
StandardBitMutation	462
SingleBitFlip	453
Nsga2ParetoFrontComputation	339
OppositeAbsoluteValue< T >	353
OppositeSquaredMagnitude< T >	356
ParsedMultivariateFunction< Parser >	362
ParsedMultivariateFunction< Parser >	364
PermutationRepresentation	379
PlusSelection	382
Population	383
Population	388
DyadicIntegerRepresentation< T >::Precision	391
RandomSelection	430
FitnessProportionateSelection	146
BoltzmannSelection	89
TournamentSelection	482
UniformSelection	519
InformationTheoreticEa::Replacement	435
BmPbil< GibbsSampler >::ResetMode	436
BmPbil< GibbsSampler >::SamplingMode	442
TsAffineMap::SamplingMode	443
ScalarToDouble< T >	444
SquaredMagnitude< T >	461
StopWatch	475
Sudoku	476
TournamentSelection< T, Compare >	484
TournamentSelection< double, std::greater< double > >	484
TournamentSelection< hnco::multiobjective::algorithm::FrontDistancePair, std::less< hnco::multiobjective::algorithm::FrontDistancePair > >	484
Transvection	488
TriangularMoment	494
TriangularMomentGibbsSampler	498
TriangularMomentHerdin	499
RamUmda::TsLengthMode	504
Tsp	505
UniversalFunction	520
UniversalFunction	521
ValueSetRepresentation< T >	527
WalshTerm	540

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

AbsoluteValue< T >	
Absolute value of a scalar	65
AbstractMaxSat	
Abstract class for MaxSat-like functions	66
AdditiveGaussianNoise	
Additive Gaussian Noise	69
AffineMap	
Affine map	71
Algorithm	
Abstract search algorithm	74
Algorithm	
Abstract multiobjective search algorithm	78
AlgorithmFactory	
Algorithm factory	80
AlgorithmFactory	
Algorithm factory	81
BiasedCrossover	
Biased crossover	82
BmPbil< GibbsSampler >	
Boltzmann machine PBIL	83
BoltzmannSelection	
Boltzmann selection	89
Cache	
Cache	91
CallCounter	
Call counter	94
CommandLineAlgorithmFactory	
Command line algorithm factory	96
CommandLineAlgorithmFactory	
Command line algorithm factory	98
CommandLineApplication	
Command line application	99
CommandLineApplication	
Command line application	101
CommandLineFunctionFactory	
Command line function factory	102

CommandLineFunctionFactory	
Command line function factory	104
CommaSelection	
Comma selection	104
CompactGa	
Compact genetic algorithm	105
CompleteSearch	
Complete search	110
ComplexRepresentation< ScalarRep >	
Complex representation	112
Controller	
Function controller	114
Crossover	
Crossover	116
DeceptiveJump	
Deceptive jump	117
DecoratedFunctionFactory	
Decorated function factory	119
Decorator	
Algorithm decorator	121
Decorator	
Function decorator	123
DyadicFloatRepresentation< T >	
Dyadic float representation	125
DyadicIntegerRepresentation< T >	
Dyadic integer representation	127
EqualProducts	
Equal products	130
ProgressTracker::Event	
Event	134
ExtendedHypercubeIterator	
Extended Hypercube iterator	134
Factorization	
Factorization	136
FfgenOptions	
Command line options for ffgen	139
FirstAscentHillClimbing	
First ascent hill climbing	143
FitnessProportionateSelection	
Fitness proportionate selection	146
FourPeaks	
Four Peaks	148
FrontDistancePair	
Front-distance pair	151
FullMoment	
Full moment	151
FullMomentGibbsSampler	
Gibbs sampler with full moments	156
FullMomentHerdning	
Herdning with full moments	157
Function	
Function	159
Function	
Function	165
FunctionFactory	
Function factory	167
FunctionFactory	
Function factory	167

FunctionMapComposition	
Composition of a function and a map	168
FunctionPlugin	
Function plugin	172
Generator	
Random number generator	173
GeneticAlgorithm	
Genetic algorithm	175
Gomea	
GOMEA	178
HammingBall	
Hamming ball	181
HammingSphere	
Hamming sphere	183
HammingSphereIterator	
Hamming sphere neighborhood iterator	186
Hboa	
Hierarchical Bayesian Optimization Algorithm	188
Hea< Herding >	
Herding evolutionary algorithm	190
Hiff	
Hierarchical if and only if	196
HncoEvaluator	
Evaluator for HNCO functions	198
HncoFitness	
Fitness for HNCO functions	199
HncoOptions	
Command line options for hnco	200
HncoOptions	
Command line options for hnco-mo	214
Human	
Human	218
HypercubeIterator	
Hypercube iterator	221
Implementation	
Implementation	222
InformationTheoreticEa	
Information-theoretic evolutionary algorithm	223
Injection	
Injection	228
IntegerCategoricalRepresentation	
Integer categorical representation	229
IterativeAlgorithm	
Iterative search	231
IterativeAlgorithm	
Iterative algorithm	235
Iterator	
Iterator over bit vectors	238
Jump	
Jump	239
Labs	
Low autocorrelation binary sequences	241
LastEvaluation	
Last evaluation	243
LeadingOnes	
Leading ones	243
LinearCategoricalRepresentation	
Linear categorical representation	245

LinearFunction	
Linear function	246
LinearMap	
Linear map	250
LocalSearchAlgorithm< Neighborhood >	
Local search algorithm	253
LogContext	
Log context	256
Logger	
Logger	257
LongPath	
Long path	259
Ltga	
Linkage Tree Genetic Algorithm	262
Map	
Map	264
MapComposition	
Map composition	266
MapgenOptions	
Command line options for mapgen	268
MaxNae3Sat	
Max not-all-equal 3SAT	270
MaxSat	
MAX-SAT	272
Mimic	
Mutual information maximizing input clustering	275
MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >	
Mixed-representation multivariate function adapter	278
MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >	
Mixed-representation multivariate function adapter	282
Mmas	
Max-min ant system	285
Modifier	
Function modifier	289
MuCommaLambdaEa	
(mu, lambda) EA	290
MultiBitFlip	
Multi bit flip	294
MultiobjectiveFunctionAdapter	
Multiobjective function adapter	296
MultivariateFunctionAdapter< Fn, Rep, Conv >	
Multivariate function adapter	299
MultivariateFunctionAdapter< Fn, Rep, Conv >	
Multivariate function adapter	303
MuPlusLambdaEa	
(mu+lambda) EA	306
NearestNeighborsIsingModel1	
Nearest neighbor Ising model in one dimension	310
NearestNeighborsIsingModel2	
Nearest neighbor Ising model in two dimensions	314
Needle	
Needle in a haystack	319
Neighborhood	
Neighborhood	321
NeighborhoodIterator	
Neighborhood iterator	324
NkLandscape	
NK landscape	326

NpsPbil	Population-based incremental learning with negative and positive selection	330
Nsga2	NSGA-II	335
Nsga2ParetoFrontComputation	Pareto front computation from the NSGA-II paper	339
OnBudgetFunction	Function with a limited number of evaluations	341
OneMax	OneMax	344
OnePlusLambdaCommaLambdaGa	(1+(lambda, lambda)) genetic algorithm	346
OnePlusOneEa	(1+1) EA	350
OppositeAbsoluteValue< T >	Opposite absolute value of a scalar	353
OppositeFunction	Opposite function	354
OppositeSquaredMagnitude< T >	Opposite squared magnitude of a complex number	356
ParameterLessPopulationPyramid	Parameter-less Population Pyramid	357
ParsedModifier	Parsed modifier	360
ParsedMultivariateFunction< Parser >	Parsed multivariate function	362
ParsedMultivariateFunction< Parser >	Parsed multivariate function	364
Partition	Partition	367
Pbil	Population-based incremental learning	370
Permutation	Permutation	374
PermutationFunctionAdapter< Fn >	Permutation function adapter	376
PermutationRepresentation	Permutation representation	379
Plateau	Plateau	380
PlusSelection	Plus selection	382
Population	Population	383
Population	Population	388
DyadicIntegerRepresentation< T >::Precision	Precision	391
PriorNoise	Prior noise	391
ProgressTracker	Progress tracker	395
ProgressTrackerContext	Log context for ProgressTracker	398
Projection	Projection	400
PvAlgorithm	Probability vector algorithm	402

PythonFunction	
Python function	405
PythonFunction	
Python function	407
Qubo	
Quadratic unconstrained binary optimization	408
RamUmda	
UMDA with random affine maps	412
RamUmda2	
UMDA with random affine maps and two probability vectors	417
RandomLocalSearch	
Random local search	423
RandomSearch	
Random search	427
RandomSelection	
Random selection	430
RandomWalk	
Random walk	431
InformationTheoreticEa::Replacement	
Selection for replacement	435
BmPbil< GibbsSampler >::ResetMode	
Markov chain reset mode	436
Restart	
Restart	437
Ridge	
Ridge	440
BmPbil< GibbsSampler >::SamplingMode	
Markov chain sampling mode	442
TsAffineMap::SamplingMode	
Sampling mode	443
ScalarToDouble< T >	
Convert a scalar to a double	444
SelfAdjustingOnePlusOneEa	
Self-adjusting (1+1) evolutionary algorithm	445
SimulatedAnnealing	
Simulated annealing	449
SingleBitFlip	
One bit neighborhood	453
SingleBitFlipIterator	
Single bit flip neighborhood iterator	455
SinusSummationCancellation	
Summation cancellation with sinus	456
SixPeaks	
Six Peaks	459
SquaredMagnitude< T >	
Squared magnitude of a complex number	461
StandardBitMutation	
Standard bit mutation	462
SteepestAscentHillClimbing	
Steepest ascent hill climbing	466
StopOnMaximum	
Stop on maximum	469
StopOnTarget	
Stop on target	472
StopWatch	
Stop watch	475
Sudoku	
Sudoku	476

SummationCancellation	
Summation cancellation	479
TargetReached	
Target reached	481
TournamentSelection	
Tournament selection	482
TournamentSelection< T, Compare >	
Tournament selection	484
Translation	
Translation	486
Transvection	
Transvection	488
Trap	
Trap	491
TriangularMoment	
Triangular moment	494
TriangularMomentGibbsSampler	
Gibbs sampler with triangular moments	498
TriangularMomentHerdin	
Herdin with lower triangular Walsh moment	499
TsAffineMap	
Transvection sequence affine map	501
RamUmda::TsLengthMode	
Transvection sequence length mode	504
Tsp	
Traveling salesman problem	505
TwoRateOnePlusLambdaEa	
Two-rate (1+lambda) evolutionary algorithm	509
Umda	
Univariate marginal distribution algorithm	513
UniformCrossover	
Uniform crossover	518
UniformSelection	
Uniform selection	519
UniversalFunction	
Universal function	520
UniversalFunction	
Universal function	521
UniversalFunctionAdapter	
Universal function adapter	522
UniversalFunctionAdapter	
Universal function adapter	524
ValueSetRepresentation< T >	
Value set	527
WalshExpansion	
Walsh expansion	528
WalshExpansion1	
Walsh expansion of degree 1	532
WalshExpansion2	
Walsh expansion of degree 2	535
WalshTerm	
Walsh transform term	540

Chapter 4

Namespace Documentation

4.1 hnco Namespace Reference

top-level HNCO namespace

Namespaces

- namespace [algorithm](#)
Algorithms.
- namespace [app](#)
Classes for applications.
- namespace [exception](#)
Exceptions.
- namespace [function](#)
Functions defined on bit vectors.
- namespace [logging](#)
Logging.
- namespace [map](#)
Maps.
- namespace [multiobjective](#)
Multiobjective optimization.
- namespace [neighborhood](#)
Neighborhoods for local search.
- namespace [random](#)
Random numbers.
- namespace [representation](#)
Representations.

Classes

- class [ExtendedHypercubeIterator](#)
Extended Hypercube iterator.
- class [HypercubeIterator](#)
Hypercube iterator.
- class [Iterator](#)
Iterator over bit vectors
- class [StopWatch](#)
Stop watch.

Functions

- void **ensure** (bool b, const std::string message)
Ensure that a condition is satisfied or throw a runtime exception.
- void **fail_with** (const std::string message, int code)
Fail with message and code.
- template<class A, class B >
bool **have_same_size** (const A &a, const B &b)
Check whether two containers have the same size.
- template<class T >
T **square** (T x)
Generic square function.
- double **logistic** (double x)
Logistic function (sigmoid)
- template<typename Iter >
std::string **join** (Iter begin, Iter end, std::string const &separator)
Convert to string and join elements of a container (from SO)

Load from and save to boost archives

- template<typename T >
void **load_from_archive** (T &object, std::string path, std::string name)
Load from a boost archive.
- template<typename T >
void **save_to_archive** (const T &object, std::string path, std::string name)
Save to a boost archive.

Range checking

- bool **is_in_range** (int i, int a, int b)
Check whether an index is in a given range.
- bool **is_in_range** (int i, int n)
Check whether an index is in a given range.

Intervals

- bool **is_in_interval** (double x, double a, double b)
Check whether a double value belongs to a given interval.

Types and functions related to bit matrices

Output and input-output function parameters appear at the beginning of the parameter list.

Output and input-output bit_matrix_t parameters are passed by reference and must have the right size for the considered function.

Input object parameters are passed by const reference.

- using **bit_matrix_t** = std::vector< **bit_vector_t** >
Bit matrix.
- **bit_matrix_t** **bm_rectangular** (int nrows, int ncols)
Make a rectangular bit matrix.

- [bit_matrix_t](#) **bm_square** (int n)
Make a square bit matrix.
- void **bm_identity** ([bit_matrix_t](#) &M)
Set a matrix to the identity matrix.
- [bit_matrix_t](#) **bm_identity** (int n)
Make an identity bit matrix.
- void **bm_transpose** ([bit_matrix_t](#) &N, const [bit_matrix_t](#) &M)
Transpose a bit matrix.
- [bit_matrix_t](#) **bm_transpose** (const [bit_matrix_t](#) &M)
Transpose a bit matrix.
- void **bm_display** (const [bit_matrix_t](#) &M, std::ostream &stream)
Display bit matrix.
- bool **bm_is_valid** (const [bit_matrix_t](#) &M)
Check whether a bit matrix is valid.
- int **bm_num_rows** (const [bit_matrix_t](#) &M)
Number of rows.
- int **bm_num_columns** (const [bit_matrix_t](#) &M)
Number of columns.
- bool **bm_is_square** (const [bit_matrix_t](#) &M)
Check whether the matrix is a square matrix.
- bool **bm_is_identity** (const [bit_matrix_t](#) &M)
Check whether the matrix is the identity matrix.
- bool **bm_is_upper_triangular** (const [bit_matrix_t](#) &M)
Check whether the matrix is upper triangular.
- void **bm_resize** ([bit_matrix_t](#) &M, int nrow, int ncol)
Resize a bit matrix.
- void **bm_resize** ([bit_matrix_t](#) &M, int nrow)
Resize a bit matrix and make it a square matrix.
- void **bm_clear** ([bit_matrix_t](#) &M)
Clear bit matrix.
- void **bm_random** ([bit_matrix_t](#) &M)
Sample a random bit matrix.
- void **bm_swap_rows** ([bit_matrix_t](#) &M, int i, int j)
Swap two rows.
- void **bm_add_rows** ([bit_matrix_t](#) &M, int dest, int src)
Add two rows.
- void **bm_add_columns** ([bit_matrix_t](#) &M, int dest, int src)
Add two columns.
- void **bm_set_column** ([bit_matrix_t](#) &M, int j, const [bit_vector_t](#) &bv)
Set column.
- void **bm_row_echelon_form** ([bit_matrix_t](#) &A)
Compute a row echelon form of a matrix.
- int **bm_rank** (const [bit_matrix_t](#) &A)
Compute the rank of a matrix.
- bool **bm_solve** ([bit_matrix_t](#) &A, [bit_vector_t](#) &b)
Solve a linear system.
- bool **bm_solve_upper_triangular** ([bit_matrix_t](#) &A, [bit_vector_t](#) &b)
Solve a linear system in upper triangular form.
- bool **bm_invert** ([bit_matrix_t](#) &M, [bit_matrix_t](#) &N)
Invert a bit matrix.
- void **bm_multiply** ([bit_vector_t](#) &y, const [bit_matrix_t](#) &M, const [bit_vector_t](#) &x)
Multiply a bit matrix and a bit vector.

Types and functions related to bits

- using **bit_t** = std::uint8_t
Bit.
- **bit_t bit_add** (bit_t b1, bit_t b2)
Add bits.
- void **bit_flip** (bit_t &b, bit_t c)
Conditionally flip a bit.
- void **bit_flip** (bit_t &b)
Flip a bit.
- **bit_t bit_random** (double p)
Sample a random bit.

Types and functions related to bit vectors

Output and input-output function parameters appear at the beginning of the parameter list.

Output and input-output bit_vector_t parameters are passed by reference and must have the right size for the considered function.

Input bit_vector_t parameters are passed by const reference.

- using **bit_vector_t** = std::vector< bit_t >
Bit vector.
- std::string **bv_domain** (const bit_vector_t &x)
Display bit vector.
- void **bv_display** (const bit_vector_t &v, std::ostream &stream)
Display bit vector.
- bool **bv_is_valid** (const bit_vector_t &x)
Check whether the bit vector is valid.
- bool **bv_is_zero** (const bit_vector_t &x)
Check whether the bit vector is zero.
- int **bv_hamming_weight** (const bit_vector_t &x)
Hamming weight.
- int **bv_hamming_weight** (const std::vector< bool > &x)
Hamming weight.
- int **bv_hamming_distance** (const bit_vector_t &x, const bit_vector_t &y)
Hamming distance between two bit vectors.
- **bit_t bv_dot_product** (const bit_vector_t &x, const bit_vector_t &y)
Dot product.
- **bit_t bv_dot_product** (const bit_vector_t &x, const std::vector< bool > &y)
Dot product.
- void **bv_clear** (bit_vector_t &x)
Clear bit vector.
- void **bv_add** (bit_vector_t &dest, const bit_vector_t &src)
Add two bit vectors.
- void **bv_add** (bit_vector_t &dest, const bit_vector_t &x, const bit_vector_t &y)
Add two bit vectors.
- void **bv_flip** (bit_vector_t &x, int i)
Flip a single bit.

- void **bv_flip** ([bit_vector_t](#) &x, const [sparse_bit_vector_t](#) &sbv)
Flip many bits given by a sparse bit vector.
- void **bv_random** ([bit_vector_t](#) &x)
Sample a random bit vector.
- void **bv_random** ([bit_vector_t](#) &x, int k)
Sample a random bit vector with given Hamming weight.
- void **bv_to_vector_bool** (std::vector< bool > &y, const [bit_vector_t](#) &x)
Convert a bit vector to a bool vector.
- void **bv_from_vector_bool** ([bit_vector_t](#) &x, const std::vector< bool > &y)
Convert a bool vector to a bit vector.
- std::size_t **bv_to_size_type** (const [bit_vector_t](#) &x)
Convert a small bit vector to a size_t.
- std::size_t **bv_to_size_type** (const [bit_vector_t](#) &x, int start, int stop)
Convert a slice of a small bit vector to a size_t.
- void **bv_from_size_type** ([bit_vector_t](#) &x, std::size_t u)
Convert a size_t to a small bit vector.
- [bit_vector_t](#) **bv_from_string** (const std::string &str)
Read a bit vector from a string.
- [bit_vector_t](#) **bv_from_stream** (std::istream &stream)
Read a bit vector from a stream.

Types and functions related to permutations

- using **permutation_t** = std::vector< int >
Permutation type
- bool **perm_is_valid** (const [permutation_t](#) &permutation)
Check that a vector represents a permutation.
- void **perm_identity** ([permutation_t](#) &s)
Identity permutation.
- void **perm_shuffle** ([permutation_t](#) &s)
Shuffle a permutation.
- void **perm_random** ([permutation_t](#) &s)
Sample a random permutation.
- void **perm_display** (const [permutation_t](#) &permutation, std::ostream &stream)
Display a permutation.

Types and functions related to sparse bit vectors

- using **sparse_bit_vector_t** = std::vector< int >
Sparse bit vector.
- bool **sbv_is_valid** (const [sparse_bit_vector_t](#) &sbv)
Check that a sparse bit vector is valid.
- bool **sbv_is_valid** (const [sparse_bit_vector_t](#) &sbv, int n)
Check that a sparse bit vector is valid.
- void **sbv_display** (const [sparse_bit_vector_t](#) &v, std::ostream &stream)
Display sparse bit vector.

4.1.1 Detailed Description

top-level HNCO namespace

4.1.2 Typedef Documentation

4.1.2.1 `sparse_bit_vector_t`

```
using sparse_bit_vector_t = std::vector<int>
```

Sparse bit vector.

A sparse bit vector is represented as an vector containing the indices of its non-zero components. The indices must be sorted in ascending order.

A sparse bit vector does not know the dimension of the space it belongs to.

Definition at line 45 of file [sparse-bit-vector.hh](#).

4.1.3 Function Documentation

4.1.3.1 `bit_add()`

```
bit_t bit_add (
    bit_t b1,
    bit_t b2 ) [inline]
```

Add bits.

Parameters

<i>b1</i>	First operand
<i>b2</i>	Second operand

Returns

`b1` xor `b2`

Definition at line 55 of file [bit-vector.hh](#).

4.1.3.2 `bit_flip()` [1/2]

```
void bit_flip (
    bit_t & b ) [inline]
```

Flip a bit.

Parameters

<i>b</i>	Bit to flip
----------	-------------

Definition at line 69 of file [bit-vector.hh](#).

4.1.3.3 bit_flip() [2/2]

```
void bit_flip (
    bit_t & b,
    bit_t c ) [inline]
```

Conditionally flip a bit.

Implements $b = b \text{ xor } c$

Parameters

<i>b</i>	Bit to flip
<i>c</i>	Operand

Definition at line 63 of file [bit-vector.hh](#).

4.1.3.4 bit_random()

```
bit_t bit_random (
    double p ) [inline]
```

Sample a random bit.

Parameters

<i>p</i>	Probability of 1
----------	------------------

Definition at line 75 of file [bit-vector.hh](#).

4.1.3.5 bm_add_columns()

```
void bm_add_columns (
    bit_matrix_t & M,
    int dest,
    int src )
```

Add two columns.

Equivalent to $\text{dest} = \text{dest} + \text{src}$.

Parameters

<i>M</i>	Bit matrix
<i>dest</i>	Destination column
<i>src</i>	Source column

Warning

M is modified by the function.

Definition at line 187 of file [bit-matrix.cc](#).

4.1.3.6 bm_add_rows()

```
void bm_add_rows (
    bit_matrix_t & M,
    int dest,
    int src )
```

Add two rows.

Equivalent to `dest = dest + src`.

Parameters

<i>M</i>	Bit matrix
<i>dest</i>	Destination row
<i>src</i>	Source row

Definition at line 178 of file [bit-matrix.cc](#).

4.1.3.7 bm_identity() [1/2]

```
void bm_identity (
    bit_matrix_t & M )
```

Set a matrix to the identity matrix.

Precondition

`bm_is_square(M)`

Definition at line 39 of file [bit-matrix.cc](#).

4.1.3.8 bm_identity() [2/2]

```
bit_matrix_t bm_identity (
    int n )
```

Make an identity bit matrix.

Parameters

n	Dimension
-----	-----------

Returns

An order n identity matrix

Definition at line 50 of file [bit-matrix.cc](#).

4.1.3.9 bm_invert()

```
bool bm_invert (
    bit_matrix_t & M,
    bit_matrix_t & N )
```

Invert a bit matrix.

Parameters

M	Bit matrix
N	Inverse bit matrix

Precondition

```
bm_is_square(M)
bm_is_square(N)
bm_num_rows(M) == bm_num_rows(N)
```

Returns

true if M is invertible

Warning

M is modified by the function. Provided that M is invertible, after returning from the function, M is the identity matrix and N is the computed inverse matrix.

Definition at line 316 of file [bit-matrix.cc](#).

4.1.3.10 bm_multiply()

```
void bm_multiply (
    bit_vector_t & y,
    const bit_matrix_t & M,
    const bit_vector_t & x )
```

Multiply a bit matrix and a bit vector.

Computes $y = Mx$.

Parameters

y	Output bit vector
M	Bit matrix
x	Bit vector

Definition at line 360 of file [bit-matrix.cc](#).

4.1.3.11 `bm_rank()`

```
int bm_rank (
    const bit\_matrix\_t & A )
```

Compute the rank of a matrix.

Precondition

A must be in row echelon form.

Definition at line 244 of file [bit-matrix.cc](#).

4.1.3.12 `bm_row_echelon_form()`

```
void bm_row_echelon_form (
    bit\_matrix\_t & A )
```

Compute a row echelon form of a matrix.

Warning

A is modified by the function.

Definition at line 213 of file [bit-matrix.cc](#).

4.1.3.13 `bm_set_column()`

```
void bm_set_column (
    bit\_matrix\_t & M,
    int j,
    const bit\_vector\_t & bv )
```

Set column.

Set a column to a given bit vector.

Parameters

M	Bit matrix
j	Column index
bv	Bit vector

Precondition

`bm_num_rows(M) == bv.size()`

Definition at line 202 of file [bit-matrix.cc](#).

4.1.3.14 `bm_solve()`

```
bool bm_solve (
    bit_matrix_t & A,
    bit_vector_t & b )
```

Solve a linear system.

Solve the linear equation $Ax = b$.

Parameters

<i>A</i>	Matrix
<i>b</i>	Right hand side

Precondition

`bm_is_square(A)`
`bm_num_rows(A) == b.size()`

Returns

true if the system has a unique solution

Warning

Both *A* and *b* are modified by the function. Provided that *A* is invertible, after returning from the function, *A* is the identity matrix and *b* is the unique solution to the linear equation.

Definition at line 262 of file [bit-matrix.cc](#).

4.1.3.15 `bm_solve_upper_triangular()`

```
bool bm_solve_upper_triangular (
    bit_matrix_t & A,
    bit_vector_t & b )
```

Solve a linear system in upper triangular form.

Solve the linear equation $Ax = b$.

Parameters

<i>A</i>	Upper triangular matrix
<i>b</i>	Right hand side

Precondition

```
bm_is_square(A)
bm_num_rows(A) == b.size()
bm_is_upper_triangular(A)
```

Returns

true if the system has a unique solution

Warning

Both A and b are modified by the function. Provided that A is invertible, after returning from the function, A is the identity matrix and b is the unique solution to the linear equation.

Definition at line 295 of file [bit-matrix.cc](#).

4.1.3.16 bm_transpose() [1/2]

```
void bm_transpose (
    bit_matrix_t & N,
    const bit_matrix_t & M )
```

Transpose a bit matrix.

Precondition

```
bm_num_columns(N) == bm_num_rows(M)
bm_num_rows(N) == bm_num_columns(M)
```

Definition at line 59 of file [bit-matrix.cc](#).

4.1.3.17 bm_transpose() [2/2]

```
bit_matrix_t bm_transpose (
    const bit_matrix_t & M )
```

Transpose a bit matrix.

Parameters

<i>M</i>	Bit matrix
----------	------------

Returns

Transposed bit matrix

Definition at line 73 of file [bit-matrix.cc](#).

4.1.3.18 bv_add() [1/2]

```
void bv_add (
    bit_vector_t & dest,
    const bit_vector_t & src )
```

Add two bit vectors.

Equivalent to `dest = dest + src`.

Parameters

<i>dest</i>	Destination bit vector
<i>src</i>	Source bit vector

Warning

Vectors must be of the same size.

Definition at line 124 of file [bit-vector.cc](#).

4.1.3.19 bv_add() [2/2]

```
void bv_add (
    bit_vector_t & dest,
    const bit_vector_t & x,
    const bit_vector_t & y )
```

Add two bit vectors.

Equivalent to `dest = x + y`.

Parameters

<i>dest</i>	Destination bit vector
<i>x</i>	First operand
<i>y</i>	Second operand

Warning

Vectors must be of the same size.

Definition at line 134 of file [bit-vector.cc](#).

4.1.3.20 bv_flip()

```
void bv_flip (
    bit_vector_t & x,
    const sparse_bit_vector_t & sbv )
```

Flip many bits given by a sparse bit vector.

Parameters

<i>x</i>	Input-output bit vector
<i>sbv</i>	Bits to flip

Definition at line 93 of file [bit-vector.cc](#).

4.1.3.21 `bv_from_size_type()`

```
void bv_from_size_type (
    bit_vector_t & x,
    std::size_t u )
```

Convert a `size_t` to a small bit vector.

Parameters

<i>x</i>	Output bit vector
<i>u</i>	Unsigned integer representing a bit vector

Precondition

`x.size() <= 8 * sizeof(std::size_t)`

Warning

Depending on the size of the output bit vector, some bits might be lost. The original bit vector can be reconstructed only if it is small and the unsigned integer `u` is the result of `bv_to_size_type`.

Definition at line 203 of file [bit-vector.cc](#).

4.1.3.22 `bv_from_stream()`

```
bit_vector_t bv_from_stream (
    std::istream & stream )
```

Read a bit vector from a stream.

Parameters

<i>stream</i>	Input stream
---------------	--------------

Returns

A `bit_vector_t`

Definition at line 234 of file [bit-vector.cc](#).

4.1.3.23 `bv_from_string()`

```
bit_vector_t bv_from_string (
    const std::string & str )
```

Read a bit vector from a string.

Parameters

<i>str</i>	Input string
------------	--------------

Returns

A `bit_vector_t`

Definition at line 218 of file [bit-vector.cc](#).

4.1.3.24 `bv_from_vector_bool()`

```
void bv_from_vector_bool (
    bit_vector_t & x,
    const std::vector< bool > & y )
```

Convert a bool vector to a bit vector.

Warning

Vectors must be of the same size.

Definition at line 158 of file [bit-vector.cc](#).

4.1.3.25 `bv_to_size_type()` [1/2]

```
std::size_t bv_to_size_type (
    const bit_vector_t & x )
```

Convert a small bit vector to a `size_t`.

`x[0]` is the least significant bit.

Parameters

<i>x</i>	Input bit vector
----------	------------------

Returns

An unsigned integer representing `x`

Precondition

`x.size() <= 8 * sizeof(std::size_t)`

Definition at line 171 of file [bit-vector.cc](#).

4.1.3.26 bv_to_size_type() [2/2]

```
std::size_t bv_to_size_type (
    const bit_vector_t & x,
    int start,
    int stop )
```

Convert a slice of a small bit vector to a `size_t`.

`x[start]` is the least significant bit.

`x[stop-1]` is the most significant bit.

Parameters

<i>x</i>	Input bit vector
<i>start</i>	Start bit
<i>stop</i>	Stop bit

Returns

An unsigned integer representing `x[start]`, ..., `x[stop-1]`

Precondition

`start` in `[0, x.size())`

`stop` in `[start+1, x.size())`

`(stop - start) <= 8 * sizeof(std::size_t)`

Definition at line 186 of file [bit-vector.cc](#).

4.1.3.27 bv_to_vector_bool()

```
void bv_to_vector_bool (
    std::vector< bool > & y,
    const bit_vector_t & x )
```

Convert a bit vector to a bool vector.

Warning

Vectors must be of the same size.

Definition at line 145 of file [bit-vector.cc](#).

4.1.3.28 ensure()

```
void ensure (
    bool b,
    const std::string message ) [inline]
```

Ensure that a condition is satisfied or throw a runtime exception.

Parameters

<i>b</i>	Boolean
<i>message</i>	Message to display if the boolean is false

Definition at line 36 of file [util.hh](#).

4.1.3.29 fail_with()

```
void fail_with (
    const std::string message,
    int code ) [inline]
```

Fail with message and code.

Parameters

<i>message</i>	Message
<i>code</i>	Code

Definition at line 48 of file [util.hh](#).

4.1.3.30 is_in_range() [1/2]

```
bool is_in_range (
    int i,
    int a,
    int b ) [inline]
```

Check whether an index is in a given range.

Parameters

<i>i</i>	Index
<i>a</i>	Lower bound
<i>b</i>	Upper bound (excluded)

Returns

true if $i \geq a$ and $i < b$

Definition at line 65 of file [util.hh](#).

4.1.3.31 is_in_range() [2/2]

```
bool is_in_range (
    int i,
    int n ) [inline]
```

Check whether an index is in a given range.

The lower bound is implicit and is equal to 0.

Parameters

<i>i</i>	Index
<i>n</i>	Upper bound (excluded)

Returns

true if $i \geq 0$ and $i < n$

Definition at line 74 of file [util.hh](#).

4.1.3.32 load_from_archive()

```
template<typename T >
void load_from_archive (
    T & object,
    std::string path,
    std::string name )
```

Load from a boost archive.

Parameters

<i>object</i>	Object to load
<i>path</i>	Path of the file
<i>name</i>	Class name

Definition at line 44 of file [serialization.hh](#).

4.1.3.33 perm_identity()

```
void perm_identity (
    permutation_t & s ) [inline]
```

Identity permutation.

Warning

This function does not set the size of the permutation.

Definition at line 47 of file [permutation.hh](#).

4.1.3.34 perm_random()

```
void perm_random (
    permutation_t & s ) [inline]
```

Sample a random permutation.

Warning

This function does not set the size of the permutation.

Definition at line 60 of file [permutation.hh](#).

4.1.3.35 save_to_archive()

```
template<typename T >
void save_to_archive (
    const T & object,
    std::string path,
    std::string name )
```

Save to a boost archive.

Parameters

<i>object</i>	Object to save
<i>path</i>	Path of the file
<i>name</i>	Class name

Definition at line 64 of file [serialization.hh](#).

4.1.3.36 sbv_is_valid() [1/2]

```
bool sbv_is_valid (
    const sparse_bit_vector_t & sbv )
```

Check that a sparse bit vector is valid.

A sparse bit vector is valid if:

- Its elements are non negative.
- Its elements are sorted in non-descending order.

Definition at line 30 of file [sparse-bit-vector.cc](#).

4.1.3.37 sbv_is_valid() [2/2]

```
bool sbv_is_valid (
    const sparse_bit_vector_t & sbv,
    int n )
```

Check that a sparse bit vector is valid.

A sparse bit vector is valid if:

- Its elements are non negative.
- Its elements are sorted in non-descending order.
- Its elements are valid indices w.r.t. the given dimension.

Parameters

<i>sbv</i>	Input sparse bit vector
<i>n</i>	Dimension

Definition at line 41 of file [sparse-bit-vector.cc](#).

4.2 hnco::algorithm Namespace Reference

Algorithms.

Namespaces

- namespace [fast_efficient_p3](#)
Algorithms from the FastEfficientP3 library.
- namespace [gomea](#)
GOMEA.
- namespace [walsh_moment](#)
Algorithms using Walsh moments.

Classes

- class [Algorithm](#)
Abstract search algorithm.
- class [BiasedCrossover](#)
Biased crossover.
- class [BoltzmannSelection](#)
Boltzmann selection.
- class [CommaSelection](#)
Comma selection.
- class [CompactGa](#)
Compact genetic algorithm.

- class [CompleteSearch](#)
Complete search.
- class [Crossover](#)
Crossover
- class [Decorator](#)
Algorithm decorator.
- class [FirstAscentHillClimbing](#)
First ascent hill climbing.
- class [FitnessProportionateSelection](#)
Fitness proportionate selection.
- class [GeneticAlgorithm](#)
Genetic algorithm.
- class [Human](#)
Human
- class [InformationTheoreticEa](#)
Information-theoretic evolutionary algorithm.
- class [IterativeAlgorithm](#)
Iterative search.
- class [LocalSearchAlgorithm](#)
Local search algorithm.
- class [Mimic](#)
Mutual information maximizing input clustering.
- class [Mmas](#)
Max-min ant system.
- class [MuCommaLambdaEa](#)
(mu, lambda) EA.
- class [MuPlusLambdaEa](#)
(mu+lambda) EA.
- class [NpsPbil](#)
Population-based incremental learning with negative and positive selection.
- class [OnePlusLambdaCommaLambdaGa](#)
(1+(lambda, lambda)) genetic algorithm.
- class [OnePlusOneEa](#)
(1+1) EA.
- class [Pbil](#)
Population-based incremental learning.
- class [PlusSelection](#)
Plus selection.
- struct [Population](#)
Population
- class [PvAlgorithm](#)
Probability vector algorithm.
- class [RamUmda](#)
UMDA with random affine maps.
- class [RamUmda2](#)
UMDA with random affine maps and two probability vectors.
- class [RandomLocalSearch](#)
Random local search.
- class [RandomSearch](#)
Random search.
- class [RandomSelection](#)

- Random selection.*
 - class [RandomWalk](#)
 - Random walk.*
 - class [Restart](#)
 - Restart.*
 - class [SelfAdjustingOnePlusOneEa](#)
 - Self-adjusting (1+1) evolutionary algorithm.*
 - class [SimulatedAnnealing](#)
 - Simulated annealing.*
 - class [SteepestAscentHillClimbing](#)
 - Steepest ascent hill climbing.*
 - class [TournamentSelection](#)
 - Tournament selection.*
 - class [TwoRateOnePlusLambdaEa](#)
 - Two-rate (1+lambda) evolutionary algorithm.*
 - class [Umda](#)
 - Univariate marginal distribution algorithm.*
 - class [UniformCrossover](#)
 - Uniform crossover.*
 - class [UniformSelection](#)
 - Uniform selection.*

Typedefs

- using **solution_t** = std::pair< [bit_vector_t](#), double >
 - Type of a solution.*

Functions

- template<class T >

bool **matrix_is_symmetric** (const std::vector< std::vector< T > > &A)

Check for symmetric matrix.
- template<class T >

bool **matrix_is_strictly_lower_triangular** (const std::vector< std::vector< T > > &A)

Check for strictly lower triangular matrix.
- template<class T >

bool **matrix_has_diagonal** (const std::vector< std::vector< T > > &A, T x)

Check for diagonal elements.
- template<class T >

bool **matrix_has_range** (const std::vector< std::vector< T > > &A, T inf, T sup)

Check for element range.
- template<class T >

bool **matrix_has_dominant_diagonal** (const std::vector< std::vector< T > > &A)

Check for element range.

Type and functions related to probability vectors

- using **pv_t** = std::vector< double >
Probability vector type.
- double **pv_entropy** (const **pv_t** &pv)
Entropy of a probability vector.
- void **pv_sample** (const **pv_t** &pv, **bit_vector_t** &bv)
Sample a bit vector.
- void **pv_uniform** (**pv_t** &pv)
Probability vector of the uniform distribution.
- void **pv_init** (**pv_t** &pv)
Initialize.
- void **pv_add** (**pv_t** &pv, const **bit_vector_t** &bv)
Accumulate a bit vector into a probability vector.
- void **pv_add** (**pv_t** &pv, const **bit_vector_t** &bv, double weight)
Accumulate a weighted bit vector into a probability vector.
- void **pv_average** (**pv_t** &pv, int count)
Average.
- template<class T >
void **pv_update** (**pv_t** &pv, const T &x, double rate)
Update a probability vector.
- void **pv_update** (**pv_t** &pv, const **pv_t** &x, const **pv_t** &y, double rate)
Update a probability vector.
- void **pv_bound** (**pv_t** &pv, double lower_bound, double upper_bound)
Bound the elements of a probability vector.

4.2.1 Detailed Description

Algorithms.

4.2.2 Function Documentation

4.2.2.1 pv_add() [1/2]

```
void pv_add (
    pv_t & pv,
    const bit_vector_t & bv )
```

Accumulate a bit vector into a probability vector.

Equivalent to `pv += x`

Parameters

<i>pv</i>	Probability vector
<i>bv</i>	Bit vector

Definition at line 59 of file [probability-vector.cc](#).

4.2.2.2 `pv_add()` [2/2]

```
void pv_add (
    pv_t & pv,
    const bit_vector_t & bv,
    double weight )
```

Accumulate a weighted bit vector into a probability vector.

Equivalent to `pv += weight * bv`

Parameters

<i>pv</i>	Probability vector
<i>bv</i>	Bit vector
<i>weight</i>	Weight

Definition at line 69 of file [probability-vector.cc](#).

4.2.2.3 `pv_average()`

```
void pv_average (
    pv_t & pv,
    int count )
```

Average.

Equivalent to `pv = pv / count`.

Parameters

<i>pv</i>	Probability vector
<i>count</i>	Number of accumulated bit vectors

Definition at line 77 of file [probability-vector.cc](#).

4.2.2.4 `pv_bound()`

```
void pv_bound (
    pv_t & pv,
    double lower_bound,
    double upper_bound )
```

Bound the elements of a probability vector.

Parameters

<i>pv</i>	Probability vector
<i>lower_bound</i>	Lower bound
<i>upper_bound</i>	Upper bound

Definition at line 94 of file [probability-vector.cc](#).

4.2.2.5 pv_init()

```
void pv_init (
    pv_t & pv ) [inline]
```

Initialize.

All the elements of the probability vector are set to 0.

Parameters

<i>pv</i>	Probability vector
-----------	--------------------

Definition at line 62 of file [probability-vector.hh](#).

4.2.2.6 pv_sample()

```
void pv_sample (
    const pv_t & pv,
    bit_vector_t & bv )
```

Sample a bit vector.

Parameters

<i>pv</i>	Probability vector
<i>bv</i>	Sampled bit vector

Definition at line 46 of file [probability-vector.cc](#).

4.2.2.7 pv_uniform()

```
void pv_uniform (
    pv_t & pv ) [inline]
```

Probability vector of the uniform distribution.

All the elements of the probability vector are set to 1/2.

Parameters

<i>pv</i>	Probability vector
-----------	--------------------

Definition at line 55 of file [probability-vector.hh](#).

4.2.2.8 pv_update() [1/2]

```
void pv_update (
    pv_t & pv,
    const pv_t & x,
    const pv_t & y,
    double rate )
```

Update a probability vector.

Equivalent to $pv += rate(x - y)$

Parameters

<i>pv</i>	Probability vector
<i>x</i>	Attractor probability vector
<i>y</i>	Repulsor probability vector
<i>rate</i>	Rate

Definition at line 84 of file [probability-vector.cc](#).

4.2.2.9 pv_update() [2/2]

```
template<class T >
void pv_update (
    pv_t & pv,
    const T & x,
    double rate )
```

Update a probability vector.

Equivalent to $pv += rate * (x - pv)$

Parameters

<i>pv</i>	Probability vector
<i>x</i>	Attractor bit vector
<i>rate</i>	Rate

Definition at line 97 of file [probability-vector.hh](#).

4.3 hnco::algorithm::fast_efficient_p3 Namespace Reference

Algorithms from the FastEfficientP3 library.

Classes

- class [Hboa](#)

- *Hierarchical Bayesian Optimization Algorithm.*
- class [HncoEvaluator](#)
Evaluator for HNCO functions.
- struct [Implementation](#)
Implementation
- class [Ltga](#)
Linkage Tree Genetic Algorithm.
- class [ParameterLessPopulationPyramid](#)
Parameter-less Population Pyramid.

4.3.1 Detailed Description

Algorithms from the FastEfficientP3 library.

4.4 `hnco::algorithm::gomea` Namespace Reference

GOMEA.

Classes

- class [Gomea](#)
GOMEA.
- class [HncoFitness](#)
Fitness for HNCO functions.

4.4.1 Detailed Description

GOMEA.

4.5 `hnco::algorithm::walsh_moment` Namespace Reference

Algorithms using Walsh moments.

Classes

- class [BmPbil](#)
Boltzmann machine PBIL.
- struct [FullMoment](#)
Full moment.
- class [FullMomentGibbsSampler](#)
Gibbs sampler with full moments.
- class [FullMomentHerding](#)
Herding with full moments.
- class [Hea](#)
Herding evolutionary algorithm.
- struct [TriangularMoment](#)
Triangular moment.
- class [TriangularMomentGibbsSampler](#)
Gibbs sampler with triangular moments.
- class [TriangularMomentHerding](#)
Herding with lower triangular Walsh moment.

4.5.1 Detailed Description

Algorithms using Walsh moments.

4.6 hnco::app Namespace Reference

Classes for applications.

Classes

- class [AlgorithmFactory](#)
Algorithm factory.
- class [CommandLineAlgorithmFactory](#)
Command line algorithm factory.
- class [CommandLineApplication](#)
Command line application.
- class [CommandLineFunctionFactory](#)
Command line function factory.
- class [DecoratedFunctionFactory](#)
Decorated function factory.
- class [FgenOptions](#)
Command line options for fgen.
- class [FunctionFactory](#)
Function factory.
- class [HncoOptions](#)
Command line options for hnco.
- class [MapgenOptions](#)
Command line options for mapgen.

Typedefs

- using **rep_var_t** = std::variant< [IntRep](#), [LongRep](#), [DoubleRep](#), [ValueSetRep](#) >
Representation variant.
- using **IntRep** = [representation::DyadicIntegerRepresentation](#)< int >
Int representation.
- using **LongRep** = [representation::DyadicIntegerRepresentation](#)< long >
Long representation.
- using **DoubleRep** = [representation::DyadicFloatRepresentation](#)< double >
Double representation.
- using **ValueSetRep** = [representation::ValueSetRepresentation](#)< double >
Value set representation.

Functions

- `std::ostream & operator<< (std::ostream &stream, const HncoOptions &options)`
Print a header containing the parameter values.
- `template<typename Options , typename Adapter >`
`Adapter * make_multivariate_function_adapter (const Options &options)`
Make a multivariate function adapter.
- `template<typename Options , typename Adapter >`
`Adapter * make_multivariate_function_adapter_complex (const Options &options)`
Make a multivariate function adapter over complex domain.
- `template<typename Options , typename Adapter >`
`Adapter * make_mixed_type_multivariate_function_adapter (const Options &options)`
Make a mixed-type multivariate function adapter.
- `std::string read_file_content (std::string path)`
Read file content.
- `std::vector< std::string > split_string (std::string str, std::string delimiter)`
Split string.
- `template<typename Options >`
`param_var_t parse_representation (std::string expression, const Options &options)`
Parse a representation.
- `template<typename Options >`
`env_t parse_representations (std::string expression, const Options &options)`
Parse representations.
- `std::ostream & operator<< (std::ostream &stream, const FfgenOptions &options)`
Print a header containing the parameter values.
- `std::ostream & operator<< (std::ostream &stream, const MapgenOptions &options)`
Print a header containing the parameter values.

4.6.1 Detailed Description

Classes for applications.

4.6.2 Function Documentation

4.6.2.1 `parse_representation()`

```
template<typename Options >
param_var_t parse_representation (
    std::string expression,
    const Options & options )
```

Parse a representation.

Parameters

<i>expression</i>	Expression to parse
<i>options</i>	Options

Definition at line 189 of file [parser.hh](#).

4.6.2.2 parse_representations()

```
template<typename Options >
env_t parse_representations (
    std::string expression,
    const Options & options )
```

Parse representations.

Parameters

<i>expression</i>	Expression to parse
<i>options</i>	Options

Syntax:

representations = declaration [; declaration]*

declaration = name : representation

representation =

- int(a, b) where a, b are int
- long(a, b) where a, b are long
- double(a, b, precision = e) where a, b, e are double
- double(a, b, size = n) where a, b are double, and n is int
- set(x1, x2, ..., xn) where all xi's are double and n is a non zero natural

Example:

"x: double(0, 1); y: double(0, 1, precision = 1e-3); z: double(0, 1, size = 8); u: int(-10, 10); v: long(-100, 100); w: set(1.1, 2.2, 3.3)"

Definition at line [246](#) of file [parser.hh](#).

4.7 hnco::exception Namespace Reference

Exceptions.

Classes

- class [LastEvaluation](#)
Last evaluation.
- class [TargetReached](#)
Target reached.

4.7.1 Detailed Description

Exceptions.

4.8 hnc0::function Namespace Reference

Functions defined on bit vectors.

Namespaces

- namespace [controller](#)
Controllers.
- namespace [modifier](#)
Modifiers.

Classes

- struct [AbsoluteValue](#)
Absolute value of a scalar.
- class [AbstractMaxSat](#)
Abstract class for MaxSat-like functions.
- class [DeceptiveJump](#)
Deceptive jump.
- class [Decorator](#)
Function decorator
- class [EqualProducts](#)
Equal products.
- class [Factorization](#)
Factorization.
- class [FourPeaks](#)
Four Peaks.
- class [Function](#)
Function
- class [FunctionPlugin](#)
Function plugin
- class [Hiff](#)
Hierarchical if and only if.
- class [Jump](#)
Jump.
- class [Labs](#)
Low autocorrelation binary sequences.
- class [LeadingOnes](#)
Leading ones.
- class [LinearFunction](#)
Linear function.
- class [LongPath](#)
Long path.
- class [MaxNae3Sat](#)

- Max not-all-equal 3SAT.*
- class [MaxSat](#)
 - MAX-SAT.*
- class [MixedRepresentationMultivariateFunctionAdapter](#)
 - Mixed-representation multivariate function adapter.*
- class [MultiobjectiveFunctionAdapter](#)
 - Multiobjective function adapter.*
- class [MultivariateFunctionAdapter](#)
 - Multivariate function adapter.*
- class [NearestNeighborIsingModel1](#)
 - Nearest neighbor Ising model in one dimension.*
- class [NearestNeighborIsingModel2](#)
 - Nearest neighbor Ising model in two dimensions.*
- class [Needle](#)
 - Needle in a haystack.*
- class [NkLandscape](#)
 - NK landscape.*
- class [OneMax](#)
 - OneMax.*
- struct [OppositeAbsoluteValue](#)
 - Opposite absolute value of a scalar.*
- struct [OppositeSquaredMagnitude](#)
 - Opposite squared magnitude of a complex number.*
- class [ParsedMultivariateFunction](#)
 - Parsed multivariate function.*
- class [Partition](#)
 - Partition.*
- class [PermutationFunctionAdapter](#)
 - Permutation function adapter.*
- class [Plateau](#)
 - Plateau.*
- class [PythonFunction](#)
 - Python function.*
- class [Qubo](#)
 - Quadratic unconstrained binary optimization.*
- class [Ridge](#)
 - Ridge.*
- struct [ScalarToDouble](#)
 - Convert a scalar to a double.*
- class [SinusSummationCancellation](#)
 - Summation cancellation with sinus.*
- class [SixPeaks](#)
 - Six Peaks.*
- struct [SquaredMagnitude](#)
 - Squared magnitude of a complex number.*
- class [Sudoku](#)
 - Sudoku*
- class [SummationCancellation](#)
 - Summation cancellation.*
- class [Trap](#)
 - Trap.*

- class [Tsp](#)
Traveling salesman problem.
- class [UniversalFunction](#)
Universal function.
- class [UniversalFunctionAdapter](#)
Universal function adapter.
- class [WalshExpansion](#)
Walsh expansion.
- class [WalshExpansion1](#)
Walsh expansion of degree 1.
- class [WalshExpansion2](#)
Walsh expansion of degree 2.
- struct [WalshTerm](#)
Walsh transform term.

Functions

- void [compute_walsh_transform](#) ([function::Function](#) *function, [std::vector](#)< [function::WalshTerm](#) > &terms)
Compute the Walsh transform of the function.
- void [compute_fast_walsh_transform](#) ([function::Function](#) *function, [std::vector](#)< [function::WalshTerm](#) > &terms)
Compute the Walsh transform of the function using a fast Walsh transform.
- bool [bv_is_locally_maximal](#) (const [bit_vector_t](#) &bv, [Function](#) &fn, [neighborhood::NeighborhoodIterator](#) &it)
Check whether a bit vector is locally maximal.
- bool [bv_is_globally_maximal](#) (const [bit_vector_t](#) &bv, [Function](#) &fn)
Check whether a bit vector is globally maximal.

4.8.1 Detailed Description

Functions defined on bit vectors.

4.8.2 Function Documentation

4.8.2.1 [compute_fast_walsh_transform\(\)](#)

```
void compute_fast_walsh_transform (
    function::Function * function,
    std::vector< function::WalshTerm > & terms )
```

Compute the Walsh transform of the function using a fast Walsh transform.

Let f be a fitness function defined on the hypercube $\{0, 1\}^n$. Then it can be expressed as $\sum_u c_u \chi_u$ where $c_u = \langle f, \chi_u \rangle$, $\langle f, g \rangle = \frac{1}{2^n} \sum_x f(x)g(x)$, $\chi_u(x) = (-1)^{x \cdot u}$, and $x \cdot u = \sum_i x_i u_i \pmod{2}$. In the respective sums, we have x and u in the hypercube and i in $\{1, \dots, n\}$.

We have dropped the normalizing constant 2^n since we are mostly interested in ratios $|c_u/c_{\max}|$, where c_{\max} is the coefficient with the largest amplitude. It is also helpful to achieve exact computations in the case of functions taking only integer values.

Parameters

<i>function</i>	Function the Walsh transform of which to compute
<i>terms</i>	Vector of non zero terms of the Walsh transform

Warning

The time complexity is exponential in the dimension n . It requires 2^n function evaluations and $n2^n$ additions, which is faster than `compute_walsh_transform`.

The size of the Walsh transform is potentially exponential in the dimension n . For example, if $n = 10$ then the number of terms is at most 1024.

Definition at line 77 of file [function.cc](#).

4.8.2.2 `compute_walsh_transform()`

```
void compute_walsh_transform (
    function::Function * function,
    std::vector< function::WalshTerm > & terms )
```

Compute the Walsh transform of the function.

Let f be a fitness function defined on the hypercube $\{0,1\}^n$. Then it can be expressed as $\sum_u c_u \chi_u$ where $c_u = \langle f, \chi_u \rangle$, $\langle f, g \rangle = \frac{1}{2^n} \sum_x f(x)g(x)$, $\chi_u(x) = (-1)^{x \cdot u}$, and $x \cdot u = \sum_i x_i u_i \pmod{2}$. In the respective sums, we have x and u in the hypercube and i in $\{1, \dots, n\}$.

We have dropped the normalizing constant 2^n since we are mostly interested in ratios $|c_u/c_{\max}|$, where c_{\max} is the coefficient with the largest amplitude. It is also helpful to achieve exact computations in the case of functions taking only integer values.

Parameters

<i>function</i>	Function the Walsh transform of which to compute
<i>terms</i>	Vector of non zero terms of the Walsh transform

Warning

The time complexity is exponential in the dimension n . The computation is done with two nested loops over the hypercube. It requires 2^n function evaluations and 2^{2n} dot products and additions.

The size of the Walsh transform is potentially exponential in the dimension n . For example, if $n = 10$ then the number of terms is at most 1024.

Definition at line 33 of file [function.cc](#).

4.9 `hnco::function::controller` Namespace Reference

Controllers.

Classes

- class [Cache](#)
Cache.
- class [CallCounter](#)
Call counter.
- class [Controller](#)
Function controller.
- class [OnBudgetFunction](#)
Function with a limited number of evaluations.
- class [ProgressTracker](#)
Progress tracker.
- class [StopOnMaximum](#)
Stop on maximum.
- class [StopOnTarget](#)
Stop on target.

Functions

- `std::ostream & operator<< (std::ostream &stream, const ProgressTracker::Event &event)`
Insert formatted output.

4.9.1 Detailed Description

Controllers.

4.10 hnco::function::modifier Namespace Reference

Modifiers.

Classes

- class [AdditiveGaussianNoise](#)
Additive Gaussian Noise.
- class [FunctionMapComposition](#)
Composition of a function and a map.
- class [Modifier](#)
Function modifier.
- class [OppositeFunction](#)
Opposite function.
- class [ParsedModifier](#)
Parsed modifier.
- class [PriorNoise](#)
Prior noise.

4.10.1 Detailed Description

Modifiers.

4.11 hnco::logging Namespace Reference

Logging.

Classes

- class [LogContext](#)
Log context.
- class [Logger](#)
Logger.
- class [ProgressTrackerContext](#)
Log context for ProgressTracker.

4.11.1 Detailed Description

Logging.

4.12 hnco::map Namespace Reference

Maps.

Classes

- class [AffineMap](#)
Affine map.
- class [Injection](#)
Injection.
- class [LinearMap](#)
Linear map.
- class [Map](#)
Map
- class [MapComposition](#)
Map composition.
- class [Permutation](#)
Permutation.
- class [Projection](#)
Projection.
- class [Translation](#)
Translation.
- struct [Transvection](#)
Transvection.
- class [TsAffineMap](#)
Transvection sequence affine map.

Types and functions related to transvections

Output and input-output function parameters appear at the beginning of the parameter list.

Output and input-output `transvection_sequence_t` parameters are passed by reference.

Input object parameters are passed by const reference.

- using `transvection_sequence_t` = `std::vector< Transvection >`
Transvection sequence.
- bool **transvections_commute** (const `Transvection` &a, const `Transvection` &b)
Check whether two transvections commute.
- bool **transvections_are_disjoint** (const `Transvection` &a, const `Transvection` &b)
Check whether two transvections are disjoint.
- bool **ts_is_valid** (const `transvection_sequence_t` &ts)
Check validity.
- bool **ts_is_valid** (const `transvection_sequence_t` &ts, int n)
Check validity.
- void **ts_display** (const `transvection_sequence_t` &ts, `std::ostream` &stream)
Display a transvection sequence.
- void **ts_random** (`transvection_sequence_t` &ts, int n, int t)
Sample a random transvection sequence.
- void **ts_random_commuting** (`transvection_sequence_t` &ts, int n, int t)
Sample a random sequence of commuting transvections.
- void **ts_random_unique_source** (`transvection_sequence_t` &ts, int n, int t)
Sample a random sequence of transvections with unique source.
- void **ts_random_unique_destination** (`transvection_sequence_t` &ts, int n, int t)
Sample a random sequence of transvections with unique destination.
- void **ts_random_disjoint** (`transvection_sequence_t` &ts, int n, int t)
Sample a random sequence of disjoint transvections.
- void **ts_random_non_commuting** (`transvection_sequence_t` &ts, int n, int t)
Sample a random sequence of non commuting transvections.
- void **ts_multiply** (`bit_vector_t` &bv, const `transvection_sequence_t` &ts)
Multiply a vector by a transvection sequence from the left.
- void **ts_multiply** (`bit_matrix_t` &bm, const `transvection_sequence_t` &ts)
Multiply a matrix by a transvection sequence from the left.
- void **ts_invert** (`transvection_sequence_t` &ts)
Invert a transvection sequence.

4.12.1 Detailed Description

Maps.

4.12.2 Typedef Documentation

4.12.2.1 transvection_sequence_t

```
using transvection_sequence_t = std::vector<Transvection>
```

Transvection sequence.

The general linear group of a linear space of dimension n over the finite field F_2 is the group of invertible n by n bit matrices.

Any invertible bit matrix can be expressed as a finite product of transvections.

Finite transvection sequences can then represent all invertible bit matrices.

Definition at line 145 of file [transvection.hh](#).

4.12.3 Function Documentation

4.12.3.1 ts_invert()

```
void ts_invert (
    transvection_sequence_t & ts )
```

Invert a transvection sequence.

Parameters

<i>ts</i>	Transvection sequence
-----------	-----------------------

Precondition

`ts_is_valid(ts)`

Definition at line 376 of file [transvection.cc](#).

4.12.3.2 ts_is_valid() [1/2]

```
bool ts_is_valid (
    const transvection_sequence_t & ts )
```

Check validity.

Parameters

<i>ts</i>	Transvection sequence
-----------	-----------------------

Definition at line 150 of file [transvection.cc](#).

4.12.3.3 ts_is_valid() [2/2]

```
bool ts_is_valid (
    const transvection_sequence_t & ts,
    int n )
```

Check validity.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension

Definition at line 156 of file [transvection.cc](#).

4.12.3.4 ts_multiply() [1/2]

```
void ts_multiply (
    bit_matrix_t & bm,
    const transvection_sequence_t & ts )
```

Multiply a matrix by a transvection sequence from the left.

Parameters

<i>ts</i>	Transvection sequence
<i>bm</i>	Bit matrix

Precondition

```
ts_is_valid(ts)
ts_is_valid(ts, bm_num_rows(M))
```

Warning

This function modifies the given bit vector.

Definition at line 366 of file [transvection.cc](#).

4.12.3.5 ts_multiply() [2/2]

```
void ts_multiply (
    bit_vector_t & bv,
    const transvection_sequence_t & ts )
```

Multiply a vector by a transvection sequence from the left.

Parameters

<i>ts</i>	Transvection sequence
<i>bv</i>	Bit vector

Precondition

`ts_is_valid(ts)`
`ts_is_valid(ts, x.size())`

Warning

This function modifies the given bit vector.

Definition at line 356 of file [transvection.cc](#).

4.12.3.6 ts_random()

```
void ts_random (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random transvection sequence.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

`n > 1`
`t >= 0`

Definition at line 172 of file [transvection.cc](#).

4.12.3.7 ts_random_commuting()

```
void ts_random_commuting (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of commuting transvections.

This function ensures that all transvections in the sequence commute.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$n > 1$
 $t \geq 0$

Warning

If $t > \text{floor}(n / 2)$ then t is set to $\text{floor}(n / 2)$.

If $t = \text{floor}(n / 2)$ then the space and time complexity of `ts_random_commuting` is quadratic in the dimension n .

Definition at line 183 of file [transvection.cc](#).

4.12.3.8 ts_random_disjoint()

```
void ts_random_disjoint (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of disjoint transvections.

Two transvections τ_{ij} and τ_{kl} are said to be disjoint if the pairs $\{i,j\}$ and $\{k,l\}$ are disjoint.

If $2t > n$ then the sequence length is set to the largest t such that $2t \leq n$.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$n > 1$
 $t \geq 0$

Definition at line 311 of file [transvection.cc](#).

4.12.3.9 ts_random_non_commuting()

```
void ts_random_non_commuting (
    transvection_sequence_t & ts,
```

```
int n,
int t )
```

Sample a random sequence of non commuting transvections.

This function ensures that two consecutive transvections do not commute.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

```
n > 1
t >= 0
```

Definition at line 341 of file [transvection.cc](#).

4.12.3.10 ts_random_unique_destination()

```
void ts_random_unique_destination (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of transvections with unique destination.

A transvection sequence with unique destination is such that, for each source, there is a unique destination.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

```
n > 1
t >= 0
```

Definition at line 278 of file [transvection.cc](#).

4.12.3.11 ts_random_unique_source()

```
void ts_random_unique_source (
    transvection_sequence_t & ts,
```

```
int n,  
int t )
```

Sample a random sequence of transvections with unique source.

A transvection sequence with unique source is such that, for each destination, there is a unique source.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$$n > 1$$

$$t \geq 0$$

Definition at line 245 of file [transvection.cc](#).

4.13 hnco::multiobjective Namespace Reference

Multiobjective optimization.

Namespaces

- namespace [algorithm](#)
Multiobjective Algorithms.
- namespace [app](#)
Classes for applications.
- namespace [function](#)
Functions defined on bit vectors.

4.13.1 Detailed Description

Multiobjective optimization.

4.14 hnco::multiobjective::algorithm Namespace Reference

Multiobjective Algorithms.

Classes

- class [Algorithm](#)
Abstract multiobjective search algorithm.
- struct [FrontDistancePair](#)
Front-distance pair.
- class [IterativeAlgorithm](#)
Iterative algorithm.
- class [Nsga2](#)
NSGA-II.
- class [Nsga2ParetoFrontComputation](#)
Pareto front computation from the NSGA-II paper.
- struct [Population](#)
Population
- class [TournamentSelection](#)
Tournament selection.

Functions

- bool [operator<](#) (const [FrontDistancePair](#) &a, const [FrontDistancePair](#) &b)
Comparison operator for front-distance pairs.

4.14.1 Detailed Description

Multiobjective Algorithms.

4.14.2 Function Documentation

4.14.2.1 [operator<\(\)](#)

```
bool operator< (
    const FrontDistancePair & a,
    const FrontDistancePair & b ) [inline]
```

Comparison operator for front-distance pairs.

Favors individuals with smaller Pareto front then greater crowding distance.

Definition at line 56 of file [nsga2.hh](#).

4.15 hnco::multiobjective::app Namespace Reference

Classes for applications.

Classes

- class [AlgorithmFactory](#)
Algorithm factory.
- class [CommandLineAlgorithmFactory](#)
Command line algorithm factory.
- class [CommandLineApplication](#)
Command line application.
- class [CommandLineFunctionFactory](#)
Command line function factory.
- class [FunctionFactory](#)
Function factory.
- class [HncoOptions](#)
Command line options for hnco-mo.

Functions

- std::ostream & [operator<<](#) (std::ostream &stream, const [HncoOptions](#) &options)
Print a header containing the parameter values.

4.15.1 Detailed Description

Classes for applications.

4.16 hnco::multiobjective::function Namespace Reference

Functions defined on bit vectors.

Classes

- class [Function](#)
Function
- class [MixedRepresentationMultivariateFunctionAdapter](#)
Mixed-representation multivariate function adapter.
- class [MultivariateFunctionAdapter](#)
Multivariate function adapter.
- class [ParsedMultivariateFunction](#)
Parsed multivariate function.
- class [PythonFunction](#)
Python function.
- class [UniversalFunction](#)
Universal function.
- class [UniversalFunctionAdapter](#)
Universal function adapter.

Typedefs

- using [value_t](#) = std::vector< double >
Value type.

Functions

- bool [dominates](#) (const [value_t](#) &a, const [value_t](#) &b)
Domination relation.
- void [value_display](#) (const [value_t](#) &a, std::ostream &stream)
Display a value.

4.16.1 Detailed Description

Functions defined on bit vectors.

4.16.2 Typedef Documentation

4.16.2.1 value_t

```
using value_t = std::vector<double>
```

Value type.

A value type is the type of the output of a [Function](#) in the context of multiobjective optimization.

Definition at line 42 of file [value.hh](#).

4.16.3 Function Documentation

4.16.3.1 dominates()

```
bool dominates (
    const value_t & a,
    const value_t & b ) [inline]
```

Domination relation.

Parameters

<i>a</i>	First value
<i>b</i>	Second value

Returns

true if a dominates b with respect to minimization

Definition at line 51 of file [value.hh](#).

4.17 hnco::neighborhood Namespace Reference

Neighborhoods for local search.

Classes

- class [HammingBall](#)
Hamming ball.
- class [HammingSphere](#)
Hamming sphere.
- class [HammingSphereIterator](#)
Hamming sphere neighborhood iterator.
- class [MultiBitFlip](#)
Multi bit flip.

- class [Neighborhood](#)
Neighborhood.
- class [NeighborhoodIterator](#)
Neighborhood iterator.
- class [SingleBitFlip](#)
One bit neighborhood.
- class [SingleBitFlipIterator](#)
Single bit flip neighborhood iterator.
- class [StandardBitMutation](#)
Standard bit mutation.

4.17.1 Detailed Description

Neighborhoods for local search.

There are two unrelated kinds of neighborhoods, those for random local search and those for exhaustive local search.

4.18 [hnco::random](#) Namespace Reference

Random numbers.

Classes

- struct [Generator](#)
Random number generator.

4.18.1 Detailed Description

Random numbers.

4.19 [hnco::representation](#) Namespace Reference

Representations.

Classes

- class [ComplexRepresentation](#)
Complex representation.
- class [DyadicFloatRepresentation](#)
Dyadic float representation.
- class [DyadicIntegerRepresentation](#)
Dyadic integer representation.
- class [IntegerCategoricalRepresentation](#)
Integer categorical representation.
- class [LinearCategoricalRepresentation](#)
Linear categorical representation.
- class [PermutationRepresentation](#)
Permutation representation.
- class [ValueSetRepresentation](#)
Value set.

Functions

- `template<class T >`
`bool difference_is_safe (T a, T b)`
Check whether the difference is safe.

4.19.1 Detailed Description

Representations.

4.19.2 Function Documentation

4.19.2.1 difference_is_safe()

```
template<class T >
bool difference_is_safe (
    T a,
    T b )
```

Check whether the difference is safe.

The template parameter T must be an integral type such as int or long.

The difference $b - a$ is safe if it can be represented by the type of a and b, i.e. there is no overflow.

Parameters

<i>a</i>	Smallest value
<i>b</i>	Greatest value

Precondition

$a < b$

Definition at line 51 of file [integer.hh](#).

Chapter 5

Class Documentation

5.1 AbsoluteValue< T > Struct Template Reference

Absolute value of a scalar.

```
#include <hnco/functions/converter.hh>
```

Public Types

- using **codomain_type** = T
Codomain type.

Public Member Functions

- double **operator()** (T x)
Absolute value.

5.1.1 Detailed Description

```
template<class T>  
struct hnco::function::AbsoluteValue< T >
```

Absolute value of a scalar.

Definition at line [41](#) of file [converter.hh](#).

The documentation for this struct was generated from the following file:


- lib/hnco/functions/converter.hh

5.2 AbstractMaxSat Class Reference

Abstract class for MaxSat-like functions.

```
#include <hnco/functions/collection/max-sat.hh>
```

Inheritance diagram for AbstractMaxSat:



Public Member Functions

- **AbstractMaxSat** ()
Default constructor.
- int **get_bv_size** () const override
Get bit vector size.
- void **display** (std::ostream &stream) const override
Display the expression.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Public Member Functions inherited from **Function**

- virtual ~**Function** ()
Destructor.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.

- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate](#) (const [bit_vector_t](#) &)=0
Evaluate a bit vector.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Protected Member Functions

- void [load_](#) (std::istream &stream)
Load an instance.
- void [save_](#) (std::ostream &stream) const
Save an instance.

Protected Attributes

- std::vector< std::vector< int > > [_expression](#)
Expression.
- int [_num_variables](#)
Number of variables.

5.2.1 Detailed Description

Abstract class for MaxSat-like functions.

Definition at line 37 of file [max-sat.hh](#).

5.2.2 Member Function Documentation

5.2.2.1 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 88 of file [max-sat.hh](#).

5.2.2.2 load_()

```
void load_ (
    std::istream & stream ) [protected]
```

Load an instance.

Parameters

<i>stream</i>	Input stream
---------------	--------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 61 of file [max-sat.cc](#).

5.2.2.3 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 100 of file [max-sat.hh](#).

5.2.2.4 save_()

```
void save_ (
```



```
std::ostream & stream ) const [protected]
```

Save an instance.

Parameters

<i>stream</i>	Outputstream
---------------	--------------

Definition at line 153 of file [max-sat.cc](#).

5.2.3 Member Data Documentation

5.2.3.1 _expression

```
std::vector<std::vector<int> > _expression [protected]
```

Expression.

An expression is represented by a vector of clauses. A clause is represented by a vector of literals. A literal is represented by a non null integer; if the integer is positive then the literal is a variable; if it is negative then it is the logical negation of a variable.

Definition at line 48 of file [max-sat.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/max-sat.hh](#)
- [lib/hnco/functions/collection/max-sat.cc](#)

5.3 AdditiveGaussianNoise Class Reference

Additive Gaussian Noise.

```
#include <hnco/functions/modifiers/modifier.hh>
```

Inheritance diagram for AdditiveGaussianNoise:



Public Member Functions

- **AdditiveGaussianNoise** ([Function](#) *function, double stddev)
Constructor.
- double **evaluate** (const [bit_vector_t](#) &bv) override
Evaluate a bit vector.

Properties

- int [get_bv_size](#) () const override

Public Member Functions inherited from [Modifier](#)

- **Modifier** ([Function](#) *function)
Constructor.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Attributes

- `std::normal_distribution< double > _dist`
Normal distribution.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * `_function`
Decorated function.

5.3.1 Detailed Description

Additive Gaussian Noise.

Definition at line 145 of file [modifier.hh](#).

5.3.2 Member Function Documentation

5.3.2.1 `get_bv_size()`

```
int get_bv_size ( ) const [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 161 of file [modifier.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/functions/modifiers/modifier.hh`
- `lib/hnco/functions/modifiers/modifier.cc`

5.4 AffineMap Class Reference

Affine map.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for AffineMap:



Public Member Functions

- void **random** (int rows, int cols, bool surjective)
Random instance.
- void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool **is_surjective** () const override
Check for surjective map.
- void **display** (std::ostream &stream) const override
Display.

Load and save map

- void **load** (std::string path)
Load map.
- void **save** (std::string path) const
Save map.

Public Member Functions inherited from [Map](#)

- virtual **~Map** ()
Destructor.

Private Member Functions

- template<class Archive >
void **save** (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void **load** (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_matrix_t](#) **bm**
Bit matrix.
- [bit_vector_t](#) **bv**
Translation vector

5.4.1 Detailed Description

Affine map.

An affine map f from F_2^m to F_2^n is defined by $f(x) = Ax + b$, where A is an $n \times m$ bit matrix and b is an n -dimensional bit vector.

Definition at line 330 of file [map.hh](#).

5.4.2 Member Function Documentation

5.4.2.1 is_surjective()

```
bool is_surjective ( ) const [override], [virtual]
```

Check for surjective map.

Returns

true if `rank(_bm) == bm_num_rows(_bm)`

Reimplemented from [Map](#).

Definition at line 139 of file [map.cc](#).

5.4.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 404 of file [map.hh](#).

5.4.2.3 random()

```
void random (
    int rows,
    int cols,
    bool surjective )
```

Random instance.

Parameters

<i>rows</i>	Number of rows
<i>cols</i>	Number of columns
<i>surjective</i>	Flag to ensure a surjective map

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 106 of file [map.cc](#).

5.4.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 411 of file [map.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/maps/map.hh](#)
- [lib/hnco/maps/map.cc](#)

5.5 Algorithm Class Reference

Abstract search algorithm.

```
#include <hnco/algorithms/algorithm.hh>
```

Inheritance diagram for Algorithm:



Public Member Functions

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** (logging::LogContext *log_context)
Set the log context.

Optimization

- virtual void **maximize** (const std::vector< function::Function * > &functions)=0
Maximize.
- virtual void **finalize** ()
Finalize.
- virtual const **solution_t** & **get_solution** ()
Get the solution.

Protected Member Functions

- void **set_functions** (const std::vector< function::Function * > &functions)
Set functions.

Managing solution

- void **random_solution** ()
Random solution.
- void **set_solution** (const bit_vector_t &bv, double value)

- *Set solution.*
void [set_solution](#) (const [bit_vector_t](#) &bv)
- *Set solution.*
void **update_solution** (const [bit_vector_t](#) &bv, double value)
- *Update solution (strict)*
void **update_solution** (const [solution_t](#) &s)
- *Update solution (strict)*
void [update_solution](#) (const [bit_vector_t](#) &bv)
- *Update solution (strict).*

Protected Attributes

- std::vector< [function::Function](#) * > [_functions](#)
Functions.
- [function::Function](#) * [_function](#)
Function.
- [solution_t](#) [_solution](#)
Solution.

Parameters

- [logging::LogContext](#) * [_log_context](#) = nullptr
Log context.

5.5.1 Detailed Description

Abstract search algorithm.

All algorithms maximize some given function, sometimes called a fitness function or an objective function.

Definition at line 46 of file [algorithm.hh](#).

5.5.2 Member Function Documentation

5.5.2.1 finalize()

```
virtual void finalize ( ) [inline], [virtual]
```

Finalize.

Does nothing.

It is usually overridden by algorithms which do not keep [_solution](#) up-to-date. In case [_function](#) throws a LastEvaluation exception, the algorithm might leave [_solution](#) in an undefined state. This can be fixed in this member function.

Reimplemented in [Hboa](#), [Ltga](#), [ParameterLessPopulationPyramid](#), [Gomea](#), [OnePlusOneEa](#), [SelfAdjustingOnePlusOneEa](#), and [RandomLocalSearch](#).

Definition at line 140 of file [algorithm.hh](#).

5.5.2.2 set_solution()

```
void set_solution (
    const bit\_vector\_t & bv ) [protected]
```

Set solution.

Warning

Evaluates the function once.

Definition at line [45](#) of file [algorithm.cc](#).

5.5.2.3 update_solution()

```
void update_solution (
    const bit\_vector\_t & bv ) [protected]
```

Update solution (strict).

Warning

Evaluates the function once.

Definition at line [69](#) of file [algorithm.cc](#).

5.5.3 Member Data Documentation

5.5.3.1 _functions

```
std::vector<function::Function *> _functions [protected]
```

Functions.

Each thread has its own function.

Definition at line [54](#) of file [algorithm.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/algorithm.hh](#)
- [lib/hnco/algorithms/algorithm.cc](#)

5.6 Algorithm Class Reference

Abstract multiobjective search algorithm.

```
#include <hnco/multiobjective/algorithms/algorithm.hh>
```

Inheritance diagram for Algorithm:



Public Types

- using **Function** = [hnco::multiobjective::function::Function](#)
Function type.

Public Member Functions

- [Algorithm](#) (int n, int num_objectives)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.

Optimization

- virtual void **minimize** (const std::vector< [Function](#) * > &functions)=0
Minimize.
- virtual const [Population](#) & **get_solutions** ()=0
Get solutions.

Protected Member Functions

- void **set_functions** (const std::vector< [Function](#) * > &functions)
Set functions.

Protected Attributes

- `std::vector< Function * > _functions`
Functions.
- `Function * _function`
Function.

Parameters

- `logging::LogContext * _log_context = nullptr`
Log context.

5.6.1 Detailed Description

Abstract multiobjective search algorithm.

All algorithms minimize some given function.

Definition at line 43 of file [algorithm.hh](#).

5.6.2 Constructor & Destructor Documentation

5.6.2.1 Algorithm()

```
Algorithm (
    int n,
    int num_objectives ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>num_objectives</i>	Number of objectives

Definition at line 85 of file [algorithm.hh](#).

5.6.3 Member Data Documentation

5.6.3.1 _functions

```
std::vector<Function *> _functions [protected]
```

Functions.

Each thread has its own function.

Definition at line 56 of file [algorithm.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/multiobjective/algorithms/algorithm.hh`

5.7 AlgorithmFactory Class Reference

Algorithm factory.

```
#include <hnco/app/algorithm-factory.hh>
```

Inheritance diagram for AlgorithmFactory:



Public Member Functions

- virtual [hnco::algorithm::Algorithm](#) * [make](#) (int `bv_size`)=0
Make an algorithm.

5.7.1 Detailed Description

Algorithm factory.

Definition at line 32 of file [algorithm-factory.hh](#).

5.7.2 Member Function Documentation

5.7.2.1 `make()`

```
virtual hnco::algorithm::Algorithm * make (  
    int bv_size ) [pure virtual]
```

Make an algorithm.

Parameters

<i>bv_size</i>	Bit vector size
----------------	-----------------

Implemented in [CommandLineAlgorithmFactory](#).

The documentation for this class was generated from the following file:


- `lib/hnco/app/algorithm-factory.hh`

5.8 AlgorithmFactory Class Reference

Algorithm factory.

```
#include <hnco/multiobjective/app/algorithm-factory.hh>
```

Inheritance diagram for AlgorithmFactory:



Public Member Functions

- virtual `hnco::multiobjective::algorithm::Algorithm * make` (int `bv_size`, int `num_objectives`)=0
Make an algorithm.

5.8.1 Detailed Description

Algorithm factory.

Definition at line 36 of file `algorithm-factory.hh`.

5.8.2 Member Function Documentation

5.8.2.1 make()

```
virtual hnco::multiobjective::algorithm::Algorithm * make (
    int bv_size,
    int num_objectives ) [pure virtual]
```

Make an algorithm.

Parameters

<i>bv_size</i>	Bit vector size
<i>num_objectives</i>	Number of objectives

Implemented in [CommandLineAlgorithmFactory](#).

The documentation for this class was generated from the following file:


- lib/hnco/multiobjective/app/algorithm-factory.hh

5.9 BiasedCrossover Class Reference

Biased crossover.

```
#include <hnco/algorithms/evolutionary-algorithms/crossover.hh>
```

Inheritance diagram for BiasedCrossover:



Public Member Functions

- **BiasedCrossover** ()
Constructor.
- void **recombine** (const [bit_vector_t](#) &parent1, const [bit_vector_t](#) &parent2, [bit_vector_t](#) &offspring)
Recombine.
- void **set_bias** (double b)
Set bias.

Public Member Functions inherited from [Crossover](#)

- virtual **~Crossover** ()
Destructor.

Private Attributes

- std::bernoulli_distribution **_bernoulli_dist**
Bernoulli distribution.

5.9.1 Detailed Description

Biased crossover.

Definition at line 75 of file [crossover.hh](#).

5.9.2 Member Function Documentation

5.9.2.1 recombine()

```
void recombine (
    const bit_vector_t & parent1,
    const bit_vector_t & parent2,
    bit_vector_t & offspring ) [virtual]
```

Recombine.

Each offspring's bit is copied from second parent with a fixed probability (the crossover bias), from first parent otherwise.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implements [Crossover](#).

Definition at line 45 of file [crossover.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/crossover.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/crossover.cc](#)

5.10 BmPbil< GibbsSampler > Class Template Reference

Boltzmann machine PBIL.

```
#include <hnco/algorithms/walsh-moment/bm-pbil.hh>
```

Inheritance diagram for BmPbil< GibbsSampler >:



Classes

- struct [ResetMode](#)
Markov chain reset mode.
- struct [SamplingMode](#)
Markov chain sampling mode.

Public Member Functions

- **BmPbil** (int n, int population_size)
Constructor.

Setters for parameters

- void [set_selection_size](#) (int size)
Set the selection size.
- void [set_learning_rate](#) (double rate)
Set the learning rate.
- void [set_num_gs_steps](#) (int n)
Set the number of gibbs sampler steps.
- void [set_num_gs_cycles](#) (int n)
Set the number of gibbs sampler cycles.
- void [set_negative_positive_selection](#) (bool b)
Set negative and positive selection.
- void [set_sampling_mode](#) (int mode)
Set the sampling mode.
- void [set_reset_mode](#) (int mode)
Set the reset mode.

Setters for logging

- void [set_log_norm_infinite](#) (bool b)
- void [set_log_norm_1](#) (bool b)
Log 1-norm of the model parameters.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual ~**Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **set_something_to_log** ()
Set flag for something to log.
- void **sample** ([bit_vector_t](#) &bv)
Sample a bit vector.
- void **sample_asynchronous** ()
Asynchronous sampling.
- void **sample_asynchronous_full_scan** ()
Asynchronous sampling with full scan.
- void **sample_synchronous** ()
Synchronous sampling.

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void [set_solution](#) (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void [update_solution](#) (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population.
- GibbsSampler::Moment **_model_parameters**
Model parameters.
- GibbsSampler **_gibbs_sampler**
Model.
- GibbsSampler::Moment **_walsh_moment_all**
Parameters averaged over all individuals.
- GibbsSampler::Moment **_walsh_moment_best**
Parameters averaged over selected individuals.
- GibbsSampler::Moment **_walsh_moment_worst**
Parameters averaged over negatively selected individuals.
- std::uniform_int_distribution< int > **_choose_bit**
Uniform distribution on [bit_vector_t](#) components.
- [permutation_t](#) **_permutation**
Permutation.

Parameters

- int [_selection_size](#) = 1
- double [_learning_rate](#) = 1e-3
Learning rate.
- int [_num_gs_steps](#) = 100
Number of gibbs sampler steps.
- int [_num_gs_cycles](#) = 1

- *Number of gibbs sampler cycles.*
• bool **_negative_positive_selection** = false
- *Negative and positive selection.*
• int **_sampling_mode** = [SamplingMode::asynchronous](#)
- *Sampling mode.*
• int **_reset_mode** = [ResetMode::no_reset](#)
- *Reset mode.*

Logging

- bool **_log_norm_infinite** = false
- bool **_log_norm_1** = false
- *Log 1-norm of the model parameters.*

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
• *Current iteration.*
- bool **_last_iteration** = false
• *Last iteration.*
- bool **_something_to_log** = false
• *Something to log.*
- int **_num_iterations** = 0
• *Number of iterations.*

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
• *Functions.*
- [function::Function](#) * **_function**
• *Function.*
- [solution_t](#) **_solution**
• *Solution.*
- [logging::LogContext](#) * **_log_context** = nullptr
• *Log context.*

5.10.1 Detailed Description

```
template<class GibbsSampler>
class hnco::algorithm::walsh_moment::BmPbil< GibbsSampler >
```

Boltzmann machine PBIL.

The BM model is slightly different from the one given in the reference below. More precisely, 0/1 variables are mapped to -1/+1 variables as in Walsh analysis.

Reference:

Arnaud Berny. 2002. Boltzmann machine for population-based incremental learning. In ECAI 2002. IOS Press, Lyon.

Definition at line 47 of file [bm-pbil.hh](#).

5.10.2 Member Function Documentation

5.10.2.1 `set_log_norm_infinite()`

```
template<class GibbsSampler >
void set_log_norm_infinite (
    bool b ) [inline]
```

Log infinite norm of the model parameters

Definition at line 291 of file [bm-pbil.hh](#).

5.10.2.2 `set_selection_size()`

```
template<class GibbsSampler >
void set_selection_size (
    int size ) [inline]
```

Set the selection size.

The selection size is the number of selected individuals in the population.

Definition at line 271 of file [bm-pbil.hh](#).

5.10.3 Member Data Documentation

5.10.3.1 `_log_norm_infinite`

```
template<class GibbsSampler >
bool _log_norm_infinite = false [protected]
```

Log infinite norm of the model parameters

Definition at line 130 of file [bm-pbil.hh](#).

5.10.3.2 `_selection_size`

```
template<class GibbsSampler >
int _selection_size = 1 [protected]
```

Selection size (number of selected individuals in the population)

Definition at line 110 of file [bm-pbil.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/algorithms/walsh-moment/bm-pbil.hh](#)

5.11 BoltzmannSelection Class Reference

Boltzmann selection.

```
#include <hnco/algorithms/evolutionary-algorithms/random-selection.hh>
```

Inheritance diagram for BoltzmannSelection:



Public Member Functions

- [BoltzmannSelection](#) (const [Population](#) &population)
Constructor.
- void **init** () override
Initialize.
- void **set_beta** (double beta)
Set beta.

Public Member Functions inherited from [FitnessProportionateSelection](#)

- [FitnessProportionateSelection](#) (const [Population](#) &population)
Constructor.
- void **init** () override
Initialize.
- const [bit_vector_t](#) & **select** () override
Select an individual in the population.

Public Member Functions inherited from [RandomSelection](#)

- [RandomSelection](#) (const [Population](#) &population)
Constructor.

Private Attributes

- `std::vector< double > _exponentiated_fitnesses`
Exponentiated fitnesses.
- `double _beta = 1`
Beta.

Additional Inherited Members

Protected Attributes inherited from [FitnessProportionateSelection](#)

- `std::discrete_distribution _distribution`
Distribution.

Protected Attributes inherited from [RandomSelection](#)

- `const Population & _population`
Population to select from

5.11.1 Detailed Description

Boltzmann selection.

Definition at line 140 of file [random-selection.hh](#).

5.11.2 Constructor & Destructor Documentation

5.11.2.1 BoltzmannSelection()

```
BoltzmannSelection (
    const Population & population ) [inline]
```

Constructor.

Parameters

<i>population</i>	Population to select from
-------------------	---------------------------

Definition at line 151 of file [random-selection.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/evolutionary-algorithms/random-selection.hh`
- `lib/hnco/algorithms/evolutionary-algorithms/random-selection.cc`

5.12 Cache Class Reference

Cache.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for Cache:



Public Member Functions

- [Cache](#) ([Function](#) *function)
Constructor.
- bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- double [get_lookup_ratio](#) ()
Get lookup ratio.

Evaluation

- double [evaluate](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Public Member Functions inherited from [Controller](#)

- [Controller](#) ([Function](#) *function)
Constructor.
- int [get_bv_size](#) () const

- *Get bit vector size.*
- double **get_maximum** () const
Get the global maximum.
- bool **has_known_maximum** () const
Check for a known maximum.
- bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- double **evaluate_safely** (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Attributes

- std::unordered_map< std::vector< bool >, double > **_cache**
Cache.
- std::vector< bool > **_key**
Key.
- int **_num_evaluations**
Evaluation counter.
- int **_num_lookups**
Lookup counter.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.12.1 Detailed Description

Cache.

This is a naive approach, in particular with respect to time complexity. Moreover, there is no control on the size of the database. There is no default hash function for `std::vector<char>` hence the need to first copy a `bit_vector_t` into a `std::vector<bool>`, for which such a function exists, before inserting it or checking its existence in the map.

Definition at line 369 of file [controller.hh](#).

5.12.2 Constructor & Destructor Documentation

5.12.2.1 Cache()

```
Cache (
    Function * function ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
-----------------	--------------------

Definition at line 389 of file [controller.hh](#).

5.12.3 Member Function Documentation

5.12.3.1 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) const [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented from [Function](#).

Definition at line 399 of file [controller.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/controllers/controller.hh](#)
- [lib/hnco/functions/controllers/controller.cc](#)

5.13 CallCounter Class Reference

Call counter.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for CallCounter:



Public Member Functions

- **CallCounter** ([Function](#) *function)

Constructor.

- int **get_num_calls** ()

Get the number of calls.

Evaluation

- double **evaluate** (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double **evaluate_incrementally** (const [bit_vector_t](#) &bv, double value, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- void **update** (const [bit_vector_t](#) &bv, double value)
Update after a safe evaluation.

Public Member Functions inherited from [Controller](#)

- **Controller** ([Function](#) *function)
Constructor.
- int **get_bv_size** () const
Get bit vector size.
- double **get_maximum** () const
Get the global maximum.
- bool **has_known_maximum** () const
Check for a known maximum.
- bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- double **evaluate_safely** (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.

Protected Attributes

- int **_num_calls**
Number of calls.

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.13.1 Detailed Description

Call counter.

Definition at line 157 of file [controller.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/controllers/controller.hh](#)
- [lib/hnco/functions/controllers/controller.cc](#)

5.14 CommandLineAlgorithmFactory Class Reference

Command line algorithm factory.

```
#include <hnco/app/algorithm-factory.hh>
```

Inheritance diagram for CommandLineAlgorithmFactory:



Public Member Functions

- **CommandLineAlgorithmFactory** (const [HncoOptions](#) &options)
Constructor.
- [hnco::algorithm::Algorithm](#) * **make** (int bv_size)
Make an algorithm.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.

5.14.1 Detailed Description

Command line algorithm factory.

Definition at line 42 of file [algorithm-factory.hh](#).

5.14.2 Member Function Documentation

5.14.2.1 make()

```
Algorithm * make (
    int bv_size ) [virtual]
```

Make an algorithm.

Parameters

<code>bv_size</code>	Bit vector size
----------------------	-----------------

Implements [AlgorithmFactory](#).

Definition at line 95 of file [algorithm-factory.cc](#).

The documentation for this class was generated from the following files:


- `lib/hnco/app/algorithm-factory.hh`
- `lib/hnco/app/algorithm-factory.cc`

5.15 CommandLineAlgorithmFactory Class Reference

Command line algorithm factory.

```
#include <hnco/multiobjective/app/algorithm-factory.hh>
```

Inheritance diagram for CommandLineAlgorithmFactory:



Public Member Functions

- **CommandLineAlgorithmFactory** (const [HncoOptions](#) &options)
Constructor.
- [hnco::multiobjective::algorithm::Algorithm](#) * **make** (int bv_size, int num_objectives)
Make an algorithm.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.

5.15.1 Detailed Description

Command line algorithm factory.

Definition at line 47 of file [algorithm-factory.hh](#).

5.15.2 Member Function Documentation

5.15.2.1 make()

```
Algorithm * make (
    int bv_size,
    int num_objectives ) [virtual]
```

Make an algorithm.

Parameters

<i>bv_size</i>	Bit vector size
<i>num_objectives</i>	Number of objectives

Implements [AlgorithmFactory](#).

Definition at line 32 of file [algorithm-factory.cc](#).

The documentation for this class was generated from the following files:

- [lib/hnco/multiobjective/app/algorithm-factory.hh](#)
- [lib/hnco/multiobjective/app/algorithm-factory.cc](#)

5.16 CommandLineApplication Class Reference

Command line application.

```
#include <hnco/app/application.hh>
```

Public Member Functions

- [CommandLineApplication](#) (const [HncoOptions](#) &options, [FunctionFactory](#) &function_factory, [AlgorithmFactory](#) &algorithm_factory)
Constructor.
- void **run** ()
Run the application.

Private Member Functions

- void **init** ()
Initialization.
- void **make_functions** ()
Make all functions.
- void **load_solution** ()
Load a solution.
- void **print_information** ()
Print information about the function.
- void **make_algorithm** ()
Make algorithm.
- void **maximize** ()
Maximize the function.
- void **print_results** (double total_time, bool target_reached)
Print results.
- void **manage_solution** (const [bit_vector_t](#) &bv)
Manage solution.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.
- [DecoratedFunctionFactory](#) **_decorated_function_factory**
Decorated function factory.
- [AlgorithmFactory](#) & **_algorithm_factory**
Algorithm factory.
- std::vector< [function::Function](#) * > **_fns**
All functions.
- [function::Function](#) * **_fn** = nullptr
Main function.
- [hnco::algorithm::Algorithm](#) * **_algorithm** = nullptr
Algorithm.
- [logging::ProgressTrackerContext](#) * **_log_context** = nullptr
Log context.

5.16.1 Detailed Description

Command line application.

Definition at line 34 of file [application.hh](#).

5.16.2 Constructor & Destructor Documentation

5.16.2.1 CommandLineApplication()

```
CommandLineApplication (
    const HncoOptions & options,
    FunctionFactory & function_factory,
    AlgorithmFactory & algorithm_factory ) [inline]
```

Constructor.

Parameters

<i>options</i>	HNCO options
<i>function_factory</i>	Function factory
<i>algorithm_factory</i>	Algorithm factory

Definition at line 89 of file [application.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/app/application.hh
- lib/hnco/app/application.cc

5.17 CommandLineApplication Class Reference

Command line application.

```
#include <hnco/multiojective/app/application.hh>
```

Public Member Functions

- [CommandLineApplication](#) (const [HncoOptions](#) &options, [FunctionFactory](#) &function_factory, [AlgorithmFactory](#) &algorithm_factory)
Constructor.
- void **run** ()
Run the application.

Private Member Functions

- void **init** ()
Initialization.
- void **make_functions** ()
Make all functions.
- void **print_information** ()
Print information about the function.
- void **make_algorithm** ()
Make algorithm.
- void **minimize** ()
Minimize objective functions.
- void **manage_solutions** ()
Manage solutions.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.
- [FunctionFactory](#) & **_function_factory**
Function factory.
- [AlgorithmFactory](#) & **_algorithm_factory**
Algorithm factory.
- `std::vector< hnco::multiobjective::function::Function * >` **_fns**
All functions.
- `hnco::multiobjective::function::Function * _fn` = nullptr
Main function.
- `hnco::multiobjective::algorithm::Algorithm * _algorithm` = nullptr
Algorithm.

5.17.1 Detailed Description

Command line application.

Definition at line 37 of file [application.hh](#).

5.17.2 Constructor & Destructor Documentation

5.17.2.1 CommandLineApplication()

```
CommandLineApplication (
    const HncoOptions & options,
    FunctionFactory & function_factory,
    AlgorithmFactory & algorithm_factory ) [inline]
```

Constructor.

Parameters

<i>options</i>	HNCO options
<i>function_factory</i>	Function factory
<i>algorithm_factory</i>	Algorithm factory

Definition at line 83 of file [application.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/multiobjective/app/application.hh
- lib/hnco/multiobjective/app/application.cc

5.18 CommandLineFunctionFactory Class Reference

Command line function factory.

```
#include <hnco/app/function-factory.hh>
```

Inheritance diagram for CommandLineFunctionFactory:



Public Member Functions

- **CommandLineFunctionFactory** (const [HncoOptions](#) &options)
Constructor.
- [hnco::function::Function](#) * **make** ()
Make a function.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.

5.18.1 Detailed Description

Command line function factory.

Definition at line 40 of file [function-factory.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/app/function-factory.hh
- lib/hnco/app/function-factory.cc

5.19 CommandLineFunctionFactory Class Reference

Command line function factory.

```
#include <hnco/multiobjective/app/function-factory.hh>
```

Inheritance diagram for CommandLineFunctionFactory:



Public Member Functions

- **CommandLineFunctionFactory** (const [HncoOptions](#) &options)
Constructor.
- [hnco::multiobjective::function::Function](#) * **make** ()
Make a function.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.

5.19.1 Detailed Description

Command line function factory.

Definition at line 41 of file [function-factory.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/multiobjective/app/function-factory.hh](#)
- [lib/hnco/multiobjective/app/function-factory.cc](#)

5.20 CommaSelection Class Reference

Comma selection.

```
#include <hnco/algorithms/evolutionary-algorithms/selection.hh>
```

Public Member Functions

- [CommaSelection](#) ([Population](#) &parents, [Population](#) &offsprings)
Constructor.
- void **select** ()
Apply selection.

Private Attributes

- [Population](#) & **_parents**
Parent population.
- [Population](#) & **_offsprings**
Offspring population.

5.20.1 Detailed Description

Comma selection.

Used as selection for replacement in evolutionary algorithms.

Definition at line 38 of file [selection.hh](#).

5.20.2 Constructor & Destructor Documentation

5.20.2.1 CommaSelection()

```
CommaSelection (
    Population & parents,
    Population & offsprings ) [inline]
```

Constructor.

Parameters

<i>parents</i>	Parent population
<i>offsprings</i>	Offspring population

Definition at line 53 of file [selection.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/algorithms/evolutionary-algorithms/selection.hh

5.21 CompactGa Class Reference

Compact genetic algorithm.

```
#include <hnco/algorithms/probability-vector/compact-ga.hh>
```

Inheritance diagram for CompactGa:



Public Member Functions

- **CompactGa** (int n)
Constructor.

Setters

- void **set_learning_rate** (double x)
Set the learning rate.

Public Member Functions inherited from [PvAlgorithm](#)

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & [get_solution](#) ()
Get the solution.

Protected Member Functions

Loop

- void [init](#) () override
Initialize.
- void [iterate](#) () override
Single iteration.

Protected Member Functions inherited from [PvAlgorithm](#)

- void [set_something_to_log](#) ()
Set flag for something to log.
- void [log](#) () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- std::vector< [bit_vector_t](#) > **_candidates**
Candidates.

Parameters

- double **_learning_rate** = 1e-3
Learning rate.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t](#) **_pv**
Probability vector.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.
- bool **_log_entropy** = false
Log entropy.
- bool **_log_pv** = false
Log probability vector.
- int **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.21.1 Detailed Description

Compact genetic algorithm.

Reference:

Georges R. Harik, Fernando G. Lobo, and David E. Goldberg. 1999. The Compact Genetic Algorithm. *IEEE Trans. on Evolutionary Computation* 3, 4 (November 1999), 287–297.

Definition at line 41 of file [compact-ga.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/probability-vector/compact-ga.hh`
- `lib/hnco/algorithms/probability-vector/compact-ga.cc`

5.22 CompleteSearch Class Reference

Complete search.

```
#include <hnco/algorithms/complete-search.hh>
```

Inheritance diagram for CompleteSearch:



Public Member Functions

- **CompleteSearch** (int n)
Constructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions)
Maximize.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.22.1 Detailed Description

Complete search.

Definition at line 34 of file [complete-search.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/complete-search.hh
- lib/hnco/algorithms/complete-search.cc

5.23 ComplexRepresentation< ScalarRep > Class Template Reference

Complex representation.

```
#include <hnco/representations/complex.hh>
```

Inheritance diagram for ComplexRepresentation< ScalarRep >:



Public Types

- using **scalar_rep** = ScalarRep
Scalar representation.
- using **scalar_type** = typename scalar_rep::domain_type
Scalar type.
- using **domain_type** = std::complex< scalar_type >
Domain type.

Public Member Functions

- **ComplexRepresentation** (scalar_rep real_part, scalar_rep imaginary_part)
Constructor.
- **ComplexRepresentation** (scalar_rep rep)
Constructor.
- int **size** () const
Size of the representation.
- **domain_type unpack** (const bit_vector_t &bv, int start)
Unpack bit vector into a value.
- void **display** (std::ostream &stream) const
Display.

Private Attributes

- [scalar_rep_real_part](#)
Representation of the real part.
- [scalar_rep_imaginary_part](#)
Representation of the imaginary part.

5.23.1 Detailed Description

```
template<class ScalarRep>
class hnco::representation::ComplexRepresentation< ScalarRep >
```

Complex representation.

Definition at line 39 of file [complex.hh](#).

5.23.2 Constructor & Destructor Documentation**5.23.2.1 ComplexRepresentation() [1/2]**

```
template<class ScalarRep >
ComplexRepresentation (
    scalar_rep real_part,
    scalar_rep imaginary_part ) [inline]
```

Constructor.

Parameters

<i>real_part</i>	Representation of real part
<i>imaginary_part</i>	Representation of imaginary part

Definition at line 68 of file [complex.hh](#).

5.23.2.2 ComplexRepresentation() [2/2]

```
template<class ScalarRep >
ComplexRepresentation (
    scalar_rep rep ) [inline]
```

Constructor.

Parameters

<i>rep</i>	Representation of both real and imaginary parts
------------	---

Definition at line 78 of file [complex.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/representations/complex.hh

5.24 Controller Class Reference

Function controller.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for Controller:



Public Member Functions

- **Controller** ([Function](#) *function)

Constructor.

Information about the function

- int **get_bv_size** () const
Get bit vector size.
- double **get_maximum** () const
Get the global maximum.
- bool **has_known_maximum** () const
Check for a known maximum.
- bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.

Evaluation

- double **evaluate_safely** (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual \sim **Function** ()
Destructor.
- virtual double **evaluate** (const [bit_vector_t](#) &)=0
Evaluate a bit vector.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.24.1 Detailed Description

[Function](#) controller.

Definition at line 41 of file [controller.hh](#).

5.24.2 Member Function Documentation

5.24.2.1 `provides_incremental_evaluation()`

```
bool provides_incremental_evaluation ( ) const [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true if the decorated function does

Reimplemented from [Function](#).

Definition at line 67 of file [controller.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/functions/controllers/controller.hh

5.25 Crossover Class Reference

Crossover

```
#include <hnco/algorithms/evolutionary-algorithms/crossover.hh>
```

Inheritance diagram for Crossover:



Public Member Functions

- virtual `~Crossover()`
Destructor.
- virtual void `recombine` (const `bit_vector_t` &parent1, const `bit_vector_t` &parent2, `bit_vector_t` &offspring)=0
Recombine.

5.25.1 Detailed Description

Crossover

Definition at line 35 of file `crossover.hh`.

5.25.2 Member Function Documentation

5.25.2.1 `recombine()`

```
virtual void recombine (  
    const bit_vector_t & parent1,  
    const bit_vector_t & parent2,  
    bit_vector_t & offspring ) [pure virtual]
```

Recombine.

The offspring is the crossover of two parents.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implemented in [UniformCrossover](#), and [BiasedCrossover](#).

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/evolutionary-algorithms/crossover.hh`

5.26 DeceptiveJump Class Reference

Deceptive jump.

```
#include <hnco/functions/collection/jump.hh>
```

Inheritance diagram for DeceptiveJump:



Public Member Functions

- **DeceptiveJump** (int bv_size, int gap)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const
Display.
- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int **_bv_size**
Bit vector size.
- int **_gap**
Gap.

5.26.1 Detailed Description

Deceptive jump.

This is a jump function with a deceptive gap as defined in "Analyzing evolutionary algorithms" by Thomas Jansen, where it is called `Jump_k`. Algorithms in the neighborhood of the maximizer (which is the all one bit vector) are taken away from it.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 85 of file [jump.hh](#).

5.26.2 Member Function Documentation

5.26.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

`_bv_size + _gap`

Reimplemented from [Function](#).

Definition at line 108 of file [jump.hh](#).

5.26.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 104 of file [jump.hh](#).

The documentation for this class was generated from the following files:

- `lib/hnco/functions/collection/jump.hh`
- `lib/hnco/functions/collection/jump.cc`

5.27 DecoratedFunctionFactory Class Reference

Decorated function factory.

```
#include <hnco/app/decorated-function-factory.hh>
```

Public Member Functions

- **DecoratedFunctionFactory** (const [HncoOptions](#) &options, [FunctionFactory](#) &function_factory)
Constructor.
- [hnco::function::Function](#) * **make_function_modifier** ()
Make a function modifier.
- [hnco::function::Function](#) * **make_function_controller** ([hnco::function::Function](#) *function)
Make a function controller.
- [hnco::map::Map](#) * **get_map** ()
Get map.
- [hnco::function::controller::ProgressTracker](#) * **get_tracker** ()
Get tracker controller.
- [hnco::function::controller::Cache](#) * **get_cache** ()
Get Cache controller.
- [hnco::function::controller::StopOnTarget](#) * **get_stop_on_target** ()
Get StopOnTarget controller.

Private Member Functions

- [hnco::function::Function](#) * **make_function** ()
Make a function.

Private Attributes

- const [HncoOptions](#) & **_options**
HNCO options.
- [FunctionFactory](#) & **_function_factory**
Factory function.
- [hnco::map::Map](#) * **_map** = nullptr
Map.
- [hnco::function::controller::ProgressTracker](#) * **_tracker** = nullptr
Tracker controller.
- [hnco::function::controller::Cache](#) * **_cache** = nullptr
Cache controller.
- [hnco::function::controller::StopOnTarget](#) * **_stop_on_target** = nullptr
StopOnTarget controller.

5.27.1 Detailed Description

Decorated function factory.

Definition at line 35 of file [decorated-function-factory.hh](#).

5.27.2 Member Function Documentation

5.27.2.1 make_function_controller()

```
Function * make_function_controller (
    hnco::function::Function * function )
```

Make a function controller.

Parameters

<i>function</i>	Decorated function
-----------------	--------------------

Definition at line 257 of file [decorated-function-factory.cc](#).

The documentation for this class was generated from the following files:


- lib/hnco/app/decorated-function-factory.hh
- lib/hnco/app/decorated-function-factory.cc

5.28 Decorator Class Reference

[Algorithm](#) decorator.

```
#include <hnco/algorithms/decorators/decorator.hh>
```

Inheritance diagram for Decorator:



Public Member Functions

- [Decorator](#) ([Algorithm](#) *algorithm)
Constructor.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **maximize** (const std::vector< [function::Function](#) * > &functions)=0
Maximize.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Attributes

- [Algorithm](#) * **_algorithm**
Decorated algorithm.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

5.28.1 Detailed Description

[Algorithm](#) decorator.

Definition at line 32 of file [decorator.hh](#).

5.28.2 Constructor & Destructor Documentation

5.28.2.1 Decorator()

```
Decorator (
    Algorithm * algorithm ) [inline]
```

Constructor.

The decorator itself is an algorithm created with the same bit vector size as that of the decorated algorithm.

Precondition

algorithm must be a pointer to a valid [Algorithm](#).

Definition at line 49 of file [decorator.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/algorithms/decorators/decorator.hh

5.29 Decorator Class Reference

Function decorator

```
#include <hnco/functions/decorator.hh>
```

Inheritance diagram for Decorator:



Public Member Functions

- **Decorator** ([Function](#) *function)
Constructor.

Display

- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual int **get_bv_size** () const =0
Get bit vector size.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate** (const [bit_vector_t](#) &)=0
Evaluate a bit vector.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Protected Attributes

- [Function](#) * **_function**
Decorated function.

5.29.1 Detailed Description

Function decorator

Definition at line 34 of file [decorator.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/functions/decorator.hh

5.30 DyadicFloatRepresentation< T > Class Template Reference

Dyadic float representation.

```
#include <hnco/representations/float.hh>
```

Inheritance diagram for DyadicFloatRepresentation< T >:



Public Types

- using **domain_type** = T
Domain type.

Public Member Functions

- [DyadicFloatRepresentation](#) (T lower_bound, T upper_bound, int [size](#))
Constructor.
- [DyadicFloatRepresentation](#) (T lower_bound, T upper_bound, T precision)
Constructor.
- int **size** () const
Size of the representation.
- [domain_type](#) **unpack** (const [bit_vector_t](#) &bv, int start)
Unpack bit vector into a value.
- void **display** (std::ostream &stream) const
Display.

Private Member Functions

- T **affine_transformation** (T x)
Affine transformation.
- void [compute_lengths](#) (int [size](#))
Compute lengths.

Private Attributes

- `std::vector< T > _lengths`
Lengths of dyadic intervals.
- `T _lower_bound`
Lower bound of the interval.
- `T _length`
Length of the interval.

5.30.1 Detailed Description

`template<class T>`
class `hnco::representation::DyadicFloatRepresentation< T >`

Dyadic float representation.

Definition at line 44 of file [float.hh](#).

5.30.2 Constructor & Destructor Documentation

5.30.2.1 DyadicFloatRepresentation() [1/2]

```
template<class T >
DyadicFloatRepresentation (
    T lower_bound,
    T upper_bound,
    int size ) [inline]
```

Constructor.

The represented interval is [lower_bound, upper_bound).

Parameters

<i>lower_bound</i>	Lower bound of the interval
<i>upper_bound</i>	Upper bound of the interval
<i>size</i>	Size in bits per float number

Definition at line 89 of file [float.hh](#).

5.30.2.2 DyadicFloatRepresentation() [2/2]

```
template<class T >
DyadicFloatRepresentation (
    T lower_bound,
    T upper_bound,
    T precision ) [inline]
```

Constructor.

The represented interval is [lower_bound, upper_bound).

Parameters

<i>lower_bound</i>	Lower bound of the interval
<i>upper_bound</i>	Upper bound of the interval
<i>precision</i>	Precision

Definition at line 108 of file [float.hh](#).

5.30.3 Member Function Documentation

5.30.3.1 compute_lengths()

```
template<class T >
void compute_lengths (
    int size ) [inline], [private]
```

Compute lengths.

Parameters

<i>size</i>	Size in bits per float number
-------------	-------------------------------

Definition at line 63 of file [float.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/representations/float.hh](#)

5.31 DyadicIntegerRepresentation< T > Class Template Reference

Dyadic integer representation.

```
#include <hnco/representations/integer.hh>
```

Inheritance diagram for DyadicIntegerRepresentation< T >:



Classes

- struct [Precision](#)
Precision

Public Types

- using **domain_type** = T
Domain type.

Public Member Functions

- [DyadicIntegerRepresentation](#) (T lower_bound, T upper_bound, int [size](#))
Constructor with given size.
- [DyadicIntegerRepresentation](#) (T lower_bound, T upper_bound)
Constructor.
- [DyadicIntegerRepresentation](#) (T lower_bound, T upper_bound, [Precision](#) precision)
Constructor with given precision.
- [DyadicIntegerRepresentation](#) (T n)
Constructor.
- int **size** () const
Size of the representation.
- **domain_type** **unpack** (const [bit_vector_t](#) &bv, int start)
Unpack bit vector into a value.
- void **display** (std::ostream &stream) const
Display.

Private Member Functions

- void **set_exact_size** (T lower_bound, T upper_bound)
Set the exact size for a given interval.

Private Attributes

- int **_size**
Size in bits.
- int **_exact_size**
Exact size required for a given interval.
- T **_lower_bound**
Lower bound of the interval.
- T **_upper_bound**
Upper bound of the interval.

5.31.1 Detailed Description

```
template<class T>
class hnco::representation::DyadicIntegerRepresentation< T >
```

Dyadic integer representation.

Definition at line 73 of file [integer.hh](#).

5.31.2 Constructor & Destructor Documentation

5.31.2.1 DyadicIntegerRepresentation() [1/4]

```
template<class T >
DyadicIntegerRepresentation (
    T lower_bound,
    T upper_bound,
    int size ) [inline]
```

Constructor with given size.

The represented interval is [lower_bound..upper_bound].

Parameters

<i>lower_bound</i>	Lower bound of the interval
<i>upper_bound</i>	Upper bound of the interval
<i>size</i>	Size in bits per integer

Definition at line 121 of file [integer.hh](#).

5.31.2.2 DyadicIntegerRepresentation() [2/4]

```
template<class T >
DyadicIntegerRepresentation (
    T lower_bound,
    T upper_bound ) [inline]
```

Constructor.

The represented interval is [lower_bound..upper_bound].

Parameters

<i>lower_bound</i>	Lower bound of the interval
<i>upper_bound</i>	Upper bound of the interval

Definition at line 142 of file [integer.hh](#).

5.31.2.3 DyadicIntegerRepresentation() [3/4]

```
template<class T >
DyadicIntegerRepresentation (
    T lower_bound,
    T upper_bound,
    Precision precision ) [inline]
```

Constructor with given precision.

The represented interval is [lower_bound..upper_bound].

Parameters

<i>lower_bound</i>	Lower bound of the interval
<i>upper_bound</i>	Upper bound of the interval
<i>precision</i>	Precision

Definition at line 159 of file [integer.hh](#).

5.31.2.4 DyadicIntegerRepresentation() [4/4]

```
template<class T >
DyadicIntegerRepresentation (
    T n ) [inline]
```

Constructor.

The represented interval is $[0..n-1]$.

Parameters

<i>n</i>	Number of elements
----------	--------------------

Definition at line 177 of file [integer.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/representations/integer.hh](#)

5.32 EqualProducts Class Reference

Equal products.

```
#include <hnco/functions/collection/equal-products.hh>
```

Inheritance diagram for EqualProducts:



Public Member Functions

- **EqualProducts** ()
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Instance generators

- template<class Generator >
void **generate** (int n, Generator generator)
Instance generator.
- void **random** (int n)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const
Display.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- `template<class Archive >`
void **serialize** (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- `std::vector< double > _numbers`
Numbers.

5.32.1 Detailed Description

Equal products.

[Partition](#) a finite set of positive numbers into two subsets such that the product of numbers in the first subset is the closest to the product of numbers in the second subset. This is equivalent to the partition problem applied to the logarithms of the given numbers.

The function computes the negation of the distance between the product of numbers corresponding to ones in the bit vector and the product of those corresponding to zeros. The negation is a consequence of the fact that algorithms in HNCO maximize rather than minimize a function.

Reference:

S. Baluja and S. Davies. 1997. Using optimal dependency-trees for combinatorial optimization: learning the structure of the search space. Technical Report CMU- CS-97-107. Carnegie-Mellon University.

Definition at line 59 of file [equal-products.hh](#).

5.32.2 Member Function Documentation

5.32.2.1 generate()

```
template<class Generator >
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Number generator

Definition at line 91 of file [equal-products.hh](#).

5.32.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 124 of file [equal-products.hh](#).

5.32.2.3 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the uniform distribution on [0,1).

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 106 of file [equal-products.hh](#).

5.32.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 131 of file [equal-products.hh](#).

The documentation for this class was generated from the following files:

- `lib/hnco/functions/collection/equal-products.hh`
- `lib/hnco/functions/collection/equal-products.cc`

5.33 ProgressTracker::Event Struct Reference

Event

```
#include <hnco/functions/controllers/controller.hh>
```

Public Attributes

- `int num_evaluations`
Number of evaluations.
- `algorithm::solution_t solution`
Solution.

5.33.1 Detailed Description

Event

Definition at line 246 of file `controller.hh`.

The documentation for this struct was generated from the following file:


- `lib/hnco/functions/controllers/controller.hh`

5.34 ExtendedHypercubeliterator Class Reference

Extended Hypercube iterator.

```
#include <hnco/iterator.hh>
```

Inheritance diagram for ExtendedHypercubeliterator:



Public Member Functions

- **ExtendedHypercubeliterator** (int n)
Constructor.
- bool **has_next** () override
Has next bit vector.
- const [bit_vector_t](#) & **next** () override
Next bit vector.

Public Member Functions inherited from [Iterator](#)

- **Iterator** (int n)
Constructor.
- virtual ~**Iterator** ()
Destructor.
- virtual void **init** ()
Initialization.

Additional Inherited Members

Protected Attributes inherited from [Iterator](#)

- [bit_vector_t](#) **_current**
Current bit vector.
- bool **_initial_state** = true
Flag for initial state.

5.34.1 Detailed Description

Extended Hypercube iterator.

Similar to Hypercube. In dimension 0, an [Hypercubeliterator](#) does not contain any element. However, in dimension 0, an [ExtendedHypercubeliterator](#) contains a unique element which is the vector of size 0. An [ExtendedHypercubeliterator](#) is helpful when the enumerated vectors are seen as prefixes or suffixes hence can be empty. This is used, in particular, in `compute_fast_walsh_transform`.

Definition at line 97 of file [iterator.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/iterator.hh`
- `lib/hnco/iterator.cc`

5.35 Factorization Class Reference

Factorization.

```
#include <hnco/functions/collection/factorization.hh>
```

Inheritance diagram for Factorization:



Public Member Functions

- **Factorization** ()
Constructor.
- **Factorization** (const std::string number)
Constructor.
- **~Factorization** ()
Destructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Load and save instance

- void **load** (std::string path)
Load instance.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.

Private Member Functions

- void `init ()`
Init GMP data structures.
- void `clear ()`
Clear GMP data structures.
- void `set_number` (const std::string number)
Set number.
- void `convert` (const `bit_vector_t` &x)
Convert a bit vector into two numbers.

Private Attributes

- `mpz_t _number`
Number to factorize.
- `mpz_t _first_factor`
First factor.
- `mpz_t _second_factor`
Second factor.
- `mpz_t _product`
Product.
- `std::string _first_factor_string`
First factor in binary form.
- `std::string _second_factor_string`
Secon factor in binary form.
- `size_t _number_size`
Number size in bits.
- `size_t _first_factor_size`
First factor size in bits.
- `size_t _second_factor_size`
Second factor size in bits.
- `int _bv_size`
Bit vector size.

5.35.1 Detailed Description

Factorization.

Reference:

Torbjörn Granlund and the GMP development team. 2012. GNU MP: The GNU Multiple Precision Arithmetic Library (5.0.5 ed.).

<http://gmplib.org/>.

Definition at line 29 of file [factorization.hh](#).

5.35.2 Constructor & Destructor Documentation

5.35.2.1 Factorization()

```
Factorization (
    const std::string number ) [inline]
```

Constructor.

Parameters

<i>number</i>	Number to factorize written in decimal form
---------------	---

Definition at line 82 of file [factorization.hh](#).

5.35.3 Member Function Documentation

5.35.3.1 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

The file referenced by the path is a text file which contains exactly one natural number written in base 10 without any space

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 102 of file [factorization.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/factorization.hh
- lib/hnco/functions/collection/factorization.cc

5.36 FfgenOptions Class Reference

Command line options for ffgen.

```
#include <ffgen-options.hh>
```

Public Member Functions

- **FfgenOptions** ()
Default constructor.
- **FfgenOptions** (int argc, char *argv[], bool ignore_bad_options=false)
Constructor.
- int **get_bv_size** () const
Get the value of bv_size.
- bool **with_bv_size** () const
With parameter bv_size.
- double **get_coupling_constant** () const
Get the value of coupling_constant.
- bool **with_coupling_constant** () const
With parameter coupling_constant.
- double **get_ep_upper_bound** () const
Get the value of ep_upper_bound.
- bool **with_ep_upper_bound** () const
With parameter ep_upper_bound.
- double **get_field_constant** () const
Get the value of field_constant.
- bool **with_field_constant** () const
With parameter field_constant.
- int **get_function** () const
Get the value of function.
- bool **with_function** () const
With parameter function.
- double **get_lin_distance** () const
Get the value of lin_distance.
- bool **with_lin_distance** () const
With parameter lin_distance.
- int **get_lin_generator** () const
Get the value of lin_generator.
- bool **with_lin_generator** () const
With parameter lin_generator.
- double **get_lin_initial_weight** () const
Get the value of lin_initial_weight.
- bool **with_lin_initial_weight** () const

- With parameter `lin_initial_weight`.*

 - double **get_lin_ratio** () const
 - Get the value of `lin_ratio`.*
 - bool **with_lin_ratio** () const
 - With parameter `lin_ratio`.*
 - int **get_ms_num_clauses** () const
 - Get the value of `ms_num_clauses`.*
 - bool **with_ms_num_clauses** () const
 - With parameter `ms_num_clauses`.*
 - int **get_ms_num_literals_per_clause** () const
 - Get the value of `ms_num_literals_per_clause`.*
 - bool **with_ms_num_literals_per_clause** () const
 - With parameter `ms_num_literals_per_clause`.*
 - int **get_nk_k** () const
 - Get the value of `nk_k`.*
 - bool **with_nk_k** () const
 - With parameter `nk_k`.*
 - int **get_nn1_generator** () const
 - Get the value of `nn1_generator`.*
 - bool **with_nn1_generator** () const
 - With parameter `nn1_generator`.*
 - int **get_nn2_generator** () const
 - Get the value of `nn2_generator`.*
 - bool **with_nn2_generator** () const
 - With parameter `nn2_generator`.*
 - int **get_nn2_num_columns** () const
 - Get the value of `nn2_num_columns`.*
 - bool **with_nn2_num_columns** () const
 - With parameter `nn2_num_columns`.*
 - int **get_nn2_num_rows** () const
 - Get the value of `nn2_num_rows`.*
 - bool **with_nn2_num_rows** () const
 - With parameter `nn2_num_rows`.*
 - int **get_part_upper_bound** () const
 - Get the value of `part_upper_bound`.*
 - bool **with_part_upper_bound** () const
 - With parameter `part_upper_bound`.*
 - std::string **get_path** () const
 - Get the value of `path`.*
 - bool **with_path** () const
 - With parameter `path`.*
 - int **get_seed** () const
 - Get the value of `seed`.*
 - bool **with_seed** () const
 - With parameter `seed`.*
 - double **get_stddev** () const
 - Get the value of `stddev`.*
 - bool **with_stddev** () const
 - With parameter `stddev`.*
 - int **get_sudoku_num_empty_cells** () const
 - Get the value of `sudoku_num_empty_cells`.*

- bool **with_sudoku_num_empty_cells** () const
With parameter sudoku_num_empty_cells.
- int **get_walsh2_generator** () const
Get the value of walsh2_generator.
- bool **with_walsh2_generator** () const
With parameter walsh2_generator.
- double **get_walsh2_ising_alpha** () const
Get the value of walsh2_ising_alpha.
- bool **with_walsh2_ising_alpha** () const
With parameter walsh2_ising_alpha.
- int **get_walsh_num_features** () const
Get the value of walsh_num_features.
- bool **with_walsh_num_features** () const
With parameter walsh_num_features.
- bool **with_ms_planted_solution** () const
With the flag ms_planted_solution.
- bool **with_periodic_boundary_conditions** () const
With the flag periodic_boundary_conditions.

Private Member Functions

- void **print_help** (std::ostream &stream) const
Print help message.
- void **print_version** (std::ostream &stream) const
Print version.

Private Attributes

- std::string **_exec_name**
Name of the executable.
- std::string **_version** = "0.26"
Name Version.
- int **_bv_size** = 100
Size of bit vectors.
- double **_coupling_constant** = 1
Coupling constant.
- double **_ep_upper_bound** = 1
Upper bound of numbers.
- double **_field_constant** = 1
Field constant.
- int **_function** = 1
Type of function.
- double **_lin_distance** = 1
Common distance of arithmetic progression.
- int **_lin_generator** = 0
Type of LinearFunction generator.
- double **_lin_initial_weight** = 1
Initial weight.
- double **_lin_ratio** = 2

- *Common ratio of geometric progression.*
- `int _ms_num_clauses = 100`
Number of clauses.
- `int _ms_num_literals_per_clause = 3`
Number of literals per clause.
- `int _nk_k = 3`
Each bit is connected to k other bits.
- `int _nn1_generator = 0`
Type of NearestNeighborIsingModel1 generator.
- `int _nn2_generator = 0`
Type of NearestNeighborIsingModel2 generator.
- `int _nn2_num_columns = 10`
Number of columns.
- `int _nn2_num_rows = 10`
Number of rows.
- `int _part_upper_bound = 100`
Upper bound of numbers.
- `std::string _path = "function.txt"`
Path (relative or absolute) of a function file.
- `int _seed`
Seed for the random number generator.
- `double _stddev = 1`
Standard deviation.
- `int _sudoku_num_empty_cells = 10`
Number of empty cells.
- `int _walsh2_generator = 0`
Type of WalshExpansion2 generator.
- `double _walsh2_ising_alpha = 2`
Dyson-Ising: exponential decay parameter for long range interactions.
- `int _walsh_num_features = 100`
Number of features.
- `bool _ms_planted_solution = false`
Generate an instance with a planted solution.
- `bool _periodic_boundary_conditions = false`
Periodic boundary conditions.

Friends

- `std::ostream & operator<< (std::ostream &, const FfgenOptions &)`
Print a header containing the parameter values.

5.36.1 Detailed Description

Command line options for ffgen.

Definition at line 11 of file [ffgen-options.hh](#).

The documentation for this class was generated from the following files:


- `app/ffgen-options.hh`
- `app/ffgen-options.cc`

5.37 FirstAscentHillClimbing Class Reference

First ascent hill climbing.

```
#include <hnco/algorithms/local-search/first-ascent-hill-climbing.hh>
```

Inheritance diagram for FirstAscentHillClimbing:



Public Member Functions

- **FirstAscentHillClimbing** (int n, [neighborhood::NeighborhoodIterator](#) *neighborhood)
Constructor.

Public Member Functions inherited from

[LocalSearchAlgorithm< neighborhood::NeighborhoodIterator >](#)

- **LocalSearchAlgorithm** (int n, [neighborhood::NeighborhoodIterator](#) *neighborhood)
Constructor.
- void **set_random_initialization** (bool b)
Set random initialization.
- void **set_starting_point** (const [bit_vector_t](#) &x)
Set the starting point.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [LocalSearchAlgorithm](#)< [neighborhood::NeighborhoodIterator](#) >

- void **init** () override
Initialize.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Additional Inherited Members

Protected Attributes inherited from [LocalSearchAlgorithm](#)< [neighborhood::NeighborhoodIterator](#) >

- [bit_vector_t](#) **_starting_point**
Starting point.
- [neighborhood::NeighborhoodIterator](#) * **_neighborhood**
Neighborhood.
- bool **_random_initialization**
Random initialization.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.37.1 Detailed Description

First ascent hill climbing.

Definition at line 34 of file [first-ascent-hill-climbing.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/local-search/first-ascent-hill-climbing.hh`
- `lib/hnco/algorithms/local-search/first-ascent-hill-climbing.cc`

5.38 FitnessProportionateSelection Class Reference

Fitness proportionate selection.

```
#include <hnco/algorithms/evolutionary-algorithms/random-selection.hh>
```

Inheritance diagram for FitnessProportionateSelection:



Public Member Functions

- [FitnessProportionateSelection](#) (const [Population](#) &population)
Constructor.
- void **init** () override
Initialize.
- const [bit_vector_t](#) & **select** () override
Select an individual in the population.

Public Member Functions inherited from [RandomSelection](#)

- [RandomSelection](#) (const [Population](#) &population)
Constructor.

Protected Attributes

- std::discrete_distribution **_distribution**
Distribution.

Protected Attributes inherited from [RandomSelection](#)

- const [Population](#) & **_population**
Population to select from

5.38.1 Detailed Description

Fitness proportionate selection.

Definition at line 119 of file [random-selection.hh](#).

5.38.2 Constructor & Destructor Documentation

5.38.2.1 FitnessProportionateSelection()

```
FitnessProportionateSelection (
    const Population & population ) [inline]
```

Constructor.

Parameters

<i>population</i>	Population to select from
-------------------	---------------------------

Precondition

population.values must be positive

Definition at line 130 of file [random-selection.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/random-selection.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/random-selection.cc](#)

5.39 FourPeaks Class Reference

Four Peaks.

```
#include <hnco/functions/collection/four-peaks.hh>
```

Inheritance diagram for FourPeaks:



Public Member Functions

- **FourPeaks** (int bv_size, int threshold)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `display` (std::ostream &stream) const
Display.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int `_bv_size`
Bit vector size.
- int `_threshold`
Threshold.
- int `_maximum`
Maximum.

5.39.1 Detailed Description

Four Peaks.

It is defined by

$$f(x) = \max\{\text{head}(x, 1) + \text{tail}(x, 0)\} + R(x)$$

where:

- `head(x, 1)` is the length of the longest prefix of x made of ones;
- `tail(x, 0)` is the length of the longest suffix of x made of zeros;
- `R(x)` is the reward;
- `R(x) = n` if (`head(x, 1) > t` and `tail(x, 0) > t`);
- `R(x) = 0` otherwise;
- the threshold `t` is a parameter of the function.

This function has four maxima, of which exactly two are global ones.

For example, if $n = 6$ and $t = 1$:

- $f(111111) = 6$ (local maximum)
- $f(111110) = 5$
- $f(111100) = 10$ (global maximum)

Reference:

S. Baluja and R. Caruana. 1995. Removing the genetics from the standard genetic algorithm. In Proceedings of the 12th Annual Conference on Machine Learning. 38–46.

Definition at line 60 of file [four-peaks.hh](#).

5.39.2 Member Function Documentation

5.39.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

$2 * _bv_size - _threshold - 1$

Reimplemented from [Function](#).

Definition at line 88 of file [four-peaks.hh](#).

5.39.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 84 of file [four-peaks.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/four-peaks.hh
- lib/hnco/functions/collection/four-peaks.cc

5.40 FrontDistancePair Struct Reference

Front-distance pair.

```
#include <hnco/multiobjective/algorithms/nsga2.hh>
```

Public Attributes

- int **pareto_front**
Pareto front.
- double **crowding_distance**
Crowding distance.

5.40.1 Detailed Description

Front-distance pair.

A front-distance pair measures the quality of an individual within a population.

Definition at line 43 of file [nsga2.hh](#).

The documentation for this struct was generated from the following file:

- [lib/hnco/multiobjective/algorithms/nsga2.hh](#)

5.41 FullMoment Struct Reference

Full moment.

```
#include <hnco/algorithms/walsh-moment/walsh-moment.hh>
```

Public Member Functions

- [FullMoment](#) (int n)
Constructor.
- void [display](#) (std::ostream &stream)
Display moment.
- void [init](#) ()
Initialize moment.
- void [add](#) (const [bit_vector_t](#) &bv)
Add a bit vector.
- void [average](#) (int count)
Compute average.
- void [update](#) (const [FullMoment](#) &fm, double rate)
Update a moment.
- void [update](#) (const [FullMoment](#) &fm1, const [FullMoment](#) &fm2, double rate)
Update a moment.

- void `scaled_difference` (double lambda, const `FullMoment` &fm1, const `FullMoment` &fm2)
Compute a scaled difference between two moments.
- void `bound` (double margin)
Bound moment.
- double `norm_1` () const
1-norm
- double `norm_2` () const
2-norm
- double `norm_infinite` () const
infinite-norm
- double `distance` (const `FullMoment` &fm) const
distance between the moment and another moment

Public Attributes

- `std::vector< double > first_moment`
First moment.
- `std::vector< std::vector< double > > second_moment`
Second moment.

5.41.1 Detailed Description

Full moment.

Definition at line 128 of file `walsh-moment.hh`.

5.41.2 Constructor & Destructor Documentation

5.41.2.1 FullMoment()

```
FullMoment (
    int n )
```

Constructor.

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 235 of file `walsh-moment.cc`.

5.41.3 Member Function Documentation

5.41.3.1 average()

```
void average (
    int count )
```

Compute average.

Parameters

<i>count</i>	Number of previously added bit vectors
--------------	--

Postcondition

`matrix_is_symmetric(second_moment)`

Definition at line 295 of file [walsh-moment.cc](#).

5.41.3.2 bound()

```
void bound (
    double margin )
```

Bound moment.

Parameters

<i>margin</i>	Distance from the -1/1 bounds
---------------	-------------------------------

Ensure that the distance from each moment to the -1/1 bounds is greater or equal to the given margin.

Definition at line 374 of file [walsh-moment.cc](#).

5.41.3.3 display()

```
void display (
    std::ostream & stream )
```

Display moment.

A [FullMoment](#) is displayed as a full symmetric matrix with diagonal entries equal to first moments and off-diagonal entries equal to second moments.

Definition at line 246 of file [walsh-moment.cc](#).

5.41.3.4 scaled_difference()

```
void scaled_difference (
    double lambda,
    const FullMoment & fm1,
    const FullMoment & fm2 )
```

Compute a scaled difference between two moments.

Parameters

<i>lambda</i>	Scale
<i>fm1</i>	First moment
<i>fm2</i>	Second moment

This member function implements:

```
self = lambda * fm1 - fm2
```

It is mostly useful in herding ([Hea](#)).

Definition at line 354 of file [walsh-moment.cc](#).

5.41.3.5 update() [1/2]

```
void update (
    const FullMoment & fm,
    double rate )
```

Update a moment.

Parameters

<i>fm</i>	Target moment
<i>rate</i>	Learning rate

Postcondition

For all i , $\text{is_in_interval}(\text{first_moment}[i], -1, 1)$

For all $i \neq j$, $\text{is_in_interval}(\text{second_moment}[i][j], -1, 1)$

$\text{matrix_is_symmetric}(\text{second_moment})$

This member function implements:

```
self += rate * (fm1 - self)
```

Definition at line 313 of file [walsh-moment.cc](#).

5.41.3.6 update() [2/2]

```
void update (
    const FullMoment & fm1,
    const FullMoment & fm2,
    double rate )
```

Update a moment.

Parameters

<i>fm1</i>	Target moment
<i>fm2</i>	Moment to move away from
<i>rate</i>	Learning rate

This member function implements:

```
self += rate * (fm1 - fm2)
```

The resulting entries are not necessarily those of a moment, that is

```
is_in_interval(first_moment[i], -1, 1) or
```

```
is_in_interval(second_moment[i][j], -1, 1)
```

might fail for some $i \neq j$.

Definition at line 334 of file [walsh-moment.cc](#).

The documentation for this struct was generated from the following files:

- [lib/hnco/algorithms/walsh-moment/walsh-moment.hh](#)
- [lib/hnco/algorithms/walsh-moment/walsh-moment.cc](#)

5.42 FullMomentGibbsSampler Class Reference

Gibbs sampler with full moments.

```
#include <hnco/algorithms/walsh-moment/gibbs-sampler.hh>
```

Public Types

- using **Moment** = [FullMoment](#)
Walsh moment type.

Public Member Functions

- **FullMomentGibbsSampler** (int n, const [FullMoment](#) &mp)
Constructor.
- void **init** ()
Initialize.
- void **update** (int i)
Update state.
- void **update_sync** ()
Update state synchronously.
- const [bit_vector_t](#) & **get_state** ()
Get the state of the Gibbs sampler.

Private Attributes

- const [FullMoment](#) & **_model_parameters**
Model parameters.
- [bit_vector_t](#) **_state**
State of the Gibbs sampler.
- [pv_t](#) **_pv**
Probability vector for synchronous Gibbs sampling.

5.42.1 Detailed Description

Gibbs sampler with full moments.

Definition at line 73 of file [gibbs-sampler.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/algorithms/walsh-moment/gibbs-sampler.hh](#)
- [lib/hnco/algorithms/walsh-moment/gibbs-sampler.cc](#)

5.43 FullMomentHerding Class Reference

Herding with full moments.

```
#include <hnco/algorithms/walsh-moment/herding.hh>
```

Public Types

- using **Moment** = [FullMoment](#)
Walsh moment type.

Public Member Functions

- [FullMomentHerding](#) (int n)
Constructor.
- void **init** ()
Initialization.
- void **sample** (const [FullMoment](#) &target, [bit_vector_t](#) &x)
Sample a bit vector.
- double **error** (const [FullMoment](#) &target)
Compute the error.

Getters

- const [FullMoment](#) & [get_delta](#) () const

Setters

- void [set_randomize_bit_order](#) (bool b)

Private Attributes

- `FullMoment_delta`
Delta moment.
- `FullMoment_count`
Counter moment.
- `FullMoment_error`
Error moment.
- `permutation_t_permutation`
Permutation.
- `int_time`
Time.

Parameters

- `bool_randomize_bit_order` = true

5.43.1 Detailed Description

Herdling with full moments.

Definition at line 99 of file [herding.hh](#).

5.43.2 Constructor & Destructor Documentation

5.43.2.1 FullMomentHerdling()

```
FullMomentHerdling (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 125 of file [herding.hh](#).

5.43.3 Member Function Documentation

5.43.3.1 get_delta()

```
const FullMoment & get_delta ( ) const [inline]
```

Get delta

Definition at line 141 of file [herding.hh](#).

5.43.3.2 `set_randomize_bit_order()`

```
void set_randomize_bit_order (
    bool b ) [inline]
```

Randomize bit order

Definition at line 148 of file [herding.hh](#).

5.43.4 Member Data Documentation

5.43.4.1 `_randomize_bit_order`

```
bool _randomize_bit_order = true [private]
```

Randomize bit order

Definition at line 115 of file [herding.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/walsh-moment/herding.hh`
- `lib/hnco/algorithms/walsh-moment/herding.cc`

5.44 Function Class Reference

Function

```
#include <hnco/functions/function.hh>
```

Inheritance diagram for Function:



Public Member Functions

- virtual **~Function** ()
Destructor.

Information about the function

- virtual int **get_bv_size** () const =0
Get bit vector size.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.

Evaluation

- virtual double **evaluate** (const [bit_vector_t](#) &)=0
Evaluate a bit vector.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Display

- virtual void **display** (std::ostream &stream) const
Display.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

5.44.1 Detailed Description

Function

Definition at line 41 of file [function.hh](#).

5.44.2 Member Function Documentation

5.44.2.1 describe()

```
virtual void describe (
    const bit\_vector\_t & x,
    std::ostream & stream ) [inline], [virtual]
```

Describe a bit vector.

The member function [Function::describe](#) is not declared const for the same reason [Function::evaluate](#) is not: it might need to decode the given bit vector hence use some pre-allocated memory buffer.

Reimplemented in [FunctionMapComposition](#), [MultiobjectiveFunctionAdapter](#), [MultivariateFunctionAdapter< Fn, Rep, Conv >](#), [MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >](#), [PermutationFunctionAdapter< Fn >](#), [UniversalFunctionAdapter](#), [Factorization](#), [Partition](#), and [Decorator](#).

Definition at line 130 of file [function.hh](#).

5.44.2.2 evaluate()

```
virtual double evaluate (
    const bit\_vector\_t & ) [pure virtual]
```

Evaluate a bit vector.

This member function is not declared const and is not supposed to be thread-safe. In particular, in order to evaluate a bit vector, it might require some data member to store temporary results. In case of parallel evaluation, there should be a copy of the function per thread, as is done in `Population::evaluate_in_parallel`.

Implemented in [LongPath](#), [FunctionPlugin](#), [Trap](#), [StopOnTarget](#), [CallCounter](#), [OnBudgetFunction](#), [ProgressTracker](#), [Cache](#), [EqualProducts](#), [Factorization](#), [FourPeaks](#), [SixPeaks](#), [NearestNeighborIsingModel1](#), [NearestNeighborIsingModel2](#), [Jump](#), [DeceptiveJump](#), [Labs](#), [LinearFunction](#), [MaxSat](#), [MaxNae3Sat](#), [NkLandscape](#), [Partition](#), [PythonFunction](#), [Qubo](#), [OneMax](#), [LeadingOnes](#), [Needle](#), [Hiff](#), [Ridge](#), [Plateau](#), [WalshExpansion1](#), [WalshExpansion2](#), [WalshExpansion](#), [ParsedModifier](#), [PriorNoise](#), [OppositeFunction](#), [FunctionMapComposition](#), [AdditiveGaussianNoise](#), [MultiobjectiveFunctionAdapter](#), [MultivariateFunctionAdapter< Fn, Rep, Conv >](#), [MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >](#), [PermutationFunctionAdapter< Fn >](#), [UniversalFunctionAdapter](#), [SummationCancellation](#), and [SinusSummationCancellation](#).

5.44.2.3 evaluate_incrementally()

```
virtual double evaluate_incrementally (
    const bit\_vector\_t & x,
    double value,
    const sparse\_bit\_vector\_t & flipped_bits ) [inline], [virtual]
```

Incrementally evaluate a bit vector.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Reimplemented in [StopOnTarget](#), [CallCounter](#), [OnBudgetFunction](#), [ProgressTracker](#), [OppositeFunction](#), [LinearFunction](#), [OneMax](#), [WalshExpansion1](#), [NearestNeighborIsingModel1](#), and [NearestNeighborIsingModel2](#).

Definition at line 91 of file [function.hh](#).

5.44.2.4 evaluate_safely()

```
virtual double evaluate_safely (
    const bit\_vector\_t & x ) [inline], [virtual]
```

Safely evaluate a bit vector.

Must neither throw any exception nor update global states (e.g. maximum) in function controllers. It is used in `Population::evaluate_in_parallel` inside a OMP parallel for loop.

By default, calls `evaluate`.

Reimplemented in [Controller](#).

Definition at line 105 of file [function.hh](#).

5.44.2.5 get_maximum()

```
virtual double get_maximum ( ) const [inline], [virtual]
```

Get the global maximum.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Reimplemented in [LongPath](#), [Trap](#), [Controller](#), [SummationCancellation](#), [FourPeaks](#), [SixPeaks](#), [Jump](#), [DeceptiveJump](#), [LinearFunction](#), [PythonFunction](#), [OneMax](#), [LeadingOnes](#), [Needle](#), [Hiff](#), [Ridge](#), [Plateau](#), [WalshExpansion1](#), [FunctionMapComposition](#), and [PriorNoise](#).

Definition at line 57 of file [function.hh](#).

5.44.2.6 provides_incremental_evaluation()

```
virtual bool provides_incremental_evaluation ( ) const [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented in [Controller](#), [Cache](#), [NearestNeighborIsingModel1](#), [NearestNeighborIsingModel2](#), [LinearFunction](#), [OneMax](#), [WalshExpansion1](#), [OppositeFunction](#), and [PriorNoise](#).

Definition at line 67 of file [function.hh](#).

5.44.2.7 update()

```
virtual void update (
    const bit\_vector\_t & x,
    double value ) [inline], [virtual]
```

Update states after a safe evaluation.

By default, does nothing.

Reimplemented in [StopOnTarget](#), [CallCounter](#), [OnBudgetFunction](#), and [ProgressTracker](#).

Definition at line 111 of file [function.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/functions/function.hh](#)

5.45 Function Class Reference

Function

```
#include <hnco/multiobjective/functions/function.hh>
```

Inheritance diagram for Function:



Public Member Functions

- virtual **~Function** ()

Destructor.

Information about the function

- virtual int **get_bv_size** () const =0
Get bit vector size.
- virtual int **get_output_size** () const =0
Get output size (number of objectives)

Evaluation

- virtual void **evaluate** (const [bit_vector_t](#) &bv, [value_t](#) &value)=0
Evaluate a bit vector.

Display

- virtual void **display** (std::ostream &stream) const
Display.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

5.45.1 Detailed Description

Function

Definition at line 41 of file [function.hh](#).

5.45.2 Member Function Documentation

5.45.2.1 describe()

```
virtual void describe (
    const bit\_vector\_t & x,
    std::ostream & stream ) [inline], [virtual]
```

Describe a bit vector.

The member function [describe\(\)](#) is not declared const for the same reason [evaluate\(\)](#) is not: it might need to decode the given bit vector hence use some pre-allocated memory buffer.

Reimplemented in [MultivariateFunctionAdapter< Fn, Rep, Conv >](#), [MixedRepresentationMultivariateFunctionAdapter< Fn, RepVaria](#) and [UniversalFunctionAdapter](#).

Definition at line 95 of file [function.hh](#).

5.45.2.2 evaluate()

```
virtual void evaluate (
    const bit\_vector\_t & bv,
    value\_t & value ) [pure virtual]
```

Evaluate a bit vector.

This member function is not declared const and is not supposed to be thread-safe. In particular, in order to evaluate a bit vector, it might require some data member to store temporary results. In case of parallel evaluation, there should be a copy of the function per thread, as is done in `Population::evaluate_in_parallel()`.

Parameters

<i>bv</i>	Bit vector to evaluate
<i>value</i>	Output value

Implemented in [PythonFunction](#), [MultivariateFunctionAdapter< Fn, Rep, Conv >](#), [MixedRepresentationMultivariateFunctionAdapter<](#) and [UniversalFunctionAdapter](#).

The documentation for this class was generated from the following file:


- `lib/hnco/multiobjective/functions/function.hh`

5.46 FunctionFactory Class Reference

Function factory.

```
#include <hnco/app/function-factory.hh>
```

Inheritance diagram for FunctionFactory:



Public Member Functions

- virtual `hnco::function::Function * make ()=0`
Make a function.

5.46.1 Detailed Description

Function factory.

Definition at line 33 of file [function-factory.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/app/function-factory.hh`

5.47 FunctionFactory Class Reference

Function factory.

```
#include <hnco/multiobjective/app/function-factory.hh>
```

Inheritance diagram for FunctionFactory:



Public Member Functions

- virtual [hnco::multiobjective::function::Function](#) * **make** ()=0
Make a function.

5.47.1 Detailed Description

Function factory.

Definition at line 34 of file [function-factory.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/multiobjective/app/function-factory.hh

5.48 FunctionMapComposition Class Reference

Composition of a function and a map.

```
#include <hnco/functions/modifiers/modifier.hh>
```

Inheritance diagram for FunctionMapComposition:



Public Member Functions

- **FunctionMapComposition** ([Function](#) *function, [hnco::map::Map](#) *map)
Constructor.
- double **evaluate** (const [bit_vector_t](#) &bv) override
Evaluate a bit vector.

Properties

- int [get_bv_size](#) () const override
- double [get_maximum](#) () const override
Get the global maximum.
- bool [has_known_maximum](#) () const override
Check for a known maximum.

Display

- void [describe](#) (const [bit_vector_t](#) &bv, std::ostream &stream) override

Public Member Functions inherited from [Modifier](#)

- **Modifier** ([Function](#) *function)
Constructor.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Attributes

- `hnco::map::Map * _map`
Map.
- `bit_vector_t _output`
Map output.

Additional Inherited Members**Protected Attributes inherited from [Decorator](#)**

- `Function * _function`
Decorated function.

5.48.1 Detailed Description

Composition of a function and a map.

Definition at line 83 of file [modifier.hh](#).

5.48.2 Constructor & Destructor Documentation**5.48.2.1 FunctionMapComposition()**

```
FunctionMapComposition (
    Function * function,
    hnco::map::Map * map ) [inline]
```

Constructor.

Precondition

`map->get_output_size() == function->get_bv_size()`

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 95 of file [modifier.hh](#).

5.48.3 Member Function Documentation**5.48.3.1 describe()**

```
void describe (
    const bit_vector_t & bv,
    std::ostream & stream ) [override], [virtual]
```

Describe a bit vector

Reimplemented from [Decorator](#).

Definition at line 50 of file [modifier.cc](#).

5.48.3.2 get_bv_size()

```
int get_bv_size ( ) const [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 110 of file [modifier.hh](#).

5.48.3.3 get_maximum()

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Reimplemented from [Function](#).

Definition at line 115 of file [modifier.hh](#).

5.48.3.4 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true if the function has a known maximum and the map is bijective.

Reimplemented from [Function](#).

Definition at line 125 of file [modifier.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/modifiers/modifier.hh](#)
- [lib/hnco/functions/modifiers/modifier.cc](#)

5.49 FunctionPlugin Class Reference

Function plugin

```
#include <hnco/functions/collection/plugin.hh>
```

Inheritance diagram for FunctionPlugin:



Public Member Functions

- [FunctionPlugin](#) (int bv_size, std::string path, std::string name)
Constructor.
- [~FunctionPlugin](#) ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- double [evaluate](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual [~Function](#) ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool [has_known_maximum](#) () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void [display](#) (std::ostream &stream) const
Display.
- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Types

- using **extern_function_t** = double (*)(const [bit_t](#) *, size_t)
Type of an extern function.

Private Attributes

- int **_bv_size**
Bit vector size.
- void * **_handle**
Handle returned by dlopen.
- [extern_function_t](#) **_extern_function**
Extern function.

5.49.1 Detailed Description

Function plugin

Definition at line 34 of file [plugin.hh](#).

5.49.2 Constructor & Destructor Documentation

5.49.2.1 FunctionPlugin()

```
FunctionPlugin (
    int bv_size,
    std::string path,
    std::string name )
```

Constructor.

Parameters

<i>bv_size</i>	Size of bit vectors
<i>path</i>	Path to a shared library
<i>name</i>	Name of a function of the shared library

Definition at line 35 of file [plugin.cc](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/plugin.hh
- lib/hnco/functions/collection/plugin.cc

5.50 Generator Struct Reference

Random number generator.

```
#include <hnco/random.hh>
```

Static Public Member Functions

- static void **set_seed** (unsigned n)
Set seed.
- static void **set_seed** ()
Set seed.
- static void **reset** ()
Reset engine.
- static double **uniform** ()
Sample random number with uniform distribution.
- static double **normal** ()
Sample random number with normal distribution.
- static bool **bernoulli** ()
Sample random number with Bernoulli distribution.

Static Public Attributes

- static std::mt19937 **engine**
Mersenne Twister engine.
- static unsigned **seed** = std::mt19937::default_seed
Seed.

5.50.1 Detailed Description

Random number generator.

Definition at line 34 of file [random.hh](#).

5.50.2 Member Function Documentation

5.50.2.1 reset()

```
void reset ( ) [static]
```

Reset engine.

Using static member seed.

Definition at line 45 of file [random.cc](#).

5.50.2.2 set_seed()

```
void set_seed ( ) [static]
```

Set seed.

Uses std::chrono::system_clock.

Definition at line 39 of file [random.cc](#).

The documentation for this struct was generated from the following files:


- lib/hnco/random.hh
- lib/hnco/random.cc

5.51 GeneticAlgorithm Class Reference

Genetic algorithm.

```
#include <hnco/algorithms/evolutionary-algorithms/genetic-algorithm.hh>
```

Inheritance diagram for GeneticAlgorithm:



Public Member Functions

- [GeneticAlgorithm](#) (int n, int mu)
Constructor.

Setters

- void **set_mutation_rate** (double p)
Set the mutation rate.
- void **set_crossover_probability** (double p)
Set the crossover probability.
- void **set_tournament_size** (int n)
Set the tournament size.
- void **set_allow_no_mutation** (bool b)
Set the flag _allow_no_mutation.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) _parents
Parents.
- [Population](#) _offsprings
Offsprings.
- [CommaSelection](#) _comma_selection
Comma selection.
- [TournamentSelection](#) _tournament_selection
Tournament selection.
- [neighborhood::StandardBitMutation](#) _mutation
Mutation operator.
- `std::bernoulli_distribution` _do_crossover
Do crossover.
- [UniformCrossover](#) _crossover
Uniform crossover.

Parameters

- `double` _mutation_rate
Mutation rate.
- `double` _crossover_probability = 0.5
Crossover probability.
- `int` _tournament_size = 10
Tournament size.
- `bool` _allow_no_mutation = false
Allow no mutation.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int` _iteration
Current iteration.
- `bool` _last_iteration = false
Last iteration.
- `bool` _something_to_log = false
Something to log.
- `int` _num_iterations = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * >` _functions
Functions.
- `function::Function *` _function
Function.
- `solution_t` _solution
Solution.
- `logging::LogContext *` _log_context = nullptr
Log context.

5.51.1 Detailed Description

Genetic algorithm.

- Tournament selection for reproduction
- Uniform crossover
- Standard bit mutation
- (mu, mu) selection (offspring population replaces parent population)

Reference:

J. H. Holland. 1975. Adaptation in natural and artificial systems. University of Michigan Press, Ann Arbor.

Definition at line 53 of file [genetic-algorithm.hh](#).

5.51.2 Constructor & Destructor Documentation

5.51.2.1 GeneticAlgorithm()

```
GeneticAlgorithm (
    int n,
    int mu ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Population size

Definition at line 115 of file [genetic-algorithm.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/evolutionary-algorithms/genetic-algorithm.hh
- lib/hnco/algorithms/evolutionary-algorithms/genetic-algorithm.cc

5.52 Gomea Class Reference

GOMEA.

```
#include <hnco/algorithms/gomea/gomea.hh>
```

Inheritance diagram for Gomea:



Public Member Functions

- **Gomea** (int n)
Constructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions)
Maximize.
- void **finalize** ()
Finalize.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual ~**Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Attributes

- ::gomea::linkage_config_t **_linkage_config**
Linkage configuration.
- ::gomea::discrete::Config **_config**
Configuration.
- std::shared_ptr< [HncoFitness](#) > **_fitness**
Fitness.
- std::shared_ptr< [hnco::function::controller::ProgressTracker](#) > **_tracker**
Progress tracker.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.52.1 Detailed Description

GOMEA.

Implementation of the Gene-pool Optimal Mixing Evolutionary [Algorithm](#).

Author: Anton Bouter

Integrated into HNCO by Arnaud Berny

References:

- A Joint Python/C++ Library for Efficient yet Accessible Black-Box and Gray-Box Optimization with GOMEA, Anton Bouter and Peter A.N. Bosman
- Parameterless Gene-pool Optimal Mixing Evolutionary Algorithms, Arkadiy Dushatskiy, Marco Virgolin, Anton Bouter, Dirk Thierens, and Peter A. N. Bosman

Definition at line 62 of file [gomea.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/gomea/gomea.hh
- lib/hnco/algorithms/gomea/gomea.cc

5.53 HammingBall Class Reference

Hamming ball.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for HammingBall:



Public Member Functions

- [HammingBall](#) (int n, int r)
Constructor.

Public Member Functions inherited from [MultiBitFlip](#)

- [MultiBitFlip](#) (int n)
Constructor.

Public Member Functions inherited from [Neighborhood](#)

- [Neighborhood](#) (int n)
Constructor.
- virtual [~Neighborhood](#) ()
Destructor.
- virtual void [set_origin](#) (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & [get_origin](#) () const
Get the origin.
- virtual const [bit_vector_t](#) & [get_candidate](#) () const
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & [get_flipped_bits](#) () const
Get flipped bits.

- virtual void **propose** ()
Propose a candidate bit vector.
- virtual void **keep** ()
Keep the candidate bit vector.
- virtual void **forget** ()
Forget the candidate bit vector.
- virtual void **mutate** ([bit_vector_t](#) &bv)
Mutate.
- virtual void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Private Member Functions

- void **sample_bits** ()
Sample bits.

Private Attributes

- `std::uniform_int_distribution< int > _choose_k`
Choose the distance to the center.

Additional Inherited Members

Protected Member Functions inherited from [MultiBitFlip](#)

- void [bernoulli_trials](#) (int k)
Sample a given number of bits using Bernoulli trials.
- void [rejection_sampling](#) (int k)
Sample a given number of bits using rejection sampling.

Protected Attributes inherited from [Neighborhood](#)

- [bit_vector_t](#) **_origin**
Origin of the neighborhood.
- [bit_vector_t](#) **_candidate**
candidate bit vector
- `std::uniform_int_distribution< int > _index_dist`
Index distribution.
- [sparse_bit_vector_t](#) **_flipped_bits**
Flipped bits.

5.53.1 Detailed Description

Hamming ball.

Choose k uniformly on $[1..r]$, where r is the radius of the ball, choose k bits uniformly among n and flip them.

Definition at line 302 of file [neighborhood.hh](#).

5.53.2 Constructor & Destructor Documentation

5.53.2.1 HammingBall()

```
HammingBall (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
r	Radius of the ball

Definition at line 318 of file [neighborhood.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.54 HammingSphere Class Reference

Hamming sphere.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for HammingSphere:



Public Member Functions

- [HammingSphere](#) (int n, int r)
Constructor.
- void **set_radius** (int r)
Set radius.

Public Member Functions inherited from [MultiBitFlip](#)

- [MultiBitFlip](#) (int n)
Constructor.

Public Member Functions inherited from [Neighborhood](#)

- [Neighborhood](#) (int n)
Constructor.
- virtual \sim **Neighborhood** ()
Destructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & **get_origin** () const
Get the origin.
- virtual const [bit_vector_t](#) & **get_candidate** () const
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & **get_flipped_bits** () const
Get flipped bits.
- virtual void **propose** ()
Propose a candidate bit vector.
- virtual void **keep** ()
Keep the candidate bit vector.
- virtual void **forget** ()
Forget the candidate bit vector.
- virtual void **mutate** ([bit_vector_t](#) &bv)
Mutate.
- virtual void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Private Member Functions

- void **sample_bits** ()
Sample bits.

Private Attributes

- int **_radius**
Radius of the sphere.

Additional Inherited Members

Protected Member Functions inherited from [MultiBitFlip](#)

- void [bernoulli_trials](#) (int k)
Sample a given number of bits using Bernoulli trials.
- void [rejection_sampling](#) (int k)
Sample a given number of bits using rejection sampling.

Protected Attributes inherited from [Neighborhood](#)

- [bit_vector_t_origin](#)
Origin of the neighborhood.
- [bit_vector_t_candidate](#)
candidate bit vector
- `std::uniform_int_distribution< int > _index_dist`
Index distribution.
- [sparse_bit_vector_t_flipped_bits](#)
Flipped bits.

5.54.1 Detailed Description

Hamming sphere.

Uniformly choose r bits among n and flip them, where r is the radius of the sphere.

Definition at line 334 of file [neighborhood.hh](#).

5.54.2 Constructor & Destructor Documentation

5.54.2.1 HammingSphere()

```
HammingSphere (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
r	Radius of the sphere

Definition at line 350 of file [neighborhood.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/neighborhoods/neighborhood.hh`
- `lib/hnco/neighborhoods/neighborhood.cc`

5.55 HammingSphereIterator Class Reference

Hamming sphere neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for HammingSphereIterator:



Public Member Functions

- [HammingSphereIterator](#) (int n, int r)
Constructor.
- bool **has_next** () override
Has next bit vector.
- const [bit_vector_t](#) & **next** () override
Next bit vector.

Public Member Functions inherited from [NeighborhoodIterator](#)

- [NeighborhoodIterator](#) (int n)
Constructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set origin.

Public Member Functions inherited from [Iterator](#)

- **Iterator** (int n)
Constructor.
- virtual **~Iterator** ()
Destructor.
- virtual void **init** ()
Initialization.

Private Attributes

- `int _radius`
Radius of the ball.
- `sparse_bit_vector_t _bit_indexes`
Bit indexes.

Additional Inherited Members**Protected Attributes inherited from [Iterator](#)**

- `bit_vector_t _current`
Current bit vector.
- `bool _initial_state = true`
Flag for initial state.

5.55.1 Detailed Description

Hamming sphere neighborhood iterator.

The Hamming sphere iterator is implemented using an array of indexes which indicate the bits to flip in the given origin.

For example, in dimension $n = 4$ and with $\text{radius} = 2$, the sequence of indexes is as follows (assuming indexes start at 1):

- 12 (first state, bits 1 and 2 are flipped)
- 13
- 14
- 23 (last index cannot be increased, first index is increased and second index is reset)
- 24
- 34

Reference: https://en.wikipedia.org/wiki/Combination#Enumerating_k-combinations

Definition at line 96 of file [neighborhood-iterator.hh](#).

5.55.2 Constructor & Destructor Documentation**5.55.2.1 HammingSphereIterator()**

```
HammingSphereIterator (
    int n,
    int r )
```

Constructor.

Parameters

n	Size of bit vectors
r	Radius of Hamming Ball

Definition at line 72 of file [neighborhood-iterator.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/neighborhoods/neighborhood-iterator.hh](#)
- [lib/hnco/neighborhoods/neighborhood-iterator.cc](#)

5.56 Hboa Class Reference

Hierarchical Bayesian Optimization Algorithm.

```
#include <hnco/algorithms/fast-efficient-p3/hboa.hh>
```

Inheritance diagram for Hboa:



Public Member Functions

- **Hboa** (int n)
Constructor.
- **~Hboa** ()
Destructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions)
Maximize.
- void **finalize** ()
Finalize.
- void **set_population_size** (int n)
Set population size.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Attributes

- [Implementation](#) * **_implementation**
Pointer to implementation.
- int **_population_size** = 10
[Population](#) size.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.56.1 Detailed Description

Hierarchical Bayesian Optimization Algorithm.

Implementation of the Hierarchical Bayesian Optimization Algorithm.

Author: Brian W. Goldman

Integrated into HNCO by Arnaud Berny

Reference:

Pelikan, M. and Goldberg, D. (2006). Hierarchical bayesian optimization algorithm. In Scalable Optimization via Probabilistic Modeling, volume 33 of Studies in Computational Intelligence, pages 63–90. Springer Berlin Heidelberg.

Definition at line 50 of file [hboa.hh](#).

5.56.2 Member Data Documentation

5.56.2.1 `_implementation`

```
Implementation* _implementation [private]
```

Pointer to implementation.

The main motivation for this pattern is to avoid including declarations from [fast_efficient_p3](#) into the global namespace.

A raw pointer is used instead of a `unique_ptr` because the latter will not compile with `pybind11`.

Definition at line 60 of file [hboa.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/fast-efficient-p3/hboa.hh`
- `lib/hnco/algorithms/fast-efficient-p3/hboa.cc`

5.57 `Hea< Herding >` Class Template Reference

Herding evolutionary algorithm.

```
#include <hnco/algorithms/walsh-moment/hea.hh>
```

Inheritance diagram for `Hea< Herding >`:



Public Member Functions

- [Hea](#) (int n, int population_size)

Constructor.

Setters

- void [set_margin](#) (double x)
- void [set_selection_size](#) (int n)
Set the selection size.
- void [set_reset_period](#) (int n)
Set the reset period.
- void [set_learning_rate](#) (double x)
Set the learning rate.
- void [set_bound_moment](#) (bool b)
Set the bound moment after update.
- void [set_randomize_bit_order](#) (bool b)
Randomize bit order.

Setters for logging

- void [set_log_herding_error](#) (bool b)
- void [set_log_target_norm](#) (bool b)
Log target 2-norm (distance to uniform moment)
- void [set_log_delta_norm](#) (bool b)
Log delta (moment increment) 2-norm.
- void [set_log_target](#) (bool b)
Log target moment as a symmetric matrix.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- [Algorithm](#) (int n)
Constructor.
- virtual [~Algorithm](#) ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & [get_solution](#) ()
Get the solution.

Private Member Functions

Loop

- void **init** () override
- void **iterate** () override
Single iteration.
- void **set_something_to_log** ()
Set flag for something to log.
- void **log** () override
Log.

Private Attributes

- Herding::Moment **_target**
Target moment.
- Herding::Moment **_selection**
Moment of selected individuals.
- **algorithm::Population** **_population**
Population
- Herding **_herding**
Herding.
- double **_herding_error**
Herding error (moment discrepancy)
- double **_target_norm**
Target 2-norm (distance to uniform moment)
- double **_delta_norm**
Delta (moment increment) 2-norm.

Parameters

- double **_margin**
- int **_selection_size** = 1
Selection size.
- int **_reset_period** = 0
Reset period.
- double **_learning_rate** = 1e-4
Learning rate.
- bool **_bound_moment** = true
Bound moment after update.

Logging

- bool **_log_herding_error** = false
- bool **_log_target_norm** = false
Log target 2-norm (distance to uniform moment)
- bool **_log_delta_norm** = false
Log delta 2-norm (moment increment)
- bool **_log_target** = false
Log target moment as a symmetric matrix.

Additional Inherited Members

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.57.1 Detailed Description

```
template<class Herding>
class hnco::algorithm::walsh_moment::Hea< Herding >
```

Herding evolutionary algorithm.

Reference:

Arnaud Berny. 2015. Herding Evolutionary Algorithm. In Proceedings of the Companion Publication of the 2015 Annual Conference on Genetic and Evolutionary Computation (GECCO Companion '15). ACM, New York, NY, USA, 1355–1356.

Definition at line 45 of file [hea.hh](#).

5.57.2 Constructor & Destructor Documentation

5.57.2.1 Hea()

```
template<class Herding >
Hea (
    int n,
    int population_size ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>population_size</i>	Population size

`_margin` is initialized to $1 / n$.

Definition at line 169 of file [hea.hh](#).

5.57.3 Member Function Documentation

5.57.3.1 init()

```
template<class Herding >
void init ( ) [inline], [override], [private], [virtual]
```

Initialization

Reimplemented from [IterativeAlgorithm](#).

Definition at line 93 of file [hea.hh](#).

5.57.3.2 set_log_herding_error()

```
template<class Herding >
void set_log_herding_error (
    bool b ) [inline]
```

Log herding error (moment discrepancy)

Definition at line 209 of file [hea.hh](#).

5.57.3.3 set_margin()

```
template<class Herding >
void set_margin (
    double x ) [inline]
```

Set the moment margin

Definition at line 182 of file [hea.hh](#).

5.57.3.4 set_reset_period()

```
template<class Herding >
void set_reset_period (
    int n ) [inline]
```

Set the reset period.

Parameters

<i>n</i>	Reset period
----------	--------------

$n \leq 0$ means no reset.

Definition at line 196 of file [hea.hh](#).

5.57.3.5 set_selection_size()

```
template<class Herding >
void set_selection_size (
    int n ) [inline]
```

Set the selection size.

The selection size is the number of selected individuals in the population.

Definition at line 189 of file [hea.hh](#).

5.57.4 Member Data Documentation

5.57.4.1 `_log_herding_error`

```
template<class Herding >
bool _log_herding_error = false [private]
```

Log herding error (moment discrepancy)

Definition at line 80 of file [hea.hh](#).

5.57.4.2 `_margin`

```
template<class Herding >
double _margin [private]
```

Moment margin

Definition at line 65 of file [hea.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/walsh-moment/hea.hh`

5.58 Hiff Class Reference

Hierarchical if and only if.

```
#include <hnco/functions/collection/theory.hh>
```

Inheritance diagram for Hiff:



Public Member Functions

- **Hiff** (int bv_size)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const
Display.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int **_bv_size**
Bit vector size.
- int **_depth**
Tree depth.

5.58.1 Detailed Description

Hierarchical if and only if.

Reference:

Watson, R. A., Hornby, G. S., & Pollack, J. B. (1998). Modeling building-block interdependency. In Parallel Problem Solving from Nature—PPSN V: 5th International Conference Amsterdam, The Netherlands September 27–30, 1998 Proceedings 5 (pp. 97-106). Springer Berlin Heidelberg.

Definition at line 143 of file [theory.hh](#).

5.58.2 Member Function Documentation

5.58.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

$(i + 1) * 2^i$ where $2^i = _bv_size$

Reimplemented from [Function](#).

Definition at line 165 of file [theory.hh](#).

5.58.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 160 of file [theory.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/functions/collection/theory.hh](#)
- [lib/hnco/functions/collection/theory.cc](#)

5.59 HncoEvaluator Class Reference

Evaluator for HNCO functions.

```
#include <hnco/algorithms/fast-efficient-p3/hnco-evaluator.hh>
```

Inherits [Evaluator](#).

Public Member Functions

- **HncoEvaluator** ([hnco::function::Function](#) *function)
Constructor.
- float **evaluate** (const std::vector< bool > &x)
Evaluate a bit vector.

Private Attributes

- [hnco::function::Function](#) * **_function**
HNCO function.
- [hnco::bit_vector_t](#) **_bv**
Argument of HNCO function.

5.59.1 Detailed Description

Evaluator for HNCO functions.

Definition at line 36 of file [hnco-evaluator.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/algorithms/fast-efficient-p3/hnco-evaluator.hh

5.60 HncoFitness Class Reference

Fitness for HNCO functions.

```
#include <hnco/algorithms/gomea/hnco-fitness.hh>
```

Inherits [BBOFitnessFunction_t< char >](#).

Public Member Functions

- **HncoFitness** ([hnco::function::Function](#) *function)
Constructor.
- double **objectiveFunction** (int objective_index, ::gomea::vec_t< char > &variables) override
Evaluate a bit vector.

Private Attributes

- [hnco::function::Function](#) * **_function**
HNCO function.
- [hnco::bit_vector_t](#) **_bv**
Argument of HNCO function.

5.60.1 Detailed Description

Fitness for HNCO functions.

Definition at line 35 of file [hnco-fitness.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/algorithms/gomea/hnco-fitness.hh

5.61 HncoOptions Class Reference

Command line options for hnco.

```
#include <hnco/app/hnco-options.hh>
```

Public Member Functions

- **HncoOptions** ()
Default constructor.
- **HncoOptions** (int argc, char *argv[], bool ignore_bad_options=false)
Constructor.
- int **get_algorithm** () const
Get the value of algorithm.
- bool **with_algorithm** () const
With parameter algorithm.
- int **get_bm_num_gs_cycles** () const
Get the value of bm_num_gs_cycles.
- bool **with_bm_num_gs_cycles** () const
With parameter bm_num_gs_cycles.
- int **get_bm_num_gs_steps** () const
Get the value of bm_num_gs_steps.
- bool **with_bm_num_gs_steps** () const
With parameter bm_num_gs_steps.
- int **get_bm_reset_mode** () const
Get the value of bm_reset_mode.
- bool **with_bm_reset_mode** () const
With parameter bm_reset_mode.
- int **get_bm_sampling_mode** () const
Get the value of bm_sampling_mode.
- bool **with_bm_sampling_mode** () const
With parameter bm_sampling_mode.
- int **get_budget** () const
Get the value of budget.
- bool **with_budget** () const
With parameter budget.
- int **get_bv_size** () const
Get the value of bv_size.
- bool **with_bv_size** () const
With parameter bv_size.
- std::string **get_description_path** () const
Get the value of description_path.
- bool **with_description_path** () const
With parameter description_path.
- double **get_ea_crossover_bias** () const
Get the value of ea_crossover_bias.
- bool **with_ea_crossover_bias** () const
With parameter ea_crossover_bias.
- double **get_ea_crossover_probability** () const
Get the value of ea_crossover_probability.

- bool **with_ea_crossover_probability** () const
With parameter ea_crossover_probability.
- int **get_ea_it_initial_hamming_weight** () const
Get the value of ea_it_initial_hamming_weight.
- bool **with_ea_it_initial_hamming_weight** () const
With parameter ea_it_initial_hamming_weight.
- int **get_ea_it_replacement** () const
Get the value of ea_it_replacement.
- bool **with_ea_it_replacement** () const
With parameter ea_it_replacement.
- int **get_ea_lambda** () const
Get the value of ea_lambda.
- bool **with_ea_lambda** () const
With parameter ea_lambda.
- int **get_ea_mu** () const
Get the value of ea_mu.
- bool **with_ea_mu** () const
With parameter ea_mu.
- double **get_ea_mutation_rate** () const
Get the value of ea_mutation_rate.
- bool **with_ea_mutation_rate** () const
With parameter ea_mutation_rate.
- double **get_ea_mutation_rate_max** () const
Get the value of ea_mutation_rate_max.
- bool **with_ea_mutation_rate_max** () const
With parameter ea_mutation_rate_max.
- double **get_ea_mutation_rate_min** () const
Get the value of ea_mutation_rate_min.
- bool **with_ea_mutation_rate_min** () const
With parameter ea_mutation_rate_min.
- double **get_ea_success_ratio** () const
Get the value of ea_success_ratio.
- bool **with_ea_success_ratio** () const
With parameter ea_success_ratio.
- int **get_ea_tournament_size** () const
Get the value of ea_tournament_size.
- bool **with_ea_tournament_size** () const
With parameter ea_tournament_size.
- double **get_ea_update_strength** () const
Get the value of ea_update_strength.
- bool **with_ea_update_strength** () const
With parameter ea_update_strength.
- std::string **get_expression** () const
Get the value of expression.
- bool **with_expression** () const
With parameter expression.
- std::string **get_fn_name** () const
Get the value of fn_name.
- bool **with_fn_name** () const
With parameter fn_name.
- int **get_fn_num_traps** () const

- Get the value of fn_num_traps.*

 - bool **with_fn_num_traps** () const

With parameter fn_num_traps.
- int **get_fn_prefix_length** () const

Get the value of fn_prefix_length.
- bool **with_fn_prefix_length** () const

With parameter fn_prefix_length.
- int **get_fn_threshold** () const

Get the value of fn_threshold.
- bool **with_fn_threshold** () const

With parameter fn_threshold.
- double **get_fp_default_double_precision** () const

Get the value of fp_default_double_precision.
- bool **with_fp_default_double_precision** () const

With parameter fp_default_double_precision.
- std::string **get_fp_default_double_rep** () const

Get the value of fp_default_double_rep.
- bool **with_fp_default_double_rep** () const

With parameter fp_default_double_rep.
- int **get_fp_default_double_size** () const

Get the value of fp_default_double_size.
- bool **with_fp_default_double_size** () const

With parameter fp_default_double_size.
- std::string **get_fp_default_int_rep** () const

Get the value of fp_default_int_rep.
- bool **with_fp_default_int_rep** () const

With parameter fp_default_int_rep.
- std::string **get_fp_default_long_rep** () const

Get the value of fp_default_long_rep.
- bool **with_fp_default_long_rep** () const

With parameter fp_default_long_rep.
- std::string **get_fp_expression** () const

Get the value of fp_expression.
- bool **with_fp_expression** () const

With parameter fp_expression.
- std::string **get_fp_representations** () const

Get the value of fp_representations.
- bool **with_fp_representations** () const

With parameter fp_representations.
- std::string **get_fp_representations_path** () const

Get the value of fp_representations_path.
- bool **with_fp_representations_path** () const

With parameter fp_representations_path.
- int **get_function** () const

Get the value of function.
- bool **with_function** () const

With parameter function.
- bool **get_he_a_bound_moment** () const

Get the value of hea_bound_moment.
- bool **with_he_a_bound_moment** () const

With parameter hea_bound_moment.

- bool **get_hearandomize_bit_order** () const
Get the value of hearandomize_bit_order.
- bool **with_hearandomize_bit_order** () const
With parameter hearandomize_bit_order.
- int **get_heareset_period** () const
Get the value of heareset_period.
- bool **with_heareset_period** () const
With parameter heareset_period.
- double **get_learning_rate** () const
Get the value of learning_rate.
- bool **with_learning_rate** () const
With parameter learning_rate.
- int **get_map** () const
Get the value of map.
- bool **with_map** () const
With parameter map.
- int **get_map_input_size** () const
Get the value of map_input_size.
- bool **with_map_input_size** () const
With parameter map_input_size.
- std::string **get_map_path** () const
Get the value of map_path.
- bool **with_map_path** () const
With parameter map_path.
- int **get_map_ts_length** () const
Get the value of map_ts_length.
- bool **with_map_ts_length** () const
With parameter map_ts_length.
- int **get_map_ts_sampling_mode** () const
Get the value of map_ts_sampling_mode.
- bool **with_map_ts_sampling_mode** () const
With parameter map_ts_sampling_mode.
- int **get_neighborhood** () const
Get the value of neighborhood.
- bool **with_neighborhood** () const
With parameter neighborhood.
- int **get_neighborhood_iterator** () const
Get the value of neighborhood_iterator.
- bool **with_neighborhood_iterator** () const
With parameter neighborhood_iterator.
- double **get_noise_stddev** () const
Get the value of noise_stddev.
- bool **with_noise_stddev** () const
With parameter noise_stddev.
- int **get_num_iterations** () const
Get the value of num_iterations.
- bool **with_num_iterations** () const
With parameter num_iterations.
- int **get_num_threads** () const
Get the value of num_threads.
- bool **with_num_threads** () const

- With parameter num_threads.*

 - **std::string get_path () const**
Get the value of path.
 - **bool with_path () const**
With parameter path.
 - **double get_pn_mutation_rate () const**
Get the value of pn_mutation_rate.
 - **bool with_pn_mutation_rate () const**
With parameter pn_mutation_rate.
 - **int get_pn_neighborhood () const**
Get the value of pn_neighborhood.
 - **bool with_pn_neighborhood () const**
With parameter pn_neighborhood.
 - **int get_pn_radius () const**
Get the value of pn_radius.
 - **bool with_pn_radius () const**
With parameter pn_radius.
 - **int get_population_size () const**
Get the value of population_size.
 - **bool with_population_size () const**
With parameter population_size.
 - **int get_pv_log_num_components () const**
Get the value of pv_log_num_components.
 - **bool with_pv_log_num_components () const**
With parameter pv_log_num_components.
 - **int get_radius () const**
Get the value of radius.
 - **bool with_radius () const**
With parameter radius.
 - **double get_ram_crossover_probability () const**
Get the value of ram_crossover_probability.
 - **bool with_ram_crossover_probability () const**
With parameter ram_crossover_probability.
 - **double get_ram_latent_space_probability () const**
Get the value of ram_latent_space_probability.
 - **bool with_ram_latent_space_probability () const**
With parameter ram_latent_space_probability.
 - **int get_ram_ts_length () const**
Get the value of ram_ts_length.
 - **bool with_ram_ts_length () const**
With parameter ram_ts_length.
 - **double get_ram_ts_length_distribution_parameter () const**
Get the value of ram_ts_length_distribution_parameter.
 - **bool with_ram_ts_length_distribution_parameter () const**
With parameter ram_ts_length_distribution_parameter.
 - **int get_ram_ts_length_increment_period () const**
Get the value of ram_ts_length_increment_period.
 - **bool with_ram_ts_length_increment_period () const**
With parameter ram_ts_length_increment_period.
 - **int get_ram_ts_length_lower_bound () const**
Get the value of ram_ts_length_lower_bound.

- bool **with_ram_ts_length_lower_bound** () const
With parameter ram_ts_length_lower_bound.
- int **get_ram_ts_length_mode** () const
Get the value of ram_ts_length_mode.
- bool **with_ram_ts_length_mode** () const
With parameter ram_ts_length_mode.
- int **get_ram_ts_length_upper_bound** () const
Get the value of ram_ts_length_upper_bound.
- bool **with_ram_ts_length_upper_bound** () const
With parameter ram_ts_length_upper_bound.
- int **get_rep_categorical_representation** () const
Get the value of rep_categorical_representation.
- bool **with_rep_categorical_representation** () const
With parameter rep_categorical_representation.
- int **get_rep_num_additional_bits** () const
Get the value of rep_num_additional_bits.
- bool **with_rep_num_additional_bits** () const
With parameter rep_num_additional_bits.
- std::string **get_results_path** () const
Get the value of results_path.
- bool **with_results_path** () const
With parameter results_path.
- int **get_rls_patience** () const
Get the value of rls_patience.
- bool **with_rls_patience** () const
With parameter rls_patience.
- double **get_sa_beta_ratio** () const
Get the value of sa_beta_ratio.
- bool **with_sa_beta_ratio** () const
With parameter sa_beta_ratio.
- double **get_sa_initial_acceptance_probability** () const
Get the value of sa_initial_acceptance_probability.
- bool **with_sa_initial_acceptance_probability** () const
With parameter sa_initial_acceptance_probability.
- int **get_sa_num_transitions** () const
Get the value of sa_num_transitions.
- bool **with_sa_num_transitions** () const
With parameter sa_num_transitions.
- int **get_sa_num_trials** () const
Get the value of sa_num_trials.
- bool **with_sa_num_trials** () const
With parameter sa_num_trials.
- unsigned **get_seed** () const
Get the value of seed.
- bool **with_seed** () const
With parameter seed.
- int **get_selection_size** () const
Get the value of selection_size.
- bool **with_selection_size** () const
With parameter selection_size.
- std::string **get_solution_path** () const

- Get the value of solution_path.*

 - bool **with_solution_path** () const
 - With parameter solution_path.*
- double **get_target** () const
 - Get the value of target.*
- bool **with_target** () const
 - With parameter target.*
- bool **with_additive_gaussian_noise** () const
 - With the flag additive_gaussian_noise.*
- bool **with_bm_log_norm_1** () const
 - With the flag bm_log_norm_1.*
- bool **with_bm_log_norm_infinite** () const
 - With the flag bm_log_norm_infinite.*
- bool **with_bm_negative_positive_selection** () const
 - With the flag bm_negative_positive_selection.*
- bool **with_cache** () const
 - With the flag cache.*
- bool **with_cache_budget** () const
 - With the flag cache_budget.*
- bool **with_concrete_solution** () const
 - With the flag concrete_solution.*
- bool **with_ea_allow_no_mutation** () const
 - With the flag ea_allow_no_mutation.*
- bool **with_ea_it_log_center_fitness** () const
 - With the flag ea_it_log_center_fitness.*
- bool **with_ea_log_mutation_rate** () const
 - With the flag ea_log_mutation_rate.*
- bool **with_fn_display** () const
 - With the flag fn_display.*
- bool **with_fn_get_bv_size** () const
 - With the flag fn_get_bv_size.*
- bool **with_fn_get_maximum** () const
 - With the flag fn_get_maximum.*
- bool **with_fn_has_known_maximum** () const
 - With the flag fn_has_known_maximum.*
- bool **with_fn_provides_incremental_evaluation** () const
 - With the flag fn_provides_incremental_evaluation.*
- bool **with_fn_walsh_transform** () const
 - With the flag fn_walsh_transform.*
- bool **with_heal_log_delta_norm** () const
 - With the flag heal_log_delta_norm.*
- bool **with_heal_log_herding_error** () const
 - With the flag heal_log_herding_error.*
- bool **with_heal_log_target** () const
 - With the flag heal_log_target.*
- bool **with_heal_log_target_norm** () const
 - With the flag heal_log_target_norm.*
- bool **with_incremental_evaluation** () const
 - With the flag incremental_evaluation.*
- bool **with_load_solution** () const
 - With the flag load_solution.*

- bool **with_log_improvement** () const
With the flag log_improvement.
- bool **with_map_display** () const
With the flag map_display.
- bool **with_map_random** () const
With the flag map_random.
- bool **with_map_surjective** () const
With the flag map_surjective.
- bool **with_minimize** () const
With the flag minimize.
- bool **with_mmas_strict** () const
With the flag mmas_strict.
- bool **with_parsed_modifier** () const
With the flag parsed_modifier.
- bool **with_pn_allow_no_mutation** () const
With the flag pn_allow_no_mutation.
- bool **with_print_default_parameters** () const
With the flag print_default_parameters.
- bool **with_print_description** () const
With the flag print_description.
- bool **with_print_parameters** () const
With the flag print_parameters.
- bool **with_print_results** () const
With the flag print_results.
- bool **with_print_solution** () const
With the flag print_solution.
- bool **with_prior_noise** () const
With the flag prior_noise.
- bool **with_pv_log_entropy** () const
With the flag pv_log_entropy.
- bool **with_pv_log_pv** () const
With the flag pv_log_pv.
- bool **with_record_evaluation_time** () const
With the flag record_evaluation_time.
- bool **with_record_total_time** () const
With the flag record_total_time.
- bool **with_restart** () const
With the flag restart.
- bool **with_rls_strict** () const
With the flag rls_strict.
- bool **with_rw_log_value** () const
With the flag rw_log_value.
- bool **with_save_description** () const
With the flag save_description.
- bool **with_save_results** () const
With the flag save_results.
- bool **with_save_solution** () const
With the flag save_solution.
- bool **with_stop_on_maximum** () const
With the flag stop_on_maximum.

Private Member Functions

- void **print_help** (std::ostream &stream) const
Print help message.
- void **print_help_fn** (std::ostream &stream) const
Print help message for section fn.
- void **print_help_fp** (std::ostream &stream) const
Print help message for section fp.
- void **print_help_rep** (std::ostream &stream) const
Print help message for section rep.
- void **print_help_mod** (std::ostream &stream) const
Print help message for section mod.
- void **print_help_ctrl** (std::ostream &stream) const
Print help message for section ctrl.
- void **print_help_pn** (std::ostream &stream) const
Print help message for section pn.
- void **print_help_map** (std::ostream &stream) const
Print help message for section map.
- void **print_help_alg** (std::ostream &stream) const
Print help message for section alg.
- void **print_help_ls** (std::ostream &stream) const
Print help message for section ls.
- void **print_help_sa** (std::ostream &stream) const
Print help message for section sa.
- void **print_help_ea** (std::ostream &stream) const
Print help message for section ea.
- void **print_help_eda** (std::ostream &stream) const
Print help message for section eda.
- void **print_help_he** (std::ostream &stream) const
Print help message for section hea.
- void **print_help_bm** (std::ostream &stream) const
Print help message for section bm.
- void **print_version** (std::ostream &stream) const
Print version.

Private Attributes

- std::string **_exec_name**
Name of the executable.
- std::string **_version** = "0.26"
Name Version.
- int **_algorithm** = 100
Type of algorithm.
- int **_bm_num_gs_cycles** = 1
Number of Gibbs sampler cycles per bit vector.
- int **_bm_num_gs_steps** = 100
Number of Gibbs sampler steps per bit vector.
- int **_bm_reset_mode** = 1
Markov chain reset mode.
- int **_bm_sampling_mode** = 1

- Sampling mode for the Boltzmann machine.*

 - `int _budget = 10000`
Number of allowed function evaluations (≤ 0 means indefinite)
 - `int _bv_size = 100`
Size of bit vectors.
 - `std::string _description_path = "description.txt"`
Path of the description file.
 - `double _ea_crossover_bias = 0.5`
Crossover bias.
 - `double _ea_crossover_probability = 0.5`
Crossover probability.
 - `int _ea_it_initial_hamming_weight = 0`
Initial Hamming weight.
 - `int _ea_it_replacement = 0`
Selection for replacement in it-EA.
 - `int _ea_lambda = 100`
Offspring population size.
 - `int _ea_mu = 10`
Parent population size.
 - `double _ea_mutation_rate`
Mutation rate (fixed or initial value)
 - `double _ea_mutation_rate_max = 0.5`
Maximum mutation rate.
 - `double _ea_mutation_rate_min`
Minimum mutation rate.
 - `double _ea_success_ratio = 4`
Success rate for for self-adjusting mutation rate.
 - `int _ea_tournament_size = 2`
Tournament size.
 - `double _ea_update_strength = 1.01`
Update strength for self-adjusting mutation rate.
 - `std::string _expression = "x"`
Expression of the variable x.
 - `std::string _fn_name`
Name of the function in the dynamic library.
 - `int _fn_num_traps = 10`
Number of traps.
 - `int _fn_prefix_length = 2`
Prefix length for long path.
 - `int _fn_threshold = 10`
Threshold (in bits) for Jump, Four Peaks, and Six Peaks.
 - `double _fp_default_double_precision`
Default precision of double representations.
 - `std::string _fp_default_double_rep = "double(0, 1, precision = 1e-3)"`
Default representation for double.
 - `int _fp_default_double_size`
Default size of double representations.
 - `std::string _fp_default_int_rep = "int(-10, 10)"`
Default representation for int.
 - `std::string _fp_default_long_rep = "long(-100, 100)"`
Default representation for long.

- **std::string _fp_expression**
Mathematical expression.
- **std::string _fp_representations**
Representations. Example: "x: double(0, 1); y: double(0, 1, precision = 1e-3); z: double(0, 1, size = 8); u: int(-10, 10); v: long(-100, 100); w: set(1.1, 2.2, 3.3)".
- **std::string _fp_representations_path** = "representations.txt"
Path of the representations file.
- **int _function** = 0
Type of function.
- **bool _hea_bound_moment** = true
Bound moment after update.
- **bool _hea_randomize_bit_order** = true
Randomize bit order.
- **int _hea_reset_period** = 0
Reset period (<= 0 means no reset)
- **double _learning_rate** = 0.001
Learning rate.
- **int _map** = 0
Type of map.
- **int _map_input_size** = 100
Input size of linear and affine maps.
- **std::string _map_path** = "map.txt"
Path of the map file.
- **int _map_ts_length** = 10
Transvection sequence length.
- **int _map_ts_sampling_mode** = 0
Transvection sequence sampling mode.
- **int _neighborhood** = 0
Type of neighborhood.
- **int _neighborhood_iterator** = 0
Type of neighborhood iterator.
- **double _noise_stddev** = 1
Noise standard deviation.
- **int _num_iterations** = 0
Number of iterations (<= 0 means indefinite)
- **int _num_threads** = 1
Number of threads.
- **std::string _path** = "function.txt"
Path of the function file.
- **double _pn_mutation_rate**
Mutation rate.
- **int _pn_neighborhood** = 0
Type of neighborhood.
- **int _pn_radius** = 2
Radius of Hamming ball or sphere.
- **int _population_size** = 10
Population size.
- **int _pv_log_num_components** = 5
Number of probability vector components to log.
- **int _radius** = 2
Radius of Hamming ball or sphere.

- double **_ram_crossover_probability** = 0.1
Crossover probability (RamUmda2)
- double **_ram_latent_space_probability** = 0.5
Probability of sampling from the latent space (RamUmda2)
- int **_ram_ts_length** = 10
Transvection sequence length.
- double **_ram_ts_length_distribution_parameter** = 0.1
Parameter of the geometric distribution of the transvection sequence length.
- int **_ram_ts_length_increment_period** = 10000
Transvection sequence length increment (or decrement) period.
- int **_ram_ts_length_lower_bound** = 0
Lower bound for the transvection sequence length.
- int **_ram_ts_length_mode** = 0
Transvection sequence length mode.
- int **_ram_ts_length_upper_bound** = 20
Upper bound for the transvection sequence length.
- int **_rep_categorical_representation** = 0
Categorical representation.
- int **_rep_num_additional_bits** = 2
Number of additional bits per element for permutation representation.
- std::string **_results_path** = "results.json"
Path of the results file.
- int **_rls_patience** = 50
Number of consecutive rejected moves before ending the search (≤ 0 means infinite)
- double **_sa_beta_ratio** = 1.2
Ratio for beta or inverse temperature.
- double **_sa_initial_acceptance_probability** = 0.6
Initial acceptance probability.
- int **_sa_num_transitions** = 50
Number of accepted transitions before annealing.
- int **_sa_num_trials** = 100
Number of trials to estimate initial inverse temperature.
- unsigned **_seed**
Seed for the random number generator.
- int **_selection_size** = 1
Selection size (number of selected individuals)
- std::string **_solution_path** = "solution.txt"
Path of the solution file.
- double **_target**
Set a target.
- bool **_additive_gaussian_noise** = false
Additive Gaussian noise.
- bool **_bm_log_norm_1** = false
Log 1-norm of the parameters.
- bool **_bm_log_norm_infinite** = false
Log infinite norm of the parameters.
- bool **_bm_negative_positive_selection** = false
Negative and positive selection.
- bool **_cache** = false
Cache function evaluations.
- bool **_cache_budget** = false

- Set cache on budget.*

 - `bool _concrete_solution = false`

Print or save the solution in the domain of the concrete function.
- `bool _ea_allow_no_mutation = false`

Allow no mutation with standard bit mutation.
- `bool _ea_it_log_center_fitness = false`

Log center fitness.
- `bool _ea_log_mutation_rate = false`

Log mutation rate.
- `bool _fn_display = false`

Display the function and exit.
- `bool _fn_get_bv_size = false`

Print the size of bit vectors.
- `bool _fn_get_maximum = false`

If the maximum is known then print it and exit with status 0 else exit with status 1.
- `bool _fn_has_known_maximum = false`

Check whether the function has a known maximum.
- `bool _fn_provides_incremental_evaluation = false`

Check whether the function provides incremental evaluation.
- `bool _fn_walsh_transform = false`

Compute the Walsh transform of the function.
- `bool _hea_log_delta_norm = false`

Log delta (moment increment) 2-norm.
- `bool _hea_log_herding_error = false`

Log herding error (moment discrepancy)
- `bool _hea_log_target = false`

Log target moment as a full matrix.
- `bool _hea_log_target_norm = false`

Log target 2-norm (distance to uniform moment)
- `bool _incremental_evaluation = false`

Incremental evaluation.
- `bool _load_solution = false`

Load a solution from a file.
- `bool _log_improvement = false`

Log improvement.
- `bool _map_display = false`

Display the map and exit.
- `bool _map_random = false`

Sample a random map.
- `bool _map_surjective = false`

Ensure that the sampled linear or affine map is surjective.
- `bool _minimize = false`

Minimize, instead of maximize, the function (implemented as the negation of the provided function)
- `bool _mmas_strict = false`

Strict (>) max-min ant system.
- `bool _parsed_modifier = false`

Parsed modifier.
- `bool _pn_allow_no_mutation = false`

Allow no mutation with standard bit mutation.
- `bool _print_default_parameters = false`

Print the default parameters and exit.

- bool **_print_description** = false
Print a description of the solution.
- bool **_print_parameters** = false
Print the parameters.
- bool **_print_results** = false
Print results.
- bool **_print_solution** = false
Print the solution.
- bool **_prior_noise** = false
Prior noise.
- bool **_pv_log_entropy** = false
Log entropy of probability vector.
- bool **_pv_log_pv** = false
Log probability vector.
- bool **_record_evaluation_time** = false
Record evaluation time.
- bool **_record_total_time** = false
Record total time.
- bool **_restart** = false
Restart any algorithm an indefinite number of times.
- bool **_rls_strict** = false
Strict (>) random local search.
- bool **_rw_log_value** = false
Log bit vector value during random walk.
- bool **_save_description** = false
Save the description of the solution in a file.
- bool **_save_results** = false
Save the results in a file.
- bool **_save_solution** = false
Save the solution in a file.
- bool **_stop_on_maximum** = false
Stop on maximum.

Friends

- std::ostream & **operator<<** (std::ostream &, const [HncoOptions](#) &)
Print a header containing the parameter values.

5.61.1 Detailed Description

Command line options for hnco.

Definition at line 11 of file [hnco-options.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/app/hnco-options.hh
- lib/hnco/app/hnco-options.cc

5.62 HncoOptions Class Reference

Command line options for hnco-mo.

```
#include <hnco/multiobjective/app/hnco-mo-options.hh>
```

Public Member Functions

- **HncoOptions** ()
Default constructor.
- **HncoOptions** (int argc, char *argv[], bool ignore_bad_options=false)
Constructor.
- int **get_algorithm** () const
Get the value of algorithm.
- bool **with_algorithm** () const
With parameter algorithm.
- int **get_bv_size** () const
Get the value of bv_size.
- bool **with_bv_size** () const
With parameter bv_size.
- double **get_ea_crossover_probability** () const
Get the value of ea_crossover_probability.
- bool **with_ea_crossover_probability** () const
With parameter ea_crossover_probability.
- int **get_ea_mu** () const
Get the value of ea_mu.
- bool **with_ea_mu** () const
With parameter ea_mu.
- double **get_ea_mutation_rate** () const
Get the value of ea_mutation_rate.
- bool **with_ea_mutation_rate** () const
With parameter ea_mutation_rate.
- int **get_ea_tournament_size** () const
Get the value of ea_tournament_size.
- bool **with_ea_tournament_size** () const
With parameter ea_tournament_size.
- std::string **get_fn_name** () const
Get the value of fn_name.
- bool **with_fn_name** () const
With parameter fn_name.
- double **get_fp_default_double_precision** () const
Get the value of fp_default_double_precision.
- bool **with_fp_default_double_precision** () const
With parameter fp_default_double_precision.
- std::string **get_fp_default_double_rep** () const
Get the value of fp_default_double_rep.
- bool **with_fp_default_double_rep** () const
With parameter fp_default_double_rep.
- int **get_fp_default_double_size** () const
Get the value of fp_default_double_size.

- bool **with_fp_default_double_size** () const
With parameter fp_default_double_size.
- std::string **get_fp_default_int_rep** () const
Get the value of fp_default_int_rep.
- bool **with_fp_default_int_rep** () const
With parameter fp_default_int_rep.
- std::string **get_fp_default_long_rep** () const
Get the value of fp_default_long_rep.
- bool **with_fp_default_long_rep** () const
With parameter fp_default_long_rep.
- std::string **get_fp_expression** () const
Get the value of fp_expression.
- bool **with_fp_expression** () const
With parameter fp_expression.
- std::string **get_fp_representations** () const
Get the value of fp_representations.
- bool **with_fp_representations** () const
With parameter fp_representations.
- std::string **get_fp_representations_path** () const
Get the value of fp_representations_path.
- bool **with_fp_representations_path** () const
With parameter fp_representations_path.
- int **get_function** () const
Get the value of function.
- bool **with_function** () const
With parameter function.
- int **get_num_iterations** () const
Get the value of num_iterations.
- bool **with_num_iterations** () const
With parameter num_iterations.
- int **get_num_threads** () const
Get the value of num_threads.
- bool **with_num_threads** () const
With parameter num_threads.
- std::string **get_path** () const
Get the value of path.
- bool **with_path** () const
With parameter path.
- int **get_rep_categorical_representation** () const
Get the value of rep_categorical_representation.
- bool **with_rep_categorical_representation** () const
With parameter rep_categorical_representation.
- int **get_rep_num_additional_bits** () const
Get the value of rep_num_additional_bits.
- bool **with_rep_num_additional_bits** () const
With parameter rep_num_additional_bits.
- unsigned **get_seed** () const
Get the value of seed.
- bool **with_seed** () const
With parameter seed.
- bool **with_ea_allow_no_mutation** () const

- *With the flag `ea_allow_no_mutation`.*
- bool **with_fn_display** () const
- *With the flag `fn_display`.*
- bool **with_fn_get_bv_size** () const
- *With the flag `fn_get_bv_size`.*
- bool **with_fn_get_output_size** () const
- *With the flag `fn_get_output_size`.*
- bool **with_print_default_parameters** () const
- *With the flag `print_default_parameters`.*
- bool **with_print_description** () const
- *With the flag `print_description`.*
- bool **with_print_parameters** () const
- *With the flag `print_parameters`.*
- bool **with_print_pareto_front** () const
- *With the flag `print_pareto_front`.*

Private Member Functions

- void **print_help** (std::ostream &stream) const
- *Print help message.*
- void **print_help_fn** (std::ostream &stream) const
- *Print help message for section `fn`.*
- void **print_help_fp** (std::ostream &stream) const
- *Print help message for section `fp`.*
- void **print_help_rep** (std::ostream &stream) const
- *Print help message for section `rep`.*
- void **print_help_alg** (std::ostream &stream) const
- *Print help message for section `alg`.*
- void **print_help_ea** (std::ostream &stream) const
- *Print help message for section `ea`.*
- void **print_version** (std::ostream &stream) const
- *Print version.*

Private Attributes

- std::string **_exec_name**
- *Name of the executable.*
- std::string **_version** = "0.26"
- *Name Version.*
- int **_algorithm** = 100
- *Type of algorithm.*
- int **_bv_size** = 100
- *Size of bit vectors.*
- double **_ea_crossover_probability** = 0.8
- *Crossover probability.*
- int **_ea_mu** = 100
- *Parent population size.*
- double **_ea_mutation_rate**
- *Mutation rate.*
- int **_ea_tournament_size** = 2

- Tournament size.*

 - **std::string _fn_name**
Name of the function in the dynamic library.
 - **double _fp_default_double_precision**
Default precision of double representations.
 - **std::string _fp_default_double_rep = "double(0, 1, precision = 1e-3)"**
Default representation for double.
 - **int _fp_default_double_size**
Default size of double representations.
 - **std::string _fp_default_int_rep = "int(-10, 10)"**
Default representation for int.
 - **std::string _fp_default_long_rep = "long(-100, 100)"**
Default representation for long.
 - **std::string _fp_expression**
Mathematical expression (list of objectives separated by ::)
 - **std::string _fp_representations**
Representations. Example: "x: double(0, 1); y: double(0, 1, precision = 1e-3); z: double(0, 1, size = 8); u: int(-10, 10); v: long(-100, 100); w: set(1.1, 2.2, 3.3)".
 - **std::string _fp_representations_path = "representations.txt"**
Path of the representations file.
 - **int _function = 180**
Type of function.
 - **int _num_iterations = 100**
Number of iterations.
 - **int _num_threads = 1**
Number of threads.
 - **std::string _path = "function.txt"**
Path of a function file.
 - **int _rep_categorical_representation = 0**
Categorical representation.
 - **int _rep_num_additional_bits = 2**
Number of additional bits per element for permutation representation.
 - **unsigned _seed**
Seed for the random number generator.
 - **bool _ea_allow_no_mutation = false**
Allow no mutation with standard bit mutation.
 - **bool _fn_display = false**
Display the function and exit.
 - **bool _fn_get_bv_size = false**
Print the size of bit vectors.
 - **bool _fn_get_output_size = false**
Print the number of objectives.
 - **bool _print_default_parameters = false**
Print the parameters and exit.
 - **bool _print_description = false**
Print a description of the solution.
 - **bool _print_parameters = false**
Print the parameters.
 - **bool _print_pareto_front = false**
Print the Pareto front.

Friends

- `std::ostream & operator<< (std::ostream &, const HncoOptions &)`
Print a header containing the parameter values.

5.62.1 Detailed Description

Command line options for hnco-mo.

Definition at line 12 of file [hnco-mo-options.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/multiobjective/app/hnco-mo-options.hh`
- `lib/hnco/multiobjective/app/hnco-mo-options.cc`

5.63 Human Class Reference

Human

```
#include <hnco/algorithms/human.hh>
```

Inheritance diagram for Human:



Public Member Functions

- **Human** (int n)
Constructor.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & [get_solution](#) ()
Get the solution.

Protected Member Functions

- void [parse_bit_vector](#) ()
Parse bit vector.

Loop

- void [init](#) () override
Initialize.
- void [iterate](#) () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [log](#) ()
Log.
- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [bit_vector_t](#) **_candidate**
Candidate.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.63.1 Detailed Description

Human

Definition at line 32 of file [human.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/human.hh](#)
- [lib/hnco/algorithms/human.cc](#)

5.64 Hypercubeliterator Class Reference

Hypercube iterator.

```
#include <hnco/iterator.hh>
```

Inheritance diagram for Hypercubeliterator:



Public Member Functions

- **Hypercubeliterator** (int n)
Constructor.
- bool **has_next** () override
Has next bit vector.
- const [bit_vector_t](#) & **next** () override
Next bit vector.

Public Member Functions inherited from [Iterator](#)

- **Iterator** (int n)
Constructor.
- virtual ~**Iterator** ()
Destructor.
- virtual void **init** ()
Initialization.

Additional Inherited Members

Protected Attributes inherited from [Iterator](#)

- [bit_vector_t](#) **_current**
Current bit vector.
- bool **_initial_state** = true
Flag for initial state.

5.64.1 Detailed Description

Hypercube iterator.

Implemented as a simple binary adder.

Definition at line 69 of file [iterator.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/iterator.hh
- lib/hnco/iterator.cc

5.65 Implementation Struct Reference

Implementation

```
#include <hnco/algorithms/fast-efficient-p3/implementation.hh>
```

Public Attributes

- Configuration **configuration**
Configuration.
- std::shared_ptr< [HncoEvaluator](#) > **evaluator**
Evaluator.
- std::shared_ptr< Middle_Layer > **middle_layer**
Middle layer.

5.65.1 Detailed Description

Implementation

Definition at line 37 of file [implementation.hh](#).

The documentation for this struct was generated from the following file:


- lib/hnco/algorithms/fast-efficient-p3/implementation.hh

5.66 InformationTheoreticEa Class Reference

Information-theoretic evolutionary algorithm.

```
#include <hnco/algorithms/evolutionary-algorithms/it-ea.hh>
```

Inheritance diagram for InformationTheoreticEa:



Classes

- struct [Replacement](#)
Selection for replacement.

Public Member Functions

- **InformationTheoreticEa** (int n, int population_size)
Constructor.

Setters

- void [set_selection_size](#) (int n)
- void **set_learning_rate** (double rate)
Set the learning rate.
- void **set_mutation_rate_init** (double rate)
Set the initial mutation rate.
- void **set_mutation_rate_min** (double rate)
Set the minimum mutation rate.
- void **set_mutation_rate_max** (double rate)
Set the maximum mutation rate.
- void **set_replacement** (int replacement)
Set replacement.
- void **set_initial_hamming_weight** (int n)
Set the initial Hamming weight.
- void **set_allow_no_mutation** (bool b)
Allow no mutation.

Setters for logging

- void [set_log_mutation_rate](#) (bool b)
- void **set_log_center_fitness** (bool b)
Log center fitness.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual ~**Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **set_something_to_log** ()
Set flag for something to log.
- void **compute_masks** (bool equivalent_individuals, std::pair< int, int > range, double c)
Compute masks.
- void **ml_update** (bool equivalent_individuals, std::pair< int, int > range, double c)
ML update.
- void **incremental_ml_update** (bool equivalent_individuals, std::pair< int, int > range, double c)
Incremental ML update.
- void **igo_update** (bool equivalent_individuals, std::pair< int, int > range, double c)
IGO update.

Loop

- void [init](#) () override
- void **iterate** () override
Single iteration.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void [set_solution](#) (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void [update_solution](#) (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population
- std::vector< [bit_vector_t](#) > **_masks**
Mutation masks.
- std::vector< double > **_likelihoods**
Mutation likelihoods.
- [neighborhood::StandardBitMutation](#) **_mutation_operator**
Mutation operator.
- [solution_t](#) **_center**
Center of the search distribution.
- double **_mutation_rate**
Mutation rate.

Parameters

- int [_selection_size](#) = 1
- double **_learning_rate** = 0.01
Learning rate.
- double **_mutation_rate_init**
Initial mutation rate.
- double **_mutation_rate_min**
Minimum mutation rate.
- double **_mutation_rate_max** = 0.5
Maximum mutation rate.
- int **_initial_hamming_weight** = 0
Initial Hamming weight.

- `int _replacement = Replacement::elitist`
Replacement.
- `bool _allow_no_mutation = false`
Allow no mutation.

Logging

- `bool _log_mutation_rate = false`
- `bool _log_center_fitness = false`
Log center fitness.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.66.1 Detailed Description

Information-theoretic evolutionary algorithm.

Definition at line 16 of file [it-ea.hh](#).

5.66.2 Member Function Documentation

5.66.2.1 `init()`

```
void init ( ) [override], [protected], [virtual]
```

Initialization

Reimplemented from [IterativeAlgorithm](#).

Definition at line 34 of file [it-ea.cc](#).

5.66.2.2 set_log_mutation_rate()

```
void set_log_mutation_rate (
    bool b ) [inline]
```

Log mutation rate

Definition at line 77 of file [it-ea.hh](#).

5.66.2.3 set_selection_size()

```
void set_selection_size (
    int n ) [inline]
```

Set the selection size

Definition at line 51 of file [it-ea.hh](#).

5.66.3 Member Data Documentation

5.66.3.1 _log_mutation_rate

```
bool _log_mutation_rate = false [protected]
```

Log entropy

Definition at line 123 of file [it-ea.hh](#).

5.66.3.2 _selection_size

```
int _selection_size = 1 [protected]
```

Selection size

Definition at line 101 of file [it-ea.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/it-ea.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/it-ea.cc](#)

5.67 Injection Class Reference

Injection.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for Injection:



Public Member Functions

- [Injection](#) (const std::vector< int > &bit_positions, int output_size)
Constructor.
- void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool **is_surjective** () const override
Check for surjective map.

Public Member Functions inherited from [Map](#)

- virtual ~**Map** ()
Destructor.
- virtual void **display** (std::ostream &stream) const
Display.

Private Attributes

- std::vector< int > **_bit_positions**
Bit positions.
- int **_output_size**
Output size.

5.67.1 Detailed Description

Injection.

An injection copies the bits of input x to given positions of output y .

Let $I = \{i_1, i_2, \dots, i_m\}$ be a subset of $\{1, 2, \dots, n\}$.

An injection f from F_2^m to F_2^n , where $n \geq m$, is defined by $f(x) = y$, where, for all $j \in \{1, 2, \dots, m\}$, $y_{i_j} = x_j$.

If f is a projection and g is an injection with the same bit positions then their composition $f \circ g$ is the identity.

Definition at line 492 of file [map.hh](#).

5.67.2 Constructor & Destructor Documentation

5.67.2.1 Injection()

```
Injection (
    const std::vector< int > & bit_positions,
    int output_size )
```

Constructor.

The input size of the map is given by the size of `bit_positions`.

Parameters

<i>bit_positions</i>	Bit positions in the output to where input bits are copied
<i>output_size</i>	Output size

Precondition

```
output_size >= bit_positions.size()
```

Definition at line 157 of file [map.cc](#).

The documentation for this class was generated from the following files:

- `lib/hnco/maps/map.hh`
- `lib/hnco/maps/map.cc`

5.68 IntegerCategoricalRepresentation Class Reference

Integer categorical representation.

```
#include <hnco/representations/categorical.hh>
```

Public Types

- using **domain_type** = std::size_t
Domain type.

Public Member Functions

- [IntegerCategoricalRepresentation](#) (int num_categories)
Constructor.
- int **size** () const
Size of the representation.
- [domain_type](#) **unpack** (const [bit_vector_t](#) &bv, int start)
Unpack bit vector into a category.
- void **display** (std::ostream &stream) const
Display.

Private Attributes

- int **_num_categories**
Number of categories.
- int **_size**
Size in bits.

5.68.1 Detailed Description

Integer categorical representation.

Definition at line 142 of file [categorical.hh](#).

5.68.2 Constructor & Destructor Documentation

5.68.2.1 IntegerCategoricalRepresentation()

```
IntegerCategoricalRepresentation (
    int num_categories ) [inline]
```

Constructor.

Parameters

<i>num_categories</i>	Number of categories
-----------------------	----------------------

Definition at line 160 of file [categorical.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/representations/categorical.hh

5.69 IterativeAlgorithm Class Reference

Iterative search.

```
#include <hnco/algorithms/iterative-algorithm.hh>
```

Inheritance diagram for IterativeAlgorithm:



Public Member Functions

- [IterativeAlgorithm](#) (int n)
Constructor.

Optimization

- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.

Setters

- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- virtual void **init** ()
Initialize.
- virtual void **iterate** ()=0
Single iteration.
- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.

Parameters

- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.69.1 Detailed Description

Iterative search.

Definition at line 32 of file [iterative-algorithm.hh](#).

5.69.2 Constructor & Destructor Documentation

5.69.2.1 IterativeAlgorithm()

```
IterativeAlgorithm (
    int n ) [inline]
```

Constructor.

Parameters

<code>n</code>	Size of bit vectors
----------------	---------------------

Definition at line 83 of file [iterative-algorithm.hh](#).

5.69.3 Member Function Documentation

5.69.3.1 loop()

```
void loop ( ) [final], [protected], [virtual]
```

Loop.

Calls [init\(\)](#) then enter the main loop which, at each iteration, calls [iterate\(\)](#) then [log\(\)](#) only if `_something_to_log` is true.

Definition at line 28 of file [iterative-algorithm.cc](#).

5.69.3.2 maximize()

```
void maximize (
    const std::vector< function::Function * > & functions ) [override], [virtual]
```

Maximize.

Calls [set_functions\(\)](#) then loop.

Implements [Algorithm](#).

Definition at line 53 of file [iterative-algorithm.cc](#).

5.69.3.3 set_num_iterations()

```
void set_num_iterations (
    int n ) [inline]
```

Set the number of iterations.

Parameters

<i>n</i>	Number of iterations
----------	----------------------

Warning

`n <= 0` means indefinite

Definition at line 110 of file [iterative-algorithm.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/iterative-algorithm.hh](#)
- [lib/hnco/algorithms/iterative-algorithm.cc](#)

5.70 IterativeAlgorithm Class Reference

Iterative algorithm.

```
#include <hnco/multiobjective/algorithms/iterative-algorithm.hh>
```

Inheritance diagram for IterativeAlgorithm:



Public Member Functions

- [IterativeAlgorithm](#) (int n, int num_objectives)
Constructor.

Optimization

- void [minimize](#) (const std::vector< [Function](#) * > &functions) override
Minimize.

Setters

- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- [Algorithm](#) (int n, int num_objectives)
Constructor.
- virtual \sim [Algorithm](#) ()
Destructor.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [Population](#) & [get_solutions](#) ()=0
Get solutions.

Protected Member Functions

Loop

- virtual void **init** ()
Initialize.
- virtual void **iterate** ()=0
Single iteration.
- virtual void **log** ()
Log.
- virtual void **finalize** ()
Finalize.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [Function](#) * > &functions)
Set functions.

Protected Attributes

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.

Parameters

- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [Function](#) * > **_functions**
Functions.
- [Function](#) * **_function**
Function.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

Additional Inherited Members

Public Types inherited from [Algorithm](#)

- using **Function** = [hnco::multiobjective::function::Function](#)
Function type.

5.70.1 Detailed Description

Iterative algorithm.

Definition at line 33 of file [iterative-algorithm.hh](#).

5.70.2 Constructor & Destructor Documentation

5.70.2.1 IterativeAlgorithm()

```
IterativeAlgorithm (
    int n,
    int num_objectives ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>num_objectives</i>	Number of objectives

Definition at line 87 of file [iterative-algorithm.hh](#).

5.70.3 Member Function Documentation

5.70.3.1 loop()

```
void loop ( ) [final], [protected], [virtual]
```

Loop.

Calls [init\(\)](#) then enter the main loop which, at each iteration, calls [iterate\(\)](#) then [log\(\)](#) only if `_something_to_log` is true.

Definition at line 28 of file [iterative-algorithm.cc](#).

5.70.3.2 minimize()

```
void minimize (
    const std::vector< Function * > & functions ) [override], [virtual]
```

Minimize.

Calls [set_functions\(\)](#) then loop.

Implements [Algorithm](#).

Definition at line 43 of file [iterative-algorithm.cc](#).

5.70.3.3 set_num_iterations()

```
void set_num_iterations (
    int n ) [inline]
```

Set the number of iterations.

Parameters

n	Number of iterations
-----	----------------------

Warning

$n \leq 0$ means indefinite

Definition at line 113 of file [iterative-algorithm.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/multiobjective/algorithms/iterative-algorithm.hh](#)
- [lib/hnco/multiobjective/algorithms/iterative-algorithm.cc](#)

5.71 Iterator Class Reference

Iterator over bit vectors

```
#include <hnco/iterator.hh>
```

Inheritance diagram for Iterator:



Public Member Functions

- **Iterator** (int n)
Constructor.
- virtual **~Iterator** ()
Destructor.
- virtual void **init** ()
Initialization.
- virtual bool **has_next** ()=0
Has next bit vector.
- virtual const **bit_vector_t** & **next** ()=0
Next bit vector.

Protected Attributes

- `bit_vector_t _current`
Current bit vector.
- `bool _initial_state = true`
Flag for initial state.

5.71.1 Detailed Description

Iterator over bit vectors

Definition at line 34 of file [iterator.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/iterator.hh`

5.72 Jump Class Reference

Jump.

```
#include <hnco/functions/collection/jump.hh>
```

Inheritance diagram for Jump:

**Public Member Functions**

- **Jump** (int bv_size, int gap)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.
- double **evaluate** (const `bit_vector_t` &) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function()`
Destructor.
- virtual bool `provides_incremental_evaluation()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void `update` (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void `display` (std::ostream &stream) const
Display.
- virtual void `describe` (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int `_bv_size`
Bit vector size.
- int `_gap`
Gap.

5.72.1 Detailed Description

Jump.

Reference:

H. Mühlenbein and T. Mahnig. 2001. Evolutionary Algorithms: From Recombination to Search Distributions. In Theoretical Aspects of Evolutionary Computing, Leila Kallel, Bart Naudts, and Alex Rogers (Eds.). Springer Berlin Heidelberg, 135–174.

Definition at line 41 of file [jump.hh](#).

5.72.2 Member Function Documentation

5.72.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 64 of file [jump.hh](#).

5.72.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 60 of file [jump.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/jump.hh
- lib/hnco/functions/collection/jump.cc

5.73 Labs Class Reference

Low autocorrelation binary sequences.

```
#include <hnco/functions/collection/labs.hh>
```

Inheritance diagram for Labs:



Public Member Functions

- **Labs** (int n)
Constructor.
- void **set_merit_factor_flag** (bool b)
Set merit factor flag.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `display` (std::ostream &stream) const
Display.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Protected Member Functions

- double `compute_autocorrelation` (const `bit_vector_t` &)
Compute autocorrelation.

Protected Attributes

- std::vector< int > `_sequence`
Binary sequence written using 1 and -1.
- bool `_merit_factor_flag` = false
Merit factor flag.

5.73.1 Detailed Description

Low autocorrelation binary sequences.

Reference:

S Mertens. 1996. Exhaustive search for low-autocorrelation binary sequences. Journal of Physics A: Mathematical and General 29, 18 (1996), L473.

<http://stacks.iop.org/0305-4470/29/i=18/a=005>

If `_merit_factor_flag` is true then the function returns $n / (2 * \text{autocorrelation})$ else it returns $-\text{autocorrelation}$.

Definition at line 44 of file [labs.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/labs.hh
- lib/hnco/functions/collection/labs.cc

5.74 LastEvaluation Class Reference

Last evaluation.

```
#include <hnco/exception.hh>
```

Inherits `runtime_error`.

5.74.1 Detailed Description

Last evaluation.

Definition at line 33 of file [exception.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/exception.hh`

5.75 LeadingOnes Class Reference

Leading ones.

```
#include <hnco/functions/collection/theory.hh>
```

Inheritance diagram for `LeadingOnes`:



Public Member Functions

- **LeadingOnes** (int bv_size)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual `bool provides_incremental_evaluation () const`
Check whether the function provides incremental evaluation.
- virtual `double evaluate_incrementally (const bit_vector_t &x, double value, const sparse_bit_vector_t &flipped_bits)`
Incrementally evaluate a bit vector.
- virtual `double evaluate_safely (const bit_vector_t &x)`
Safely evaluate a bit vector.
- virtual `void update (const bit_vector_t &x, double value)`
Update states after a safe evaluation.
- virtual `void display (std::ostream &stream) const`
Display.
- virtual `void describe (const bit_vector_t &x, std::ostream &stream)`
Describe a bit vector.

Private Attributes

- `int _bv_size`
Bit vector size.

5.75.1 Detailed Description

Leading ones.

Reference: Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 77 of file [theory.hh](#).

5.75.2 Member Function Documentation

5.75.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 98 of file [theory.hh](#).

5.75.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 93 of file [theory.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/theory.hh
- lib/hnco/functions/collection/theory.cc

5.76 LinearCategoricalRepresentation Class Reference

Linear categorical representation.

```
#include <hnco/representations/categorical.hh>
```

Public Types

- using **domain_type** = std::size_t
Domain type.

Public Member Functions

- [LinearCategoricalRepresentation](#) (int num_categories)
Constructor.
- int **size** () const
Size of the representation.
- **domain_type** **unpack** (const [bit_vector_t](#) &bv, int start)
Unpack bit vector into a category.
- void **display** (std::ostream &stream) const
Display.

Private Attributes

- `int _num_categories`
Number of categories.
- `int _nrows`
Number of rows.
- `int _ncols`
Number of columns.
- `bit_matrix_t _A`
Linear code as a bit matrix.
- `bit_vector_t _y`
Output category.
- `bit_vector_t _x`
Input bit vector.

5.76.1 Detailed Description

Linear categorical representation.

Definition at line 42 of file [categorical.hh](#).

5.76.2 Constructor & Destructor Documentation

5.76.2.1 LinearCategoricalRepresentation()

```
LinearCategoricalRepresentation (
    int num_categories ) [inline]
```

Constructor.

Parameters

<code>num_categories</code>	Number of categories
-----------------------------	----------------------

Definition at line 72 of file [categorical.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/representations/categorical.hh`

5.77 LinearFunction Class Reference

Linear function.

```
#include <hnco/functions/collection/linear-function.hh>
```

Inheritance diagram for LinearFunction:



Public Member Functions

- **LinearFunction** ()

Constructor.

Instance generators

- template<class Generator >
void **generate** (int n, Generator generator)
Instance generator.
- void **random** (int n)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Evaluation

- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- double **evaluate_incrementally** (const [bit_vector_t](#) &x, double v, const [hnco::sparse_bit_vector_t](#) &flipped_bits) override
Incrementally evaluate a bit vector.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.
- double **get_maximum** () const override
Get the global maximum.
- bool **has_known_maximum** () const override
Check for a known maximum.
- bool **provides_incremental_evaluation** () const override
Check whether the function provides incremental evaluation.
- void **display** (std::ostream &stream) const override
Display.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- template<class Archive >
void `serialize` (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- std::vector< double > `_weights`
Weights.

5.77.1 Detailed Description

Linear function.

Definition at line 40 of file [linear-function.hh](#).

5.77.2 Member Function Documentation

5.77.2.1 generate()

```
template<class Generator >
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Weight generator

Definition at line 71 of file [linear-function.hh](#).

5.77.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 136 of file [linear-function.hh](#).

5.77.2.3 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 100 of file [linear-function.hh](#).

5.77.2.4 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) const [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 141 of file [linear-function.hh](#).

5.77.2.5 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 83 of file [linear-function.hh](#).

5.77.2.6 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 107 of file [linear-function.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/linear-function.hh
- lib/hnco/functions/collection/linear-function.cc

5.78 LinearMap Class Reference

Linear map.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for LinearMap:



Public Member Functions

- void **random** (int rows, int cols, bool surjective)
Random instance.
- void **map** (const **bit_vector_t** &input, **bit_vector_t** &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool **is_surjective** () const override
Check for surjective map.

Load and save map

- void **load** (std::string path)
Load map.
- void **save** (std::string path) const
Save map.

Public Member Functions inherited from **Map**

- virtual \sim **Map** ()
Destructor.
- virtual void **display** (std::ostream &stream) const
Display.

Private Member Functions

- template<class Archive >
void **save** (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void **load** (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_matrix_t_bm](#)

Bit matrix.

5.78.1 Detailed Description

Linear map.

A linear map f from F_2^m to F_2^n is defined by $f(x) = Ax$, where A is an $n \times m$ bit matrix.

Definition at line 247 of file [map.hh](#).

5.78.2 Member Function Documentation

5.78.2.1 is_surjective()

```
bool is_surjective ( ) const [override], [virtual]
```

Check for surjective map.

Returns

true if $\text{rank}(_bm) == \text{bm_num_rows}(_bm)$

Reimplemented from [Map](#).

Definition at line 98 of file [map.cc](#).

5.78.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 310 of file [map.hh](#).

5.78.2.3 random()

```
void random (
    int rows,
    int cols,
    bool surjective )
```

Random instance.

Parameters

<i>rows</i>	Number of rows
<i>cols</i>	Number of columns
<i>surjective</i>	Flag to ensure a surjective map

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 71 of file [map.cc](#).

5.78.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 317 of file [map.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/maps/map.hh](#)
- [lib/hnco/maps/map.cc](#)

5.79 LocalSearchAlgorithm< Neighborhood > Class Template Reference

Local search algorithm.

```
#include <hnco/algorithms/local-search/local-search-algorithm.hh>
```

Inheritance diagram for LocalSearchAlgorithm< Neighborhood >:



Public Member Functions

- **LocalSearchAlgorithm** (int n, Neighborhood *neighborhood)
Constructor.

Setters

- void **set_random_initialization** (bool b)
Set random initialization.
- void **set_starting_point** (const [bit_vector_t](#) &x)
Set the starting point.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **iterate** ()=0
Single iteration.
- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [bit_vector_t](#) **_starting_point**
Starting point.
- Neighborhood * **_neighborhood**
Neighborhood.

Parameters

- bool **_random_initialization** = true
Random initialization.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.79.1 Detailed Description

`template<class Neighborhood>`
`class hnco::algorithm::LocalSearchAlgorithm< Neighborhood >`

Local search algorithm.

Definition at line 33 of file [local-search-algorithm.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/local-search/local-search-algorithm.hh`

5.80 LogContext Class Reference

Log context.

```
#include <hnco/logging/log-context.hh>
```

Inheritance diagram for LogContext:



Public Member Functions

- virtual std::string **to_string** ()=0
Convert context to string.

5.80.1 Detailed Description

Log context.

A log context gives an algorithm more information about what is going on during optimization than what can be gained through its function. In particular, its function may not be a function controller. Information is provided through a log context in the form of a string.

Definition at line 38 of file [log-context.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/logging/log-context.hh

5.81 Logger Class Reference

Logger.

```
#include <hnco/logging/logger.hh>
```

Public Member Functions

- **Logger** ()
Default constructor.
- **Logger** ([LogContext](#) *context)
Constructor.
- virtual **~Logger** ()
Destructor.
- template<class T >
Logger & **operator**<< (T value)
Append data to the line.

Private Attributes

- std::ostringstream **_line**
Line.

5.81.1 Detailed Description

Logger.

Simple logger inspired by the Log class published in Dr. Dobb's:

<https://www.drdobbs.com/cpp/logging-in-c/201804215>

Definition at line 41 of file [logger.hh](#).

5.81.2 Constructor & Destructor Documentation

5.81.2.1 Logger()

```
Logger (
    LogContext * context ) [inline]
```

Constructor.

Parameters

<code>context</code>	Log context
----------------------	-------------

Definition at line 51 of file [logger.hh](#).

5.81.2.2 ~Logger()

```
virtual ~Logger ( ) [inline], [virtual]
```

Destructor.

Sends `_line` to `std::cout` and flushes it.

Definition at line 59 of file [logger.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/logging/logger.hh`

5.82 LongPath Class Reference

Long path.

```
#include <hnco/functions/collection/long-path.hh>
```

Inheritance diagram for LongPath:



Public Member Functions

- **LongPath** (int `bv_size`, int `prefix_length`)
Constructor.
- double **evaluate** (const [bit_vector_t](#) &)
Evaluate a bit vector.

Information about the function

- int **get_bv_size** () const
Get bit vector size.
- bool **has_known_maximum** () const
Check for a known maximum.
- double **get_maximum** () const
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual bool `provides_incremental_evaluation () const`
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally (const bit_vector_t &x, double value, const sparse_bit_vector_t &flipped_bits)`
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely (const bit_vector_t &x)`
Safely evaluate a bit vector.
- virtual void `update (const bit_vector_t &x, double value)`
Update states after a safe evaluation.
- virtual void `display (std::ostream &stream) const`
Display.
- virtual void `describe (const bit_vector_t &x, std::ostream &stream)`
Describe a bit vector.

Private Attributes

- int `_bv_size`
Bit vector size.
- int `_prefix_length`
Prefix length.

5.82.1 Detailed Description

Long path.

Long paths have been introduced by Jeffrey Horn, David E. Goldberg, and Kalyanmoy Deb. Here we mostly follow the definition given by Thomas Jansen (see references below).

As an example, here is the 2-long path of dimension 4:

- 0000
- 0001
- 0011
- 0111
- 1111
- 1101
- 1100

The fitness is increasing along the path. The fitness on the complementary of the path is defined as a linear function pointing to the beginning of the path.

To help with the detection of maximum, we have dropped the constant n^2 whose sole purpose was to make the function non negative.

References:

Jeffrey Horn, David E. Goldberg, and Kalyanmoy Deb, "Long Path Problems", PPSN III, 1994.

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 62 of file [long-path.hh](#).

5.82.2 Member Function Documentation

5.82.2.1 `get_maximum()`

```
double get_maximum ( ) const [virtual]
```

Get the global maximum.

Let n be the bit vector size and k the prefix length which must divide n . Then the maximum is $k2^{n/k} - k + 1$.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Reimplemented from [Function](#).

Definition at line 62 of file [long-path.cc](#).

5.82.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [virtual]
```

Check for a known maximum.

Let n be the bit vector size and k the prefix length which must divide n .

We have to check that the maximum can be represented exactly as a double, that is, it must be lower or equal to 2^{53} . We are a little bit more conservative with the following test.

If $\log_2(k) + n/k \leq 53$ then returns true else returns false.

Reimplemented from [Function](#).

Definition at line 52 of file [long-path.cc](#).

The documentation for this class was generated from the following files:


- `lib/hnco/functions/collection/long-path.hh`
- `lib/hnco/functions/collection/long-path.cc`

5.83 Ltga Class Reference

Linkage Tree Genetic Algorithm.

```
#include <hnco/algorithms/fast-efficient-p3/ltga.hh>
```

Inheritance diagram for Ltga:



Public Member Functions

- **Ltga** (int n)
Constructor.
- **~Ltga** ()
Destructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions)
Maximize.
- void **finalize** ()
Finalize.
- void **set_population_size** (int n)
Set population size.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Attributes

- [Implementation](#) * [_implementation](#)
Pointer to implementation.
- int [_population_size](#) = 10
Population size.

Additional Inherited Members**Protected Member Functions inherited from [Algorithm](#)**

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void [set_solution](#) (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void [update_solution](#) (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > [_functions](#)
Functions.
- [function::Function](#) * [_function](#)
Function.
- [solution_t](#) [_solution](#)
Solution.
- [logging::LogContext](#) * [_log_context](#) = nullptr
Log context.

5.83.1 Detailed Description

Linkage Tree Genetic Algorithm.

Implementation of the Linkage Tree Genetic Algorithm.

Author: Brian W. Goldman

Integrated into HNCO by Arnaud Berny

Reference:

"Hierarchical problem solving with the linkage tree genetic algorithm" by D. Thierens and P. A. N. Bosman

Definition at line 48 of file [ltga.hh](#).

5.83.2 Member Data Documentation

5.83.2.1 `_implementation`

`Implementation* _implementation [private]`

Pointer to implementation.

The main motivation for this pattern is to avoid including declarations from `fast_efficient_p3` into the global namespace.

A raw pointer is used instead of a `unique_ptr` because the latter will not compile with `pybind11`.

Definition at line 58 of file `ltga.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/fast-efficient-p3/ltga.hh`
- `lib/hnco/algorithms/fast-efficient-p3/ltga.cc`

5.84 Map Class Reference

Map

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for Map:



Public Member Functions

- virtual `~Map ()`
Destructor.
- virtual void `map` (const `bit_vector_t` &input, `bit_vector_t` &output)=0
Map
- virtual int `get_input_size` () const =0
Get input size.
- virtual int `get_output_size` () const =0
Get output size.
- virtual bool `is_surjective` () const
Check for surjective map.
- virtual void `display` (std::ostream &stream) const
Display.

5.84.1 Detailed Description

Map

Definition at line 45 of file [map.hh](#).

5.84.2 Member Function Documentation

5.84.2.1 `is_surjective()`

```
virtual bool is_surjective ( ) const [inline], [virtual]
```

Check for surjective map.

Returns

false

Reimplemented in [Translation](#), [Permutation](#), [LinearMap](#), [AffineMap](#), [MapComposition](#), [Injection](#), [Projection](#), and [TsAffineMap](#).

Definition at line 65 of file [map.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/maps/map.hh`

5.85 MapComposition Class Reference

Map composition.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for MapComposition:



Public Member Functions

- **MapComposition** ()
Default constructor.
- **MapComposition** (**Map** *outer, **Map** *inner)
Constructor.
- void **map** (const **bit_vector_t** &input, **bit_vector_t** &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool **is_surjective** () const override
Check for surjective map.

Public Member Functions inherited from **Map**

- virtual ~**Map** ()
Destructor.
- virtual void **display** (std::ostream &stream) const
Display.

Private Attributes

- **Map** * **_outer**
Outer map.
- **Map** * **_inner**
Inner map.
- **bit_vector_t** **_bv**
Temporary bit vector.

5.85.1 Detailed Description

Map composition.

The resulting composition f is defined for all bit vector x by $f(x) = \text{outer}(\text{inner}(x))$.

Definition at line 423 of file [map.hh](#).

5.85.2 Constructor & Destructor Documentation

5.85.2.1 MapComposition()

```
MapComposition (
    Map * outer,
    Map * inner ) [inline]
```

Constructor.

Parameters

<i>outer</i>	outer map
<i>inner</i>	inner map

Precondition

```
outer->get_input_size() == inner->get_output_size()
```

Definition at line 447 of file [map.hh](#).

5.85.3 Member Function Documentation

5.85.3.1 is_surjective()

```
bool is_surjective ( ) const [inline], [override], [virtual]
```

Check for surjective map.

Returns

true if both maps are surjective

Reimplemented from [Map](#).

Definition at line 471 of file [map.hh](#).

The documentation for this class was generated from the following file:

- [lib/hnco/maps/map.hh](#)

5.86 MapgenOptions Class Reference

Command line options for mapgen.

```
#include <mapgen-options.hh>
```

Public Member Functions

- **MapgenOptions** ()
Default constructor.
- **MapgenOptions** (int argc, char *argv[], bool ignore_bad_options=false)
Constructor.
- int **get_input_size** () const
Get the value of input_size.
- bool **with_input_size** () const
With parameter input_size.
- int **get_map** () const
Get the value of map.
- bool **with_map** () const
With parameter map.
- int **get_output_size** () const
Get the value of output_size.
- bool **with_output_size** () const
With parameter output_size.
- std::string **get_path** () const
Get the value of path.
- bool **with_path** () const
With parameter path.
- int **get_seed** () const
Get the value of seed.
- bool **with_seed** () const
With parameter seed.
- int **get_ts_length** () const
Get the value of ts_length.
- bool **with_ts_length** () const
With parameter ts_length.
- int **get_ts_sampling_mode** () const
Get the value of ts_sampling_mode.
- bool **with_ts_sampling_mode** () const
With parameter ts_sampling_mode.
- bool **with_surjective** () const
With the flag surjective.

Private Member Functions

- void **print_help** (std::ostream &stream) const
Print help message.
- void **print_version** (std::ostream &stream) const
Print version.

Private Attributes

- `std::string _exec_name`
Name of the executable.
- `std::string _version = "0.26"`
Name Version.
- `int _input_size = 100`
Input bit vector size.
- `int _map = 1`
Type of map.
- `int _output_size = 100`
Output bit vector size.
- `std::string _path = "map.txt"`
Path (relative or absolute) of a map file.
- `int _seed`
Seed for the random number generator.
- `int _ts_length = 10`
Transvection sequence length.
- `int _ts_sampling_mode = 0`
Transvection sequence sampling mode.
- `bool _surjective = false`
Ensure that the sampled linear or affine map is surjective.

Friends

- `std::ostream & operator<< (std::ostream &, const MapgenOptions &)`
Print a header containing the parameter values.

5.86.1 Detailed Description

Command line options for mapgen.

Definition at line 11 of file [mapgen-options.hh](#).

The documentation for this class was generated from the following files:


- `app/mapgen-options.hh`
- `app/mapgen-options.cc`

5.87 MaxNae3Sat Class Reference

Max not-all-equal 3SAT.

```
#include <hnco/functions/collection/max-sat.hh>
```

Inheritance diagram for MaxNae3Sat:



Public Member Functions

- **MaxNae3Sat** ()
Default constructor.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- void **load** (std::string path)
Load instance.

Public Member Functions inherited from [AbstractMaxSat](#)

- **AbstractMaxSat** ()
Default constructor.
- int **get_bv_size** () const override
Get bit vector size.
- void **display** (std::ostream &stream) const override
Display the expression.
- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Additional Inherited Members

Protected Member Functions inherited from [AbstractMaxSat](#)

- void `load_` (std::istream &stream)
Load an instance.
- void `save_` (std::ostream &stream) const
Save an instance.

Protected Attributes inherited from [AbstractMaxSat](#)

- std::vector< std::vector< int > > `_expression`
Expression.
- int `_num_variables`
Number of variables.

5.87.1 Detailed Description

Max not-all-equal 3SAT.

Reference:

Christos M. Papadimitriou. 1994. Computational complexity. Addison-Wesley, Reading, Massachusetts.

Definition at line 163 of file [max-sat.hh](#).

5.87.2 Member Function Documentation

5.87.2.1 `load()`

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 178 of file [max-sat.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/max-sat.hh](#)
- [lib/hnco/functions/collection/max-sat.cc](#)

5.88 MaxSat Class Reference

MAX-SAT.

```
#include <hnco/functions/collection/max-sat.hh>
```

Inheritance diagram for MaxSat:



Public Member Functions

- **MaxSat** ()
Default constructor.
- void **random** (int n, int k, int c)
Random instance.
- void **random** (const [bit_vector_t](#) &solution, int k, int c)
Random instance with satisfiable expression.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [AbstractMaxSat](#)

- **AbstractMaxSat** ()
Default constructor.
- int **get_bv_size** () const override
Get bit vector size.
- void **display** (std::ostream &stream) const override
Display the expression.
- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Additional Inherited Members

Protected Member Functions inherited from [AbstractMaxSat](#)

- void **load_** (std::istream &stream)
Load an instance.
- void **save_** (std::ostream &stream) const
Save an instance.

Protected Attributes inherited from [AbstractMaxSat](#)

- `std::vector< std::vector< int > > _expression`
Expression.
- `int _num_variables`
Number of variables.

5.88.1 Detailed Description

MAX-SAT.

Reference:

Christos M. Papadimitriou. 1994. Computational complexity. Addison-Wesley, Reading, Massachusetts.

Definition at line 120 of file [max-sat.hh](#).

5.88.2 Member Function Documentation

5.88.2.1 `random()` [1/2]

```
void random (
    const bit\_vector\_t & solution,
    int k,
    int c )
```

Random instance with satisfiable expression.

Warning

Since the expression is satisfiable, the maximum of the function is equal to the number of clauses in the expression. However, this information is lost in the save and load cycle as the archive format only manages the expression itself.

Parameters

<i>solution</i>	Solution
<i>k</i>	Number of literals per clause
<i>c</i>	Number of clauses

Definition at line 218 of file [max-sat.cc](#).

5.88.2.2 `random()` [2/2]

```
void random (
    int n,
    int k,
    int c )
```

Random instance.

Parameters

n	Size of bit vectors
k	Number of literals per clause
c	Number of clauses

Definition at line 190 of file [max-sat.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/max-sat.hh](#)
- [lib/hnco/functions/collection/max-sat.cc](#)

5.89 Mimic Class Reference

Mutual information maximizing input clustering.

```
#include <hnco/algorithms/mimic.hh>
```

Inheritance diagram for Mimic:



Public Member Functions

- **Mimic** (int n , int $population_size$)
Constructor.

Setters

- void **set_selection_size** (int $selection_size$)
Set the selection size.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual ~**Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **sample** ([bit_vector_t](#) &bv)
Sample a bit vector.
- void **compute_conditional_entropy** (int index)
Compute conditional entropy.
- void **update_model** ()
Update model.

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population.
- [permutation_t](#) **_permutation**
Permutation.
- std::array< [pv_t](#), 2 > **_parameters**
Model parameters.
- [pv_t](#) **_mean**
Mean of selected bit vectors.
- std::vector< double > **_entropies**
Conditional entropies.
- std::array< std::array< int, 2 >, 2 > **_table**
Contingency table.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.

Parameters

- int **_selection_size**
Selection size.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.89.1 Detailed Description

Mutual information maximizing input clustering.

This implementation differs from the algorithm described in the reference below in that it constrains all probabilities (marginal and conditional) to stay away from the values 0 and 1 by a fixed margin equal to $1/n$, as usually done in algorithms such as [Pbil](#) or [Umda](#).

Reference:

Jeremy S. De Bonet and Charles L. Isbell and Jr. and Paul Viola, MIMIC: Finding Optima by Estimating Probability Densities, in Advances in Neural Information Processing Systems, 1996, MIT Press.

Definition at line 52 of file [mimic.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/mimic.hh`
- `lib/hnco/algorithms/mimic.cc`

5.90 [MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >](#) Class Template Reference

Mixed-representation multivariate function adapter.

```
#include <hnco/functions/multivariate-function-adapter.hh>
```

Inheritance diagram for [MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >](#):



Public Types

- using **function_type** = Fn
Function type

Public Member Functions

- [MixedRepresentationMultivariateFunctionAdapter](#) (Fn *fn, const std::vector< RepVariant > &vs)
Constructor.

Information about the function

- int [get_bv_size](#) () const override

Evaluation

- double [evaluate](#) (const [bit_vector_t](#) &bv) override

Display

- void [display](#) (std::ostream &stream) const override
- void [describe](#) (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool [has_known_maximum](#) () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Member Functions

- void [unpack](#) (const [bit_vector_t](#) &bv)
Unpack a bit vector into values.

Private Attributes

- `Fn * _function`
Multivariate function.
- `std::vector< RepVariant > _rep_variants`
Representation variants.
- `std::vector< typename Fn::domain_type > _variables`
Variables.
- `Conv _converter`
Converter from codomain to double.

5.90.1 Detailed Description

```
template<typename Fn, typename RepVariant, class Conv>
class hnco::function::MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >
```

Mixed-representation multivariate function adapter.

Template Parameters

<i>Fn</i>	Type of the multivariate function
<i>RepVariant</i>	Type of the representation variant
<i>Conv</i>	Type of the converter

Precondition

`RepVariant` must be a variant of representations.

The purpose of this class is to build a regular `hnco` function from an arbitrary multivariate function. This is achieved using a composition:

- Representations: bit vector -> domain
- Multivariate function: product of domains -> codomain
- Converter: codomain -> double

Representations can be of different types thanks to the use of variants.

Definition at line 154 of file [multivariate-function-adapter.hh](#).

5.90.2 Constructor & Destructor Documentation

5.90.2.1 MixedRepresentationMultivariateFunctionAdapter()

```
template<typename Fn , typename RepVariant , class Conv >
MixedRepresentationMultivariateFunctionAdapter (
    Fn * fn,
    const std::vector< RepVariant > & vs ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Multivariate function
<i>vs</i>	Representation variants

Definition at line 183 of file [multivariate-function-adapter.hh](#).

5.90.3 Member Function Documentation

5.90.3.1 display()

```
template<typename Fn , typename RepVariant , class Conv >
void display (
    std::ostream & stream ) const [inline], [override], [virtual]
```

Display

Reimplemented from [Function](#).

Definition at line 218 of file [multivariate-function-adapter.hh](#).

5.90.3.2 evaluate()

```
template<typename Fn , typename RepVariant , class Conv >
double evaluate (
    const bit\_vector\_t & bv ) [inline], [override], [virtual]
```

Evaluate

Implements [Function](#).

Definition at line 207 of file [multivariate-function-adapter.hh](#).

5.90.3.3 get_bv_size()

```
template<typename Fn , typename RepVariant , class Conv >
int get_bv_size ( ) const [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 195 of file [multivariate-function-adapter.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/functions/multivariate-function-adapter.hh](#)

5.91 MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv > Class Template Reference

Mixed-representation multivariate function adapter.

```
#include <hnco/multiobjective/functions/multivariate-function-adapter.hh>
```

Inheritance diagram for MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >:



Public Types

- using **function_type** = Fn
Function type.

Public Member Functions

- **MixedRepresentationMultivariateFunctionAdapter** (Fn *fn, const std::vector< RepVariant > &vs)
Constructor.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.
- int **get_output_size** () const override
Get output size (number of objectives)

Evaluation

- void **evaluate** (const **bit_vector_t** &bv, **value_t** &value) override

Display

- void **display** (std::ostream &stream) const override
- void **describe** (const **bit_vector_t** &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function()`

Destructor.

Private Member Functions

- void `unpack` (const [bit_vector_t](#) &bv)

Unpack a bit vector into variables.

Private Attributes

- `Fn * _function`
Multivariate function.
- `std::vector< RepVariant > _rep_variants`
Representation variants.
- `std::vector< typename Fn::domain_type > _variables`
Variables.
- `Conv _converter`
Converter from codomain to double.

5.91.1 Detailed Description

```
template<typename Fn, typename RepVariant, class Conv>
class hnco::multiobjective::function::MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant,
Conv >
```

Mixed-representation multivariate function adapter.

Template Parameters

<i>Fn</i>	Type of the multivariate function
<i>RepVariant</i>	Type of the representation variant
<i>Conv</i>	Type of the converter

Precondition

RepVariant must be a variant of representations.

The purpose of this class is to build a regular hnco function from an arbitrary multivariate function. This is achieved using a composition:

- Representations (Rep): hypercube -> domain
- Multivariate function (Fn): product of domains -> product of codomains
- Converter (Conv): codomain -> double

Definition at line 171 of file [multivariate-function-adapter.hh](#).

5.91.2 Constructor & Destructor Documentation

5.91.2.1 MixedRepresentationMultivariateFunctionAdapter()

```
template<typename Fn , typename RepVariant , class Conv >
MixedRepresentationMultivariateFunctionAdapter (
    Fn * fn,
    const std::vector< RepVariant > & vs ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Multivariate function
<i>vs</i>	Representation variants

Definition at line 205 of file [multivariate-function-adapter.hh](#).

5.91.3 Member Function Documentation

5.91.3.1 display()

```
template<typename Fn , typename RepVariant , class Conv >
void display (
    std::ostream & stream ) const [inline], [override], [virtual]
```

Display

Reimplemented from [Function](#).

Definition at line 250 of file [multivariate-function-adapter.hh](#).

5.91.3.2 evaluate()

```
template<typename Fn , typename RepVariant , class Conv >
void evaluate (
    const bit\_vector\_t & bv,
    value\_t & value ) [inline], [override], [virtual]
```

Evaluate

Implements [Function](#).

Definition at line 235 of file [multivariate-function-adapter.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/multiobjective/functions/multivariate-function-adapter.hh](#)

5.92 Mmas Class Reference

Max-min ant system.

```
#include <hnco/algorithms/probability-vector/mmas.hh>
```

Inheritance diagram for Mmas:



Public Member Functions

- **Mmas** (int n)
Constructor.

Setters

- void **set_compare** (std::function< bool(double, double)> x)
Set the binary operator for comparing evaluations.
- void **set_learning_rate** (double x)
Set the learning rate.

Public Member Functions inherited from **PvAlgorithm**

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & [get_solution](#) ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [PvAlgorithm](#)

- void [set_something_to_log](#) ()
Set flag for something to log.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [bit_vector_t_x](#)
Candidate solution.

Parameters

- std::function< bool(double, double)> **_compare** = std::greater_equal<double>()
Binary operator for comparing evaluations.
- double **_learning_rate** = 1e-3
Learning rate.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t_pv](#)
Probability vector.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.
- bool **_log_entropy** = false
Log entropy.
- bool **_log_pv** = false
Log probability vector.
- int **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- **int `_iteration`**
Current iteration.
- **bool `_last_iteration` = false**
Last iteration.
- **bool `_something_to_log` = false**
Something to log.
- **int `_num_iterations` = 0**
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- **std::vector< [function::Function](#) * > `_functions`**
Functions.
- **[function::Function](#) * `_function`**
Function.
- **[solution_t](#) `_solution`**
Solution.
- **[logging::LogContext](#) * `_log_context` = nullptr**
Log context.

5.92.1 Detailed Description

Max-min ant system.

Reference:

Thomas Stützle and Holger H. Hoos. 2000. MAX-MIN Ant System. *Future Generation Computer Systems* 16, 8 (2000), 889–914.

Definition at line 42 of file [mmas.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/probability-vector/mmas.hh](#)
- [lib/hnco/algorithms/probability-vector/mmas.cc](#)

5.93 Modifier Class Reference

Function modifier.

```
#include <hnco/functions/modifiers/modifier.hh>
```

Inheritance diagram for Modifier:



Public Member Functions

- **Modifier** ([Function](#) *function)
Constructor.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual int **get_bv_size** () const =0
Get bit vector size.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const

- *Check for a known maximum.*
virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate](#) (const [bit_vector_t](#) &)=0
Evaluate a bit vector.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * [_function](#)
Decorated function.

5.93.1 Detailed Description

[Function](#) modifier.

Definition at line 36 of file [modifier.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/functions/modifiers/modifier.hh

5.94 MuCommaLambdaEa Class Reference

(mu, lambda) EA.

```
#include <hnco/algorithms/evolutionary-algorithms/mu-comma-lambda-ea.hh>
```

Inheritance diagram for MuCommaLambdaEa:



Public Member Functions

- [MuCommaLambdaEa](#) (int n, int mu, int lambda)
Constructor.

Setters

- void **set_mutation_rate** (double p)
Set the mutation rate.
- void **set_allow_no_mutation** (bool b)
Set the flag _allow_no_mutation.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_parents**
Parents.
- [Population](#) **_offsprings**
Offsprings.
- [CommaSelection](#) **_comma_selection**
Comma selection.
- [neighborhood::StandardBitMutation](#) **_mutation**
Mutation operator.
- std::uniform_int_distribution< int > **_select_parent**
Select parent.

Parameters

- double **_mutation_rate**
Mutation rate.
- bool **_allow_no_mutation** = false
Allow no mutation.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.94.1 Detailed Description

(mu, lambda) EA.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 43 of file [mu-comma-lambda-ea.hh](#).

5.94.2 Constructor & Destructor Documentation

5.94.2.1 MuCommaLambdaEa()

```
MuCommaLambdaEa (
    int n,
    int mu,
    int lambda ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Parent population size
<i>lambda</i>	Offspring population size

Definition at line 94 of file [mu-comma-lambda-ea.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/mu-comma-lambda-ea.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/mu-comma-lambda-ea.cc](#)

5.95 MultiBitFlip Class Reference

Multi bit flip.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for MultiBitFlip:



Public Member Functions

- [MultiBitFlip](#) (int n)
Constructor.

Public Member Functions inherited from [Neighborhood](#)

- [Neighborhood](#) (int n)
Constructor.
- virtual [~Neighborhood](#) ()
Destructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & **get_origin** () const
Get the origin.
- virtual const [bit_vector_t](#) & **get_candidate** () const
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & **get_flipped_bits** () const

- Get flipped bits.*
- virtual void **propose** ()
Propose a candidate bit vector.
- virtual void **keep** ()
Keep the candidate bit vector.
- virtual void **forget** ()
Forget the candidate bit vector.
- virtual void **mutate** (bit_vector_t &bv)
Mutate.
- virtual void **map** (const bit_vector_t &input, bit_vector_t &output)
Map.

Protected Member Functions

- void **bernoulli_trials** (int k)
Sample a given number of bits using Bernoulli trials.
- void **rejection_sampling** (int k)
Sample a given number of bits using rejection sampling.

Protected Member Functions inherited from [Neighborhood](#)

- virtual void **sample_bits** ()=0
Sample bits.

Additional Inherited Members

Protected Attributes inherited from [Neighborhood](#)

- **bit_vector_t_origin**
Origin of the neighborhood.
- **bit_vector_t_candidate**
candidate bit vector
- std::uniform_int_distribution< int > **_index_dist**
Index distribution.
- **sparse_bit_vector_t_flipped_bits**
Flipped bits.

5.95.1 Detailed Description

Multi bit flip.

Definition at line 185 of file [neighborhood.hh](#).

5.95.2 Constructor & Destructor Documentation

5.95.2.1 MultiBitFlip()

```
MultiBitFlip (
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

Definition at line 208 of file [neighborhood.hh](#).

5.95.3 Member Function Documentation

5.95.3.1 bernoulli_trials()

```
void bernoulli_trials (  
    int k ) [protected]
```

Sample a given number of bits using Bernoulli trials.

Parameters

k	Number of bits to sample
-----	--------------------------

Definition at line 34 of file [neighborhood.cc](#).

5.95.3.2 rejection_sampling()

```
void rejection_sampling (  
    int k ) [protected]
```

Sample a given number of bits using rejection sampling.

Parameters

k	Number of bits to sample
-----	--------------------------

Definition at line 52 of file [neighborhood.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/neighborhoods/neighborhood.hh](#)
- [lib/hnco/neighborhoods/neighborhood.cc](#)

5.96 MultiobjectiveFunctionAdapter Class Reference

Multiobjective function adapter.

```
#include <hnco/functions/multiobjective-function-adapter.hh>
```

Inheritance diagram for MultiobjectiveFunctionAdapter:



Public Member Functions

- [MultiobjectiveFunctionAdapter](#) ([multiobjective::function::Function](#) *fn)
Constructor.

Properties

- int [get_bv_size](#) () const override

Evaluation

- double [evaluate](#) (const [bit_vector_t](#) &bv) override

Display

- void [display](#) (std::ostream &stream) const override
- void [describe](#) (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual [~Function](#) ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool [has_known_maximum](#) () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Attributes

- `multiobjective::function::Function * _function`
Multiobjective function.
- `multiobjective::function::value_t _value`
Output value of the multiobjective function.

5.96.1 Detailed Description

Multiobjective function adapter.

The purpose of this class is to build a function from an arbitrary multiobjective function. This is achieved using a composition:

- Multiobjective function: bit vector -> [double]
- Linear combination: [double] -> double

Definition at line 42 of file [multiobjective-function-adapter.hh](#).

5.96.2 Constructor & Destructor Documentation

5.96.2.1 MultiobjectiveFunctionAdapter()

```
MultiobjectiveFunctionAdapter (
    multiobjective::function::Function * fn )    [inline]
```

Constructor.

Parameters

<i>fn</i>	Multiobjective function
-----------	-------------------------

Definition at line 53 of file [multiobjective-function-adapter.hh](#).

5.96.3 Member Function Documentation

5.96.3.1 display()

```
void display (
    std::ostream & stream ) const    [inline], [override], [virtual]
```

Display

Reimplemented from [Function](#).

Definition at line 81 of file [multiobjective-function-adapter.hh](#).

5.96.3.2 evaluate()

```
double evaluate (
    const bit_vector_t & bv ) [inline], [override], [virtual]
```

Evaluate

Implements [Function](#).

Definition at line 71 of file [multiobjective-function-adapter.hh](#).

5.96.3.3 get_bv_size()

```
int get_bv_size ( ) const [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 64 of file [multiobjective-function-adapter.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/functions/multiobjective-function-adapter.hh](#)

5.97 MultivariateFunctionAdapter< Fn, Rep, Conv > Class Template Reference

Multivariate function adapter.

```
#include <hnco/functions/multivariate-function-adapter.hh>
```

Inheritance diagram for MultivariateFunctionAdapter< Fn, Rep, Conv >:



Public Types

- using **function_type** = Fn
Function type
- using **representation_type** = Rep
Representation type.
- using **converter_type** = Conv
Converter type.

Public Member Functions

- [MultivariateFunctionAdapter](#) (Fn *fn, std::vector< Rep > reps)
Constructor.

Information about the function

- int [get_bv_size](#) () const override

Evaluation

- double [evaluate](#) (const [bit_vector_t](#) &bv) override

Display

- void [display](#) (std::ostream &stream) const override
- void [describe](#) (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool [has_known_maximum](#) () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Member Functions

- void **unpack** (const [bit_vector_t](#) &bv)
Unpack a bit vector into values.

Private Attributes

- Fn * **_function**
Multivariate function.
- std::vector< Rep > **_representations**
Representations.
- std::vector< typename Fn::domain_type > **_variables**
Variables.
- Conv **_converter**
Converter from codomain to double.

5.97.1 Detailed Description

```
template<class Fn, class Rep, class Conv>
class hnco::function::MultivariateFunctionAdapter< Fn, Rep, Conv >
```

Multivariate function adapter.

Template Parameters

<i>Fn</i>	Type of the multivariate function
<i>Rep</i>	Type of representations
<i>Conv</i>	Type of the converter

The purpose of this class is to build a regular hnco function from an arbitrary multivariate function. This is achieved using a composition:

- Representations: bit vector -> domain
- Multivariate function: product of domains -> codomain
- Converter: codomain -> double

All representations are of the same type.

Definition at line 51 of file [multivariate-function-adapter.hh](#).

5.97.2 Constructor & Destructor Documentation

5.97.2.1 MultivariateFunctionAdapter()

```
template<class Fn , class Rep , class Conv >
MultivariateFunctionAdapter (
    Fn * fn,
    std::vector< Rep > reps ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Multivariate function
<i>reps</i>	Representations

Definition at line 85 of file [multivariate-function-adapter.hh](#).

5.97.3 Member Function Documentation

5.97.3.1 display()

```
template<class Fn , class Rep , class Conv >
void display (
    std::ostream & stream ) const [inline], [override], [virtual]
```

Display

Reimplemented from [Function](#).

Definition at line 120 of file [multivariate-function-adapter.hh](#).

5.97.3.2 evaluate()

```
template<class Fn , class Rep , class Conv >
double evaluate (
    const bit\_vector\_t & bv ) [inline], [override], [virtual]
```

Evaluate

Implements [Function](#).

Definition at line 109 of file [multivariate-function-adapter.hh](#).

5.97.3.3 get_bv_size()

```
template<class Fn , class Rep , class Conv >
int get_bv_size ( ) const [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 97 of file [multivariate-function-adapter.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/functions/multivariate-function-adapter.hh](#)

5.98 MultivariateFunctionAdapter< Fn, Rep, Conv > Class Template Reference

Multivariate function adapter.

```
#include <hnco/multiojective/functions/multivariate-function-adapter.hh>
```

Inheritance diagram for MultivariateFunctionAdapter< Fn, Rep, Conv >:



Public Types

- using **function_type** = Fn
Function type.
- using **representation_type** = Rep
Representation type.
- using **converter_type** = Conv
Converter type.

Public Member Functions

- [MultivariateFunctionAdapter](#) (Fn *fn, std::vector< Rep > reps)
Constructor.

Information about the function

- int [get_bv_size](#) () const override
- int [get_output_size](#) () const override
Get output size (number of objectives)

Evaluation

- void [evaluate](#) (const [bit_vector_t](#) &bv, [value_t](#) &value) override

Display

- void [display](#) (std::ostream &stream) const override
- void [describe](#) (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.

Private Member Functions

- void **unpack** (const [bit_vector_t](#) &bv)
Unpack a bit vector into variables.

Private Attributes

- Fn * **_function**
Multivariate function.
- std::vector< Rep > **_representations**
Representations.
- std::vector< typename Fn::domain_type > **_variables**
Variables.
- std::vector< typename Fn::codomain_type > **_codomain_value**
Codomain value.
- Conv **_converter**
Converter from codomain to double.

5.98.1 Detailed Description

```
template<class Fn, class Rep, class Conv>
class hnco::multiobjective::function::MultivariateFunctionAdapter< Fn, Rep, Conv >
```

Multivariate function adapter.

Template Parameters

<i>Fn</i>	Type of the multivariate function
<i>Rep</i>	Type of representations
<i>Conv</i>	Type of the converter

The purpose of this class is to build a regular hnco function from an arbitrary multivariate function. This is achieved using a composition:

- Representations (Rep): hypercube -> domain
- Multivariate function (Fn): product of domains -> product of codomains
- Converter (Conv): codomain -> double

Definition at line 50 of file [multivariate-function-adapter.hh](#).

5.98.2 Constructor & Destructor Documentation

5.98.2.1 MultivariateFunctionAdapter()

```
template<class Fn , class Rep , class Conv >
MultivariateFunctionAdapter (
    Fn * fn,
    std::vector< Rep > reps ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Multivariate function
<i>reps</i>	Representations

Definition at line 92 of file [multivariate-function-adapter.hh](#).

5.98.3 Member Function Documentation

5.98.3.1 display()

```
template<class Fn , class Rep , class Conv >
void display (
    std::ostream & stream ) const [inline], [override], [virtual]
```

Display

Reimplemented from [Function](#).

Definition at line 140 of file [multivariate-function-adapter.hh](#).

5.98.3.2 evaluate()

```
template<class Fn , class Rep , class Conv >
void evaluate (
    const bit\_vector\_t & bv,
    value\_t & value ) [inline], [override], [virtual]
```

Evaluate

Implements [Function](#).

Definition at line 124 of file [multivariate-function-adapter.hh](#).

5.98.3.3 `get_bv_size()`

```
template<class Fn , class Rep , class Conv >
int get_bv_size ( ) const [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 107 of file [multivariate-function-adapter.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/multiobjective/functions/multivariate-function-adapter.hh](#)

5.99 MuPlusLambdaEa Class Reference

(mu+lambda) EA.

```
#include <hnco/algorithms/evolutionary-algorithms/mu-plus-lambda-ea.hh>
```

Inheritance diagram for MuPlusLambdaEa:



Public Member Functions

- [MuPlusLambdaEa](#) (int n, int mu, int lambda)
Constructor.

Setters

- void **set_mutation_rate** (double p)
Set the mutation rate.
- void **set_allow_no_mutation** (bool b)
Set the flag `_allow_no_mutation`.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_parents**
Parents.
- [Population](#) **_offsprings**
Offsprings.
- [PlusSelection](#) **_plus_selection**
Plus selection.
- [neighborhood::StandardBitMutation](#) **_mutation**
Mutation operator.
- std::uniform_int_distribution< int > **_select_parent**
Select parent.

Parameters

- double **_mutation_rate**
Mutation rate.
- bool **_allow_no_mutation** = false
Allow no mutation.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.99.1 Detailed Description

(mu+lambda) EA.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 43 of file [mu-plus-lambda-ea.hh](#).

5.99.2 Constructor & Destructor Documentation

5.99.2.1 MuPlusLambdaEa()

```
MuPlusLambdaEa (
    int n,
    int mu,
    int lambda ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Parent population size
<i>lambda</i>	Offspring population size

Definition at line 94 of file [mu-plus-lambda-ea.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/mu-plus-lambda-ea.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/mu-plus-lambda-ea.cc](#)

5.100 NearestNeighborIsingModel1 Class Reference

Nearest neighbor Ising model in one dimension.

```
#include <hnco/functions/collection/ising/nearest-neighbor-ising-model-1.h>
hh>
```

Inheritance diagram for NearestNeighborIsingModel1:



Public Member Functions

- **NearestNeighborIsingModel1** ()
Constructor.
- void **set_periodic_boundary_conditions** (bool x)
Set periodic boundary conditions.

Instance generators

- template<class CouplingGen , class FieldGen >
void **generate** (int n, CouplingGen coupling_gen, FieldGen field_gen)
Instance generator.
- void **random** (int n)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Evaluation

- double **evaluate** (const **bit_vector_t** &) override
Evaluate a bit vector.
- double **evaluate_incrementally** (const **bit_vector_t** &x, double v, const **sparse_bit_vector_t** &flipped_bits) override
Incrementally evaluate a bit vector.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.
- bool **provides_incremental_evaluation** () const override
Check whether the function provides incremental evaluation.
- void **display** (std::ostream &stream) const override
Display.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- template<class Archive >
void `save` (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void `load` (Archive &ar, const unsigned int version)
Load.
- void `resize` (int n)
Resize data structures.

Private Attributes

- std::vector< double > `_coupling`
Coupling with nearest neighbor to the right.
- std::vector< double > `_field`
External field.
- `bit_vector_t` `_flipped_bits`
Flipped bits.
- bool `_periodic_boundary_conditions` = false
Periodic boundary conditions.

5.100.1 Detailed Description

Nearest neighbor Ising model in one dimension.

Its expression is of the form

$$f(x) = \sum_i J_{i,i+1}(1 - 2x_i)(1 - 2x_{i+1}) + \sum_i h_i(1 - 2x_i)$$

or equivalently

$$f(x) = \sum_i J_{i,i+1}(-1)^{x_i+x_{i+1}} + \sum_i h_i(-1)^{x_i}$$

where $J_{i,i+1}$ is the interaction between adjacent sites i and $i+1$ and h_i is the external magnetic field interacting with site i .

In the case of periodic boundary conditions, the sum $i + 1$ is mod n .

Since we are maximizing f or minimizing $-f$, the expression of f is compatible with what can be found in physics textbooks.

It should be noted that such an Ising model can be represented by a Walsh expansion of degree 2, that is [WalshExpansion2](#).

Reference: https://en.wikipedia.org/wiki/Ising_model

Definition at line 63 of file [nearest-neighbor-ising-model-1.hh](#).

5.100.2 Member Function Documentation

5.100.2.1 evaluate()

```
double evaluate (
    const bit_vector_t & s ) [override], [virtual]
```

Evaluate a bit vector.

Complexity: $O(n)$

Implements [Function](#).

Definition at line 46 of file [nearest-neighbor-ising-model-1.cc](#).

5.100.2.2 generate()

```
template<class CouplingGen , class FieldGen >
void generate (
    int n,
    CouplingGen coupling_gen,
    FieldGen field_gen ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>coupling_gen</i>	Coupling generator
<i>field_gen</i>	External field generator

Definition at line 124 of file [nearest-neighbor-ising-model-1.hh](#).

5.100.2.3 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 158 of file [nearest-neighbor-ising-model-1.hh](#).

5.100.2.4 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) const [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 199 of file [nearest-neighbor-ising-model-1.hh](#).

5.100.2.5 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 140 of file [nearest-neighbor-ising-model-1.hh](#).

5.100.2.6 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 165 of file [nearest-neighbor-ising-model-1.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/ising/nearest-neighbor-ising-model-1.hh](#)
- [lib/hnco/functions/collection/ising/nearest-neighbor-ising-model-1.cc](#)

5.101 NearestNeighborIsingModel2 Class Reference

Nearest neighbor Ising model in two dimensions.

```
#include <hnco/functions/collection/ising/nearest-neighbor-ising-model-2.↵
hh>
```

Inheritance diagram for NearestNeighborIsingModel2:



Public Member Functions

- **NearestNeighborIsingModel2** ()
Constructor.
- void **set_periodic_boundary_conditions** (bool x)
Set periodic boundary conditions.

Instance generators

- template<class CouplingGen , class FieldGen >
void **generate** (int num_rows, int num_columns, CouplingGen coupling_gen, FieldGen field_gen)
Instance generator.
- void **random** (int num_rows, int num_columns)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Evaluation

- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- double **evaluate_incrementally** (const [bit_vector_t](#) &x, double v, const [sparse_bit_vector_t](#) &flipped_bits) override
Incrementally evaluate a bit vector.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.
- bool **provides_incremental_evaluation** () const override
Check whether the function provides incremental evaluation.
- void **display** (std::ostream &stream) const override
Display.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- `template<class Archive >`
void **save** (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
void **load** (Archive &ar, const unsigned int version)
Load.
- void **resize** (int num_rows, int num_columns)
Resize data structures.

Private Attributes

- `std::vector< std::vector< double > > _coupling_right`
Coupling with nearest neighbor to the right.
- `std::vector< std::vector< double > > _coupling_below`
Coupling with nearest neighbor below.
- `std::vector< std::vector< double > > _field`
External field.
- `bit_vector_t _flipped_bits`
Flipped bits.
- `bool _periodic_boundary_conditions = false`
Periodic boundary conditions.

5.101.1 Detailed Description

Nearest neighbor Ising model in two dimensions.

We are considering a rectangular lattice in which each site has (at most) four neighbors (left, right, above, below).

The expression of the function is of the form

$$f(x) = \sum_{(i,j)} J_{ij}(1 - 2x_i)(1 - 2x_j) + \sum_i h_i(1 - 2x_i)$$

or equivalently

$$f(x) = \sum_{(i,j)} J_{ij}(-1)^{x_i+x_j} + \sum_i h_i(-1)^{x_i}$$

where the first sum is over adjacent sites (i, j), J_{ij} is the interaction between adjacent sites i and j, and h_i is the external magnetic field interacting with site i.

Since we are maximizing f or minimizing -f, the expression of f is compatible with what can be found in physics textbooks.

It should be noted that such an Ising model can be represented by a Walsh expansion of degree 2, that is [WalshExpansion2](#).

Reference: https://en.wikipedia.org/wiki/Ising_model

Definition at line 65 of file [nearest-neighbor-ising-model-2.hh](#).

5.101.2 Member Function Documentation

5.101.2.1 evaluate()

```
double evaluate (
    const bit\_vector\_t & s ) [override], [virtual]
```

Evaluate a bit vector.

Complexity: O(n)

Implements [Function](#).

Definition at line 49 of file [nearest-neighbor-ising-model-2.cc](#).

5.101.2.2 generate()

```
template<class CouplingGen , class FieldGen >
void generate (
    int num_rows,
    int num_columns,
    CouplingGen coupling_gen,
    FieldGen field_gen ) [inline]
```

Instance generator.

Parameters

<i>num_rows</i>	Number of rows
<i>num_columns</i>	Number of columns
<i>coupling_gen</i>	Coupling generator
<i>field_gen</i>	External field generator

Definition at line 132 of file [nearest-neighbor-ising-model-2.hh](#).

5.101.2.3 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 170 of file [nearest-neighbor-ising-model-2.hh](#).

5.101.2.4 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) const [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 216 of file [nearest-neighbor-ising-model-2.hh](#).

5.101.2.5 random()

```
void random (
    int num_rows,
    int num_columns ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

<i>num_rows</i>	Number of rows
<i>num_columns</i>	Number of columns

Definition at line 152 of file [nearest-neighbor-ising-model-2.hh](#).

5.101.2.6 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 177 of file [nearest-neighbor-ising-model-2.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/ising/nearest-neighbor-ising-model-2.hh](#)
- [lib/hnco/functions/collection/ising/nearest-neighbor-ising-model-2.cc](#)

5.102 Needle Class Reference

Needle in a haystack.

```
#include <hnco/functions/collection/theory.hh>
```

Inheritance diagram for Needle:



Public Member Functions

- **Needle** (int bv_size)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `display` (std::ostream &stream) const
Display.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int `_bv_size`
Bit vector size.

5.102.1 Detailed Description

Needle in a haystack.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 108 of file [theory.hh](#).

5.102.2 Member Function Documentation

5.102.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

1

Reimplemented from [Function](#).

Definition at line 129 of file [theory.hh](#).

5.102.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 124 of file [theory.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/theory.hh
- lib/hnco/functions/collection/theory.cc

5.103 Neighborhood Class Reference

Neighborhood.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for Neighborhood:



Public Member Functions

- [Neighborhood](#) (int n)
Constructor.
- virtual `~Neighborhood ()`
Destructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & **get_origin** () const
Get the origin.
- virtual const [bit_vector_t](#) & **get_candidate** () const
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & **get_flipped_bits** () const
Get flipped bits.
- virtual void **propose** ()
Propose a candidate bit vector.
- virtual void **keep** ()
Keep the candidate bit vector.
- virtual void **forget** ()
Forget the candidate bit vector.
- virtual void **mutate** ([bit_vector_t](#) &bv)
Mutate.
- virtual void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Protected Member Functions

- virtual void **sample_bits** ()=0
Sample bits.

Protected Attributes

- [bit_vector_t](#) **_origin**
Origin of the neighborhood.
- [bit_vector_t](#) **_candidate**
candidate bit vector
- `std::uniform_int_distribution< int > _index_dist`
Index distribution.
- [sparse_bit_vector_t](#) **_flipped_bits**
Flipped bits.

5.103.1 Detailed Description

Neighborhood.

A neighborhood maintains two points, `_origin` and `_candidate`. They are initialized in the same state by `set_origin`. A [Neighborhood](#) class must implement the member function `sample_bits` which samples the bits to flip in `_origin` to get a `_candidate`. The following member functions take care of the modifications:

- `propose`: flip `_candidate`
- `keep`: flip `_origin`
- `forget` flip `_candidate`

After `keep` or `forget`, `_origin` and `_candidate` are in the same state again.

A [Neighborhood](#) class can also behave as a mutation operator through the member functions `mutate` and `map`.

Definition at line 61 of file [neighborhood.hh](#).

5.103.2 Constructor & Destructor Documentation

5.103.2.1 Neighborhood()

```
Neighborhood (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 86 of file [neighborhood.hh](#).

5.103.3 Member Function Documentation

5.103.3.1 map()

```
virtual void map (
    const bit_vector_t & input,
    bit_vector_t & output ) [inline], [virtual]
```

Map.

The output bit vector is a mutated version of the input bit vector.

Parameters

<i>input</i>	Input bit vector
<i>output</i>	Output bit vector

Definition at line 151 of file [neighborhood.hh](#).

5.103.3.2 mutate()

```
virtual void mutate (  
    bit\_vector\_t & bv ) [inline], [virtual]
```

Mutate.

In-place mutation of the bit vector.

Parameters

<i>bv</i>	Bit vector to mutate
-----------	----------------------

Definition at line 137 of file [neighborhood.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/neighborhoods/neighborhood.hh](#)

5.104 NeighborhoodIterator Class Reference

Neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for NeighborhoodIterator:



Public Member Functions

- [NeighborhoodIterator](#) (int n)
Constructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set origin.

Public Member Functions inherited from [Iterator](#)

- **Iterator** (int n)
Constructor.
- virtual **~Iterator** ()
Destructor.
- virtual void **init** ()
Initialization.
- virtual bool **has_next** ()=0
Has next bit vector.
- virtual const [bit_vector_t](#) & **next** ()=0
Next bit vector.

Additional Inherited Members

Protected Attributes inherited from [Iterator](#)

- [bit_vector_t](#) **_current**
Current bit vector.
- bool **_initial_state** = true
Flag for initial state.

5.104.1 Detailed Description

Neighborhood iterator.

A neighborhood iterator allows to iterate over bit vectors in the neighborhood of a given origin. The origin itself should not belong to the neighborhood.

Definition at line 38 of file [neighborhood-iterator.hh](#).

5.104.2 Constructor & Destructor Documentation

5.104.2.1 NeighborhoodIterator()

```
NeighborhoodIterator (  
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 47 of file [neighborhood-iterator.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.105 NkLandscape Class Reference

NK landscape.

```
#include <hnco/functions/collection/nk-landscape.hh>
```

Inheritance diagram for NkLandscape:



Public Member Functions

- **NkLandscape** ()
Default constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- void **display** (std::ostream &stream) const override
Display.

Instance generators

- template<class Generator >
void [generate](#) (int n, int k, Generator generator)
Instance generator.
- void [random](#) (int n, int k)
Random instance.

Load and save instance

- void [load](#) (std::string path)
Load instance.
- void [save](#) (std::string path) const
Save instance.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void `update` (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void `describe` (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- template<class Archive >
void `serialize` (Archive &ar, const unsigned int version)
Serialize.
- void `random_structure` (int n, int k)
Random structure.

Private Attributes

- std::vector< std::vector< int > > `_neighbors`
Bit neighbors.
- std::vector< std::vector< double > > `_partial_functions`
Partial functions.

5.105.1 Detailed Description

NK landscape.

Reference:

S. A. Kauffman. 1993. The origins of order: self-organisation and selection in evolution. Oxford University Press.

Definition at line 45 of file [nk-landscape.hh](#).

5.105.2 Member Function Documentation

5.105.2.1 generate()

```
template<class Generator >
void generate (
    int n,
    int k,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vector
<i>k</i>	Number of neighbors per bit
<i>generator</i>	Generator for partial function values

Definition at line 89 of file [nk-landscape.hh](#).

5.105.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 126 of file [nk-landscape.hh](#).

5.105.2.3 random()

```
void random (
    int n,
    int k ) [inline]
```

Random instance.

Partial function values are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
<i>k</i>	Number of neighbors per bit

Definition at line 107 of file [nk-landscape.hh](#).

5.105.2.4 random_structure()

```
void random_structure (
    int n,
    int k ) [private]
```

Random structue.

Parameters

n	Size of bit vector
k	Number of neighbors per bit

Definition at line 34 of file [nk-landscape.cc](#).

5.105.2.5 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 133 of file [nk-landscape.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/nk-landscape.hh](#)
- [lib/hnco/functions/collection/nk-landscape.cc](#)

5.106 NpsPbil Class Reference

Population-based incremental learning with negative and positive selection.

```
#include <hnco/algorithms/probability-vector/nps-pbil.hh>
```

Inheritance diagram for NpsPbil:



Public Member Functions

- **NpsPbil** (int n, int population_size)
Constructor.

Setters

- void **set_selection_size** (int x)
Set the selection size.
- void **set_learning_rate** (double x)
Set the learning rate.

Public Member Functions inherited from **PvAlgorithm**

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [PvAlgorithm](#)

- void **set_something_to_log** ()
Set flag for something to log.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population.
- [pv_t](#) **_mean_best**
Mean of best individuals.
- [pv_t](#) **_mean_worst**
Mean of worst individuals.

Parameters

- int **_selection_size** = 1
Selection size.
- double **_learning_rate** = 1e-3
Learning rate.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t](#) **_pv**
Probability vector.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.
- bool **_log_entropy** = false
Log entropy.
- bool **_log_pv** = false
Log probability vector.
- int **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.106.1 Detailed Description

Population-based incremental learning with negative and positive selection.

Reference:

Arnaud Berny. 2001. Extending selection learning toward fixed-length d-ary strings. In Artificial Evolution (Lecture Notes in Computer Science), P. Collet and others (Eds.). Springer, Le Creusot.

Definition at line 42 of file [nps-pbil.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/probability-vector/nps-pbil.hh`
- `lib/hnco/algorithms/probability-vector/nps-pbil.cc`

5.107 Nsga2 Class Reference

NSGA-II.

```
#include <hnco/multiobjective/algorithms/nsga2.hh>
```

Inheritance diagram for Nsga2:



Public Member Functions

- [Nsga2](#) (int n, int num_objectives, int population_size)
Constructor.
- const [Population](#) & **get_solutions** () override
Get solutions.

Setters

- void [set_tournament_size](#) (int size)
- void **set_mutation_rate** (double rate)
Set the mutation rate.
- void **set_allow_no_mutation** (bool b)
Set the flag_allow_no_mutation.
- void **set_crossover_probability** (double p)
Set the crossover probability.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n, int num_objectives)
Constructor.
- void [minimize](#) (const std::vector< [Function](#) * > &functions) override
Minimize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- [Algorithm](#) (int n, int num_objectives)
Constructor.
- virtual \sim [Algorithm](#) ()
Destructor.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.

Protected Member Functions

Loop

- void [init](#) () override
- void [iterate](#) () override
Single iteration.
- void [finalize](#) () override
Finalize.
- void [log](#) () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [Function](#) * > &functions)
Set functions.

Protected Attributes

- [Population](#) _parents
Parent population.
- [Population](#) _offsprings
Offspring population.
- [Population](#) _full_population
Full population.
- [Population](#) _solutions
Solutions.
- [neighborhood::StandardBitMutation](#) _mutation
Mutation operator.
- std::bernoulli_distribution _do_crossover
Do crossover.
- [hnc::algorithm::UniformCrossover](#) _crossover
Uniform crossover.
- [Nsga2ParetoFrontComputation](#) _pareto_front_computation
Pareto front computation.
- std::vector< int > _pareto_fronts

- *Pareto fronts.*
- `std::vector< double > _crowding_distances`
Crowding distances.
- `hnco::permutation_t _permutation`
Permutation relative to Pareto front.
- `std::vector< FrontDistancePair > _front_distance_pairs`
Front distance pairs.
- `TournamentSelection< FrontDistancePair, std::less< FrontDistancePair > > _selection_by_front_distance_pair`
Selection by front distance pairs.

Parameters

- `int _tournament_size = 2`
- `double _mutation_rate`
Mutation rate.
- `bool _allow_no_mutation = false`
Allow no mutation.
- `double _crossover_probability = 0.8`
Crossover probability.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< Function * > _functions`
Functions.
- `Function * _function`
Function.
- `logging::LogContext * _log_context = nullptr`
Log context.

Additional Inherited Members

Public Types inherited from [Algorithm](#)

- using `Function` = `hnco::multiobjective::function::Function`
Function type.

5.107.1 Detailed Description

NSGA-II.

NSGA-II is a (mu+mu) evolutionary algorithm for multiobjective optimization.

Deb, Agrawal, Pratap, and Meyarivan, "A Fast Elitist Non-dominated Sorting Genetic %Algorithm for Multi-objective Optimization: NSGA-II", Parallel Problem Solving from Nature PPSN VI, 2000, Springer Berlin Heidelberg.

https://link.springer.com/chapter/10.1007/3-540-45356-3_83

Definition at line 79 of file [nsga2.hh](#).

5.107.2 Constructor & Destructor Documentation

5.107.2.1 Nsga2()

```
Nsga2 (
    int n,
    int num_objectives,
    int population_size ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>num_objectives</i>	Number of objectives
<i>population_size</i>	Population size

Definition at line 143 of file [nsga2.hh](#).

5.107.3 Member Function Documentation

5.107.3.1 init()

```
void init ( ) [override], [protected], [virtual]
```

Initialize

Reimplemented from [IterativeAlgorithm](#).

Definition at line 34 of file [nsga2.cc](#).

5.107.3.2 set_tournament_size()

```
void set_tournament_size (
    int size ) [inline]
```

Set the tournament size

Definition at line 167 of file [nsga2.hh](#).

5.107.4 Member Data Documentation

5.107.4.1 `_tournament_size`

```
int _tournament_size = 2 [protected]
```

Tournament size

Definition at line 113 of file [nsga2.hh](#).

The documentation for this class was generated from the following files:

- `lib/hnco/multiobjective/algorithms/nsga2.hh`
- `lib/hnco/multiobjective/algorithms/nsga2.cc`

5.108 Nsga2ParetoFrontComputation Class Reference

Pareto front computation from the NSGA-II paper.

```
#include <hnco/multiobjective/algorithms/pareto-front-computation.hh>
```

Public Member Functions

- **Nsga2ParetoFrontComputation** ([Population](#) &population)
Constructor.
- void [compute](#) (std::vector< int > &pareto_fronts)
Compute Pareto fronts.

Private Member Functions

- bool [is_non_dominated](#) (int i)
Check that a value is non dominated.

Private Attributes

- const [Population](#) & **_population**
Population
- std::vector< int > **_pool**
Pool of values to consider for inclusion in the Pareto front.
- std::vector< int > **_next_pool**
Next pool of values.
- std::unordered_set< int > **_non_dominated**
Non dominated values.
- std::vector< int > [_dominated](#)
Dominated values.

5.108.1 Detailed Description

Pareto front computation from the NSGA-II paper.

Definition at line 40 of file [pareto-front-computation.hh](#).

5.108.2 Member Function Documentation

5.108.2.1 compute()

```
void compute (
    std::vector< int > & pareto_fronts ) [inline]
```

Compute Pareto fronts.

Parameters

<i>pareto_fronts</i>	Pareto fronts (output parameter)
----------------------	----------------------------------

Definition at line 89 of file [pareto-front-computation.hh](#).

5.108.2.2 is_non_dominated()

```
bool is_non_dominated (
    int i ) [inline], [private]
```

Check that a value is non dominated.

Check that no value in the non dominated set dominates the considered value.

Parameters

<i>i</i>	Index of the value
----------	--------------------

Definition at line 67 of file [pareto-front-computation.hh](#).

5.108.3 Member Data Documentation

5.108.3.1 _dominated

```
std::vector<int> _dominated [private]
```

Dominated values.

To be removed from the non dominated ones.

Definition at line 58 of file [pareto-front-computation.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/multiobjective/algorithms/pareto-front-computation.hh](#)

5.109 OnBudgetFunction Class Reference

[Function](#) with a limited number of evaluations.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for OnBudgetFunction:



Public Member Functions

- **OnBudgetFunction** ([Function](#) *function, int budget)
Constructor.

Evaluation

- double [evaluate](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [evaluate_incrementally](#) (const [bit_vector_t](#) &bv, double value, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- void [update](#) (const [bit_vector_t](#) &bv, double value)
Update after a safe evaluation.

Public Member Functions inherited from [CallCounter](#)

- **CallCounter** ([Function](#) *function)
Constructor.
- int **get_num_calls** ()
Get the number of calls.

Public Member Functions inherited from [Controller](#)

- **Controller** ([Function](#) *function)
Constructor.
- int **get_bv_size** () const
Get bit vector size.
- double **get_maximum** () const
Get the global maximum.
- bool **has_known_maximum** () const
Check for a known maximum.
- bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- double **evaluate_safely** (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.

Private Attributes

- int **_budget**
Budget.

Additional Inherited Members

Protected Attributes inherited from [CallCounter](#)

- int **_num_calls**
Number of calls.

Protected Attributes inherited from [Decorator](#)

- [Function](#) * `_function`

Decorated function.

5.109.1 Detailed Description

[Function](#) with a limited number of evaluations.

Definition at line 195 of file [controller.hh](#).

5.109.2 Member Function Documentation

5.109.2.1 `evaluate()`

```
double evaluate (
    const bit\_vector\_t & bv ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 89 of file [controller.cc](#).

5.109.2.2 `evaluate_incrementally()`

```
double evaluate_incrementally (
    const bit\_vector\_t & bv,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [virtual]
```

Incrementally evaluate a bit vector.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 97 of file [controller.cc](#).

5.109.2.3 `update()`

```
void update (
```

```
const bit_vector_t & bv,
double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 105 of file [controller.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/controllers/controller.hh](#)
- [lib/hnco/functions/controllers/controller.cc](#)

5.110 OneMax Class Reference

OneMax.

```
#include <hnco/functions/collection/theory.hh>
```

Inheritance diagram for OneMax:



Public Member Functions

- **OneMax** (int bv_size)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **get_maximum** () const override
Get the global maximum.
- bool **has_known_maximum** () const override
Check for a known maximum.
- bool **provides_incremental_evaluation** () const override

Check whether the function provides incremental evaluation.

- void **display** (std::ostream &stream) const override

Display.

- double **evaluate** (const [bit_vector_t](#) &) override

Evaluate a bit vector.

- double **evaluate_incrementally** (const [bit_vector_t](#) &x, double v, const [hnco::sparse_bit_vector_t](#) &flipped↔_bits) override

Incrementally evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()

Destructor.

- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)

Safely evaluate a bit vector.

- virtual void [update](#) (const [bit_vector_t](#) &x, double value)

Update states after a safe evaluation.

- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)

Describe a bit vector.

Private Attributes

- int **_bv_size**

Bit vector size.

5.110.1 Detailed Description

OneMax.

Reference:

Heinz Mühlenbein, "How genetic algorithms really work: I. mutation and hillclimbing", in Proc. 2nd Int. Conf. on Parallel Problem Solving from Nature, 1992

Definition at line 38 of file [theory.hh](#).

5.110.2 Member Function Documentation

5.110.2.1 [get_maximum\(\)](#)

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

[_bv_size](#)

Reimplemented from [Function](#).

Definition at line 52 of file [theory.hh](#).

5.110.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 57 of file [theory.hh](#).

5.110.2.3 `provides_incremental_evaluation()`

```
bool provides_incremental_evaluation ( ) const [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 62 of file [theory.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/theory.hh
- lib/hnco/functions/collection/theory.cc

5.111 OnePlusLambdaCommaLambdaGa Class Reference

(1+(lambda, lambda)) genetic algorithm.

```
#include <hnco/algorithms/evolutionary-algorithms/one-plus-lambda-comma-lambda-ga.↵  
hh>
```

Inheritance diagram for OnePlusLambdaCommaLambdaGa:



Public Member Functions

- [OnePlusLambdaCommaLambdaGa](#) (int n, int lambda)
Constructor.

Setters

- void **set_mutation_rate** (double p)
Set the mutation rate.
- void **set_crossover_bias** (double x)
Set the crossover bias.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_offsprings**
Offsprings.
- std::binomial_distribution< int > **_radius_dist**
Radius distribution.
- [neighborhood::HammingSphere](#) **_mutation**
Mutation operator.
- [bit_vector_t](#) **_parent**
Parent.
- [BiasedCrossover](#) **_crossover**
Biased crossover.

Parameters

- double **_mutation_rate**
Mutation rate.
- double **_crossover_bias**
[Crossover](#) *bias.*

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.111.1 Detailed Description

(1+(lambda, lambda)) genetic algorithm.

Reference:

Benjamin Doerr, Carola Doerr, and Franziska Ebel. 2015. From black-box complexity to designing new genetic algorithms. *Theoretical Computer Science* 567 (2015), 87–104.

Definition at line 49 of file [one-plus-lambda-comma-lambda-ga.hh](#).

5.111.2 Constructor & Destructor Documentation

5.111.2.1 OnePlusLambdaCommaLambdaGa()

```
OnePlusLambdaCommaLambdaGa (
    int n,
    int lambda ) [inline]
```

Constructor.

By default, `_mutation_rate` is set to `lambda / n` and `_crossover_bias` to `1 / lambda`.

Parameters

<i>n</i>	Size of bit vectors
<i>lambda</i>	Offspring population size

Definition at line 102 of file [one-plus-lambda-comma-lambda-ga.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/one-plus-lambda-comma-lambda-ga.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/one-plus-lambda-comma-lambda-ga.cc](#)

5.112 OnePlusOneEa Class Reference

(1+1) EA.

```
#include <hnco/algorithms/evolutionary-algorithms/one-plus-one-ea.hh>
```

Inheritance diagram for OnePlusOneEa:



Public Member Functions

- [OnePlusOneEa](#) (int n)
Constructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void **finalize** () override
Finalize.

Setters

- void [set_num_iterations](#) (int x)
Set the number of iterations.
- void [set_mutation_rate](#) (double p)
Set the mutation rate.
- void [set_allow_no_mutation](#) (bool b)
Set the flag_allow_no_mutation.
- void [set_incremental_evaluation](#) (bool x)
Set incremental evaluation.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Attributes

- [neighborhood::StandardBitMutation](#) _neighborhood
Neighborhood.
- [RandomLocalSearch](#) _rls
Random local search.

Parameters

- int **_num_iterations** = 0
Number of iterations.
- double **_mutation_rate**
Mutation rate.
- bool **_allow_no_mutation** = false
Allow no mutation.
- bool **_incremental_evaluation** = false
Incremental evaluation.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.112.1 Detailed Description

(1+1) EA.

(1+1) EA is implemented as a [RandomLocalSearch](#) with a `StandardBitMutation` neighborhood and infinite patience. Thus the class [OnePlusOneEa](#) is derived from [Algorithm](#) instead of [IterativeAlgorithm](#).

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 45 of file [one-plus-one-ea.hh](#).

5.112.2 Constructor & Destructor Documentation

5.112.2.1 [OnePlusOneEa](#)()

```
OnePlusOneEa (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

`_mutation_rate` is initialized to $1 / n$.

Definition at line 80 of file [one-plus-one-ea.hh](#).

5.112.3 Member Function Documentation

5.112.3.1 [set_num_iterations](#)()

```
void set_num_iterations (
    int x ) [inline]
```

Set the number of iterations.

Parameters

<i>x</i>	Number of iterations
----------	----------------------

$x \leq 0$ means indefinite

Definition at line 111 of file [one-plus-one-ea.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/algorithms/evolutionary-algorithms/one-plus-one-ea.hh

5.113 OppositeAbsoluteValue< T > Struct Template Reference

Opposite absolute value of a scalar.

```
#include <hnco/functions/converter.hh>
```

Public Types

- using **codomain_type** = T
Codomain type.

Public Member Functions

- double **operator()** (T x)
Opposite absolute value.

5.113.1 Detailed Description

```
template<class T>
struct hnco::function::OppositeAbsoluteValue< T >
```

Opposite absolute value of a scalar.

Definition at line 50 of file [converter.hh](#).

The documentation for this struct was generated from the following file:


- lib/hnco/functions/converter.hh

5.114 OppositeFunction Class Reference

Opposite function.

```
#include <hnco/functions/modifiers/modifier.hh>
```

Inheritance diagram for OppositeFunction:



Public Member Functions

- **OppositeFunction** ([Function](#) *function)
Constructor.

Properties

- int [get_bv_size](#) () const override
- bool [provides_incremental_evaluation](#) () const override
Check whether the function provides incremental evaluation.

Evaluation

- double [evaluate](#) (const [bit_vector_t](#) &bv) override
- double **evaluate_incrementally** (const [bit_vector_t](#) &bv, double value, const [hnco::sparse_bit_vector_t](#) &flipped_bits) override
Incrementally evaluate a bit vector.

Public Member Functions inherited from [Modifier](#)

- **Modifier** ([Function](#) *function)
Constructor.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.114.1 Detailed Description

Opposite function.

Possible use cases:

- To minimize rather than maximize a function
- To apply an algorithm that minimizes rather than maximizes a function
- When minimization is needed inside an algorithm

Definition at line 51 of file [modifier.hh](#).

5.114.2 Member Function Documentation

5.114.2.1 evaluate()

```
double evaluate (
    const bit\_vector\_t & bv )  [override], [virtual]
```

Evaluate a bit vector

Implements [Function](#).

Definition at line 31 of file [modifier.cc](#).

5.114.2.2 get_bv_size()

```
int get_bv_size ( ) const  [inline], [override], [virtual]
```

Get bit vector size

Implements [Function](#).

Definition at line 63 of file [modifier.hh](#).

5.114.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) const  [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 68 of file [modifier.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/functions/modifiers/modifier.hh](#)
- [lib/hnco/functions/modifiers/modifier.cc](#)

5.115 OppositeSquaredMagnitude< T > Struct Template Reference

Opposite squared magnitude of a complex number.

```
#include <hnco/functions/converter.hh>
```


Public Types

- using **codomain_type** = std::complex< T >
Codomain type.

Public Member Functions

- double **operator()** (std::complex< T > z)
Opposite squared magnitude.

5.115.1 Detailed Description

template<class T>
struct hnco::function::OppositeSquaredMagnitude< T >

Opposite squared magnitude of a complex number.

Definition at line 68 of file [converter.hh](#).

The documentation for this struct was generated from the following file:


- lib/hnco/functions/converter.hh

5.116 ParameterLessPopulationPyramid Class Reference

Parameter-less Population Pyramid.

```
#include <hnco/algorithms/fast-efficient-p3/p3.hh>
```

Inheritance diagram for ParameterLessPopulationPyramid:



Public Member Functions

- **ParameterLessPopulationPyramid** (int n)
Constructor.
- **~ParameterLessPopulationPyramid** ()
Destructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions)
Maximize.
- void **finalize** ()
Finalize.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Attributes

- [Implementation](#) * **_implementation**
Pointer to implementation.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.116.1 Detailed Description

Parameter-less Population Pyramid.

Implementation of the Parameter-less Population Pyramid (P3 for short).

Author: Brian W. Goldman

Integrated into HNCO by Arnaud Berny

Reference:

"Fast and Efficient Black Box Optimization using the Parameter-less Population Pyramid" by B. W. Goldman and W. F. Punch

Definition at line 51 of file [p3.hh](#).

5.116.2 Member Data Documentation

5.116.2.1 `_implementation`

```
Implementation* _implementation [private]
```

Pointer to implementation.

The main motivation for this pattern is to avoid including declarations from [fast_efficient_p3](#) into the global namespace.

A raw pointer is used instead of a `unique_ptr` because the latter will not compile with pybind11.

Definition at line 61 of file [p3.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/fast-efficient-p3/p3.hh`
- `lib/hnco/algorithms/fast-efficient-p3/p3.cc`

5.117 ParsedModifier Class Reference

Parsed modifier.

```
#include <hnco/functions/modifiers/parsed-modifier.hh>
```

Inheritance diagram for ParsedModifier:



Public Member Functions

- [ParsedModifier](#) ([Function](#) *function, std::string expression)
Constructor.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.

Evaluation

- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Modifier](#)

- **Modifier** ([Function](#) *function)
Constructor.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Attributes

- FunctionParser **_fparser**
[Function](#) parser.
- double **_values** [1]
Array of values.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.117.1 Detailed Description

Parsed modifier.

Let f be the original function. Then the modified function is equivalent to $g \circ f$, where g is a real function defined by an expression $g(x)$ provided as a string.

Definition at line 40 of file [parsed-modifier.hh](#).

5.117.2 Constructor & Destructor Documentation

5.117.2.1 ParsedModifier()

```
ParsedModifier (
    Function * function,
    std::string expression )
```

Constructor.

Parameters

<i>function</i>	Decorated function
<i>expression</i>	Expression to parse

Definition at line 31 of file [parsed-modifier.cc](#).

The documentation for this class was generated from the following files:

- [lib/hnco/functions/modifiers/parsed-modifier.hh](#)
- [lib/hnco/functions/modifiers/parsed-modifier.cc](#)

5.118 ParsedMultivariateFunction< Parser > Class Template Reference

Parsed multivariate function.

```
#include <hnco/functions/collection/parsed-multivariate-function.hh>
```

Public Types

- using **domain_type** = typename Parser::value_type
Domain type.
- using **codomain_type** = typename Parser::value_type
Codomain type.

Public Member Functions

- [ParsedMultivariateFunction](#) (std::string expression)
Constructor.
- bool **add_constant** (std::string name, [domain_type](#) value)
Add a constant to the parser.
- void **parse** ()
Parse the expression.
- void **display** (std::ostream &stream) const
Display the problem.
- [codomain_type](#) **evaluate** (const std::vector< [domain_type](#) > &x)
Evaluate.
- void **describe** (const std::vector< [domain_type](#) > &x, std::ostream &stream)
Describe a solution.
- int **get_num_variables** ()
Get the number of variables.
- const std::vector< std::string > & **get_variable_names** ()
Get variable names.

Private Attributes

- Parser **_fparser**
Function parser
- std::vector< std::string > **_variable_names**
Variable names.
- std::string **_expression**
Expression.

5.118.1 Detailed Description

template<class Parser>
class hnco::function::ParsedMultivariateFunction< Parser >

Parsed multivariate function.

Uses the C++ library "Function Parser" (fparser):

<http://warp.povusers.org/FunctionParser/fparser.html>

Warning

The function string syntax depends on the chosen parser.

Definition at line 49 of file [parsed-multivariate-function.hh](#).

5.118.2 Constructor & Destructor Documentation

5.118.2.1 ParsedMultivariateFunction()

```
template<class Parser >
ParsedMultivariateFunction (
    std::string expression ) [inline]
```

Constructor.

Parameters

<i>expression</i>	Expression to parse
-------------------	---------------------

Definition at line 72 of file [parsed-multivariate-function.hh](#).

The documentation for this class was generated from the following file:

- [lib/hnco/functions/collection/parsed-multivariate-function.hh](#)

5.119 **ParsedMultivariateFunction**< **Parser** > Class Template Reference

Parsed multivariate function.

```
#include <hnco/multiojective/functions/collection/parsed-multivariate-function.↵
hh>
```

Public Types

- using **domain_type** = typename Parser::value_type
Domain type.
- using **codomain_type** = [domain_type](#)
Codomain type.

Public Member Functions

- [ParsedMultivariateFunction](#) (std::string expression)
Constructor.
- void **add_constant** (std::string name, [domain_type](#) value)
Add a constant to the parsers.
- void **parse** ()
Parse the expression.
- int **get_num_variables** () const
Get the number of variables.
- int **get_output_size** () const
Get output size (number of objectives)
- void **evaluate** (const std::vector< [domain_type](#) > &xs, std::vector< [codomain_type](#) > &values)
Evaluate.
- void **display** (std::ostream &stream) const
Display the problem.
- void **describe** (const std::vector< [domain_type](#) > &xs, std::ostream &stream)
Describe a solution.
- const std::vector< std::string > &**get_variable_names** ()
Get variable names.

Private Attributes

- `std::vector< std::string > _expressions`
Expressions.
- `std::vector< Parser > _parsers`
Function parsers
- `std::vector< std::vector< std::string > > _names`
Names.
- `std::vector< std::vector< domain_type > > _variables`
Variables.
- `std::vector< std::vector< int > > _indices`
Indices.
- `std::vector< std::string > _ordered_names`
Ordered variable names.

5.119.1 Detailed Description

```
template<class Parser>
class hnco::multiobjective::function::ParsedMultivariateFunction< Parser >
```

Parsed multivariate function.

Uses the C++ library "Function Parser" (fparser):

<http://warp.povusers.org/FunctionParser/fparser.html>

Warning

The function string syntax depends on the chosen parser.

Definition at line 54 of file `parsed-multivariate-function.hh`.

5.119.2 Constructor & Destructor Documentation

5.119.2.1 `ParsedMultivariateFunction()`

```
template<class Parser >
ParsedMultivariateFunction (
    std::string expression ) [inline]
```

Constructor.

An expression is a list of sub expressions separated by double colons (::). Each sub expression defines a multivariate function.

Parameters

<i>expression</i>	Expression to parse
-------------------	---------------------

Definition at line 114 of file [parsed-multivariate-function.hh](#).

5.119.3 Member Data Documentation

5.119.3.1 `_indices`

```
template<class Parser >
std::vector<std::vector<int> > _indices [private]
```

Indices.

Indexed by parser then variable. Then, `_indices[i][j]` is the index in the vector to evaluate of the *j*th variable of the *i*th parser.

Definition at line 95 of file [parsed-multivariate-function.hh](#).

5.119.3.2 `_names`

```
template<class Parser >
std::vector<std::vector<std::string> > _names [private]
```

Names.

Indexed by parser then variable. Then, `_names[i][j]` is the name of the *j*th variable of the *i*th parser.

Definition at line 78 of file [parsed-multivariate-function.hh](#).

5.119.3.3 `_ordered_names`

```
template<class Parser >
std::vector<std::string> _ordered_names [private]
```

Ordered variable names.

As expected by [evaluate\(\)](#).

Definition at line 102 of file [parsed-multivariate-function.hh](#).

5.119.3.4 `_variables`

```
template<class Parser >
std::vector<std::vector<domain_type> > _variables [private]
```

Variables.

Indexed by parser then variable. Then, `_variables[i][j]` is the value of the *j*th variable of the *i*th parser.

Definition at line 86 of file [parsed-multivariate-function.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/multiobjective/functions/collection/parsed-multivariate-function.hh`

5.120 Partition Class Reference

Partition.

```
#include <hnco/functions/collection/partition.hh>
```

Inheritance diagram for Partition:



Public Member Functions

- **Partition** ()
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Instance generators

- template<class Generator >
void **generate** (int n, Generator generator)
Instance generator.
- void **random** (int n, int upper_bound)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Display

- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.

Private Member Functions

- template<class Archive >
void `serialize` (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- `std::vector< int > _numbers`
Multiset of positive integers.

5.120.1 Detailed Description

Partition.

Partition a finite multiset of positive integers into two subsets such that the sum of numbers in the first subset is the closest to the sum of numbers in the second subset.

The function computes the negation of the distance between the sum of numbers corresponding to ones in the bit vector and the sum of those corresponding to zeros. The negation is a consequence of the fact that algorithms in HNCO maximize rather than minimize a function.

Definition at line 52 of file [partition.hh](#).

5.120.2 Member Function Documentation

5.120.2.1 `generate()`

```
template<class Generator >
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Number generator

Definition at line 84 of file [partition.hh](#).

5.120.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 120 of file [partition.hh](#).

5.120.2.3 random()

```
void random (
    int n,
    int upper_bound ) [inline]
```

Random instance.

The numbers are sampled from the uniform distribution on [1..upper_bound].

Parameters

<i>n</i>	Size of bit vector
<i>upper_bound</i>	Upper bound of positive integers

Definition at line 100 of file [partition.hh](#).

5.120.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 127 of file [partition.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/partition.hh
- lib/hnco/functions/collection/partition.cc

5.121 Pbil Class Reference

Population-based incremental learning.

```
#include <hnco/algorithms/probability-vector/pbil.hh>
```

Inheritance diagram for Pbil:



Public Member Functions

- **Pbil** (int n, int population_size)
Constructor.

Setters

- void **set_selection_size** (int x)
Set the selection size.
- void **set_learning_rate** (double x)
Set the learning rate.

Public Member Functions inherited from [PvAlgorithm](#)

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [PvAlgorithm](#)

- void **set_something_to_log** ()
Set flag for something to log.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population.
- [pv_t](#) **_mean**
Mean of selected bit vectors.

Parameters

- int **_selection_size** = 1
Selection size.
- double **_learning_rate** = 1e-3
Learning rate.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t_pv](#)
Probability vector.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.
- bool **_log_entropy** = false
Log entropy.
- bool **_log_pv** = false
Log probability vector.
- int **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t_solution](#)
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.121.1 Detailed Description

Population-based incremental learning.

Reference:

S. Baluja and R. Caruana. 1995. Removing the genetics from the standard genetic algorithm. In Proceedings of the 12th Annual Conference on Machine Learning. 38–46.

Definition at line 42 of file [pbil.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/probability-vector/pbil.hh
- lib/hnco/algorithms/probability-vector/pbil.cc

5.122 Permutation Class Reference

Permutation.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for Permutation:



Public Member Functions

- void **random** (int n)
Random instance.
- void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool [is_surjective](#) () const override
Check for surjective map.

Load and save map

- void [load](#) (std::string path)
Load map.
- void [save](#) (std::string path) const
Save map.

Public Member Functions inherited from [Map](#)

- virtual **~Map** ()
Destructor.
- virtual void **display** (std::ostream &stream) const
Display.

Private Member Functions

- `template<class Archive >`
void **save** (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
void **load** (Archive &ar, const unsigned int version)
Load.

Private Attributes

- `permutation_t _permutation`
Permutation.

5.122.1 Detailed Description

Permutation.

A permutation is a linear map f from F_2^n to itself defined by $f(x) = y$, where $y_i = x_{\sigma_i}$ and σ is a permutation of 0, 1, ..., $n - 1$.

Definition at line 166 of file [map.hh](#).

5.122.2 Member Function Documentation

5.122.2.1 is_surjective()

```
bool is_surjective ( ) const [inline], [override], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 217 of file [map.hh](#).

5.122.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 228 of file [map.hh](#).

5.122.2.3 save()

```
void save (
    std::string path ) const [inline]
```

Save map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 235 of file [map.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/maps/map.hh](#)
- [lib/hnco/maps/map.cc](#)

5.123 PermutationFunctionAdapter< Fn > Class Template Reference

Permutation function adapter.

```
#include <hnco/functions/permutation-function-adapter.hh>
```

Inheritance diagram for PermutationFunctionAdapter< Fn >:



Public Member Functions

- [PermutationFunctionAdapter](#) (Fn *fn, [representation::PermutationRepresentation](#) rep)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &bv) override
Evaluate.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Member Functions

- void **unpack** (const [bit_vector_t](#) &bv)
Unpack a bit vector into a permutation.

Private Attributes

- [Fn](#) * **_function**
Permutation function.
- [representation::PermutationRepresentation](#) **_representation**
Permutation representation.
- [permutation_t](#) **_permutation**
Permutation.

5.123.1 Detailed Description

```
template<class Fn>
class hnco::function::PermutationFunctionAdapter< Fn >
```

Permutation function adapter.

The purpose of this class is to build a regular hnco function from an arbitrary function over permutations. This is achieved using a permutation representation.

Definition at line 42 of file [permutation-function-adapter.hh](#).

5.123.2 Constructor & Destructor Documentation

5.123.2.1 PermutationFunctionAdapter()

```
template<class Fn >
PermutationFunctionAdapter (
    Fn * fn,
    representation::PermutationRepresentation rep ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Multivariate function
<i>rep</i>	Permutation representation

Definition at line 66 of file [permutation-function-adapter.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/functions/permutation-function-adapter.hh

5.124 PermutationRepresentation Class Reference

Permutation representation.

```
#include <hnco/representations/permutation.hh>
```

Public Member Functions

- [PermutationRepresentation](#) (int num_elements, int num_additional_bits)
Constructor.
- int **get_num_elements** () const
Get number of elements.
- int **size** () const
Size of the representation.
- void **unpack** (const [bit_vector_t](#) &bv, int start, [hnco::permutation_t](#) &permutation)
Unpack bit vector into a permutation.
- void **display** (std::ostream &stream) const
Display.

Private Attributes

- std::vector< int > **_values**
Values to be sorted.
- int **_element_size**
Element size in bits.
- int **_size**
Size in bits.

5.124.1 Detailed Description

Permutation representation.

Definition at line 39 of file [permutation.hh](#).

5.124.2 Constructor & Destructor Documentation

5.124.2.1 PermutationRepresentation()

```
PermutationRepresentation (  
    int num_elements,  
    int num_additional_bits ) [inline]
```

Constructor.

Each element is represented by an integer encoded using $\text{std::ceil}(\text{std::log}(\text{num_elements}) / \text{std::log}(2)) + \text{num_additional_bits}$.

Parameters

<i>num_elements</i>	Number of elements
<i>num_additional_bits</i>	Number of additional bits per element

Definition at line 62 of file [permutation.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/representations/permutation.hh`

5.125 Plateau Class Reference

Plateau.

```
#include <hnco/functions/collection/theory.hh>
```

Inheritance diagram for Plateau:



Public Member Functions

- **Plateau** (int bv_size)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual bool `provides_incremental_evaluation () const`
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally (const bit_vector_t &x, double value, const sparse_bit_vector_t &flipped_bits)`
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely (const bit_vector_t &x)`
Safely evaluate a bit vector.
- virtual void `update (const bit_vector_t &x, double value)`
Update states after a safe evaluation.
- virtual void `display (std::ostream &stream) const`
Display.
- virtual void `describe (const bit_vector_t &x, std::ostream &stream)`
Describe a bit vector.

Private Attributes

- int `_bv_size`
Bit vector size.

5.125.1 Detailed Description

Plateau.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 207 of file [theory.hh](#).

5.125.2 Member Function Documentation

5.125.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

`_bv_size + 2`

Reimplemented from [Function](#).

Definition at line 228 of file [theory.hh](#).

5.125.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 223 of file [theory.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/theory.hh
- lib/hnco/functions/collection/theory.cc

5.126 PlusSelection Class Reference

Plus selection.

```
#include <hnco/algorithms/evolutionary-algorithms/selection.hh>
```

Public Member Functions

- [PlusSelection](#) ([Population](#) &parents, [Population](#) &offsprings)
Constructor.
- void **select** ()
Apply selection.

Private Attributes

- [Population](#) & **_parents**
Parent population.
- [Population](#) & **_offsprings**
Offspring population.
- [Population](#) **_pool**
Union of parent and offspring population.

5.126.1 Detailed Description

Plus selection.

Used as selection for replacement in evolutionary algorithms.

Definition at line 78 of file [selection.hh](#).

5.126.2 Constructor & Destructor Documentation

5.126.2.1 PlusSelection()

```
PlusSelection (
    Population & parents,
    Population & offsprings ) [inline]
```

Constructor.

Parameters

<i>parents</i>	Parent population
<i>offsprings</i>	Offspring population

Definition at line 96 of file [selection.hh](#).

The documentation for this class was generated from the following file:

- `lib/hnco/algorithms/evolutionary-algorithms/selection.hh`

5.127 Population Struct Reference

Population

```
#include <hnco/algorithms/population.hh>
```

Public Types

- using **Function** = [hnco::function::Function](#)
Function type

Public Member Functions

- [Population](#) (int size, int n)
Constructor.
- void **random** ()
Sample a random population.

Properties

- int [get_size](#) () const
- int **get_bv_size** () const
Get bit vector size.

Evaluation and sorting

- void [evaluate](#) ([Function](#) *function)
- void **evaluate_in_parallel** (const std::vector< [Function](#) * > &functions)
Evaluate the population in parallel.
- void [sort](#) ()
Sort the population.
- void [partial_sort](#) (int selection_size)
Partially sort the population.
- std::pair< int, int > [get_equivalent_bvs](#) (int index) const
Get equivalent bit vectors.

Get sorted bit vectors

- [bit_vector_t](#) & [get_best_bv](#) ()
Get best bit vector.
- [bit_vector_t](#) & [get_best_bv](#) (int i)
Get best bit vector.
- [bit_vector_t](#) & [get_worst_bv](#) (int i)
Get worst bit vector.

Get sorted values

- double [get_best_value](#) () const
Get best value.
- double [get_best_value](#) (int i) const
Get best value.

Get sorted indices

- int [get_best_index](#) () const
Get best index.
- int [get_best_index](#) (int i) const
Get best index.

Public Attributes

- std::vector< [bit_vector_t](#) > **bvs**
Bit vectors.
- std::vector< double > **values**
Values.
- [hnco::permutation_t](#) **permutation**
Permutation.

5.127.1 Detailed Description

Population

Definition at line 38 of file [population.hh](#).

5.127.2 Constructor & Destructor Documentation

5.127.2.1 Population()

```
Population (
    int size,
    int n ) [inline]
```

Constructor.

Parameters

<i>size</i>	Population size
<i>n</i>	Bit vector size

Definition at line 53 of file [population.hh](#).

5.127.3 Member Function Documentation

5.127.3.1 evaluate()

```
void evaluate (
    Function * function )
```

Evaluate the population

Definition at line 43 of file [population.cc](#).

5.127.3.2 get_best_bv() [1/2]

```
bit_vector_t & get_best_bv ( ) [inline]
```

Get best bit vector.

Precondition

The population must be sorted.

Definition at line 130 of file [population.hh](#).

5.127.3.3 get_best_bv() [2/2]

```
bit_vector_t & get_best_bv (
    int i ) [inline]
```

Get best bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 136 of file [population.hh](#).

5.127.3.4 get_best_index() [1/2]

```
int get_best_index ( ) const [inline]
```

Get best index.

Precondition

The population must be sorted.

Definition at line 176 of file [population.hh](#).

5.127.3.5 get_best_index() [2/2]

```
int get_best_index (
    int i ) const [inline]
```

Get best index.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 182 of file [population.hh](#).

5.127.3.6 get_best_value() [1/2]

```
double get_best_value ( ) const [inline]
```

Get best value.

Precondition

The population must be sorted.

Definition at line 156 of file [population.hh](#).

5.127.3.7 get_best_value() [2/2]

```
double get_best_value (
    int i ) const [inline]
```

Get best value.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 162 of file [population.hh](#).

5.127.3.8 get_equivalent_bvs()

```
std::pair< int, int > get_equivalent_bvs (
    int index ) const
```

Get equivalent bit vectors.

This member function returns a pair of ints (a, b) such that,

- for all i in $[0, a)$, $f(\text{get_best_bv}(i)) > f(\text{get_best_bv}(\text{index}))$
- for all i in $[a, b)$, $f(\text{get_best_bv}(i)) = f(\text{get_best_bv}(\text{index}))$
- for all i in $[b, \text{size})$, $f(\text{get_best_bv}(i)) < f(\text{get_best_bv}(\text{index}))$

Put another way, the range $[a, b)$ is the equivalence class of index , where two indices i and j are equivalent if $f(\text{get_best_bv}(i)) = f(\text{get_best_bv}(j))$.

Parameters

<i>index</i>	Bit vector's index in the sorted population
--------------	---

Precondition

The population must be sorted.

Definition at line 72 of file [population.cc](#).

5.127.3.9 get_size()

```
int get_size ( ) const [inline]
```

Get population size

Definition at line 68 of file [population.hh](#).

5.127.3.10 get_worst_bv()

```
bit_vector_t & get_worst_bv (
    int i ) [inline]
```

Get worst bit vector.

Parameters

<i>i</i>	Backward index in the sorted population
----------	---

Precondition

The population must be sorted.

Definition at line 145 of file [population.hh](#).

5.127.3.11 partial_sort()

```
void partial_sort (
    int selection_size ) [inline]
```

Partially sort the population.

Only the permutation is sorted using the order defined by $i < j$ if $\text{values}[i] > \text{values}[j]$. Before sorting, the permutation is shuffled to break ties randomly.

Parameters

<i>selection_size</i>	Sort the best selection_size individuals
-----------------------	--

Definition at line 100 of file [population.hh](#).

5.127.3.12 sort()

```
void sort ( ) [inline]
```

Sort the population.

Only the permutation is sorted using the order defined by $i < j$ if $\text{values}[i] > \text{values}[j]$. Before sorting, the permutation is shuffled to break ties randomly.

Definition at line 89 of file [population.hh](#).

The documentation for this struct was generated from the following files:

- [lib/hnco/algorithms/population.hh](#)
- [lib/hnco/algorithms/population.cc](#)

5.128 Population Struct Reference**Population**

```
#include <hnco/multiobjective/algorithms/population.hh>
```


Public Types

- using **Function** = [hnco::multiobjective::function::Function](#)
Function type
- using **value_t** = [hnco::multiobjective::function::value_t](#)
Value type.

Public Member Functions

- **Population** ()=default
Default constructor.
- [Population](#) (int population_size, int bv_size, int num_objectives)
Constructor.
- int **get_size** () const
Get the population size.
- void [resize](#) (int population_size, int bv_size, int num_objectives)
Resize the population.
- void [shrink](#) (int population_size)
Shrink the population.
- void **random** ()
Sample a random population.
- void **evaluate** ([Function](#) *function)
Evaluate a population.
- void **evaluate_in_parallel** (const std::vector< [Function](#) * > &functions)
Evaluate a population in parallel.

Public Attributes

- std::vector< [bit_vector_t](#) > **bvs**
Bit vectors.
- std::vector< [value_t](#) > **values**
Values.

5.128.1 Detailed Description

Population

Definition at line 36 of file [population.hh](#).

5.128.2 Constructor & Destructor Documentation

5.128.2.1 Population()

```

Population (
    int population_size,
    int bv_size,
    int num_objectives ) [inline]

```

Constructor.

Parameters

<i>population_size</i>	Population size
<i>bv_size</i>	Size of bit vectors
<i>num_objectives</i>	Number of objectives

Definition at line 59 of file [population.hh](#).

5.128.3 Member Function Documentation

5.128.3.1 `resize()`

```
void resize (
    int population_size,
    int bv_size,
    int num_objectives ) [inline]
```

Resize the population.

Parameters

<i>population_size</i>	Population size
<i>bv_size</i>	Size of bit vectors
<i>num_objectives</i>	Number of objectives

Definition at line 80 of file [population.hh](#).

5.128.3.2 `shrink()`

```
void shrink (
    int population_size ) [inline]
```

Shrink the population.

If `population_size > get_size\(\)`, does nothing.

Parameters

<i>population_size</i>	Population size
------------------------	-----------------

Precondition

`population_size > 0`

Definition at line 100 of file [population.hh](#).

The documentation for this struct was generated from the following files:

- `lib/hnco/multiobjective/algorithms/population.hh`
- `lib/hnco/multiobjective/algorithms/population.cc`

5.129 DyadicIntegerRepresentation< T >::Precision Struct Reference

Precision

```
#include <hnco/representations/integer.hh>
```

Public Member Functions

- **Precision** (int [precision](#))
Constructor.

Public Attributes

- int **precision**
Precision.

5.129.1 Detailed Description

```
template<class T>  
struct hnco::representation::DyadicIntegerRepresentation< T >::Precision
```

Precision

Definition at line [103](#) of file [integer.hh](#).

The documentation for this struct was generated from the following file:


- lib/hnco/representations/integer.hh

5.130 PriorNoise Class Reference

Prior noise.

```
#include <hnco/functions/modifiers/prior-noise.hh>
```

Inheritance diagram for PriorNoise:



Public Member Functions

- **PriorNoise** ([Function](#) *fn, [neighborhood::Neighborhood](#) *nh)
Constructor.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.
- double **get_maximum** () const override
Get the global maximum.
- bool **has_known_maximum** () const override
Check for a known maximum.
- bool **provides_incremental_evaluation** () const override
Check whether the function provides incremental evaluation.

Evaluation

- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Modifier](#)

- **Modifier** ([Function](#) *function)
Constructor.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual ~**Function** ()
Destructor.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.

Private Attributes

- [neighborhood::Neighborhood](#) * **_neighborhood**
Neighborhood.
- [bit_vector_t](#) **_noisy_bv**
Noisy bit vector.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.130.1 Detailed Description

Prior noise.

Definition at line 37 of file [prior-noise.hh](#).

5.130.2 Member Function Documentation

5.130.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Delegation is questionable here.

Reimplemented from [Function](#).

Definition at line 69 of file [prior-noise.hh](#).

5.130.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Delegation is questionable here.

Reimplemented from [Function](#).

Definition at line 75 of file [prior-noise.hh](#).

5.130.2.3 `provides_incremental_evaluation()`

```
bool provides_incremental_evaluation ( ) const [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented from [Function](#).

Definition at line 79 of file [prior-noise.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/modifiers/prior-noise.hh](#)
- [lib/hnco/functions/modifiers/prior-noise.cc](#)

5.131 ProgressTracker Class Reference

Progress tracker.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for ProgressTracker:



Classes

- struct [Event](#)
Event

Public Member Functions

- **ProgressTracker** ([Function](#) *function)
Constructor.

Evaluation

- double **evaluate** (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double **evaluate_incrementally** (const [bit_vector_t](#) &bv, double value, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- void **update** (const [bit_vector_t](#) &bv, double value)

Update after a safe evaluation.

Get information

- const [Event](#) & [get_last_improvement](#) ()
Get the last improvement.
- double [get_evaluation_time](#) ()
Get evaluation time.

Setters

- void [set_log_improvement](#) (bool b)
Log improvement.
- void [set_record_evaluation_time](#) (bool b)
Record evaluation time.
- void [set_record_bit_vector](#) (bool b)
Record bit vector.

Public Member Functions inherited from [CallCounter](#)

- [CallCounter](#) ([Function](#) *function)
Constructor.
- int [get_num_calls](#) ()
Get the number of calls.

Public Member Functions inherited from [Controller](#)

- [Controller](#) ([Function](#) *function)
Constructor.
- int [get_bv_size](#) () const
Get bit vector size.
- double [get_maximum](#) () const
Get the global maximum.
- bool [has_known_maximum](#) () const
Check for a known maximum.
- bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- double [evaluate_safely](#) (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- [Decorator](#) ([Function](#) *function)
Constructor.
- void [display](#) (std::ostream &stream) const override
Display.
- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function()`
Destructor.

Protected Member Functions

- void `update_last_improvement` (const [bit_vector_t](#) &bv, double value)
Update last improvement.
- void `update_last_improvement_details` (const [bit_vector_t](#) &bv, double value)
Update last improvement (details)

Protected Attributes

- [Event](#) `_last_improvement`
Last improvement.
- [StopWatch](#) `_stop_watch`
Stop watch.

Parameters

- bool `_log_improvement` = false
Log improvement.
- bool `_record_evaluation_time` = false
Record evaluation time.
- bool `_record_bit_vector` = false
Record bit vector.

Protected Attributes inherited from [CallCounter](#)

- int `_num_calls`
Number of calls.

Protected Attributes inherited from [Decorator](#)

- [Function](#) * `_function`
Decorated function.

5.131.1 Detailed Description

Progress tracker.

A ProgressTracker is a [CallCounter](#) which keeps track of the last improvement, that is its value and the number of evaluations needed to reach it.

Definition at line 241 of file [controller.hh](#).

5.131.2 Member Function Documentation

5.131.2.1 `get_last_improvement()`

```
const Event & get_last_improvement ( ) [inline]
```

Get the last improvement.

Warning

If `_last_improvement.num_evaluations` is zero then `_function` has never been called. The [Event](#) returned by `get_last_improvement` has therefore no meaning.

Definition at line 331 of file [controller.hh](#).

5.131.3 Member Data Documentation

5.131.3.1 `_record_evaluation_time`

```
bool _record_evaluation_time = false [protected]
```

Record evaluation time.

Only relevant for [ProgressTracker::evaluate](#).

Definition at line 276 of file [controller.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/controllers/controller.hh](#)
- [lib/hnco/functions/controllers/controller.cc](#)

5.132 ProgressTrackerContext Class Reference

Log context for ProgressTracker.

```
#include <hnco/logging/log-context.hh>
```

Inheritance diagram for ProgressTrackerContext:



Public Member Functions

- **ProgressTrackerContext** ([function::controller::ProgressTracker](#) *pt)
Constructor.
- `std::string` [to_string](#) ()
Convert context to string.

Private Attributes

- [function::controller::ProgressTracker](#) * **_progress_tracker**
Progress tracker.

5.132.1 Detailed Description

Log context for ProgressTracker.

Definition at line 45 of file [log-context.hh](#).

5.132.2 Member Function Documentation

5.132.2.1 to_string()

```
std::string to_string ( ) [inline], [virtual]
```

Convert context to string.

Returns

A string made of the following information:

- Number of evaluations
- Number of evaluations to find the best so far solution
- Value of the best so far solution

Implements [LogContext](#).

Definition at line 61 of file [log-context.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/logging/log-context.hh`

5.133 Projection Class Reference

Projection.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for Projection:



Public Member Functions

- [Projection](#) (const std::vector< int > &bit_positions, int input_size)
Constructor.
- void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool [is_surjective](#) () const override
Check for surjective map.

Public Member Functions inherited from [Map](#)

- virtual **~Map** ()
Destructor.
- virtual void **display** (std::ostream &stream) const
Display.

Private Attributes

- std::vector< int > **_bit_positions**
Bit positions.
- int **_input_size**
Input size.

5.133.1 Detailed Description

Projection.

The projection y of a bit vector x is x where we have dropped a given set of components.

Let $I = \{i_1, i_2, \dots, i_m\}$ be a subset of $\{1, 2, \dots, n\}$.

A projection f from F_2^n to F_2^m , where $n \geq m$, is defined by $f(x) = y$, where, for all $j \in \{1, 2, \dots, m\}$, $y_j = x_{i_j}$.

If f is a projection and g is an injection with the same bit positions then their composition $f \circ g$ is the identity.

Definition at line 548 of file [map.hh](#).

5.133.2 Constructor & Destructor Documentation

5.133.2.1 Projection()

```
Projection (
    const std::vector< int > & bit_positions,
    int input_size )
```

Constructor.

The output size of the map is given by the size of `bit_positions`.

Parameters

<i>bit_positions</i>	Bit positions in the input from where output bits are copied
<i>input_size</i>	Input size

Precondition

```
input_size >= bit_positions.size()
```

Definition at line 175 of file [map.cc](#).

5.133.3 Member Function Documentation

5.133.3.1 is_surjective()

```
bool is_surjective ( ) const [inline], [override], [virtual]
```

Check for surjective map.

Returns

```
true
```

Reimplemented from [Map](#).

Definition at line 586 of file [map.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/maps/map.hh`
- `lib/hnco/maps/map.cc`

5.134 PvAlgorithm Class Reference

Probability vector algorithm.

```
#include <hnco/algorithms/probability-vector/pv-algorithm.hh>
```

Inheritance diagram for PvAlgorithm:



Public Member Functions

- **PvAlgorithm** (int n)

Constructor.

Setters for logging

- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **set_something_to_log** ()
Set flag for something to log.

Loop

- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **init** ()
Initialize.
- virtual void **iterate** ()=0
Single iteration.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- `pv_t_pv`
Probability vector.
- `double _lower_bound`
Lower bound of probability.
- `double _upper_bound`
Upper bound of probability.

Logging

- `bool _log_entropy = false`
Log entropy.
- `bool _log_pv = false`
Log probability vector.
- `int _log_num_components = 5`
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.134.1 Detailed Description

Probability vector algorithm.

Definition at line 33 of file [pv-algorithm.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/probability-vector/pv-algorithm.hh`
- `lib/hnco/algorithms/probability-vector/pv-algorithm.cc`

5.135 PythonFunction Class Reference

Python function.

```
#include <hnco/functions/collection/python-function.hh>
```

Inheritance diagram for PythonFunction:



Public Member Functions

- [PythonFunction](#) (std::string path, std::string name)
Constructor.
- [~PythonFunction](#) ()
Destructor.
- int [get_bv_size](#) () const override
Get bit vector size.
- bool [has_known_maximum](#) () const override
Check for a known maximum.
- double [get_maximum](#) () const override
Get the global maximum.
- double [evaluate](#) (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual [~Function](#) ()
Destructor.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void [display](#) (std::ostream &stream) const
Display.
- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- `pybind11::object _scope`
Module.
- `Function * _function`
Function.

5.135.1 Detailed Description

Python function.

Uses pybind11.

The constructor initializes the python interpreter and the destructor finalizes it.

The python code must import the `hnco` module (built separately) to allow for communication between C++ and python. It must also define a derived class that inherits `Function` and an instance of it.

Definition at line 46 of file `python-function.hh`.

5.135.2 Constructor & Destructor Documentation

5.135.2.1 PythonFunction()

```
PythonFunction (
    std::string path,
    std::string name )
```

Constructor.

Parameters

<i>path</i>	Path of the python file
<i>name</i>	Name of the <code>Function</code> instance defined in the python file

Definition at line 32 of file `python-function.cc`.

5.135.3 Member Function Documentation

5.135.3.1 get_maximum()

```
double get_maximum ( ) const [override], [virtual]
```

Get the global maximum.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Reimplemented from [Function](#).

Definition at line 59 of file [python-function.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/python-function.hh](#)
- [lib/hnco/functions/collection/python-function.cc](#)

5.136 PythonFunction Class Reference

Python function.

```
#include <hnco/multiobjective/functions/collection/python-function.hh>
```

Inheritance diagram for PythonFunction:



Public Member Functions

- [PythonFunction](#) (std::string path, std::string name)
Constructor.
- `~PythonFunction ()`
Destructor.
- `int get_bv_size () const`
Get bit vector size.
- `int get_output_size () const`
Get output size (number of objectives)
- `void evaluate` (const [bit_vector_t](#) &bv, [value_t](#) &value)
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- `virtual ~Function ()`
Destructor.
- `virtual void display` (std::ostream &stream) const
Display.
- `virtual void describe` (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- `pybind11::object _scope`
Module.
- `Function * _function`
Function.

5.136.1 Detailed Description

Python function.

Uses pybind11.

The constructor initializes the python interpreter and the destructor finalizes it.

The python code must import the `hnco` module (built separately) to allow for communication between C++ and python. It must also define a derived class that inherits `Function` and an instance of it.

Definition at line 48 of file `python-function.hh`.

5.136.2 Constructor & Destructor Documentation

5.136.2.1 PythonFunction()

```
PythonFunction (
    std::string path,
    std::string name )
```

Constructor.

Parameters

<i>path</i>	Path of the python file
<i>name</i>	Name of the <code>Function</code> instance defined in the python file

Definition at line 31 of file `python-function.cc`.

The documentation for this class was generated from the following files:


- `lib/hnco/multiobjective/functions/collection/python-function.hh`
- `lib/hnco/multiobjective/functions/collection/python-function.cc`

5.137 Qubo Class Reference

Quadratic unconstrained binary optimization.

```
#include <hnco/functions/collection/qubo.hh>
```

Inheritance diagram for Qubo:



Public Member Functions

- **Qubo** ()
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Load and save instance

- void [load](#) (std::string path)
Load instance.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const
Display.
- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- void [load](#) (std::istream &stream)
Load an instance.

Private Attributes

- std::vector< std::vector< double > > [_q](#)
Matrix.

5.137.1 Detailed Description

Quadratic unconstrained binary optimization.

Its expression is of the form $f(x) = \sum_i Q_{ii}x_i + \sum_{i<j} Q_{ij}x_ix_j = x^T Qx$, where Q is an n x n upper-triangular matrix.

[Qubo](#) is the problem addressed by qbsolv. Here is its description as given on github:

Qbsolv, a decomposing solver, finds a minimum value of a large quadratic unconstrained binary optimization (QUBO) problem by splitting it into pieces solved either via a D-Wave system or a classical tabu solver.

There are some differences between [WalshExpansion2](#) and [Qubo](#):

- [WalshExpansion2](#) maps 0/1 variables into -1/1 variables whereas [Qubo](#) directly deals with binary variables.
- Hence, there is a separate linear part in [WalshExpansion2](#) whereas the linear part in [Qubo](#) stems from the diagonal elements of the given matrix.

qbsolv aims at minimizing quadratic functions whereas hnco algorithms aim at maximizing them. Hence [Qubo::load](#) negates all elements so that maximizing the resulting function is equivalent to minimizing the original [Qubo](#).

References:

Michael Booth, Steven P. Reinhardt, and Aidan Roy. 2017. Partitioning Optimization Problems for Hybrid Classical/Quantum Execution. Technical Report. D-Wave.

<https://github.com/dwavesystems/qbsolv>

<http://people.brunel.ac.uk/~mastjjb/jeb/orlib/bqpinfo.html>

Definition at line 74 of file [qubo.hh](#).

5.137.2 Member Function Documentation

5.137.2.1 load() [1/2]

```
void load (
    std::istream & stream ) [private]
```

Load an instance.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 38 of file [qubo.cc](#).

5.137.2.2 load() [2/2]

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 105 of file [qubo.hh](#).

5.137.3 Member Data Documentation**5.137.3.1 _q**

```
std::vector<std::vector<double> > _q [private]
```

Matrix.

n x n upper triangular matrix.

Definition at line 82 of file [qubo.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/qubo.hh](#)
- [lib/hnco/functions/collection/qubo.cc](#)

5.138 RamUmda Class Reference

UMDA with random affine maps.

```
#include <hnco/algorithms/probability-vector/ram-umda.hh>
```

Inheritance diagram for RamUmda:



Classes

- struct [TsLengthMode](#)
Transvection sequence length mode.

Public Member Functions

- **RamUmda** (int n, int population_size)
Constructor.

Setters

- void [set_selection_size](#) (int n)
- void [set_ts_length_mode](#) (int n)
Set the transvection sequence length mode.
- void [set_ts_length](#) (int n)
Set the transvection sequence length.
- void [set_ts_length_lower_bound](#) (int n)

- *Set the lower bound for the transvection sequence length.*
- void **set_ts_length_upper_bound** (int n)
Set the upper bound for the transvection sequence length.
- void **set_ts_length_increment_period** (int n)
Set the transvection sequence length increment (or decrement) period.
- void **set_ts_length_distribution_parameter** (double f)
Set the parameter of the geometric distribution of the transvection sequence length.

Public Member Functions inherited from [PvAlgorithm](#)

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **compute_ts_length** ()
Compute the transvection sequence length.

Loop

- void **init** () override
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [PvAlgorithm](#)

- void **set_something_to_log** ()
Set flag for something to log.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population_x**
Population in the x space.
- [Population](#) **_population_y**
Population in the y space.
- [map::TsAffineMap](#) **_map**
Transvection sequence affine map.
- [map::TsAffineMap](#) **_inverse_map**
Inverse transvection sequence affine map.
- [bit_vector_t](#) **_a**
Temporary bit vector.
- [bit_vector_t](#) **_b**
Temporary bit vector.
- [bit_vector_t](#) **_c**
Temporary bit vector.

Parameters

- `int` **_selection_size** = 10
- `int` **_ts_length_mode** = [TsLengthMode::constant](#)
Transvection sequence length mode.
- `int` **_ts_length** = 10
Transvection sequence length.
- `int` **_ts_length_lower_bound** = 0
Lower bound for the transvection sequence length.
- `int` **_ts_length_upper_bound** = 20
Upper bound for the transvection sequence length.
- `int` **_ts_length_increment_period** = 10000
Transvection sequence length increment (or decrement) period.
- `double` **_ts_length_distribution_parameter** = 0.1
Parameter of the geometric distribution of the transvection sequence length.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t](#) **_pv**
Probability vector.
- `double` **_lower_bound**
Lower bound of probability.
- `double` **_upper_bound**
Upper bound of probability.
- `bool` **_log_entropy** = false
Log entropy.
- `bool` **_log_pv** = false
Log probability vector.
- `int` **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- **int `_iteration`**
Current iteration.
- **bool `_last_iteration` = false**
Last iteration.
- **bool `_something_to_log` = false**
Something to log.
- **int `_num_iterations` = 0**
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- **std::vector< [function::Function](#) * > `_functions`**
Functions.
- **[function::Function](#) * `_function`**
Function.
- **[solution_t](#) `_solution`**
Solution.
- **[logging::LogContext](#) * `_log_context` = nullptr**
Log context.

5.138.1 Detailed Description

UMDA with random affine maps.

`_pv` is the probability vector in the latent space.

Definition at line 35 of file [ram-umda.hh](#).

5.138.2 Member Function Documentation

5.138.2.1 `init()`

```
void init ( ) [override], [protected], [virtual]
```

Initialize

Reimplemented from [IterativeAlgorithm](#).

Reimplemented in [RamUmda2](#).

Definition at line 35 of file [ram-umda.cc](#).

5.138.2.2 set_selection_size()

```
void set_selection_size (
    int n ) [inline]
```

Set the selection size

Definition at line 69 of file [ram-umda.hh](#).

5.138.3 Member Data Documentation

5.138.3.1 _selection_size

```
int _selection_size = 10 [protected]
```

Selection size

Definition at line 104 of file [ram-umda.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/probability-vector/ram-umda.hh](#)
- [lib/hnco/algorithms/probability-vector/ram-umda.cc](#)

5.139 RamUmda2 Class Reference

UMDA with random affine maps and two probability vectors.

```
#include <hnco/algorithms/probability-vector/ram-umda.hh>
```

Inheritance diagram for RamUmda2:



Public Member Functions

- **RamUmda2** (int n, int population_size)

Constructor.

Setters

- void **set_crossover_probability** (double p)
- void **set_latent_space_probability** (double p)
Set the probability of sampling from the latent space.

Public Member Functions inherited from **RamUmda**

- **RamUmda** (int n, int population_size)
Constructor.
- void **set_selection_size** (int n)
- void **set_ts_length_mode** (int n)
Set the transvection sequence length mode.
- void **set_ts_length** (int n)
Set the transvection sequence length.
- void **set_ts_length_lower_bound** (int n)
Set the lower bound for the transvection sequence length.
- void **set_ts_length_upper_bound** (int n)
Set the upper bound for the transvection sequence length.
- void **set_ts_length_increment_period** (int n)
Set the transvection sequence length increment (or decrement) period.
- void **set_ts_length_distribution_parameter** (double f)
Set the parameter of the geometric distribution of the transvection sequence length.

Public Member Functions inherited from **PvAlgorithm**

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from **IterativeAlgorithm**

- **IterativeAlgorithm** (int n)
Constructor.
- void **maximize** (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void **set_num_iterations** (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Member Functions

Loop

- void **init** () override
- void **iterate** () override
Single iteration.

Private Attributes

- [pv_t_pv_y](#)
Probability vector in the latent space.

Parameters

- double [_crossover_probability](#) = 0.1
- double [_latent_space_probability](#) = 0.5
Probability of sampling from the latent space.

Additional Inherited Members

Protected Member Functions inherited from [RamUmda](#)

- void **compute_ts_length** ()
Compute the transvection sequence length.

Protected Member Functions inherited from [PvAlgorithm](#)

- void **set_something_to_log** ()
Set flag for something to log.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void [set_solution](#) (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void [update_solution](#) (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [RamUmda](#)

- [Population](#) **_population_x**
Population in the x space.
- [Population](#) **_population_y**
Population in the y space.
- [map::TsAffineMap](#) **_map**
Transvection sequence affine map.
- [map::TsAffineMap](#) **_inverse_map**
Inverse transvection sequence affine map.
- [bit_vector_t](#) **_a**
Temporary bit vector.
- [bit_vector_t](#) **_b**
Temporary bit vector.
- [bit_vector_t](#) **_c**
Temporary bit vector.
- int **_selection_size** = 10
- int **_ts_length_mode** = [TsLengthMode::constant](#)
Transvection sequence length mode.
- int **_ts_length** = 10
Transvection sequence length.
- int **_ts_length_lower_bound** = 0
Lower bound for the transvection sequence length.
- int **_ts_length_upper_bound** = 20
Upper bound for the transvection sequence length.
- int **_ts_length_increment_period** = 10000
Transvection sequence length increment (or decrement) period.
- double **_ts_length_distribution_parameter** = 0.1
Parameter of the geometric distribution of the transvection sequence length.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t_pv](#)
Probability vector.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.
- bool **_log_entropy** = false
Log entropy.
- bool **_log_pv** = false
Log probability vector.
- int **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.139.1 Detailed Description

UMDA with random affine maps and two probability vectors.

`_pv` is the probability vector in the solution space. `_pv_y` is the probability vector in the latent space.

Definition at line 136 of file [ram-umda.hh](#).

5.139.2 Member Function Documentation

5.139.2.1 `init()`

```
void init ( ) [override], [private], [virtual]
```

Initialize

Reimplemented from [RamUmda](#).

Definition at line 126 of file [ram-umda.cc](#).

5.139.2.2 `set_crossover_probability()`

```
void set_crossover_probability (
    double p ) [inline]
```

Set the crossover probability

Definition at line 148 of file [ram-umda.hh](#).

5.139.3 Member Data Documentation

5.139.3.1 `_crossover_probability`

```
double _crossover_probability = 0.1 [private]
```

[Crossover](#) probability

Definition at line 161 of file [ram-umda.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/probability-vector/ram-umda.hh](#)
- [lib/hnco/algorithms/probability-vector/ram-umda.cc](#)

5.140 RandomLocalSearch Class Reference

Random local search.

```
#include <hnco/algorithms/local-search/random-local-search.hh>
```

Inheritance diagram for RandomLocalSearch:



Public Member Functions

- **RandomLocalSearch** (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void **finalize** () override
Finalize.

Setters

- void **set_compare** (std::function< bool(double, double)> x)
Set the binary operator for comparing evaluations.
- void **set_patience** (int x)
Set patience.
- void **set_incremental_evaluation** (bool x)
Set incremental evaluation.

Public Member Functions inherited from

[LocalSearchAlgorithm](#)< [neighborhood::Neighborhood](#) >

- **LocalSearchAlgorithm** (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void **set_random_initialization** (bool b)
Set random initialization.
- void **set_starting_point** (const [bit_vector_t](#) &x)
Set the starting point.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **iterate_full** ()
Single iteration with full evaluation.
- void **iterate_incremental** ()
Single iteration with incremental evaluation.

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Loop

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- int **_num_failures**
Number of failure.

Parameters

- std::function< bool(double, double)> **_compare** = std::greater_equal<double>()
Binary operator for comparing evaluations.
- int **_patience** = 50
Patience.
- bool **_incremental_evaluation** = false
Incremental evaluation.

Protected Attributes inherited from [LocalSearchAlgorithm](#)< [neighborhood::Neighborhood](#) >

- [bit_vector_t](#) **_starting_point**
Starting point.
- [neighborhood::Neighborhood](#) * **_neighborhood**
Neighborhood.
- bool **_random_initialization**
Random initialization.

Protected Attributes inherited from [IterativeAlgorithm](#)

- **int `_iteration`**
Current iteration.
- **bool `_last_iteration` = false**
Last iteration.
- **bool `_something_to_log` = false**
Something to log.
- **int `_num_iterations` = 0**
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- **std::vector< [function::Function](#) * > `_functions`**
Functions.
- **[function::Function](#) * `_function`**
Function.
- **[solution_t](#) `_solution`**
Solution.
- **[logging::LogContext](#) * `_log_context` = nullptr**
Log context.

5.140.1 Detailed Description

Random local search.

Definition at line 36 of file [random-local-search.hh](#).

5.140.2 Member Function Documentation

5.140.2.1 `set_patience()`

```
void set_patience (
    int x ) [inline]
```

Set patience.

Number of consecutive rejected moves before ending the search.

Parameters

<code>x</code>	Patience
----------------	----------

If $x \leq 0$ then patience is considered infinite.

Definition at line 104 of file [random-local-search.hh](#).

5.140.3 Member Data Documentation

5.140.3.1 `_patience`

```
int _patience = 50 [protected]
```

Patience.

Number of consecutive rejected moves before ending the search.

Definition at line 55 of file [random-local-search.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/local-search/random-local-search.hh`
- `lib/hnco/algorithms/local-search/random-local-search.cc`

5.141 RandomSearch Class Reference

Random search.

```
#include <hnco/algorithms/random-search.hh>
```

Inheritance diagram for RandomSearch:



Public Member Functions

- **RandomSearch** (int n)
Constructor.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [bit_vector_t](#) **_candidate**
Candidate.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.141.1 Detailed Description

Random search.

Definition at line 31 of file [random-search.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/random-search.hh](#)
- [lib/hnco/algorithms/random-search.cc](#)

5.142 RandomSelection Class Reference

Random selection.

```
#include <hnco/algorithms/evolutionary-algorithms/random-selection.hh>
```

Inheritance diagram for RandomSelection:



Public Member Functions

- [RandomSelection](#) (const [Population](#) &population)
Constructor.
- virtual void **init** ()
Initialize.
- virtual const [bit_vector_t](#) & **select** ()=0
Select an individual in the population.

Protected Attributes

- const [Population](#) & **_population**
Population to select from

5.142.1 Detailed Description

Random selection.

Used as selection for reproduction in evolutionary algorithms.

Definition at line 38 of file [random-selection.hh](#).

5.142.2 Constructor & Destructor Documentation

5.142.2.1 RandomSelection()

```
RandomSelection (
    const Population & population ) [inline]
```

Constructor.

Parameters

<i>population</i>	Population to select from
-------------------	---------------------------

Definition at line 48 of file [random-selection.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/algorithms/evolutionary-algorithms/random-selection.hh](#)

5.143 RandomWalk Class Reference

Random walk.

```
#include <hnco/algorithms/local-search/random-walk.hh>
```

Inheritance diagram for RandomWalk:



Public Member Functions

- **RandomWalk** (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.

Setters

- void **set_incremental_evaluation** (bool x)
Set incremental evaluation.
- void **set_log_value** ()
Set log.

Public Member Functions inherited from [LocalSearchAlgorithm< neighborhood::Neighborhood >](#)

- **LocalSearchAlgorithm** (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void **set_random_initialization** (bool b)
Set random initialization.
- void **set_starting_point** (const [bit_vector_t](#) &x)
Set the starting point.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **iterate_full** ()
Single iteration with full evaluation.
- void **iterate_incremental** ()
Single iteration with incremental evaluation.

Loop

- void **iterate** () override
Single iteration.
- void **log** () override
Log.

Protected Member Functions inherited from [LocalSearchAlgorithm](#)< [neighborhood::Neighborhood](#) >

- void **init** () override
Initialize.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void [set_solution](#) (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void [update_solution](#) (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- double **_value**
Value of the last visited bit vector.

Parameters

- bool **_incremental_evaluation** = false
Incremental evaluation.

Protected Attributes inherited from [LocalSearchAlgorithm](#)< [neighborhood::Neighborhood](#) >

- [bit_vector_t](#) **_starting_point**
Starting point.
- [neighborhood::Neighborhood](#) * **_neighborhood**
Neighborhood.
- bool **_random_initialization**
Random initialization.

Protected Attributes inherited from [IterativeAlgorithm](#)

- **int `_iteration`**
Current iteration.
- **bool `_last_iteration`** = false
Last iteration.
- **bool `_something_to_log`** = false
Something to log.
- **int `_num_iterations`** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- **std::vector< [function::Function](#) * > `_functions`**
Functions.
- **[function::Function](#) * `_function`**
Function.
- **[solution_t](#) `_solution`**
Solution.
- **[logging::LogContext](#) * `_log_context`** = nullptr
Log context.

5.143.1 Detailed Description

Random walk.

The algorithm simply performs a random walk on the graph implicitly given by the neighborhood. At each iteration, the chosen neighbor does not depend on its evaluation. However optimization takes place as in random search, that is the best visited bit vector is remembered.

Definition at line 41 of file [random-walk.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/algorithms/local-search/random-walk.hh](#)
- [lib/hnco/algorithms/local-search/random-walk.cc](#)

5.144 InformationTheoreticEa::Replacement Struct Reference

Selection for replacement.

```
#include <hnco/algorithms/evolutionary-algorithms/it-ea.hh>
```

Public Types

- enum {
[elitist](#) = 0 , [non_elitist](#) = 1 , [ml_update](#) = 2 , [incremental_ml_update](#) = 3 ,
[no_replacement](#) = 4 }

5.144.1 Detailed Description

Selection for replacement.

Definition at line 19 of file [it-ea.hh](#).

5.144.2 Member Enumeration Documentation

5.144.2.1 anonymous enum

anonymous enum

Enumerator

elitist	Elitist replacement.
non_elitist	Non elitist replacement.
ml_update	Maximum likelihood update.
incremental_ml_update	Incremental maximum likelihood update.
no_replacement	No replacement (static search)

Definition at line 20 of file [it-ea.hh](#).

The documentation for this struct was generated from the following file:

- lib/hnco/algorithms/evolutionary-algorithms/it-ea.hh

5.145 BmPbil< GibbsSampler >::ResetMode Struct Reference

Markov chain reset mode.

```
#include <hnco/algorithms/walsh-moment/bm-pbil.hh>
```

Public Types

- enum { [no_reset](#) , [iteration](#) , [bit_vector](#) }

5.145.1 Detailed Description

```
template<class GibbsSampler>
struct hnco::algorithm::walsh_moment::BmPbil< GibbsSampler >::ResetMode
```

Markov chain reset mode.

Definition at line 76 of file [bm-pbil.hh](#).

5.145.2 Member Enumeration Documentation

5.145.2.1 anonymous enum

```
template<class GibbsSampler >
anonymous enum
```

Enumerator

no_reset	No reset.
iteration	Reset the Markov chain at the beginning of each iteration.
bit_vector	Reset the Markov chain before sampling each bit vector.

Definition at line 77 of file [bm-pbil.hh](#).

The documentation for this struct was generated from the following file:


- [lib/hnco/algorithms/walsh-moment/bm-pbil.hh](#)

5.146 Restart Class Reference

Restart.

```
#include <hnco/algorithms/decorators/restart.hh>
```

Inheritance diagram for Restart:



Public Member Functions

- **Restart** ([Algorithm](#) *algorithm)
Constructor.

Optimization

- void **maximize** (const std::vector< [function::Function](#) * > &functions) override
Maximize.

Setters

- void **set_num_iterations** (int n)
Set the number of iterations.

Public Member Functions inherited from [Decorator](#)

- [Decorator](#) ([Algorithm](#) *algorithm)
Constructor.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void **finalize** ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Member Functions

- void **iterate** (bool first_iteration)
Iterate.

Private Attributes

- int **_num_iterations** = 0
Number of iterations.

Additional Inherited Members

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [Decorator](#)

- [Algorithm](#) * **_algorithm**
Decorated algorithm.

Protected Attributes inherited from [Algorithm](#)

- std::vector< [function::Function](#) * > **_functions**
Functions.
- [function::Function](#) * **_function**
Function.
- [solution_t](#) **_solution**
Solution.
- [logging::LogContext](#) * **_log_context** = nullptr
Log context.

5.146.1 Detailed Description

Restart.

Restart an algorithm an indefinite number of times. The Restart decorator can be used in conjunction with On↔ BudgetFunction or StopOnMaximum.

Definition at line 38 of file [restart.hh](#).

5.146.2 Member Function Documentation

5.146.2.1 iterate()

```
void iterate (
    bool first_iteration ) [private]
```

Iterate.

Parameters

<i>first_iteration</i>	Boolean which is true if this is the first iteration.
------------------------	---

Definition at line 29 of file [restart.cc](#).

5.146.2.2 set_num_iterations()

```
void set_num_iterations (
    int n ) [inline]
```

Set the number of iterations.

Parameters

<i>n</i>	Number of iterations
----------	----------------------

Warning

$n \leq 0$ means indefinite

Definition at line 79 of file [restart.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/decorators/restart.hh](#)
- [lib/hnco/algorithms/decorators/restart.cc](#)

5.147 Ridge Class Reference

Ridge.

```
#include <hnco/functions/collection/theory.hh>
```

Inheritance diagram for Ridge:



Public Member Functions

- **Ridge** (int bv_size)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const
Display.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int **_bv_size**
Bit vector size.

5.147.1 Detailed Description

Ridge.

Reference:

R. J. Quick, V. J. Rayward-Smith, and G. D. Smith. Fitness distance correlation and Ridge functions. Parallel Problem Solving from Nature — PPSN V, Springer Berlin Heidelberg, 1998.

Definition at line 176 of file [theory.hh](#).

5.147.2 Member Function Documentation

5.147.2.1 `get_maximum()`

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

`2 * _bv_size`

Reimplemented from [Function](#).

Definition at line 197 of file [theory.hh](#).

5.147.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 192 of file [theory.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/functions/collection/theory.hh](#)
- [lib/hnco/functions/collection/theory.cc](#)

5.148 `BmPbil< GibbsSampler >::SamplingMode` Struct Reference

Markov chain sampling mode.

```
#include <hnco/algorithms/walsh-moment/bm-pbil.hh>
```

Public Types

- enum { [asynchronous](#) , [asynchronous_full_scan](#) , [synchronous](#) }

5.148.1 Detailed Description

```
template<class GibbsSampler>
```

```
struct hnco::algorithm::walsh_moment::BmPbil< GibbsSampler >::SamplingMode
```

Markov chain sampling mode.

Definition at line 50 of file [bm-pbil.hh](#).

5.148.2 Member Enumeration Documentation

5.148.2.1 anonymous enum

```
template<class GibbsSampler >
```

```
anonymous enum
```

Enumerator

asynchronous	Asynchronous sampling. A single component of the internal state is randomly selected then updated by Gibbs sampling. This step is repeated <code>_num_gs_steps</code> times.
asynchronous_full_scan	Asynchronous sampling with full scan. To sample a new bit vector, a random permutation is sampled and all components of the internal state are updated by Gibbs sampling in the order defined by the permutation.
synchronous	Synchronous sampling. The full internal state is updated in one step from the probability vector made of the very marginal probabilities used in Gibbs sampling.

Definition at line 51 of file [bm-pbil.hh](#).

The documentation for this struct was generated from the following file:

- `lib/hnco/algorithms/walsh-moment/bm-pbil.hh`

5.149 TsAffineMap::SamplingMode Struct Reference

Sampling mode.

```
#include <hnco/maps/map.hh>
```

Public Types

- enum [mode](#) {
[unconstrained](#) , [commuting_transvections](#) , [unique_source](#) , [unique_destination](#) ,
[disjoint_transvections](#) , [non_commuting_transvections](#) }

5.149.1 Detailed Description

Sampling mode.

Definition at line 628 of file [map.hh](#).

5.149.2 Member Enumeration Documentation

5.149.2.1 mode

```
enum mode
```

Enumerator

unconstrained	Unconstrained.
commuting_transvections	Commuting transvections.
unique_source	Transvection sequence with unique source
unique_destination	Transvection sequence with unique destination
disjoint_transvections	Disjoint transvections.
non_commuting_transvections	Non commuting transvections.

Definition at line 629 of file [map.hh](#).

The documentation for this struct was generated from the following file:

- [lib/hnco/maps/map.hh](#)

5.150 ScalarToDouble< T > Struct Template Reference

Convert a scalar to a double.

```
#include <hnco/functions/converter.hh>
```

Public Types

- using **codomain_type** = T
Codomain type.

Public Member Functions

- double **operator()** (T x)
Convert to double.

5.150.1 Detailed Description

```
template<class T>  
struct hnco::function::ScalarToDouble< T >
```

Convert a scalar to a double.

Definition at line 32 of file [converter.hh](#).

The documentation for this struct was generated from the following file:


- [lib/hnco/functions/converter.hh](#)

5.151 SelfAdjustingOnePlusOneEa Class Reference

Self-adjusting (1+1) evolutionary algorithm.

```
#include <hnco/algorithms/evolutionary-algorithms/self-adjusting-one-plus-one-ea.h>
hh>
```

Inheritance diagram for SelfAdjustingOnePlusOneEa:



Public Member Functions

- **SelfAdjustingOnePlusOneEa** (int n)
Constructor.
- void **finalize** () override
Finalize.

Setters

- void **set_mutation_rate_init** (double p)
Set the initial mutation rate.
- void **set_mutation_rate_min** (double p)
Set the minimum mutation rate.
- void **set_mutation_rate_max** (double p)
Set the maximum mutation rate.
- void **set_update_strength** (double x)
Set update strength.
- void **set_success_ratio** (double x)
Set success ratio.
- void **set_allow_no_mutation** (bool b)
Allow no mutation.
- void **set_incremental_evaluation** (bool b)
Turn on incremental evaluation.

Setters for logging

- void **set_log_mutation_rate** (bool b)
Log mutation rate.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual ~**Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Private Member Functions

- void **iterate_full** ()
Single iteration with full evaluation.
- void **iterate_incremental** ()
Single iteration with incremental evaluation.
- void **set_something_to_log** ()
Set flag for something to log.

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.
- void **log** () override
Log.

Private Attributes

- [neighborhood::StandardBitMutation](#) **_mutation**
Mutation operator.
- double **_mutation_rate**
Mutation rate.
- double **_coefficient**
Update strength to the power the success rate.

Parameters

- double **_mutation_rate_init**
Initial mutation rate.
- double **_mutation_rate_min**
Minimum mutation rate.
- double **_mutation_rate_max** = 0.5
Maximum mutation rate.
- double **_success_ratio** = 4
Success ratio.
- double **_update_strength**
Update strength.
- bool **_allow_no_mutation** = false
Allow no mutation.
- bool **_incremental_evaluation** = false
Incremental evaluation.

Logging

- bool **_log_mutation_rate** = false
Log mutation rate.

Additional Inherited Members

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.151.1 Detailed Description

Self-adjusting (1+1) evolutionary algorithm.

Reference: Benjamin Doerr, Carola Doerr, and Johannes Lengler. 2019. Self-adjusting mutation rates with provably optimal success rules. In Proceedings of the Genetic and Evolutionary Computation Conference (GECCO '19). Association for Computing Machinery, New York, NY, USA, 1479–1487. <https://doi.org/10.1145/3321707.3321733>

Definition at line 41 of file [self-adjusting-one-plus-one-ea.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/evolutionary-algorithms/self-adjusting-one-plus-one-ea.hh`
- `lib/hnco/algorithms/evolutionary-algorithms/self-adjusting-one-plus-one-ea.cc`

5.152 SimulatedAnnealing Class Reference

Simulated annealing.

```
#include <hnco/algorithms/local-search/simulated-annealing.hh>
```

Inheritance diagram for SimulatedAnnealing:



Public Member Functions

- **SimulatedAnnealing** (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.

Setters

- void **set_num_transitions** (int x)
Set the number of accepted transitions before annealing.
- void **set_num_trials** (int x)
Set the Number of trials.
- void **set_initial_acceptance_probability** (double x)
Set the initial acceptance probability.
- void **set_beta_ratio** (double x)
Set ratio for beta.

Public Member Functions inherited from

[LocalSearchAlgorithm](#)< [neighborhood::Neighborhood](#) >

- **LocalSearchAlgorithm** (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void **set_random_initialization** (bool b)
Set random initialization.
- void **set_starting_point** (const [bit_vector_t](#) &x)
Set the starting point.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void [init_beta](#) ()
Initialize beta.

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Loop

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void **log** ()
Log.
- virtual void **loop** () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- double **_beta**
Inverse temperature.
- double **_current_value**
Current value.
- int **_transitions**
Number of accepted transitions.

Parameters

- int **_num_transitions** = 50
Number of accepted transitions before annealing.
- int **_num_trials** = 100
Number of trials.
- double **_initial_acceptance_probability** = 0.6
Initial acceptance probability.
- double **_beta_ratio** = 1.2
Ratio for beta.

Protected Attributes inherited from**LocalSearchAlgorithm** < **neighborhood::Neighborhood** >

- **bit_vector_t _starting_point**
Starting point.
- **neighborhood::Neighborhood * _neighborhood**
Neighborhood.
- **bool _random_initialization**
Random initialization.

Protected Attributes inherited from **IterativeAlgorithm**

- **int _iteration**
Current iteration.
- **bool _last_iteration = false**
Last iteration.
- **bool _something_to_log = false**
Something to log.
- **int _num_iterations = 0**
Number of iterations.

Protected Attributes inherited from **Algorithm**

- **std::vector< function::Function * > _functions**
Functions.
- **function::Function * _function**
Function.
- **solution_t _solution**
Solution.
- **logging::LogContext * _log_context = nullptr**
Log context.

5.152.1 Detailed Description

Simulated annealing.

Reference:

S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. 1983. Optimization by simulated annealing. Science 220, 4598 (May 1983), 671–680.

Definition at line 42 of file [simulated-annealing.hh](#).

5.152.2 Member Function Documentation

5.152.2.1 init_beta()

```
void init_beta ( ) [protected]
```

Initialize beta.

Requires $(2 * \text{_num_trials})$ evaluations. This should be taken into account when using OnBudgetFunction.

Definition at line 34 of file [simulated-annealing.cc](#).

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/local-search/simulated-annealing.hh
- lib/hnco/algorithms/local-search/simulated-annealing.cc

5.153 SingleBitFlip Class Reference

One bit neighborhood.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for SingleBitFlip:



Public Member Functions

- **SingleBitFlip** (int n)
Constructor.

Public Member Functions inherited from [Neighborhood](#)

- [Neighborhood](#) (int n)
Constructor.
- virtual \sim **Neighborhood** ()
Destructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & **get_origin** () const
Get the origin.
- virtual const [bit_vector_t](#) & **get_candidate** () const
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & **get_flipped_bits** () const
Get flipped bits.
- virtual void **propose** ()
Propose a candidate bit vector.
- virtual void **keep** ()
Keep the candidate bit vector.
- virtual void **forget** ()
Forget the candidate bit vector.
- virtual void **mutate** ([bit_vector_t](#) &bv)
Mutate.
- virtual void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Private Member Functions

- void **sample_bits** ()
Sample bits.

Additional Inherited Members

Protected Attributes inherited from [Neighborhood](#)

- [bit_vector_t](#) _origin
Origin of the neighborhood.
- [bit_vector_t](#) _candidate
candidate bit vector
- std::uniform_int_distribution< int > _index_dist
Index distribution.
- [sparse_bit_vector_t](#) _flipped_bits
Flipped bits.

5.153.1 Detailed Description

One bit neighborhood.

Definition at line 163 of file [neighborhood.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/neighborhoods/neighborhood.hh

5.154 SingleBitFlipterator Class Reference

Single bit flip neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for SingleBitFlipterator:



Public Member Functions

- [SingleBitFlipterator](#) (int n)
Constructor.
- bool **has_next** () override
Has next bit vector.
- const [bit_vector_t](#) & **next** () override
Next bit vector.

Public Member Functions inherited from [NeighborhoodIterator](#)

- [NeighborhoodIterator](#) (int n)
Constructor.
- virtual void **set_origin** (const [bit_vector_t](#) &x)
Set origin.

Public Member Functions inherited from [Iterator](#)

- **Iterator** (int n)
Constructor.
- virtual **~Iterator** ()
Destructor.
- virtual void **init** ()
Initialization.

Private Attributes

- `size_t _index`
Index of the last flipped bit.

Additional Inherited Members

Protected Attributes inherited from [Iterator](#)

- `bit_vector_t _current`
Current bit vector.
- `bool _initial_state = true`
Flag for initial state.

5.154.1 Detailed Description

Single bit flip neighborhood iterator.

Definition at line 56 of file [neighborhood-iterator.hh](#).

5.154.2 Constructor & Destructor Documentation

5.154.2.1 SingleBitFlipIterator()

```
SingleBitFlipIterator (
    int n ) [inline]
```

Constructor.

Parameters

<code>n</code>	Size of bit vectors
----------------	---------------------

Definition at line 68 of file [neighborhood-iterator.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/neighborhoods/neighborhood-iterator.hh`
- `lib/hnco/neighborhoods/neighborhood-iterator.cc`

5.155 SinusSummationCancellation Class Reference

Summation cancellation with sinus.

```
#include <hnco/functions/collection/cancellation.hh>
```

Inheritance diagram for SinusSummationCancellation:



Public Member Functions

- **SinusSummationCancellation** (int n)
Constructor.
- double **evaluate** (const [bit_vector_t](#) &x) override
Evaluate a bit vector.

Public Member Functions inherited from [SummationCancellation](#)

- [SummationCancellation](#) (int n)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- bool [has_known_maximum](#) () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.
- double **evaluate** (const [bit_vector_t](#) &x) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)

Incrementally evaluate a bit vector.

- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)

Safely evaluate a bit vector.

- virtual void [update](#) (const [bit_vector_t](#) &x, double value)

Update states after a safe evaluation.

- virtual void **display** (std::ostream &stream) const

Display.

- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)

Describe a bit vector.

Additional Inherited Members

Protected Member Functions inherited from [SummationCancellation](#)

- void **convert** (const [bit_vector_t](#) &x)

Convert a bit vector into a real vector.

Protected Attributes inherited from [SummationCancellation](#)

- int **_bv_size**

Bit vector size.

- std::vector< double > **_buffer**

Buffer.

5.155.1 Detailed Description

Summation cancellation with sinus.

Reference:

M. Sebag and M. Schoenauer. 1997. A society of hill-climbers. In Proc. IEEE Int. Conf. on Evolutionary Computation. Indianapolis, 319–324.

Definition at line [101](#) of file [cancellation.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/cancellation.hh
- lib/hnco/functions/collection/cancellation.cc

5.156 SixPeaks Class Reference

Six Peaks.

```
#include <hnco/functions/collection/four-peaks.hh>
```

Inheritance diagram for SixPeaks:



Public Member Functions

- **SixPeaks** (int bv_size, int threshold)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- bool **has_known_maximum** () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const
Display.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- `int _bv_size`
Bit vector size.
- `int _threshold`
Threshold.
- `int _maximum`
Maximum.

5.156.1 Detailed Description

Six Peaks.

It is defined by

$$f(x) = \max\{\text{head}(x, 0) + \text{tail}(x, 1) + \text{head}(x, 1) + \text{tail}(x, 0)\} + R(x)$$

where:

- $\text{head}(x, 0)$ is the length of the longest prefix of x made of zeros;
- $\text{head}(x, 1)$ is the length of the longest prefix of x made of ones;
- $\text{tail}(x, 0)$ is the length of the longest suffix of x made of zeros;
- $\text{tail}(x, 1)$ is the length of the longest suffix of x made of ones;
- $R(x)$ is the reward;
- $R(x) = n$ if $(\text{head}(x, 0) > t \text{ and } \text{tail}(x, 1) > t)$ or $(\text{head}(x, 1) > t \text{ and } \text{tail}(x, 0) > t)$;
- $R(x) = 0$ otherwise;
- the threshold t is a parameter of the function.

This function has six maxima, of which exactly four are global ones.

For example, if $n = 6$ and $t = 1$:

- $f(111111) = 6$ (local maximum)
- $f(111110) = 5$
- $f(111100) = 10$ (global maximum)

Reference:

J. S. De Bonet, C. L. Isbell, and P. Viola. 1996. MIMIC: finding optima by estimating probability densities. In *Advances in Neural Information Processing Systems*. Vol. 9. MIT Press, Denver.

Definition at line 128 of file [four-peaks.hh](#).

5.156.2 Member Function Documentation

5.156.2.1 get_maximum()

```
double get_maximum ( ) const [inline], [override], [virtual]
```

Get the global maximum.

Returns

$2 * _bv_size - _threshold - 1$

Reimplemented from [Function](#).

Definition at line 156 of file [four-peaks.hh](#).

5.156.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 152 of file [four-peaks.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/four-peaks.hh
- lib/hnco/functions/collection/four-peaks.cc

5.157 SquaredMagnitude< T > Struct Template Reference

Squared magnitude of a complex number.

```
#include <hnco/functions/converter.hh>
```

Public Types

- using **codomain_type** = std::complex< T >
Codomain type.

Public Member Functions

- double **operator()** (std::complex< T > z)
squared magnitude

5.157.1 Detailed Description

```
template<class T>
struct hnco::function::SquaredMagnitude< T >
```

Squared magnitude of a complex number.

Definition at line 59 of file [converter.hh](#).

The documentation for this struct was generated from the following file:


- lib/hnco/functions/converter.hh

5.158 StandardBitMutation Class Reference

Standard bit mutation.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for StandardBitMutation:



Public Member Functions

- [StandardBitMutation](#) (int n)
Constructor.
- [StandardBitMutation](#) (int n, double p)
Constructor.

Setters

- void [set_mutation_rate](#) (double p)
Set mutation rate.
- void [set_allow_no_mutation](#) (bool b)
Set the flag _allow_no_mutation.

Public Member Functions inherited from [MultiBitFlip](#)

- [MultiBitFlip](#) (int n)
Constructor.

Public Member Functions inherited from [Neighborhood](#)

- [Neighborhood](#) (int n)
Constructor.
- virtual \sim [Neighborhood](#) ()
Destructor.
- virtual void [set_origin](#) (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) & [get_origin](#) () const
Get the origin.
- virtual const [bit_vector_t](#) & [get_candidate](#) () const
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) & [get_flipped_bits](#) () const
Get flipped bits.
- virtual void [propose](#) ()
Propose a candidate bit vector.
- virtual void [keep](#) ()
Keep the candidate bit vector.
- virtual void [forget](#) ()
Forget the candidate bit vector.
- virtual void [mutate](#) ([bit_vector_t](#) &bv)
Mutate.
- virtual void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.
- void [bernoulli_process](#) ()
Bernoulli process.

Private Attributes

- `std::bernoulli_distribution _bernoulli_dist`
Bernoulli distribution (biased coin)
- `std::binomial_distribution< int > _binomial_dist`
Binomial distribution.
- `bool _rejection_sampling = false`
Rejection sampling.

Parameters

- `bool _allow_no_mutation = false`
Allow no mutation.

Additional Inherited Members**Protected Member Functions inherited from [MultiBitFlip](#)**

- `void bernoulli_trials (int k)`
Sample a given number of bits using Bernoulli trials.
- `void rejection_sampling (int k)`
Sample a given number of bits using rejection sampling.

Protected Attributes inherited from [Neighborhood](#)

- `bit_vector_t _origin`
Origin of the neighborhood.
- `bit_vector_t _candidate`
candidate bit vector
- `std::uniform_int_distribution< int > _index_dist`
Index distribution.
- `sparse_bit_vector_t _flipped_bits`
Flipped bits.

5.158.1 Detailed Description

Standard bit mutation.

Each component of the origin bit vector is flipped with some fixed probability. Unless stated otherwise, if no component has been flipped at the end, the process is started all over again. Thus the number of flipped bits follows a pseudo binomial law.

Definition at line 222 of file [neighborhood.hh](#).

5.158.2 Constructor & Destructor Documentation**5.158.2.1 StandardBitMutation() [1/2]**

```
StandardBitMutation (
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

The Bernoulli probability is set to $1 / n$.

Definition at line 257 of file [neighborhood.hh](#).

5.158.2.2 StandardBitMutation() [2/2]

```
StandardBitMutation (
    int n,
    double p ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
p	Bernoulli probability

Definition at line 267 of file [neighborhood.hh](#).

5.158.3 Member Function Documentation

5.158.3.1 set_mutation_rate()

```
void set_mutation_rate (
    double p ) [inline]
```

Set mutation rate.

Sets `_rejection_sampling` to true if $E(X) < \sqrt{n}$, where X is a random variable with a binomial distribution $B(n, p)$, that is if $np < \sqrt{n}$ or $p < 1 / \sqrt{n}$.

Definition at line 282 of file [neighborhood.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/neighborhoods/neighborhood.hh`
- `lib/hnco/neighborhoods/neighborhood.cc`

5.159 SteepestAscentHillClimbing Class Reference

Steepest ascent hill climbing.

```
#include <hnco/algorithms/local-search/steepest-ascent-hill-climbing.hh>
```

Inheritance diagram for SteepestAscentHillClimbing:



Public Member Functions

- **SteepestAscentHillClimbing** (int n, [neighborhood::NeighborhoodIterator](#) *neighborhood)
Constructor.

Public Member Functions inherited from

[LocalSearchAlgorithm< neighborhood::NeighborhoodIterator >](#)

- **LocalSearchAlgorithm** (int n, [neighborhood::NeighborhoodIterator](#) *neighborhood)
Constructor.
- void **set_random_initialization** (bool b)
Set random initialization.
- void **set_starting_point** (const [bit_vector_t](#) &x)
Set the starting point.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & [get_solution](#) ()
Get the solution.

Protected Member Functions

- void [iterate](#) () override
Single iteration.

Protected Member Functions inherited from [LocalSearchAlgorithm](#)< [neighborhood::NeighborhoodIterator](#) >

- void [init](#) () override
Initialize.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [log](#) ()
Log.
- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- std::vector< [bit_vector_t](#) > **_candidates**
Potential candidate.

Protected Attributes inherited from [LocalSearchAlgorithm](#)< [neighborhood::NeighborhoodIterator](#) >

- [bit_vector_t](#) **_starting_point**
Starting point.
- [neighborhood::NeighborhoodIterator](#) * **_neighborhood**
Neighborhood.
- bool **_random_initialization**
Random initialization.

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.159.1 Detailed Description

Steepest ascent hill climbing.

Definition at line 34 of file [steepest-ascent-hill-climbing.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/local-search/steepest-ascent-hill-climbing.hh`
- `lib/hnco/algorithms/local-search/steepest-ascent-hill-climbing.cc`

5.160 StopOnMaximum Class Reference

Stop on maximum.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for StopOnMaximum:



Public Member Functions

- [StopOnMaximum](#) ([Function](#) *function)
Constructor.

Public Member Functions inherited from [StopOnTarget](#)

- [StopOnTarget](#) ([Function](#) *function, double target)
Constructor.
- const [algorithm::solution_t](#) & [get_trigger](#) ()
Get trigger.
- double [evaluate](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [evaluate_incrementally](#) (const [bit_vector_t](#) &bv, double value, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- void [update](#) (const [bit_vector_t](#) &bv, double value)
Update after a safe evaluation.

Public Member Functions inherited from [Controller](#)

- [Controller](#) ([Function](#) *function)
Constructor.
- int [get_bv_size](#) () const
Get bit vector size.
- double [get_maximum](#) () const
Get the global maximum.
- bool [has_known_maximum](#) () const
Check for a known maximum.
- bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- double [evaluate_safely](#) (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- [Decorator](#) ([Function](#) *function)
Constructor.
- void [display](#) (std::ostream &stream) const override
Display.
- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function()`
Destructor.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * `_function`
Decorated function.

5.160.1 Detailed Description

Stop on maximum.

Definition at line 144 of file [controller.hh](#).

5.160.2 Constructor & Destructor Documentation

5.160.2.1 StopOnMaximum()

```
StopOnMaximum (
    Function * function ) [inline]
```

Constructor.

Precondition

function->[has_known_maximum\(\)](#)

Definition at line 151 of file [controller.hh](#).

The documentation for this class was generated from the following file:


- `lib/hnco/functions/controllers/controller.hh`

5.161 StopOnTarget Class Reference

Stop on target.

```
#include <hnco/functions/controllers/controller.hh>
```

Inheritance diagram for StopOnTarget:



Public Member Functions

- **StopOnTarget** (**Function** *function, double target)
Constructor.
- const **algorithm::solution_t** & **get_trigger** ()
Get trigger.

Evaluation

- double **evaluate** (const **bit_vector_t** &)
Evaluate a bit vector.
- double **evaluate_incrementally** (const **bit_vector_t** &bv, double value, const **hnco::sparse_bit_vector_t** &flipped_bits)
Incrementally evaluate a bit vector.
- void **update** (const **bit_vector_t** &bv, double value)
Update after a safe evaluation.

Public Member Functions inherited from [Controller](#)

- **Controller** ([Function](#) *function)
Constructor.
- int **get_bv_size** () const
Get bit vector size.
- double **get_maximum** () const
Get the global maximum.
- bool **has_known_maximum** () const
Check for a known maximum.
- bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- double **evaluate_safely** (const [bit_vector_t](#) &bv)
Safely evaluate a bit vector.

Public Member Functions inherited from [Decorator](#)

- **Decorator** ([Function](#) *function)
Constructor.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &x, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.

Private Attributes

- double **_target**
Target.
- [algorithm::solution_t](#) **_trigger**
Trigger.

Additional Inherited Members

Protected Attributes inherited from [Decorator](#)

- [Function](#) * **_function**
Decorated function.

5.161.1 Detailed Description

Stop on target.

The member function `eval` throws an exception `TargetReached` when the value of its decorated function reaches a given target.

Warning

The target is detected using the greater or equal operator hence the result should be taken with care in case of non integer (floating point) function values.

Definition at line 93 of file [controller.hh](#).

5.161.2 Constructor & Destructor Documentation

5.161.2.1 StopOnTarget()

```
StopOnTarget (
    Function * function,
    double target ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
<i>target</i>	Target

Definition at line 108 of file [controller.hh](#).

5.161.3 Member Function Documentation

5.161.3.1 evaluate()

```
double evaluate (
    const bit_vector_t & bv ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>TargetReached</i>	
----------------------	--

Implements [Function](#).

Definition at line 31 of file [controller.cc](#).

5.161.3.2 evaluate_incrementally()

```
double evaluate_incrementally (
    const bit_vector_t & bv,
    double value,
    const hnco::sparse_bit_vector_t & flipped_bits ) [virtual]
```

Incrementally evaluate a bit vector.

Exceptions

<i>TargetReached</i>	
----------------------	--

Reimplemented from [Function](#).

Definition at line 43 of file [controller.cc](#).

5.161.3.3 update()

```
void update (
    const bit_vector_t & bv,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>TargetReached</i>	
----------------------	--

Reimplemented from [Function](#).

Definition at line 55 of file [controller.cc](#).

The documentation for this class was generated from the following files:

- [lib/hnco/functions/controllers/controller.hh](#)
- [lib/hnco/functions/controllers/controller.cc](#)

5.162 Stopwatch Class Reference

Stop watch.

```
#include <hnco/stop-watch.hh>
```

Public Member Functions

- void **start** ()
Start.
- void **stop** ()
Stop.
- double **get_total_time** ()
Get total time.
- void **reset** ()
Reset.

Private Attributes

- double **_total_time** = 0
Total time.
- clock_t **_start**
Start time.

5.162.1 Detailed Description

Stop watch.

Definition at line 31 of file [stop-watch.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/stop-watch.hh

5.163 Sudoku Class Reference

Sudoku

```
#include <hnco/functions/collection/sudoku.hh>
```

Public Types

- using **domain_type** = std::size_t
Domain type.
- using **codomain_type** = double
Codomain type.

Public Member Functions

- **Sudoku** ()
Default constructor.
- void **random** (int c)
Random instance.
- int **get_num_variables** ()
Get the number of variables.
- void **display** (std::ostream &stream) const
Display the problem.
- void **describe** (const std::vector< [domain_type](#) > &x, std::ostream &stream)
Describe a solution.
- double **evaluate** (const std::vector< [domain_type](#) > &x)
Evaluate a solution.

Private Member Functions

- void **write_variables** (const std::vector< [domain_type](#) > &x)
Write variables.

Private Attributes

- std::vector< std::vector< char > > **_problem_instance**
Problem instance.
- std::vector< std::vector< [domain_type](#) > > **_candidate**
Candidate.
- std::vector< int > **_counts**
Counts.
- int **_num_variables**
Number of variables.

Load and save instance

- void **load_** (std::istream &stream)
Load an instance.
- void **save_** (std::ostream &stream) const
Save an instance.
- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

5.163.1 Detailed Description

Sudoku

Definition at line 34 of file [sudoku.hh](#).

5.163.2 Member Function Documentation**5.163.2.1 load()**

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 100 of file [sudoku.hh](#).

5.163.2.2 load_()

```
void load_ (
    std::istream & stream ) [private]
```

Load an instance.

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 57 of file [sudoku.cc](#).

5.163.2.3 random()

```
void random (
    int c )
```

Random instance.

Parameters

<i>c</i>	Number of empty cells
----------	-----------------------

Definition at line 96 of file [sudoku.cc](#).

5.163.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 112 of file [sudoku.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/functions/collection/sudoku.hh`
- `lib/hnco/functions/collection/sudoku.cc`

5.164 SummationCancellation Class Reference

Summation cancellation.

```
#include <hnco/functions/collection/cancellation.hh>
```

Inheritance diagram for SummationCancellation:



Public Member Functions

- [SummationCancellation](#) (int n)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- bool [has_known_maximum](#) () const override
Check for a known maximum.
- double **get_maximum** () const override
Get the global maximum.
- double **evaluate** (const [bit_vector_t](#) &x) override
Evaluate a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual `bool provides_incremental_evaluation () const`
Check whether the function provides incremental evaluation.
- virtual `double evaluate_incrementally (const bit_vector_t &x, double value, const sparse_bit_vector_t &flipped_bits)`
Incrementally evaluate a bit vector.
- virtual `double evaluate_safely (const bit_vector_t &x)`
Safely evaluate a bit vector.
- virtual `void update (const bit_vector_t &x, double value)`
Update states after a safe evaluation.
- virtual `void display (std::ostream &stream) const`
Display.
- virtual `void describe (const bit_vector_t &x, std::ostream &stream)`
Describe a bit vector.

Protected Member Functions

- void `convert (const bit_vector_t &x)`
Convert a bit vector into a real vector.

Protected Attributes

- `int _bv_size`
Bit vector size.
- `std::vector< double > _buffer`
Buffer.

5.164.1 Detailed Description

Summation cancellation.

Encoding of a signed integer:

- bit 0: sign
- bits 1 to 8: two's complement representation

Reference:

S. Baluja and S. Davies. 1997. Using optimal dependency-trees for combinatorial optimization: learning the structure of the search space. Technical Report CMU- CS-97-107. Carnegie-Mellon University.

Definition at line 46 of file [cancellation.hh](#).

5.164.2 Constructor & Destructor Documentation

5.164.2.1 SummationCancellation()

```
SummationCancellation (
    int n ) [inline]
```

Constructor.

The bit vector size n must be a multiple of 9. The size of `_buffer` is then n / 9.

Parameters

n	Size of the bit vector
-----	------------------------

Definition at line 68 of file [cancellation.hh](#).

5.164.3 Member Function Documentation

5.164.3.1 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 81 of file [cancellation.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/cancellation.hh
- lib/hnco/functions/collection/cancellation.cc

5.165 TargetReached Class Reference

Target reached.

```
#include <hnco/exception.hh>
```

Inherits `runtime_error`.

5.165.1 Detailed Description

Target reached.

Definition at line 40 of file [exception.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.166 TournamentSelection Class Reference

Tournament selection.

```
#include <hnco/algorithms/evolutionary-algorithms/random-selection.hh>
```

Inheritance diagram for TournamentSelection:



Public Member Functions

- [TournamentSelection](#) (const [Population](#) &population)
Constructor.
- void **init** () override
Initialize.
- const [bit_vector_t](#) & **select** () override
Select an individual in the population.

Setters

- void [set_tournament_size](#) (int n)

Public Member Functions inherited from [RandomSelection](#)

- [RandomSelection](#) (const [Population](#) &population)
Constructor.

Private Attributes

- [hnco::multiobjective::algorithm::TournamentSelection](#)< double, std::greater< double > > **_tournament_selection**
Tournament selection.

Parameters

- int [_tournament_size](#) = 2

Additional Inherited Members

Protected Attributes inherited from [RandomSelection](#)

- const [Population](#) & `_population`
Population to select from

5.166.1 Detailed Description

Tournament selection.

Reuses the [hnco::multiobjective::algorithm::TournamentSelection](#) class.

Definition at line 80 of file [random-selection.hh](#).

5.166.2 Constructor & Destructor Documentation

5.166.2.1 TournamentSelection()

```
TournamentSelection (
    const Population & population ) [inline]
```

Constructor.

Parameters

<i>population</i>	Population to select from
-------------------	---------------------------

Definition at line 96 of file [random-selection.hh](#).

5.166.3 Member Function Documentation

5.166.3.1 select()

```
const bit\_vector\_t & select ( ) [override], [virtual]
```

Select an individual in the population.

The selection only requires that the population be evaluated, not necessarily sorted.

Precondition

The population must be evaluated.

Implements [RandomSelection](#).

Definition at line 46 of file [random-selection.cc](#).

5.166.3.2 set_tournament_size()

```
void set_tournament_size (
    int n ) [inline]
```

Set the tournament size

Definition at line 114 of file [random-selection.hh](#).

5.166.4 Member Data Documentation

5.166.4.1 _tournament_size

```
int _tournament_size = 2 [private]
```

Tournament size

Definition at line 88 of file [random-selection.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/random-selection.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/random-selection.cc](#)

5.167 TournamentSelection< T, Compare > Class Template Reference

Tournament selection.

```
#include <hnco/multiobjective/algorithms/random-selection.hh>
```

Inheritance diagram for TournamentSelection< T, Compare >:



Public Member Functions

- **TournamentSelection** (const std::vector< [bit_vector_t](#) > &bvs, const std::vector< T > &values)
Constructor.
- void **init** ()
Initialize.
- const [bit_vector_t](#) & **select** ()
Select a bit vector.

Setters

- void **set_tournament_size** (int n)
Set the tournament size.

Private Attributes

- const std::vector< [bit_vector_t](#) > & **_bvs**
Bit vectors.
- const std::vector< T > & **_values**
Values.
- [hnco::permutation_t](#) **_permutation**
Permutation.
- int **_start**
Beginning of the slice of permutation used in a tournament round.
- int **_stop**
End of the slice of permutation used in a tournament round.
- Compare **_compare**
Comparison operator.

Parameters

- int **_tournament_size** = 2
Tournament size.

5.167.1 Detailed Description

template<typename T, typename Compare>
class hnco::multiobjective::algorithm::TournamentSelection< T, Compare >

Tournament selection.

Implement tournament selection without replacement as explained in the reference:

Goldberg, Korb, and Deb, "Messy genetic algorithms: Motivation, analysis, and first results", Complex systems, 1989.

https://www.complex-systems.com/abstracts/v03_i05_a05/

Definition at line 45 of file [random-selection.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/multiobjective/algorithms/random-selection.hh

5.168 Translation Class Reference

Translation.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for Translation:



Public Member Functions

- void **map** (const [bit_vector_t](#) &input, [bit_vector_t](#) &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool **is_surjective** () const override
Check for surjective map.
- void **display** (std::ostream &stream) const override
Display.
- void **random** (int n)
Random instance.
- void **set_bv** (const [bit_vector_t](#) &bv)
Set the translation vector.

Load and save map

- void **load** (std::string path)
Load map.
- void **save** (std::string path) const
Save map.

Public Member Functions inherited from [Map](#)

- virtual **~Map** ()
Destructor.

Private Member Functions

- `template<class Archive >`
void **save** (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
void **load** (Archive &ar, const unsigned int version)
Load.

Private Attributes

- `bit_vector_t_bv`
Translation vector

5.168.1 Detailed Description

Translation.

A translation is an affine map f from $F_2 y^n$ to itself defined by $f(x) = x + b$, where b is an n -dimensional bit vector.

Definition at line 79 of file [map.hh](#).

5.168.2 Member Function Documentation

5.168.2.1 is_surjective()

```
bool is_surjective ( ) const [inline], [override], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 121 of file [map.hh](#).

5.168.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 146 of file [map.hh](#).

5.168.2.3 save()

```
void save (
    std::string path ) const [inline]
```

Save map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 153 of file [map.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/maps/map.hh
- lib/hnco/maps/map.cc

5.169 Transvection Struct Reference

Transvection.

```
#include <hnco/maps/transvection.hh>
```

Public Member Functions

- `template<class Archive >`
void **save** (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
void **load** (Archive &ar, const unsigned int version)
Load.
- `bool is_valid ()` const
Check validity.
- `bool is_valid (int n)` const
Check validity.
- void **display** (std::ostream &stream) const

Display transvection.

- void `random` (int n)
Sample a random transvection.
- void `random_non_commuting` (int n, const `Transvection` &a)
Sample a random transvection.
- void `multiply` (`bit_vector_t` &bv) const
Multiply a bit vector from the left.
- void `multiply` (`bit_matrix_t` &bm) const
Multiply a bit matrix from the left.

Public Attributes

- int `row_index`
Row index.
- int `column_index`
Column index.

5.169.1 Detailed Description

Transvection.

We only consider transvections defined by matrices $\tau_{ij} = I_n + B_{ij}$, where I_n is the $n \times n$ identity matrix and B_{ij} is the matrix whose (i, j) entry is 1 and other entries are zero. Such a matrix is also sometimes called a shear matrix.

Transvections generate invertible matrices over the finite field F_2 .

Definition at line 61 of file [transvection.hh](#).

5.169.2 Member Function Documentation

5.169.2.1 `is_valid()`

```
bool is_valid (
    int n ) const
```

Check validity.

Parameters

<i>n</i>	Dimension
----------	-----------

Definition at line 48 of file [transvection.cc](#).

5.169.2.2 `multiply()` [1/2]

```
void multiply (
    bit_matrix_t & bm ) const
```

Multiply a bit matrix from the left.

Parameters

<i>bm</i>	Bit matrix
-----------	------------

Precondition

[is_valid\(\)](#)
[is_valid\(bm_num_rows\(M\)\)](#)

Warning

This function modifies the given bit vector.

Definition at line [117](#) of file [transvection.cc](#).

5.169.2.3 multiply() [2/2]

```
void multiply (  
    bit\_vector\_t & bv ) const
```

Multiply a bit vector from the left.

Parameters

<i>bv</i>	Bit vector
-----------	------------

Precondition

[is_valid\(\)](#)
[is_valid\(x.size\(\)\)](#)

Warning

This function modifies the given bit vector.

Definition at line [105](#) of file [transvection.cc](#).

5.169.2.4 random()

```
void random (  
    int n )
```

Sample a random transvection.

Parameters

<i>n</i>	Dimension
----------	-----------

Precondition $n > 1$

Definition at line 61 of file [transvection.cc](#).

5.169.2.5 random_non_commuting()

```
void random_non_commuting (
    int n,
    const Transvection & a )
```

Sample a random transvection.

This member function ensures that the sampled transvection does not commute with some given one.

Parameters

n	Dimension
a	Given transvection

Precondition $n > 1$

Definition at line 77 of file [transvection.cc](#).

The documentation for this struct was generated from the following files:


- [lib/hnco/maps/transvection.hh](#)
- [lib/hnco/maps/transvection.cc](#)

5.170 Trap Class Reference

Trap.

```
#include <hnco/functions/collection/trap.hh>
```

Inheritance diagram for Trap:



Public Member Functions

- [Trap](#) (int bv_size, int num_traps)
Constructor.
- int [get_bv_size](#) () const
Get bit vector size.
- double [evaluate](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) () const
Check for a known maximum.
- double [get_maximum](#) () const
Get the global maximum.

Public Member Functions inherited from [Function](#)

- virtual [~Function](#) ()
Destructor.
- virtual bool [provides_incremental_evaluation](#) () const
Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void [update](#) (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void [display](#) (std::ostream &stream) const
Display.
- virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_num_traps](#)
Number of traps.
- int [_trap_size](#)
Trap size

5.170.1 Detailed Description

Trap.

Reference:

Kalyanmoy Deb and David E. Goldberg. 1993. Analyzing Deception in Trap Functions. In Foundations of Genetic Algorithms 2, L. Darrell Whitley (Ed.). Morgan Kaufmann, San Mateo, CA, 93–108.

Definition at line 43 of file [trap.hh](#).

5.170.2 Constructor & Destructor Documentation

5.170.2.1 Trap()

```
Trap (
    int bv_size,
    int num_traps ) [inline]
```

Constructor.

Parameters

<i>bv_size</i>	Bit vector size
<i>num_traps</i>	Number of traps

Warning

bv_size must be a multiple of *num_traps*

Definition at line 64 of file [trap.hh](#).

5.170.3 Member Function Documentation

5.170.3.1 get_maximum()

```
double get_maximum ( ) const [inline], [virtual]
```

Get the global maximum.

Returns

_bv_size

Reimplemented from [Function](#).

Definition at line 88 of file [trap.hh](#).

5.170.3.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 84 of file [trap.hh](#).

The documentation for this class was generated from the following files:

- lib/hnco/functions/collection/trap.hh
- lib/hnco/functions/collection/trap.cc

5.171 TriangularMoment Struct Reference

Triangular moment.

```
#include <hnco/algorithms/walsh-moment/walsh-moment.hh>
```

Public Member Functions

- [TriangularMoment](#) (int n)
Constructor.
- void [display](#) (std::ostream &stream)
Display moment.
- void **init** ()
Initialize moment.
- void **add** (const [bit_vector_t](#) &bv)
Add a bit vector.
- void [average](#) (int count)
Compute average.
- void [update](#) (const [TriangularMoment](#) &tm, double rate)
Update a moment.
- void [update](#) (const [TriangularMoment](#) &tm1, const [TriangularMoment](#) &tm2, double rate)
Update a moment.
- void [scaled_difference](#) (double lambda, const [TriangularMoment](#) &tm1, const [TriangularMoment](#) &tm2)
Compute a scaled difference between two moments.
- void [bound](#) (double margin)
Bound moment.
- double **norm_1** () const
1-norm
- double **norm_2** () const
2-norm
- double **norm_infinite** () const
infinite-norm
- double **distance** (const [TriangularMoment](#) &wm) const
distance between the moment and another moment

Public Attributes

- std::vector< double > **first_moment**
First moment.
- std::vector< std::vector< double > > **second_moment**
Second moment.

5.171.1 Detailed Description

Triangular moment.

Definition at line 35 of file [walsh-moment.hh](#).

5.171.2 Constructor & Destructor Documentation

5.171.2.1 TriangularMoment()

```
TriangularMoment (  
    int n )
```

Constructor.

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 35 of file [walsh-moment.cc](#).

5.171.3 Member Function Documentation

5.171.3.1 average()

```
void average (  
    int count )
```

Compute average.

Parameters

<i>count</i>	Number of previously added bit vectors
--------------	--

Definition at line 92 of file [walsh-moment.cc](#).

5.171.3.2 bound()

```
void bound (  
    double margin )
```

Bound moment.

Parameters

<i>margin</i>	Distance from the -1/1 bounds
---------------	-------------------------------

Ensure that the distance from each moment to the -1/1 bounds is greater or equal to the given margin.

Definition at line 160 of file [walsh-moment.cc](#).

5.171.3.3 display()

```
void display (  
    std::ostream & stream )
```

Display moment.

A [TriangularMoment](#) is displayed as a full symmetric matrix with diagonal entries equal to first moments and off-diagonal entries equal to second moments.

Definition at line 46 of file [walsh-moment.cc](#).

5.171.3.4 scaled_difference()

```
void scaled_difference (
    double lambda,
    const TriangularMoment & tm1,
    const TriangularMoment & tm2 )
```

Compute a scaled difference between two moments.

Parameters

<i>lambda</i>	Scale
<i>tm1</i>	First moment
<i>tm2</i>	Second moment

This member function implements:

$\text{self} = \text{lambda} * \text{tm1} - \text{tm2}$

It is mostly useful in herding ([Hea](#)).

Definition at line [143](#) of file [walsh-moment.cc](#).

5.171.3.5 update() [1/2]

```
void update (
    const TriangularMoment & tm,
    double rate )
```

Update a moment.

Parameters

<i>tm</i>	Target moment
<i>rate</i>	Learning rate

Postcondition

For all i , $\text{is_in_interval}(\text{first_moment}[i], -1, 1)$

For all $j < i$, $\text{is_in_interval}(\text{second_moment}[i][j], -1, 1)$

This member function implements:

$\text{self} += \text{rate} * (\text{tm1} - \text{self})$

Definition at line [107](#) of file [walsh-moment.cc](#).

5.171.3.6 update() [2/2]

```
void update (
    const TriangularMoment & tm1,
    const TriangularMoment & tm2,
    double rate )
```

Update a moment.

Parameters

<i>tm1</i>	Target moment
<i>tm2</i>	Moment to move away from
<i>rate</i>	Learning rate

This member function implements:

```
self += rate * (tm1 - tm2)
```

The resulting entries are not necessarily those of a moment, that is

`is_in_interval(first_moment[i], -1, 1)` or

`is_in_interval(second_moment[i][j], -1, 1)`

might fail for some *i*, *j*.

Definition at line 125 of file [walsh-moment.cc](#).

The documentation for this struct was generated from the following files:

- `lib/hnco/algorithms/walsh-moment/walsh-moment.hh`
- `lib/hnco/algorithms/walsh-moment/walsh-moment.cc`

5.172 TriangularMomentGibbsSampler Class Reference

Gibbs sampler with triangular moments.

```
#include <hnco/algorithms/walsh-moment/gibbs-sampler.hh>
```

Public Types

- using **Moment** = [TriangularMoment](#)
Walsh moment type.

Public Member Functions

- **TriangularMomentGibbsSampler** (int n, const [TriangularMoment](#) &mp)
Constructor.
- void **init** ()
Initialize.
- void **update** (int i)
Update state.
- void **update_sync** ()
Update state synchronously.
- const [bit_vector_t](#) & **get_state** ()
Get the state of the Gibbs sampler.

Private Attributes

- const [TriangularMoment](#) & `_model_parameters`
Model parameters.
- [bit_vector_t](#) `_state`
State of the Gibbs sampler.
- [pv_t](#) `_pv`
Probability vector for synchronous Gibbs sampling.

5.172.1 Detailed Description

Gibbs sampler with triangular moments.

Definition at line 36 of file [gibbs-sampler.hh](#).

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/walsh-moment/gibbs-sampler.hh`
- `lib/hnco/algorithms/walsh-moment/gibbs-sampler.cc`

5.173 TriangularMomentHerding Class Reference

Herding with lower triangular Walsh moment.

```
#include <hnco/algorithms/walsh-moment/herding.hh>
```

Public Types

- using **Moment** = [TriangularMoment](#)
Walsh moment type.

Public Member Functions

- [TriangularMomentHerding](#) (int n)
Constructor.
- void **init** ()
Initialization.
- void **sample** (const [TriangularMoment](#) &target, [bit_vector_t](#) &x)
Sample a bit vector.
- double **error** (const [TriangularMoment](#) &target)
Compute the error.

Getters

- const [TriangularMoment](#) & [get_delta](#) () const

Setters

- void [set_randomize_bit_order](#) (bool b)

Private Attributes

- [TriangularMoment_delta](#)
Delta moment.
- [TriangularMoment_count](#)
Counter moment.
- [TriangularMoment_error](#)
Error moment.
- [permutation_t_permutation](#)
Permutation.
- `int_time`
Time.

Parameters

- `bool_randomize_bit_order` = true

5.173.1 Detailed Description

Herdling with lower triangular Walsh moment.

Definition at line 43 of file [herding.hh](#).

5.173.2 Constructor & Destructor Documentation

5.173.2.1 TriangularMomentHerdling()

```
TriangularMomentHerdling (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 69 of file [herding.hh](#).

5.173.3 Member Function Documentation

5.173.3.1 get_delta()

```
const TriangularMoment & get_delta ( ) const [inline]
```

Get delta

Definition at line 85 of file [herding.hh](#).

5.173.3.2 set_randomize_bit_order()

```
void set_randomize_bit_order (
    bool b ) [inline]
```

Randomize bit order

Definition at line 92 of file [herding.hh](#).

5.173.4 Member Data Documentation

5.173.4.1 _randomize_bit_order

```
bool _randomize_bit_order = true [private]
```

Randomize bit order

Definition at line 59 of file [herding.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/walsh-moment/herding.hh
- lib/hnco/algorithms/walsh-moment/herding.cc

5.174 TsAffineMap Class Reference

Transvection sequence affine map.

```
#include <hnco/maps/map.hh>
```

Inheritance diagram for TsAffineMap:



Classes

- struct [SamplingMode](#)
Sampling mode.

Public Member Functions

- void **random** (int n, int t, int mode)
Random instance.
- void **map** (const **bit_vector_t** &input, **bit_vector_t** &output) override
Map
- int **get_input_size** () const override
Get input size.
- int **get_output_size** () const override
Get output size.
- bool **is_surjective** () const override
Check for surjective map.
- void **display** (std::ostream &stream) const override
Display.
- void **invert** ()
Invert the map.

Load and save map

- void **load** (std::string path)
Load map.
- void **save** (std::string path) const
Save map.

Public Member Functions inherited from **Map**

- virtual **~Map** ()
Destructor.

Private Member Functions

- template<class Archive >
void **save** (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void **load** (Archive &ar, const unsigned int version)
Load.

Private Attributes

- **transvection_sequence_t_ts**
Transvection sequence
- **bit_vector_t_bv**
Translation vector

5.174.1 Detailed Description

Transvection sequence affine map.

An affine map f from F_2^m to F_2^n is defined by $f(x) = Ax + b$, where A is an $n \times m$ bit matrix and b is an n -dimensional bit vector.

In [TsAffineMap](#), A is a finite product of transvections represented by a `transvection_sequence_t`.

Definition at line 601 of file [map.hh](#).

5.174.2 Member Function Documentation

5.174.2.1 `is_surjective()`

```
bool is_surjective ( ) const [inline], [override], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 662 of file [map.hh](#).

5.174.2.2 `load()`

```
void load (
    std::string path ) [inline]
```

Load map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 676 of file [map.hh](#).

5.174.2.3 `random()`

```
void random (
    int n,
```

```
int t,
int mode )
```

Random instance.

Parameters

<i>n</i>	Dimension
<i>t</i>	Length of sequence of transvections
<i>mode</i>	Sampling mode

Precondition

$t \geq 0$

Definition at line 194 of file [map.cc](#).

5.174.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save map.

Parameters

<i>path</i>	Path of the file
-------------	------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 682 of file [map.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/maps/map.hh](#)
- [lib/hnco/maps/map.cc](#)

5.175 RamUmda::TsLengthMode Struct Reference

Transvection sequence length mode.

```
#include <hnco/algorithms/probability-vector/ram-umda.hh>
```

Public Types

- enum {
[constant](#) = 0 , [increasing](#) = 1 , [decreasing](#) = 2 , [uniform](#) = 3 ,
[geometric](#) = 4 , [reverse_geometric](#) = 5 }

5.175.1 Detailed Description

Transvection sequence length mode.

Definition at line 38 of file [ram-umda.hh](#).

5.175.2 Member Enumeration Documentation

5.175.2.1 anonymous enum

anonymous enum

Enumerator

constant	Constant.
increasing	Increasing.
decreasing	Decreasing.
uniform	Random with uniform distribution.
geometric	Random with geometric distribution.
reverse_geometric	Random with reverse geometric distribution.

Definition at line 39 of file [ram-umda.hh](#).

The documentation for this struct was generated from the following file:

- [lib/hnco/algorithms/probability-vector/ram-umda.hh](#)

5.176 Tsp Class Reference

Traveling salesman problem.

```
#include <hnco/functions/collection/tsp.hh>
```

Public Member Functions

- **Tsp** ()
Default constructor.
- int **get_num_elements** () const
Get the number of elements.
- void **display** (std::ostream &stream) const
Display the problem.
- void **describe** (const [hnco::permutation_t](#) &permutation, std::ostream &stream)
Describe a solution.
- double **evaluate** (const [hnco::permutation_t](#) &permutation)
Evaluate a solution.

Instance generators

- template<class Generator >
void **generate** (int n, Generator generator)
Instance generator.
- void **random** (int n)
Random instance.

Private Types

- enum class `EdgeWeightType` { `ATT` , `EUC_2D` }
Edge weight type.

Private Attributes

- `std::string _name`
Instance name.
- `std::string _comment`
Comment.
- `int _num_cities`
Number of cities.
- `std::vector< float > _xs`
Abscissas of cities.
- `std::vector< float > _ys`
Ordinates of cities.
- `EdgeWeightType _edge_weight_type = EdgeWeightType::ATT`
Edge weight type.
- `std::vector< std::vector< float > > _distances`
Distances.

Load and save instance

- void `load_` (std::istream &stream)
Load an instance.
- void `load_coordinates` (std::istream &stream)
Load coordinates.
- void `save_` (std::ostream &stream) const
Save an instance.
- void `load` (std::string path)
Load instance.
- void `save` (std::string path) const
Save instance.

5.176.1 Detailed Description

Traveling salesman problem.

Source: TSPLIB 95, Gerhard Reinelt

<http://comopt.ifi.uni-heidelberg.de/software/TSPLIB95/>

Definition at line 41 of file `tsp.hh`.

5.176.2 Member Enumeration Documentation

5.176.2.1 EdgeWeightType

```
enum class EdgeWeightType [strong], [private]
```

Edge weight type.

Enumerator

ATT	ATT.
EUC_2D	Euclidean 2D.

Definition at line 54 of file [tsp.hh](#).

5.176.3 Member Function Documentation

5.176.3.1 generate()

```
template<class Generator >
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Number of vertices
<i>generator</i>	Generator for distances

Definition at line 98 of file [tsp.hh](#).

5.176.3.2 load()

```
void load (
    std::string path )
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 30 of file [tsp.cc](#).

5.176.3.3 load_()

```
void load_ (
    std::istream & stream ) [private]
```

Load an instance.

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 38 of file [tsp.cc](#).

5.176.3.4 random()

```
void random (
    int n ) [inline]
```

Random instance.

Parameters

<i>n</i>	Number of vertices
----------	--------------------

Distances are sampled from the normal distribution.

Definition at line 116 of file [tsp.hh](#).

5.176.3.5 save()

```
void save (
    std::string path ) const
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 164 of file [tsp.cc](#).

5.176.3.6 save_()

```
void save_ (
    std::ostream & stream ) const [private]
```

Save an instance.

Warning

Does nothing

Definition at line 172 of file [tsp.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/tsp.hh](#)
- [lib/hnco/functions/collection/tsp.cc](#)

5.177 TwoRateOnePlusLambdaEa Class Reference

Two-rate (1+lambda) evolutionary algorithm.

```
#include <hnco/algorithms/evolutionary-algorithms/two-rate-one-plus-lambda-ea.↵  
hh>
```

Inheritance diagram for TwoRateOnePlusLambdaEa:



Public Member Functions

- **TwoRateOnePlusLambdaEa** (int n, int population_size)
Constructor.

Setters

- void [set_mutation_rate_init](#) (double rate)
- void **set_allow_no_mutation** (bool b)
Allow no mutation.

Setters for logging

- void [set_log_mutation_rate](#) (bool b)

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual **~Algorithm** ()
Destructor.
- int **get_bv_size** () const
Get bit vector size.
- void **set_log_context** ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & **get_solution** ()
Get the solution.

Protected Member Functions

- void **set_something_to_log** ()
Set flag for something to log.

Loop

- void [init](#) () override
- void **iterate** () override
Single iteration.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population.
- [neighborhood::StandardBitMutation](#) **_mutation_operator**
Mutation operator.
- double **_mutation_rate**
Mutation rate.

Parameters

- double **_mutation_rate_init**
- double **_mutation_rate_min**
Minimum mutation rate.
- double **_mutation_rate_max** = 0.25
Maximum mutation rate.
- bool **_allow_no_mutation** = false
Allow no mutation.

Logging

- bool **_log_mutation_rate** = false

Protected Attributes inherited from [IterativeAlgorithm](#)

- int **_iteration**
Current iteration.
- bool **_last_iteration** = false
Last iteration.
- bool **_something_to_log** = false
Something to log.
- int **_num_iterations** = 0
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.177.1 Detailed Description

Two-rate (1+lambda) evolutionary algorithm.

Reference:

Benjamin Doerr, Christian Gießen, Carsten Witt, and Jing Yang.

1. The (1+lambda) evolutionary algorithm with self-adjusting mutation rate. In Proceedings of the Genetic and Evolutionary Computation Conference (GECCO '17). Association for Computing Machinery, New York, NY, USA, 1351–1358. <https://doi.org/10.1145/3071178.3071279>

Definition at line 43 of file [two-rate-one-plus-lambda-ea.hh](#).

5.177.2 Member Function Documentation

5.177.2.1 `init()`

```
void init ( ) [override], [protected], [virtual]
```

Initialization

Reimplemented from [IterativeAlgorithm](#).

Definition at line 31 of file [two-rate-one-plus-lambda-ea.cc](#).

5.177.2.2 `set_log_mutation_rate()`

```
void set_log_mutation_rate (
    bool b ) [inline]
```

Log mutation rate

Definition at line 69 of file [two-rate-one-plus-lambda-ea.hh](#).

5.177.2.3 `set_mutation_rate_init()`

```
void set_mutation_rate_init (
    double rate ) [inline]
```

Set the initial mutation rate

Definition at line 59 of file [two-rate-one-plus-lambda-ea.hh](#).

5.177.3 Member Data Documentation

5.177.3.1 `_log_mutation_rate`

```
bool _log_mutation_rate = false [protected]
```

Log entropy

Definition at line 99 of file [two-rate-one-plus-lambda-ea.hh](#).

5.177.3.2 `_mutation_rate_init`

```
double _mutation_rate_init [protected]
```

Initial mutation rate

Definition at line 85 of file [two-rate-one-plus-lambda-ea.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/two-rate-one-plus-lambda-ea.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/two-rate-one-plus-lambda-ea.cc](#)

5.178 Umda Class Reference

Univariate marginal distribution algorithm.

```
#include <hnco/algorithms/probability-vector/umda.hh>
```

Inheritance diagram for Umda:



Public Member Functions

- **Umda** (int n, int population_size)
Constructor.

Setters

- void **set_selection_size** (int x)
Set the selection size.

Public Member Functions inherited from **PvAlgorithm**

- **PvAlgorithm** (int n)
Constructor.
- void **set_log_entropy** (bool x)
Log entropy.
- void **set_log_num_components** (int x)
Set the number of probability vector components to log.
- void **set_log_pv** (bool x)
Log probability vector.

Public Member Functions inherited from [IterativeAlgorithm](#)

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) (const std::vector< [function::Function](#) * > &functions) override
Maximize.
- void [set_num_iterations](#) (int n)
Set the number of iterations.

Public Member Functions inherited from [Algorithm](#)

- **Algorithm** (int n)
Constructor.
- virtual \sim **Algorithm** ()
Destructor.
- int [get_bv_size](#) () const
Get bit vector size.
- void [set_log_context](#) ([logging::LogContext](#) *log_context)
Set the log context.
- virtual void [finalize](#) ()
Finalize.
- virtual const [solution_t](#) & [get_solution](#) ()
Get the solution.

Protected Member Functions

Loop

- void **init** () override
Initialize.
- void **iterate** () override
Single iteration.

Protected Member Functions inherited from [PvAlgorithm](#)

- void [set_something_to_log](#) ()
Set flag for something to log.
- void **log** () override
Log.

Protected Member Functions inherited from [IterativeAlgorithm](#)

- virtual void [loop](#) () final
Loop.

Protected Member Functions inherited from [Algorithm](#)

- void **set_functions** (const std::vector< [function::Function](#) * > &functions)
Set functions.
- void **random_solution** ()
Random solution.
- void **set_solution** (const [bit_vector_t](#) &bv, double value)
Set solution.
- void **set_solution** (const [bit_vector_t](#) &bv)
Set solution.
- void **update_solution** (const [bit_vector_t](#) &bv, double value)
Update solution (strict)
- void **update_solution** (const [solution_t](#) &s)
Update solution (strict)
- void **update_solution** (const [bit_vector_t](#) &bv)
Update solution (strict).

Protected Attributes

- [Population](#) **_population**
Population.

Parameters

- int **_selection_size** = 1
Selection size.

Protected Attributes inherited from [PvAlgorithm](#)

- [pv_t](#) **_pv**
Probability vector.
- double **_lower_bound**
Lower bound of probability.
- double **_upper_bound**
Upper bound of probability.
- bool **_log_entropy** = false
Log entropy.
- bool **_log_pv** = false
Log probability vector.
- int **_log_num_components** = 5
Number of probability vector components to log.

Protected Attributes inherited from [IterativeAlgorithm](#)

- `int _iteration`
Current iteration.
- `bool _last_iteration = false`
Last iteration.
- `bool _something_to_log = false`
Something to log.
- `int _num_iterations = 0`
Number of iterations.

Protected Attributes inherited from [Algorithm](#)

- `std::vector< function::Function * > _functions`
Functions.
- `function::Function * _function`
Function.
- `solution_t _solution`
Solution.
- `logging::LogContext * _log_context = nullptr`
Log context.

5.178.1 Detailed Description

Univariate marginal distribution algorithm.

Reference:

H. Mühlenbein. 1997. The equation for response to selection and its use for prediction. *Evolutionary Computation* 5, 3 (1997), 303–346.

Definition at line 41 of file [umda.hh](#).

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/probability-vector/umda.hh`
- `lib/hnco/algorithms/probability-vector/umda.cc`

5.179 UniformCrossover Class Reference

Uniform crossover.

```
#include <hnco/algorithms/evolutionary-algorithms/crossover.hh>
```

Inheritance diagram for UniformCrossover:



Public Member Functions

- void `recombine` (const `bit_vector_t` &parent1, const `bit_vector_t` &parent2, `bit_vector_t` &offspring)
Recombine.

Public Member Functions inherited from `Crossover`

- virtual `~Crossover` ()
Destructor.

5.179.1 Detailed Description

Uniform crossover.

Definition at line 56 of file `crossover.hh`.

5.179.2 Member Function Documentation

5.179.2.1 `recombine()`

```
void recombine (  
    const bit_vector_t & parent1,  
    const bit_vector_t & parent2,  
    bit_vector_t & offspring ) [virtual]
```

Recombine.

The offspring is the uniform crossover of two parents.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implements [Crossover](#).

Definition at line 30 of file [crossover.cc](#).

The documentation for this class was generated from the following files:


- [lib/hnco/algorithms/evolutionary-algorithms/crossover.hh](#)
- [lib/hnco/algorithms/evolutionary-algorithms/crossover.cc](#)

5.180 UniformSelection Class Reference

Uniform selection.

```
#include <hnco/algorithms/evolutionary-algorithms/random-selection.hh>
```

Inheritance diagram for UniformSelection:



Public Member Functions

- [UniformSelection](#) (const [Population](#) &population)
Constructor.
- const [bit_vector_t](#) & **select** () override
Select an individual in the population.

Public Member Functions inherited from [RandomSelection](#)

- [RandomSelection](#) (const [Population](#) &population)
Constructor.
- virtual void **init** ()
Initialize.

Private Attributes

- `std::uniform_int_distribution< int > _choose_individual`
Random index.

Additional Inherited Members

Protected Attributes inherited from [RandomSelection](#)

- `const Population & _population`
Population to select from

5.180.1 Detailed Description

Uniform selection.

Definition at line 58 of file [random-selection.hh](#).

5.180.2 Constructor & Destructor Documentation

5.180.2.1 UniformSelection()

```
UniformSelection (
    const Population & population ) [inline]
```

Constructor.

Parameters

<i>population</i>	Population to select from
-------------------	---------------------------

Definition at line 67 of file [random-selection.hh](#).

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/evolutionary-algorithms/random-selection.hh`
- `lib/hnco/algorithms/evolutionary-algorithms/random-selection.cc`

5.181 UniversalFunction Class Reference

Universal function.

```
#include <hnco/functions/universal-function.hh>
```

Public Member Functions

- virtual `~UniversalFunction ()`
Destructor.
- virtual double **evaluate** (const [bit_vector_t](#) &boolean_vars, const std::vector< int > &integer_vars, const std::vector< double > &float_vars, const std::vector< std::complex< double > > &complex_vars, const std::vector< int > &categorical_vars, const std::vector< [permutation_t](#) > &permutation_vars)=0
Evaluate the function.
- virtual void **display** (std::ostream &stream) const
Display the function.
- virtual void **describe** (const [bit_vector_t](#) &boolean_vars, const std::vector< int > &integer_vars, const std::vector< double > &float_vars, const std::vector< std::complex< double > > &complex_vars, const std::vector< int > &categorical_vars, const std::vector< [permutation_t](#) > &permutation_vars, std::ostream &stream)
Describe variables in the context of the function.

5.181.1 Detailed Description

Universal function.

A universal function is a function taking parameters of all types (boolean, integer, float, complex, categorical, permutation) and returning a double.

Definition at line 40 of file [universal-function.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/functions/universal-function.hh

5.182 UniversalFunction Class Reference

Universal function.

```
#include <hnco/multiobjective/functions/universal-function.hh>
```

Public Member Functions

- virtual `~UniversalFunction ()`
Destructor.
- virtual int **get_output_size** () const =0
Get output size (number of objectives)
- virtual void **evaluate** (const [bit_vector_t](#) &boolean_vars, const std::vector< int > &integer_vars, const std::vector< double > &float_vars, const std::vector< std::complex< double > > &complex_vars, const std::vector< int > &categorical_vars, const std::vector< [permutation_t](#) > &permutation_vars, [value_t](#) &value)=0
Evaluate the function.
- virtual void **display** (std::ostream &stream) const
Display the function.
- virtual void **describe** (const [bit_vector_t](#) &boolean_vars, const std::vector< int > &integer_vars, const std::vector< double > &float_vars, const std::vector< std::complex< double > > &complex_vars, const std::vector< int > &categorical_vars, const std::vector< [permutation_t](#) > &permutation_vars, std::ostream &stream)
Describe variables in the context of the function.

5.182.1 Detailed Description

Universal function.

A universal function is a function taking parameters of all types (boolean, integer, float, complex, categorical, permutation) and returning a double.

Definition at line 43 of file [universal-function.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/multiobjective/functions/universal-function.hh](#)

5.183 UniversalFunctionAdapter Class Reference

Universal function adapter.

```
#include <hnco/functions/universal-function-adapter.hh>
```

Inheritance diagram for UniversalFunctionAdapter:



Public Member Functions

- [UniversalFunctionAdapter](#) ([UniversalFunction](#) *fn, int num_boolean_vars, std::vector< [representation::DyadicIntegerRepresentation](#) > integer_reps, std::vector< [representation::DyadicFloatRepresentation](#) < double > > float_reps, std::vector< [representation::ComplexRepresentation](#) < [DoubleRep](#) > > complex_reps, std::vector< [representation::LinearCategoricalRepresentation](#) > categorical_reps, std::vector< [representation::PermutationRepresentation](#) > permutation_reps)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &bv) override
Evaluate a bit vector.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual `~Function ()`
Destructor.
- virtual double `get_maximum ()` const
Get the global maximum.
- virtual bool `has_known_maximum ()` const
Check for a known maximum.
- virtual bool `provides_incremental_evaluation ()` const
Check whether the function provides incremental evaluation.
- virtual double `evaluate_incrementally` (const `bit_vector_t` &x, double value, const `sparse_bit_vector_t` &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.

Private Member Functions

- void `unpack` (const `bit_vector_t` &bv)
Unpack bit vector into variables.

Private Attributes

- `UniversalFunction * _function`
Universal function.
- `std::vector< representation::DyadicIntegerRepresentation< int > > _integer_reps`
Integer representations.
- `std::vector< representation::DyadicFloatRepresentation< double > > _float_reps`
Float representations.
- `std::vector< representation::ComplexRepresentation< DoubleRep > > _complex_reps`
Complex representations.
- `std::vector< representation::LinearCategoricalRepresentation > _categorical_reps`
Categorical representations.
- `std::vector< representation::PermutationRepresentation > _permutation_reps`
Permutation representations.
- `bit_vector_t _boolean_vars`
Boolean variables.
- `std::vector< int > _integer_vars`
Integer variables.
- `std::vector< double > _float_vars`
Float variables.
- `std::vector< std::complex< double > > _complex_vars`
Complex variables.
- `std::vector< int > _categorical_vars`
Categorical variables.
- `std::vector< permutation_t > _permutation_vars`
Permutation variables.
- int `_bv_size`
Bit vector size.

5.183.1 Detailed Description

Universal function adapter.

A universal function adapter turns a universal function into a regular hnco function defined on bit vectors.

Definition at line 45 of file [universal-function-adapter.hh](#).

5.183.2 Constructor & Destructor Documentation

5.183.2.1 UniversalFunctionAdapter()

```
UniversalFunctionAdapter (
    UniversalFunction * fn,
    int num_boolean_vars,
    std::vector< representation::DyadicIntegerRepresentation< int > > integer_reps,
    std::vector< representation::DyadicFloatRepresentation< double > > float_reps,
    std::vector< representation::ComplexRepresentation< DoubleRep > > complex_reps,
    std::vector< representation::LinearCategoricalRepresentation > categorical_reps,
    std::vector< representation::PermutationRepresentation > permutation_reps ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Universal function
<i>num_boolean_vars</i>	Number of boolean variables
<i>integer_reps</i>	Integer representations
<i>float_reps</i>	Float representations
<i>complex_reps</i>	Complex representations
<i>categorical_reps</i>	Categorical representations
<i>permutation_reps</i>	Permutation representations

Replace reps with {} if there is no corresponding variable. For example, if there is no categorical variable,

[UniversalFunctionAdapter](#)(fn, num_boolean_vars, integer_reps, float_reps, complex_reps, {}, permutation_reps)

Definition at line 134 of file [universal-function-adapter.hh](#).

The documentation for this class was generated from the following file:


- lib/hnco/functions/universal-function-adapter.hh

5.184 UniversalFunctionAdapter Class Reference

Universal function adapter.

```
#include <hnco/multiobjective/functions/universal-function-adapter.hh>
```


Inheritance diagram for UniversalFunctionAdapter:



Public Member Functions

- [UniversalFunctionAdapter](#) ([UniversalFunction](#) *fn, int num_boolean_vars, std::vector< [representation::DyadicIntegerRepresentation](#) > integer_reps, std::vector< [representation::DyadicFloatRepresentation](#) < double > > float_reps, std::vector< [representation::ComplexRepresentation](#) < [DoubleRep](#) > > complex_reps, std::vector< [representation::LinearCategoricalRepresentation](#) > categorical_reps, std::vector< [representation::PermutationRepresentation](#) > permutation_reps)
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- int **get_output_size** () const override
Get output size (number of objectives)
- void **evaluate** (const [bit_vector_t](#) &bv, [value_t](#) &value) override
Evaluate a bit vector.
- void **display** (std::ostream &stream) const override
Display.
- void **describe** (const [bit_vector_t](#) &bv, std::ostream &stream) override
Describe a bit vector.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.

Private Member Functions

- void **unpack** (const [bit_vector_t](#) &bv)
Unpack bit vector into variables.

Private Attributes

- [UniversalFunction](#) * **_function**
Universal function.
- `std::vector< representation::DyadicIntegerRepresentation< int > > _integer_reps`
Integer representations.
- `std::vector< DoubleRep > _float_reps`
Float representations.
- `std::vector< representation::ComplexRepresentation< DoubleRep > > _complex_reps`
Complex representations.
- `std::vector< representation::LinearCategoricalRepresentation > _categorical_reps`
Categorical representations.
- `std::vector< representation::PermutationRepresentation > _permutation_reps`
Permutation representations.
- [bit_vector_t](#) **_boolean_vars**
Boolean variables.
- `std::vector< int > _integer_vars`
Integer variables.
- `std::vector< double > _float_vars`
Float variables.
- `std::vector< std::complex< double > > _complex_vars`
Complex variables.
- `std::vector< int > _categorical_vars`
Categorical variables.
- `std::vector< permutation_t > _permutation_vars`
Permutation variables.
- `int _bv_size`
Bit vector size.

5.184.1 Detailed Description

Universal function adapter.

A universal function adapter turns a universal function into a regular hnco function defined on bit vectors.

Definition at line 46 of file [universal-function-adapter.hh](#).

5.184.2 Constructor & Destructor Documentation

5.184.2.1 UniversalFunctionAdapter()

```
UniversalFunctionAdapter (
    UniversalFunction * fn,
    int num_boolean_vars,
    std::vector< representation::DyadicIntegerRepresentation< int > > integer_reps,
    std::vector< representation::DyadicFloatRepresentation< double > > float_reps,
    std::vector< representation::ComplexRepresentation< DoubleRep > > complex_reps,
    std::vector< representation::LinearCategoricalRepresentation > categorical_reps,
    std::vector< representation::PermutationRepresentation > permutation_reps ) [inline]
```

Constructor.

Parameters

<i>fn</i>	Universal function
<i>num_boolean_vars</i>	Number of boolean variables
<i>integer_reps</i>	Integer representations
<i>float_reps</i>	Float representations
<i>complex_reps</i>	Complex representations
<i>categorical_reps</i>	Categorical representations
<i>permutation_reps</i>	Permutation representations

Replace reps with {} if there is no corresponding variable. For example, if there is no categorical variable,

[UniversalFunctionAdapter](#)(fn, num_boolean_vars, integer_reps, float_reps, complex_reps, {}, permutation_reps)

Definition at line 135 of file [universal-function-adapter.hh](#).

The documentation for this class was generated from the following file:

- lib/hnco/multiobjective/functions/universal-function-adapter.hh

5.185 ValueSetRepresentation< T > Class Template Reference

Value set.

```
#include <hnco/representations/value-set.hh>
```

Public Types

- using **domain_type** = T
Domain type.

Public Member Functions

- [ValueSetRepresentation](#) (const std::vector< T > &values)
Constructor.
- int **size** () const
Size of the representation.
- [domain_type](#) **unpack** (const [bit_vector_t](#) &bv, int start)
Unpack bit vector into a value.
- void **display** (std::ostream &stream) const
Display.

Private Attributes

- std::vector< T > **_values**
Values.
- [DyadicIntegerRepresentation](#)< int > **_index_representation**
Index representation.

5.185.1 Detailed Description

```
template<class T>
class hnco::representation::ValueSetRepresentation< T >
```

Value set.

Definition at line 40 of file [value-set.hh](#).

5.185.2 Constructor & Destructor Documentation

5.185.2.1 ValueSetRepresentation()

```
template<class T >
ValueSetRepresentation (
    const std::vector< T > & values ) [inline]
```

Constructor.

Parameters

<i>values</i>	Values
---------------	--------

Definition at line 53 of file [value-set.hh](#).

The documentation for this class was generated from the following file:


- [lib/hnco/representations/value-set.hh](#)

5.186 WalshExpansion Class Reference

Walsh expansion.

```
#include <hnco/functions/collection/walsh/walsh-expansion.hh>
```

Inheritance diagram for WalshExpansion:



Public Member Functions

- **WalshExpansion** ()
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.
- void **display** (std::ostream &stream) const override
Display.
- void **set_terms** (const std::vector< [function::WalshTerm](#) > terms)
Set terms.

Instance generators

- template<class Generator >
void **generate** (int n, int num_features, Generator generator)
Instance generator.
- void **random** (int n, int num_features)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double **get_maximum** () const
Get the global maximum.
- virtual bool **has_known_maximum** () const
Check for a known maximum.
- virtual bool **provides_incremental_evaluation** () const
Check whether the function provides incremental evaluation.
- virtual double **evaluate_incrementally** (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)
Incrementally evaluate a bit vector.
- virtual double **evaluate_safely** (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void **update** (const [bit_vector_t](#) &x, double value)
Update states after a safe evaluation.
- virtual void **describe** (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- `template<class Archive >`
void **serialize** (Archive &ar, const unsigned int version)
Save.

Private Attributes

- `std::vector< function::WalshTerm > _terms`
Terms.

5.186.1 Detailed Description

Walsh expansion.

Its expression is of the form

$$f(x) = \sum_u a_u (-1)^{x \cdot u}$$

where the sum is over a subset of $\{0, 1\}^n$ and $x \cdot u = \sum_i x_i u_i$ is mod 2. The real numbers a_u are the coefficients of the expansion and the bit vectors u are its feature vectors.

Definition at line 52 of file [walsh-expansion.hh](#).

5.186.2 Member Function Documentation

5.186.2.1 generate()

```
template<class Generator >
void generate (
    int n,
    int num_features,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>num_features</i>	Number of feature vectors
<i>generator</i>	Coefficient generator

Definition at line 85 of file [walsh-expansion.hh](#).

5.186.2.2 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 130 of file [walsh-expansion.hh](#).

5.186.2.3 random()

```
void random (
    int n,
    int num_features ) [inline]
```

Random instance.

The coefficients are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
<i>num_features</i>	Number of feature vectors

Definition at line 111 of file [walsh-expansion.hh](#).

5.186.2.4 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 137 of file [walsh-expansion.hh](#).

The documentation for this class was generated from the following files:


- [lib/hnco/functions/collection/walsh/walsh-expansion.hh](#)
- [lib/hnco/functions/collection/walsh/walsh-expansion.cc](#)

5.187 WalshExpansion1 Class Reference

Walsh expansion of degree 1.

```
#include <hnco/functions/collection/walsh/walsh-expansion-1.hh>
```

Inheritance diagram for WalshExpansion1:



Public Member Functions

- **WalshExpansion1** ()

Constructor.

Instance generators

- template<class Generator >
void **generate** (int n, Generator generator)
Instance generator.
- void **random** (int n)
Random instance.

Load and save instance

- void **load** (std::string path)
Load instance.
- void **save** (std::string path) const
Save instance.

Evaluation

- double **evaluate** (const **bit_vector_t** &) override
Evaluate a bit vector.
- double **evaluate_incrementally** (const **bit_vector_t** &x, double v, const **hnco::sparse_bit_vector_t** &flipped_bits) override
Incrementally evaluate a bit vector.

Information about the function

- int **get_bv_size** () const override
Get bit vector size.
- double **get_maximum** () const override
Get the global maximum.
- bool **has_known_maximum** () const override
Check for a known maximum.
- bool **provides_incremental_evaluation** () const override
Check whether the function provides incremental evaluation.

Public Member Functions inherited from [Function](#)

- virtual `~Function()`
Destructor.
- virtual double `evaluate_safely` (const `bit_vector_t` &x)
Safely evaluate a bit vector.
- virtual void `update` (const `bit_vector_t` &x, double value)
Update states after a safe evaluation.
- virtual void `display` (std::ostream &stream) const
Display.
- virtual void `describe` (const `bit_vector_t` &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- template<class Archive >
void `serialize` (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- std::vector< double > `_linear`
Linear part.

5.187.1 Detailed Description

Walsh expansion of degree 1.

Its expression is of the form

$$f(x) = \sum_i a_i (1 - 2x_i)$$

or equivalently

$$f(x) = \sum_i a_i (-1)^{x_i}$$

Definition at line 49 of file [walsh-expansion-1.hh](#).

5.187.2 Member Function Documentation

5.187.2.1 `generate()`

```
template<class Generator >
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Weight generator

Definition at line 81 of file [walsh-expansion-1.hh](#).

5.187.2.2 has_known_maximum()

```
bool has_known_maximum ( ) const [inline], [override], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 149 of file [walsh-expansion-1.hh](#).

5.187.2.3 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 113 of file [walsh-expansion-1.hh](#).

5.187.2.4 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) const [inline], [override], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 154 of file [walsh-expansion-1.hh](#).

5.187.2.5 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 95 of file [walsh-expansion-1.hh](#).

5.187.2.6 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 120 of file [walsh-expansion-1.hh](#).

The documentation for this class was generated from the following files:


- lib/hnco/functions/collection/walsh/walsh-expansion-1.hh
- lib/hnco/functions/collection/walsh/walsh-expansion-1.cc

5.188 WalshExpansion2 Class Reference

Walsh expansion of degree 2.

```
#include <hnco/functions/collection/walsh/walsh-expansion-2.hh>
```

Inheritance diagram for WalshExpansion2:



Public Member Functions

- **WalshExpansion2** ()
Constructor.
- int **get_bv_size** () const override
Get bit vector size.
- double **evaluate** (const [bit_vector_t](#) &) override
Evaluate a bit vector.

Instance generators

- template<class LinearGen , class QuadraticGen >
void [generate](#) (int n, LinearGen linear_gen, QuadraticGen quadratic_gen)
Instance generators.
- void [random](#) (int n)
Instance generator.
- void [generate_ising1_long_range](#) (int n, double alpha)
Generate one dimensional Ising model with long range interactions.
- void [generate_ising1_long_range_periodic](#) (int n, double alpha)
Generate one dimensional Ising model with long range interactions and periodic boundary conditions.

Load and save instance

- void [load](#) (std::string path)
Load instance.
- void [save](#) (std::string path) const
Save instance.

Public Member Functions inherited from [Function](#)

- virtual **~Function** ()
Destructor.
- virtual double [get_maximum](#) () const
Get the global maximum.
- virtual bool **has_known_maximum** () const

- Check for a known maximum.*

 - virtual bool [provides_incremental_evaluation](#) () const

Check whether the function provides incremental evaluation.
- virtual double [evaluate_incrementally](#) (const [bit_vector_t](#) &x, double value, const [sparse_bit_vector_t](#) &flipped_bits)

Incrementally evaluate a bit vector.

 - virtual double [evaluate_safely](#) (const [bit_vector_t](#) &x)

Safely evaluate a bit vector.

 - virtual void [update](#) (const [bit_vector_t](#) &x, double value)

Update states after a safe evaluation.
- virtual void **display** (std::ostream &stream) const

Display.

 - virtual void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)

Describe a bit vector.

Private Member Functions

- template<class Archive >
void **serialize** (Archive &ar, const unsigned int version)
- Serialize.*
- void **resize** (int n)
- Resize data structures.*

Private Attributes

- std::vector< double > **_linear**
- Linear part.*
- std::vector< std::vector< double > > **_quadratic**
- Quadratic part.*

5.188.1 Detailed Description

Walsh expansion of degree 2.

Its expression is of the form

$$f(x) = \sum_i a_i (1 - 2x_i) + \sum_{i < j} a_{ij} (1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_i a_i (-1)^{x_i} + \sum_{i < j} a_{ij} (-1)^{x_i + x_j}$$

Definition at line 49 of file [walsh-expansion-2.hh](#).

5.188.2 Member Function Documentation

5.188.2.1 generate()

```
template<class LinearGen , class QuadraticGen >
void generate (
    int n,
    LinearGen linear_gen,
    QuadraticGen quadratic_gen ) [inline]
```

Instance generators.

Parameters

<i>n</i>	Size of bit vectors
<i>linear_gen</i>	Generator for the linear part
<i>quadratic_gen</i>	Generator for the quadratic part

Definition at line 93 of file [walsh-expansion-2.hh](#).

5.188.2.2 generate_ising1_long_range()

```
void generate_ising1_long_range (
    int n,
    double alpha )
```

Generate one dimensional Ising model with long range interactions.

Similar to a Dyson-Ising model except for the finite, instead of infinite, linear chain of spins.

Its expression is of the form

$$f(x) = \sum_{ij} J(d_{ij})(1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_{ij} J(d_{ij})(-1)^{x_i + x_j}$$

where $J(d_{ij})$ is the interaction between sites i and j , $d_{ij} = |i - j|$, and $J(n) = n^{-\alpha}$.

Since we are maximizing f or minimizing $-f$, the expression of f is compatible with what can be found in physics textbooks.

Parameters

<i>n</i>	Size of bit vectors
<i>alpha</i>	Exponential decay parameter

Definition at line 83 of file [walsh-expansion-2.cc](#).

5.188.2.3 generate_ising1_long_range_periodic()

```
void generate_ising1_long_range_periodic (
    int n,
    double alpha )
```

Generate one dimensional Ising model with long range interactions and periodic boundary conditions.

Similar to a Dyson-Ising model except for the finite, instead of infinite, linear chain of spins.

Its expression is of the form

$$f(x) = \sum_{ij} J(d_{ij})(1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_{ij} J(d_{ij})(-1)^{x_i+x_j}$$

where $J(d_{ij})$ is the interaction between sites i and j , $d_{ij} = \min\{|i-j|, n-|i-j|\}$, and $J(n) = n^{-\alpha}$.

Since we are maximizing f or minimizing $-f$, the expression of f is compatible with what can be found in physics textbooks.

Parameters

<i>n</i>	Size of bit vectors
<i>alpha</i>	Exponential decay parameter

Definition at line 104 of file [walsh-expansion-2.cc](#).

5.188.2.4 load()

```
void load (
    std::string path ) [inline]
```

Load instance.

Parameters

<i>path</i>	Path of the instance to load
-------------	------------------------------

Exceptions

<code>std::runtime_error</code>	
---------------------------------	--

Definition at line 184 of file [walsh-expansion-2.hh](#).

5.188.2.5 random()

```
void random (
    int n ) [inline]
```

Instance generator.

The weights are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 115 of file [walsh-expansion-2.hh](#).

5.188.2.6 save()

```
void save (
    std::string path ) const [inline]
```

Save instance.

Parameters

<i>path</i>	Path of the instance to save
-------------	------------------------------

Exceptions

<i>std::runtime_error</i>	
---------------------------	--

Definition at line 191 of file [walsh-expansion-2.hh](#).

5.188.3 Member Data Documentation**5.188.3.1 _quadratic**

```
std::vector<std::vector<double> > _quadratic [private]
```

Quadratic part.

Represented as a lower triangular matrix (without its diagonal).

Definition at line 71 of file [walsh-expansion-2.hh](#).

The documentation for this class was generated from the following files:

- [lib/hnco/functions/collection/walsh/walsh-expansion-2.hh](#)
- [lib/hnco/functions/collection/walsh/walsh-expansion-2.cc](#)

5.189 WalshTerm Struct Reference

Walsh transform term.

```
#include <hnco/functions/walsh-term.hh>
```

Public Member Functions

- `template<class Archive >`
`void serialize (Archive &ar, const unsigned int version)`
Serialize.

Public Attributes

- `std::vector< bool >` [feature](#)
Feature.
- `double` **coefficient**
Coefficient.

5.189.1 Detailed Description

Walsh transform term.

Definition at line 33 of file [walsh-term.hh](#).

5.189.2 Member Data Documentation

5.189.2.1 feature

```
std::vector<bool> feature
```

Feature.

Implemented with a vector bool instead of a `bit_vector_t` to reduce the memory consumption.

Definition at line 40 of file [walsh-term.hh](#).

The documentation for this struct was generated from the following file:

- `lib/hnco/functions/walsh-term.hh`

Index

- `_crossover_probability`
 - `RamUmda2`, [422](#)
 - `_dominated`
 - `Nsga2ParetoFrontComputation`, [340](#)
 - `_expression`
 - `AbstractMaxSat`, [69](#)
 - `_functions`
 - `Algorithm`, [77](#), [79](#)
 - `_implementation`
 - `Hboa`, [190](#)
 - `Ltga`, [264](#)
 - `ParameterLessPopulationPyramid`, [359](#)
 - `_indices`
 - `ParsedMultivariateFunction< Parser >`, [366](#)
 - `_log_herding_error`
 - `Hea< Herding >`, [196](#)
 - `_log_mutation_rate`
 - `InformationTheoreticEa`, [227](#)
 - `TwoRateOnePlusLambdaEa`, [513](#)
 - `_log_norm_infinite`
 - `BmPbil< GibbsSampler >`, [88](#)
 - `_margin`
 - `Hea< Herding >`, [196](#)
 - `_mutation_rate_init`
 - `TwoRateOnePlusLambdaEa`, [513](#)
 - `_names`
 - `ParsedMultivariateFunction< Parser >`, [366](#)
 - `_ordered_names`
 - `ParsedMultivariateFunction< Parser >`, [366](#)
 - `_patience`
 - `RandomLocalSearch`, [427](#)
 - `_q`
 - `Qubo`, [411](#)
 - `_quadratic`
 - `WalshExpansion2`, [540](#)
 - `_randomize_bit_order`
 - `FullMomentHerding`, [159](#)
 - `TriangularMomentHerding`, [501](#)
 - `_record_evaluation_time`
 - `ProgressTracker`, [398](#)
 - `_selection_size`
 - `BmPbil< GibbsSampler >`, [88](#)
 - `InformationTheoreticEa`, [227](#)
 - `RamUmda`, [417](#)
 - `_tournament_size`
 - `Nsga2`, [339](#)
 - `TournamentSelection`, [484](#)
 - `_variables`
 - `ParsedMultivariateFunction< Parser >`, [366](#)
- `~Logger`
 - `Logger`, [259](#)
- `AbsoluteValue< T >`, [65](#)
- `AbstractMaxSat`, [66](#)
 - `_expression`, [69](#)
 - `load`, [67](#)
 - `load_`, [68](#)
 - `save`, [68](#)
 - `save_`, [68](#)
- `AdditiveGaussianNoise`, [69](#)
 - `get_bv_size`, [71](#)
- `AffineMap`, [71](#)
 - `is_surjective`, [73](#)
 - `load`, [73](#)
 - `random`, [73](#)
 - `save`, [74](#)
- `Algorithm`, [74](#), [78](#)
 - `_functions`, [77](#), [79](#)
 - `Algorithm`, [79](#)
 - `finalize`, [76](#)
 - `set_solution`, [76](#)
 - `update_solution`, [77](#)
- `AlgorithmFactory`, [80](#), [81](#)
 - `make`, [80](#), [81](#)
- `asynchronous`
 - `BmPbil< GibbsSampler >::SamplingMode`, [443](#)
- `asynchronous_full_scan`
 - `BmPbil< GibbsSampler >::SamplingMode`, [443](#)
- `ATT`
 - `Tsp`, [507](#)
- `average`
 - `FullMoment`, [152](#)
 - `TriangularMoment`, [495](#)
- `bernoulli_trials`
 - `MultiBitFlip`, [296](#)
- `BiasedCrossover`, [82](#)
 - `recombine`, [83](#)
- `bit_add`
 - `hnco`, [20](#)
- `bit_flip`
 - `hnco`, [20](#), [21](#)
- `bit_random`
 - `hnco`, [21](#)
- `bit_vector`
 - `BmPbil< GibbsSampler >::ResetMode`, [437](#)
- `bm_add_columns`
 - `hnco`, [21](#)
- `bm_add_rows`

- hnco, 22
- bm_identity
 - hnco, 22
- bm_invert
 - hnco, 23
- bm_multiply
 - hnco, 23
- bm_rank
 - hnco, 24
- bm_row_echelon_form
 - hnco, 24
- bm_set_column
 - hnco, 24
- bm_solve
 - hnco, 25
- bm_solve_upper_triangular
 - hnco, 25
- bm_transpose
 - hnco, 26
- BmPbil< GibbsSampler >, 83
 - _log_norm_infinite, 88
 - _selection_size, 88
 - set_log_norm_infinite, 88
 - set_selection_size, 88
- BmPbil< GibbsSampler >::ResetMode, 436
 - bit_vector, 437
 - iteration, 437
 - no_reset, 437
- BmPbil< GibbsSampler >::SamplingMode, 442
 - asynchronous, 443
 - asynchronous_full_scan, 443
 - synchronous, 443
- BoltzmannSelection, 89
 - BoltzmannSelection, 90
- bound
 - FullMoment, 154
 - TriangularMoment, 495
- bv_add
 - hnco, 26, 27
- bv_flip
 - hnco, 27
- bv_from_size_type
 - hnco, 28
- bv_from_stream
 - hnco, 28
- bv_from_string
 - hnco, 28
- bv_from_vector_bool
 - hnco, 29
- bv_to_size_type
 - hnco, 29, 30
- bv_to_vector_bool
 - hnco, 30
- Cache, 91
 - Cache, 93
 - provides_incremental_evaluation, 93
- CallCounter, 94
- CommandLineAlgorithmFactory, 96, 98
 - make, 97, 99
- CommandLineApplication, 99, 101
 - CommandLineApplication, 100, 102
- CommandLineFunctionFactory, 102, 104
- CommaSelection, 104
 - CommaSelection, 105
- commuting_transvections
 - TsAffineMap::SamplingMode, 443
- CompactGa, 105
- CompleteSearch, 110
- ComplexRepresentation
 - ComplexRepresentation< ScalarRep >, 113
- ComplexRepresentation< ScalarRep >, 112
 - ComplexRepresentation, 113
- compute
 - Nsga2ParetoFrontComputation, 340
- compute_fast_walsh_transform
 - hnco::function, 47
- compute_lengths
 - DyadicFloatRepresentation< T >, 127
- compute_walsh_transform
 - hnco::function, 48
- constant
 - RamUmda::TsLengthMode, 505
- Controller, 114
 - provides_incremental_evaluation, 115
- Crossover, 116
 - recombine, 116
- DeceptiveJump, 117
 - get_maximum, 119
 - has_known_maximum, 119
- DecoratedFunctionFactory, 119
 - make_function_controller, 120
- Decorator, 121, 123
 - Decorator, 123
- decreasing
 - RamUmda::TsLengthMode, 505
- describe
 - Function, 161, 166
 - FunctionMapComposition, 170
- difference_is_safe
 - hnco::representation, 63
- disjoint_transvections
 - TsAffineMap::SamplingMode, 443
- display
 - FullMoment, 154
 - MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >, 281, 284
 - MultiojectiveFunctionAdapter, 298
 - MultivariateFunctionAdapter< Fn, Rep, Conv >, 302, 305
 - TriangularMoment, 495
- dominates
 - hnco::multiojective::function, 61
- DyadicFloatRepresentation
 - DyadicFloatRepresentation< T >, 126
- DyadicFloatRepresentation< T >, 125
 - compute_lengths, 127

- DyadicFloatRepresentation, 126
- DyadicIntegerRepresentation
 - DyadicIntegerRepresentation< T >, 129, 130
- DyadicIntegerRepresentation< T >, 127
 - DyadicIntegerRepresentation, 129, 130
- DyadicIntegerRepresentation< T >::Precision, 391
- EdgeWeightType
 - Tsp, 506
- elitist
 - InformationTheoreticEa::Replacement, 436
- ensure
 - hnco, 30
- EqualProducts, 130
 - generate, 132
 - load, 132
 - random, 133
 - save, 133
- EUC_2D
 - Tsp, 507
- evaluate
 - Function, 161, 166
 - MixedRepresentationMultivariateFunctionAdapter<
 - Fn, RepVariant, Conv >, 281, 284
 - MultiojectiveFunctionAdapter, 298
 - MultivariateFunctionAdapter< Fn, Rep, Conv >,
 - 302, 305
 - NearestNeighborIsingModel1, 312
 - NearestNeighborIsingModel2, 317
 - OnBudgetFunction, 343
 - OppositeFunction, 356
 - Population, 385
 - StopOnTarget, 474
- evaluate_incrementally
 - Function, 162
 - OnBudgetFunction, 343
 - StopOnTarget, 474
- evaluate_safely
 - Function, 162
- ExtendedHypercubeIterator, 134
- Factorization, 136
 - Factorization, 138
 - load, 138
- fail_with
 - hnco, 31
- feature
 - WalshTerm, 541
- FfgenOptions, 139
- finalize
 - Algorithm, 76
- FirstAscentHillClimbing, 143
- FitnessProportionateSelection, 146
 - FitnessProportionateSelection, 147
- FourPeaks, 148
 - get_maximum, 150
 - has_known_maximum, 150
- FrontDistancePair, 151
- FullMoment, 151
 - average, 152
 - bound, 154
 - display, 154
 - FullMoment, 152
 - scaled_difference, 154
 - update, 155
- FullMomentGibbsSampler, 156
- FullMomentHerdling, 157
 - _randomize_bit_order, 159
- FullMomentHerdling, 158
 - get_delta, 158
 - set_randomize_bit_order, 158
- Function, 159, 165
 - describe, 161, 166
 - evaluate, 161, 166
 - evaluate_incrementally, 162
 - evaluate_safely, 162
 - get_maximum, 162
 - provides_incremental_evaluation, 164
 - update, 164
- FunctionFactory, 167
- FunctionMapComposition, 168
 - describe, 170
- FunctionMapComposition, 170
 - get_bv_size, 171
 - get_maximum, 171
 - has_known_maximum, 171
- FunctionPlugin, 172
 - FunctionPlugin, 173
- generate
 - EqualProducts, 132
 - LinearFunction, 248
 - NearestNeighborIsingModel1, 312
 - NearestNeighborIsingModel2, 317
 - NkLandscape, 328
 - Partition, 368
 - Tsp, 507
 - WalshExpansion, 530
 - WalshExpansion1, 533
 - WalshExpansion2, 537
- generate_ising1_long_range
 - WalshExpansion2, 538
- generate_ising1_long_range_periodic
 - WalshExpansion2, 538
- Generator, 173
 - reset, 174
 - set_seed, 174
- GeneticAlgorithm, 175
 - GeneticAlgorithm, 178
- geometric
 - RamUmda::TsLengthMode, 505
- get_best_bv
 - Population, 385
- get_best_index
 - Population, 385, 386
- get_best_value
 - Population, 386
- get_bv_size

- AdditiveGaussianNoise, 71
- FunctionMapComposition, 171
- MixedRepresentationMultivariateFunctionAdapter<
 - Fn, RepVariant, Conv >, 281
- MultiobjectiveFunctionAdapter, 299
- MultivariateFunctionAdapter< Fn, Rep, Conv >,
 - 302, 305
- OppositeFunction, 356
- get_delta
 - FullMomentHerdning, 158
 - TriangularMomentHerdning, 500
- get_equivalent_bvs
 - Population, 387
- get_last_improvement
 - ProgressTracker, 398
- get_maximum
 - DeceptiveJump, 119
 - FourPeaks, 150
 - Function, 162
 - FunctionMapComposition, 171
 - Hiff, 198
 - Jump, 240
 - LeadingOnes, 244
 - LongPath, 261
 - Needle, 320
 - OneMax, 345
 - Plateau, 381
 - PriorNoise, 394
 - PythonFunction, 406
 - Ridge, 442
 - SixPeaks, 461
 - Trap, 493
- get_size
 - Population, 387
- get_worst_bv
 - Population, 387
- Gomea, 178
- HammingBall, 181
 - HammingBall, 183
- HammingSphere, 183
 - HammingSphere, 185
- HammingSphereIterator, 186
 - HammingSphereIterator, 187
- has_known_maximum
 - DeceptiveJump, 119
 - FourPeaks, 150
 - FunctionMapComposition, 171
 - Hiff, 198
 - Jump, 240
 - LeadingOnes, 244
 - LinearFunction, 249
 - LongPath, 261
 - Needle, 320
 - OneMax, 345
 - Plateau, 381
 - PriorNoise, 394
 - Ridge, 442
 - SixPeaks, 461
 - SummationCancellation, 481
 - Trap, 493
 - WalshExpansion1, 534
- Hboa, 188
 - _implementation, 190
- Hea
 - Hea< Herding >, 194
- Hea< Herding >, 190
 - _log_herdning_error, 196
 - _margin, 196
 - Hea, 194
 - init, 194
 - set_log_herdning_error, 194
 - set_margin, 195
 - set_reset_period, 195
 - set_selection_size, 195
- Hiff, 196
 - get_maximum, 198
 - has_known_maximum, 198
- hnco, 15
 - bit_add, 20
 - bit_flip, 20, 21
 - bit_random, 21
 - bm_add_columns, 21
 - bm_add_rows, 22
 - bm_identity, 22
 - bm_invert, 23
 - bm_multiply, 23
 - bm_rank, 24
 - bm_row_echelon_form, 24
 - bm_set_column, 24
 - bm_solve, 25
 - bm_solve_upper_triangular, 25
 - bm_transpose, 26
 - bv_add, 26, 27
 - bv_flip, 27
 - bv_from_size_type, 28
 - bv_from_stream, 28
 - bv_from_string, 28
 - bv_from_vector_bool, 29
 - bv_to_size_type, 29, 30
 - bv_to_vector_bool, 30
 - ensure, 30
 - fail_with, 31
 - is_in_range, 31
 - load_from_archive, 32
 - perm_identity, 32
 - perm_random, 32
 - save_to_archive, 33
 - sbv_is_valid, 33
 - sparse_bit_vector_t, 20
- hnco::algorithm, 34
 - pv_add, 37
 - pv_average, 38
 - pv_bound, 38
 - pv_init, 39
 - pv_sample, 39
 - pv_uniform, 39

- pv_update, [39, 40](#)
- hnco::algorithm::fast_efficient_p3, [40](#)
- hnco::algorithm::gomea, [41](#)
- hnco::algorithm::walsh_moment, [41](#)
- hnco::app, [42](#)
 - parse_representation, [43](#)
 - parse_representations, [43](#)
- hnco::exception, [44](#)
- hnco::function, [45](#)
 - compute_fast_walsh_transform, [47](#)
 - compute_walsh_transform, [48](#)
- hnco::function::controller, [48](#)
- hnco::function::modifier, [49](#)
- hnco::logging, [50](#)
- hnco::map, [50](#)
 - transvection_sequence_t, [52](#)
 - ts_invert, [52](#)
 - ts_is_valid, [52](#)
 - ts_multiply, [53](#)
 - ts_random, [54](#)
 - ts_random_commuting, [54](#)
 - ts_random_disjoint, [55](#)
 - ts_random_non_commuting, [55](#)
 - ts_random_unique_destination, [56](#)
 - ts_random_unique_source, [56](#)
- hnco::multiobjective, [58](#)
- hnco::multiobjective::algorithm, [58](#)
 - operator<, [59](#)
- hnco::multiobjective::app, [59](#)
- hnco::multiobjective::function, [60](#)
 - dominates, [61](#)
 - value_t, [61](#)
- hnco::neighborhood, [61](#)
- hnco::random, [62](#)
- hnco::representation, [62](#)
 - difference_is_safe, [63](#)
- HncoEvaluator, [198](#)
- HncoFitness, [199](#)
- HncoOptions, [200, 214](#)
- Human, [218](#)
- Hypercubeliterator, [221](#)
- Implementation, [222](#)
- increasing
 - RamUmda::TsLengthMode, [505](#)
- incremental_ml_update
 - InformationTheoreticEa::Replacement, [436](#)
- InformationTheoreticEa, [223](#)
 - _log_mutation_rate, [227](#)
 - _selection_size, [227](#)
 - init, [226](#)
 - set_log_mutation_rate, [226](#)
 - set_selection_size, [227](#)
- InformationTheoreticEa::Replacement, [435](#)
 - elitist, [436](#)
 - incremental_ml_update, [436](#)
 - ml_update, [436](#)
 - no_replacement, [436](#)
 - non_elitist, [436](#)
- init
 - Hea< Herding >, [194](#)
 - InformationTheoreticEa, [226](#)
 - Nsga2, [338](#)
 - RamUmda, [416](#)
 - RamUmda2, [422](#)
 - TwoRateOnePlusLambdaEa, [512](#)
- init_beta
 - SimulatedAnnealing, [453](#)
- Injection, [228](#)
 - Injection, [229](#)
- IntegerCategoricalRepresentation, [229](#)
 - IntegerCategoricalRepresentation, [230](#)
- is_in_range
 - hnco, [31](#)
- is_non_dominated
 - Nsga2ParetoFrontComputation, [340](#)
- is_surjective
 - AffineMap, [73](#)
 - LinearMap, [252](#)
 - Map, [265](#)
 - MapComposition, [267](#)
 - Permutation, [375](#)
 - Projection, [401](#)
 - Translation, [487](#)
 - TsAffineMap, [503](#)
- is_valid
 - Transvection, [489](#)
- iterate
 - Restart, [439](#)
- iteration
 - BmPbil< GibbsSampler >::ResetMode, [437](#)
- IterativeAlgorithm, [231, 235](#)
 - IterativeAlgorithm, [233, 237](#)
 - loop, [234, 237](#)
 - maximize, [234](#)
 - minimize, [237](#)
 - set_num_iterations, [234, 237](#)
- Iterator, [238](#)
- Jump, [239](#)
 - get_maximum, [240](#)
 - has_known_maximum, [240](#)
- Labs, [241](#)
- LastEvaluation, [243](#)
- LeadingOnes, [243](#)
 - get_maximum, [244](#)
 - has_known_maximum, [244](#)
- LinearCategoricalRepresentation, [245](#)
 - LinearCategoricalRepresentation, [246](#)
- LinearFunction, [246](#)
 - generate, [248](#)
 - has_known_maximum, [249](#)
 - load, [249](#)
 - provides_incremental_evaluation, [249](#)
 - random, [249](#)
 - save, [250](#)
- LinearMap, [250](#)

- is_surjective, [252](#)
- load, [252](#)
- random, [252](#)
- save, [253](#)
- load
 - AbstractMaxSat, [67](#)
 - AffineMap, [73](#)
 - EqualProducts, [132](#)
 - Factorization, [138](#)
 - LinearFunction, [249](#)
 - LinearMap, [252](#)
 - MaxNae3Sat, [271](#)
 - NearestNeighborIsingModel1, [313](#)
 - NearestNeighborIsingModel2, [317](#)
 - NkLandscape, [329](#)
 - Partition, [369](#)
 - Permutation, [375](#)
 - Qubo, [410](#), [411](#)
 - Sudoku, [477](#)
 - Translation, [487](#)
 - TsAffineMap, [503](#)
 - Tsp, [507](#)
 - WalshExpansion, [530](#)
 - WalshExpansion1, [534](#)
 - WalshExpansion2, [539](#)
- load_
 - AbstractMaxSat, [68](#)
 - Sudoku, [478](#)
 - Tsp, [507](#)
- load_from_archive
 - hnco, [32](#)
- LocalSearchAlgorithm< Neighborhood >, [253](#)
- LogContext, [256](#)
- Logger, [257](#)
 - ~Logger, [259](#)
 - Logger, [258](#)
- LongPath, [259](#)
 - get_maximum, [261](#)
 - has_known_maximum, [261](#)
- loop
 - IterativeAlgorithm, [234](#), [237](#)
- Ltga, [262](#)
 - _implementation, [264](#)
- make
 - AlgorithmFactory, [80](#), [81](#)
 - CommandLineAlgorithmFactory, [97](#), [99](#)
- make_function_controller
 - DecoratedFunctionFactory, [120](#)
- Map, [264](#)
 - is_surjective, [265](#)
- map
 - Neighborhood, [323](#)
- MapComposition, [266](#)
 - is_surjective, [267](#)
 - MapComposition, [267](#)
- MapgenOptions, [268](#)
- maximize
 - IterativeAlgorithm, [234](#)
 - MaxNae3Sat, [270](#)
 - load, [271](#)
 - MaxSat, [272](#)
 - random, [274](#)
 - Mimic, [275](#)
 - minimize
 - IterativeAlgorithm, [237](#)
 - MixedRepresentationMultivariateFunctionAdapter
 - MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >, [280](#), [284](#)
 - MixedRepresentationMultivariateFunctionAdapter< Fn, RepVariant, Conv >, [278](#), [282](#)
 - display, [281](#), [284](#)
 - evaluate, [281](#), [284](#)
 - get_bv_size, [281](#)
 - MixedRepresentationMultivariateFunctionAdapter, [280](#), [284](#)
 - ml_update
 - InformationTheoreticEa::Replacement, [436](#)
 - Mmas, [285](#)
 - mode
 - TsAffineMap::SamplingMode, [443](#)
 - Modifier, [289](#)
 - MuCommaLambdaEa, [290](#)
 - MuCommaLambdaEa, [293](#)
 - MultiBitFlip, [294](#)
 - bernoulli_trials, [296](#)
 - MultiBitFlip, [295](#)
 - rejection_sampling, [296](#)
 - MultiobjectiveFunctionAdapter, [296](#)
 - display, [298](#)
 - evaluate, [298](#)
 - get_bv_size, [299](#)
 - MultiobjectiveFunctionAdapter, [298](#)
 - multiply
 - Transvection, [489](#), [490](#)
 - MultivariateFunctionAdapter
 - MultivariateFunctionAdapter< Fn, Rep, Conv >, [301](#), [305](#)
 - MultivariateFunctionAdapter< Fn, Rep, Conv >, [299](#), [303](#)
 - display, [302](#), [305](#)
 - evaluate, [302](#), [305](#)
 - get_bv_size, [302](#), [305](#)
 - MultivariateFunctionAdapter, [301](#), [305](#)
 - MuPlusLambdaEa, [306](#)
 - MuPlusLambdaEa, [309](#)
 - mutate
 - Neighborhood, [324](#)
 - NearestNeighborIsingModel1, [310](#)
 - evaluate, [312](#)
 - generate, [312](#)
 - load, [313](#)
 - provides_incremental_evaluation, [313](#)
 - random, [313](#)
 - save, [314](#)
 - NearestNeighborIsingModel2, [314](#)
 - evaluate, [317](#)

- generate, 317
- load, 317
- provides_incremental_evaluation, 318
- random, 318
- save, 318
- Needle, 319
 - get_maximum, 320
 - has_known_maximum, 320
- Neighborhood, 321
 - map, 323
 - mutate, 324
 - Neighborhood, 323
- NeighborhoodIterator, 324
 - NeighborhoodIterator, 325
- NkLandscape, 326
 - generate, 328
 - load, 329
 - random, 329
 - random_structure, 329
 - save, 330
- no_replacement
 - InformationTheoreticEa::Replacement, 436
- no_reset
 - BmPbil< GibbsSampler >::ResetMode, 437
- non_commuting_transvections
 - TsAffineMap::SamplingMode, 443
- non_elitist
 - InformationTheoreticEa::Replacement, 436
- NpsPbil, 330
- Nsga2, 335
 - _tournament_size, 339
 - init, 338
 - Nsga2, 338
 - set_tournament_size, 338
- Nsga2ParetoFrontComputation, 339
 - _dominated, 340
 - compute, 340
 - is_non_dominated, 340
- OnBudgetFunction, 341
 - evaluate, 343
 - evaluate_incrementally, 343
 - update, 343
- OneMax, 344
 - get_maximum, 345
 - has_known_maximum, 345
 - provides_incremental_evaluation, 346
- OnePlusLambdaCommaLambdaGa, 346
 - OnePlusLambdaCommaLambdaGa, 349
- OnePlusOneEa, 350
 - OnePlusOneEa, 352
 - set_num_iterations, 352
- operator<
 - hnco::multiobjective::algorithm, 59
- OppositeAbsoluteValue< T >, 353
- OppositeFunction, 354
 - evaluate, 356
 - get_bv_size, 356
 - provides_incremental_evaluation, 356
- OppositeSquaredMagnitude< T >, 356
- ParameterLessPopulationPyramid, 357
 - _implementation, 359
- parse_representation
 - hnco::app, 43
- parse_representations
 - hnco::app, 43
- ParsedModifier, 360
 - ParsedModifier, 362
- ParsedMultivariateFunction
 - ParsedMultivariateFunction< Parser >, 363, 365
- ParsedMultivariateFunction< Parser >, 362, 364
 - _indices, 366
 - _names, 366
 - _ordered_names, 366
 - _variables, 366
 - ParsedMultivariateFunction, 363, 365
- partial_sort
 - Population, 388
- Partition, 367
 - generate, 368
 - load, 369
 - random, 369
 - save, 369
- Pbil, 370
- perm_identity
 - hnco, 32
- perm_random
 - hnco, 32
- Permutation, 374
 - is_surjective, 375
 - load, 375
 - save, 376
- PermutationFunctionAdapter
 - PermutationFunctionAdapter< Fn >, 378
- PermutationFunctionAdapter< Fn >, 376
 - PermutationFunctionAdapter, 378
- PermutationRepresentation, 379
 - PermutationRepresentation, 379
- Plateau, 380
 - get_maximum, 381
 - has_known_maximum, 381
- PlusSelection, 382
 - PlusSelection, 382
- Population, 383, 388
 - evaluate, 385
 - get_best_bv, 385
 - get_best_index, 385, 386
 - get_best_value, 386
 - get_equivalent_bvs, 387
 - get_size, 387
 - get_worst_bv, 387
 - partial_sort, 388
 - Population, 384, 389
 - resize, 390
 - shrink, 390
 - sort, 388
- PriorNoise, 391

- get_maximum, 394
 - has_known_maximum, 394
 - provides_incremental_evaluation, 394
- ProgressTracker, 395
 - _record_evaluation_time, 398
 - get_last_improvement, 398
- ProgressTracker::Event, 134
- ProgressTrackerContext, 398
 - to_string, 399
- Projection, 400
 - is_surjective, 401
 - Projection, 401
- provides_incremental_evaluation
 - Cache, 93
 - Controller, 115
 - Function, 164
 - LinearFunction, 249
 - NearestNeighborIsingModel1, 313
 - NearestNeighborIsingModel2, 318
 - OneMax, 346
 - OppositeFunction, 356
 - PriorNoise, 394
 - WalshExpansion1, 534
- pv_add
 - hnco::algorithm, 37
- pv_average
 - hnco::algorithm, 38
- pv_bound
 - hnco::algorithm, 38
- pv_init
 - hnco::algorithm, 39
- pv_sample
 - hnco::algorithm, 39
- pv_uniform
 - hnco::algorithm, 39
- pv_update
 - hnco::algorithm, 39, 40
- PvAlgorithm, 402
- PythonFunction, 405, 407
 - get_maximum, 406
 - PythonFunction, 406, 408
- Qubo, 408
 - _q, 411
 - load, 410, 411
- RamUmda, 412
 - _selection_size, 417
 - init, 416
 - set_selection_size, 416
- RamUmda2, 417
 - _crossover_probability, 422
 - init, 422
 - set_crossover_probability, 422
- RamUmda::TsLengthMode, 504
 - constant, 505
 - decreasing, 505
 - geometric, 505
 - increasing, 505
 - reverse_geometric, 505
 - uniform, 505
- random
 - AffineMap, 73
 - EqualProducts, 133
 - LinearFunction, 249
 - LinearMap, 252
 - MaxSat, 274
 - NearestNeighborIsingModel1, 313
 - NearestNeighborIsingModel2, 318
 - NkLandscape, 329
 - Partition, 369
 - Sudoku, 478
 - Transvection, 490
 - TsAffineMap, 503
 - Tsp, 508
 - WalshExpansion, 531
 - WalshExpansion1, 534
 - WalshExpansion2, 539
- random_non_commuting
 - Transvection, 491
- random_structure
 - NkLandscape, 329
- RandomLocalSearch, 423
 - _patience, 427
 - set_patience, 426
- RandomSearch, 427
- RandomSelection, 430
 - RandomSelection, 431
- RandomWalk, 431
- recombine
 - BiasedCrossover, 83
 - Crossover, 116
 - UniformCrossover, 518
- rejection_sampling
 - MultiBitFlip, 296
- reset
 - Generator, 174
- resize
 - Population, 390
- Restart, 437
 - iterate, 439
 - set_num_iterations, 440
- reverse_geometric
 - RamUmda::TsLengthMode, 505
- Ridge, 440
 - get_maximum, 442
 - has_known_maximum, 442
- save
 - AbstractMaxSat, 68
 - AffineMap, 74
 - EqualProducts, 133
 - LinearFunction, 250
 - LinearMap, 253
 - NearestNeighborIsingModel1, 314
 - NearestNeighborIsingModel2, 318
 - NkLandscape, 330
 - Partition, 369

- Permutation, 376
- Sudoku, 478
- Translation, 488
- TsAffineMap, 504
- Tsp, 508
- WalshExpansion, 531
- WalshExpansion1, 535
- WalshExpansion2, 539
- save_
 - AbstractMaxSat, 68
 - Tsp, 508
- save_to_archive
 - hnco, 33
- sbv_is_valid
 - hnco, 33
- ScalarToDouble< T >, 444
- scaled_difference
 - FullMoment, 154
 - TriangularMoment, 495
- select
 - TournamentSelection, 483
- SelfAdjustingOnePlusOneEa, 445
- set_crossover_probability
 - RamUmda2, 422
- set_log_herding_error
 - Hea< Herding >, 194
- set_log_mutation_rate
 - InformationTheoreticEa, 226
 - TwoRateOnePlusLambdaEa, 512
- set_log_norm_infinite
 - BmPbil< GibbsSampler >, 88
- set_margin
 - Hea< Herding >, 195
- set_mutation_rate
 - StandardBitMutation, 465
- set_mutation_rate_init
 - TwoRateOnePlusLambdaEa, 512
- set_num_iterations
 - IterativeAlgorithm, 234, 237
 - OnePlusOneEa, 352
 - Restart, 440
- set_patience
 - RandomLocalSearch, 426
- set_randomize_bit_order
 - FullMomentHerding, 158
 - TriangularMomentHerding, 500
- set_reset_period
 - Hea< Herding >, 195
- set_seed
 - Generator, 174
- set_selection_size
 - BmPbil< GibbsSampler >, 88
 - Hea< Herding >, 195
 - InformationTheoreticEa, 227
 - RamUmda, 416
- set_solution
 - Algorithm, 76
- set_tournament_size
 - Nsga2, 338
 - TournamentSelection, 483
- shrink
 - Population, 390
- SimulatedAnnealing, 449
 - init_beta, 453
- SingleBitFlip, 453
- SingleBitFlipIterator, 455
 - SingleBitFlipIterator, 456
- SinusSummationCancellation, 456
- SixPeaks, 459
 - get_maximum, 461
 - has_known_maximum, 461
- sort
 - Population, 388
- sparse_bit_vector_t
 - hnco, 20
- SquaredMagnitude< T >, 461
- StandardBitMutation, 462
 - set_mutation_rate, 465
 - StandardBitMutation, 464, 465
- SteepestAscentHillClimbing, 466
- StopOnMaximum, 469
 - StopOnMaximum, 471
- StopOnTarget, 472
 - evaluate, 474
 - evaluate_incrementally, 474
 - StopOnTarget, 474
 - update, 475
- StopWatch, 475
- Sudoku, 476
 - load, 477
 - load_, 478
 - random, 478
 - save, 478
- SummationCancellation, 479
 - has_known_maximum, 481
 - SummationCancellation, 480
- synchronous
 - BmPbil< GibbsSampler >::SamplingMode, 443
- TargetReached, 481
- to_string
 - ProgressTrackerContext, 399
- TournamentSelection, 482
 - _tournament_size, 484
 - select, 483
 - set_tournament_size, 483
 - TournamentSelection, 483
- TournamentSelection< T, Compare >, 484
- Translation, 486
 - is_surjective, 487
 - load, 487
 - save, 488
- Transvection, 488
 - is_valid, 489
 - multiply, 489, 490
 - random, 490
 - random_non_commuting, 491

- transvection_sequence_t
 - hnco::map, 52
- Trap, 491
 - get_maximum, 493
 - has_known_maximum, 493
 - Trap, 493
- TriangularMoment, 494
 - average, 495
 - bound, 495
 - display, 495
 - scaled_difference, 495
 - TriangularMoment, 494
 - update, 496
- TriangularMomentGibbsSampler, 498
- TriangularMomentHerdning, 499
 - _randomize_bit_order, 501
 - get_delta, 500
 - set_randomize_bit_order, 500
 - TriangularMomentHerdning, 500
- ts_invert
 - hnco::map, 52
- ts_is_valid
 - hnco::map, 52
- ts_multiply
 - hnco::map, 53
- ts_random
 - hnco::map, 54
- ts_random_commuting
 - hnco::map, 54
- ts_random_disjoint
 - hnco::map, 55
- ts_random_non_commuting
 - hnco::map, 55
- ts_random_unique_destination
 - hnco::map, 56
- ts_random_unique_source
 - hnco::map, 56
- TsAffineMap, 501
 - is_surjective, 503
 - load, 503
 - random, 503
 - save, 504
- TsAffineMap::SamplingMode, 443
 - commuting_transvections, 443
 - disjoint_transvections, 443
 - mode, 443
 - non_commuting_transvections, 443
 - unconstrained, 443
 - unique_destination, 443
 - unique_source, 443
- Tsp, 505
 - ATT, 507
 - EdgeWeightType, 506
 - EUC_2D, 507
 - generate, 507
 - load, 507
 - load_, 507
 - random, 508
 - save, 508
 - save_, 508
- TwoRateOnePlusLambdaEa, 509
 - _log_mutation_rate, 513
 - _mutation_rate_init, 513
 - init, 512
 - set_log_mutation_rate, 512
 - set_mutation_rate_init, 512
- Umda, 513
- unconstrained
 - TsAffineMap::SamplingMode, 443
- uniform
 - RamUmda::TsLengthMode, 505
- UniformCrossover, 518
 - recombine, 518
- UniformSelection, 519
 - UniformSelection, 520
- unique_destination
 - TsAffineMap::SamplingMode, 443
- unique_source
 - TsAffineMap::SamplingMode, 443
- UniversalFunction, 520, 521
- UniversalFunctionAdapter, 522, 524
 - UniversalFunctionAdapter, 524, 526
- update
 - FullMoment, 155
 - Function, 164
 - OnBudgetFunction, 343
 - StopOnTarget, 475
 - TriangularMoment, 496
- update_solution
 - Algorithm, 77
- value_t
 - hnco::multiobjective::function, 61
- ValueSetRepresentation
 - ValueSetRepresentation< T >, 528
- ValueSetRepresentation< T >, 527
 - ValueSetRepresentation, 528
- WalshExpansion, 528
 - generate, 530
 - load, 530
 - random, 531
 - save, 531
- WalshExpansion1, 532
 - generate, 533
 - has_known_maximum, 534
 - load, 534
 - provides_incremental_evaluation, 534
 - random, 534
 - save, 535
- WalshExpansion2, 535
 - _quadratic, 540
 - generate, 537
 - generate_ising1_long_range, 538
 - generate_ising1_long_range_periodic, 538
 - load, 539

random, [539](#)
save, [539](#)
WalshTerm, [540](#)
feature, [541](#)