

HNCO

Influence of the learning rate on the performance of PBIL

August 31, 2021

Abstract

PBIL is applied many times to the same collection of fitness functions (bit vector size $n = 100$), each time with a different learning rate taken from a finite set of values. All learning rates are ranked according to their median fitness over 20 independent runs, first for each fitness function, then across the entire collection of fitness functions. The mean and standard deviation of fitness are also plotted as a function of the learning rate.



Contents

| | | |
|-----------|------------------------------|-----------|
| 1 | Global results | 1 |
| 2 | Function one-max | 2 |
| 3 | Function leading-ones | 4 |
| 4 | Function jmp-5 | 6 |
| 5 | Function nk | 8 |
| 6 | Function max-sat | 10 |
| 7 | Function labs | 12 |
| 8 | Function ep | 14 |
| 9 | Function cancel | 16 |
| 10 | Function walsh2 | 18 |
| A | Plan | 19 |
| B | Default parameters | 20 |


1 Global results


| Learning rate | Rank | | | | |
|---------------|------|-------|------|-------|-----|
| | min | Q_1 | med. | Q_3 | max |
| 1 | 1 | 1.00 | 1.0 | 1.00 | 6 |
| 0.01 | 1 | 1.00 | 2.0 | 2.00 | 7 |
| 0.02 | 1 | 1.00 | 3.0 | 3.00 | 4 |
| 0.5 | 1 | 2.00 | 3.0 | 6.00 | 7 |
| 0.05 | 1 | 1.00 | 4.0 | 6.00 | 7 |
| 0.1 | 1 | 4.00 | 4.0 | 6.00 | 7 |
| 0.2 | 1 | 3.00 | 5.0 | 5.00 | 7 |

2 Function one-max





| Learning rate | Function value | | | | |
|---------------|----------------|--------|-------|--------|-----|
| | min | Q_1 | med. | Q_3 | max |
| 0.01 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.02 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.05 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.1 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.2 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.5 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 1 | 100 | 100.00 | 100.0 | 100.00 | 100 |







3 Function leading-ones





| Learning rate | Function value | | | | |
|---------------|----------------|--------|-------|--------|-----|
| | min | Q_1 | med. | Q_3 | max |
| 0.01 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.02 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.05 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.1 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.2 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.5 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 1 | 100 | 100.00 | 100.0 | 100.00 | 100 |







4 Function jmp-5





| Learning rate | Function value | | | | |
|---------------|----------------|---------------|--------------|---------------|------------|
| | min | Q_1 | med. | Q_3 | max |
| 0.01 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.02 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.05 | 100 | 100.00 | 100.0 | 100.00 | 100 |
| 0.1 | 95 | 100.00 | 100.0 | 100.00 | 100 |
| 0.2 | 95 | 95.00 | 95.0 | 95.00 | 100 |
| 0.5 | 95 | 95.00 | 95.0 | 95.00 | 95 |
| 1 | 95 | 95.00 | 95.0 | 95.00 | 95 |







5 Function nk





| Learning rate | Function value | | | | |
|---------------|----------------|----------------|--------------|----------------|-------------|
| | min | Q_1 | med. | Q_3 | max |
| 1 | 0.84 | 0.917,5 | 0.938 | 0.960,3 | 0.98 |
| 0.01 | 0.88 | 0.905,6 | 0.920 | 0.943,5 | 0.99 |
| 0.02 | 0.84 | 0.882,7 | 0.905 | 0.927,3 | 1.01 |
| 0.05 | 0.80 | 0.873,1 | 0.892 | 0.934,5 | 0.97 |
| 0.2 | 0.80 | 0.842,0 | 0.860 | 0.889,3 | 0.94 |
| 0.1 | 0.80 | 0.844,1 | 0.859 | 0.886,8 | 0.95 |
| 0.5 | 0.79 | 0.824,7 | 0.849 | 0.907,9 | 0.97 |







6 Function max-sat





| Learning rate | Function value | | | | |
|---------------|----------------|---------------|--------------|---------------|------------|
| | min | Q_1 | med. | Q_3 | max |
| 1 | 963 | 966.00 | 967.0 | 967.00 | 968 |
| 0.01 | 965 | 965.00 | 966.0 | 967.00 | 967 |
| 0.02 | 963 | 964.75 | 966.0 | 967.00 | 967 |
| 0.05 | 960 | 964.75 | 966.0 | 967.00 | 967 |
| 0.2 | 957 | 964.00 | 965.0 | 967.00 | 968 |
| 0.1 | 959 | 964.00 | 965.0 | 967.00 | 967 |
| 0.5 | 959 | 961.75 | 963.0 | 967.00 | 967 |







7 Function labs





| Learning rate | Function value | | | | |
|---------------|----------------|----------------|--------------|----------------|-------------|
| | min | Q_1 | med. | Q_3 | max |
| 1 | 4.47 | 4.725,9 | 4.817 | 4.970,4 | 5.54 |
| 0.5 | 3.95 | 4.085,3 | 4.188 | 4.262,6 | 4.71 |
| 0.2 | 3.52 | 3.690,2 | 3.906 | 4.019,6 | 4.62 |
| 0.02 | 3.34 | 3.745,3 | 3.906 | 3.943,3 | 4.39 |
| 0.05 | 3.37 | 3.589,6 | 3.894 | 4.095,0 | 4.42 |
| 0.1 | 3.43 | 3.681,9 | 3.876 | 4.146,1 | 4.66 |
| 0.01 | 3.25 | 3.725,9 | 3.858 | 4.081,8 | 4.67 |







8 Function ep





| Learning rate | Function value | | | | |
|---------------|-----------------------|-------------------------|------------------------|-------------------------|-----------------------|
| | min | Q_1 | med. | Q_3 | max |
| 1 | 6.4×10^{-29} | 8.927×10^{-28} | 5.62×10^{-27} | 1.028×10^{-26} | 1.6×10^{-26} |
| 0.01 | 5.4×10^{-28} | 3.108×10^{-27} | 6.40×10^{-27} | 1.314×10^{-26} | 5.4×10^{-26} |
| 0.5 | 6.4×10^{-29} | 4.523×10^{-27} | 8.04×10^{-27} | 2.183×10^{-26} | 6.3×10^{-26} |
| 0.02 | 1.4×10^{-27} | 5.575×10^{-27} | 1.18×10^{-26} | 2.686×10^{-26} | 5.0×10^{-26} |
| 0.2 | 1.7×10^{-27} | 1.160×10^{-26} | 2.76×10^{-26} | 5.574×10^{-26} | 1.2×10^{-25} |
| 0.05 | 5.5×10^{-28} | 1.298×10^{-26} | 3.04×10^{-26} | 5.844×10^{-26} | 9.9×10^{-26} |
| 0.1 | 1.5×10^{-27} | 9.633×10^{-27} | 4.09×10^{-26} | 6.983×10^{-26} | 2.6×10^{-25} |







9 Function cancel





| Learning rate | Function value | | | | |
|---------------|----------------|----------------|--------------|----------------|-------------|
| | min | Q_1 | med. | Q_3 | max |
| 0.01 | 0.04 | 0.097,5 | 0.185 | 0.305,0 | 1.33 |
| 0.02 | 0.09 | 0.237,5 | 0.455 | 0.727,5 | 1.64 |
| 1 | 0.12 | 0.390,0 | 0.755 | 1.382,5 | 1.97 |
| 0.1 | 0.12 | 0.667,5 | 0.985 | 1.755,0 | 3.03 |
| 0.5 | 0.16 | 0.417,5 | 1.195 | 1.992,5 | 2.96 |
| 0.05 | 0.35 | 0.875,0 | 1.200 | 1.820,0 | 2.98 |
| 0.2 | 0.08 | 0.927,5 | 1.420 | 1.927,5 | 4.18 |







10 Function walsh2



| Learning rate | Function value | | | | |
|---------------|----------------|---------------|---------------|---------------|---------------|
| | min | Q_1 | med. | Q_3 | max |
| 1 | 681.90 | 717.40 | 725.26 | 728.67 | 740.55 |
| 0.5 | 654.29 | 679.89 | 689.477 | 703.958 | 728.55 |
| 0.02 | 617.32 | 654.36 | 680.890 | 706.381 | 726.07 |
| 0.1 | 611.54 | 658.97 | 680.462 | 698.162 | 727.67 |
| 0.2 | 631.53 | 663.06 | 680.143 | 702.004 | 726.48 |
| 0.01 | 593.18 | 657.67 | 679.825 | 691.700 | 733.81 |
| 0.05 | 567.56 | 652.50 | 677.868 | 697.966 | 732.02 |





A Plan

```
{
  "exec": "hnco",
  "opt": "-A 500 -x 10 -y 1 --print-results --map 1 --map-random -s 100",
  "budget": 200000,
  "num_runs": 20,
  "parallel": true,
  "parameter": {
    "id": "learning-rate",
    "name": "Learning rate",
    "values": [ 1e-2, 2e-2, 5e-2, 1e-1, 2e-1, 5e-1, 1 ]
  },
  "graphics": {
    "logscale": true,
    "candlesticks": {
      "title": true,
      "boxwidth": "$1 * 0.3"
    }
  },
  "functions": [
    {
      "id": "one-max",
      "opt": "-F 0 --stop-on-maximum",
      "rounding": {
        "value": { "before": 3, "after": 0 },
        "time": { "before": 1, "after": 2 } }
    },
    {
      "id": "leading-ones",
      "opt": "-F 10 --stop-on-maximum",
      "rounding": {
        "value": { "before": 3, "after": 0 },
        "time": { "before": 1, "after": 2 } }
    },
    {
      "id": "jmp-5",
      "opt": "-F 30 --stop-on-maximum -t 5",
      "rounding": {
        "value": { "before": 3, "after": 0 },
        "time": { "before": 1, "after": 2 } }
    },
    {
      "id": "nk",
      "opt": "-F 60 -p instances/nk.100.4",

```

```

        "rounding": {
            "value": { "before": 1, "after": 2 },
            "time": { "before": 1, "after": 2 } }
    },
    {
        "id": "max-sat",
        "opt": "-F 70 -p instances/ms.100.3.1000",
        "rounding": {
            "value": { "before": 3, "after": 0 },
            "time": { "before": 1, "after": 2 } }
    },
    {
        "id": "labs",
        "opt": "-F 81",
        "rounding": {
            "value": { "before": 1, "after": 2 },
            "time": { "before": 1, "after": 2 } }
    },
    {
        "id": "ep",
        "opt": "-F 90 -p instances/ep.100",
        "reverse": true,
        "logscale": true,
        "rounding": {
            "value": { "before": 1, "after": 1 },
            "time": { "before": 1, "after": 2 } }
    },
    {
        "id": "cancel",
        "opt": "-F 100 -s 99",
        "reverse": true,
        "rounding": {
            "value": { "before": 1, "after": 2 },
            "time": { "before": 1, "after": 2 } }
    },
    {
        "id": "walsh2",
        "opt": "-F 162 -p instances/walsh2.100",
        "rounding": {
            "value": { "before": 3, "after": 2 },
            "time": { "before": 1, "after": 2 } }
    }
}
]
}

```

B Default parameters

```

# algorithm = 100
# bm_mc_reset_strategy = 1
# bm_num_gs_cycles = 1
# bm_num_gs_steps = 100
# bm_sampling = 1
# budget = 10000
# bv_size = 100
# description_path = description.txt
# ea_lambda = 100
# ea_mu = 10
# expression = x
# fn_name = noname
# fn_num_traps = 10
# fn_prefix_length = 2
# fn_threshold = 10

```

```

# fp_expression = (1-x)^2+100*(y-x^2)^2
# fp_lower_bound = -2
# fp_num_bits = 8
# fp_precision = 0.01
# fp_upper_bound = 2
# function = 0
# ga_crossover_bias = 0.5
# ga_crossover_probability = 0.5
# ga_tournament_size = 10
# hea_bit_herding = 0
# hea_num_seq_updates = 100
# hea_reset_period = 0
# hea_sampling_method = 0
# hea_weight = 1
# learning_rate = 0.001
# map = 0
# map_input_size = 100
# map_path = map.txt
# map_ts_length = 10
# map_ts_sampling_mode = 0
# mutation_rate = 1
# neighborhood = 0
# neighborhood_iterator = 0
# noise_stddev = 1
# num_iterations = 0
# num_threads = 1
# path = function.txt
# pn_mutation_rate = 1
# pn_neighborhood = 0
# pn_radius = 2
# population_size = 10
# pv_log_num_components = 5
# radius = 2
# rep_categorical_representation = 0
# results_path = results.json
# rls_patience = 50
# sa_beta_ratio = 1.2
# sa_initial_acceptance_probability = 0.6
# sa_num_transitions = 50
# sa_num_trials = 100
# seed = 0
# selection_size = 1
# solution_path = solution.txt
# target = 100
# print_defaults
# last_parameter
# exec_name = hnco
# version = 0.18
# Generated from hnco.json

```