

HNCO

0.13

Generated by Doxygen 1.8.13

Contents

1	Namespace Index	1
1.1	Namespace List	1
2	Hierarchical Index	3
2.1	Class Hierarchy	3
3	Class Index	7
3.1	Class List	7
4	Namespace Documentation	13
4.1	hnco Namespace Reference	13
4.1.1	Detailed Description	18
4.1.2	Typedef Documentation	18
4.1.2.1	bit_t	18
4.1.2.2	sparse_bit_matrix_t	18
4.1.2.3	sparse_bit_vector_t	18
4.1.2.4	transvection_sequence_t	19
4.1.3	Function Documentation	19
4.1.3.1	bm_add_columns()	19
4.1.3.2	bm_add_rows()	19
4.1.3.3	bm_identity() [1/2]	20
4.1.3.4	bm_identity() [2/2]	20
4.1.3.5	bm_invert()	20
4.1.3.6	bm_multiply()	21
4.1.3.7	bm_rank()	21

4.1.3.8	bm_row_echelon_form()	22
4.1.3.9	bm_solve()	22
4.1.3.10	bm_solve_upper_triangular()	23
4.1.3.11	bv_from_vector_bool()	23
4.1.3.12	bv_to_vector_bool()	24
4.1.3.13	is_in_range() [1/2]	24
4.1.3.14	is_in_range() [2/2]	24
4.1.3.15	perm_identity()	25
4.1.3.16	perm_random()	25
4.1.3.17	sbm_multiply()	25
4.1.3.18	ts_is_valid() [1/2]	25
4.1.3.19	ts_is_valid() [2/2]	26
4.1.3.20	ts_multiply() [1/2]	26
4.1.3.21	ts_multiply() [2/2]	27
4.1.3.22	ts_random()	27
4.1.3.23	ts_random_commuting()	28
4.1.3.24	ts_random_disjoint()	28
4.1.3.25	ts_random_non_commuting()	29
4.1.3.26	ts_random_unique_destination()	29
4.1.3.27	ts_random_unique_source()	30
4.2	hnco::algorithm Namespace Reference	30
4.2.1	Detailed Description	32
4.3	hnco::algorithm::bm_pbil Namespace Reference	33
4.3.1	Detailed Description	33
4.4	hnco::algorithm::hea Namespace Reference	33
4.4.1	Detailed Description	33
4.5	hnco::exception Namespace Reference	33
4.5.1	Detailed Description	34
4.6	hnco::function Namespace Reference	34
4.6.1	Detailed Description	36
4.7	hnco::function::real Namespace Reference	36
4.7.1	Detailed Description	37
4.8	hnco::neighborhood Namespace Reference	37
4.8.1	Detailed Description	37
4.9	hnco::random Namespace Reference	38
4.9.1	Detailed Description	38

5	Class Documentation	39
5.1	AbstractLabs Class Reference	39
5.1.1	Detailed Description	40
5.2	AbstractMaxSat Class Reference	40
5.2.1	Detailed Description	41
5.2.2	Member Function Documentation	41
5.2.2.1	load()	41
5.2.3	Member Data Documentation	41
5.2.3.1	_expression	41
5.3	AdditiveGaussianNoise Class Reference	42
5.3.1	Detailed Description	43
5.4	AffineMap Class Reference	43
5.4.1	Detailed Description	44
5.4.2	Member Function Documentation	44
5.4.2.1	is_surjective()	44
5.4.2.2	random()	44
5.5	Algorithm Class Reference	45
5.5.1	Detailed Description	47
5.5.2	Member Function Documentation	47
5.5.2.1	set_solution()	47
5.5.2.2	update_solution()	48
5.5.3	Member Data Documentation	48
5.5.3.1	_functions	48
5.6	BernoulliProcess Class Reference	48
5.6.1	Detailed Description	49
5.6.2	Constructor & Destructor Documentation	49
5.6.2.1	BernoulliProcess() [1/2]	49
5.6.2.2	BernoulliProcess() [2/2]	50
5.6.3	Member Function Documentation	50
5.6.3.1	set_allow_stay()	50

5.6.3.2	set_probability()	50
5.7	BiasedCrossover Class Reference	51
5.7.1	Detailed Description	51
5.7.2	Member Function Documentation	51
5.7.2.1	breed()	51
5.8	BitHerding Class Reference	52
5.8.1	Detailed Description	53
5.8.2	Member Enumeration Documentation	53
5.8.2.1	anonymous enum	53
5.9	BitMoment Struct Reference	54
5.9.1	Detailed Description	55
5.10	BmPbil Class Reference	55
5.10.1	Detailed Description	57
5.10.2	Member Enumeration Documentation	57
5.10.2.1	anonymous enum	57
5.10.2.2	anonymous enum	58
5.10.2.3	anonymous enum	58
5.10.3	Member Function Documentation	58
5.10.3.1	set_selection_size()	58
5.11	Cache Class Reference	59
5.11.1	Detailed Description	60
5.11.2	Constructor & Destructor Documentation	60
5.11.2.1	Cache()	60
5.11.3	Member Function Documentation	60
5.11.3.1	provides_incremental_evaluation()	61
5.12	CallCounter Class Reference	61
5.12.1	Detailed Description	62
5.13	CompactGa Class Reference	62
5.13.1	Detailed Description	64
5.14	CompleteSearch Class Reference	64

5.14.1 Detailed Description	65
5.15 Crossover Class Reference	65
5.15.1 Detailed Description	65
5.15.2 Member Function Documentation	66
5.15.2.1 breed()	66
5.16 DeceptiveJump Class Reference	66
5.16.1 Detailed Description	67
5.16.2 Member Function Documentation	67
5.16.2.1 get_maximum()	67
5.16.2.2 has_known_maximum()	68
5.17 DyadicRealRepresentation Class Reference	68
5.17.1 Detailed Description	69
5.17.2 Constructor & Destructor Documentation	69
5.17.2.1 DyadicRealRepresentation()	69
5.18 EqualProducts Class Reference	70
5.18.1 Detailed Description	71
5.18.2 Member Function Documentation	71
5.18.2.1 generate()	71
5.18.2.2 random()	71
5.19 Error Class Reference	73
5.19.1 Detailed Description	74
5.20 ProgressTracker::Event Struct Reference	74
5.20.1 Detailed Description	74
5.21 Exception Class Reference	74
5.21.1 Detailed Description	75
5.22 Factorization Class Reference	75
5.22.1 Detailed Description	76
5.22.2 Constructor & Destructor Documentation	76
5.22.2.1 Factorization()	76
5.22.3 Member Function Documentation	77

5.22.3.1	load()	77
5.23	FirstAscentHillClimbing Class Reference	77
5.23.1	Detailed Description	78
5.24	FourPeaks Class Reference	79
5.24.1	Detailed Description	80
5.24.2	Member Function Documentation	80
5.24.2.1	get_maximum()	80
5.24.2.2	has_known_maximum()	81
5.25	Function Class Reference	81
5.25.1	Detailed Description	83
5.25.2	Member Function Documentation	83
5.25.2.1	compute_walsh_transform()	83
5.25.2.2	get_maximum()	84
5.25.2.3	incremental_eval()	84
5.25.2.4	provides_incremental_evaluation()	85
5.25.2.5	safe_eval()	85
5.26	FunctionController Class Reference	86
5.26.1	Detailed Description	87
5.26.2	Member Function Documentation	87
5.26.2.1	provides_incremental_evaluation()	87
5.27	FunctionDecorator Class Reference	87
5.27.1	Detailed Description	88
5.28	FunctionMapComposition Class Reference	88
5.28.1	Detailed Description	89
5.28.2	Constructor & Destructor Documentation	89
5.28.2.1	FunctionMapComposition()	89
5.28.3	Member Function Documentation	90
5.28.3.1	get_maximum()	90
5.28.3.2	has_known_maximum()	90
5.29	FunctionModifier Class Reference	91

5.29.1 Detailed Description	91
5.30 FunctionPlugin Class Reference	92
5.30.1 Detailed Description	93
5.30.2 Constructor & Destructor Documentation	93
5.30.2.1 FunctionPlugin()	93
5.31 GeneticAlgorithm Class Reference	93
5.31.1 Detailed Description	95
5.31.2 Constructor & Destructor Documentation	95
5.31.2.1 GeneticAlgorithm()	95
5.31.3 Member Function Documentation	96
5.31.3.1 set_allow_stay()	96
5.32 HammingBall Class Reference	96
5.32.1 Detailed Description	97
5.32.2 Constructor & Destructor Documentation	97
5.32.2.1 HammingBall()	97
5.33 HammingSphere Class Reference	98
5.33.1 Detailed Description	99
5.33.2 Constructor & Destructor Documentation	99
5.33.2.1 HammingSphere()	99
5.34 HammingSphereIterator Class Reference	99
5.34.1 Detailed Description	100
5.34.2 Constructor & Destructor Documentation	101
5.34.2.1 HammingSphereIterator()	101
5.35 Hboa Class Reference	101
5.35.1 Detailed Description	102
5.36 Hea< Moment, Herding > Class Template Reference	102
5.36.1 Detailed Description	105
5.36.2 Member Enumeration Documentation	105
5.36.2.1 anonymous enum	105
5.36.3 Constructor & Destructor Documentation	105

5.36.3.1	Hea()	105
5.36.4	Member Function Documentation	106
5.36.4.1	set_reset_period()	106
5.36.4.2	set_selection_size()	106
5.37	Hiff Class Reference	107
5.37.1	Detailed Description	107
5.37.2	Member Function Documentation	108
5.37.2.1	get_maximum()	108
5.37.2.2	has_known_maximum()	108
5.38	HncoEvaluator Class Reference	108
5.38.1	Detailed Description	109
5.39	Hypercubeliterator Class Reference	109
5.39.1	Detailed Description	110
5.40	Injection Class Reference	110
5.40.1	Detailed Description	111
5.40.2	Constructor & Destructor Documentation	111
5.40.2.1	Injection()	111
5.41	IterativeAlgorithm Class Reference	112
5.41.1	Detailed Description	113
5.41.2	Constructor & Destructor Documentation	113
5.41.2.1	IterativeAlgorithm()	113
5.41.3	Member Function Documentation	114
5.41.3.1	maximize()	114
5.41.3.2	set_num_iterations()	114
5.42	Iterator Class Reference	115
5.42.1	Detailed Description	116
5.43	Jump Class Reference	116
5.43.1	Detailed Description	117
5.43.2	Member Function Documentation	117
5.43.2.1	get_maximum()	117

5.43.2.2	has_known_maximum()	117
5.44	Labs Class Reference	118
5.44.1	Detailed Description	118
5.45	LabsMeritFactor Class Reference	119
5.45.1	Detailed Description	119
5.46	LastEvaluation Class Reference	120
5.46.1	Detailed Description	120
5.47	LeadingOnes Class Reference	120
5.47.1	Detailed Description	121
5.47.2	Member Function Documentation	121
5.47.2.1	get_maximum()	121
5.47.2.2	has_known_maximum()	122
5.48	LinearFunction Class Reference	122
5.48.1	Detailed Description	123
5.48.2	Member Function Documentation	124
5.48.2.1	generate()	124
5.48.2.2	has_known_maximum()	124
5.48.2.3	provides_incremental_evaluation()	124
5.48.2.4	random()	124
5.49	LinearMap Class Reference	125
5.49.1	Detailed Description	126
5.49.2	Member Function Documentation	126
5.49.2.1	is_surjective()	126
5.49.2.2	random()	126
5.50	LocalMaximum Class Reference	127
5.50.1	Detailed Description	128
5.51	LogContext Class Reference	128
5.51.1	Detailed Description	128
5.52	LongPath Class Reference	129
5.52.1	Detailed Description	130

5.52.2	Member Function Documentation	130
5.52.2.1	get_maximum()	130
5.52.2.2	has_known_maximum()	131
5.53	Ltga Class Reference	131
5.53.1	Detailed Description	132
5.54	Map Class Reference	132
5.54.1	Detailed Description	133
5.54.2	Member Function Documentation	134
5.54.2.1	is_surjective()	134
5.55	MapComposition Class Reference	134
5.55.1	Detailed Description	135
5.55.2	Constructor & Destructor Documentation	135
5.55.2.1	MapComposition()	135
5.55.3	Member Function Documentation	136
5.55.3.1	is_surjective()	136
5.56	MaximumReached Class Reference	136
5.56.1	Detailed Description	137
5.57	MaxNae3Sat Class Reference	137
5.57.1	Detailed Description	138
5.57.2	Member Function Documentation	138
5.57.2.1	load()	138
5.58	MaxSat Class Reference	138
5.58.1	Detailed Description	139
5.58.2	Member Function Documentation	139
5.58.2.1	random() [1/2]	139
5.58.2.2	random() [2/2]	140
5.59	Mimic Class Reference	140
5.59.1	Detailed Description	142
5.60	Mmas Class Reference	143
5.60.1	Detailed Description	144

5.61	Model Class Reference	144
5.61.1	Detailed Description	145
5.62	ModelParameters Class Reference	145
5.62.1	Detailed Description	146
5.63	MuCommaLambdaEa Class Reference	146
5.63.1	Detailed Description	147
5.63.2	Constructor & Destructor Documentation	147
5.63.2.1	MuCommaLambdaEa()	147
5.63.3	Member Function Documentation	148
5.63.3.1	set_allow_stay()	148
5.64	MultiBitFlip Class Reference	148
5.64.1	Detailed Description	149
5.64.2	Constructor & Destructor Documentation	149
5.64.2.1	MultiBitFlip()	149
5.64.3	Member Function Documentation	149
5.64.3.1	bernoulli_trials()	149
5.64.3.2	reservoir_sampling()	150
5.65	MuPlusLambdaEa Class Reference	150
5.65.1	Detailed Description	151
5.65.2	Constructor & Destructor Documentation	152
5.65.2.1	MuPlusLambdaEa()	152
5.65.3	Member Function Documentation	152
5.65.3.1	set_allow_stay()	152
5.66	NearestNeighborIsingModel1 Class Reference	153
5.66.1	Detailed Description	154
5.66.2	Member Function Documentation	155
5.66.2.1	eval()	155
5.66.2.2	generate()	155
5.66.2.3	provides_incremental_evaluation()	155
5.66.2.4	random()	156

5.67 NearestNeighborIsingModel2 Class Reference	156
5.67.1 Detailed Description	158
5.67.2 Member Function Documentation	158
5.67.2.1 eval()	158
5.67.2.2 generate()	158
5.67.2.3 provides_incremental_evaluation()	159
5.67.2.4 random()	159
5.68 Needle Class Reference	160
5.68.1 Detailed Description	160
5.68.2 Member Function Documentation	161
5.68.2.1 get_maximum()	161
5.68.2.2 has_known_maximum()	161
5.69 Negation Class Reference	162
5.69.1 Detailed Description	163
5.69.2 Member Function Documentation	163
5.69.2.1 provides_incremental_evaluation()	163
5.70 Neighborhood Class Reference	164
5.70.1 Detailed Description	165
5.70.2 Constructor & Destructor Documentation	165
5.70.2.1 Neighborhood()	165
5.70.3 Member Function Documentation	166
5.70.3.1 map()	166
5.70.3.2 mutate()	166
5.71 NeighborhoodIterator Class Reference	167
5.71.1 Detailed Description	167
5.71.2 Constructor & Destructor Documentation	167
5.71.2.1 NeighborhoodIterator()	167
5.72 NkLandscape Class Reference	168
5.72.1 Detailed Description	169
5.72.2 Member Function Documentation	169

5.72.2.1	generate()	169
5.72.2.2	random()	170
5.72.2.3	random_structure()	170
5.73	NpsPbil Class Reference	170
5.73.1	Detailed Description	172
5.74	OnBudgetFunction Class Reference	172
5.74.1	Detailed Description	173
5.74.2	Member Function Documentation	173
5.74.2.1	eval()	173
5.74.2.2	incremental_eval()	174
5.74.2.3	update()	174
5.75	OneMax Class Reference	174
5.75.1	Detailed Description	175
5.75.2	Member Function Documentation	176
5.75.2.1	get_maximum()	176
5.75.2.2	has_known_maximum()	176
5.75.2.3	provides_incremental_evaluation()	176
5.76	OnePlusLambdaCommaLambdaGa Class Reference	177
5.76.1	Detailed Description	178
5.76.2	Constructor & Destructor Documentation	178
5.76.2.1	OnePlusLambdaCommaLambdaGa()	178
5.77	OnePlusOneEa Class Reference	179
5.77.1	Detailed Description	180
5.77.2	Constructor & Destructor Documentation	180
5.77.2.1	OnePlusOneEa()	180
5.77.3	Member Function Documentation	181
5.77.3.1	set_allow_stay()	181
5.77.3.2	set_num_iterations()	181
5.78	ParameterLessPopulationPyramid Class Reference	181
5.78.1	Detailed Description	182

5.79	ParsedModifier Class Reference	183
5.79.1	Detailed Description	184
5.79.2	Constructor & Destructor Documentation	184
5.79.2.1	ParsedModifier()	184
5.80	ParsedRealMultivariateFunction Class Reference	184
5.80.1	Detailed Description	185
5.80.2	Constructor & Destructor Documentation	185
5.80.2.1	ParsedRealMultivariateFunction()	185
5.81	Pbil Class Reference	186
5.81.1	Detailed Description	187
5.82	Permutation Class Reference	187
5.82.1	Detailed Description	188
5.82.2	Member Function Documentation	188
5.82.2.1	is_surjective()	189
5.83	Plateau Class Reference	189
5.83.1	Detailed Description	190
5.83.2	Member Function Documentation	190
5.83.2.1	get_maximum()	190
5.83.2.2	has_known_maximum()	190
5.84	PointValueException Class Reference	191
5.84.1	Detailed Description	191
5.85	Population Class Reference	192
5.85.1	Detailed Description	193
5.85.2	Member Function Documentation	194
5.85.2.1	comma_selection() [1/2]	194
5.85.2.2	comma_selection() [2/2]	194
5.85.2.3	get_best_bv() [1/4]	195
5.85.2.4	get_best_bv() [2/4]	195
5.85.2.5	get_best_bv() [3/4]	195
5.85.2.6	get_best_bv() [4/4]	195

5.85.2.7	get_best_value() [1/2]	196
5.85.2.8	get_best_value() [2/2]	196
5.85.2.9	get_worst_bv() [1/2]	196
5.85.2.10	get_worst_bv() [2/2]	197
5.85.2.11	plus_selection() [1/2]	197
5.85.2.12	plus_selection() [2/2]	198
5.85.3	Member Data Documentation	198
5.85.3.1	_compare_index_value	198
5.85.3.2	_lookup	198
5.86	PriorNoise Class Reference	199
5.86.1	Detailed Description	200
5.86.2	Member Function Documentation	200
5.86.2.1	get_maximum()	200
5.86.2.2	has_known_maximum()	200
5.86.2.3	provides_incremental_evaluation()	201
5.87	ProgressTracker Class Reference	201
5.87.1	Detailed Description	203
5.87.2	Member Function Documentation	203
5.87.2.1	get_last_improvement()	203
5.88	ProgressTrackerContext Class Reference	203
5.88.1	Detailed Description	204
5.89	Projection Class Reference	204
5.89.1	Detailed Description	205
5.89.2	Constructor & Destructor Documentation	205
5.89.2.1	Projection()	205
5.89.3	Member Function Documentation	206
5.89.3.1	is_surjective()	206
5.90	PvAlgorithm Class Reference	206
5.90.1	Detailed Description	208
5.91	Qubo Class Reference	208

5.91.1 Detailed Description	209
5.91.2 Member Function Documentation	209
5.91.2.1 load()	209
5.91.3 Member Data Documentation	210
5.91.3.1 _q	210
5.92 Random Struct Reference	210
5.92.1 Detailed Description	211
5.93 RandomLocalSearch Class Reference	211
5.93.1 Detailed Description	212
5.93.2 Member Function Documentation	212
5.93.2.1 set_patience()	212
5.94 RandomSearch Class Reference	213
5.94.1 Detailed Description	214
5.95 RandomWalk Class Reference	214
5.95.1 Detailed Description	215
5.96 RealMultivariateFunction Class Reference	215
5.96.1 Detailed Description	216
5.97 RealMultivariateFunctionAdapter Class Reference	216
5.97.1 Detailed Description	217
5.97.2 Constructor & Destructor Documentation	217
5.97.2.1 RealMultivariateFunctionAdapter()	217
5.98 RealRepresentation Class Reference	218
5.98.1 Detailed Description	218
5.99 Restart Class Reference	219
5.99.1 Detailed Description	220
5.100Ridge Class Reference	220
5.100.1 Detailed Description	221
5.100.2 Member Function Documentation	221
5.100.2.1 get_maximum()	221
5.100.2.2 has_known_maximum()	221

5.101 SimulatedAnnealing Class Reference	222
5.101.1 Detailed Description	223
5.101.2 Member Function Documentation	223
5.101.2.1 init_beta()	223
5.102 SingleBitFlip Class Reference	224
5.102.1 Detailed Description	224
5.103 SingleBitFlipIterator Class Reference	225
5.103.1 Detailed Description	225
5.103.2 Constructor & Destructor Documentation	226
5.103.2.1 SingleBitFlipIterator()	226
5.104 SinusSummationCancellation Class Reference	226
5.104.1 Detailed Description	227
5.105 SixPeaks Class Reference	227
5.105.1 Detailed Description	228
5.105.2 Member Function Documentation	229
5.105.2.1 get_maximum()	229
5.105.2.2 has_known_maximum()	229
5.106 SpinHerdng Class Reference	229
5.106.1 Detailed Description	231
5.106.2 Member Enumeration Documentation	231
5.106.2.1 anonymous enum	231
5.106.3 Constructor & Destructor Documentation	232
5.106.3.1 SpinHerdng()	232
5.106.4 Member Function Documentation	232
5.106.4.1 q_variation()	232
5.107 SpinMoment Struct Reference	232
5.107.1 Detailed Description	233
5.107.2 Member Data Documentation	233
5.107.2.1 _second	234
5.108 SteepestAscentHillClimbing Class Reference	234

5.108.1 Detailed Description	235
5.109StopOnMaximum Class Reference	235
5.109.1 Detailed Description	236
5.109.2 Constructor & Destructor Documentation	236
5.109.2.1 StopOnMaximum()	236
5.109.3 Member Function Documentation	237
5.109.3.1 eval()	237
5.109.3.2 incremental_eval()	237
5.109.3.3 update()	237
5.110StopOnTarget Class Reference	238
5.110.1 Detailed Description	239
5.110.2 Constructor & Destructor Documentation	239
5.110.2.1 StopOnTarget()	239
5.110.3 Member Function Documentation	240
5.110.3.1 eval()	240
5.110.3.2 incremental_eval()	240
5.110.3.3 update()	241
5.111StopWatch Class Reference	241
5.111.1 Detailed Description	242
5.112SummationCancellation Class Reference	242
5.112.1 Detailed Description	243
5.112.2 Constructor & Destructor Documentation	243
5.112.2.1 SummationCancellation()	243
5.112.3 Member Function Documentation	244
5.112.3.1 has_known_maximum()	244
5.113TargetReached Class Reference	244
5.113.1 Detailed Description	245
5.114TournamentSelection Class Reference	245
5.114.1 Detailed Description	246
5.114.2 Member Function Documentation	246

5.114.2.1 <code>select()</code>	246
5.115 Translation Class Reference	247
5.115.1 Detailed Description	248
5.115.2 Member Function Documentation	248
5.115.2.1 <code>is_surjective()</code>	248
5.116 Transvection Struct Reference	248
5.116.1 Detailed Description	249
5.116.2 Member Function Documentation	249
5.116.2.1 <code>is_valid()</code>	249
5.116.2.2 <code>multiply()</code> [1/2]	250
5.116.2.3 <code>multiply()</code> [2/2]	250
5.116.2.4 <code>multiply_right()</code>	251
5.116.2.5 <code>random()</code>	251
5.116.2.6 <code>random_non_commuting()</code>	252
5.117 Trap Class Reference	252
5.117.1 Detailed Description	253
5.117.2 Constructor & Destructor Documentation	253
5.117.2.1 <code>Trap()</code>	253
5.117.3 Member Function Documentation	254
5.117.3.1 <code>get_maximum()</code>	254
5.117.3.2 <code>has_known_maximum()</code>	254
5.118 TsAffineMap Class Reference	255
5.118.1 Detailed Description	256
5.118.2 Member Enumeration Documentation	256
5.118.2.1 <code>SamplingMode</code>	256
5.118.3 Member Function Documentation	256
5.118.3.1 <code>is_surjective()</code>	257
5.118.3.2 <code>random()</code>	257
5.119 Umda Class Reference	257
5.119.1 Detailed Description	259

5.120UniformCrossover Class Reference	259
5.120.1 Detailed Description	259
5.120.2 Member Function Documentation	260
5.120.2.1 breed()	260
5.121WalshExpansion Class Reference	260
5.121.1 Detailed Description	261
5.121.2 Member Function Documentation	262
5.121.2.1 generate()	262
5.121.2.2 random()	262
5.122WalshExpansion1 Class Reference	262
5.122.1 Detailed Description	264
5.122.2 Member Function Documentation	264
5.122.2.1 generate()	264
5.122.2.2 has_known_maximum()	264
5.122.2.3 provides_incremental_evaluation()	265
5.122.2.4 random()	265
5.123WalshExpansion2 Class Reference	265
5.123.1 Detailed Description	267
5.123.2 Member Function Documentation	267
5.123.2.1 generate()	267
5.123.2.2 generate_ising1_long_range()	267
5.123.2.3 generate_ising1_long_range_periodic()	268
5.123.2.4 random()	269
5.123.3 Member Data Documentation	269
5.123.3.1 _quadratic	269
5.124Function::WalshTransformTerm Struct Reference	269
5.124.1 Detailed Description	270
5.124.2 Member Data Documentation	270
5.124.2.1 feature	270

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

hnco	Top-level HNCO namespace	13
hnco::algorithm	Algorithms	30
hnco::algorithm::bm_pbil	Boltzmann machine PBIL	33
hnco::algorithm::hea	Herdling evolutionary algorithm	33
hnco::exception	Exceptions	33
hnco::function	Real black box functions defined on bit vectors	34
hnco::function::real	Real multivariate functions	36
hnco::neighborhood	Neighborhoods for local search	37
hnco::random	Pseudo random numbers	38

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Algorithm	45
CompleteSearch	64
Hboa	101
Ltga	131
ParameterLessPopulationPyramid	181
IterativeAlgorithm	112
BmPbil	55
Mimic	140
FirstAscentHillClimbing	77
GeneticAlgorithm	93
Hea< Moment, Herding >	102
MuCommaLambdaEa	146
MuPlusLambdaEa	150
OnePlusLambdaCommaLambdaGa	177
PvAlgorithm	206
CompactGa	62
Mmas	143
NpsPbil	170
Pbil	186
Umda	257
RandomLocalSearch	211
RandomSearch	213
RandomWalk	214
Restart	219
SimulatedAnnealing	222
SteepestAscentHillClimbing	234
OnePlusOneEa	179
BitHerding	52
BitMoment	54
Crossover	65
BiasedCrossover	51
UniformCrossover	259
Evaluator	
HncoEvaluator	108

ProgressTracker::Event	74
Exception	74
Error	73
LastEvaluation	120
PointValueException	191
LocalMaximum	127
MaximumReached	136
TargetReached	244
Function	81
AbstractLabs	39
Labs	118
LabsMeritFactor	119
AbstractMaxSat	40
MaxNae3Sat	137
MaxSat	138
DeceptiveJump	66
EqualProducts	70
Factorization	75
FourPeaks	79
FunctionDecorator	87
FunctionController	86
Cache	59
CallCounter	61
OnBudgetFunction	172
ProgressTracker	201
StopOnMaximum	235
StopOnTarget	238
FunctionModifier	91
AdditiveGaussianNoise	42
FunctionMapComposition	88
Negation	162
ParsedModifier	183
PriorNoise	199
FunctionPlugin	92
Hiff	107
Jump	116
LeadingOnes	120
LinearFunction	122
LongPath	129
NearestNeighborIsingModel1	153
NearestNeighborIsingModel2	156
Needle	160
NkLandscape	168
OneMax	174
Plateau	189
Qubo	208
RealMultivariateFunctionAdapter	216
Ridge	220
SixPeaks	227
SummationCancellation	242
SinusSummationCancellation	226
Trap	252
WalshExpansion	260
WalshExpansion1	262
WalshExpansion2	265
Iterator	115
HypercubeIterator	109

NeighborhoodIterator	167
HammingSphereIterator	99
SingleBitFlipIterator	225
LogContext	128
ProgressTrackerContext	203
Map	132
AffineMap	43
Injection	110
LinearMap	125
MapComposition	134
Permutation	187
Projection	204
Translation	247
TsAffineMap	255
Model	144
ModelParameters	145
Neighborhood	164
MultiBitFlip	148
BernoulliProcess	48
HammingBall	96
HammingSphere	98
SingleBitFlip	224
Population	192
TournamentSelection	245
Random	210
RealMultivariateFunction	215
ParsedRealMultivariateFunction	184
RealRepresentation	218
DyadicRealRepresentation	68
SpinHerdin	229
SpinMoment	232
StopWatch	241
Transvection	248
Function::WalshTransformTerm	269

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

AbstractLabs	Abstract class for low autocorrelation binary sequences	39
AbstractMaxSat	Abstract class for MaxSat-like functions	40
AdditiveGaussianNoise	Additive Gaussian Noise	42
AffineMap	Affine map	43
Algorithm	Abstract search algorithm	45
BernoulliProcess	Bernoulli process	48
BiasedCrossover	Biased crossover	51
BitHerding	Herding with bit features	52
BitMoment	Moment for bit features	54
BmPbil	Boltzmann machine PBIL	55
Cache	Cache	59
CallCounter	Call counter	61
CompactGa	Compact genetic algorithm	62
CompleteSearch	Complete search	64
Crossover	Crossover	65
DeceptiveJump	Deceptive jump	66
DyadicRealRepresentation	Dyadic real representation	68
EqualProducts	Equal products	70

Error	
Error	73
ProgressTracker::Event	
Event	74
Exception	
Basic exception	74
Factorization	
Factorization	75
FirstAscentHillClimbing	
First ascent hill climbing	77
FourPeaks	
Four Peaks	79
Function	
Function	81
FunctionController	
Function controller	86
FunctionDecorator	
Function decorator	87
FunctionMapComposition	
Composition of a function and a map	88
FunctionModifier	
Function modifier	91
FunctionPlugin	
Function plugin	92
GeneticAlgorithm	
Genetic algorithm	93
HammingBall	
Hamming ball	96
HammingSphere	
Hamming sphere	98
HammingSphereIterator	
Hamming sphere neighborhood iterator	99
Hboa	
Hierarchical Bayesian Optimization Algorithm	101
Hea< Moment, Herding >	
Herding evolutionary algorithm	102
Hiff	
Hierarchical if and only if	107
HncoEvaluator	
Evaluator for HNCO functions	108
HypercubeIterator	
Hypercube iterator	109
Injection	
Injection	110
IterativeAlgorithm	
Iterative search	112
Iterator	
Iterator over bit vectors	115
Jump	
Jump	116
Labs	
Low autocorrelation binary sequences	118
LabsMeritFactor	
Low autocorrelation binary sequences merit factor	119
LastEvaluation	
Last evaluation	120
LeadingOnes	
Leading ones	120

LinearFunction	
Linear function	122
LinearMap	
Linear map	125
LocalMaximum	
Local maximum	127
LogContext	
Log context	128
LongPath	
Long path	129
Ltga	
Linkage Tree Genetic Algorithm	131
Map	
Map	132
MapComposition	
Map composition	134
MaximumReached	
Maximum reached	136
MaxNae3Sat	
Max not-all-equal 3SAT	137
MaxSat	
MAX-SAT	138
Mimic	
Mutual information maximizing input clustering	140
Mmas	
Max-min ant system	143
Model	
Model of a Boltzmann machine	144
ModelParameters	
Parameters of a Boltzmann machine	145
MuCommaLambdaEa	
(mu, lambda) EA	146
MultiBitFlip	
Multi bit flip	148
MuPlusLambdaEa	
(mu+lambda) EA	150
NearestNeighborsIsingModel1	
Nearest neighbor Ising model in one dimension	153
NearestNeighborsIsingModel2	
Nearest neighbor Ising model in two dimensions	156
Needle	
Needle in a haystack	160
Negation	
Negation	162
Neighborhood	
Neighborhood	164
NeighborhoodIterator	
Neighborhood iterator	167
NkLandscape	
NK landscape	168
NpsPbil	
Population-based incremental learning with negative and positive selection	170
OnBudgetFunction	
CallCounter with a limited number of evaluations	172
OneMax	
OneMax	174
OnePlusLambdaCommaLambdaGa	
(1+(lambda, lambda)) genetic algorithm	177

OnePlusOneEa	
(1+1) EA	179
ParameterLessPopulationPyramid	
Parameter-less Population Pyramid	181
ParsedModifier	
Parsed modifier	183
ParsedRealMultivariateFunction	
Parsed real multivariate function	184
Pbil	
Population-based incremental learning	186
Permutation	
Permutation	187
Plateau	
Plateau	189
PointValueException	
Point-value exception	191
Population	
Population	192
PriorNoise	
Prior noise	199
ProgressTracker	
ProgressTracker	201
ProgressTrackerContext	
Log context for ProgressTracker	203
Projection	
Projection	204
PvAlgorithm	
Probability vector algorithm	206
Qubo	
Quadratic unconstrained binary optimization	208
Random	
Random numbers	210
RandomLocalSearch	
Random local search	211
RandomSearch	
Random search	213
RandomWalk	
Random walk	214
RealMultivariateFunction	
Real multivariate function	215
RealMultivariateFunctionAdapter	
Real multivariate function adapter	216
RealRepresentation	
Real representation	218
Restart	
Restart	219
Ridge	
Ridge	220
SimulatedAnnealing	
Simulated annealing	222
SingleBitFlip	
One bit neighborhood	224
SingleBitFlipIterator	
Single bit flip neighborhood iterator	225
SinusSummationCancellation	
Summation cancellation with sinus	226
SixPeaks	
Six Peaks	227

SpinHerding	
Herding with spin variables	229
SpinMoment	
Moment for spin variables	232
SteepestAscentHillClimbing	
Steepest ascent hill climbing	234
StopOnMaximum	
Stop on maximum	235
StopOnTarget	
Stop on target	238
StopWatch	
Stop watch	241
SummationCancellation	
Summation cancellation	242
TargetReached	
Target reached	244
TournamentSelection	
Population with tournament selection	245
Translation	
Translation	247
Transvection	
Transvection	248
Trap	
Trap	252
TsAffineMap	
Transvection sequence affine map	255
Umda	
Univariate marginal distribution algorithm	257
UniformCrossover	
Uniform crossover	259
WalshExpansion	
Walsh expansion	260
WalshExpansion1	
Walsh expansion of degree 1	262
WalshExpansion2	
Walsh expansion of degree 2	265
Function::WalshTransformTerm	
Walsh transform term	269

Chapter 4

Namespace Documentation

4.1 hnco Namespace Reference

top-level HNCO namespace

Namespaces

- [algorithm](#)
Algorithms.
- [exception](#)
Exceptions.
- [function](#)
Real black box functions defined on bit vectors.
- [neighborhood](#)
Neighborhoods for local search.
- [random](#)
Pseudo random numbers.

Classes

- class [AffineMap](#)
Affine map.
- class [HypercubeIterator](#)
Hypercube iterator.
- class [Injection](#)
Injection.
- class [Iterator](#)
Iterator over bit vectors
- class [LinearMap](#)
Linear map.
- class [Map](#)
Map
- class [MapComposition](#)
Map composition.

- class [Permutation](#)
Permutation.
- class [Projection](#)
Projection.
- class [StopWatch](#)
Stop watch.
- class [Translation](#)
Translation.
- struct [Transvection](#)
Transvection.
- class [TsAffineMap](#)
Transvection sequence affine map.

Functions

- template<class T >
T [square](#) (T x)
Generic square function.
- double [logistic](#) (double x)
Logistic function (sigmoid)

Range checking

- bool [is_in_range](#) (int i, int n)
Check whether an index is in a given range.
- bool [is_in_range](#) (int i, int a, int b)
Check whether an index is in a given range.

Types and functions related to bit matrices

- typedef std::vector< [bit_vector_t](#) > [bit_matrix_t](#)
Bit matrix.
- void [bm_display](#) (const [bit_matrix_t](#) &M, std::ostream &stream)
Display bit matrix.
- bool [bm_is_valid](#) (const [bit_matrix_t](#) &M)
Check whether a bit matrix is valid.
- int [bm_num_rows](#) (const [bit_matrix_t](#) &M)
Number of rows.
- int [bm_num_columns](#) (const [bit_matrix_t](#) &M)
Number of columns.
- bool [bm_is_square](#) (const [bit_matrix_t](#) &M)
Check whether the matrix is a square matrix.
- bool [bm_is_identity](#) (const [bit_matrix_t](#) &M)
Check whether the matrix is the identity matrix.
- bool [bm_is_upper_triangular](#) (const [bit_matrix_t](#) &M)
Check whether the matrix is upper triangular.
- void [bm_resize](#) ([bit_matrix_t](#) &M, int num_rows, int num_columns)
Resize a bit matrix.
- void [bm_resize](#) ([bit_matrix_t](#) &M, int num_rows)
Resize a bit matrix and make it a square matrix.

- void [bm_clear](#) ([bit_matrix_t](#) &M)
Clear bit matrix.
- void [bm_identity](#) ([bit_matrix_t](#) &M)
Set the matrix to the identity matrix.
- void [bm_identity](#) ([bit_matrix_t](#) &M, int n)
Set the matrix to the identity matrix.
- void [bm_random](#) ([bit_matrix_t](#) &M)
Sample a random bit matrix.
- void [bm_swap_rows](#) ([bit_matrix_t](#) &M, int i, int j)
Swap two rows.
- void [bm_add_rows](#) ([bit_matrix_t](#) &M, int i, int j)
Add two rows.
- void [bm_add_columns](#) ([bit_matrix_t](#) &M, int src, int dest)
Add two columns.
- void [bm_row_echelon_form](#) ([bit_matrix_t](#) &A)
Compute a row echelon form of a matrix.
- int [bm_rank](#) (const [bit_matrix_t](#) &A)
Compute the rank of a matrix.
- bool [bm_solve](#) ([bit_matrix_t](#) &A, [bit_vector_t](#) &b)
Solve a linear system.
- bool [bm_solve_upper_triangular](#) ([bit_matrix_t](#) &A, [bit_vector_t](#) &b)
Solve a linear system in upper triangular form.
- bool [bm_invert](#) ([bit_matrix_t](#) &M, [bit_matrix_t](#) &N)
Invert a bit matrix.
- void [bm_multiply](#) (const [bit_matrix_t](#) &M, const [bit_vector_t](#) &x, [bit_vector_t](#) &y)
Multiply a bit matrix and a bit vector.
- void [bm_transpose](#) (const [bit_matrix_t](#) &M, [bit_matrix_t](#) &N)
Transpose.

Types and functions related to bit

- typedef char [bit_t](#)
Bit.
- [bit_t](#) [bit_flip](#) ([bit_t](#) b)
Flip bit.
- [bit_t](#) [bit_random](#) (double p)
Sample a random bit.

Types and functions related to bit vectors

- typedef std::vector< [bit_t](#) > [bit_vector_t](#)
Bit vector.
- typedef std::pair< [bit_vector_t](#), double > [point_value_t](#)
Type to represent point value pairs.
- void [bv_display](#) (const [bit_vector_t](#) &v, std::ostream &stream)
Display bit vector.
- bool [bv_is_valid](#) (const [bit_vector_t](#) &x)
Check whether the bit vector is valid.
- bool [bv_is_zero](#) (const [bit_vector_t](#) &x)

- Check whether the bit vector is zero.*

 - `int bv_hamming_weight (const bit_vector_t &x)`
Hamming weight.
 - `int bv_hamming_weight (const std::vector< bool > &x)`
Hamming weight.
 - `int bv_hamming_distance (const bit_vector_t &x, const bit_vector_t &y)`
Hamming distance between two bit vectors.
 - `bit_t bv_dot_product (const bit_vector_t &x, const bit_vector_t &y)`
Dot product.
 - `bit_t bv_dot_product (const bit_vector_t &x, const std::vector< bool > &y)`
Dot product.
 - `void bv_clear (bit_vector_t &x)`
Clear bit vector.
 - `void bv_flip (bit_vector_t &x, int i)`
Flip a single bit.
 - `void bv_flip (bit_vector_t &x, const bit_vector_t &mask)`
Flip many bits.
 - `void bv_random (bit_vector_t &x)`
Sample a random bit vector.
 - `void bv_random (bit_vector_t &x, int k)`
Sample a random bit vector with given Hamming weight.
 - `void bv_add (const bit_vector_t &src, bit_vector_t &dest)`
Add two bit vectors.
 - `void bv_add (const bit_vector_t &x, const bit_vector_t &y, bit_vector_t &dest)`
Add two bit vectors.
 - `void bv_to_vector_bool (const bit_vector_t &x, std::vector< bool > &y)`
Convert a bit vector to a bool vector.
 - `void bv_from_vector_bool (bit_vector_t &x, const std::vector< bool > &y)`
Convert a bool vector to a bit vector.
 - `std::size_t bv_to_size_type (const bit_vector_t &x)`
Convert a bit vector to a size_t.
 - `void bv_from_size_type (bit_vector_t &x, std::size_t index)`
Convert a size_t to a bit vector.
 - `void bv_from_stream (bit_vector_t &x, std::istream &stream)`
Read a bit vector from a stream.

Types and functions related to permutations

- `typedef std::vector< int > permutation_t`
Permutation type
 - `bool perm_is_valid (const permutation_t &permutation)`
Check that a vector represents a permutation.
 - `void perm_identity (permutation_t &s)`
Identity permutation.
 - `void perm_random (permutation_t &s)`
Sample a random permutation.

Types and functions related to sparse bit matrices

- typedef std::vector< [sparse_bit_vector_t](#) > [sparse_bit_matrix_t](#)
Sparse bit matrix.
- void [sbm_display](#) (const [sparse_bit_matrix_t](#) &sbm, std::ostream &stream)
Display sparse bit matrix.
- void [bm_to_sbm](#) (const [bit_matrix_t](#) &bm, [sparse_bit_matrix_t](#) &sbm)
Convert a bit matrix to a sparse bit matrix.
- void [sbm_multiply](#) (const [sparse_bit_matrix_t](#) &M, const [bit_vector_t](#) &x, [bit_vector_t](#) &y)
Multiply a sparse bit matrix and a bit vector.

Types and functions related to sparse bit vectors

- typedef std::vector< int > [sparse_bit_vector_t](#)
Sparse bit vector.
- void [bv_flip](#) ([bit_vector_t](#) &x, const [sparse_bit_vector_t](#) &sbv)
Flip many bits.
- void [sbv_display](#) (const [sparse_bit_vector_t](#) &v, std::ostream &stream)
Display sparse bit vector.
- void [bv_to_sbv](#) (const [bit_vector_t](#) &bv, [sparse_bit_vector_t](#) &sbv)
Convert a bit vector to a sparse bit vector.

Types and functions related to transvections

- typedef std::vector< [Transvection](#) > [transvection_sequence_t](#)
Transvection sequence.
- bool [transvections_commute](#) (const [Transvection](#) &a, const [Transvection](#) &b)
Check whether two transvections commute.
- bool [ts_is_valid](#) (const [transvection_sequence_t](#) &ts)
Check validity.
- bool [ts_is_valid](#) (const [transvection_sequence_t](#) &ts, int n)
Check validity.
- void [ts_display](#) (const [transvection_sequence_t](#) &ts, std::ostream &stream)
Display a transvection sequence.
- void [ts_random](#) ([transvection_sequence_t](#) &ts, int n, int t)
Sample a random transvection sequence.
- void [ts_random_commuting](#) ([transvection_sequence_t](#) &ts, int n, int t)
Sample a random sequence of commuting transvections.
- void [ts_random_unique_source](#) ([transvection_sequence_t](#) &ts, int n, int t)
Sample a random sequence of transvections with unique source.
- void [ts_random_unique_destination](#) ([transvection_sequence_t](#) &ts, int n, int t)
Sample a random sequence of transvections with unique destination.
- void [ts_random_disjoint](#) ([transvection_sequence_t](#) &ts, int n, int t)
Sample a random sequence of disjoint transvections.
- void [ts_random_non_commuting](#) ([transvection_sequence_t](#) &ts, int n, int t)
Sample a random sequence of non commuting transvections.
- void [ts_multiply](#) (const [transvection_sequence_t](#) &ts, [bit_vector_t](#) &x)
Multiply a vector by a transvection sequence from the left.
- void [ts_multiply](#) (const [transvection_sequence_t](#) &ts, [bit_matrix_t](#) &M)
Multiply a matrix by a transvection sequence from the left.

4.1.1 Detailed Description

top-level HNCO namespace

4.1.2 Typedef Documentation

4.1.2.1 `bit_t`

```
typedef char bit_t
```

Bit.

A single bit is represented by a char.

Definition at line 49 of file bit-vector.hh.

4.1.2.2 `sparse_bit_matrix_t`

```
typedef std::vector<sparse_bit_vector_t> sparse_bit_matrix_t
```

Sparse bit matrix.

A sparse bit matrix is represented as an array of sparse bit vectors. It knows its number of row, not its number of columns.

Definition at line 45 of file sparse-bit-matrix.hh.

4.1.2.3 `sparse_bit_vector_t`

```
typedef std::vector<int> sparse_bit_vector_t
```

Sparse bit vector.

A sparse bit vector is represented as an array containing the indices of its non-zero components. The indices must be sorted in ascending order.

A sparse bit vector does not know the dimension of the space it belongs to.

Definition at line 47 of file sparse-bit-vector.hh.

4.1.2.4 transvection_sequence_t

```
typedef std::vector<Transvection> transvection_sequence_t
```

Transvection sequence.

The general linear group of a linear space of dimension n over the finite field F_2 is the group of invertible n by n bit matrices.

Any invertible bit matrix can be expressed as a finite product of transvections.

Finite transvection sequences can then represent all invertible bit matrices.

Definition at line 164 of file transvection.hh.

4.1.3 Function Documentation

4.1.3.1 bm_add_columns()

```
void bm_add_columns (
    bit_matrix_t & M,
    int src,
    int dest )
```

Add two columns.

Column *src* is added to column *dest*.

Parameters

<i>M</i>	Bit matrix
<i>src</i>	Source column
<i>dest</i>	Destination column

Warning

M is modified by the function.

Definition at line 150 of file bit-matrix.cc.

4.1.3.2 bm_add_rows()

```
void bm_add_rows (
    bit_matrix_t & M,
```

```
    int i,
    int j )
```

Add two rows.

Row i is added to row j .

Definition at line 141 of file bit-matrix.cc.

4.1.3.3 `bm_identity()` [1/2]

```
void bm_identity (
    bit_matrix_t & M )
```

Set the matrix to the identity matrix.

Precondition

`bm_is_square(M)`

Definition at line 56 of file bit-matrix.cc.

4.1.3.4 `bm_identity()` [2/2]

```
void bm_identity (
    bit_matrix_t & M,
    int n )
```

Set the matrix to the identity matrix.

Parameters

M	Bit matrix
n	Dimension

Definition at line 67 of file bit-matrix.cc.

4.1.3.5 `bm_invert()`

```
bool bm_invert (
    bit_matrix_t & M,
    bit_matrix_t & N )
```

Invert a bit matrix.

Parameters

M	input matrix
N	inverse matrix

Precondition

`bm_is_square(M)`
`bm_is_square(N)`

Returns

true if M is invertible

Warning

M is modified by the function. Provided that M is invertible, after returning from the function, M is the identity matrix and N is the computed inverse matrix.

Definition at line 268 of file bit-matrix.cc.

4.1.3.6 `bm_multiply()`

```
void bm_multiply (
    const bit_matrix_t & M,
    const bit_vector_t & x,
    bit_vector_t & y )
```

Multiply a bit matrix and a bit vector.

The result is $y = Mx$.

Definition at line 312 of file bit-matrix.cc.

4.1.3.7 `bm_rank()`

```
int bm_rank (
    const bit_matrix_t & A )
```

Compute the rank of a matrix.

Precondition

A must be in row echelon form.

Definition at line 196 of file bit-matrix.cc.

4.1.3.8 `bm_row_echelon_form()`

```
void bm_row_echelon_form (
    bit_matrix_t & A )
```

Compute a row echelon form of a matrix.

Warning

A is modified by the function.

Definition at line 165 of file bit-matrix.cc.

4.1.3.9 `bm_solve()`

```
bool bm_solve (
    bit_matrix_t & A,
    bit_vector_t & b )
```

Solve a linear system.

Solve the linear equation $Ax = b$.

Parameters

A	Matrix
b	Right hand side

Precondition

```
bm_is_square(A)
bm_num_rows(A) == b.size()
```

Returns

true if the system has a unique solution

Warning

Both A and b are modified by the function. Provided that A is invertible, after returning from the function, A is the identity matrix and b is the unique solution to the linear equation.

Definition at line 214 of file bit-matrix.cc.

4.1.3.10 `bm_solve_upper_triangular()`

```
bool bm_solve_upper_triangular (
    bit_matrix_t & A,
    bit_vector_t & b )
```

Solve a linear system in upper triangular form.

Solve the linear equation $Ax = b$.

Parameters

<i>A</i>	Upper triangular matrix
<i>b</i>	Right hand side

Precondition

```
bm_is_square(A)
bm_num_rows(A) == b.size()
bm_is_upper_triangular(A)
```

Returns

true if the system has a unique solution

Warning

Both *A* and *b* are modified by the function. Provided that *A* is invertible, after returning from the function, *A* is the identity matrix and *b* is the unique solution to the linear equation.

Definition at line 247 of file bit-matrix.cc.

4.1.3.11 `bv_from_vector_bool()`

```
void bv_from_vector_bool (
    bit_vector_t & x,
    const std::vector< bool > & y )
```

Convert a bool vector to a bit vector.

Warning

Vectors must be of the same size.

Definition at line 155 of file bit-vector.cc.

4.1.3.12 `bv_to_vector_bool()`

```
void bv_to_vector_bool (
    const bit_vector_t & x,
    std::vector< bool > & y )
```

Convert a bit vector to a bool vector.

Warning

Vectors must be of the same size.

Definition at line 142 of file `bit-vector.cc`.

4.1.3.13 `is_in_range()` [1/2]

```
bool hnco::is_in_range (
    int i,
    int n ) [inline]
```

Check whether an index is in a given range.

The lower bound is implicit and is equal to 0.

Parameters

<i>i</i>	Index
<i>n</i>	Upper bound

Returns

true if $i \geq 0$ and $i < n$

Definition at line 152 of file `bit-vector.hh`.

4.1.3.14 `is_in_range()` [2/2]

```
bool hnco::is_in_range (
    int i,
    int a,
    int b ) [inline]
```

Check whether an index is in a given range.

Parameters

<i>i</i>	Index
<i>a</i>	Lower bound
<i>b</i>	Upper bound

Returns

true if $i \geq a$ and $i < b$

Definition at line 162 of file bit-vector.hh.

4.1.3.15 perm_identity()

```
void hnco::perm_identity (
    permutation_t & s ) [inline]
```

Identity permutation.

Warning

This function does not set the size of the permutation.

Definition at line 46 of file permutation.hh.

4.1.3.16 perm_random()

```
void hnco::perm_random (
    permutation_t & s ) [inline]
```

Sample a random permutation.

Warning

This function does not set the size of the permutation.

Definition at line 56 of file permutation.hh.

4.1.3.17 sbm_multiply()

```
void sbm_multiply (
    const sparse_bit_matrix_t & M,
    const bit_vector_t & x,
    bit_vector_t & y )
```

Multiply a sparse bit matrix and a bit vector.

The result is $y = Mx$.

Definition at line 47 of file sparse-bit-matrix.cc.

4.1.3.18 ts_is_valid() [1/2]

```
bool ts_is_valid (
    const transvection_sequence_t & ts )
```

Check validity.

Parameters

<i>ts</i>	Transvection sequence
-----------	-----------------------

Definition at line 143 of file transvection.cc.

4.1.3.19 ts_is_valid() [2/2]

```
bool ts_is_valid (
    const transvection_sequence_t & ts,
    int n )
```

Check validity.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension

Definition at line 149 of file transvection.cc.

4.1.3.20 ts_multiply() [1/2]

```
void ts_multiply (
    const transvection_sequence_t & ts,
    bit_vector_t & x )
```

Multiply a vector by a transvection sequence from the left.

Parameters

<i>ts</i>	Transvection sequence
<i>x</i>	Bit vector

Precondition

```
ts_is_valid(ts)
ts_is_valid(ts, x.size())
```

Warning

This function modifies the given bit vector.

Definition at line 348 of file transvection.cc.

4.1.3.21 `ts_multiply()` [2/2]

```
void ts_multiply (
    const transvection_sequence_t & ts,
    bit_matrix_t & M )
```

Multiply a matrix by a transvection sequence from the left.

Parameters

<i>ts</i>	Transvection sequence
<i>M</i>	Bit matrix

Precondition

```
ts_is_valid(ts)
ts_is_valid(ts, bm_num_rows(M))
```

Warning

This function modifies the given bit vector.

Definition at line 358 of file transvection.cc.

4.1.3.22 `ts_random()`

```
void ts_random (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random transvection sequence.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

```
n > 1
t >= 0
```

Definition at line 165 of file transvection.cc.

4.1.3.23 ts_random_commuting()

```
void ts_random_commuting (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of commuting transvections.

This function ensures that all transvections in the sequence commute.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$n > 1$
 $t \geq 0$

Definition at line 176 of file transvection.cc.

4.1.3.24 ts_random_disjoint()

```
void ts_random_disjoint (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of disjoint transvections.

Two transvections τ_{ij} and τ_{kl} are said to be disjoint if the pairs $\{i,j\}$ and $\{k,l\}$ are disjoint.

If $2t > n$ then the sequence length is set to the largest t such that $2t \leq n$.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$n > 1$
 $t \geq 0$

Definition at line 304 of file transvection.cc.

4.1.3.25 ts_random_non_commuting()

```
void ts_random_non_commuting (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of non commuting transvections.

This function ensures that two consecutive transvections do not commute.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$n > 1$
 $t \geq 0$

Definition at line 333 of file transvection.cc.

4.1.3.26 ts_random_unique_destination()

```
void ts_random_unique_destination (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of transvections with unique destination.

A transvection sequence with unique destination is such that, for each source, there is a unique destination.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

$n > 1$
 $t \geq 0$

Definition at line 271 of file transvection.cc.

4.1.3.27 ts_random_unique_source()

```
void ts_random_unique_source (
    transvection_sequence_t & ts,
    int n,
    int t )
```

Sample a random sequence of transvections with unique source.

A transvection sequence with unique source is such that, for each destination, there is a unique source.

Parameters

<i>ts</i>	Transvection sequence
<i>n</i>	Dimension
<i>t</i>	Length of the sequence

Precondition

```
n > 1
t >= 0
```

Definition at line 238 of file transvection.cc.

4.2 hnco::algorithm Namespace Reference

Algorithms.

Namespaces

- [bm_pbil](#)
Boltzmann machine PBIL.
- [hea](#)
Herding evolutionary algorithm.

Classes

- class [Algorithm](#)
Abstract search algorithm.
- class [BiasedCrossover](#)
Biased crossover.
- class [CompactGa](#)
Compact genetic algorithm.
- class [CompleteSearch](#)
Complete search.
- class [Crossover](#)
Crossover.
- class [FirstAscentHillClimbing](#)

- First ascent hill climbing.*
- class [GeneticAlgorithm](#)
 - Genetic algorithm.*
- class [IterativeAlgorithm](#)
 - Iterative search.*
- class [LogContext](#)
 - Log context.*
- class [Mmas](#)
 - Max-min ant system.*
- class [MuCommaLambdaEa](#)
 - (mu, lambda) EA.*
- class [MuPlusLambdaEa](#)
 - (mu+lambda) EA.*
- class [NpsPbil](#)
 - Population-based incremental learning with negative and positive selection.*
- class [OnePlusLambdaCommaLambdaGa](#)
 - (1+(lambda, lambda)) genetic algorithm.*
- class [OnePlusOneEa](#)
 - (1+1) EA.*
- class [Pbil](#)
 - Population-based incremental learning.*
- class [Population](#)
 - Population.*
- class [ProgressTrackerContext](#)
 - Log context for ProgressTracker.*
- class [PvAlgorithm](#)
 - Probability vector algorithm.*
- class [RandomLocalSearch](#)
 - Random local search.*
- class [RandomSearch](#)
 - Random search.*
- class [RandomWalk](#)
 - Random walk.*
- class [Restart](#)
 - Restart.*
- class [SimulatedAnnealing](#)
 - Simulated annealing.*
- class [SteepestAscentHillClimbing](#)
 - Steepest ascent hill climbing.*
- class [TournamentSelection](#)
 - Population with tournament selection.*
- class [Umda](#)
 - Univariate marginal distribution algorithm.*
- class [UniformCrossover](#)
 - Uniform crossover.*

Functions

- `template<class T >`
`bool matrix_is_symmetric (const std::vector< std::vector< T > > &A)`
Check for symmetric matrix.
- `template<class T >`
`bool matrix_is_strictly_lower_triangular (const std::vector< std::vector< T > > &A)`
Check for strictly lower triangular matrix.
- `template<class T >`
`bool matrix_has_diagonal (const std::vector< std::vector< T > > &A, T x)`
Check for diagonal elements.
- `template<class T >`
`bool matrix_has_range (const std::vector< std::vector< T > > &A, T inf, T sup)`
Check for element range.
- `template<class T >`
`bool matrix_has_dominant_diagonal (const std::vector< std::vector< T > > &A)`
Check for element range.

Type and functions related to probability vectors

- `typedef std::vector< double > pv_t`
Probability vector type.
- `double pv_entropy (const pv_t &pv)`
Entropy of a probability vector.
- `void pv_sample (const pv_t &pv, bit_vector_t &x)`
Sample a bit vector.
- `void pv_uniform (pv_t &pv)`
Probability vector of the uniform distribution.
- `void pv_init (pv_t &pv)`
Initialize.
- `void pv_add (pv_t &pv, const bit_vector_t &x)`
Accumulate a bit vector.
- `void pv_add (pv_t &pv, const bit_vector_t &x, double weight)`
Accumulate a bit vector.
- `void pv_average (pv_t &pv, int count)`
Average.
- `void pv_update (pv_t &pv, double rate, const bit_vector_t &x)`
Update a probability vector toward a bit vector.
- `void pv_update (pv_t &pv, double rate, const std::vector< double > &x)`
Update a probability vector toward a probability vector.
- `void pv_update (pv_t &pv, double rate, const std::vector< double > &x, const std::vector< double > &y)`
Update a probability vector toward a probability vector and away from another one.
- `void pv_bound (pv_t &pv, double lower_bound, double upper_bound)`
Bound the components of a probability vector.

4.2.1 Detailed Description

Algorithms.

4.3 hnco::algorithm::bm_pbil Namespace Reference

Boltzmann machine PBIL.

Classes

- class [BmPbil](#)
Boltzmann machine PBIL.
- class [Model](#)
Model of a Boltzmann machine.
- class [ModelParameters](#)
Parameters of a Boltzmann machine.

4.3.1 Detailed Description

Boltzmann machine PBIL.

4.4 hnco::algorithm::hea Namespace Reference

Herding evolutionary algorithm.

Classes

- class [BitHerding](#)
Herding with bit features.
- struct [BitMoment](#)
Moment for bit features.
- class [Hea](#)
Herding evolutionary algorithm.
- class [SpinHerding](#)
Herding with spin variables.
- struct [SpinMoment](#)
Moment for spin variables.

4.4.1 Detailed Description

Herding evolutionary algorithm.

4.5 hnco::exception Namespace Reference

Exceptions.

Classes

- class [Error](#)
Error.
- class [Exception](#)
Basic exception.
- class [LastEvaluation](#)
Last evaluation.
- class [LocalMaximum](#)
Local maximum.
- class [MaximumReached](#)
Maximum reached.
- class [PointValueException](#)
Point-value exception.
- class [TargetReached](#)
target reached

4.5.1 Detailed Description

Exceptions.

4.6 hnco::function Namespace Reference

Real black box functions defined on bit vectors.

Namespaces

- [real](#)
Real multivariate functions.

Classes

- class [AbstractLabs](#)
Abstract class for low autocorrelation binary sequences.
- class [AbstractMaxSat](#)
Abstract class for MaxSat-like functions.
- class [AdditiveGaussianNoise](#)
Additive Gaussian Noise.
- class [Cache](#)
Cache.
- class [CallCounter](#)
Call counter.
- class [DeceptiveJump](#)
Deceptive jump.
- class [EqualProducts](#)
Equal products.
- class [Factorization](#)

- *Factorization.*
- class [FourPeaks](#)
 - Four Peaks.*
- class [Function](#)
 - Function.*
- class [FunctionController](#)
 - Function controller.*
- class [FunctionDecorator](#)
 - Function decorator.*
- class [FunctionMapComposition](#)
 - Composition of a function and a map.*
- class [FunctionModifier](#)
 - Function modifier.*
- class [FunctionPlugin](#)
 - Function plugin.*
- class [Hiff](#)
 - Hierarchical if and only if.*
- class [Jump](#)
 - Jump.*
- class [Labs](#)
 - Low autocorrelation binary sequences.*
- class [LabsMeritFactor](#)
 - Low autocorrelation binary sequences merit factor.*
- class [LeadingOnes](#)
 - Leading ones.*
- class [LinearFunction](#)
 - Linear function.*
- class [LongPath](#)
 - Long path.*
- class [MaxNae3Sat](#)
 - Max not-all-equal 3SAT.*
- class [MaxSat](#)
 - MAX-SAT.*
- class [NearestNeighborIsingModel1](#)
 - Nearest neighbor Ising model in one dimension.*
- class [NearestNeighborIsingModel2](#)
 - Nearest neighbor Ising model in two dimensions.*
- class [Needle](#)
 - Needle in a haystack.*
- class [Negation](#)
 - Negation.*
- class [NkLandscape](#)
 - NK landscape.*
- class [OnBudgetFunction](#)
 - CallCounter with a limited number of evaluations.*
- class [OneMax](#)
 - OneMax.*
- class [ParsedModifier](#)
 - Parsed modifier.*
- class [Plateau](#)
 - Plateau.*

- class [PriorNoise](#)
Prior noise.
- class [ProgressTracker](#)
ProgressTracker.
- class [Qubo](#)
Quadratic unconstrained binary optimization.
- class [Ridge](#)
Ridge.
- class [SinusSummationCancellation](#)
Summation cancellation with sinus.
- class [SixPeaks](#)
Six Peaks.
- class [StopOnMaximum](#)
Stop on maximum.
- class [StopOnTarget](#)
Stop on target.
- class [SummationCancellation](#)
Summation cancellation.
- class [Trap](#)
Trap.
- class [WalshExpansion](#)
Walsh expansion.
- class [WalshExpansion1](#)
Walsh expansion of degree 1.
- class [WalshExpansion2](#)
Walsh expansion of degree 2.

Functions

- `std::ostream & operator<< (std::ostream &stream, const ProgressTracker::Event &event)`
Insert formatted output.
- `bool bv_is_locally_maximal (const bit_vector_t &bv, Function &fn, hnco::neighborhood::NeighborhoodIterator &it)`
Check whether a bit vector is locally maximal.
- `bool bv_is_globally_maximal (const bit_vector_t &bv, Function &fn)`
Check whether a bit vector is globally maximal.

4.6.1 Detailed Description

Real black box functions defined on bit vectors.

4.7 [hnco::function::real](#) Namespace Reference

Real multivariate functions.

Classes

- class [DyadicRealRepresentation](#)
Dyadic real representation.
- class [ParsedRealMultivariateFunction](#)
Parsed real multivariate function.
- class [RealMultivariateFunction](#)
Real multivariate function.
- class [RealMultivariateFunctionAdapter](#)
Real multivariate function adapter.
- class [RealRepresentation](#)
Real representation.

4.7.1 Detailed Description

Real multivariate functions.

4.8 `hnco::neighborhood` Namespace Reference

Neighborhoods for local search.

Classes

- class [BernoulliProcess](#)
Bernoulli process.
- class [HammingBall](#)
Hamming ball.
- class [HammingSphere](#)
Hamming sphere.
- class [HammingSphereIterator](#)
Hamming sphere neighborhood iterator.
- class [MultiBitFlip](#)
Multi bit flip.
- class [Neighborhood](#)
Neighborhood.
- class [NeighborhoodIterator](#)
Neighborhood iterator.
- class [SingleBitFlip](#)
One bit neighborhood.
- class [SingleBitFlipIterator](#)
Single bit flip neighborhood iterator.

4.8.1 Detailed Description

Neighborhoods for local search.

There are two unrelated kinds of neighborhoods, those for random local search and those for exhaustive local search.

4.9 hnco::random Namespace Reference

Pseudo random numbers.

Classes

- struct [Random](#)
Random numbers.

4.9.1 Detailed Description

Pseudo random numbers.

Chapter 5


Class Documentation

5.1 AbstractLabs Class Reference

Abstract class for low autocorrelation binary sequences.

```
#include <hnco/functions/labs.hh>
```

Inheritance diagram for AbstractLabs:



Public Member Functions

- [AbstractLabs](#) (int n)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [compute_autocorrelation](#) (const [bit_vector_t](#) &)
Compute autocorrelation.

Protected Attributes

- `std::vector< int > _sequence`
Binary sequence written using 1 and -1.

5.1.1 Detailed Description

Abstract class for low autocorrelation binary sequences.

Definition at line 32 of file labs.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/labs.hh
- lib/hnco/functions/labs.cc

5.2 AbstractMaxSat Class Reference

Abstract class for MaxSat-like functions.

```
#include <hnco/functions/max-sat.hh>
```

Inheritance diagram for AbstractMaxSat:



Public Member Functions

- `AbstractMaxSat ()`
Default constructor.
- `int get_bv_size ()`
Get bit vector size.
- `void display (std::ostream &stream)`
Display the expression.
- `virtual void load (std::istream &stream)`
Load an instance.
- `virtual void save (std::ostream &stream)`
Save an instance.

Protected Attributes

- `std::vector< std::vector< int > > _expression`
Expression.
- `int _num_variables`
Number of variables.

5.2.1 Detailed Description

Abstract class for MaxSat-like functions.

Definition at line 35 of file max-sat.hh.

5.2.2 Member Function Documentation

5.2.2.1 load()

```
void load (
    std::istream & stream ) [virtual]
```

Load an instance.

Exceptions

Error	
-------	--

Reimplemented in [MaxNae3Sat](#).

Definition at line 61 of file max-sat.cc.

5.2.3 Member Data Documentation

5.2.3.1 _expression

```
std::vector<std::vector<int> > _expression [protected]
```

Expression.

An expression is represented by a vector of clauses. A clause is represented by a vector of literals. A literal is represented by a non null integer; if the integer is positive then the literal is a variable; if it is negative then it is the logical negation of a variable.

Definition at line 47 of file max-sat.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/max-sat.hh
- lib/hnco/functions/max-sat.cc

5.3 AdditiveGaussianNoise Class Reference

Additive Gaussian Noise.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for AdditiveGaussianNoise:



Public Member Functions

- [AdditiveGaussianNoise](#) ([Function](#) *function, double stddev)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.

Private Attributes

- `std::normal_distribution< double > _dist`
Normal distribution.

Additional Inherited Members

5.3.1 Detailed Description

Additive Gaussian Noise.

Definition at line 169 of file function-modifier.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-modifier.hh
- lib/hnco/functions/decorators/function-modifier.cc

5.4 AffineMap Class Reference

Affine map.

```
#include <hnco/map.hh>
```

Inheritance diagram for AffineMap:



Public Member Functions

- void `random` (int rows, int cols, bool surjective)
Random instance.
- void `map` (const `bit_vector_t` &input, `bit_vector_t` &output)
Map
- int `get_input_size` ()
Get input size.
- int `get_output_size` ()
Get output size.
- bool `is_surjective` ()
Check for surjective map.

Private Member Functions

- `template<class Archive >`
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_matrix_t _bm](#)
Bit matrix.
- [bit_vector_t _bv](#)
Translation vector

Friends

- class **boost::serialization::access**

5.4.1 Detailed Description

Affine map.

An affine map f from F_2^m to F_2^n is defined by $f(x) = Ax + b$, where A is an $n \times m$ bit matrix and b is an n -dimensional bit vector.

Definition at line 258 of file map.hh.

5.4.2 Member Function Documentation

5.4.2.1 is_surjective()

```
bool is_surjective ( ) [virtual]
```

Check for surjective map.

Returns

true if `rank(_bm) == bm_num_rows(_bm)`

Reimplemented from [Map](#).

Definition at line 136 of file map.cc.

5.4.2.2 random()

```
void random (
    int rows,
    int cols,
    bool surjective )
```

Random instance.

Parameters

<i>rows</i>	Number of rows
<i>cols</i>	Number of columns
<i>surjective</i>	Flag to ensure a surjective map

Exceptions

<i>Error</i>	
--------------	--

Definition at line 99 of file map.cc.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.5 Algorithm Class Reference

Abstract search algorithm.

```
#include <hnco/algorithms/algorithm.hh>
```

Inheritance diagram for Algorithm:



Public Member Functions

- [Algorithm](#) (int n)
Constructor.
- virtual [~Algorithm](#) ()
Destructor.

Optimization

- virtual void [init](#) ()
Initialization.
- virtual void [maximize](#) ()=0
Maximize.

Getters

- virtual const [point_value_t](#) & [get_solution](#) ()
Solution.
- virtual int [get_bv_size](#) ()
Get bit vector size.

Setters

- virtual void [set_function](#) (function::Function *function)
Set function.
- virtual void [set_functions](#) (const std::vector< [function::Function](#) *> functions)
Set functions.
- void [set_stream](#) (std::ostream *x)
Output stream.
- void [set_log_context](#) (LogContext *lc)
Set log context.

Protected Member Functions

Managing solution

- void [random_solution](#) ()
Random solution.
- void [set_solution](#) (const [bit_vector_t](#) &x, double value)
Set solution.
- void [set_solution](#) (const [bit_vector_t](#) &x)
Set solution.
- void [update_solution](#) (const [bit_vector_t](#) &x, double value)
Update solution (strict)
- void [update_solution](#) (const [point_value_t](#) &pv)
Update solution (strict)
- void [update_solution](#) (const [bit_vector_t](#) &x)
Update solution (strict).

Protected Attributes

- `function::Function * _function`
Function.
- `std::vector< function::Function * > _functions`
Functions.
- `point_value_t _solution`
Solution.
- `LogContext * _log_context = nullptr`
Log context.

Parameters

- `std::ostream * _stream = &std::cout`
Output stream.

5.5.1 Detailed Description

Abstract search algorithm.

All algorithms maximize some given function, sometimes called a fitness function or an objective function.

Definition at line 41 of file algorithm.hh.

5.5.2 Member Function Documentation

5.5.2.1 set_solution()

```
void set_solution (
    const bit_vector_t & x ) [protected]
```

Set solution.

Warning

Evaluates the function once.

Definition at line 47 of file algorithm.cc.

5.5.2.2 update_solution()

```
void update_solution (
    const bit_vector_t & x ) [protected]
```

Update solution (strict).

Warning

Evaluates the function once.

Definition at line 70 of file algorithm.cc.

5.5.3 Member Data Documentation

5.5.3.1 _functions

```
std::vector<function::Function *> _functions [protected]
```

Functions.

Each thread has its own function.

Definition at line 52 of file algorithm.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/algorithm.hh
- lib/hnco/algorithms/algorithm.cc

5.6 BernoulliProcess Class Reference

Bernoulli process.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for BernoulliProcess:



Public Member Functions

- [BernoulliProcess](#) (int n)
Constructor.
- [BernoulliProcess](#) (int n, double p)
Constructor.
- void [set_probability](#) (double p)
Set probability.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.
- void [bernoulli_process](#) ()
Bernoulli process.

Private Attributes

- std::bernoulli_distribution [_bernoulli_dist](#)
Bernoulli distribution (biased coin)
- std::binomial_distribution< int > [_binomial_dist](#)
Binomial distribution.
- bool [_reservoir_sampling](#) = false
Reservoir sampling.

Parameters

- bool [_allow_stay](#) = false
Allow stay.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Additional Inherited Members

5.6.1 Detailed Description

Bernoulli process.

Each component of the origin bit vector is flipped with some fixed probability. If no component has been flipped at the end, the process is started all over again. Thus the number of flipped bits follows a pseudo binomial law.

Definition at line 220 of file neighborhood.hh.

5.6.2 Constructor & Destructor Documentation

5.6.2.1 BernoulliProcess() [1/2]

```
BernoulliProcess (
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

The Bernoulli probability is set to $1 / n$.

Definition at line 255 of file neighborhood.hh.

5.6.2.2 BernoulliProcess() [2/2]

```
BernoulliProcess (
    int n,
    double p ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
p	Bernoulli probability

Definition at line 265 of file neighborhood.hh.

5.6.3 Member Function Documentation**5.6.3.1 set_allow_stay()**

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 292 of file neighborhood.hh.

5.6.3.2 set_probability()

```
void set_probability (
    double p ) [inline]
```

Set probability.

Sets `_reservoir_sampling` to true if $E(X) < \sqrt{n}$, where X is a random variable with a binomial distribution $B(n, p)$, that is if $np < \sqrt{n}$ or $p < 1 / \sqrt{n}$.

Definition at line 276 of file neighborhood.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.7 BiasedCrossover Class Reference

Biased crossover.

```
#include <hnco/algorithms/ea/crossover.hh>
```

Inheritance diagram for BiasedCrossover:



Public Member Functions

- [BiasedCrossover](#) ()
Constructor.
- void [breed](#) (const [bit_vector_t](#) &parent1, const [bit_vector_t](#) &parent2, [bit_vector_t](#) &offspring)
Breed.
- void [set_bias](#) (double b)
Set bias.

Private Attributes

- `std::bernoulli_distribution` [_bernoulli_dist](#)
Bernoulli distribution.

5.7.1 Detailed Description

Biased crossover.

Definition at line 75 of file `crossover.hh`.

5.7.2 Member Function Documentation

5.7.2.1 breed()

```
void breed (
    const bit\_vector\_t & parent1,
    const bit\_vector\_t & parent2,
    bit\_vector\_t & offspring ) [virtual]
```

Breed.

Each offspring's bit is copied from second parent with a fixed probability (the crossover bias), from first parent otherwise.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implements [Crossover](#).

Definition at line 45 of file crossover.cc.

The documentation for this class was generated from the following files:

- lib/hnco/algorithms/ea/crossover.hh
- lib/hnco/algorithms/ea/crossover.cc

5.8 BitHerding Class Reference

Herding with bit features.

```
#include <hnco/algorithms/hea/bit-herding.hh>
```

Public Types

- enum { [DYNAMICS_MINIMIZE_NORM](#), [DYNAMICS_MAXIMIZE_INNER_PRODUCT](#) }

Public Member Functions

- [BitHerding](#) (int n)
Constructor.
- void [init](#) ()
Initialization.
- void [sample](#) (const [BitMoment](#) &target, [bit_vector_t](#) &x)
Sample a bit vector.
- double [error](#) (const [BitMoment](#) &target)
Compute the error.

Getters

- const [BitMoment](#) & [get_delta](#) ()
Get delta.

Setters

- void [set_randomize_bit_order](#) (bool x)
Randomize bit order.
- void [set_dynamics](#) (int x)
Set the dynamics.
- void [set_weight](#) (double x)
Set the weight of second order moments.

Protected Member Functions

- void `compute_delta` (const `BitMoment` &target)
Compute delta.
- void `sample_minimize_norm` (const `BitMoment` &target, `bit_vector_t` &x)
Sample a bit vector.
- void `sample_maximize_inner_product` (const `BitMoment` &target, `bit_vector_t` &x)
Sample a bit vector.

Protected Attributes

- `BitMoment _count`
Counter moment.
- `BitMoment _delta`
Delta moment.
- `permutation_t _permutation`
Permutation.
- `std::uniform_int_distribution< int > _choose_bit`
Choose bit.
- `int _time`
Time.

Parameters

- `bool _randomize_bit_order` = false
Randomize bit order.
- `int _dynamics` = `DYNAMICS_MINIMIZE_NORM`
Dynamics.
- `double _weight` = 1
Weight of second order moments.

5.8.1 Detailed Description

Herding with bit features.

Definition at line 38 of file `bit-herding.hh`.

5.8.2 Member Enumeration Documentation

5.8.2.1 anonymous enum

anonymous enum

Enumerator

<code>DYNAMICS_MINIMIZE_NORM</code>	Dynamics defined as minimization of a norm.
<code>DYNAMICS_MAXIMIZE_INNER_PRODUCT</code>	Dynamics defined as maximization of an inner product.

Definition at line 83 of file bit-herding.hh.

The documentation for this class was generated from the following files:

- lib/hnco/algorithms/hea/bit-herding.hh
- lib/hnco/algorithms/hea/bit-herding.cc

5.9 BitMoment Struct Reference

Moment for bit features.

```
#include <hnco/algorithms/hea/bit-moment.hh>
```

Public Member Functions

- [BitMoment](#) (int n)
Constructor.
- void [uniform](#) ()
Set the moment to that of the uniform distribution.
- void [init](#) ()
Initialize.
- void [add](#) (const [bit_vector_t](#) &x)
Accumulate a bit vector.
- void [average](#) (int count)
Compute average.
- void [update](#) (const [BitMoment](#) &p, double rate)
Update moment.
- void [bound](#) (double margin)
Bound moment.
- double [distance](#) (const [BitMoment](#) &p) const
Distance.
- double [norm_2](#) () const
Compute the norm 2.
- double [diameter](#) () const
Compute the diameter.
- size_t [size](#) () const
Size.
- void [display](#) (std::ostream &stream)
Display.

Public Attributes

- std::vector< std::vector< double > > [_moment](#)
Moment.
- double [_weight](#) = 1
Weight of second order moments.

5.9.1 Detailed Description

Moment for bit features.

Definition at line 38 of file bit-moment.hh.

The documentation for this struct was generated from the following files:


- lib/hnco/algorithms/hea/bit-moment.hh
- lib/hnco/algorithms/hea/bit-moment.cc

5.10 BmPbil Class Reference

Boltzmann machine PBIL.

```
#include <hnco/algorithms/bm-pbil/bm-pbil.hh>
```

Inheritance diagram for BmPbil:



Public Types

- enum { LOG_NORM_INFINITE, LOG_NORM_L1, **LAST_LOG** }
- enum { **SAMPLING_ASYNCHRONOUS**, **SAMPLING_ASYNCHRONOUS_FULL_SCAN**, **SAMPLING_SYNCHRONOUS** }
- enum { **RESET_NO_RESET**, **RESET_ITERATION**, **RESET_BIT_VECTOR** }
- typedef std::bitset< LAST_LOG > **log_flags_t**

Public Member Functions

- **BmPbil** (int n, int population_size)
Constructor.
- void **init** ()
Initialization.

Private Member Functions

- void `iterate ()`
Single iteration.
- void `log ()`
Log.
- void `sample (bit_vector_t &x)`
Sample a bit vector.
- void `sample_asynchronous ()`
Asynchronous sampling.
- void `sample_asynchronous_full_scan ()`
Asynchronous sampling with full scan.
- void `sample_synchronous ()`
Synchronous sampling.

Private Attributes

- `log_flags_t _log_flags`
Log flags.
- `Population _population`
Population.
- `Model _model`
Model.
- `ModelParameters _parameters_all`
Parameters averaged over all individuals.
- `ModelParameters _parameters_best`
Parameters averaged over selected individuals.
- `ModelParameters _parameters_worst`
Parameters averaged over negatively selected individuals.
- `std::uniform_int_distribution< size_t > _choose_bit`
Uniform distribution on bit_vector_t components.
- `permutation_t _permutation`
Permutation.

Parameters

- `int _selection_size = 1`
Selection size (number of selected individuals in the population)
- `double _learning_rate = 1e-3`
Learning rate.
- `int _num_gs_steps = 100`
Number of gibbs sampler steps.
- `int _num_gs_cycles = 1`
Number of gibbs sampler cycles.
- `bool _negative_positive_selection = false`
Negative and positive selection.
- `int _sampling = SAMPLING_ASYNCHRONOUS`
Sampling mode.
- `int _mc_reset_strategy = RESET_NO_RESET`

- MC reset strategy.*
 - void [set_selection_size](#) (int x)
Set the selection size.
 - void [set_learning_rate](#) (double x)
Set the learning rate.
 - void [set_num_gs_steps](#) (int x)
Set the number of gibbs sampler steps.
 - void [set_num_gs_cycles](#) (int x)
Set the number of gibbs sampler cycles.
 - void [set_negative_positive_selection](#) (bool x)
Set negative and positive selection.
 - void [set_sampling](#) (int x)
Set the sampling mode.
 - void [set_mc_reset_strategy](#) (int x)
Set the MC reset strategy.
 - void [set_log_flags](#) (const log_flags_t &lf)
Set log flags.

Additional Inherited Members

5.10.1 Detailed Description

Boltzmann machine PBIL.

The BM model is slightly different from the one given in the reference below. More precisely, 0/1 variables are mapped to -1/+1 variables as in Walsh analysis.

Reference:

Arnaud Berny. 2002. Boltzmann machine for population-based incremental learning. In ECAI 2002. IOS Press, Lyon.

Definition at line 51 of file bm-pbil.hh.

5.10.2 Member Enumeration Documentation

5.10.2.1 anonymous enum

anonymous enum

Enumerator

LOG_NORM_INFINITE	Log infinite norm of the model parameters.
LOG_NORM_L1	Log 1-norm of the model parameters.

Definition at line 56 of file bm-pbil.hh.

5.10.2.2 anonymous enum

anonymous enum

Enumerator

SAMPLING_ASYNCHRONOUS	Asynchronous sampling. A single component of the internal state is randomly selected then updated by Gibbs sampling. This step is repeated <code>_num_gs_steps</code> times.
SAMPLING_ASYNCHRONOUS_FULL_SCAN	Asynchronous sampling with full scan. To sample a new bit vector, a random permutation is sampled and all components of the internal state are updated by Gibbs sampling in the order defined by the permutation.
SAMPLING_SYNCHRONOUS	Synchronous sampling. The full internal state is updated in one step from the probability vector made of the very marginal probabilities used in Gibbs sampling.

Definition at line 66 of file bm-pbil.hh.

5.10.2.3 anonymous enum

anonymous enum

Enumerator

RESET_NO_RESET	No reset.
RESET_ITERATION	Reset MC at the beginning of each iteration.
RESET_BIT_VECTOR	Reset MC before sampling each bit vector.

Definition at line 93 of file bm-pbil.hh.

5.10.3 Member Function Documentation

5.10.3.1 `set_selection_size()`

```
void set_selection_size (
    int x ) [inline]
```

Set the selection size.

The selection size is the number of selected individuals in the population.

Definition at line 210 of file bm-pbil.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/bm-pbil/bm-pbil.hh
- lib/hnco/algorithms/bm-pbil/bm-pbil.cc

5.11 Cache Class Reference

[Cache](#).

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for Cache:



Public Member Functions

- [Cache](#) ([Function](#) *function)
Constructor.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.
- double [get_lookup_ratio](#) ()
Get lookup ratio.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- `std::unordered_map< std::vector< bool >, double > _cache`
Cache.
- `std::vector< bool > _key`
Key.
- `int _num_evaluations`
Evaluation counter.
- `int _num_lookups`
Lookup counter.

Additional Inherited Members

5.11.1 Detailed Description

Cache.

This is a naive approach, in particular with respect to time complexity. Moreover, there is no control on the size of the database.

There is no default hash function for `std::vector<char>` hence the need to first copy a `bit_vector_t` into a `std::vector<bool>`, for which such a function exists, before inserting it or checking its existence in the map.

Definition at line 362 of file `function-controller.hh`.

5.11.2 Constructor & Destructor Documentation

5.11.2.1 Cache()

```
Cache (
    Function * function ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
-----------------	--------------------

Definition at line 381 of file `function-controller.hh`.

5.11.3 Member Function Documentation

5.11.3.1 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented from [FunctionController](#).

Definition at line 390 of file function-controller.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.12 CallCounter Class Reference

Call counter.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for CallCounter:



Public Member Functions

- [CallCounter](#) ([Function](#) *function)

Constructor.

- int [get_num_calls](#) ()

Get the number of calls.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)

Evaluate a bit vector.

- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped←_bits)

Incremental evaluation.

- void [update](#) (const [bit_vector_t](#) &x, double value)

Update after a safe evaluation.

Protected Attributes

- int [_num_calls](#)

Number of calls.

5.12.1 Detailed Description

Call counter.

Definition at line 173 of file function-controller.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.13 CompactGa Class Reference

Compact genetic algorithm.

```
#include <hnco/algorithms/pv/compact-ga.hh>
```

Inheritance diagram for CompactGa:



Public Member Functions

- [CompactGa](#) (int n)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_learning_rate](#) (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- std::vector< [bit_vector_t](#) > [_candidates](#)
Candidates.

Parameters

- double [_learning_rate](#) = 1e-3
Learning rate.

5.13.1 Detailed Description

Compact genetic algorithm.

Reference:

Georges R. Harik, Fernando G. Lobo, and David E. Goldberg. 1999. The Compact Genetic Algorithm. IEEE Trans. on Evolutionary Computation 3, 4 (November 1999), 287–297.

Definition at line 43 of file compact-ga.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/pv/compact-ga.hh
- lib/hnco/algorithms/pv/compact-ga.cc

5.14 CompleteSearch Class Reference

Complete search.

```
#include <hnco/algorithms/complete-search.hh>
```

Inheritance diagram for CompleteSearch:



Public Member Functions

- [CompleteSearch](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.

Additional Inherited Members

5.14.1 Detailed Description

Complete search.

Definition at line 34 of file complete-search.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/complete-search.hh
- lib/hnco/algorithms/complete-search.cc

5.15 Crossover Class Reference

[Crossover](#).

```
#include <hnco/algorithms/ea/crossover.hh>
```

Inheritance diagram for Crossover:



Public Member Functions

- virtual [~Crossover](#) ()
Destructor.
- virtual void [breed](#) (const [bit_vector_t](#) &parent1, const [bit_vector_t](#) &parent2, [bit_vector_t](#) &offspring)=0
Breed.

5.15.1 Detailed Description

[Crossover](#).

Definition at line 35 of file crossover.hh.

5.15.2 Member Function Documentation

5.15.2.1 breed()

```
virtual void breed (
    const bit\_vector\_t & parent1,
    const bit\_vector\_t & parent2,
    bit\_vector\_t & offspring ) [pure virtual]
```

Breed.

The offspring is the crossover of two parents.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implemented in [BiasedCrossover](#), and [UniformCrossover](#).

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/ea/crossover.hh`

5.16 DeceptiveJump Class Reference

Deceptive jump.

```
#include <hnco/functions/jump.hh>
```

Inheritance diagram for DeceptiveJump:



Public Member Functions

- [DeceptiveJump](#) (int bv_size, int gap)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_gap](#)
Gap.

5.16.1 Detailed Description

Deceptive jump.

This is a jump function with a deceptive gap as defined in "Analyzing evolutionary algorithms" by Thomas Jansen, where it is called Jump_k. Algorithms in the neighborhood of the maximizer (which is the all one bit vector) are taken away from it.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 85 of file jump.hh.

5.16.2 Member Function Documentation

5.16.2.1 [get_maximum\(\)](#)

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

[_bv_size](#) + [_gap](#)

Reimplemented from [Function](#).

Definition at line 111 of file jump.hh.

5.16.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 107 of file jump.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/jump.hh
- lib/hnco/functions/jump.cc

5.17 DyadicRealRepresentation Class Reference

Dyadic real representation.

```
#include <hnco/functions/real/real-representation.hh>
```

Inheritance diagram for DyadicRealRepresentation:



Public Member Functions

- [DyadicRealRepresentation](#) (double lower_bound, double upper_bound, int num_bits)
Constructor.
- int [size](#) ()
Size of the representation.
- double [convert](#) (hnco::bit_vector_t::const_iterator first, hnco::bit_vector_t::const_iterator last)
Convert a bit vector range into a double.

Private Member Functions

- double `affine_transformation` (double x)
Affine transformation.

Private Attributes

- `std::vector< double > _lengths`
Lengths of dyadic intervals.
- double `_lower_bound`
Lower bound of the search interval.
- double `_length`
Length of the search interval.

5.17.1 Detailed Description

Dyadic real representation.

Definition at line 52 of file `real-representation.hh`.

5.17.2 Constructor & Destructor Documentation

5.17.2.1 DyadicRealRepresentation()

```
DyadicRealRepresentation (
    double lower_bound,
    double upper_bound,
    int num_bits )
```

Constructor.

Parameters

<code>lower_bound</code>	Lower bound of the search interval
<code>upper_bound</code>	Upper bound of the search interval
<code>num_bits</code>	Number of bits per real

Definition at line 31 of file `real-representation.cc`.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/real/real-representation.hh`
- `lib/hnco/functions/real/real-representation.cc`

5.18 EqualProducts Class Reference

Equal products.

```
#include <hnco/functions/equal-products.hh>
```

Inheritance diagram for EqualProducts:



Public Member Functions

- [EqualProducts](#) ()
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Instance generators

- template<class Generator >
void [generate](#) (int n, Generator generator)
Instance generator.
- void [random](#) (int n)
Random instance.

Private Member Functions

- template<class Archive >
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- std::vector< double > [_numbers](#)
Numbers.

Friends

- class **boost::serialization::access**

5.18.1 Detailed Description

Equal products.

Partition a finite set of positive numbers into two subsets such that the product of numbers in the first subset is the closest to the product of numbers in the second subset. This is equivalent to the partition problem applied to the logarithms of the given numbers.

The function computes the negation of the distance between the product of numbers corresponding to ones in the bit vector and the product of those corresponding to zeros. The negation is a consequence of the fact that algorithms in HNCO maximize rather than minimize a function.

Reference:

S. Baluja and S. Davies. 1997. Using optimal dependency-trees for combinatorial optimization: learning the structure of the search space. Technical Report CMU- CS-97-107. Carnegie-Mellon University.

Definition at line 61 of file equal-products.hh.

5.18.2 Member Function Documentation

5.18.2.1 generate()

```
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Number generator

Definition at line 94 of file equal-products.hh.

5.18.2.2 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the uniform distribution on $[0,1)$.

Parameters

n	Size of bit vector
-----	--------------------

Definition at line 109 of file equal-products.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/equal-products.hh
- lib/hnco/functions/equal-products.cc

5.19 Error Class Reference

[Error](#).

```
#include <hnco/exception.hh>
```

Inheritance diagram for Error:



Public Member Functions

- [Error](#) ()
Constructor.
- [Error](#) (const std::string &s)
Constructor.
- virtual [~Error](#) ()
Destructor.
- virtual const char * [what](#) () const
Get message.

Protected Attributes

- std::string [_what](#)
Message.

5.19.1 Detailed Description

[Error](#).

Definition at line 84 of file exception.hh.

The documentation for this class was generated from the following file:

- lib/hnco/exception.hh

5.20 ProgressTracker::Event Struct Reference

[Event](#).

```
#include <hnco/functions/decorators/function-controller.hh>
```

Public Attributes

- int [num_evaluations](#)
Number of evaluations.
- double [value](#)
Value.

5.20.1 Detailed Description

[Event](#).

Definition at line 222 of file function-controller.hh.

The documentation for this struct was generated from the following file:


- lib/hnco/functions/decorators/function-controller.hh

5.21 Exception Class Reference

Basic exception.

```
#include <hnco/exception.hh>
```

Inheritance diagram for Exception:



5.21.1 Detailed Description

Basic exception.

Definition at line 36 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.22 Factorization Class Reference

[Factorization](#).

```
#include <hnco/functions/factorization.hh>
```

Inheritance diagram for Factorization:



Public Member Functions

- [Factorization](#) ()
Constructor.
- [Factorization](#) (const std::string number)
Constructor.
- [~Factorization](#) ()
Destructor.
- void [load](#) (std::istream &stream)
Load an instance.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- void [display](#) (std::ostream &stream)
Display.
- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- void `init` ()
Init GMP data structures.
- void `clear` ()
Clear GMP data structures.
- void `set_number` (const std::string number)
Set number.
- void `convert` (const `bit_vector_t` &x)
Convert a bit vector into two numbers.

Private Attributes

- `mpz_t _number`
Number to factorize.
- `mpz_t _first_factor`
First factor.
- `mpz_t _second_factor`
Second factor.
- `mpz_t _product`
Product.
- `std::string _first_factor_string`
First factor in binary form.
- `std::string _second_factor_string`
Secon factor in binary form.
- `size_t _number_size`
Number size in bits.
- `size_t _first_factor_size`
First factor size in bits.
- `size_t _second_factor_size`
Second factor size in bits.
- `int _bv_size`
Bit vector size.

5.22.1 Detailed Description

[Factorization](#).

Reference:

Torbjörn Granlund and the GMP development team. 2012. GNU MP: The GNU Multiple Precision Arithmetic Library (5.0.5 ed.).

<http://gmplib.org/>.

Definition at line 28 of file factorization.hh.

5.22.2 Constructor & Destructor Documentation

5.22.2.1 Factorization()

```
Factorization (
    const std::string number ) [inline]
```

Constructor.

Parameters

<i>number</i>	Number to factorize written in decimal form
---------------	---

Definition at line 82 of file factorization.hh.

5.22.3 Member Function Documentation

5.22.3.1 load()

```
void load (
    std::istream & stream )
```

Load an instance.

Warning

The file is a text file which contains exactly one natural number written in base 10 without any space.

Exceptions

<i>Error</i>	
--------------	--

Definition at line 37 of file factorization.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/factorization.hh
- lib/hnco/functions/factorization.cc

5.23 FirstAscentHillClimbing Class Reference

First ascent hill climbing.

```
#include <hnco/algorithms/ls/first-ascent-hill-climbing.hh>
```

Inheritance diagram for FirstAscentHillClimbing:



Public Member Functions

- [FirstAscentHillClimbing](#) (int n, [neighborhood::NeighborhoodIterator](#) *neighborhood)
Constructor.
- void [init](#) ()
Random initialization.
- void [init](#) (const [bit_vector_t](#) &x)
Explicit initialization.
- void [init](#) (const [bit_vector_t](#) &x, double value)
Explicit initialization.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [neighborhood::NeighborhoodIterator](#) * [_neighborhood](#)
Neighborhood.

5.23.1 Detailed Description

First ascent hill climbing.

Definition at line 35 of file first-ascent-hill-climbing.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ls/first-ascent-hill-climbing.hh
- lib/hnco/algorithms/ls/first-ascent-hill-climbing.cc

5.24 FourPeaks Class Reference

Four Peaks.

```
#include <hnco/functions/four-peaks.hh>
```

Inheritance diagram for FourPeaks:



Public Member Functions

- `FourPeaks` (int bv_size, int threshold)
Constructor.
- int `get_bv_size` ()
Get bit vector size.
- double `eval` (const `bit_vector_t` &)
Evaluate a bit vector.
- bool `has_known_maximum` ()
Check for a known maximum.
- double `get_maximum` ()
Get the global maximum.

Private Attributes

- int `_bv_size`
Bit vector size.
- int `_threshold`
Threshold.
- int `_maximum`
Maximum.

5.24.1 Detailed Description

Four Peaks.

It is defined by

$$f(x) = \max\{\text{head}(x, 1) + \text{tail}(x, 0)\} + R(x)$$

where:

- $\text{head}(x, 1)$ is the length of the longest prefix of x made of ones;
- $\text{tail}(x, 0)$ is the length of the longest suffix of x made of zeros;
- $R(x)$ is the reward;
- $R(x) = n$ if $(\text{head}(x, 1) > t \text{ and } \text{tail}(x, 0) > t)$;
- $R(x) = 0$ otherwise;
- the threshold t is a parameter of the function.

This function has four maxima, of which exactly two are global ones.

For example, if $n = 6$ and $t = 1$:

- $f(111111) = 6$ (local maximum)
- $f(111110) = 5$
- $f(111100) = 10$ (global maximum)

Reference:

S. Baluja and R. Caruana. 1995. Removing the genetics from the standard genetic algorithm. In Proceedings of the 12th Annual Conference on Machine Learning. 38–46.

Definition at line 60 of file four-peaks.hh.

5.24.2 Member Function Documentation

5.24.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$2 * \text{_bv_size} - \text{_threshold} - 1$

Reimplemented from [Function](#).

Definition at line 91 of file four-peaks.hh.

5.24.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 87 of file four-peaks.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/four-peaks.hh
- lib/hnco/functions/four-peaks.cc

5.25 Function Class Reference

[Function](#).

```
#include <hnco/functions/function.hh>
```

Inheritance diagram for Function:



Classes

- struct [WalshTransformTerm](#)
Walsh transform term.

Public Member Functions

- virtual [~Function](#) ()

Destructor.

Information about the function

- virtual int `get_bv_size` ()=0
Get bit vector size.
- virtual double `get_maximum` ()
Get the global maximum.
- virtual bool `has_known_maximum` ()
Check for a known maximum.
- virtual bool `provides_incremental_evaluation` ()
Check whether the function provides incremental evaluation.
- virtual void `compute_walsh_transform` (std::vector< [Function::WalshTransformTerm](#) > &terms)
Compute the Walsh transform of the function.

Evaluation

- virtual double `eval` (const [bit_vector_t](#) &)=0
Evaluate a bit vector.
- virtual double `incremental_eval` (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.
- virtual double `safe_eval` (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.
- virtual void `update` (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Display

- virtual void `display` (std::ostream &stream)
Display.
- virtual void `describe` (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

5.25.1 Detailed Description

[Function.](#)

Definition at line 41 of file `function.hh`.

5.25.2 Member Function Documentation

5.25.2.1 `compute_walsh_transform()`

```
void compute_walsh_transform (
    std::vector< Function::WalshTransformTerm > & terms ) [virtual]
```

Compute the Walsh transform of the function.

Let f be a fitness function defined on the hypercube $\{0,1\}^n$. Then it can be expressed as $\sum_u c_u \chi_u$ where $c_u = \langle f, \chi_u \rangle$, $\langle f, g \rangle = \frac{1}{2^n} \sum_x f(x)g(x)$, $\chi_u(x) = (-1)^{x \cdot u}$, and $x \cdot u = \sum_i x_i u_i \pmod{2}$. In the respective sums, we have x and u in the hypercube and i in $\{1, \dots, n\}$.

We have dropped the normalizing constant 2^n since we are mostly interested in ratios $|c_u/c_{\max}|$, where c_{\max} is the coefficient with the largest amplitude.

Parameters

<i>terms</i>	Vector of non zero terms of the Walsh transform
--------------	---

Warning

The time complexity is exponential in the dimension n . The computation is done with two nested loops over the hypercube. It requires 2^n function evaluations and 2^{2n} dot products and additions.

The size of the Walsh transform is potentially exponential in the dimension n . For example, if $n = 10$ then the number of terms is at most 1024.

Definition at line 31 of file function.cc.

5.25.2.2 `get_maximum()`

```
virtual double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Exceptions

<i>Error</i>	
--------------	--

Reimplemented in [Plateau](#), [Ridge](#), [Hiff](#), [SixPeaks](#), [Needle](#), [FunctionMapComposition](#), [WalshExpansion1](#), [LeadingOnes](#), [LinearFunction](#), [DeceptiveJump](#), [LongPath](#), [FourPeaks](#), [SummationCancellation](#), [Trap](#), [PriorNoise](#), [Jump](#), [OneMax](#), and [FunctionController](#).

Definition at line 80 of file function.hh.

5.25.2.3 `incremental_eval()`

```
virtual double incremental_eval (
    const bit\_vector\_t & x,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [inline], [virtual]
```

Incremental evaluation.

Exceptions

<i>Error</i>	
--------------	--

Reimplemented in [OnBudgetFunction](#), [ProgressTracker](#), [CallCounter](#), [NearestNeighborIsingModel2](#), [NearestNeighborIsingModel1](#), [StopOnTarget](#), [StopOnMaximum](#), [WalshExpansion1](#), [LinearFunction](#), [Negation](#), and [OneMax](#).

Definition at line 133 of file function.hh.

5.25.2.4 provides_incremental_evaluation()

```
virtual bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented in [Cache](#), [NearestNeighborIsingModel2](#), [NearestNeighborIsingModel1](#), [WalshExpansion1](#), [LinearFunction](#), [Negation](#), [PriorNoise](#), [OneMax](#), and [FunctionController](#).

Definition at line 88 of file function.hh.

5.25.2.5 safe_eval()

```
virtual double safe_eval (
    const bit\_vector\_t & x ) [inline], [virtual]
```

Safely evaluate a bit vector.

Must be thread-safe, that is must avoid throwing exceptions and updating global states (e.g. maximum) in function decorators.

Reimplemented in [FunctionController](#).

Definition at line 143 of file function.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/function.hh
- lib/hnco/functions/function.cc

5.26 FunctionController Class Reference

Function controller.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for FunctionController:



Public Member Functions

- [FunctionController](#) ([Function](#) *function)
Constructor.

Information about the function

- [int](#) [get_bv_size](#) ()
Get bit vector size.
- [double](#) [get_maximum](#) ()
Get the global maximum.
- [bool](#) [has_known_maximum](#) ()
Check for a known maximum.
- [bool](#) [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- [double](#) [safe_eval](#) (const [bit_vector_t](#) &x)
Safely evaluate a bit vector.

Additional Inherited Members

5.26.1 Detailed Description

[Function](#) controller.

Definition at line 39 of file function-controller.hh.

5.26.2 Member Function Documentation

5.26.2.1 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true if the decorated function does

Reimplemented from [Function](#).

Reimplemented in [Cache](#).

Definition at line 64 of file function-controller.hh.

The documentation for this class was generated from the following file:


- lib/hnco/functions/decorators/function-controller.hh

5.27 FunctionDecorator Class Reference

[Function](#) decorator.

```
#include <hnco/functions/decorators/function-decorator.hh>
```

Inheritance diagram for FunctionDecorator:



Public Member Functions

- [FunctionDecorator](#) ([Function](#) *function)
Constructor.

Display

- void [display](#) (std::ostream &stream)
Display.
- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Protected Attributes

- [Function](#) * [_function](#)
Decorated function.

5.27.1 Detailed Description

[Function](#) decorator.

Definition at line 33 of file `function-decorator.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/functions/decorators/function-decorator.hh`

5.28 FunctionMapComposition Class Reference

Composition of a function and a map.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for `FunctionMapComposition`:



Public Member Functions

- [FunctionMapComposition](#) ([Function](#) *function, [Map](#) *map)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.

Display

- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Attributes

- [Map](#) * [_map](#)
Map.
- [bit_vector_t](#) [_bv](#)
Image of bit vectors under the map.

Additional Inherited Members

5.28.1 Detailed Description

Composition of a function and a map.

Definition at line 99 of file function-modifier.hh.

5.28.2 Constructor & Destructor Documentation

5.28.2.1 FunctionMapComposition()

```
FunctionMapComposition (
    Function * function,
    Map * map ) [inline]
```

Constructor.

Precondition

map->get_output_size() == function->get_bv_size()

Exceptions

Error	
-------	--

Definition at line 114 of file function-modifier.hh.

5.28.3 Member Function Documentation

5.28.3.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Exceptions

Error	
-------	--

Reimplemented from [Function](#).

Definition at line 134 of file function-modifier.hh.

5.28.3.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true if the function has a known maximum and the map is bijective.

Reimplemented from [Function](#).

Definition at line 144 of file function-modifier.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-modifier.hh
- lib/hnco/functions/decorators/function-modifier.cc

5.29 FunctionModifier Class Reference

Function modifier.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for FunctionModifier:



Public Member Functions

- [FunctionModifier](#) ([Function](#) *function)

Constructor.

Additional Inherited Members

5.29.1 Detailed Description

Function modifier.

Definition at line 38 of file function-modifier.hh.

The documentation for this class was generated from the following file:


- lib/hnco/functions/decorators/function-modifier.hh

5.30 FunctionPlugin Class Reference

Function plugin.

```
#include <hnco/functions/plugin.hh>
```

Inheritance diagram for FunctionPlugin:



Public Member Functions

- [FunctionPlugin](#) (int bv_size, std::string path, std::string name)
Constructor.
- [~FunctionPlugin](#) ()
Destructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Types

- typedef double(* [extern_function_t](#)) (const [bit_t](#) *, size_t)
Type of an extern function.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- void * [_handle](#)
Handle returned by dlopen.
- [extern_function_t](#) [_extern_function](#)
Extern function.

5.30.1 Detailed Description

Function plugin.

Definition at line 34 of file plugin.hh.

5.30.2 Constructor & Destructor Documentation

5.30.2.1 FunctionPlugin()

```
FunctionPlugin (
    int bv_size,
    std::string path,
    std::string name )
```

Constructor.

Parameters

<i>bv_size</i>	Size of bit vectors
<i>path</i>	Path to a shared library
<i>name</i>	Name of a function of the shared library

Definition at line 33 of file plugin.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/plugin.hh
- lib/hnco/functions/plugin.cc

5.31 GeneticAlgorithm Class Reference

Genetic algorithm.

```
#include <hnco/algorithms/ea/genetic-algorithm.hh>
```

Inheritance diagram for GeneticAlgorithm:



Public Member Functions

- [GeneticAlgorithm](#) (int n, int mu)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_crossover_probability](#) (double x)
Set the crossover probability.
- void [set_tournament_size](#) (int x)
Set the tournament size.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [TournamentSelection _parents](#)
Parents.
- [TournamentSelection _offsprings](#)
Offsprings.
- [neighborhood::BernoulliProcess _mutation](#)

Mutation operator.

- `std::bernoulli_distribution _do_crossover`

Do crossover.

- `UniformCrossover _crossover`

Uniform crossover.

Parameters

- `double _mutation_probability`
Mutation probability.
- `double _crossover_probability = 0.5`
Crossover probability.
- `int _tournament_size = 10`
Tournament size.
- `bool _allow_stay = false`
Allow stay.

Additional Inherited Members

5.31.1 Detailed Description

Genetic algorithm.

- Tournament selection for reproduction
- Uniform crossover
- Mutation
- (mu, mu) selection (offspring population replaces parent population)

Reference:

J. H. Holland. 1975. Adaptation in natural and artificial systems. University of Michigan Press, Ann Arbor.

Definition at line 51 of file genetic-algorithm.hh.

5.31.2 Constructor & Destructor Documentation

5.31.2.1 GeneticAlgorithm()

```
GeneticAlgorithm (
    int n,
    int mu ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Population size

Definition at line 97 of file genetic-algorithm.hh.

5.31.3 Member Function Documentation

5.31.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 125 of file genetic-algorithm.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/genetic-algorithm.hh
- lib/hnco/algorithms/ea/genetic-algorithm.cc

5.32 HammingBall Class Reference

Hamming ball.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for HammingBall:



Public Member Functions

- [HammingBall](#) (int n, int r)
Constructor.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.

Private Attributes

- std::uniform_int_distribution< int > [_choose_k](#)
Choose the distance to the center.

Additional Inherited Members

5.32.1 Detailed Description

Hamming ball.

Choose k uniformly on [1..r], where r is the radius of the ball, choose k bits uniformly among n and flip them.

Definition at line 304 of file neighborhood.hh.

5.32.2 Constructor & Destructor Documentation

5.32.2.1 HammingBall()

```
HammingBall (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>r</i>	Radius of the ball

Definition at line 320 of file neighborhood.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/neighborhoods/neighborhood.hh`
- `lib/hnco/neighborhoods/neighborhood.cc`

5.33 HammingSphere Class Reference

Hamming sphere.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for HammingSphere:



Public Member Functions

- [HammingSphere](#) (int n, int r)
Constructor.
- void [set_radius](#) (int r)
Set radius.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.

Private Attributes

- int [_radius](#)
Radius of the sphere.

Additional Inherited Members

5.33.1 Detailed Description

Hamming sphere.

Uniformly choose r bits among n and flip them, where r is the radius of the sphere.

Definition at line 337 of file neighborhood.hh.

5.33.2 Constructor & Destructor Documentation

5.33.2.1 HammingSphere()

```
HammingSphere (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
r	Radius of the sphere

Definition at line 353 of file neighborhood.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.34 HammingSphereIterator Class Reference

Hamming sphere neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for HammingSphereIterator:



Public Member Functions

- [HammingSphereIterator](#) (int n, int r)
Constructor.
- bool [has_next](#) ()
Has next bit vector.
- const [bit_vector_t](#) & [next](#) ()
Next bit vector.

Private Attributes

- [bit_vector_t](#) [_mask](#)
Mutation mask.
- int [_radius](#)
Radius of the ball.
- int [_index](#)
Index of the next bit to shift to the right.
- int [_weight](#)
Partial Hamming weight.

Additional Inherited Members

5.34.1 Detailed Description

Hamming sphere neighborhood iterator.

This iterator enumerates mutation masks with hamming weight equal to the given radius. Suppose that `_mask` has a first (from left to right) sequence of ones of length `_weight` and ending at `_index`:

0 ... 0 1 ... 1 0 ...

Then the next mask is obtained by moving to the left the first `_weight - 1` ones and moving to the right the last one.

1 ... 1 0 ... 0 1 ...

Definition at line 91 of file neighborhood-iterator.hh.

5.34.2 Constructor & Destructor Documentation

5.34.2.1 HammingSphereIterator()

```
HammingSphereIterator (
    int n,
    int r ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>r</i>	Radius of Hamming Ball

Definition at line 113 of file neighborhood-iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.35 Hboa Class Reference

Hierarchical Bayesian Optimization Algorithm.

```
#include <hnco/algorithms/eda/hboa.hh>
```

Inheritance diagram for Hboa:



Public Member Functions

- [Hboa](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.
- void [set_population_size](#) (int n)
Set population size.

Private Attributes

- int [_population_size](#) = 10
Population size.

Additional Inherited Members

5.35.1 Detailed Description

Hierarchical Bayesian Optimization Algorithm.

Implementation of the Hierarchical Bayesian Optimization Algorithm and helper classes based on the publication: Pelikan, M. and Goldberg, D. (2006). Hierarchical bayesian optimization algorithm. In Scalable Optimization via Probabilistic Modeling, volume 33 of Studies in Computational Intelligence, pages 63–90. Springer Berlin Heidelberg.

Author: Brian W. Goldman

Integrated into HNCO by Arnaud Berny

Definition at line 44 of file hboa.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/eda/hboa.hh
- lib/hnco/algorithms/eda/hboa.cc

5.36 Hea< Moment, Herding > Class Template Reference

Herding evolutionary algorithm.

```
#include <hnco/algorithms/hea/hea.hh>
```

Inheritance diagram for Hea< Moment, Herding >:



Public Types

- enum {
LOG_ERROR, LOG_DTU, LOG_DELTA, LOG_SELECTION,
LOG_MOMENT_MATRIX, **LAST_LOG** }
- typedef std::bitset< LAST_LOG > log_flags_t
Type for log flags.

Public Member Functions

- **Hea** (int n, int population_size)
Constructor.
- void **init** ()
Initialization.

Setters

- void **set_herding** (Herding *x)
Set the herding algorithm.
- void **set_margin** (double x)
Set the moment margin.
- void **set_selection_size** (int x)
Set the selection size.
- void **set_reset_period** (int x)
Set the reset period.
- void **set_learning_rate** (double x)
Set the learning rate.
- void **set_bound_moment** (bool x)
Set the bound moment after update.
- void **set_weight** (double weight)
Set weight.
- void **set_log_flags** (const log_flags_t &lf)
Set log flags.

Private Member Functions

- void [iterate](#) ()
Single iteration.
- void [log](#) ()
Log.

Private Attributes

- Moment [_target](#)
Moment.
- Moment [_selection](#)
Moment of selected individuals.
- Moment [_uniform](#)
Uniform moment.
- [algorithm::Population](#) [_population](#)
Population.
- Herding * [_herding](#)
Herding.

Logging

- double [_error_cache](#)
Error cache.
- double [_dtu_cache](#)
Distance to uniform cache.
- double [_delta_cache](#)
Delta cache.
- double [_selection_cache](#)
Selection distance cache.
- [log_flags_t](#) [_log_flags](#)
Log flags.

Parameters

- double [_margin](#)
Moment margin.
- int [_selection_size](#) = 1
Selection size.
- int [_reset_period](#) = 0
Reset period.
- double [_learning_rate](#) = 1e-4
Learning rate.
- bool [_bound_moment](#) = false
Bound moment after update.

Additional Inherited Members

5.36.1 Detailed Description

```
template<class Moment, class Herding>
class hnco::algorithm::hea::Hea< Moment, Herding >
```

Herding evolutionary algorithm.

Reference:

Arnaud Berny. 2015. Herding Evolutionary Algorithm. In Proceedings of the Companion Publication of the 2015 Annual Conference on Genetic and Evolutionary Computation (GECCO Companion '15). ACM, New York, NY, USA, 1355–1356.

Definition at line 50 of file hea.hh.

5.36.2 Member Enumeration Documentation

5.36.2.1 anonymous enum

anonymous enum

Enumerator

LOG_ERROR	Log error.
LOG_DTU	Log distance to uniform.
LOG_DELTA	Log delta (moment increment)
LOG_SELECTION	Log the distance between the target and the selection moment.
LOG_MOMENT_MATRIX	Log the moment matrix.

Definition at line 55 of file hea.hh.

5.36.3 Constructor & Destructor Documentation

5.36.3.1 Hea()

```
Hea (
    int n,
    int population_size ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>population_size</i>	Population size

`_margin` is initialized to $1 / n$.

Definition at line 214 of file `hea.hh`.

5.36.4 Member Function Documentation

5.36.4.1 `set_reset_period()`

```
void set_reset_period (  
    int x ) [inline]
```

Set the reset period.

Parameters

<i>x</i>	Reset period
----------	--------------

$x \leq 0$ means no reset.

Definition at line 258 of file `hea.hh`.

5.36.4.2 `set_selection_size()`

```
void set_selection_size (  
    int x ) [inline]
```

Set the selection size.

The selection size is the number of selected individuals in the population.

Definition at line 250 of file `hea.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/hea/hea.hh`

5.37 Hiff Class Reference

Hierarchical if and only if.

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for Hiff:



Public Member Functions

- [Hiff](#) (int bv_size)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_depth](#)
Tree depth.

5.37.1 Detailed Description

Hierarchical if and only if.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 170 of file theory.hh.

5.37.2 Member Function Documentation

5.37.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$(i + 1) * 2^i$ where $2^i = _bv_size$

Reimplemented from [Function](#).

Definition at line 196 of file theory.hh.

5.37.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 192 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.38 HncoEvaluator Class Reference

Evaluator for HNCO functions.

```
#include <hnco/algorithms/eda/hnco-evaluator.hh>
```

Inheritance diagram for HncoEvaluator:



Public Member Functions

- [HncoEvaluator](#) ([hnco::function::Function](#) *function)
Constructor.
- float [evaluate](#) (const std::vector< bool > &x)
Evaluate a bit vector.

Private Attributes

- [hnco::function::Function](#) * [_function](#)
HNCO function.
- [hnco::bit_vector_t_bv](#)
Argument of HNCO function.

5.38.1 Detailed Description

Evaluator for HNCO functions.

Definition at line 36 of file hnco-evaluator.hh.

The documentation for this class was generated from the following file:


- lib/hnco/algorithms/eda/hnco-evaluator.hh

5.39 Hypercubeliterator Class Reference

Hypercube iterator.

```
#include <hnco/iterator.hh>
```

Inheritance diagram for Hypercubeliterator:



Public Member Functions

- [Hypercubeliterator](#) (int n)
Constructor.
- bool [has_next](#) ()
Has next bit vector.
- const [bit_vector_t](#) & [next](#) ()
Next bit vector.

Additional Inherited Members

5.39.1 Detailed Description

Hypercube iterator.

Implemented as a simple binary adder.

Definition at line 69 of file iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/iterator.hh
- lib/hnco/iterator.cc

5.40 Injection Class Reference

Injection.

```
#include <hnco/map.hh>
```

Inheritance diagram for Injection:



Public Member Functions

- [Injection](#) (const std::vector< int > &bit_positions, int output_size)
Constructor.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map
- int [get_input_size](#) ()
Get input size.
- int [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Attributes

- std::vector< int > [_bit_positions](#)
Bit positions.
- int [_output_size](#)
Output size.

5.40.1 Detailed Description

Injection.

An injection copies the bits of input x to given positions of output y.

Let $I = \{i_1, i_2, \dots, i_m\}$ be a subset of $\{1, 2, \dots, n\}$.

An injection f from F_2^m to F_2^n , where $n \geq m$, is defined by $f(x) = y$, where, for all $j \in \{1, 2, \dots, m\}$, $y_{i_j} = x_j$.

If f is a projection and g is an injection with the same bit positions then their composition $f \circ g$ is the identity.

Definition at line 397 of file map.hh.

5.40.2 Constructor & Destructor Documentation

5.40.2.1 Injection()

```
Injection (
    const std::vector< int > & bit_positions,
    int output_size )
```

Constructor.

The input size of the map is given by the size of bit_positions.

Parameters

<i>bit_positions</i>	Bit positions in the output to where input bits are copied
<i>output_size</i>	Output size

Precondition

`output_size >= bit_positions.size()`

Definition at line 144 of file map.cc.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.41 IterativeAlgorithm Class Reference

Iterative search.

```
#include <hnco/algorithms/algorithm.hh>
```

Inheritance diagram for IterativeAlgorithm:



Public Member Functions

- [IterativeAlgorithm](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.

Setters

- void [set_num_iterations](#) (int x)
Set the number of iterations.

Protected Member Functions

- virtual void [iterate](#) ()=0
Single iteration.
- virtual void [log](#) ()
Log.

Protected Attributes

- int [_iteration](#)
Current iteration.
- bool [_something_to_log](#)
Something to log.

Parameters

- int [_num_iterations](#) = 0
Number of iterations.

5.41.1 Detailed Description

Iterative search.

Definition at line 169 of file algorithm.hh.

5.41.2 Constructor & Destructor Documentation

5.41.2.1 IterativeAlgorithm()

```
IterativeAlgorithm (  
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

Definition at line 199 of file algorithm.hh.

5.41.3 Member Function Documentation

5.41.3.1 maximize()

```
void maximize ( ) [virtual]
```

Maximize.

Inside the loop:

- call [iterate\(\)](#)
- call [log\(\)](#)

Warning

If an exception such as LocalMaximum is thrown by [iterate\(\)](#), [log\(\)](#) will not be called. However, hnco reports the maximum at the end of the search.

Implements [Algorithm](#).

Definition at line 77 of file algorithm.cc.

5.41.3.2 set_num_iterations()

```
void set_num_iterations (
    int x ) [inline]
```

Set the number of iterations.

Parameters

x	Number of iterations
-----	----------------------

$x \leq 0$ means indefinite

Definition at line 223 of file algorithm.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/algorithm.hh`
- `lib/hnco/algorithms/algorithm.cc`

5.42 Iterator Class Reference

Iterator over bit vectors

```
#include <hnco/iterator.hh>
```

Inheritance diagram for Iterator:



Public Member Functions

- `Iterator` (int n)
Constructor.
- `virtual ~Iterator` ()
Destructor.
- `virtual void init` ()
Initialization.
- `virtual bool has_next` ()=0
Has next bit vector.
- `virtual const bit_vector_t & next` ()=0
Next bit vector.

Protected Attributes

- `bit_vector_t _current`
Current bit vector.
- `bool _initial_state` = true
Flag for initial state.

5.42.1 Detailed Description

Iterator over bit vectors

Definition at line 34 of file iterator.hh.

The documentation for this class was generated from the following file:


- lib/hnco/iterator.hh

5.43 Jump Class Reference

[Jump](#).

```
#include <hnco/functions/jump.hh>
```

Inheritance diagram for Jump:



Public Member Functions

- [Jump](#) (int bv_size, int gap)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_gap](#)
Gap.

5.43.1 Detailed Description

[Jump](#).

Reference:

H. Mühlenbein and T. Mahnig. 2001. Evolutionary Algorithms: From Recombination to Search Distributions. In Theoretical Aspects of Evolutionary Computing, Leila Kallel, Bart Naudts, and Alex Rogers (Eds.). Springer Berlin Heidelberg, 135–174.

Definition at line 41 of file jump.hh.

5.43.2 Member Function Documentation

5.43.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 67 of file jump.hh.

5.43.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 63 of file jump.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/jump.hh
- lib/hnco/functions/jump.cc

5.44 Labs Class Reference

Low autocorrelation binary sequences.

```
#include <hnco/functions/labs.hh>
```

Inheritance diagram for Labs:



Public Member Functions

- [Labs](#) (int n)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Additional Inherited Members

5.44.1 Detailed Description

Low autocorrelation binary sequences.

Reference:

S Mertens. 1996. Exhaustive search for low-autocorrelation binary sequences. Journal of Physics A: Mathematical and General 29, 18 (1996), L473.

<http://stacks.iop.org/0305-4470/29/i=18/a=005>

Definition at line 65 of file labs.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/labs.hh
- lib/hnco/functions/labs.cc

5.45 LabsMeritFactor Class Reference

Low autocorrelation binary sequences merit factor.

```
#include <hnco/functions/labs.hh>
```

Inheritance diagram for LabsMeritFactor:



Public Member Functions

- [LabsMeritFactor](#) (int n)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Additional Inherited Members

5.45.1 Detailed Description

Low autocorrelation binary sequences merit factor.

Reference:

S Mertens. 1996. Exhaustive search for low-autocorrelation binary sequences. Journal of Physics A: Mathematical and General 29, 18 (1996), L473.

<http://stacks.iop.org/0305-4470/29/i=18/a=005>

Definition at line 90 of file labs.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/labs.hh
- lib/hnco/functions/labs.cc

5.46 LastEvaluation Class Reference

Last evaluation.

```
#include <hnco/exception.hh>
```

Inheritance diagram for LastEvaluation:



5.46.1 Detailed Description

Last evaluation.

Definition at line 80 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.47 LeadingOnes Class Reference

Leading ones.

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for LeadingOnes:



Public Member Functions

- [LeadingOnes](#) (int bv_size)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.

5.47.1 Detailed Description

Leading ones.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 98 of file theory.hh.

5.47.2 Member Function Documentation

5.47.2.1 [get_maximum\(\)](#)

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

[_bv_size](#)

Reimplemented from [Function](#).

Definition at line 122 of file theory.hh.

5.47.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 118 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.48 LinearFunction Class Reference

Linear function.

```
#include <hnco/functions/linear-function.hh>
```

Inheritance diagram for LinearFunction:



Public Member Functions

- [LinearFunction](#) ()
Constructor.

Instance generators

- `template<class Generator >`
void [generate](#) (int n, Generator generator)
Instance generator.
- void [random](#) (int n)
Random instance.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double v, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Private Member Functions

- `template<class Archive >`
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- `std::vector< double >` [_weights](#)
Weights.

Friends

- class **boost::serialization::access**

5.48.1 Detailed Description

Linear function.

Definition at line 40 of file linear-function.hh.

5.48.2 Member Function Documentation

5.48.2.1 generate()

```
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Weight generator

Definition at line 72 of file linear-function.hh.

5.48.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 119 of file linear-function.hh.

5.48.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 124 of file linear-function.hh.

5.48.2.4 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

n	Size of bit vectors
-----	---------------------

Definition at line 86 of file linear-function.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/linear-function.hh
- lib/hnco/functions/linear-function.cc

5.49 LinearMap Class Reference

Linear map.

```
#include <hnco/map.hh>
```

Inheritance diagram for LinearMap:



Public Member Functions

- void [random](#) (int rows, int cols, bool surjective)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map
- int [get_input_size](#) ()
Get input size.
- int [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Member Functions

- `template<class Archive >`
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- `template<class Archive >`
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_matrix_t_bm](#)
Bit matrix.

Friends

- class **boost::serialization::access**

5.49.1 Detailed Description

Linear map.

A linear map f from F_2^m to F_2^n is defined by $f(x) = Ax$, where A is an $n \times m$ bit matrix.

Definition at line 194 of file map.hh.

5.49.2 Member Function Documentation

5.49.2.1 is_surjective()

```
bool is_surjective ( ) [virtual]
```

Check for surjective map.

Returns

true if `rank(_bm) == bm_num_rows(_bm)`

Reimplemented from [Map](#).

Definition at line 90 of file map.cc.

5.49.2.2 random()

```
void random (
    int rows,
    int cols,
    bool surjective )
```

Random instance.

Parameters

<i>rows</i>	Number of rows
<i>cols</i>	Number of columns
<i>surjective</i>	Flag to ensure a surjective map

Exceptions

<i>Error</i>	
--------------	--

Definition at line 61 of file map.cc.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.50 LocalMaximum Class Reference

Local maximum.

```
#include <hnco/exception.hh>
```

Inheritance diagram for LocalMaximum:



Public Member Functions

- [LocalMaximum](#) (const [point_value_t](#) &pv)
Const.

Additional Inherited Members

5.50.1 Detailed Description

Local maximum.

Definition at line 71 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.51 LogContext Class Reference

Log context.

```
#include <hnco/algorithms/log-context.hh>
```

Inheritance diagram for LogContext:



Public Member Functions

- virtual std::string `get_context` ()=0
Get context.

5.51.1 Detailed Description

Log context.

A log context gives an algorithm more information about what is going on during optimization than what can be gained through its function. In particular, its function may not be a function controller. Information is provided through a log context in the form of a string.

Definition at line 39 of file log-context.hh.

The documentation for this class was generated from the following file:


- lib/hnco/algorithms/log-context.hh

5.52 LongPath Class Reference

Long path.

```
#include <hnco/functions/long-path.hh>
```

Inheritance diagram for LongPath:



Public Member Functions

- [LongPath](#) (int bv_size, int prefix_length)

Constructor.

- double [eval](#) (const [bit_vector_t](#) &)

Evaluate a bit vector.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_prefix_length](#)
Prefix length.

5.52.1 Detailed Description

Long path.

Long paths have been introduced by Jeffrey Horn, David E. Goldberg, and Kalyanmoy Deb. Here we mostly follow the definition given by Thomas Jansen (see references below).

As an example, here is the 2-long path of dimension 4:

- 0000
- 0001
- 0011
- 0111
- 1111
- 1101
- 1100

The fitness is increasing along the path. The fitness on the complementary of the path is defined as a linear function pointing to the beginning of the path.

To help with the detection of maximum, we have dropped the constant n^2 whose sole purpose was to make the function non negative.

References:

Jeffrey Horn, David E. Goldberg, and Kalyanmoy Deb, "Long Path Problems", PPSN III, 1994.

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 62 of file long-path.hh.

5.52.2 Member Function Documentation

5.52.2.1 get_maximum()

```
double get_maximum ( ) [virtual]
```

Get the global maximum.

Let n be the bit vector size and k the prefix length which must divide n . Then the maximum is $k2^{n/k} - k + 1$.

Exceptions

Error	
-------	--

Reimplemented from [Function](#).

Definition at line 62 of file long-path.cc.

5.52.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [virtual]
```

Check for a known maximum.

Let n be the bit vector size and k the prefix length which must divide n .

We have to check that the maximum can be represented exactly as a double, that is, it must be lower or equal to 2^{53} . We are a little bit more conservative with the following test.

If $\log_2(k) + n/k \leq 53$ then returns true else returns false.

Reimplemented from [Function](#).

Definition at line 52 of file long-path.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/long-path.hh
- lib/hnco/functions/long-path.cc

5.53 Ltga Class Reference

Linkage Tree Genetic Algorithm.

```
#include <hnco/algorithms/eda/ltga.hh>
```

Inheritance diagram for Ltga:



Public Member Functions

- [Ltga](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.
- void [set_population_size](#) (int n)
Set population size.

Private Attributes

- int [_population_size](#) = 10
Population size.

Additional Inherited Members

5.53.1 Detailed Description

Linkage Tree Genetic Algorithm.

Implementation of the Linkage Tree Genetic Algorithm Designed to match the variant in the paper: "Hierarchical problem solving with the linkage tree genetic algorithm" by D. Thierens and P. A. N. Bosman

Author: Brian W. Goldman

Integrated into HNCO by Arnaud Berny

Definition at line 42 of file ltga.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/eda/ltga.hh
- lib/hnco/algorithms/eda/ltga.cc

5.54 Map Class Reference

Map

```
#include <hnco/map.hh>
```

Inheritance diagram for Map:



Public Member Functions

- virtual `~Map()`
Destructor.
- virtual void `map(const bit_vector_t &input, bit_vector_t &output)=0`
Map
- virtual int `get_input_size()`=0
Get input size.
- virtual int `get_output_size()`=0
Get output size.
- virtual bool `is_surjective()`
Check for surjective map.

5.54.1 Detailed Description

Map

Definition at line 40 of file map.hh.

5.54.2 Member Function Documentation

5.54.2.1 is_surjective()

```
virtual bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

false

Reimplemented in [TsAffineMap](#), [Projection](#), [Injection](#), [MapComposition](#), [AffineMap](#), [LinearMap](#), [Permutation](#), and [Translation](#).

Definition at line 60 of file map.hh.

The documentation for this class was generated from the following file:


- lib/hnco/map.hh

5.55 MapComposition Class Reference

Map composition.

```
#include <hnco/map.hh>
```

Inheritance diagram for MapComposition:



Public Member Functions

- [MapComposition](#) ()
Default constructor.
- [MapComposition](#) ([Map](#) *outer, [Map](#) *inner)
Constructor.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map
- int [get_input_size](#) ()
Get input size.
- int [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Attributes

- [Map](#) * [_outer](#)
Outer map.
- [Map](#) * [_inner](#)
Inner map.
- [bit_vector_t](#) [_bv](#)
Temporary bit vector.

5.55.1 Detailed Description

Map composition.

The resulting composition f is defined for all bit vector x by $f(x) = \text{outer}(\text{inner}(x))$.

Definition at line 328 of file map.hh.

5.55.2 Constructor & Destructor Documentation

5.55.2.1 MapComposition()

```
MapComposition (
    Map * outer,
    Map * inner ) [inline]
```

Constructor.

Parameters

<i>outer</i>	outer map
<i>inner</i>	inner map

Precondition

```
outer->get_input_size() == inner->get_output_size()
```

Definition at line 352 of file map.hh.

5.55.3 Member Function Documentation

5.55.3.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true if both maps are surjective

Reimplemented from [Map](#).

Definition at line 376 of file map.hh.

The documentation for this class was generated from the following file:


- lib/hnco/map.hh

5.56 MaximumReached Class Reference

Maximum reached.

```
#include <hnco/exception.hh>
```

Inheritance diagram for MaximumReached:



Public Member Functions

- [MaximumReached](#) (const [point_value_t](#) &pv)
Constructor.

Additional Inherited Members

5.56.1 Detailed Description

Maximum reached.

Definition at line 53 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.57 MaxNae3Sat Class Reference

Max not-all-equal 3SAT.

```
#include <hnco/functions/max-sat.hh>
```

Inheritance diagram for MaxNae3Sat:



Public Member Functions

- [MaxNae3Sat](#) ()
Default constructor.
- void [load](#) (std::istream &stream)
Load an instance.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Additional Inherited Members

5.57.1 Detailed Description

Max not-all-equal 3SAT.

Reference:

Christos M. Papadimitriou. 1994. Computational complexity. Addison-Wesley, Reading, Massachusetts.

Definition at line 125 of file max-sat.hh.

5.57.2 Member Function Documentation

5.57.2.1 load()

```
void load (
    std::istream & stream ) [virtual]
```

Load an instance.

Exceptions

Error

Reimplemented from [AbstractMaxSat](#).

Definition at line 282 of file max-sat.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/max-sat.hh
- lib/hnco/functions/max-sat.cc

5.58 MaxSat Class Reference

MAX-SAT.

```
#include <hnco/functions/max-sat.hh>
```


Inheritance diagram for MaxSat:



Public Member Functions

- [MaxSat](#) ()
Default constructor.
- void [random](#) (int n, int k, int c)
Random instance.
- void [random](#) (const [bit_vector_t](#) &solution, int k, int c)
Random instance with satisfiable expression.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Additional Inherited Members

5.58.1 Detailed Description

MAX-SAT.

Reference:

Christos M. Papadimitriou. 1994. Computational complexity. Addison-Wesley, Reading, Massachusetts.

Definition at line 81 of file max-sat.hh.

5.58.2 Member Function Documentation

5.58.2.1 [random\(\)](#) [1/2]

```
void random (  
    int n,  
    int k,  
    int c )
```

Random instance.

Parameters

<i>n</i>	Size of bit vectors
<i>k</i>	Number of literals per clause
<i>c</i>	Number of clauses

Definition at line 190 of file max-sat.cc.

5.58.2.2 random() [2/2]

```
void random (
    const bit_vector_t & solution,
    int k,
    int c )
```

Random instance with satisfiable expression.

Warning

Since the expression is satisfiable, the maximum of the function is equal to the number of clauses in the expression. However, this information is lost in the save and load cycle as the archive format only manages the expression itself.

Parameters

<i>solution</i>	Solution
<i>k</i>	Number of literals per clause
<i>c</i>	Number of clauses

Definition at line 218 of file max-sat.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/max-sat.hh
- lib/hnco/functions/max-sat.cc

5.59 Mimic Class Reference

Mutual information maximizing input clustering.

```
#include <hnco/algorithms/eda/mimic.hh>
```

Inheritance diagram for Mimic:



Public Member Functions

- [Mimic](#) (int n, int population_size)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_selection_size](#) (int x)
Set the selection size.

Protected Member Functions

- void [iterate](#) ()
Single iteration.
- void [sample](#) (bit_vector_t &bv)
Sample a bit vector.
- void [compute_conditional_entropy](#) (int index)
Compute conditional entropy.
- void [update_model](#) ()
Update model.

Protected Attributes

- [Population _population](#)
Population.
- [permutation_t _permutation](#)
Permutation.
- `std::array< pv_t, 2 > _parameters`
Model parameters.
- [pv_t _mean](#)
Mean of selected bit vectors.
- `std::vector< double > _entropies`
Conditional entropies.
- `std::array< std::array< int, 2 >, 2 > _table`
Contingency table.
- `double _lower_bound`
Lower bound of probability.
- `double _upper_bound`
Upper bound of probability.

Parameters

- `int _selection_size`
Selection size.

5.59.1 Detailed Description

Mutual information maximizing input clustering.

This implementation differs from the algorithm described in the reference below in that it constrains all probabilities (marginal and conditional) to stay away from the values 0 and 1 by a fixed margin equal to $1 / n$, as usually done in algorithms such as [Pbil](#) or [Umda](#).

Reference:

Jeremy S. De Bonet and Charles L. Isbell and Jr. and Paul Viola, MIMIC: Finding Optima by Estimating Probability Densities, in Advances in Neural Information Processing Systems, 1996, MIT Press.

Definition at line 54 of file `mimic.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/eda/mimic.hh`
- `lib/hnco/algorithms/eda/mimic.cc`

5.60 Mmas Class Reference

Max-min ant system.

```
#include <hnco/algorithms/pv/mmas.hh>
```

Inheritance diagram for Mmas:



Public Member Functions

- [Mmas](#) (int n)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_compare](#) (std::function< bool(double, double)> x)
Set the binary operator for comparing evaluations.
- void [set_learning_rate](#) (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [bit_vector_t_x](#)
Candidate solution.

Parameters

- `std::function< bool(double, double)> _compare = std::greater_equal<double>()`
Binary operator for comparing evaluations.
- `double _learning_rate = 1e-3`
Learning rate.

5.60.1 Detailed Description

Max-min ant system.

Reference:

Thomas Stützle and Holger H. Hoos. 2000. MAX-MIN Ant System. *Future Generation Computer Systems* 16, 8 (2000), 889–914.

Definition at line 42 of file mmas.hh.

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/pv/mmas.hh`
- `lib/hnco/algorithms/pv/mmas.cc`

5.61 Model Class Reference

[Model](#) of a Boltzmann machine.

```
#include <hnco/algorithms/bm-pbil/model.hh>
```

Public Member Functions

- [Model](#) (int n)
Constructor.
- void [init](#) ()
Initialize.
- void [reset_mc](#) ()
Reset Markov chain.
- void [gibbs_sampler](#) (size_t i)
A Gibbs sampler cycle.
- void [gibbs_sampler_synchronous](#) ()
A synchronous Gibbs sampler.
- const [bit_vector_t](#) & [get_state](#) ()
Get the state of the Gibbs sampler.
- void [update](#) (const [ModelParameters](#) &p, const [ModelParameters](#) &q, double rate)
Update parameters in the direction of p and away from q.
- double [norm_infinite](#) ()
Infinite norm of the parameters.
- double [norm_l1](#) ()
l1 norm of the parameters

Private Attributes

- [ModelParameters _model_parameters](#)
Model parameters.
- [bit_vector_t _state](#)
State of the Gibbs sampler.
- [pv_t _pv](#)
Probability vector for synchronous Gibbs sampling.

5.61.1 Detailed Description

[Model](#) of a Boltzmann machine.

Definition at line 75 of file `model.hh`.

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/bm-pbil/model.hh`
- `lib/hnco/algorithms/bm-pbil/model.cc`

5.62 ModelParameters Class Reference

Parameters of a Boltzmann machine.

```
#include <hnco/algorithms/bm-pbil/model.hh>
```

Public Member Functions

- [ModelParameters](#) (int n)
Constructor.
- void [init](#) ()
Initialize.
- void [add](#) (const [bit_vector_t](#) &x)
Add a bit_vector_t.
- void [average](#) (int count)
Compute averages.
- void [update](#) (const [ModelParameters](#) &p, const [ModelParameters](#) &q, double rate)
Update parameters in the direction of p and away from q.
- double [norm_infinite](#) ()
Infinite norm of the parameters.
- double [norm_l1](#) ()
l1 norm of the parameters

Private Attributes

- `std::vector< std::vector< double > >` [_weight](#)
Weights.
- `std::vector< double >` [_bias](#)
Bias.

Friends

- class **Model**

5.62.1 Detailed Description

Parameters of a Boltzmann machine.

Definition at line 36 of file model.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/bm-pbil/model.hh
- lib/hnco/algorithms/bm-pbil/model.cc

5.63 MuCommaLambdaEa Class Reference

(mu, lambda) EA.

```
#include <hnco/algorithms/ea/mu-comma-lambda-ea.hh>
```

Inheritance diagram for MuCommaLambdaEa:



Public Member Functions

- [MuCommaLambdaEa](#) (int n, int mu, int lambda)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [Population _parents](#)
Parents.
- [Population _offsprings](#)
Offsprings.
- [neighborhood::BernoulliProcess _mutation](#)
Mutation operator.
- `std::uniform_int_distribution< int > _select_parent`
Select parent.

Parameters

- double [_mutation_probability](#)
Mutation probability.
- bool [_allow_stay](#) = false
Allow stay.

Additional Inherited Members

5.63.1 Detailed Description

(mu, lambda) EA.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 41 of file mu-comma-lambda-ea.hh.

5.63.2 Constructor & Destructor Documentation

5.63.2.1 MuCommaLambdaEa()

```
MuCommaLambdaEa (
    int n,
    int mu,
    int lambda ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Parent population size
<i>lambda</i>	Offspring population size

Definition at line 79 of file mu-comma-lambda-ea.hh.

5.63.3 Member Function Documentation

5.63.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 102 of file mu-comma-lambda-ea.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/mu-comma-lambda-ea.hh
- lib/hnco/algorithms/ea/mu-comma-lambda-ea.cc

5.64 MultiBitFlip Class Reference

Multi bit flip.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for MultiBitFlip:



Public Member Functions

- [MultiBitFlip](#) (int n)
Constructor.

Protected Member Functions

- void [bernoulli_trials](#) (int k)
Sample a given number of bits using Bernoulli trials.
- void [reservoir_sampling](#) (int k)
Sample a given number of bits using resevoir sampling.

Additional Inherited Members

5.64.1 Detailed Description

Multi bit flip.

Definition at line 183 of file neighborhood.hh.

5.64.2 Constructor & Destructor Documentation

5.64.2.1 MultiBitFlip()

```
MultiBitFlip (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 206 of file neighborhood.hh.

5.64.3 Member Function Documentation

5.64.3.1 bernoulli_trials()

```
void bernoulli_trials (
    int k ) [protected]
```

Sample a given number of bits using Bernoulli trials.

Parameters

k	Number of bits to sample
-----	--------------------------

Definition at line 34 of file neighborhood.cc.

5.64.3.2 reservoir_sampling()

```
void reservoir_sampling (  
    int  $k$  ) [protected]
```

Sample a given number of bits using resevoir sampling.

Parameters

k	Number of bits to sample
-----	--------------------------

Definition at line 52 of file neighborhood.cc.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood.hh
- lib/hnco/neighborhoods/neighborhood.cc

5.65 MuPlusLambdaEa Class Reference

(mu+lambda) EA.

```
#include <hnco/algorithms/ea/mu-plus-lambda-ea.hh>
```

Inheritance diagram for MuPlusLambdaEa:



Public Member Functions

- [MuPlusLambdaEa](#) (int n, int mu, int lambda)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_allow_stay](#) (bool x)
Set the flag _allow_stay.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [Population _parents](#)
Parents.
- [Population _offsprings](#)
Offsprings.
- [neighborhood::BernoulliProcess _mutation](#)
Mutation operator.
- [std::uniform_int_distribution< int > _select_parent](#)
Select parent.

Parameters

- double [_mutation_probability](#)
Mutation probability.
- bool [_allow_stay](#) = false
Allow stay.

Additional Inherited Members

5.65.1 Detailed Description

(mu+lambda) EA.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 40 of file mu-plus-lambda-ea.hh.

5.65.2 Constructor & Destructor Documentation

5.65.2.1 MuPlusLambdaEa()

```
MuPlusLambdaEa (
    int n,
    int mu,
    int lambda ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
<i>mu</i>	Parent population size
<i>lambda</i>	Offspring population size

Definition at line 78 of file mu-plus-lambda-ea.hh.

5.65.3 Member Function Documentation

5.65.3.1 set_allow_stay()

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 101 of file mu-plus-lambda-ea.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/mu-plus-lambda-ea.hh
- lib/hnco/algorithms/ea/mu-plus-lambda-ea.cc

5.66 NearestNeighborIsingModel1 Class Reference

Nearest neighbor Ising model in one dimension.

```
#include <hnco/functions/ising/nearest-neighbor-ising-model-1.hh>
```

Inheritance diagram for NearestNeighborIsingModel1:



Public Member Functions

- [NearestNeighborIsingModel1](#) ()
Constructor.
- void [set_periodic_boundary_conditions](#) (bool x)
Set periodic boundary conditions.
- void [display](#) (std::ostream &stream)
Display.

Instance generators

- template<class CouplingGen , class FieldGen >
void [generate](#) (int n, CouplingGen coupling_gen, FieldGen field_gen)
Instance generator.
- void [random](#) (int n)
Random instance.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double v, const [sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Private Member Functions

- `template<class Archive >`
`void save (Archive &ar, const unsigned int version) const`
Save.
- `template<class Archive >`
`void load (Archive &ar, const unsigned int version)`
Load.
- `void resize (int n)`
Resize data structures.

Private Attributes

- `std::vector< double > _coupling`
Coupling with nearest neighbor to the right.
- `std::vector< double > _field`
External field.
- `bit_vector_t _flipped_bits`
Flipped bits.
- `bool _periodic_boundary_conditions = false`
Periodic boundary conditions.

Friends

- `class boost::serialization::access`

5.66.1 Detailed Description

Nearest neighbor Ising model in one dimension.

Its expression is of the form

$$f(x) = \sum_i J_{i,i+1} (1 - 2x_i)(1 - 2x_{i+1}) + \sum_i h_i (1 - 2x_i)$$

or equivalently

$$f(x) = \sum_i J_{i,i+1} (-1)^{x_i + x_{i+1}} + \sum_i h_i (-1)^{x_i}$$

where $J_{i,i+1}$ is the interaction between adjacent sites i and $i+1$ and h_i is the external magnetic field interacting with site i .

In the case of periodic boundary conditions, the sum $i + 1$ is mod n .

Since we are maximizing f or minimizing $-f$, the expression of f is compatible with what can be found in physics textbooks.

It should be noted that such an Ising model can be represented by a Walsh expansion of degree 2, that is [Walsh↵Expansion2](#).

Reference: https://en.wikipedia.org/wiki/Ising_model

Definition at line 65 of file nearest-neighbor-ising-model-1.hh.

5.66.2 Member Function Documentation

5.66.2.1 eval()

```
double eval (
    const bit\_vector\_t & s ) [virtual]
```

Evaluate a bit vector.

Complexity: $O(n)$

Implements [Function](#).

Definition at line 44 of file nearest-neighbor-ising-model-1.cc.

5.66.2.2 generate()

```
void generate (
    int n,
    CouplingGen coupling_gen,
    FieldGen field_gen ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>coupling_gen</i>	Coupling generator
<i>field_gen</i>	External field generator

Definition at line 126 of file nearest-neighbor-ising-model-1.hh.

5.66.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 176 of file nearest-neighbor-ising-model-1.hh.

5.66.2.4 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 142 of file nearest-neighbor-ising-model-1.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/ising/nearest-neighbor-ising-model-1.hh
- lib/hnco/functions/ising/nearest-neighbor-ising-model-1.cc

5.67 NearestNeighborIsingModel2 Class Reference

Nearest neighbor Ising model in two dimensions.

```
#include <hnco/functions/ising/nearest-neighbor-ising-model-2.hh>
```

Inheritance diagram for NearestNeighborIsingModel2:



Public Member Functions

- [NearestNeighborIsingModel2 \(\)](#)
Constructor.
- void [set_periodic_boundary_conditions](#) (bool x)
Set periodic boundary conditions.
- void [display](#) (std::ostream &stream)
Display.

Instance generators

- template<class CouplingGen , class FieldGen >
void [generate](#) (int num_rows, int num_columns, CouplingGen coupling_gen, FieldGen field_gen)
Instance generator.
- void [random](#) (int num_rows, int num_columns)
Random instance.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double v, const [sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.
- void [resize](#) (int num_rows, int num_columns)
Resize data structures.

Private Attributes

- std::vector< std::vector< double > > [_coupling_right](#)
Coupling with nearest neighbor to the right.
- std::vector< std::vector< double > > [_coupling_below](#)
Coupling with nearest neighbor below.
- std::vector< std::vector< double > > [_field](#)
External field.
- [bit_vector_t](#) [_flipped_bits](#)
Flipped bits.
- bool [_periodic_boundary_conditions](#) = false
Periodic boundary conditions.

Friends

- class **boost::serialization::access**

5.67.1 Detailed Description

Nearest neighbor Ising model in two dimensions.

We are considering a rectangular lattice in which each site has (at most) four neighbors (left, right, above, below).

The expression of the function is of the form

$$f(x) = \sum_{(i,j)} J_{ij}(1 - 2x_i)(1 - 2x_j) + \sum_i h_i(1 - 2x_i)$$

or equivalently

$$f(x) = \sum_{(i,j)} J_{ij}(-1)^{x_i+x_j} + \sum_i h_i(-1)^{x_i}$$

where the first sum is over adjacent sites (i, j), J_{ij} is the interaction between adjacent sites i and j, and h_i is the external magnetic field interacting with site i.

Since we are maximizing f or minimizing -f, the expression of f is compatible with what can be found in physics textbooks.

It should be noted that such an Ising model can be represented by a Walsh expansion of degree 2, that is [Walsh↔Expansion2](#).

Reference: https://en.wikipedia.org/wiki/Ising_model

Definition at line 67 of file nearest-neighbor-ising-model-2.hh.

5.67.2 Member Function Documentation

5.67.2.1 eval()

```
double eval (
    const bit_vector_t & s ) [virtual]
```

Evaluate a bit vector.

Complexity: O(n)

Implements [Function](#).

Definition at line 47 of file nearest-neighbor-ising-model-2.cc.

5.67.2.2 generate()

```
void generate (
    int num_rows,
    int num_columns,
    CouplingGen coupling_gen,
    FieldGen field_gen ) [inline]
```

Instance generator.

Parameters

<i>num_rows</i>	Number of rows
<i>num_columns</i>	Number of columns
<i>coupling_gen</i>	Coupling generator
<i>field_gen</i>	External field generator

Definition at line 134 of file nearest-neighbor-ising-model-2.hh.

5.67.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 194 of file nearest-neighbor-ising-model-2.hh.

5.67.2.4 random()

```
void random (
    int num_rows,
    int num_columns ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

<i>num_rows</i>	Number of rows
<i>num_columns</i>	Number of columns

Definition at line 154 of file nearest-neighbor-ising-model-2.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/ising/nearest-neighbor-ising-model-2.hh
- lib/hnco/functions/ising/nearest-neighbor-ising-model-2.cc

5.68 Needle Class Reference

[Needle](#) in a haystack.

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for Needle:



Public Member Functions

- [Needle](#) (int bv_size)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.

5.68.1 Detailed Description

[Needle](#) in a haystack.

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 134 of file theory.hh.

5.68.2 Member Function Documentation

5.68.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

1

Reimplemented from [Function](#).

Definition at line 158 of file theory.hh.

5.68.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 154 of file theory.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/theory.hh
- lib/hnco/functions/theory.cc

5.69 Negation Class Reference

Negation.

```
#include <hnco/functions/decorators/function-modifier.hh>
```

Inheritance diagram for Negation:



Public Member Functions

- [Negation](#) ([Function](#) *function)
Constructor.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped, [_bits](#))
Incremental evaluation.

Additional Inherited Members

5.69.1 Detailed Description

[Negation](#).

Use cases:

- for algorithms which minimize rather than maximize a function
- for functions one wishes to minimize
- when minimization is needed inside an algorithm

Definition at line 59 of file function-modifier.hh.

5.69.2 Member Function Documentation

5.69.2.1 `provides_incremental_evaluation()`

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 78 of file function-modifier.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-modifier.hh
- lib/hnco/functions/decorators/function-modifier.cc

5.70 Neighborhood Class Reference

[Neighborhood](#).

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for Neighborhood:



Public Member Functions

- [Neighborhood](#) (int n)
Constructor.
- virtual [~Neighborhood](#) ()
Destructor.
- virtual void [set_origin](#) (const [bit_vector_t](#) &x)
Set the origin.
- virtual const [bit_vector_t](#) &[get_origin](#) ()
Get the origin.
- virtual const [bit_vector_t](#) &[get_candidate](#) ()
Get the candidate bit vector.
- virtual const [sparse_bit_vector_t](#) &[get_flipped_bits](#) ()
Get flipped bits.
- virtual void [propose](#) ()
Propose a candidate bit vector.
- virtual void [keep](#) ()
Keep the candidate bit vector.
- virtual void [forget](#) ()
Forget the candidate bit vector.
- virtual void [mutate](#) ([bit_vector_t](#) &bv)
Mutate.
- virtual void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map.

Protected Member Functions

- virtual void `sample_bits` ()=0
Sample bits.

Protected Attributes

- `bit_vector_t _origin`
Origin of the neighborhood.
- `bit_vector_t _candidate`
candidate bit vector
- `std::uniform_int_distribution< int > _index_dist`
Index distribution.
- `sparse_bit_vector_t _flipped_bits`
Flipped bits.

5.70.1 Detailed Description

Neighborhood.

A neighborhood maintains two points, `_origin` and `_candidate`. They are initialized in the same state by `set_origin`. A `Neighborhood` class must implement the member function `sample_bits` which samples the bits to flip in `_origin` to get a `_candidate`. The following member functions take care of the modifications:

- `propose`: flip `_candidate`
- `keep`: flip `_origin`
- `forget` flip `_candidate`

After `keep` or `forget`, `_origin` and `_candidate` are in the same state again.

A `Neighborhood` class can also behave as a mutation operator through the member functions `mutate` and `map`.

Definition at line 61 of file `neighborhood.hh`.

5.70.2 Constructor & Destructor Documentation

5.70.2.1 Neighborhood()

```
Neighborhood (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

Definition at line 86 of file neighborhood.hh.

5.70.3 Member Function Documentation

5.70.3.1 map()

```
virtual void map (
    const bit\_vector\_t & input,
    bit\_vector\_t & output ) [inline], [virtual]
```

Map.

The output bit vector is a mutated version of the input bit vector.

Parameters

<i>input</i>	Input bit vector
<i>output</i>	Output bit vector

Definition at line 148 of file neighborhood.hh.

5.70.3.2 mutate()

```
virtual void mutate (
    bit\_vector\_t & bv ) [inline], [virtual]
```

Mutate.

In-place mutation of the bit vector.

Parameters

<i>bv</i>	Bit vector to mutate
-----------	----------------------

Definition at line 134 of file neighborhood.hh.

The documentation for this class was generated from the following file:


- lib/hnco/neighborhoods/neighborhood.hh

5.71 NeighborhoodIterator Class Reference

[Neighborhood](#) iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for NeighborhoodIterator:



Public Member Functions

- [NeighborhoodIterator](#) (int n)
Constructor.
- virtual void [set_origin](#) (const [bit_vector_t](#) &x)
Set origin.

Additional Inherited Members

5.71.1 Detailed Description

[Neighborhood](#) iterator.

Definition at line 35 of file neighborhood-iterator.hh.

5.71.2 Constructor & Destructor Documentation

5.71.2.1 NeighborhoodIterator()

```
NeighborhoodIterator (  
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

Definition at line 44 of file neighborhood-iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.72 NkLandscape Class Reference

NK landscape.

```
#include <hnco/functions/nk-landscape.hh>
```

Inheritance diagram for NkLandscape:



Public Member Functions

- [NkLandscape](#) ()
Default constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- void [display](#) (std::ostream &stream)
Display.

Instance generators

- template<class Generator >
void [generate](#) (int n, int k, Generator generator)
Instance generator.
- void [random](#) (int n, int k)
Random instance.

Private Member Functions

- template<class Archive >
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.
- void [random_structure](#) (int n, int k)
Random structue.

Private Attributes

- std::vector< std::vector< int > > [_neighbors](#)
Bit neighbors.
- std::vector< std::vector< double > > [_partial_functions](#)
Partial functions.

Friends

- class **boost::serialization::access**

5.72.1 Detailed Description

NK landscape.

Reference:

S. A. Kauffman. 1993. The origins of order: self-organisation and selection in evolution. Oxford University Press.

Definition at line 47 of file nk-landscape.hh.

5.72.2 Member Function Documentation

5.72.2.1 generate()

```
void generate (
    int n,
    int k,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vector
<i>k</i>	Number of neighbors of each bit
<i>generator</i>	Generator for partial function values

Definition at line 92 of file nk-landscape.hh.

5.72.2.2 random()

```
void random (
    int n,
    int k ) [inline]
```

Random instance.

Partial function values are sampled from the normal distribution.

Parameters

n	Size of bit vector
-----	--------------------

Definition at line 109 of file nk-landscape.hh.

5.72.2.3 random_structure()

```
void random_structure (
    int n,
    int k ) [private]
```

Random structue.

Parameters

n	Size of bit vector
k	Number of neighbors of each bit

Definition at line 32 of file nk-landscape.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/nk-landscape.hh
- lib/hnco/functions/nk-landscape.cc

5.73 NpsPbil Class Reference

Population-based incremental learning with negative and positive selection.

```
#include <hnco/algorithms/pv/nps-pbil.hh>
```


Inheritance diagram for NpsPbil:



Public Member Functions

- [NpsPbil](#) (int n, int population_size)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_selection_size](#) (int x)
Set the selection size.
- void [set_learning_rate](#) (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [Population _population](#)
Population.
- [pv_t _mean_best](#)
Mean of best individuals.
- [pv_t _mean_worst](#)

Mean of worst individuals.

Parameters

- int `_selection_size` = 1
Selection size.
- double `_learning_rate` = 1e-3
Learning rate.

5.73.1 Detailed Description

Population-based incremental learning with negative and positive selection.

Reference:

Arnaud Berny. 2001. Extending selection learning toward fixed-length d-ary strings. In Artificial Evolution (Lecture Notes in Computer Science), P. Collet and others (Eds.). Springer, Le Creusot.

Definition at line 42 of file nps-pbil.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/pv/nps-pbil.hh
- lib/hnco/algorithms/pv/nps-pbil.cc

5.74 OnBudgetFunction Class Reference

[CallCounter](#) with a limited number of evaluations.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for OnBudgetFunction:



Public Member Functions

- [OnBudgetFunction](#) ([Function](#) *function, int budget)
Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↔
_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Private Attributes

- int [_budget](#)
Budget.

Additional Inherited Members

5.74.1 Detailed Description

[CallCounter](#) with a limited number of evaluations.

Definition at line 317 of file function-controller.hh.

5.74.2 Member Function Documentation

5.74.2.1 [eval\(\)](#)

```
double eval (
    const bit\_vector\_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 121 of file function-controller.cc.

5.74.2.2 incremental_eval()

```
double incremental_eval (
    const bit_vector_t & x,
    double value,
    const hnco::sparse_bit_vector_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 132 of file function-controller.cc.

5.74.2.3 update()

```
void update (
    const bit_vector_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>LastEvaluation</i>	
-----------------------	--

Reimplemented from [CallCounter](#).

Definition at line 143 of file function-controller.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.75 OneMax Class Reference

[OneMax](#).

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for OneMax:



Public Member Functions

- [OneMax](#) (int bv_size)
Constructor.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double v, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.

Private Attributes

- int [_bv_size](#)
Bit vector size.

5.75.1 Detailed Description

[OneMax](#).

References:

Heinz Mühlenbein, "How genetic algorithms really work: I. mutation and hillclimbing", in Proc. 2nd Int. Conf. on Parallel Problem Solving from Nature, 1992

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 41 of file theory.hh.

5.75.2 Member Function Documentation

5.75.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 62 of file theory.hh.

5.75.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 66 of file theory.hh.

5.75.2.3 `provides_incremental_evaluation()`

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 71 of file theory.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/theory.hh`
- `lib/hnco/functions/theory.cc`

5.76 OnePlusLambdaCommaLambdaGa Class Reference

(1+(lambda, lambda)) genetic algorithm.

```
#include <hnco/algorithms/ea/one-plus-lambda-comma-lambda-ga.hh>
```

Inheritance diagram for OnePlusLambdaCommaLambdaGa:



Public Member Functions

- [OnePlusLambdaCommaLambdaGa](#) (int n, int lambda)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_crossover_bias](#) (double x)
Set the crossover bias.

Private Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [Population _offsprings](#)
Offsprings.
- `std::binomial_distribution< int > _radius_dist`
Radius distribution.
- [neighborhood::HammingSphere _mutation](#)
Mutation operator.
- [bit_vector_t _parent](#)
Parent.
- [BiasedCrossover _crossover](#)
Biased crossover.

Parameters

- `double _mutation_probability`
Mutation probability.
- `double _crossover_bias`
Crossover bias.

Additional Inherited Members

5.76.1 Detailed Description

(1+(lambda, lambda)) genetic algorithm.

Reference:

Benjamin Doerr, Carola Doerr, and Franziska Ebel. 2015. From black-box complexity to designing new genetic algorithms. Theoretical Computer Science 567 (2015), 87–104.

Definition at line 49 of file one-plus-lambda-comma-lambda-ga.hh.

5.76.2 Constructor & Destructor Documentation

5.76.2.1 OnePlusLambdaCommaLambdaGa()

```
OnePlusLambdaCommaLambdaGa (
    int n,
    int lambda ) [inline]
```

Constructor.

By default, `_mutation_probability` is set to `lambda / n` and `_crossover_bias` to `1 / lambda`.

Parameters

<i>n</i>	Size of bit vectors
<i>lambda</i>	Offspring population size

Definition at line 92 of file one-plus-lambda-comma-lambda-ga.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ea/one-plus-lambda-comma-lambda-ga.hh
- lib/hnco/algorithms/ea/one-plus-lambda-comma-lambda-ga.cc

5.77 OnePlusOneEa Class Reference

(1+1) EA.

```
#include <hnco/algorithms/ea/one-plus-one-ea.hh>
```

Inheritance diagram for OnePlusOneEa:



Public Member Functions

- [OnePlusOneEa](#) (int n)
Constructor.
- void [set_function](#) (function::Function *function)
Set function.
- void [init](#) ()
Initialization.
- void [maximize](#) ()
Maximize.
- const [point_value_t](#) & [get_solution](#) ()
Solution.

Setters

- void [set_num_iterations](#) (int x)
Set the number of iterations.
- void [set_mutation_probability](#) (double x)
Set the mutation probability.
- void [set_allow_stay](#) (bool x)
Set the flag_allow_stay.
- void [set_incremental_evaluation](#) (bool x)
Set incremental evaluation.

Private Attributes

- [neighborhood::BernoulliProcess _neighborhood](#)
Neighborhood.
- [RandomLocalSearch _rls](#)
Random local search.

Parameters

- `int _num_iterations = 0`
Number of iterations.
- `double _mutation_probability`
Mutation probability.
- `bool _allow_stay = false`
Allow stay.
- `bool _incremental_evaluation = false`
Incremental evaluation.

Additional Inherited Members

5.77.1 Detailed Description

(1+1) EA.

(1+1) EA is implemented as a [RandomLocalSearch](#) with a [BernoulliProcess](#) neighborhood and infinite patience. Thus it does derive from [IterativeAlgorithm](#). It should be noted that member [Algorithm::_solution](#) is not used by [OnePlusOneEa](#).

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 45 of file one-plus-one-ea.hh.

5.77.2 Constructor & Destructor Documentation

5.77.2.1 OnePlusOneEa()

```
OnePlusOneEa (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

`_mutation_probability` is initialized to $1 / n$.

Definition at line 80 of file `one-plus-one-ea.hh`.

5.77.3 Member Function Documentation

5.77.3.1 `set_allow_stay()`

```
void set_allow_stay (
    bool x ) [inline]
```

Set the flag `_allow_stay`.

In case no mutation occurs allow the current bit vector to stay unchanged.

Definition at line 127 of file `one-plus-one-ea.hh`.

5.77.3.2 `set_num_iterations()`

```
void set_num_iterations (
    int x ) [inline]
```

Set the number of iterations.

Parameters

<code>x</code>	Number of iterations
----------------	----------------------

$x \leq 0$ means indefinite

Definition at line 117 of file `one-plus-one-ea.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/algorithms/ea/one-plus-one-ea.hh`

5.78 ParameterLessPopulationPyramid Class Reference

Parameter-less Population Pyramid.

```
#include <hnco/algorithms/eda/p3.hh>
```

Inheritance diagram for ParameterLessPopulationPyramid:



Public Member Functions

- [ParameterLessPopulationPyramid](#) (int n)
Constructor.
- void [maximize](#) ()
Maximize.

Additional Inherited Members

5.78.1 Detailed Description

Parameter-less Population Pyramid.

Implementation of the Parameter-less Population Pyramid (P3 for short).

Author: Brian W. Goldman

Reference:

"Fast and Efficient Black Box Optimization using the Parameter-less Population Pyramid" by B. W. Goldman and W. F. Punch

Integrated into HNCO by Arnaud Berny

Definition at line 46 of file p3.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/eda/p3.hh
- lib/hnco/algorithms/eda/p3.cc

5.79 ParsedModifier Class Reference

Parsed modifier.

```
#include <hnco/functions/decorators/parsed-modifier.hh>
```

Inheritance diagram for ParsedModifier:



Public Member Functions

- **ParsedModifier** (**Function** *function, std::string expression)
Constructor.

Information about the function

- int **get_bv_size** ()
Get bit vector size.

Evaluation

- double **eval** (const **bit_vector_t** &)
Evaluate a bit vector.

Private Attributes

- **FunctionParser** **_parser**
Function parser.
- double **_values** [1]
Array of values.

Additional Inherited Members

5.79.1 Detailed Description

Parsed modifier.

Let f be the original function. Then the modified function is equivalent to $g \circ f$, where g is a real function defined by an expression $g(x)$ provided as a string.

Definition at line 39 of file `parsed-modifier.hh`.

5.79.2 Constructor & Destructor Documentation

5.79.2.1 ParsedModifier()

```
ParsedModifier (
    Function * function,
    std::string expression )
```

Constructor.

Parameters

<i>function</i>	Decorated function
<i>expression</i>	Expression to parse

Definition at line 30 of file `parsed-modifier.cc`.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/decorators/parsed-modifier.hh`
- `lib/hnco/functions/decorators/parsed-modifier.cc`

5.80 ParsedRealMultivariateFunction Class Reference

Parsed real multivariate function.

```
#include <hnco/functions/real/real-multivariate-function.hh>
```

Inheritance diagram for ParsedRealMultivariateFunction:



Public Member Functions

- [ParsedRealMultivariateFunction](#) (std::string expression)
Constructor.
- int [get_dimension](#) ()
Get the dimension of vectors.
- double [eval](#) (const std::vector< double > x)
Evaluate a real vector.

Private Attributes

- FunctionParser [_fparser](#)
Function parser.
- int [_num_variables](#) = 0
Number of variables.

5.80.1 Detailed Description

Parsed real multivariate function.

Definition at line 52 of file real-multivariate-function.hh.

5.80.2 Constructor & Destructor Documentation

5.80.2.1 ParsedRealMultivariateFunction()

```
ParsedRealMultivariateFunction (  
    std::string expression )
```

Constructor.

Parameters

<i>expression</i>	Expression to parse
-------------------	---------------------

Definition at line 34 of file real-multivariate-function.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/real/real-multivariate-function.hh
- lib/hnco/functions/real/real-multivariate-function.cc

5.81 Pbil Class Reference

Population-based incremental learning.

```
#include <hnco/algorithms/pv/pbil.hh>
```

Inheritance diagram for Pbil:



Public Member Functions

- **Pbil** (int n, int population_size)
Constructor.
- void **init** ()
Initialization.

Setters

- void **set_selection_size** (int x)
Set the selection size.
- void **set_learning_rate** (double x)
Set the learning rate.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [Population _population](#)
Population.
- [pv_t _mean](#)
Mean of selected bit vectors.

Parameters

- int [_selection_size](#) = 1
Selection size.
- double [_learning_rate](#) = 1e-3
Learning rate.

5.81.1 Detailed Description

Population-based incremental learning.

Reference:

S. Baluja and R. Caruana. 1995. Removing the genetics from the standard genetic algorithm. In Proceedings of the 12th Annual Conference on Machine Learning. 38–46.

Definition at line 41 of file pbil.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/pv/pbil.hh
- lib/hnco/algorithms/pv/pbil.cc

5.82 Permutation Class Reference

Permutation.

```
#include <hnco/map.hh>
```

Inheritance diagram for Permutation:



Public Member Functions

- void [random](#) (int n)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map
- int [get_input_size](#) ()
Get input size.
- int [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [permutation_t _permutation](#)
Permutation.

Friends

- class **boost::serialization::access**

5.82.1 Detailed Description

Permutation.

A permutation is a linear map f from F_2^n to itself defined by $f(x) = y$, where $y_i = x_{\sigma_i}$ and σ is a permutation of 0, 1, ..., n - 1.

Definition at line 133 of file map.hh.

5.82.2 Member Function Documentation

5.82.2.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 184 of file map.hh.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.83 Plateau Class Reference

[Plateau](#).

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for Plateau:



Public Member Functions

- [Plateau](#) (int bv_size)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- `int _bv_size`
Bit vector size.

5.83.1 Detailed Description

[Plateau](#).

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 244 of file theory.hh.

5.83.2 Member Function Documentation

5.83.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size + 2`

Reimplemented from [Function](#).

Definition at line 268 of file theory.hh.

5.83.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 264 of file theory.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/theory.hh`
- `lib/hnco/functions/theory.cc`

5.84 PointValueException Class Reference

Point-value exception.

```
#include <hnco/exception.hh>
```

Inheritance diagram for PointValueException:



Public Member Functions

- `PointValueException` (const `point_value_t` &pv)
Constructor.
- const `point_value_t` & `get_point_value` () const
Get point-value.

Protected Attributes

- `point_value_t _pv`
Point-value.

5.84.1 Detailed Description

Point-value exception.

Definition at line 39 of file `exception.hh`.

The documentation for this class was generated from the following file:


- `lib/hnco/exception.hh`

5.85 Population Class Reference

Population.

```
#include <hnco/algorithms/population.hh>
```

Inheritance diagram for Population:



Public Types

- typedef std::pair< int, double > [index_value_t](#)
Index-value type.

Public Member Functions

- [Population](#) (int population_size, int n)
Constructor.
- int [size](#) () const
Size.
- void [random](#) ()
Initialize the population with random bit vectors.

Get bit vectors for non const populations

- [bit_vector_t](#) & [get_bv](#) (int i)
Get a bit vector.
- [bit_vector_t](#) & [get_best_bv](#) ()
Get best bit vector.
- [bit_vector_t](#) & [get_best_bv](#) (int i)
Get best bit vector.
- [bit_vector_t](#) & [get_worst_bv](#) (int i)
Get worst bit vector.

Get bit vectors for const populations

- const [bit_vector_t](#) & [get_bv](#) (int i) const
Get a bit vector.
- const [bit_vector_t](#) & [get_best_bv](#) () const

- *Get best bit vector.*
const [bit_vector_t](#) & [get_best_bv](#) (int i) const
- *Get best bit vector.*
const [bit_vector_t](#) & [get_worst_bv](#) (int i) const
- *Get worst bit vector.*

Get sorted values

- double [get_best_value](#) (int i) const
Get best value.
- double [get_best_value](#) () const
Get best value.

Evaluation and sorting

- void [eval](#) (function::Function *function)
Evaluate the population.
- void [eval](#) (const std::vector< function::Function *> &functions)
Parallel evaluation of the population.
- void [sort](#) ()
Sort the lookup table.
- void [partial_sort](#) (int selection_size)
Partially sort the lookup table.
- void [shuffle](#) ()
Shuffle the lookup table.

Selection

- void [plus_selection](#) (const Population &offsprings)
Plus selection.
- void [plus_selection](#) (Population &offsprings)
Plus selection.
- void [comma_selection](#) (const Population &offsprings)
Comma selection.
- void [comma_selection](#) (Population &offsprings)
Comma selection.

Protected Attributes

- std::vector< [bit_vector_t](#) > [_bvs](#)
Bit vectors.
- std::vector< [index_value_t](#) > [_lookup](#)
Lookup table.
- std::function< bool(const [index_value_t](#) &, const [index_value_t](#) &)> [_compare_index_value](#)
Binary operator for comparing index-value pairs.

5.85.1 Detailed Description

[Population](#).

Definition at line 36 of file population.hh.

5.85.2 Member Function Documentation

5.85.2.1 comma_selection() [1/2]

```
void comma_selection (
    const Population & offsprings )
```

Comma selection.

Implemented with a copy.

Precondition

Offspring population must be partially sorted.

Warning

The function does not break ties randomly (workaround: shuffle offsprings).

Definition at line 112 of file population.cc.

5.85.2.2 comma_selection() [2/2]

```
void comma_selection (
    Population & offsprings )
```

Comma selection.

Implemented with a swap. Should be faster than comma_selection with a copy.

Precondition

Offspring population must be partially sorted.

Warning

The function does not break ties randomly (workaround: shuffle offsprings).
Modifies its argument.

Definition at line 126 of file population.cc.

5.85.2.3 `get_best_bv()` [1/4]

```
bit_vector_t& get_best_bv ( ) [inline]
```

Get best bit vector.

Precondition

The population must be sorted.

Definition at line 85 of file population.hh.

5.85.2.4 `get_best_bv()` [2/4]

```
bit_vector_t& get_best_bv (
    int i ) [inline]
```

Get best bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 93 of file population.hh.

5.85.2.5 `get_best_bv()` [3/4]

```
const bit_vector_t& get_best_bv ( ) const [inline]
```

Get best bit vector.

Precondition

The population must be sorted.

Definition at line 117 of file population.hh.

5.85.2.6 `get_best_bv()` [4/4]

```
const bit_vector_t& get_best_bv (
    int i ) const [inline]
```

Get best bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 125 of file population.hh.

5.85.2.7 get_best_value() [1/2]

```
double get_best_value (  
    int i ) const [inline]
```

Get best value.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 148 of file population.hh.

5.85.2.8 get_best_value() [2/2]

```
double get_best_value ( ) const [inline]
```

Get best value.

Precondition

The population must be sorted.

Definition at line 154 of file population.hh.

5.85.2.9 get_worst_bv() [1/2]

```
bit_vector_t& get_worst_bv (  
    int i ) [inline]
```

Get worst bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 101 of file population.hh.

5.85.2.10 get_worst_bv() [2/2]

```
const bit_vector_t& get_worst_bv (  
    int i ) const [inline]
```

Get worst bit vector.

Parameters

<i>i</i>	Index in the sorted population
----------	--------------------------------

Precondition

The population must be sorted.

Definition at line 133 of file population.hh.

5.85.2.11 plus_selection() [1/2]

```
void plus_selection (  
    const Population & offsprings )
```

Plus selection.

Implemented with a copy.

Precondition

Both populations must be completely sorted.

Warning

The function does not break ties randomly (workaround: shuffle parents and offsprings).

Definition at line 74 of file population.cc.

5.85.2.12 plus_selection() [2/2]

```
void plus_selection (
    Population & offsprings )
```

Plus selection.

Implemented with a swap. Should be faster than plus_selection with a copy.

Precondition

Both populations must be completely sorted.

Warning

The function does not break ties randomly (workaround: shuffle parents and offsprings).
Modifies its argument.

Definition at line 93 of file population.cc.

5.85.3 Member Data Documentation

5.85.3.1 _compare_index_value

```
std::function<bool(const index_value_t&, const index_value_t&)> _compare_index_value [protected]
```

Initial value:

```
=
    [](const index_value_t& a, const index_value_t& b) { return a.second > b.
    second; }
```

Binary operator for comparing index-value pairs.

Definition at line 57 of file population.hh.

5.85.3.2 _lookup

```
std::vector<index_value_t> _lookup [protected]
```

Lookup table.

Let p be of type std::pair<int, double>. Then p.first is the bv index in the unsorted population whereas p.second is the bv value.

Definition at line 54 of file population.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/population.hh
- lib/hnco/algorithms/population.cc

5.86 PriorNoise Class Reference

Prior noise.

```
#include <hnco/functions/decorators/prior-noise.hh>
```

Inheritance diagram for PriorNoise:



Public Member Functions

- [PriorNoise](#) ([Function](#) *fn, [neighborhood::Neighborhood](#) *nh)
Constructor.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Private Attributes

- [neighborhood::Neighborhood](#) * [_neighborhood](#)
Neighborhood.
- [bit_vector_t](#) [_noisy_bv](#)
Noisy bit vector.

Additional Inherited Members

5.86.1 Detailed Description

Prior noise.

Definition at line 36 of file prior-noise.hh.

5.86.2 Member Function Documentation

5.86.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Delegation is questionable here.

Reimplemented from [Function](#).

Definition at line 68 of file prior-noise.hh.

5.86.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Delegation is questionable here.

Reimplemented from [Function](#).

Definition at line 74 of file prior-noise.hh.

5.86.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

false

Reimplemented from [Function](#).

Definition at line 78 of file prior-noise.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/prior-noise.hh
- lib/hnco/functions/decorators/prior-noise.cc

5.87 ProgressTracker Class Reference

[ProgressTracker](#).

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for ProgressTracker:



Classes

- struct [Event](#)
Event.

Public Member Functions

- [ProgressTracker](#) ([Function](#) *function)
Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped←_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Get information

- const [Event](#) & [get_last_improvement](#) ()
Get the last improvement.
- double [get_evaluation_time](#) ()
Get evaluation time.

Setters

- void [set_log_improvement](#) (bool x)
Log improvement.
- void [set_stream](#) (std::ostream *x)
Output stream.

Protected Member Functions

- void [update_last_improvement](#) (double value)
Update last improvement.

Protected Attributes

- [Event_last_improvement](#)
Last improvement.
- [StopWatch_stop_watch](#)
Stop watch.

Parameters

- bool [_log_improvement](#) = false
Log improvement.
- std::ostream * [_stream](#) = &std::cout
Output stream.

5.87.1 Detailed Description

[ProgressTracker](#).

A [ProgressTracker](#) is a [CallCounter](#) which keeps track the last improvement, that is its value and the number of evaluations needed to reach it.

Definition at line 216 of file function-controller.hh.

5.87.2 Member Function Documentation

5.87.2.1 `get_last_improvement()`

```
const Event& get_last_improvement ( ) [inline]
```

Get the last improvement.

Warning

If `_last_improvement.num_evaluations` is zero then `_function` has never been called. The [Event](#) returned by `get_last_improvement` has therefore no meaning.

Definition at line 290 of file function-controller.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/decorators/function-controller.hh`
- `lib/hnco/functions/decorators/function-controller.cc`

5.88 ProgressTrackerContext Class Reference

Log context for ProgressTracker.

```
#include <hnco/algorithms/log-context.hh>
```

Inheritance diagram for ProgressTrackerContext:



Public Member Functions

- [ProgressTrackerContext](#) ([hnco::function::ProgressTracker](#) *pt)
Constructor.
- `std::string` [get_context](#) ()
Get context.

Private Attributes

- [hnco::function::ProgressTracker](#) * [_pt](#)
Progress tracker.

5.88.1 Detailed Description

Log context for ProgressTracker.

Definition at line 48 of file log-context.hh.

The documentation for this class was generated from the following file:


- lib/hnco/algorithms/log-context.hh

5.89 Projection Class Reference

Projection.

```
#include <hnco/map.hh>
```

Inheritance diagram for Projection:



Public Member Functions

- **Projection** (const std::vector< int > &bit_positions, int input_size)
Constructor.
- void **map** (const bit_vector_t &input, bit_vector_t &output)
Map
- int **get_input_size** ()
Get input size.
- int **get_output_size** ()
Get output size.
- bool **is_surjective** ()
Check for surjective map.

Private Attributes

- std::vector< int > **_bit_positions**
Bit positions.
- int **_input_size**
Input size.

5.89.1 Detailed Description

Projection.

The projection y of a bit vector x is x where we have dropped a given set of components.

Let $I = \{i_1, i_2, \dots, i_m\}$ be a subset of $\{1, 2, \dots, n\}$.

A projection f from F_2^n to F_2^m , where $n \geq m$, is defined by $f(x) = y$, where, for all $j \in \{1, 2, \dots, m\}$, $y_j = x_{i_j}$.

If f is a projection and g is an injection with the same bit positions then their composition $f \circ g$ is the identity.

Definition at line 453 of file map.hh.

5.89.2 Constructor & Destructor Documentation

5.89.2.1 Projection()

```
Projection (
    const std::vector< int > & bit_positions,
    int input_size )
```

Constructor.

The output size of the map is given by the size of bit_positions.

Parameters

<i>bit_positions</i>	Bit positions in the input from where output bits are copied
<i>input_size</i>	Input size

Precondition

`input_size >= bit_positions.size()`

Definition at line 164 of file map.cc.

5.89.3 Member Function Documentation

5.89.3.1 `is_surjective()`

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

`true`

Reimplemented from [Map](#).

Definition at line 491 of file map.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/map.hh`
- `lib/hnco/map.cc`

5.90 PvAlgorithm Class Reference

Probability vector algorithm.

```
#include <hnco/algorithms/pv/pv-algorithm.hh>
```

Inheritance diagram for PvAlgorithm:



Public Member Functions

- [PvAlgorithm](#) (int n)
Constructor.

Setters for logging

- void [set_log_entropy](#) (bool x)
Log entropy.
- void [set_log_num_components](#) (int x)
Set the number of probability vector components to log.
- void [set_log_pv](#) (bool x)
Log probability vector.
- void [set_something_to_log](#) ()
Set flag for something to log.

Protected Member Functions

- void [log](#) ()
Log.

Protected Attributes

- [pv_t_pv](#)
Probability vector.
- double [_lower_bound](#)
Lower bound of probability.
- double [_upper_bound](#)

Upper bound of probability.

Logging

- bool `_log_entropy` = false
Log entropy.
- bool `_log_pv` = false
Log probability vector.
- int `_log_num_components` = 5
Number of probability vector components to log.

5.90.1 Detailed Description

Probability vector algorithm.

Definition at line 35 of file pv-algorithm.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/pv/pv-algorithm.hh
- lib/hnco/algorithms/pv/pv-algorithm.cc

5.91 Qubo Class Reference

Quadratic unconstrained binary optimization.

```
#include <hnco/functions/qubo.hh>
```

Inheritance diagram for Qubo:



Public Member Functions

- `Qubo ()`
Constructor.
- void `load` (std::istream &stream)
Load an instance.
- int `get_bv_size` ()
Get bit vector size.
- double `eval` (const `bit_vector_t` &)
Evaluate a bit vector.

Private Attributes

- `std::vector< std::vector< double > > _q`
Matrix.

5.91.1 Detailed Description

Quadratic unconstrained binary optimization.

Its expression is of the form $f(x) = \sum_i Q_{ii}x_i + \sum_{i<j} Q_{ij}x_ix_j = x^T Q x$, where Q is an n x n upper-triangular matrix.

[Qubo](#) is the problem addressed by qbsolv. Here is its description as given on github:

Qbsolv, a decomposing solver, finds a minimum value of a large quadratic unconstrained binary optimization (QUBO) problem by splitting it into pieces solved either via a D-Wave system or a classical tabu solver.

There are some differences between [WalshExpansion2](#) and [Qubo](#):

- [WalshExpansion2](#) maps 0/1 variables into -1/1 variables whereas [Qubo](#) directly deals with binary variables.
- Hence, there is a separate linear part in [WalshExpansion2](#) whereas the linear part in [Qubo](#) stems from the diagonal elements of the given matrix.

qbsolv aims at minimizing quadratic functions whereas hnco algorithms aim at maximizing them. Hence [Qubo::load](#) negates all elements so that maximizing the resulting function is equivalent to minimizing the original [Qubo](#).

References:

Michael Booth, Steven P. Reinhardt, and Aidan Roy. 2017. Partitioning Optimization Problems for Hybrid Classical/Quantum Execution. Technical Report. D-Wave.

<https://github.com/dwavesystems/qbsolv>

<http://people.brunel.ac.uk/~mastjjb/jeb/orlib/bqpinfo.html>

Definition at line 74 of file qubo.hh.

5.91.2 Member Function Documentation

5.91.2.1 load()

```
void load (
    std::istream & stream )
```

Load an instance.

Exceptions

Error	
-------	--

Definition at line 35 of file qubo.cc.

5.91.3 Member Data Documentation

5.91.3.1 `_q`

```
std::vector<std::vector<double> > _q [private]
```

Matrix.

$n \times n$ upper triangular matrix.

Definition at line 83 of file qubo.hh.

The documentation for this class was generated from the following files:

- lib/hnco/functions/qubo.hh
- lib/hnco/functions/qubo.cc

5.92 Random Struct Reference

[Random](#) numbers.

```
#include <hnco/random.hh>
```

Static Public Member Functions

- static double [uniform](#) ()
Next uniformly distributed sample.
- static double [normal](#) ()
Next normally distributed sample.
- static bool [bernoulli](#) ()
Next random bit.

Static Public Attributes

- static std::mt19937 [generator](#)
Mersenne Twister 19937 generator.

5.92.1 Detailed Description

[Random](#) numbers.

Definition at line 33 of file random.hh.

The documentation for this struct was generated from the following files:


- lib/hnco/random.hh
- lib/hnco/random.cc

5.93 RandomLocalSearch Class Reference

Random local search.

```
#include <hnco/algorithms/ls/random-local-search.hh>
```

Inheritance diagram for RandomLocalSearch:



Public Member Functions

- [RandomLocalSearch](#) (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void [init](#) ()
Random initialization.
- void [init](#) (const [bit_vector_t](#) &x)
Explicit initialization.
- void [init](#) (const [bit_vector_t](#) &x, double value)
Explicit initialization.
- const [point_value_t](#) & [get_solution](#) ()
Solution.

Setters

- void [set_compare](#) (std::function< bool(double, double)> x)
Set the binary operator for comparing evaluations.
- void [set_patience](#) (int x)
Set patience.
- void [set_incremental_evaluation](#) (bool x)
Set incremental evaluation.

Protected Member Functions

- void `iterate` ()
Single iteration.
- void `iterate_full` ()
Single iteration with full evaluation.
- void `iterate_incremental` ()
Single iteration with incremental evaluation.

Protected Attributes

- `neighborhood::Neighborhood * _neighborhood`
Neighborhood.
- int `_num_failures`
Number of failure.

Parameters

- `std::function< bool(double, double)> _compare` = `std::greater_equal<double>()`
Binary operator for comparing evaluations.
- int `_patience` = 50
Patience.
- bool `_incremental_evaluation` = false
Incremental evaluation.

5.93.1 Detailed Description

Random local search.

Definition at line 39 of file random-local-search.hh.

5.93.2 Member Function Documentation

5.93.2.1 `set_patience()`

```
void set_patience (
    int x ) [inline]
```

Set patience.

Number of consecutive rejected moves before throwing a LocalMaximum exception

Parameters

<code>x</code>	Patience
----------------	----------

If $x \leq 0$ then patience is considered infinite, meaning that the algorithm will never throw any LocalMaximum exception.

Definition at line 110 of file random-local-search.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ls/random-local-search.hh
- lib/hnco/algorithms/ls/random-local-search.cc

5.94 RandomSearch Class Reference

Random search.

```
#include <hnco/algorithms/random-search.hh>
```

Inheritance diagram for RandomSearch:



Public Member Functions

- [RandomSearch](#) (int n)
Constructor.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Private Attributes

- [bit_vector_t _candidate](#)
Candidate.

Additional Inherited Members

5.94.1 Detailed Description

Random search.

Definition at line 31 of file random-search.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/random-search.hh
- lib/hnco/algorithms/random-search.cc

5.95 RandomWalk Class Reference

Random walk.

```
#include <hnco/algorithms/ls/random-walk.hh>
```

Inheritance diagram for RandomWalk:



Public Member Functions

- [RandomWalk](#) (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void [init](#) ()
Random initialization.
- void [init](#) (const [bit_vector_t](#) &x)
Explicit initialization.
- void [init](#) (const [bit_vector_t](#) &x, double value)
Explicit initialization.
- void [log](#) ()
Log.

Setters

- void [set_incremental_evaluation](#) (bool x)
Set incremental evaluation.
- void [set_log_value](#) ()
Set log.

Protected Member Functions

- void `iterate` ()
Single iteration.
- void `iterate_full` ()
Single iteration with full evaluation.
- void `iterate_incremental` ()
Single iteration with incremental evaluation.

Protected Attributes

- `neighborhood::Neighborhood * _neighborhood`
Neighborhood.
- double `_value`
Value of the last visited bit vector.

Parameters

- bool `_incremental_evaluation` = false
Incremental evaluation.

5.95.1 Detailed Description

Random walk.

The algorithm simply performs a random walk on the graph implicitly given by the neighborhood. At each iteration, the chosen neighbor does not depend on its evaluation. However optimization takes place as in random search, that is the best visited bit vector is remembered.

Definition at line 42 of file random-walk.hh.

The documentation for this class was generated from the following files:


- lib/hnco/algorithms/ls/random-walk.hh
- lib/hnco/algorithms/ls/random-walk.cc

5.96 RealMultivariateFunction Class Reference

Real multivariate function.

```
#include <hnco/functions/real/real-multivariate-function.hh>
```

Inheritance diagram for RealMultivariateFunction:



Public Member Functions

- virtual `~RealMultivariateFunction` ()
Destructor.
- virtual int `get_dimension` ()=0
Get the dimension of vectors.
- virtual double `eval` (const std::vector< double > x)=0
Evaluate a real vector.

5.96.1 Detailed Description

Real multivariate function.

Definition at line 35 of file real-multivariate-function.hh.

The documentation for this class was generated from the following file:


- lib/hnco/functions/real/real-multivariate-function.hh

5.97 RealMultivariateFunctionAdapter Class Reference

Real multivariate function adapter.

```
#include <hnco/functions/real/real-multivariate-function-adapter.hh>
```

Inheritance diagram for RealMultivariateFunctionAdapter:



Public Member Functions

- [RealMultivariateFunctionAdapter](#) ([RealRepresentation](#) *rep, [RealMultivariateFunction](#) *fn)
Constructor.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &x)
Evaluate a bit vector.

Display

- void [describe](#) (const [bit_vector_t](#) &x, std::ostream &stream)
Describe a bit vector.

Private Member Functions

- void [convert](#) (const [bit_vector_t](#) &x)
Convert a bit vector.

Private Attributes

- [RealRepresentation](#) * [_representation](#)
Real representation.
- [RealMultivariateFunction](#) * [_function](#)
Real multivariate function.
- std::vector< double > [_rv](#)
Real vector.

5.97.1 Detailed Description

Real multivariate function adapter.

Definition at line 37 of file real-multivariate-function-adapter.hh.

5.97.2 Constructor & Destructor Documentation

5.97.2.1 RealMultivariateFunctionAdapter()

```
RealMultivariateFunctionAdapter (
    RealRepresentation * rep,
    RealMultivariateFunction * fn ) [inline]
```

Constructor.

Parameters

<i>rep</i>	Real representation
<i>fn</i>	Real multivariate function

Definition at line 59 of file real-multivariate-function-adapter.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/real/real-multivariate-function-adapter.hh
- lib/hnco/functions/real/real-multivariate-function-adapter.cc

5.98 RealRepresentation Class Reference

Real representation.

```
#include <hnco/functions/real/real-representation.hh>
```

Inheritance diagram for RealRepresentation:



Public Member Functions

- virtual `~RealRepresentation()`
Destructor.
- virtual `int size()`=0
Size of the representation.
- virtual `double convert(hnco::bit_vector_t::const_iterator first, hnco::bit_vector_t::const_iterator last)`=0
Convert a bit vector range into a double.

5.98.1 Detailed Description

Real representation.

Definition at line 35 of file real-representation.hh.

The documentation for this class was generated from the following file:


- lib/hnco/functions/real/real-representation.hh

5.99 Restart Class Reference

[Restart](#).

```
#include <hnco/algorithms/decorators/restart.hh>
```

Inheritance diagram for Restart:



Public Member Functions

- [Restart](#) (int n, [Algorithm](#) *algorithm)
Constructor.
- void [init](#) ()
Initialization.
- void [set_function](#) (function::Function *function)
Set function.
- void [set_functions](#) (const std::vector< [function::Function](#) *> functions)
Set functions.

Private Member Functions

- void [iterate](#) ()
Optimize.

Private Attributes

- [Algorithm](#) * [_algorithm](#)
Algorithm.

Additional Inherited Members

5.99.1 Detailed Description

[Restart](#).

[Restart](#) an [Algorithm](#) an indefinite number of times. Should be used in conjunction with `OnBudgetFunction` or `StopOnMaximum`.

Definition at line 38 of file `restart.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/decorators/restart.hh`
- `lib/hnco/algorithms/decorators/restart.cc`

5.100 Ridge Class Reference

[Ridge](#).

```
#include <hnco/functions/theory.hh>
```

Inheritance diagram for `Ridge`:



Public Member Functions

- [Ridge](#) (int `bv_size`)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- `int _bv_size`
Bit vector size.

5.100.1 Detailed Description

[Ridge](#).

Reference:

Thomas Jansen, Analyzing Evolutionary Algorithms. Springer, 2013.

Definition at line 208 of file theory.hh.

5.100.2 Member Function Documentation

5.100.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`2 * _bv_size`

Reimplemented from [Function](#).

Definition at line 232 of file theory.hh.

5.100.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 228 of file theory.hh.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/theory.hh`
- `lib/hnco/functions/theory.cc`

5.101 SimulatedAnnealing Class Reference

Simulated annealing.

```
#include <hnco/algorithms/ls/simulated-annealing.hh>
```

Inheritance diagram for SimulatedAnnealing:



Public Member Functions

- [SimulatedAnnealing](#) (int n, [neighborhood::Neighborhood](#) *neighborhood)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_num_transitions](#) (int x)
Set the number of accepted transitions before annealing.
- void [set_num_trials](#) (int x)
Set the Number of trials.
- void [set_initial_acceptance_probability](#) (double x)
Set the initial acceptance probability.
- void [set_beta_ratio](#) (double x)
Set ratio for beta.

Private Member Functions

- void [init_beta](#) ()
Initialize beta.
- void [iterate](#) ()
Single iteration.

Private Attributes

- `neighborhood::Neighborhood * _neighborhood`
Neighborhood.
- `double _beta`
Inverse temperature.
- `double _current_value`
Current value.
- `int _transitions`
Number of accepted transitions.

Parameters

- `int _num_transitions = 50`
Number of accepted transitions before annealing.
- `int _num_trials = 100`
Number of trials.
- `double _initial_acceptance_probability = 0.6`
Initial acceptance probability.
- `double _beta_ratio = 1.2`
Ratio for beta.

Additional Inherited Members

5.101.1 Detailed Description

Simulated annealing.

Reference:

S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. 1983. Optimization by simulated annealing. *Science* 220, 4598 (May 1983), 671–680.

Definition at line 44 of file simulated-annealing.hh.

5.101.2 Member Function Documentation

5.101.2.1 `init_beta()`

```
void init_beta ( ) [private]
```

Initialize beta.

Requires (2 * `_num_trials`) evaluations. This should be taken into account when using `OnBudgetFunction`.

Definition at line 34 of file simulated-annealing.cc.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ls/simulated-annealing.hh`
- `lib/hnco/algorithms/ls/simulated-annealing.cc`

5.102 SingleBitFlip Class Reference

One bit neighborhood.

```
#include <hnco/neighborhoods/neighborhood.hh>
```

Inheritance diagram for SingleBitFlip:



Public Member Functions

- [SingleBitFlip](#) (int n)
Constructor.

Private Member Functions

- void [sample_bits](#) ()
Sample bits.

Additional Inherited Members

5.102.1 Detailed Description

One bit neighborhood.

Definition at line 160 of file neighborhood.hh.

The documentation for this class was generated from the following file:


- lib/hnco/neighborhoods/neighborhood.hh

5.103 SingleBitFlipterator Class Reference

Single bit flip neighborhood iterator.

```
#include <hnco/neighborhoods/neighborhood-iterator.hh>
```

Inheritance diagram for SingleBitFlipterator:



Public Member Functions

- [SingleBitFlipterator](#) (int n)
Constructor.
- bool [has_next](#) ()
Has next bit vector.
- const [bit_vector_t](#) & [next](#) ()
Next bit vector.

Private Attributes

- [size_t](#) [_index](#)
Index of the last flipped bit.

Additional Inherited Members

5.103.1 Detailed Description

Single bit flip neighborhood iterator.

Definition at line 53 of file neighborhood-iterator.hh.

5.103.2 Constructor & Destructor Documentation

5.103.2.1 SingleBitFlipIterator()

```
SingleBitFlipIterator (
    int n ) [inline]
```

Constructor.

Parameters

n	Size of bit vectors
-----	---------------------

Definition at line 65 of file neighborhood-iterator.hh.

The documentation for this class was generated from the following files:


- lib/hnco/neighborhoods/neighborhood-iterator.hh
- lib/hnco/neighborhoods/neighborhood-iterator.cc

5.104 SinusSummationCancellation Class Reference

Summation cancellation with sinus.

```
#include <hnco/functions/cancellation.hh>
```

Inheritance diagram for SinusSummationCancellation:



Public Member Functions

- [SinusSummationCancellation](#) (int n)
Constructor.
- double [eval](#) (const [bit_vector_t](#) &x)
Evaluate a bit vector.

Additional Inherited Members

5.104.1 Detailed Description

Summation cancellation with sinus.

Reference:

M. Sebag and M. Schoenauer. 1997. A society of hill-climbers. In Proc. IEEE Int. Conf. on Evolutionary Computation. Indianapolis, 319–324.

Definition at line 104 of file `cancellation.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/cancellation.hh`
- `lib/hnco/functions/cancellation.cc`

5.105 SixPeaks Class Reference

Six Peaks.

```
#include <hnco/functions/four-peaks.hh>
```

Inheritance diagram for SixPeaks:



Public Member Functions

- [SixPeaks](#) (int bv_size, int threshold)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_threshold](#)
Threshold.
- int [_maximum](#)
Maximum.

5.105.1 Detailed Description

Six Peaks.

It is defined by

$$f(x) = \max\{\text{head}(x, 0) + \text{tail}(x, 1) + \text{head}(x, 1) + \text{tail}(x, 0)\} + R(x)$$

where:

- $\text{head}(x, 0)$ is the length of the longest prefix of x made of zeros;
- $\text{head}(x, 1)$ is the length of the longest prefix of x made of ones;
- $\text{tail}(x, 0)$ is the length of the longest suffix of x made of zeros;
- $\text{tail}(x, 1)$ is the length of the longest suffix of x made of ones;
- $R(x)$ is the reward;
- $R(x) = n$ if $(\text{head}(x, 0) > t \text{ and } \text{tail}(x, 1) > t) \text{ or } (\text{head}(x, 1) > t \text{ and } \text{tail}(x, 0) > t)$;
- $R(x) = 0$ otherwise;
- the threshold t is a parameter of the function.

This function has six maxima, of which exactly four are global ones.

For example, if $n = 6$ and $t = 1$:

- $f(111111) = 6$ (local maximum)
- $f(111110) = 5$
- $f(111100) = 10$ (global maximum)

Reference:

J. S. De Bonet, C. L. Isbell, and P. Viola. 1996. MIMIC: finding optima by estimating probability densities. In *Advances in Neural Information Processing Systems*. Vol. 9. MIT Press, Denver.

Definition at line 128 of file four-peaks.hh.

5.105.2 Member Function Documentation

5.105.2.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

$2 * \text{_bv_size} - \text{_threshold} - 1$

Reimplemented from [Function](#).

Definition at line 159 of file four-peaks.hh.

5.105.2.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 155 of file four-peaks.hh.

The documentation for this class was generated from the following files:

- lib/hnco/functions/four-peaks.hh
- lib/hnco/functions/four-peaks.cc

5.106 SpinHerdling Class Reference

Herdling with spin variables.

```
#include <hnco/algorithms/hea/spin-herding.hh>
```

Public Types

- enum { [SAMPLE_GREEDY](#), [SAMPLE_RLS](#), [SAMPLE_DLS](#), **LAST_SAMPLE** }

Public Member Functions

- [SpinHerd](#)(int n)
Constructor.
- void [init](#)()
Initialization.
- void [sample](#)(const [SpinMoment](#) &target, [bit_vector_t](#) &x)
Sample a bit vector.
- double [error](#)(const [SpinMoment](#) &target)
Compute the error.

Getters

- const [SpinMoment](#) & [get_delta](#)()
Get delta.

Setters

- void [set_randomize_bit_order](#)(bool x)
Randomize bit order.
- void [set_sampling_method](#)(int x)
Set the sampling method.
- void [set_num_seq_updates](#)(int x)
Set the number of sequential updates per sample.
- void [set_weight](#)(double x)
Set the weight of second order moments.

Protected Member Functions

- void [compute_delta](#)(const [SpinMoment](#) &target)
Compute delta.
- void [sample_greedy](#)([bit_vector_t](#) &x)
Sample by means of a greedy algorithm.
- double [q_derivative](#)(const [bit_vector_t](#) &x, int i)
Derivative of q.
- double [q_variation](#)(const [bit_vector_t](#) &x, int i)
Variation of q.
- void [sample_rls](#)([bit_vector_t](#) &x)
Sample by means of random local search.
- void [sample_dls](#)([bit_vector_t](#) &x)
Sample by means of deterministic local search.

Protected Attributes

- [SpinMoment_delta](#)
Delta moment.
- [SpinMoment_count](#)
Counter moment.
- [permutation_t_permutation](#)
Permutation.
- `std::uniform_int_distribution< int > _choose_bit`
Choose bit.
- `int _time`
Time.

Parameters

- `bool _randomize_bit_order = false`
Randomize bit order.
- `int _sampling_method = SAMPLE_GREEDY`
Sampling method.
- `int _num_seq_updates`
Number of sequential updates per sample.
- `double _weight = 1`
Weight of second order moments.

5.106.1 Detailed Description

Herding with spin variables.

By spin variables, we mean variables taking values 1 or -1, instead of 0 or 1 in the case of binary variables.

Definition at line 37 of file spin-herding.hh.

5.106.2 Member Enumeration Documentation

5.106.2.1 anonymous enum

anonymous enum

Enumerator

<code>SAMPLE_GREEDY</code>	Greedy algorithm.
<code>SAMPLE_RLS</code>	Random local search.
<code>SAMPLE_DLS</code>	Deterministic local search.

Definition at line 97 of file spin-herding.hh.

5.106.3 Constructor & Destructor Documentation

5.106.3.1 SpinHerdin()

```
SpinHerdin (
    int n ) [inline]
```

Constructor.

Parameters

<i>n</i>	Size of bit vectors
----------	---------------------

`_num_seq_updates` is initialized to `n`.

Definition at line 116 of file `spin-herding.hh`.

5.106.4 Member Function Documentation

5.106.4.1 q_variation()

```
double q_variation (
    const bit_vector_t & x,
    int i ) [protected]
```

Variation of `q`.

Up to a positive multiplicative constant. Only the sign of the variation matters to local search.

Definition at line 162 of file `spin-herding.cc`.

The documentation for this class was generated from the following files:

- `lib/hnco/algorithms/hea/spin-herding.hh`
- `lib/hnco/algorithms/hea/spin-herding.cc`

5.107 SpinMoment Struct Reference

Moment for spin variables.

```
#include <hnco/algorithms/hea/spin-moment.hh>
```

Public Member Functions

- [SpinMoment](#) (int n)
Constructor.
- void [uniform](#) ()
Set the moment to that of the uniform distribution.
- void [init](#) ()
Initialize accumulators.
- void [add](#) (const [bit_vector_t](#) &x)
Update accumulators.
- void [average](#) (int count)
Compute average.
- void [update](#) (const [SpinMoment](#) &p, double rate)
Update moment.
- void [bound](#) (double margin)
Bound moment.
- double [distance](#) (const [SpinMoment](#) &p) const
Distance.
- double [norm_2](#) () const
Compute the norm 2.
- double [diameter](#) () const
Compute the diameter.
- size_t [size](#) () const
Size.
- void [display](#) (std::ostream &stream)
Display.

Public Attributes

- std::vector< double > [_first](#)
First moment.
- std::vector< std::vector< double > > [_second](#)
Second moment.
- double [_weight](#) = 1
Weight of second order moments.

5.107.1 Detailed Description

Moment for spin variables.

Definition at line 38 of file spin-moment.hh.

5.107.2 Member Data Documentation

5.107.2.1 `_second`

```
std::vector<std::vector<double> > _second
```

Second moment.

This is a lower triangular matrix with only zeros on the diagonal. Only entries `_second[i][j]` with $j < i$ are considered.

Definition at line 50 of file `spin-moment.hh`.

The documentation for this struct was generated from the following files:


- `lib/hnco/algorithms/hea/spin-moment.hh`
- `lib/hnco/algorithms/hea/spin-moment.cc`

5.108 SteepestAscentHillClimbing Class Reference

Steepest ascent hill climbing.

```
#include <hnco/algorithms/ls/steepest-ascent-hill-climbing.hh>
```

Inheritance diagram for `SteepestAscentHillClimbing`:



Public Member Functions

- `SteepestAscentHillClimbing` (int n, `neighborhood::NeighborhoodIterator` *neighborhood)
Constructor.
- void `init` ()
Random initialization.
- void `init` (const `bit_vector_t` &x)
Explicit initialization.
- void `init` (const `bit_vector_t` &x, double value)
Explicit initialization.

Protected Member Functions

- void `iterate()`
Single iteration.

Protected Attributes

- `std::vector< bit_vector_t > _candidates`
Potential candidate.
- `neighborhood::NeighborhoodIterator * _neighborhood`
Neighborhood.

5.108.1 Detailed Description

Steepest ascent hill climbing.

Definition at line 39 of file `steepest-ascent-hill-climbing.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ls/steepest-ascent-hill-climbing.hh`
- `lib/hnco/algorithms/ls/steepest-ascent-hill-climbing.cc`

5.109 StopOnMaximum Class Reference

Stop on maximum.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for StopOnMaximum:



Public Member Functions

- [StopOnMaximum](#) ([Function](#) *function)

Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↔
_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Additional Inherited Members

5.109.1 Detailed Description

Stop on maximum.

The member function `eval` throws an exception `MaximumReached` when its argument maximizes the decorated function.

Warning

The maximum is detected using the equality operator hence the result should be taken with care in case of non integer (floating point) function values.

Definition at line 90 of file `function-controller.hh`.

5.109.2 Constructor & Destructor Documentation

5.109.2.1 StopOnMaximum()

```
StopOnMaximum (
    Function * function ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
-----------------	--------------------

Precondition

function->[has_known_maximum\(\)](#)

Definition at line 98 of file function-controller.hh.

5.109.3 Member Function Documentation

5.109.3.1 eval()

```
double eval (
    const bit\_vector\_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>MaximumReached</i>	
-----------------------	--

Implements [Function](#).

Definition at line 31 of file function-controller.cc.

5.109.3.2 incremental_eval()

```
double incremental_eval (
    const bit\_vector\_t & x,
    double value,
    const hnco::sparse\_bit\_vector\_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>MaximumReached</i>	
-----------------------	--

Reimplemented from [Function](#).

Definition at line 43 of file function-controller.cc.

5.109.3.3 update()

```
void update (
    const bit\_vector\_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>MaximumReached</i>	
-----------------------	--

Reimplemented from [Function](#).

Definition at line 55 of file function-controller.cc.

The documentation for this class was generated from the following files:


- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.110 StopOnTarget Class Reference

Stop on target.

```
#include <hnco/functions/decorators/function-controller.hh>
```

Inheritance diagram for StopOnTarget:



Public Member Functions

- [StopOnTarget](#) ([Function](#) *function, double target)
Constructor.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double value, const [hnco::sparse_bit_vector_t](#) &flipped↵_bits)
Incremental evaluation.
- void [update](#) (const [bit_vector_t](#) &x, double value)
Update after a safe evaluation.

Private Attributes

- double [_target](#)
Target.

Additional Inherited Members

5.110.1 Detailed Description

Stop on target.

The member function eval throws an exception TargetReached when the value of its decorated function reaches a given target.

Warning

The target is detected using the greater or equal operator hence the result should be taken with care in case of non integer (floating point) function values.

Definition at line 134 of file function-controller.hh.

5.110.2 Constructor & Destructor Documentation

5.110.2.1 StopOnTarget()

```
StopOnTarget (
    Function * function,
    double target ) [inline]
```

Constructor.

Parameters

<i>function</i>	Decorated function
<i>target</i>	Target

Definition at line 147 of file function-controller.hh.

5.110.3 Member Function Documentation

5.110.3.1 eval()

```
double eval (
    const bit_vector_t & x ) [virtual]
```

Evaluate a bit vector.

Exceptions

<i>TargetReached</i>	
----------------------	--

Implements [Function](#).

Definition at line 66 of file function-controller.cc.

5.110.3.2 incremental_eval()

```
double incremental_eval (
    const bit_vector_t & x,
    double value,
    const hnco::sparse_bit_vector_t & flipped_bits ) [virtual]
```

Incremental evaluation.

Exceptions

<i>TargetReached</i>	
----------------------	--

Reimplemented from [Function](#).

Definition at line 76 of file function-controller.cc.

5.110.3.3 update()

```
void update (
    const bit\_vector\_t & x,
    double value ) [virtual]
```

Update after a safe evaluation.

Exceptions

<i>TargetReached</i>	
----------------------	--

Reimplemented from [Function](#).

Definition at line 86 of file function-controller.cc.

The documentation for this class was generated from the following files:

- lib/hnco/functions/decorators/function-controller.hh
- lib/hnco/functions/decorators/function-controller.cc

5.111 Stopwatch Class Reference

Stop watch.

```
#include <hnco/stop-watch.hh>
```

Public Member Functions

- void [start](#) ()
Start.
- void [stop](#) ()
Stop.
- double [get_total_time](#) ()
Get total time.

Private Attributes

- double [_total_time](#) = 0
Total time.
- clock_t [_start](#)
Start time.

5.111.1 Detailed Description

Stop watch.

Definition at line 31 of file stop-watch.hh.

The documentation for this class was generated from the following file:


- lib/hnco/stop-watch.hh

5.112 SummationCancellation Class Reference

Summation cancellation.

```
#include <hnco/functions/cancellation.hh>
```

Inheritance diagram for SummationCancellation:



Public Member Functions

- [SummationCancellation](#) (int n)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &x)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Protected Member Functions

- void `convert` (const `bit_vector_t` &x)
Convert a bit vector into a real vector.

Protected Attributes

- int `_bv_size`
Bit vector size.
- `std::vector< double > _buffer`
Buffer.

5.112.1 Detailed Description

Summation cancellation.

Encoding of a signed integer:

- bit 0: sign
- bits 1 to 8: two's complement representation

Reference:

S. Baluja and S. Davies. 1997. Using optimal dependency-trees for combinatorial optimization: learning the structure of the search space. Technical Report CMU- CS-97-107. Carnegie-Mellon University.

Definition at line 48 of file `cancellation.hh`.

5.112.2 Constructor & Destructor Documentation

5.112.2.1 SummationCancellation()

```
SummationCancellation (
    int n ) [inline]
```

Constructor.

The bit vector size `n` must be a multiple of 9. The size of `_buffer` is then `n / 9`.

Parameters

<code>n</code>	Size of the bit vector
----------------	------------------------

Definition at line 71 of file `cancellation.hh`.

5.112.3 Member Function Documentation

5.112.3.1 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 87 of file `cancellation.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/cancellation.hh`
- `lib/hnco/functions/cancellation.cc`

5.113 TargetReached Class Reference

target reached

```
#include <hnco/exception.hh>
```

Inheritance diagram for TargetReached:



Public Member Functions

- [TargetReached](#) (const [point_value_t](#) &pv)
Constructor.

Additional Inherited Members

5.113.1 Detailed Description

target reached

Definition at line 62 of file exception.hh.

The documentation for this class was generated from the following file:


- lib/hnco/exception.hh

5.114 TournamentSelection Class Reference

[Population](#) with tournament selection.

```
#include <hnco/algorithms/ea/tournament-selection.hh>
```

Inheritance diagram for TournamentSelection:



Public Member Functions

- [TournamentSelection](#) (int population_size, int n)
Constructor.
- const [bit_vector_t](#) & [select](#) ()
Selection.

Setters

- void [set_tournament_size](#) (int x)
Set the tournament size.

Private Attributes

- `std::uniform_int_distribution< int > _choose_individual`
Random index.

Parameters

- `int _tournament_size = 10`
Tournament size.

Additional Inherited Members

5.114.1 Detailed Description

[Population](#) with tournament selection.

Definition at line 34 of file tournament-selection.hh.

5.114.2 Member Function Documentation

5.114.2.1 `select()`

```
const bit\_vector\_t & select ( )
```

Selection.

The selection only requires that the population be evaluated, not necessarily sorted.

Precondition

The population must be evaluated.

Definition at line 33 of file tournament-selection.cc.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ea/tournament-selection.hh`
- `lib/hnco/algorithms/ea/tournament-selection.cc`

5.115 Translation Class Reference

Translation.

```
#include <hnco/map.hh>
```

Inheritance diagram for Translation:



Public Member Functions

- void [random](#) (int n)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map
- int [get_input_size](#) ()
Get input size.
- int [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [bit_vector_t_bv](#)
Translation vector

Friends

- class **boost::serialization::access**

5.115.1 Detailed Description

Translation.

A translation is an affine map f from $F_2 y^n$ to itself defined by $f(x) = x + b$, where b is an n -dimensional bit vector.

Definition at line 71 of file map.hh.

5.115.2 Member Function Documentation

5.115.2.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 122 of file map.hh.

The documentation for this class was generated from the following files:

- lib/hnco/map.hh
- lib/hnco/map.cc

5.116 Transvection Struct Reference

Transvection.

```
#include <hnco/transvection.hh>
```

Public Member Functions

- `template<class Archive >`
`void save (Archive &ar, const unsigned int version) const`
Save.
- `template<class Archive >`
`void load (Archive &ar, const unsigned int version)`
Load.
- `bool is_valid () const`
Check validity.
- `bool is_valid (int n) const`
Check validity.
- `void display (std::ostream &stream) const`
Display transvection.
- `void random (int n)`
Sample a random transvection.
- `void random_non_commuting (int n, const Transvection &a)`
Sample a random transvection.
- `void multiply (bit_vector_t &x) const`
Multiply a bit vector from the left.
- `void multiply (bit_matrix_t &M) const`
Multiply a bit matrix from the left.
- `void multiply_right (bit_matrix_t &M) const`
Multiply a bit matrix from the right.

Public Attributes

- `int row_index`
Row index.
- `int column_index`
Column index.

5.116.1 Detailed Description

Transvection.

We only consider transvections defined by matrices $\tau_{ij} = I_n + B_{ij}$, where I_n is the $n \times n$ identity matrix and B_{ij} is the matrix whose (i, j) entry is 1 and other entries are zero. Such a matrix is also sometimes called a shear matrix.

Transvections generate invertible matrices over the finite field F_2 .

Definition at line 53 of file transvection.hh.

5.116.2 Member Function Documentation

5.116.2.1 is_valid()

```
bool is_valid (
    int n ) const
```

Check validity.

Parameters

n	Dimension
-----	-----------

Definition at line 46 of file transvection.cc.

5.116.2.2 multiply() [1/2]

```
void multiply (  
    bit_vector_t & x ) const
```

Multiply a bit vector from the left.

Parameters

x	Bit vector
-----	------------

Precondition

```
is_valid()  
is_valid(x.size())
```

Warning

This function modifies the given bit vector.

Definition at line 102 of file transvection.cc.

5.116.2.3 multiply() [2/2]

```
void multiply (  
    bit_matrix_t & M ) const
```

Multiply a bit matrix from the left.

Parameters

M	Bit matrix
-----	------------

Precondition

```
is_valid()  
is_valid(bm_num_rows(M))
```


Warning

This function modifies the given bit vector.

Definition at line 114 of file transvection.cc.

5.116.2.4 multiply_right()

```
void multiply_right (
    bit_matrix_t & M ) const
```

Multiply a bit matrix from the right.

Parameters

M	Bit matrix
-----	------------

Precondition

```
is_valid()
is_valid(bm_num_rows(M))
```

Warning

This function modifies the given bit vector.

Definition at line 124 of file transvection.cc.

5.116.2.5 random()

```
void random (
    int n )
```

Sample a random transvection.

Parameters

n	Dimension
-----	-----------

Precondition

$n > 1$

Definition at line 59 of file transvection.cc.

5.116.2.6 random_non_commuting()

```
void random_non_commuting (
    int n,
    const Transvection & a )
```

Sample a random transvection.

This member function ensures that the sampled transvection does not commute with some given one.

Parameters

<i>n</i>	Dimension
<i>a</i>	Given transvection

Precondition

$n > 1$

Definition at line 75 of file transvection.cc.

The documentation for this struct was generated from the following files:


- lib/hnco/transvection.hh
- lib/hnco/transvection.cc

5.117 Trap Class Reference

[Trap](#).

```
#include <hnco/functions/trap.hh>
```

Inheritance diagram for Trap:



Public Member Functions

- [Trap](#) (int *bv_size*, int *num_traps*)
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- double [get_maximum](#) ()
Get the global maximum.

Private Attributes

- int [_bv_size](#)
Bit vector size.
- int [_num_traps](#)
Number of traps.
- int [_trap_size](#)
Trap size.

5.117.1 Detailed Description

[Trap](#).

Reference:

Kalyanmoy Deb and David E. Goldberg. 1993. Analyzing Deception in Trap Functions. In Foundations of Genetic Algorithms 2, L. Darrell Whitley (Ed.). Morgan Kaufmann, San Mateo, CA, 93–108.

Definition at line 43 of file trap.hh.

5.117.2 Constructor & Destructor Documentation

5.117.2.1 [Trap\(\)](#)

```
Trap (
    int bv_size,
    int num_traps ) [inline]
```

Constructor.

Parameters

<i>bv_size</i>	Bit vector size
<i>num_traps</i>	Number of traps

Warning

`bv_size` must be a multiple of `num_traps`

Definition at line 64 of file `trap.hh`.

5.117.3 Member Function Documentation

5.117.3.1 `get_maximum()`

```
double get_maximum ( ) [inline], [virtual]
```

Get the global maximum.

Returns

`_bv_size`

Reimplemented from [Function](#).

Definition at line 88 of file `trap.hh`.

5.117.3.2 `has_known_maximum()`

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

`true`

Reimplemented from [Function](#).

Definition at line 84 of file `trap.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/functions/trap.hh`
- `lib/hnco/functions/trap.cc`

5.118 TsAffineMap Class Reference

Transvection sequence affine map.

```
#include <hnco/map.hh>
```

Inheritance diagram for TsAffineMap:



Public Types

- enum [SamplingMode](#) {
[Unconstrained](#), [CommutingTransvections](#), [UniqueSource](#), [UniqueDestination](#),
[DisjointTransvections](#), [NonCommutingTransvections](#) }
Sampling mode.

Public Member Functions

- void [random](#) (int n, int t, [SamplingMode](#) mode)
Random instance.
- void [map](#) (const [bit_vector_t](#) &input, [bit_vector_t](#) &output)
Map
- int [get_input_size](#) ()
Get input size.
- int [get_output_size](#) ()
Get output size.
- bool [is_surjective](#) ()
Check for surjective map.

Private Member Functions

- template<class Archive >
void [save](#) (Archive &ar, const unsigned int version) const
Save.
- template<class Archive >
void [load](#) (Archive &ar, const unsigned int version)
Load.

Private Attributes

- [transvection_sequence_t_ts](#)
Transvection sequence
- [bit_vector_t_bv](#)
Translation vector

Friends

- class **boost::serialization::access**

5.118.1 Detailed Description

Transvection sequence affine map.

An affine map f from F_2^m to F_2^n is defined by $f(x) = Ax + b$, where A is an $n \times m$ bit matrix and b is an n -dimensional bit vector.

In [TsAffineMap](#), A is a finite product of transvections represented by a [transvection_sequence_t](#).

Definition at line 505 of file map.hh.

5.118.2 Member Enumeration Documentation

5.118.2.1 SamplingMode

enum [SamplingMode](#)

Sampling mode.

Enumerator

Unconstrained	Unconstrained.
CommutingTransvections	Commuting transvections.
UniqueSource	Transvection sequence with unique source
UniqueDestination	Transvection sequence with unique destination
DisjointTransvections	Disjoint transvections.
NonCommutingTransvections	Non commuting transvections.

Definition at line 542 of file map.hh.

5.118.3 Member Function Documentation

5.118.3.1 is_surjective()

```
bool is_surjective ( ) [inline], [virtual]
```

Check for surjective map.

Returns

true

Reimplemented from [Map](#).

Definition at line 585 of file map.hh.

5.118.3.2 random()

```
void random (
    int n,
    int t,
    SamplingMode mode )
```

Random instance.

Parameters

<i>n</i>	Dimension
<i>t</i>	Length of sequence of transvections
<i>mode</i>	Sampling mode

Definition at line 185 of file map.cc.

The documentation for this class was generated from the following files:


- lib/hnco/map.hh
- lib/hnco/map.cc

5.119 Umda Class Reference

Univariate marginal distribution algorithm.

```
#include <hnco/algorithms/pv/umda.hh>
```

Inheritance diagram for Umda:



Public Member Functions

- [Umda](#) (int n, int population_size)
Constructor.
- void [init](#) ()
Initialization.

Setters

- void [set_selection_size](#) (int x)
Set the selection size.

Protected Member Functions

- void [iterate](#) ()
Single iteration.

Protected Attributes

- [Population _population](#)
Population.

Parameters

- int [_selection_size](#) = 1
Selection size.

5.119.1 Detailed Description

Univariate marginal distribution algorithm.

Reference:

H. Mühlenbein. 1997. The equation for response to selection and its use for prediction. *Evolutionary Computation* 5, 3 (1997), 303–346.

Definition at line 41 of file `umda.hh`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/pv/umda.hh`
- `lib/hnco/algorithms/pv/umda.cc`

5.120 UniformCrossover Class Reference

Uniform crossover.

```
#include <hnco/algorithms/ea/crossover.hh>
```

Inheritance diagram for `UniformCrossover`:



Public Member Functions

- `void breed` (const `bit_vector_t` &parent1, const `bit_vector_t` &parent2, `bit_vector_t` &offspring)
Breed.

5.120.1 Detailed Description

Uniform crossover.

Definition at line 56 of file `crossover.hh`.

5.120.2 Member Function Documentation

5.120.2.1 `breed()`

```
void breed (
    const bit\_vector\_t & parent1,
    const bit\_vector\_t & parent2,
    bit\_vector\_t & offspring ) [virtual]
```

Breed.

The offspring is the uniform crossover of two parents.

Parameters

<i>parent1</i>	First parent
<i>parent2</i>	Second parent
<i>offspring</i>	Offspring

Implements [Crossover](#).

Definition at line 30 of file `crossover.cc`.

The documentation for this class was generated from the following files:


- `lib/hnco/algorithms/ea/crossover.hh`
- `lib/hnco/algorithms/ea/crossover.cc`

5.121 WalshExpansion Class Reference

Walsh expansion.

```
#include <hnco/functions/walsh/walsh-expansion.hh>
```

Inheritance diagram for WalshExpansion:



Public Member Functions

- [WalshExpansion](#) ()
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- void [display](#) (std::ostream &stream)
Display.
- void [set_terms](#) (const std::vector< [Function::WalshTransformTerm](#) > terms)
Set terms.

Instance generators

- template<class Generator >
void [generate](#) (int n, int num_features, Generator generator)
Instance generator.
- void [random](#) (int n, int num_features)
Random instance.

Private Member Functions

- template<class Archive >
void [serialize](#) (Archive &ar, const unsigned int version)
Save.

Private Attributes

- std::vector< [Function::WalshTransformTerm](#) > [_terms](#)
Terms.

Friends

- class [boost::serialization::access](#)

5.121.1 Detailed Description

Walsh expansion.

Its expression is of the form

$$f(x) = \sum_u a_u (-1)^{x \cdot u}$$

where the sum is over a subset of $\{0, 1\}^n$ and $x \cdot u = \sum_i x_i u_i \text{ mod } 2$. The real numbers a_u are the coefficients of the expansion and the bit vectors u are its feature vectors.

Definition at line 53 of file walsh-expansion.hh.

5.121.2 Member Function Documentation

5.121.2.1 generate()

```
void generate (
    int n,
    int num_features,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>num_features</i>	Number of feature vectors
<i>generator</i>	Coefficient generator

Definition at line 87 of file walsh-expansion.hh.

5.121.2.2 random()

```
void random (
    int n,
    int num_features ) [inline]
```

Random instance.

The coefficients are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
<i>num_features</i>	Number of feature vectors

Definition at line 113 of file walsh-expansion.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/walsh/walsh-expansion.hh
- lib/hnco/functions/walsh/walsh-expansion.cc

5.122 WalshExpansion1 Class Reference

Walsh expansion of degree 1.

```
#include <hnco/functions/walsh/walsh-expansion-1.hh>
```

Inheritance diagram for WalshExpansion1:



Public Member Functions

- [WalshExpansion1](#) ()

Constructor.

Instance generators

- `template<class Generator >`
void [generate](#) (int n, Generator generator)
Instance generator.
- void [random](#) (int n)
Random instance.

Evaluation

- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.
- double [incremental_eval](#) (const [bit_vector_t](#) &x, double v, const [hnco::sparse_bit_vector_t](#) &flipped_bits)
Incremental evaluation.

Information about the function

- int [get_bv_size](#) ()
Get bit vector size.
- double [get_maximum](#) ()
Get the global maximum.
- bool [has_known_maximum](#) ()
Check for a known maximum.
- bool [provides_incremental_evaluation](#) ()
Check whether the function provides incremental evaluation.

Private Member Functions

- `template<class Archive >`
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.

Private Attributes

- `std::vector< double > _linear`
Linear part.

Friends

- class `boost::serialization::access`

5.122.1 Detailed Description

Walsh expansion of degree 1.

Its expression is of the form

$$f(x) = \sum_i a_i (1 - 2x_i)$$

or equivalently

$$f(x) = \sum_i a_i (-1)^{x_i}$$

Definition at line 50 of file walsh-expansion-1.hh.

5.122.2 Member Function Documentation

5.122.2.1 generate()

```
void generate (
    int n,
    Generator generator ) [inline]
```

Instance generator.

Parameters

<i>n</i>	Size of bit vectors
<i>generator</i>	Weight generator

Definition at line 83 of file walsh-expansion-1.hh.

5.122.2.2 has_known_maximum()

```
bool has_known_maximum ( ) [inline], [virtual]
```

Check for a known maximum.

Returns

true

Reimplemented from [Function](#).

Definition at line 130 of file walsh-expansion-1.hh.

5.122.2.3 provides_incremental_evaluation()

```
bool provides_incremental_evaluation ( ) [inline], [virtual]
```

Check whether the function provides incremental evaluation.

Returns

true

Reimplemented from [Function](#).

Definition at line 135 of file walsh-expansion-1.hh.

5.122.2.4 random()

```
void random (
    int n ) [inline]
```

Random instance.

The weights are sampled from the normal distribution.

Parameters

n	Size of bit vectors
-----	---------------------

Definition at line 97 of file walsh-expansion-1.hh.

The documentation for this class was generated from the following files:


- lib/hnco/functions/walsh/walsh-expansion-1.hh
- lib/hnco/functions/walsh/walsh-expansion-1.cc

5.123 WalshExpansion2 Class Reference

Walsh expansion of degree 2.

```
#include <hnco/functions/walsh/walsh-expansion-2.hh>
```

Inheritance diagram for WalshExpansion2:



Public Member Functions

- [WalshExpansion2](#) ()
Constructor.
- int [get_bv_size](#) ()
Get bit vector size.
- double [eval](#) (const [bit_vector_t](#) &)
Evaluate a bit vector.

Instance generators

- `template<class LinearGen , class QuadraticGen >`
void [generate](#) (int n, LinearGen linear_gen, QuadraticGen quadratic_gen)
Instance generators.
- void [random](#) (int n)
Instance generator.
- void [generate_ising1_long_range](#) (int n, double alpha)
Generate one dimensional Ising model with long range interactions.
- void [generate_ising1_long_range_periodic](#) (int n, double alpha)
Generate one dimensional Ising model with long range interactions and periodic boundary conditions.

Private Member Functions

- `template<class Archive >`
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.
- void [resize](#) (int n)
Resize data structures.

Private Attributes

- `std::vector< double >` [_linear](#)
Linear part.
- `std::vector< std::vector< double > >` [_quadratic](#)
Quadratic part.

Friends

- class **boost::serialization::access**

5.123.1 Detailed Description

Walsh expansion of degree 2.

Its expression is of the form

$$f(x) = \sum_i a_i (1 - 2x_i) + \sum_{i < j} a_{ij} (1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_i a_i (-1)^{x_i} + \sum_{i < j} a_{ij} (-1)^{x_i + x_j}$$

Definition at line 50 of file walsh-expansion-2.hh.

5.123.2 Member Function Documentation

5.123.2.1 generate()

```
void generate (
    int n,
    LinearGen linear_gen,
    QuadraticGen quadratic_gen ) [inline]
```

Instance generators.

Parameters

<i>n</i>	Size of bit vectors
<i>linear_gen</i>	Generator for the linear part
<i>quadratic_gen</i>	Generator for the quadratic part

Definition at line 95 of file walsh-expansion-2.hh.

5.123.2.2 generate_ising1_long_range()

```
void generate_ising1_long_range (
    int n,
    double alpha )
```

Generate one dimensional Ising model with long range interactions.

Similar to a Dyson-Ising model except for the finite, instead of infinite, linear chain of spins.

Its expression is of the form

$$f(x) = \sum_{ij} J(d_{ij})(1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_{ij} J(d_{ij})(-1)^{x_i+x_j}$$

where $J(d_{ij})$ is the interaction between sites i and j , $d_{ij} = |i - j|$, and $J(n) = n^{-\alpha}$.

Since we are maximizing f or minimizing $-f$, the expression of f is compatible with what can be found in physics textbooks.

Parameters

n	Size of bit vectors
$alpha$	Exponential decay parameter

Definition at line 82 of file walsh-expansion-2.cc.

5.123.2.3 generate_ising1_long_range_periodic()

```
void generate_ising1_long_range_periodic (
    int n,
    double alpha )
```

Generate one dimensional Ising model with long range interactions and periodic boundary conditions.

Similar to a Dyson-Ising model except for the finite, instead of infinite, linear chain of spins.

Its expression is of the form

$$f(x) = \sum_{ij} J(d_{ij})(1 - 2x_i)(1 - 2x_j)$$

or equivalently

$$f(x) = \sum_{ij} J(d_{ij})(-1)^{x_i+x_j}$$

where $J(d_{ij})$ is the interaction between sites i and j , $d_{ij} = \min\{|i - j|, n - |i - j|\}$, and $J(n) = n^{-\alpha}$.

Since we are maximizing f or minimizing $-f$, the expression of f is compatible with what can be found in physics textbooks.

Parameters

n	Size of bit vectors
$alpha$	Exponential decay parameter

Definition at line 103 of file walsh-expansion-2.cc.

5.123.2.4 random()

```
void random (
    int n ) [inline]
```

Instance generator.

The weights are sampled from the normal distribution.

Parameters

<i>n</i>	Size of bit vector
----------	--------------------

Definition at line 117 of file walsh-expansion-2.hh.

5.123.3 Member Data Documentation

5.123.3.1 _quadratic

```
std::vector<std::vector<double> > _quadratic [private]
```

Quadratic part.

Represented as a lower triangular matrix (without its diagonal).

Definition at line 73 of file walsh-expansion-2.hh.

The documentation for this class was generated from the following files:

- lib/hnco/functions/walsh/walsh-expansion-2.hh
- lib/hnco/functions/walsh/walsh-expansion-2.cc

5.124 Function::WalshTransformTerm Struct Reference

Walsh transform term.

```
#include <hnco/functions/function.hh>
```

Public Member Functions

- template<class Archive >
void [serialize](#) (Archive &ar, const unsigned int version)
Serialize.

Public Attributes

- `std::vector< bool > feature`
Feature.
- `double coefficient`
Coefficient.

5.124.1 Detailed Description

Walsh transform term.

Definition at line 46 of file `function.hh`.

5.124.2 Member Data Documentation

5.124.2.1 feature

```
std::vector<bool> feature
```

Feature.

Implemented with a vector `bool` instead of a `bit_vector_t` to reduce the memory consumption.

Definition at line 53 of file `function.hh`.

The documentation for this struct was generated from the following file:

- `lib/hnco/functions/function.hh`

Index

- `_compare_index_value`
 - `hnco::algorithm::Population`, 198
 - `_expression`
 - `hnco::function::AbstractMaxSat`, 41
 - `_functions`
 - `hnco::algorithm::Algorithm`, 48
 - `_lookup`
 - `hnco::algorithm::Population`, 198
 - `_q`
 - `hnco::function::Qubo`, 210
 - `_quadratic`
 - `hnco::function::WalshExpansion2`, 269
 - `_second`
 - `hnco::algorithm::hea::SpinMoment`, 233
- `AbstractLabs`, 39
- `AbstractMaxSat`, 40
- `AdditiveGaussianNoise`, 42
- `AffineMap`, 43
- `Algorithm`, 45
- `bernoulli_trials`
 - `hnco::neighborhood::MultiBitFlip`, 149
- `BernoulliProcess`, 48
 - `hnco::neighborhood::BernoulliProcess`, 49, 50
- `BiasedCrossover`, 51
- `bit_t`
 - `hnco`, 18
- `BitHerding`, 52
- `BitMoment`, 54
- `bm_add_columns`
 - `hnco`, 19
- `bm_add_rows`
 - `hnco`, 19
- `bm_identity`
 - `hnco`, 20
- `bm_invert`
 - `hnco`, 20
- `bm_multiply`
 - `hnco`, 21
- `bm_rank`
 - `hnco`, 21
- `bm_row_echelon_form`
 - `hnco`, 21
- `bm_solve`
 - `hnco`, 22
- `bm_solve_upper_triangular`
 - `hnco`, 22
- `BmPbil`, 55
- `breed`
 - `hnco::algorithm::BiasedCrossover`, 51
 - `hnco::algorithm::Crossover`, 66
 - `hnco::algorithm::UniformCrossover`, 260
- `bv_from_vector_bool`
 - `hnco`, 23
- `bv_to_vector_bool`
 - `hnco`, 23
- `Cache`, 59
 - `hnco::function::Cache`, 60
- `CallCounter`, 61
- `comma_selection`
 - `hnco::algorithm::Population`, 194
- `CompactGa`, 62
- `CompleteSearch`, 64
- `compute_walsh_transform`
 - `hnco::function::Function`, 83
- `Crossover`, 65
- `DeceptiveJump`, 66
- `DyadicRealRepresentation`, 68
 - `hnco::function::real::DyadicRealRepresentation`, 69
- `EqualProducts`, 70
- `Error`, 73
- `eval`
 - `hnco::function::NearestNeighborIsingModel1`, 155
 - `hnco::function::NearestNeighborIsingModel2`, 158
 - `hnco::function::OnBudgetFunction`, 173
 - `hnco::function::StopOnMaximum`, 237
 - `hnco::function::StopOnTarget`, 240
- `Exception`, 74
- `Factorization`, 75
 - `hnco::function::Factorization`, 76
- `feature`
 - `hnco::function::Function::WalshTransformTerm`, 270
- `FirstAscentHillClimbing`, 77
- `FourPeaks`, 79
- `Function`, 81
- `Function::WalshTransformTerm`, 269
- `FunctionController`, 86
- `FunctionDecorator`, 87
- `FunctionMapComposition`, 88
 - `hnco::function::FunctionMapComposition`, 89
- `FunctionModifier`, 91
- `FunctionPlugin`, 92
 - `hnco::function::FunctionPlugin`, 93
- `generate`

- hnco::function::EqualProducts, 71
 - hnco::function::LinearFunction, 124
 - hnco::function::NearestNeighborIsingModel1, 155
 - hnco::function::NearestNeighborIsingModel2, 158
 - hnco::function::NkLandscape, 169
 - hnco::function::WalshExpansion, 262
 - hnco::function::WalshExpansion1, 264
 - hnco::function::WalshExpansion2, 267
- generate_ising1_long_range
 - hnco::function::WalshExpansion2, 267
- generate_ising1_long_range_periodic
 - hnco::function::WalshExpansion2, 268
- GeneticAlgorithm, 93
 - hnco::algorithm::GeneticAlgorithm, 95
- get_best_bv
 - hnco::algorithm::Population, 194, 195
- get_best_value
 - hnco::algorithm::Population, 196
- get_last_improvement
 - hnco::function::ProgressTracker, 203
- get_maximum
 - hnco::function::DeceptiveJump, 67
 - hnco::function::FourPeaks, 80
 - hnco::function::Function, 84
 - hnco::function::FunctionMapComposition, 90
 - hnco::function::Hiff, 108
 - hnco::function::Jump, 117
 - hnco::function::LeadingOnes, 121
 - hnco::function::LongPath, 130
 - hnco::function::Needle, 161
 - hnco::function::OneMax, 176
 - hnco::function::Plateau, 190
 - hnco::function::PriorNoise, 200
 - hnco::function::Ridge, 221
 - hnco::function::SixPeaks, 229
 - hnco::function::Trap, 254
- get_worst_bv
 - hnco::algorithm::Population, 196, 197
- HammingBall, 96
 - hnco::neighborhood::HammingBall, 97
- HammingSphere, 98
 - hnco::neighborhood::HammingSphere, 99
- HammingSphereIterator, 99
 - hnco::neighborhood::HammingSphereIterator, 101
- has_known_maximum
 - hnco::function::DeceptiveJump, 67
 - hnco::function::FourPeaks, 80
 - hnco::function::FunctionMapComposition, 90
 - hnco::function::Hiff, 108
 - hnco::function::Jump, 117
 - hnco::function::LeadingOnes, 121
 - hnco::function::LinearFunction, 124
 - hnco::function::LongPath, 131
 - hnco::function::Needle, 161
 - hnco::function::OneMax, 176
 - hnco::function::Plateau, 190
 - hnco::function::PriorNoise, 200
 - hnco::function::Ridge, 221
 - hnco::function::SixPeaks, 229
 - hnco::function::SummationCancellation, 244
 - hnco::function::Trap, 254
 - hnco::function::WalshExpansion1, 264
- Hboa, 101
- Hea
 - hnco::algorithm::hea::Hea, 105
- Hea< Moment, Herding >, 102
- Hiff, 107
- hnco, 13
 - bit_t, 18
 - bm_add_columns, 19
 - bm_add_rows, 19
 - bm_identity, 20
 - bm_invert, 20
 - bm_multiply, 21
 - bm_rank, 21
 - bm_row_echelon_form, 21
 - bm_solve, 22
 - bm_solve_upper_triangular, 22
 - bv_from_vector_bool, 23
 - bv_to_vector_bool, 23
 - is_in_range, 24
 - perm_identity, 25
 - perm_random, 25
 - sbm_multiply, 25
 - sparse_bit_matrix_t, 18
 - sparse_bit_vector_t, 18
 - transvection_sequence_t, 18
 - ts_is_valid, 25, 26
 - ts_multiply, 26
 - ts_random, 27
 - ts_random_commuting, 27
 - ts_random_disjoint, 28
 - ts_random_non_commuting, 28
 - ts_random_unique_destination, 29
 - ts_random_unique_source, 29
- hnco::AffineMap
 - is_surjective, 44
 - random, 44
- hnco::Injection
 - Injection, 111
- hnco::LinearMap
 - is_surjective, 126
 - random, 126
- hnco::Map
 - is_surjective, 134
- hnco::MapComposition
 - is_surjective, 136
 - MapComposition, 135
- hnco::Permutation
 - is_surjective, 188
- hnco::Projection
 - is_surjective, 206
 - Projection, 205
- hnco::Translation
 - is_surjective, 248
- hnco::Transvection

- is_valid, [249](#)
- multiply, [250](#)
- multiply_right, [251](#)
- random, [251](#)
- random_non_commuting, [251](#)
- hnco::TsAffineMap
 - is_surjective, [256](#)
 - random, [257](#)
 - SamplingMode, [256](#)
- hnco::algorithm, [30](#)
- hnco::algorithm::Algorithm
 - _functions, [48](#)
 - set_solution, [47](#)
 - update_solution, [47](#)
- hnco::algorithm::BiasedCrossover
 - breed, [51](#)
- hnco::algorithm::Crossover
 - breed, [66](#)
- hnco::algorithm::GeneticAlgorithm
 - GeneticAlgorithm, [95](#)
 - set_allow_stay, [96](#)
- hnco::algorithm::IterativeAlgorithm
 - IterativeAlgorithm, [113](#)
 - maximize, [114](#)
 - set_num_iterations, [114](#)
- hnco::algorithm::MuCommaLambdaEa
 - MuCommaLambdaEa, [147](#)
 - set_allow_stay, [148](#)
- hnco::algorithm::MuPlusLambdaEa
 - MuPlusLambdaEa, [152](#)
 - set_allow_stay, [152](#)
- hnco::algorithm::OnePlusLambdaCommaLambdaGa
 - OnePlusLambdaCommaLambdaGa, [178](#)
- hnco::algorithm::OnePlusOneEa
 - OnePlusOneEa, [180](#)
 - set_allow_stay, [181](#)
 - set_num_iterations, [181](#)
- hnco::algorithm::Population
 - _compare_index_value, [198](#)
 - _lookup, [198](#)
 - comma_selection, [194](#)
 - get_best_bv, [194](#), [195](#)
 - get_best_value, [196](#)
 - get_worst_bv, [196](#), [197](#)
 - plus_selection, [197](#)
- hnco::algorithm::RandomLocalSearch
 - set_patience, [212](#)
- hnco::algorithm::SimulatedAnnealing
 - init_beta, [223](#)
- hnco::algorithm::TournamentSelection
 - select, [246](#)
- hnco::algorithm::UniformCrossover
 - breed, [260](#)
- hnco::algorithm::bm_pbil, [33](#)
- hnco::algorithm::bm_pbil::BmPbil
 - set_selection_size, [58](#)
- hnco::algorithm::hea, [33](#)
- hnco::algorithm::hea::Hea
 - Hea, [105](#)
 - set_reset_period, [106](#)
 - set_selection_size, [106](#)
- hnco::algorithm::hea::SpinHerdin
 - q_variation, [232](#)
 - SpinHerdin, [232](#)
- hnco::algorithm::hea::SpinMoment
 - _second, [233](#)
- hnco::exception, [33](#)
- hnco::function, [34](#)
- hnco::function::AbstractMaxSat
 - _expression, [41](#)
 - load, [41](#)
- hnco::function::Cache
 - Cache, [60](#)
 - provides_incremental_evaluation, [60](#)
- hnco::function::DeceptiveJump
 - get_maximum, [67](#)
 - has_known_maximum, [67](#)
- hnco::function::EqualProducts
 - generate, [71](#)
 - random, [71](#)
- hnco::function::Factorization
 - Factorization, [76](#)
 - load, [77](#)
- hnco::function::FourPeaks
 - get_maximum, [80](#)
 - has_known_maximum, [80](#)
- hnco::function::Function
 - compute_walsh_transform, [83](#)
 - get_maximum, [84](#)
 - incremental_eval, [84](#)
 - provides_incremental_evaluation, [85](#)
 - safe_eval, [85](#)
- hnco::function::Function::WalshTransformTerm
 - feature, [270](#)
- hnco::function::FunctionController
 - provides_incremental_evaluation, [87](#)
- hnco::function::FunctionMapComposition
 - FunctionMapComposition, [89](#)
 - get_maximum, [90](#)
 - has_known_maximum, [90](#)
- hnco::function::FunctionPlugin
 - FunctionPlugin, [93](#)
- hnco::function::Hiff
 - get_maximum, [108](#)
 - has_known_maximum, [108](#)
- hnco::function::Jump
 - get_maximum, [117](#)
 - has_known_maximum, [117](#)
- hnco::function::LeadingOnes
 - get_maximum, [121](#)
 - has_known_maximum, [121](#)
- hnco::function::LinearFunction
 - generate, [124](#)
 - has_known_maximum, [124](#)
 - provides_incremental_evaluation, [124](#)
 - random, [124](#)

hnco::function::LongPath
 get_maximum, 130
 has_known_maximum, 131
 hnco::function::MaxNae3Sat
 load, 138
 hnco::function::MaxSat
 random, 139, 140
 hnco::function::NearestNeighborIsingModel1
 eval, 155
 generate, 155
 provides_incremental_evaluation, 155
 random, 155
 hnco::function::NearestNeighborIsingModel2
 eval, 158
 generate, 158
 provides_incremental_evaluation, 159
 random, 159
 hnco::function::Needle
 get_maximum, 161
 has_known_maximum, 161
 hnco::function::Negation
 provides_incremental_evaluation, 163
 hnco::function::NkLandscape
 generate, 169
 random, 170
 random_structure, 170
 hnco::function::OnBudgetFunction
 eval, 173
 incremental_eval, 173
 update, 174
 hnco::function::OneMax
 get_maximum, 176
 has_known_maximum, 176
 provides_incremental_evaluation, 176
 hnco::function::ParsedModifier
 ParsedModifier, 184
 hnco::function::Plateau
 get_maximum, 190
 has_known_maximum, 190
 hnco::function::PriorNoise
 get_maximum, 200
 has_known_maximum, 200
 provides_incremental_evaluation, 200
 hnco::function::ProgressTracker
 get_last_improvement, 203
 hnco::function::Qubo
 _q, 210
 load, 209
 hnco::function::Ridge
 get_maximum, 221
 has_known_maximum, 221
 hnco::function::SixPeaks
 get_maximum, 229
 has_known_maximum, 229
 hnco::function::StopOnMaximum
 eval, 237
 incremental_eval, 237
 StopOnMaximum, 236
 update, 237
 hnco::function::StopOnTarget
 eval, 240
 incremental_eval, 240
 StopOnTarget, 239
 update, 240
 hnco::function::SummationCancellation
 has_known_maximum, 244
 SummationCancellation, 243
 hnco::function::Trap
 get_maximum, 254
 has_known_maximum, 254
 Trap, 253
 hnco::function::WalshExpansion
 generate, 262
 random, 262
 hnco::function::WalshExpansion1
 generate, 264
 has_known_maximum, 264
 provides_incremental_evaluation, 265
 random, 265
 hnco::function::WalshExpansion2
 _quadratic, 269
 generate, 267
 generate_ising1_long_range, 267
 generate_ising1_long_range_periodic, 268
 random, 269
 hnco::function::real, 36
 hnco::function::real::DyadicRealRepresentation
 DyadicRealRepresentation, 69
 hnco::function::real::ParsedRealMultivariateFunction
 ParsedRealMultivariateFunction, 185
 hnco::function::real::RealMultivariateFunctionAdapter
 RealMultivariateFunctionAdapter, 217
 hnco::neighborhood, 37
 hnco::neighborhood::BernoulliProcess
 BernoulliProcess, 49, 50
 set_allow_stay, 50
 set_probability, 50
 hnco::neighborhood::HammingBall
 HammingBall, 97
 hnco::neighborhood::HammingSphere
 HammingSphere, 99
 hnco::neighborhood::HammingSphereIterator
 HammingSphereIterator, 101
 hnco::neighborhood::MultiBitFlip
 bernoulli_trials, 149
 MultiBitFlip, 149
 reservoir_sampling, 150
 hnco::neighborhood::Neighborhood
 map, 166
 mutate, 166
 Neighborhood, 165
 hnco::neighborhood::NeighborhoodIterator
 NeighborhoodIterator, 167
 hnco::neighborhood::SingleBitFlipIterator
 SingleBitFlipIterator, 226
 hnco::random, 38

- HncoEvaluator, [108](#)
- Hypercubeliterator, [109](#)
- incremental_eval
 - hnco::function::Function, [84](#)
 - hnco::function::OnBudgetFunction, [173](#)
 - hnco::function::StopOnMaximum, [237](#)
 - hnco::function::StopOnTarget, [240](#)
- init_beta
 - hnco::algorithm::SimulatedAnnealing, [223](#)
- Injection, [110](#)
 - hnco::Injection, [111](#)
- is_in_range
 - hnco, [24](#)
- is_surjective
 - hnco::AffineMap, [44](#)
 - hnco::LinearMap, [126](#)
 - hnco::Map, [134](#)
 - hnco::MapComposition, [136](#)
 - hnco::Permutation, [188](#)
 - hnco::Projection, [206](#)
 - hnco::Translation, [248](#)
 - hnco::TsAffineMap, [256](#)
- is_valid
 - hnco::Transvection, [249](#)
- IterativeAlgorithm, [112](#)
 - hnco::algorithm::IterativeAlgorithm, [113](#)
- Iterator, [115](#)
- Jump, [116](#)
- Labs, [118](#)
- LabsMeritFactor, [119](#)
- LastEvaluation, [120](#)
- LeadingOnes, [120](#)
- LinearFunction, [122](#)
- LinearMap, [125](#)
- load
 - hnco::function::AbstractMaxSat, [41](#)
 - hnco::function::Factorization, [77](#)
 - hnco::function::MaxNae3Sat, [138](#)
 - hnco::function::Qubo, [209](#)
- LocalMaximum, [127](#)
- LogContext, [128](#)
- LongPath, [129](#)
- Ltga, [131](#)
- Map, [132](#)
- map
 - hnco::neighborhood::Neighborhood, [166](#)
- MapComposition, [134](#)
 - hnco::MapComposition, [135](#)
- MaxNae3Sat, [137](#)
- MaxSat, [138](#)
- maximize
 - hnco::algorithm::IterativeAlgorithm, [114](#)
- MaximumReached, [136](#)
- Mimic, [140](#)
- Mmas, [143](#)
- Model, [144](#)
- ModelParameters, [145](#)
- MuCommaLambdaEa, [146](#)
 - hnco::algorithm::MuCommaLambdaEa, [147](#)
- MuPlusLambdaEa, [150](#)
 - hnco::algorithm::MuPlusLambdaEa, [152](#)
- MultiBitFlip, [148](#)
 - hnco::neighborhood::MultiBitFlip, [149](#)
- multiply
 - hnco::Transvection, [250](#)
- multiply_right
 - hnco::Transvection, [251](#)
- mutate
 - hnco::neighborhood::Neighborhood, [166](#)
- NearestNeighborIsingModel1, [153](#)
- NearestNeighborIsingModel2, [156](#)
- Needle, [160](#)
- Negation, [162](#)
- Neighborhood, [164](#)
 - hnco::neighborhood::Neighborhood, [165](#)
- NeighborhoodIterator, [167](#)
 - hnco::neighborhood::NeighborhoodIterator, [167](#)
- NkLandscape, [168](#)
- NpsPbil, [170](#)
- OnBudgetFunction, [172](#)
- OneMax, [174](#)
- OnePlusLambdaCommaLambdaGa, [177](#)
 - hnco::algorithm::OnePlusLambdaCommaLambdaGa, [178](#)
- OnePlusOneEa, [179](#)
 - hnco::algorithm::OnePlusOneEa, [180](#)
- ParameterLessPopulationPyramid, [181](#)
- ParsedModifier, [183](#)
 - hnco::function::ParsedModifier, [184](#)
- ParsedRealMultivariateFunction, [184](#)
 - hnco::function::real::ParsedRealMultivariateFunction, [185](#)
- Pbil, [186](#)
- perm_identity
 - hnco, [25](#)
- perm_random
 - hnco, [25](#)
- Permutation, [187](#)
- Plateau, [189](#)
- plus_selection
 - hnco::algorithm::Population, [197](#)
- PointValueException, [191](#)
- Population, [192](#)
- PriorNoise, [199](#)
- ProgressTracker, [201](#)
- ProgressTracker::Event, [74](#)
- ProgressTrackerContext, [203](#)
- Projection, [204](#)
 - hnco::Projection, [205](#)
- provides_incremental_evaluation
 - hnco::function::Cache, [60](#)

- hnco::function::Function, 85
- hnco::function::FunctionController, 87
- hnco::function::LinearFunction, 124
- hnco::function::NearestNeighborIsingModel1, 155
- hnco::function::NearestNeighborIsingModel2, 159
- hnco::function::Negation, 163
- hnco::function::OneMax, 176
- hnco::function::PriorNoise, 200
- hnco::function::WalshExpansion1, 265
- PvAlgorithm, 206
- q_variation
 - hnco::algorithm::hea::SpinHerd, 232
- Qubo, 208
- Random, 210
- random
 - hnco::AffineMap, 44
 - hnco::LinearMap, 126
 - hnco::Transvection, 251
 - hnco::TsAffineMap, 257
 - hnco::function::EqualProducts, 71
 - hnco::function::LinearFunction, 124
 - hnco::function::MaxSat, 139, 140
 - hnco::function::NearestNeighborIsingModel1, 155
 - hnco::function::NearestNeighborIsingModel2, 159
 - hnco::function::NkLandscape, 170
 - hnco::function::WalshExpansion, 262
 - hnco::function::WalshExpansion1, 265
 - hnco::function::WalshExpansion2, 269
- random_non_commuting
 - hnco::Transvection, 251
- random_structure
 - hnco::function::NkLandscape, 170
- RandomLocalSearch, 211
- RandomSearch, 213
- RandomWalk, 214
- RealMultivariateFunction, 215
- RealMultivariateFunctionAdapter, 216
 - hnco::function::real::RealMultivariateFunctionAdapter, 217
- RealRepresentation, 218
- reservoir_sampling
 - hnco::neighborhood::MultiBitFlip, 150
- Restart, 219
- Ridge, 220
- safe_eval
 - hnco::function::Function, 85
- SamplingMode
 - hnco::TsAffineMap, 256
- sbm_multiply
 - hnco, 25
- select
 - hnco::algorithm::TournamentSelection, 246
- set_allow_stay
 - hnco::algorithm::GeneticAlgorithm, 96
 - hnco::algorithm::MuCommaLambdaEa, 148
 - hnco::algorithm::MuPlusLambdaEa, 152
 - hnco::algorithm::OnePlusOneEa, 181
 - hnco::neighborhood::BernoulliProcess, 50
- set_num_iterations
 - hnco::algorithm::IterativeAlgorithm, 114
 - hnco::algorithm::OnePlusOneEa, 181
- set_patience
 - hnco::algorithm::RandomLocalSearch, 212
- set_probability
 - hnco::neighborhood::BernoulliProcess, 50
- set_reset_period
 - hnco::algorithm::hea::Hea, 106
- set_selection_size
 - hnco::algorithm::bm_pbil::BmPbil, 58
 - hnco::algorithm::hea::Hea, 106
- set_solution
 - hnco::algorithm::Algorithm, 47
- SimulatedAnnealing, 222
- SingleBitFlip, 224
- SingleBitFlipIterator, 225
 - hnco::neighborhood::SingleBitFlipIterator, 226
- SinusSummationCancellation, 226
- SixPeaks, 227
- sparse_bit_matrix_t
 - hnco, 18
- sparse_bit_vector_t
 - hnco, 18
- SpinHerd, 229
 - hnco::algorithm::hea::SpinHerd, 232
- SpinMoment, 232
- SteepestAscentHillClimbing, 234
- StopOnMaximum, 235
 - hnco::function::StopOnMaximum, 236
- StopOnTarget, 238
 - hnco::function::StopOnTarget, 239
- StopWatch, 241
- SummationCancellation, 242
 - hnco::function::SummationCancellation, 243
- TargetReached, 244
- TournamentSelection, 245
- Translation, 247
- Transvection, 248
- transvection_sequence_t
 - hnco, 18
- Trap, 252
 - hnco::function::Trap, 253
- ts_is_valid
 - hnco, 25, 26
- ts_multiply
 - hnco, 26
- ts_random
 - hnco, 27
- ts_random_commuting
 - hnco, 27
- ts_random_disjoint
 - hnco, 28
- ts_random_non_commuting
 - hnco, 28
- ts_random_unique_destination

- hncο, [29](#)
- ts_random_unique_source
 - hncο, [29](#)
- TsAffineMap, [255](#)

- Umda, [257](#)
- UniformCrossover, [259](#)
- update
 - hncο::function::OnBudgetFunction, [174](#)
 - hncο::function::StopOnMaximum, [237](#)
 - hncο::function::StopOnTarget, [240](#)
- update_solution
 - hncο::algorithm::Algorithm, [47](#)

- WalshExpansion, [260](#)
- WalshExpansion1, [262](#)
- WalshExpansion2, [265](#)