HNCO

Empirical cumulative distribution functions of the runtime of various black box optimization algorithms

August 15, 2021

Abstract

We partly follow the experimental procedure of the COCO framework for the performance assessment of black box optimization algorithms Hansen et al. [2016]. Each algorithm is run independently 20 times on each objective (or fitness) function. The dimension is fixed at n=100. Then 50 equally spaced targets are computed for each objective function. For each algorithm and each function we compute the empirical cumulative distribution function (ECDF) of the runtime, that is the proportion of targets reached as a function of the number of evaluations over all 20 runs. We also compute the global ECDF which takes into account the targets of all functions. The results are listed by function. For clarity reasons only 8 algorithms (hence 8 colors) are included in the study. It should be noted that the linear scale of targets does not fit the function EqualProducts.


Contents

	1.1 1.2	0	3 4 4				
2	Res	sults for one-max	5				
	2.1	All algorithms	5				
	2.2	Groups	5				
		2.2.1 ec	5				
		2.2.2 eda	6				
	ъ		,				
3		sults for lin	t				
	3.1	All algorithms	6				
	3.2		-				
		3.2.1 ec	-				
		3.2.2 eda	(
4	Results for leading-ones						
	4.1	All algorithms	8				
	4.2	Groups	8				
		4.2.1 ec	8				
		4.2.1 ec	8				
_	_	4.2.2 eda	9				
5		4.2.2 edasults for ridge	9				
5	5.1	4.2.2 eda	9				
5		4.2.2 eda	9 9 10				
5	5.1	4.2.2 eda	9 9 10 10				
5	5.1	4.2.2 eda	9 9 10				
	5.1 5.2	4.2.2 eda	9 9 10 10 10				
	5.1 5.2 Res	4.2.2 eda	9 9 9 10 10 10 10				
	5.1 5.2 Res 6.1	4.2.2 eda	9 9 10 10 10 11				
	5.1 5.2 Res	4.2.2 eda	9 9 9 10 10 10 10				


7 Results for jmp-10							
	7.1		12				
	7.2	1	13				
			13				
		7.2.2 eda	13				
8	Res	ults for djmp-5	14				
0	8.1	* -	14				
	8.2	ů	14				
		•	14				
			15				
9	Res		15				
	9.1		15				
	9.2	•	16				
			16				
		9.2.2 eda	16				
10	Res	ults for fp-5	17				
-0		-	17				
		ů	17				
		•	$\frac{17}{17}$				
			18				
11		±	18				
			18				
	11.2		19				
			19				
		11.2.2 eda	19				
12	Res	alts for nk	20				
12			20				
			20				
	12.2	•	20				
			21				
13 Results for max-sat							
			21				
	13.2	Groups	22				
			22				
		13.2.2 eda	22				
14	Res	alts for labs	23				
			23				
			23				
			23				
		14.2.2 eda	24				
15		r	24				
			24				
	15.2	1	25				
			2525				
		19.2.2 eda	20				
16	Res	alts for cancel	26				
			26				
		ů	26				
		•	26				
		16.2.2 eda	27				
	_						
17			27				
			27				
	17.2	1	28				
			28				
		17.2.2 eda	28				

18	8 Results for hiff				
	18.1 All algorithms	29			
	18.2 Groups	29			
	18.2.1 ec	29			
	18.2.2 eda	30			
19	Results for plateau	30			
	19.1 All algorithms	30			
	19.2 Groups	31			
	19.2.1 ec				
20	Results for walsh2	32			
	20.1 All algorithms	32			
	20.2 Groups	32			
	20.2.1 ec	-			
	20.2.2 eda	33			
	20.2.2 Cda	00			
A	Plan	33			
В	Default parameters	35			


1 Global results



1.2.1 ec




1.2.2 eda





2 Results for one-max

2.1 All algorithms




2.2 Groups







3 Results for lin



3.2.1 ec




3.2.2 eda





4 Results for leading-ones

4.1 All algorithms





4.2 Groups






5 Results for ridge






5.2.2 eda





6 Results for jmp-5

6.1 All algorithms





6.2 Groups






7 Results for jmp-10






7.2.2 eda





8 Results for djmp-5

8.1 All algorithms




8.2 Groups







9 Results for djmp-10



9.2.1 ec




9.2.2 eda





10 Results for fp-5

10.1 All algorithms





10.2 Groups






11 Results for fp-10






11.2.2 eda





12 Results for nk




12.2 Groups









13 Results for max-sat



13.2 Groups




13.2.2 eda





14 Results for labs

14.1 All algorithms





14.2 Groups






15 Results for ep






15.2.2 eda




Number of evaluations


16 Results for cancel

16.1 All algorithms




16.2 Groups






17 Results for trap




17.2 Groups


17.2.1 ec



17.2.2 eda





18 Results for hiff




18.2 Groups









19 Results for plateau




19.2 Groups




19.2.2 eda




20 Results for walsh2



20.2 Groups





References

Nikolaus Hansen, Anne Auger, Dimo Brockhoff, Dejan Tusar, and Tea Tusar. COCO: performance assessment. CoRR, abs/1605.03560, 2016. URL http://arxiv.org/abs/1605.03560.

A Plan

```
{
    "exec": "hnco",
    "opt": "--log-improvement --map 1 --map-random -s 100",
    "budget": 500000,
    "num_runs": 20,
    "num_targets": 50,
    "parallel": true,
    "graphics": {
        "all": {
            "helper": true,
            "font_size": 14
        },
        "groups": [
            {
                "id": "ec",
                "algorithms": [ "ea-1p1", "ea-1p10", "ea-10p1", "ea-1c10", "ga" ],
                "helper": true,
                "font_size": 14
            },
                "id": "eda",
                "algorithms": [ "pbil", "umda" ],
                "helper": false,
                "font_size": 14
            }
```

```
]
},
"functions": [
    {
        "id": "one-max",
        "opt": "-F 0 --stop-on-maximum"
    },
        "id": "lin",
        "opt": "-F 1 -p instances/lin.100"
   },
        "id": "leading-ones",
        "opt": "-F 10 --stop-on-maximum"
    },
        "id": "ridge",
        "opt": "-F 11 --stop-on-maximum"
   },
        "id": "jmp-5",
        "opt": "-F 30 --stop-on-maximum -t 5"
    },
    {
        "id": "jmp-10",
        "opt": "-F 30 --stop-on-maximum -t 10"
   },
        "id": "djmp-5",
        "opt": "-F 31 --stop-on-maximum -t 5"
   },
    {
        "id": "djmp-10",
        "opt": "-F 31 --stop-on-maximum -t 10"
    },
        "id": "fp-5",
        "opt": "-F 40 --stop-on-maximum -t 5"
   },
        "id": "fp-10",
        "opt": "-F 40 --stop-on-maximum -t 10"
    },
        "id": "nk",
        "opt": "-F 60 -p instances/nk.100.4"
    },
    {
        "id": "max-sat",
        "opt": "-F 70 -p instances/ms.100.3.1000"
    },
        "id": "labs",
        "opt": "-F 81"
    },
        "id": "ep",
        "opt": "-F 90 -p instances/ep.100",
        "reverse": true,
        "logscale": true
   },
    {
        "id": "cancel",
```

```
"opt": "-F 100 -s 99",
        "reverse": true
    },
    {
        "id": "trap",
        "opt": "-F 110 --stop-on-maximum --fn-num-traps 10"
    },
        "id": "hiff",
        "opt": "-F 120 --stop-on-maximum -s 128"
    },
        "id": "plateau",
        "opt": "-F 130 --stop-on-maximum"
    },
        "id": "walsh2",
        "opt": "-F 162 -p instances/walsh2.100"
],
"algorithms": [
    {
        "id": "sa",
        "opt": "-A 200 --sa-beta-ratio 1.05 --sa-num-trials 10"
    },
    {
        "id": "ea-1p1",
        "opt": "-A 300"
    },
        "id": "ea-1p10",
        "opt": "-A 310 --ea-mu 1 --ea-lambda 10"
    },
        "id": "ea-10p1",
        "opt": "-A 310 --ea-mu 10 --ea-lambda 1"
    },
        "id": "ea-1c10",
        "opt": "-A 320 --ea-mu 1 --ea-lambda 10 --allow-no-mutation"
    },
        "id": "ga",
        "opt": "-A 400 --ea-mu 100"
    },
        "id": "pbil",
        "opt": "-A 500 -1 5e-3"
    },
        "id": "umda",
        "opt": "-A 600 -x 100 -y 10"
    }
]
```

B Default parameters

```
# algorithm = 100
# bm_mc_reset_strategy = 1
# bm_num_gs_cycles = 1
# bm_num_gs_steps = 100
```

}

```
# bm_sampling = 1
# budget = 10000
# bv_size = 100
# description_path = description.txt
\# ea_lambda = 100
\# ea_mu = 10
\# expression = x
# fn_name = noname
# fn_num_traps = 10
# fn_prefix_length = 2
# fn_threshold = 10
# fp_expression = (1-x)^2+100*(y-x^2)^2
# fp_lower_bound = -2
# fp_num_bits = 8
# fp_upper_bound = 2
# function = 0
# ga_crossover_bias = 0.5
# ga_crossover_probability = 0.5
# ga_tournament_size = 10
# hea_bit_herding = 0
# hea_num_seq_updates = 100
# hea_reset_period = 0
# hea_sampling_method = 0
# hea_weight = 1
# learning_rate = 0.001
# map = 0
# map_input_size = 100
# map_path = map.txt
# map_ts_length = 10
# map_ts_sampling_mode = 0
# mutation_rate = 1
# neighborhood = 0
# neighborhood_iterator = 0
# noise_stddev = 1
# num_iterations = 0
# num_threads = 1
# path = function.txt
# pn_mutation_rate = 1
# pn_neighborhood = 0
# pn_radius = 2
# population_size = 10
# pv_log_num_components = 5
# radius = 2
# results_path = results.json
# rls_patience = 50
# sa_beta_ratio = 1.2
# sa_initial_acceptance_probability = 0.6
# sa_num_transitions = 50
# sa_num_trials = 100
\# seed = 0
# selection_size = 1
# solution_path = solution.txt
# target = 100
# print_defaults
# last_parameter
# exec_name = hnco
\# version = 0.15
# Generated from hnco.json
```