```c
//
// Created by hfwei on 2024/9/25.
//

#include <stdio.h>

int main(void) {
  const double MOL = 6.02E23;
  const int GRAM_PER_MOL = 32;

  int mass = 6;

  double quantity = mass * 1.0 / GRAM_PER_MOL * MOL;

  printf("quantity = %.3e\nquantity = %.5g\n",
         quantity, quantity);

  return 0;
}
```

```c
//
// Created by hfwei on 2024/9/25.
//

#include <math.h>
#include <stdio.h>
#include <ctype.h>

int main(void) {
  char first_name[] = "Tayu";
  char last_name[] = "Lo";

  char gender = 'm';
  // char upper_gender = 'm' + 'A' - 'a';
  // printf("upper_gender : %c\n", upper_gender);

  int birth_year = 1954;
  int birth_month = 7;
  int birth_day = 20;
  char weekday[] = "Tuesday";

  int c_score = 50;
  int music_score = 99;
  int medicine_score = 78;

  double mean = (c_score + music_score + medicine_score
) / 3.0;
  double sd = sqrt((pow(c_score - mean, 2) +
      pow(music_score - mean, 2) +
      pow(medicine_score - mean, 2)) / 3.0);

  int rank = 10;

  printf("%s %s \t %c\n"
         "%.2d-%d-%d \t %.3s.\n"
         "%d \t %d \t %d\n"
         "%.1f \t %.2f \t %d%%\n",
         first_name, last_name, toupper(gender),
         birth_month, birth_day, birth_year, weekday,
         c_score, music_score, medicine_score,
         mean, sd, rank);

  return 0;
}
```

```c
//
// Created by hfwei on 2024/9/25.
//

#include <stdio.h>

int main(void) {
  // const: constant
  const double PI = 3.14159;

  int radius = 10;

  double circumference = 2 * PI * radius;

  double area = PI * radius * radius;

  /*
   *  format is composed of zero or more directives:
   *    ordinary characters and conversion specifications introduced by %
   */
  printf("radius = %d\ncircumference = %.2f\narea = %.2f\n",
         radius, circumference, area);

  return 0;
}
```

```c
//
// Created by hfwei on 2024/9/25.
//

#include <stdio.h>
#include <math.h>

int main(void) {
  const double PI = 3.14159;

  int radius = 100;

  double surface_area = 4 * PI * pow(radius, 2);
  double volume = 4.0 / 3 * PI * pow(radius, 3);

  // .4: precision
  // 15: minimum width
  // -: flag
  printf("%-15.4f : surface_area\n%-15.4f : volume\n",
         surface_area, volume);

  return 0;
}
```

```c
//
// Created by hfwei on 2024/9/25.
//

#include <math.h>
#include <stdio.h>
#include <ctype.h>

int main(void) {
  char first_name[10];
  char last_name[10];

  char gender;

  int birth_year;
  int birth_month;
  int birth_day;
  char weekday[10];

  int c_score;
  int music_score;
  int medicine_score;
  int rank;

  /*
   * zero or more directives:
   * (1) one or more white-space characters ( , \t, \n);
   * (2) ordinary characters (neither % nor white-space characters)
   * (3) conversion specification introduced by %
   */
  scanf("%9s%9s %c %d-%d-%d %9s %d%d%d %*lf%*lf %d%%",
        first_name, last_name, &gender,
        &birth_year, &birth_month, &birth_day, weekday,
        &c_score, &music_score, &medicine_score,
        &rank);

  double mean = (c_score + music_score + medicine_score) / 3.0;

  double sd = sqrt((pow(c_score - mean, 2) +
      pow(music_score - mean, 2) +
      pow(medicine_score - mean, 2)) / 3.0);

```

```c

  printf("%s %s \t %c\n"
         "%.2d-%d-%d \t %.3s.\n"
         "%d \t %d \t %d\n"
         "%.1f \t %.2f \t %d%%\n",
         first_name, last_name, toupper(gender),
         birth_month, birth_day, birth_year, weekday,
         c_score, music_score, medicine_score,
         mean, sd, rank);

  return 0;

  return 0;
}
```

```
 1 add_executable(circle circle.c)
 2
 3 add_executable(sphere sphere.c)
 4 target_link_libraries(sphere m)
 5
 6 add_executable(mol mol.c)
 7
 8 add_executable(admin admin.c)
 9 target_link_libraries(admin m)
10
11 add_executable(admin-scanf admin-scanf.c)
12 target_link_libraries(admin-scanf m)
```