# Decompositions of Graphs

Hengfeng Wei

hfwei@nju.edu.cn

June 12, 2018





John Hopcroft



Robert Tarjan

"For fundamental achievements in the design and analysis of algorithms and data structures."

— Turing Award, 1986

# Depth-first search

SIAM J. COMPUT. Vol. 1, No. 2, June 1972

#### DEPTH-FIRST SEARCH AND LINEAR GRAPH ALGORITHMS\*

ROBERT TARJAN†

Abstract. The value of depth-first search or "backfracking" as a technique for solving problems is illustrated by two examples. An improved version of an algorithm for finding the strongly connected components of a directed graph and an algorithm for finding the biconnected components of an unitered graph are presented. The space and time requirements of both algorithms are bounded by  $k_1V + k_2E + k_3$  for some constants  $k_1, k_2, \text{and } k_3, \text{where } V$  is the number of vertices and E is the number of edges of the graph being examined.

Key words. Algorithm, backtracking, biconnectivity, connectivity, depth-first, graph, search, spanning tree, strong-connectivity.

#### Reference

• "Depth-First Search And Linear Graph Algorithms" by Robert Tarjan.

# Depth-first search

SIAM J. COMPUT. Vol. 1, No. 2, June 1972

#### DEPTH-FIRST SEARCH AND LINEAR GRAPH ALGORITHMS\*

ROBERT TARJAN†

Abstract. The value of depth-first search or "backtracking" as a technique for solving problems is illustrated by two examples. An improved version of an algorithm for finding the strongly connected components of a directed graph and an algorithm for finding the biconnected components of an undirect graph are presented. The space and time requirements of both algorithms are bounded by  $k_1V + k_2E + k_3$  for some constants  $k_1, k_2$ , and  $k_3$ , where V is the number of vertices and E is the number of edges of the graph being examined.

Key words. Algorithm, backtracking, biconnectivity, connectivity, depth-first, graph, search, spanning tree, strong-connectivity.

"We have seen how the depth-first search method may be used in the construction of very efficient graph algorithms. . . .

Depth-first search is a powerful technique with many applications."

#### Reference

"Depth-First Search And Linear Graph Algorithms" by Robert Tarjan.

### The POWER of DFS

Graph decomposition vs. Graph traversal

Structures!

### The POWER of DFS

#### Graph decomposition vs. Graph traversal

#### Structures!

- 1. states of vertices
- 2. types of edges
- 3. lifetime of vertices (DFS)
  - $\mathbf{v} : \mathsf{d}[v], \mathsf{f}[v]$
  - f[v]: DAG, SCC
  - d[v]: biconnectivity

# Types of edges

```
Definition (Classifying edges)
```

Given a DFS/BFS traversal  $\Rightarrow$  DFS/BFS tree:

Tree edge:  $\rightarrow$  child

Back edge:  $\rightarrow$  ancestor

Forward edge: → *nonchild* descendant

Cross edge: → neither ancestor nor descendant

# Types of edges

#### Definition (Classifying edges)

Given a DFS/BFS traversal  $\Rightarrow$  DFS/BFS tree:

Tree edge:  $\rightarrow$  child


Back edge:  $\rightarrow$  ancestor

Forward edge: → *nonchild* descendant


Cross edge:  $\rightarrow$  neither ancestor nor descendant

#### Remarks


- applicable to both DFS and BFS
- w.r.t. DFS/BFS trees




DFS on directed graph




DFS on directed graph




DFS on undirected graph



BFS on directed graph



BFS on directed graph



BFS on undirected graph

Undirected connected graph  $G = (V, E), v \in V$ 

DFS tree T from  $v \equiv$  BFS tree T' from v

Undirected connected graph  $G = (V, E), v \in V$ 

DFS tree T from  $v \equiv BFS$  tree T' from v

$$G \equiv T$$

Undirected connected graph  $G=(V,E),v\in V$ 

DFS tree T from  $v \equiv BFS$  tree T' from v

$$G \equiv T$$

Proof.

$$G_{\mathsf{DFS}}$$
: tree + back vs.  $G_{\mathsf{BFS}}$ : tree + cross



Undirected connected graph  $G=(V,E),v\in V$ 

DFS tree T from  $v \equiv$  BFS tree T' from v

$$G \equiv T$$


Proof.

$$G_{\mathsf{DFS}}$$
: tree + back vs.  $G_{\mathsf{BFS}}$ : tree + cross

Q: What if G is a digraph?



### Lift time of vertices in DFS




## Theorem (Disjoint or Contained (Problem 4.2: (1) & (2)))

$$\forall u,v: [_u\ ]_u\cap [_v\ ]_v=\emptyset\bigvee\left([_u\ ]_u\subsetneqq [_v\ ]_v\vee [_v\ ]_v\subsetneqq [_u\ ]_u\right)$$


## Theorem (Disjoint or Contained (Problem 4.2: (1) & (2)))

$$\forall u, v : [_u ]_u \cap [_v ]_v = \emptyset \bigvee \left( [_u ]_u \subsetneq [_v ]_v \vee [_v ]_v \subsetneq [_u ]_u \right)$$

Proof.




## Preprocessing for ancestor/descendant relation (Problem 5.23)



Q: Is u an ancestor of v? O(1)


### Preprocessing for ancestor/descendant relation (Problem 5.23)



Q: Is u an ancestor of v? O(1)

 $v:\mathsf{d}[v],\mathsf{f}[v]$ 

#### Preprocessing for ancestor/descendant relation (Problem 5.23)



Q: Is u an ancestor of v? O(1)

 $v : \mathsf{d}[v], \mathsf{f}[v]$ 

Q: # of descendants of any v?

$$\forall u \rightarrow v$$
:

- ▶ tree/forward edge:  $\begin{bmatrix} u & v \end{bmatrix}_v$
- ▶ back edge:  $\begin{bmatrix} v & u \end{bmatrix} u \end{bmatrix} v$
- ightharpoonup cross edge:  $\begin{bmatrix} v \end{bmatrix}_v \begin{bmatrix} u \end{bmatrix}_u$

$$\forall u \to v$$
:

- ▶ tree/forward edge:  $[u \ [v \ ]v \ ]u$
- ▶ back edge:  $\begin{bmatrix} v & u \end{bmatrix} u \end{bmatrix} v$
- ightharpoonup cross edge:  $\begin{bmatrix} v \end{bmatrix}_v \begin{bmatrix} u \end{bmatrix}_u$

$$f[v] < d[u] \iff edge$$

$$\exists$$
 cycle  $\Longrightarrow$ 



$$\forall u \to v$$
:

- ▶ tree/forward edge:  $[u \ [v \ ]v \ ]u$
- ▶ back edge:  $\begin{bmatrix} v & u \end{bmatrix} u \end{bmatrix} v$
- ightharpoonup cross edge:  $\begin{bmatrix} v \end{bmatrix}_v \begin{bmatrix} u \end{bmatrix}_u$

$$f[v] < d[u] \iff \operatorname{cross} \operatorname{edge}$$

$$\exists$$
 cycle  $\Longrightarrow$ 



$$\forall u \to v$$
:

- ▶ tree/forward edge:  $[u \ [v \ ]v \ ]u$
- ▶ back edge:  $\begin{bmatrix} v & u \end{bmatrix} u \end{bmatrix} v$
- ightharpoonup cross edge:  $\begin{bmatrix} v \end{bmatrix}_v \begin{bmatrix} u \end{bmatrix}_u$

$$\mathsf{f}[v] < \mathsf{d}[u] \iff \mathsf{cross} \; \mathsf{edge}$$

$$f[u] < f[v] \iff$$

$$\sharp$$
 cycle  $\Longrightarrow$ 



$$\forall u \to v$$
:

- ▶ tree/forward edge:  $[u \ [v \ ]v \ ]u$
- ▶ back edge:  $\begin{bmatrix} v & u \end{bmatrix} u \end{bmatrix} v$
- ightharpoonup cross edge:  $\begin{bmatrix} v \end{bmatrix}_v \begin{bmatrix} u \end{bmatrix}_u$

$$\mathsf{f}[v] < \mathsf{d}[u] \iff \mathsf{cross} \; \mathsf{edge}$$

$$\mathsf{f}[u] < \mathsf{f}[v] \iff \mathsf{back} \; \mathsf{edge}$$

$$\nexists \ \mathsf{cycle} \ \Longrightarrow$$



$$\forall u \to v:$$

- ▶ tree/forward edge:  $[u \ [v \ ]v \ ]u$
- ▶ back edge:  $\begin{bmatrix} v & u \end{bmatrix} u \end{bmatrix} v$
- ightharpoonup cross edge:  $\begin{bmatrix} v \end{bmatrix}_v \begin{bmatrix} u \end{bmatrix}_u$

$$\mathsf{f}[v] < \mathsf{d}[u] \iff \mathsf{cross}\;\mathsf{edge}$$

$$\mathsf{f}[u] < \mathsf{f}[v] \iff \mathsf{back} \; \mathsf{edge}$$

$$\nexists \; \mathsf{cycle} \implies \boxed{u \to v \iff \mathsf{f}[v] < \mathsf{f}[u]}$$

Height and diameter of tree (Problem 5.4)

Binary tree T = (V, E) with |V| = n:

- $\blacktriangleright \ \operatorname{height} \ H(T) \ \operatorname{in} \ O(n)$
- ▶ diameter D(T) in O(n)

Height and diameter of tree (Problem 5.4)

Binary tree T = (V, E) with |V| = n:

- $\blacktriangleright \ \, \mathsf{height} \,\, H(T) \,\, \mathsf{in} \,\, O(n)$
- ▶ diameter D(T) in O(n)

$$\left\{ \begin{array}{ll} H(T)=0, & T \text{ is a leave} \\ H(T)=\max\left(H(L_T),H(R_T)\right)+1, & \text{o.w.} \end{array} \right.$$
 throught root or not?

Height and diameter of tree (Problem 5.4)

Binary tree T = (V, E) with |V| = n:

- ▶ height H(T) in O(n)
- diameter D(T) in O(n)

$$\left\{ \begin{array}{l} H(T)=0, & T \text{ is a leave} \\ H(T)=\max\left(H(L_T),H(R_T)\right)+1, & \text{o.w.} \end{array} \right.$$

throught root or not?

#### Question

Diameter of a tree without a designated root?

#### Perfect subtree

Perfect subtree (Problem 5.22)

- ▶ binary tree T = (V, E)
- ▶ root  $r \in V$
- ▶ goal: find all perfect subtrees

# Counting shortest paths

Counting shortest paths (Problem 5.26)

Counting # of shortest paths in (un)directed graphs using BFS.

# Counting shortest paths

Counting shortest paths (Problem 5.26)

Counting # of shortest paths in (un)directed graphs using BFS.

Maybe in the next class...

