— DFS&BFS, Cycle, DAG, SCC, and Biconnectivity

hengxin0912@gmail.com

May 19, 2016

1 / 22

- Overview
- 2 DFS and BFS
- Cycle
- 4 DAG
- 5 SCC

Contents of Tutorials

- 1. Graph Traversal Decomposition
- 2. MST (Greedy Algorithm) & Path
- 3. DP: Dynamic Programming

Graph decomposition vs. Graph traversal



- Overview
- DFS and BFS
- 3 Cycle
- 4 DAG
- 5 SCC

Classifying edges

Definition (Classifying edges)


Given a dfs/bfs traversal:

- ► Tree edge
- ► Back edge
- ► Forward edge
- ► Cross edge

Remarks:

- ► Applicable to both DFS and BFS
- ► With respect to DFS/BFS trees


Classifying edges [Problem: 3.4.1]




(a) DFS on directed graph.



(c) BFS on directed graph.



(b) DFS on undirected graph.



(d) BFS on undirected graph.

Classifying edges

DFS tree and BFS tree coincide [Problem: 3.4.30]

$$G = (V, E), v \in V$$
. DFS tree $T = BFS$ tree T' .

- G is an undirected graph $\Rightarrow G = T$.
- ▶ G is a digraph \Rightarrow ? G = T.

Solution.

- ightharpoonup T: tree + back; T': tree + cross
- ightharpoonup T: tree + back + forward + cross; T': tree + back + cross

Distance constraints for BFS

Distance constraints for BFS [Problem: 3.4.4]

BFS on digraph:

BFS on undirected graph:

TE:
$$d[v] = d[u] + 1$$

$$TE: d[v] = d[u] + 1$$

$$\mathsf{BE} \colon \ 0 \leq d[v] \leq d[u]$$

$$\mathsf{CE} \colon \, d[v] = d[u] \vee d[v] = d[u] + 1$$

 $\mathsf{CE} \colon d[v] \le d[u] + 1$

Solution to "CE in BFS on undirected graph".

- d[v] = d[u], d[v] = d[u] + 1
- b d[v] < d[u], d[v] > d[u] + 1

Remark.

- ▶ BFS tree defines a *shortest-path* from its root to every other node.
- ► Layers in BFS on *undirected* graph ⇒ bipartite testing [Problem: 3.4.26]

- Overview
- 2 DFS and BFS
- Cycle
- 4 DAG
- 5 SCC

Cycle detection

Table: Cycle detection [Problem: 3.4.21]

	Digraph	Undirected graph
DFS	back edge ←⇒ cycle	back edge ⇔ cycle
BFS	back edge \Rightarrow cycle	cross edge ←⇒ cycle
	cycle ∌ back edge	

Remark.

- cycle in undirected graphs
- cycle in digraphs
 - DAG
 - ► SCC

8 / 22

Orientation of undirected graph

Orientation of undirected graph [Problem: 3.4.13]

Undirected (connected) graph G, edge oriented s.t. $\forall v, \text{in}[v] \geq 1$.

Solution.

orientation $\iff \exists$ cycle; DFS

Bipartite graph

Bipartite graph [Problem: 3.4.26; 3.4.32]

To test bipartiteness of an undirected graph.

Solution.

BFS + Coloring:

- ightharpoonup pick any s, c[s] = 0
- $u \leftarrow \mathsf{Dequeue}(Q)$
- $ightharpoonup \forall (u,v)$:
 - tree edge
 - cross edge: check

Proof.

Check cross edge (u, v):

- ▶ (∃) d[v] = d[u] ⇒ the same layer ⇒ odd cycle ([Problem: 3.4.17]; EX) ⇒ non-bipartite
- ▶ (\forall) $d[v] = d[u] + 1 \Rightarrow$ different layers \Rightarrow different colors



- Overview
- DFS and BFS
- 3 Cycle
- 4 DAG
- 5 SCC

DAG

no back edge \iff DAG \iff \exists topo. ordering

Topo. sorting

DFS on digraph, $u \rightarrow v$:

- ▶ back edge: f(u) < f(v)
- ▶ others: f(u) > f(v)

$$u \to v \Rightarrow u \prec v$$

 $u \to v \Rightarrow f(u) > f(v)$

Topo. sorting: sort vertices in *decreasing* order of their *finish* times.



Digraph as DAG

Digraph as DAG [Problem: 3.4.6]

Theorem

Every digraph is a dag of its SCCs.

Remark.

- SCC algorithm
- ► SCC: reachability/connectivity equivalence class
- two tiered structure of digraphs

Kahn's toposort algorithm

Kahn's toposort algorithm (1962) [Problem: 3.4.19]

- queue for source vertices (in[v] = 0)
- ightharpoonup repeat: dequeue v, delete it, output it

Solution.

Lemma

Every DAG has at least one source and at least one sink vertex.

Remark

DFS on DAG:

- ▶ $arg max_v f(v) \Rightarrow source (used in SCC algorithm)$
- $ightharpoonup \arg\min_{v} f(v) \Rightarrow \sinh$

Hamiltonian path in DAG

Hamilton path in DAG [Problem: 3.4.16]

- ightharpoonup DAG G
- ► path visiting each vertex once

Solution.

- general digraph: NP-hard
- ▶ dag: ∃ HP ⇔ ∃! topo. ordering
 - $\blacktriangleright \Leftarrow$: By contridiction. $\exists u \sim v : u \nrightarrow v$; swap

Algorithm:

- toposort, check edges
- ▶ the Kahn toposort algorithm

Semi-connected DAG

Definition

Semi-connected digraph $\forall u, v : u \leadsto v \lor v \leadsto u$

Semi-connected DAG [Problem: 3.4.21 (c) + (d)]

To test whether a DAG is semi-connected.

Solution.

dag: \exists HP \iff \exists ! topo. ordering \iff semi-connected

Proof.

- $\blacktriangleright \Leftarrow$: by contradiction; total order $(\forall u, v : u \prec v \lor v \prec u)$
- ⇒: ∃HP



Minimum cost reachable

Minimun cost reachable [Problem: 3.4.22]

Compute
$$cost[u] = min\{cost[v] \mid u \leadsto v\}.$$

Solution.

- dag: reverse topo. ordering
 - ▶ backtracking: $cost[u] = min_{u \to v} \{cost[v]\}$
- digraph: dag of scc

Line up

Line up [Problem: 3.4.29]

- ▶ i hates j: $i \prec j$
- ▶ i hates j: #i < #j

Solution.

```
i hates j: i \rightarrow j;
```

- ► DAG?
- ▶ longest path; critical path



One-to-all reachability

One-to-all reachability [Problem: 3.4.28]

- ▶ given $v:v \leadsto^? \forall u$
- $ightharpoonup \exists ?v: v \leadsto \forall u$

Solution.

- ▶ DFS/BFS
- ▶ SCC; \exists ! source vertex $v \iff v \leadsto \forall u$

Proof.

- ightharpoonup \Rightarrow : By contradiction. $\exists u: v \nrightarrow u \land \operatorname{in}[u] > 0 \Rightarrow \exists u' \to u \land v \nrightarrow u'$. Cycle.
- ► <=: (1) source (2) ∃!



- Overview
- DFS and BFS
- Cycle
- 4 DAG
- SCC

SCC

Kosaraju SCC algorithm, 1978 [Problem: 3.4.7]

- ► 1st DFS ⇒? BFS
- ▶ 2nd DFS ⇒? BFS

Solution.

digraph = dag of SCCs

- ▶ (2nd round) Repeat: traversal from $s \in sink$ scc; delete
- ▶ (1nd round) dag: toposort \Rightarrow decreasing finish time \Rightarrow s \in source scc

Remark.

- ▶ DFS on G^T ; DFS/BFS on G
- ▶ DFS on G; DFS/BFS on G^T

One-way streets

One-way streets [Problem: 3.4.23]

- $\blacktriangleright \forall u, v : u \leftrightsquigarrow v$
- $\triangleright s: s \leadsto v \leadsto s$

Solution.

- ightharpoonup G is an SCC
- $\{v \mid s \leadsto v\}$ is an SCC
 - ▶ compute $\{v \mid s \leadsto v\}$
 - compute SCCs
 - compare

Infinite path

Infinite path [Problem: 3.4.25]

- ▶ prove: $Inf(p) \subseteq \exists SCC$
- ▶ an infinite path?
- ... \land visiting $\exists g \in V_G$ infinitely often
- ... \wedge not visiting $\exists b \in V_B$ infinitely often

Solution.

- cycle ⊆ ∃scc
- $ightharpoonup \exists \mathsf{scc} : s \leadsto \mathsf{scc}$
- ▶ $\exists scc : s \leadsto scc \land scc \cap V_G \neq \emptyset$
- ▶ delete V_B ; $\exists scc : scc \cap V_G \neq \emptyset$; in G: $s \rightsquigarrow scc$
 - ▶ wrong: \exists scc : $s \leadsto \text{scc} \land \text{scc} \cap V_G \neq \emptyset \land \text{scc} \cap V_B = \emptyset$
 - wrong: delete V_B ; $\exists scc : s \leadsto scc \land scc \cap V_G \neq \emptyset$

Odd cycle in digraph

Odd cycle in digraph [Problem: 3.4.15]

Find an odd cycle in a digraph G.

Lemma

A digraph G has an odd directed cycle $\iff \exists scc : scc \text{ is non-bipartite}$ (when treated undirected).

Proof.

- $\blacktriangleright \Leftarrow$: undirected C; oriented
 - odd directed cycle
 - ▶ choose a direction $\forall u \to v$: Len $(v \leadsto u)$



 $\mathsf{DFS} + \mathsf{Coloring}$ on G