

# Dynamic Programming

Hengfeng Wei

hfwei@nju.edu.cn

June 11 – June 19, 2017



# Dynamic Programming

1 Overview

2 1D DP

3 2D DP

4 DP on Graphs

5 The Knapsack Problem

# What is DP?

DP  $\approx$  “brute force”

DP  $\approx$  “smart scheduling of subproblems”

DP  $\approx$  “shortest/longest paths in some DAG”

# What is DP?

DP  $\approx$  “smarter brute force”

DP  $\approx$  “smart scheduling of subproblems”

DP  $\approx$  “shortest/longest paths in some DAG”

# What is not DP?

Programming = Planning

# What is not DP?

Programming = Planning

Programming  $\neq$  Coding  
(Richard Bellman, 1940s)

# Steps for applying DP

1. Define subproblems
  - ▶ # of subproblems
2. Set the goal
3. Define the recurrence
  - ▶ larger subproblem  $\leftarrow$  # smaller subproblems
  - ▶ init. conditions
4. Write pseudo-code: fill “table” in topo. order
5. Analyze Time/Space complexity
6. Extract the optimal solution

# Common subproblems in DP

1D subproblems:

**Input:**  $x_1, x_2, \dots, x_n$  (array, sequence, string)

**Subproblems:**  $x_1, x_2, \dots, x_i$  (prefix/suffix)

**#:**  $\Theta(n)$



# Common subproblems in DP

1D subproblems:

**Input:**  $x_1, x_2, \dots, x_n$  (array, sequence, string)

**Subproblems:**  $x_1, x_2, \dots, x_i$  (prefix/suffix)

**#:**  $\Theta(n)$

**Examples:** Fib, Maximum-sum subarray, Longest increasing subsequence, Highway restaurants, Text justification

# Common subproblems in DP

2D subproblems:

1. Input:  $x_1, x_2, \dots, x_m; \quad y_1, y_2, \dots, y_n$

Subproblems:  $x_1, x_2, \dots, x_i; \quad y_1, y_2, \dots, y_j$

#:  $\Theta(mn)$

# Common subproblems in DP

2D subproblems:

1. Input:  $x_1, x_2, \dots, x_m; \quad y_1, y_2, \dots, y_n$

Subproblems:  $x_1, x_2, \dots, x_i; \quad y_1, y_2, \dots, y_j$

#:  $\Theta(mn)$

Examples: Edit distance, Longest common subsequence

# Common subproblems in DP

2D subproblems:

1. Input:  $x_1, x_2, \dots, x_m; \quad y_1, y_2, \dots, y_n$

Subproblems:  $x_1, x_2, \dots, x_i; \quad y_1, y_2, \dots, y_j$

#:  $\Theta(mn)$

Examples: Edit distance, Longest common subsequence

2. Input:  $x_1, x_2, \dots, x_n$

Subproblems:  $x_i, \dots, x_j$

#:  $\Theta(n^2)$

# Common subproblems in DP

2D subproblems:

1. Input:  $x_1, x_2, \dots, x_m; \quad y_1, y_2, \dots, y_n$

Subproblems:  $x_1, x_2, \dots, x_i; \quad y_1, y_2, \dots, y_j$

#:  $\Theta(mn)$

Examples: Edit distance, Longest common subsequence

2. Input:  $x_1, x_2, \dots, x_n$

Subproblems:  $x_i, \dots, x_j$

#:  $\Theta(n^2)$

Examples: Matrix chain multiplication, Optimal BST

# Common subproblems in DP

3D subproblems:

- ▶ Floyd-Warshall algorithm

$$d(i, j, k) = \min\{d(i, j, k - 1), d(i, k, k - 1) + d(k, j, k - 1)\}$$

# Common subproblems in DP

3D subproblems:

- ▶ Floyd-Warshall algorithm

$$d(i, j, k) = \min\{d(i, j, k-1), d(i, k, k-1) + d(k, j, k-1)\}$$

DP on graphs:

1. On rooted tree

**Subproblems:** rooted subtrees

2. On DAG

**Subproblems:** nodes after/before in the topo. order

# Common subproblems in DP

3D subproblems:

- ▶ Floyd-Warshall algorithm

$$d(i, j, k) = \min\{d(i, j, k-1), d(i, k, k-1) + d(k, j, k-1)\}$$

DP on graphs:

1. On rooted tree

**Subproblems:** rooted subtrees

2. On DAG

**Subproblems:** nodes after/before in the topo. order

Knapsack problem:

- ▶ Subset sum problem, change-making problem



# Common subproblems in DP

And Others . . .

# Dynamic Programming

- 1 Overview
- 2 1D DP**
- 3 2D DP
- 4 DP on Graphs
- 5 The Knapsack Problem

# Dynamic Programming

- 1 Overview
- 2 1D DP
- 3 2D DP**
- 4 DP on Graphs
- 5 The Knapsack Problem

# Dynamic Programming

- 1 Overview
- 2 1D DP
- 3 2D DP
- 4 DP on Graphs**
- 5 The Knapsack Problem

# Dynamic Programming

- 1 Overview
- 2 1D DP
- 3 2D DP
- 4 DP on Graphs
- 5 The Knapsack Problem**

