


# Asymptotics, Recurrences, and Divide and Conquer

Hengfeng Wei

hfwei@nju.edu.cn

April 17, 2018



Problem  $P$

Algorithm  $A$

Problem  $P$       Algorithm  $A$

Inputs:  $\mathcal{X}_n$  of size  $n$

Problem  $P$       Algorithm  $A$

Inputs:  $\mathcal{X}_n$  of size  $n$

$$W(n) = \max_{X \in \mathcal{X}_n} T(X)$$

## Problem $P$      Algorithm $A$

Inputs:  $\mathcal{X}_n$  of size  $n$

$$W(n) = \max_{X \in \mathcal{X}_n} T(X)$$

$$B(n) = \min_{X \in \mathcal{X}_n} T(X)$$

## Problem $P$      Algorithm $A$

Inputs:  $\mathcal{X}_n$  of size  $n$

$$W(n) = \max_{X \in \mathcal{X}_n} T(X)$$

$$B(n) = \min_{X \in \mathcal{X}_n} T(X)$$

$$A(n) = \sum_{X \in \mathcal{X}_n} T(X) \cdot P(X)$$

## Problem $P$      Algorithm $A$

Inputs:  $\mathcal{X}_n$  of size  $n$

$$W(n) = \max_{X \in \mathcal{X}_n} T(X)$$

$$B(n) = \min_{X \in \mathcal{X}_n} T(X)$$

$$A(n) = \sum_{X \in \mathcal{X}_n} T(X) \cdot P(X) = \mathbb{E}_{X \in \mathcal{X}_n} [T(X)]$$



## Average-case Time Complexity (Problem 1.8)

Input :  $r \in [1, n]$ ,  $r \in \mathbb{Z}^+$

$$P\{r = i\} = \begin{cases} \frac{1}{n}, & 1 \leq i \leq \frac{n}{4} \\ \frac{2}{n}, & \frac{n}{4} < i \leq \frac{n}{2} \\ \frac{1}{2n}, & \frac{n}{2} < i \leq n \end{cases}$$

## Average-case Time Complexity (Problem 1.8)

Input :  $r \in [1, n]$ ,  $r \in \mathbb{Z}^+$

$$P\{r = i\} = \begin{cases} \frac{1}{n}, & 1 \leq i \leq \frac{n}{4} \\ \frac{2}{n}, & \frac{n}{4} < i \leq \frac{n}{2} \\ \frac{1}{2n}, & \frac{n}{2} < i \leq n \end{cases}$$

$$\begin{aligned} A &= \sum_{X \in \mathcal{X}} T(X) \cdot P(X) \\ &= T(1)P(1) + T(2)P(2) + \cdots + T(n)P(n) \\ &= \frac{n}{4} \times 10 \times \frac{1}{n} + \frac{n}{4} \times 20 \times \frac{2}{n} + \frac{n}{4} \times 30 \times \frac{1}{2n} + \frac{n}{4} \times n \times \frac{1}{2n} \\ &= \frac{1}{8}n + \frac{55}{4} \end{aligned}$$

# Average-case Analysis of Quicksort

$$A(n) = n - 1 + \frac{1}{n} \sum_{i=0}^{n-1} (A(i) + A(n - i - 1))$$

$$A(n) = \mathbb{E}_{X \in \mathcal{X}_n} [T(X)] = \sum_{X \in \mathcal{X}_n} T(X) \cdot P(X)$$

# Average-case Analysis of Quicksort

$$A(n) = n - 1 + \frac{1}{n} \sum_{i=0}^{i=n-1} (A(i) + A(n - i - 1))$$

$$A(n) = \mathbb{E}_{X \in \mathcal{X}_n} [T(X)] = \sum_{X \in \mathcal{X}_n} T(X) \cdot P(X)$$

$$\begin{aligned} A(n) &= \mathbb{E}[T(X)] \\ &= \mathbb{E}[\mathbb{E}[T(X)|I]] \\ &= \sum_{i=0}^{i=n-1} P(I = i) \mathbb{E}[T(X) \mid I = i] \\ &= \sum_{i=0}^{i=n-1} \frac{1}{n} [n - 1 + A(i) + A(n - i - 1)] \end{aligned}$$