

Sorting, Searching, and Amortized Analysis

Hengfeng Wei

hfwei@nju.edu.cn

April 24, 2018



Maximal-sum Subarray (Problem 3.7)

- ▶ Array $A[1 \cdots n]$, $a_i \geq 0$
- ▶ To find (the sum of) an MS in A

$$A[-2, 1, -3, \boxed{4, -1, 2, 1}, -5, 4]$$

$MSS[i]$: the sum of the MS ($MS[i]$) in $A[1 \cdots i]$

$MSS[i]$: the sum of the MS ($MS[i]$) in $A[1 \cdots i]$

$$mss = MSS[n]$$

$MSS[i]$: the sum of the MS ($MS[i]$) in $A[1 \cdots i]$

$$mss = MSS[n]$$

Q : Is $a_i \in MS[i]$?

$MSS[i]$: the sum of the MS ($MS[i]$) in $A[1 \cdots i]$

$$mss = MSS[n]$$

Q : Is $a_i \in MS[i]$?

$$MSS[i] = \max\{MSS[i-1], ???\}$$

$MSS[i]$: the sum of the MS *ending with* a_i or 0

$MSS[i]$: the sum of the MS *ending with* a_i or 0

$$mss = \max_{1 \leq i \leq n} MSS[i]$$

Q: where does the $MS[i]$ start?

$MSS[i]$: the sum of the MS *ending with* a_i or 0

$$mss = \max_{1 \leq i \leq n} MSS[i]$$

Q : where does the $MS[i]$ start?

$$MSS[i] = \max \{MSS[i - 1] + a_i, 0\}$$

$MSS[i]$: the sum of the MS *ending with* a_i or 0


$$mss = \max_{1 \leq i \leq n} MSS[i]$$

Q : where does the $MS[i]$ start?


$$MSS[i] = \max \{MSS[i - 1] + a_i, 0\}$$

$$MSS[0] = 0$$

```
1: procedure MSS( $A[1 \cdots n]$ )
2:   MSS[0]  $\leftarrow$  0
3:   for  $i \leftarrow 1$  to  $n$  do
4:     MSS[ $i$ ]  $\leftarrow$   $\max \{ \text{MSS}[i - 1] + A[i], 0 \}$ 
5:   return  $\max_{1 \leq i \leq n} \text{MSS}[i]$ 
```




Ulf Grenander $O(n^3) \implies O(n^2)$



Ulf Grenander $O(n^3) \implies O(n^2)$


Michael Shamos $O(n \log n)$, onenight



Ulf Grenander $O(n^3) \implies O(n^2)$

Michael Shamos $O(n \log n)$, onenight

Jon Bentley Conjecture: $\Omega(n \log n)$




Ulf Grenander $O(n^3) \implies O(n^2)$

Michael Shamos $O(n \log n)$, onenight

Jon Bentley Conjecture: $\Omega(n \log n)$

Michael Shamos Carnegie Mellon seminar




Ulf Grenander $O(n^3) \implies O(n^2)$

Michael Shamos $O(n \log n)$, onenight

Jon Bentley Conjecture: $\Omega(n \log n)$

Michael Shamos Carnegie Mellon seminar

Jay Kadane $O(n)$,



Ulf Grenander $O(n^3) \implies O(n^2)$

Michael Shamos $O(n \log n)$, onenight

Jon Bentley Conjecture: $\Omega(n \log n)$

Michael Shamos Carnegie Mellon seminar

Jay Kadane $O(n)$, ≤ 1 minute

Definition (K -sorting (Problem 6.8))

An array $A[1 \cdots n]$ is *k -sorted* if it can be divided into k blocks, each of size n/k (we assume that $n/k \in \mathbb{N}$), such that the elements in each block are larger than the elements in earlier blocks and smaller than elements in later blocks. The elements within each block need *not* be sorted.

$$n = 16, k = 4, \frac{n}{k} = 4$$

1, 2, 4, 3; 7, 6, 8, 5; 10, 11, 9, 12; 15, 13, 16, 14

k -sorted

k -sorted

1-sorted

k -sorted

1-sorted \rightarrow 2-sorted

k -sorted

1-sorted \rightarrow 2-sorted \rightarrow 4-sorted

k -sorted

1-sorted \rightarrow 2-sorted \rightarrow 4-sorted $\rightarrow \cdots \rightarrow n$ -sorted

k -sorted

1-sorted \rightarrow 2-sorted \rightarrow 4-sorted $\rightarrow \dots \rightarrow n$ -sorted

Quicksort (with median as pivot) stops after the $\log k$ recursions.

k -sorted

1-sorted \rightarrow 2-sorted \rightarrow 4-sorted $\rightarrow \dots \rightarrow n$ -sorted

Quicksort (with median as pivot) stops after the $\log k$ recursions.

$$\Theta(n \log k)$$

$$\Omega(n \log k)$$

$$\Omega(n \log k)$$

$$L =$$

$$\Omega(n \log k)$$

$$L = \binom{n}{n/k, \dots, n/k}$$

$$\Omega(n \log k)$$

$$L = \binom{n}{n/k, \dots, n/k} = \frac{n!}{((\frac{n}{k})!)^k}$$

$$\Omega(n \log k)$$

$$L = \binom{n}{n/k, \dots, n/k} = \frac{n!}{((\frac{n}{k})!)^k}$$

$$H \geq$$

$$\Omega(n \log k)$$

$$L = \binom{n}{n/k, \dots, n/k} = \frac{n!}{((\frac{n}{k})!)^k}$$

$$H \geq \log \left(\frac{n!}{((\frac{n}{k})!)^k} \right)$$

$$\Omega(n \log k)$$

$$L = \binom{n}{n/k, \dots, n/k} = \frac{n!}{((\frac{n}{k})!)^k}$$

$$H \geq \log \left(\frac{n!}{((\frac{n}{k})!)^k} \right)$$

$$n! \sim \sqrt{2\pi n} \left(\frac{n}{e}\right)^n \implies \log n! \sim n \log n$$

Bolts and Nuts (Problem 6.9)



Bolts and Nuts (Problem 6.9)



Quicksort

Bolts and Nuts (Problem 6.9)



Quicksort

$$A(n) = O(n \log n)$$

Bolts and Nuts (Problem 6.9)



Quicksort

$$A(n) = O(n \log n)$$

In the worst case:

- ▶ “Matching Nuts and Bolts” by Alon *et al.*, $\Theta(n \log^4 n)$
- ▶ “Matching Nuts and Bolts Optimality” by Bradford, 1995, $\Theta(n \log n)$



$$\Omega(n \log n)$$



$$\Omega(n \log n)$$

$$3^H \geq L \geq n!$$



$$\Omega(n \log n)$$

$$3^H \geq L \geq n! \implies H \geq \log n! \implies H = \Omega(n \log n)$$

Repeated elements (Problem 2.12)

$$R[1 \dots n]$$

$$\# > \frac{n}{13}$$

Repeated elements (Problem 2.12)

$$R[1 \dots n]$$

$$\# > \frac{n}{13}$$

$\text{check}(R[i], R[j])$

$$\# > \frac{n}{k}$$

$$\# > \frac{n}{k}$$

An $O(n \log k)$ algorithm

$$\# > \frac{n}{k}$$

An $O(n \log k)$ algorithm

Lower bound $\Omega(n \log k)$

$$\# > \frac{n}{k}$$

An $O(n \log k)$ algorithm

Lower bound $\Omega(n \log k)$

L : # of leaves?

$$\# > \frac{n}{k}$$

An $O(n \log k)$ algorithm

Lower bound $\Omega(n \log k)$

L : # of leaves?

“Finding Repeated Elements” by Misra & Gries, 1982

Amortized analysis is
an algorithm analysis technique for
analyzing a sequence of operations
irrespective of the input to show that
the average cost per operation is small, even though
a single operation within the sequence might be expensive.

The Summation Method

$$o_1, o_2, \dots, o_n$$

$$c_1, c_2, \dots, c_n$$

The Summation Method

$$o_1, o_2, \dots, o_n$$

$$c_1, c_2, \dots, c_n$$

$$\forall i, \hat{c}_i = \frac{\left(\sum_{i=1}^n c_i \right)}{n}$$

The Summation Method for Array Doubling

The Summation Method for Array Doubling

On **any sequence** of n INSERTs on an **initially empty** array.

The Summation Method for Array Doubling

On **any sequence** of n INSERTs on an **initially empty** array.

$o_i :$	o_1	o_2	o_3	o_4	o_5	o_6	o_7	o_8	o_9	o_{10}
$c_i :$	1	2	3	1	5	1	1	1	9	1

The Summation Method for Array Doubling

On **any sequence** of n INSERTs on an **initially empty** array.

$$\begin{array}{cccccccccc} o_i : & o_1 & o_2 & o_3 & o_4 & o_5 & o_6 & o_7 & o_8 & o_9 & o_{10} \\ c_i : & 1 & 2 & 3 & 1 & 5 & 1 & 1 & 1 & 9 & 1 \end{array}$$

$$c_i = \begin{cases} (i-1) + 1 = i & \text{if } i-1 \text{ is an exact power of 2} \\ 1 & \text{o.w.} \end{cases}$$

The Summation Method for Array Doubling

On **any sequence** of n INSERTs on an **initially empty** array.

$$\begin{array}{cccccccccc} o_i : & o_1 & o_2 & o_3 & o_4 & o_5 & o_6 & o_7 & o_8 & o_9 & o_{10} \\ c_i : & 1 & 2 & 3 & 1 & 5 & 1 & 1 & 1 & 9 & 1 \end{array}$$

$$c_i = \begin{cases} (i-1) + 1 = i & \text{if } i-1 \text{ is an exact power of 2} \\ 1 & \text{o.w.} \end{cases}$$

$$\sum_{i=1}^n c_i \leq n + \sum_{j=0}^{\lceil \lg n \rceil - 1} 2^j = n + (2^{\lceil \lg n \rceil} - 1) \leq n + 2n = 3n$$

The Summation Method for Array Doubling

On **any sequence** of n INSERTs on an **initially empty** array.

$$\begin{array}{lcl} o_i : & o_1 & o_2 \quad o_3 \quad o_4 \quad o_5 \quad o_6 \quad o_7 \quad o_8 \quad o_9 \quad o_{10} \\ c_i : & 1 & 2 \quad 3 \quad 1 \quad 5 \quad 1 \quad 1 \quad 1 \quad 9 \quad 1 \end{array}$$

$$c_i = \begin{cases} (i-1) + 1 = i & \text{if } i-1 \text{ is an exact power of 2} \\ 1 & \text{o.w.} \end{cases}$$

$$\sum_{i=1}^n c_i \leq n + \sum_{j=0}^{\lceil \lg n \rceil - 1} 2^j = n + (2^{\lceil \lg n \rceil} - 1) \leq n + 2n = 3n$$

$$\boxed{\forall i, \hat{c}_i = 3}$$

The Accounting Method

$$o_1, o_2, \dots, o_n$$

$$c_1, c_2, \dots, c_n$$

$$a_1, a_2, \dots, a_n$$

The Accounting Method

$$o_1, o_2, \dots, o_n$$

$$c_1, c_2, \dots, c_n$$

$$a_1, a_2, \dots, a_n$$

$$\hat{c}_i = c_i + a_i, \quad a_i \geq 0$$

Amortized Cost = Actual Cost + Accounting Cost

The Accounting Method

$$O_1, O_2, \dots, O_n$$

$$C_1, C_2, \dots, C_n$$

$$a_1, a_2, \dots, a_n$$

$$\hat{c}_i = c_i + a_i, a_i \geq 0$$

Amortized Cost = Actual Cost + Accounting Cost

$$\forall n, \sum_{i=1}^n c_i \leq \sum_{i=1}^n \hat{c}_i$$

The Accounting Method

$$O_1, O_2, \dots, O_n$$

$$C_1, C_2, \dots, C_n$$

$$a_1, a_2, \dots, a_n$$

$$\hat{c}_i = c_i + a_i, \quad a_i \geq 0$$

Amortized Cost = Actual Cost + Accounting Cost

$$\forall n, \sum_{i=1}^n c_i \leq \sum_{i=1}^n \hat{c}_i \implies \forall n, \sum_{i=1}^n a_i \geq 0$$

The Accounting Method

$$O_1, O_2, \dots, O_n$$

$$c_1, c_2, \dots, c_n$$

$$a_1, a_2, \dots, a_n$$

$$\hat{c}_i = c_i + a_i, \quad a_i \geq 0$$

Amortized Cost = Actual Cost + Accounting Cost

$$\forall n, \sum_{i=1}^n c_i \leq \sum_{i=1}^n \hat{c}_i \implies \forall n, \sum_{i=1}^n a_i \geq 0$$

Key Point: Put the accounting cost on specific objects.

The Accounting Method for Array Doubling

$$Q : \hat{c}_i = 3 \text{ vs. } \hat{c}_i = 2$$

The Accounting Method for Array Doubling

$Q : \hat{c}_i = 3$ vs. $\hat{c}_i = 2$

$$\hat{c}_i = 3 = \underbrace{1}_{\text{insert}} + \underbrace{1}_{\text{move itself}} + \underbrace{1}_{\text{help move another}}$$

The Accounting Method for Array Doubling

$Q : \hat{c}_i = 3 \text{ vs. } \hat{c}_i = 2$

$$\hat{c}_i = 3 = \underbrace{1}_{\text{insert}} + \underbrace{1}_{\text{move itself}} + \underbrace{1}_{\text{help move another}}$$

	\hat{c}_i	c_i (<i>actual cost</i>)	a_i (<i>accounting cost</i>)
INSERT (<i>normal</i>)	3	1	2
INSERT (<i>expansion</i>)	3	$1 + t$	$-t + 2$

Simulating a queue Q using two stacks S_1, S_2 (Problem)

procedure ENQ(x)

Push(S_1, x)

procedure DEQ()

if $S_2 = \emptyset$ **then**

while $S_1 \neq \emptyset$ **do**

Push($S_2, \text{Pop}(S_1)$)

Pop(S_2)

The Summation Method for Queue Simulation

$$\frac{\left(\sum_{i=1}^n c_i \right)}{n}$$

The Summation Method for Queue Simulation

$$\frac{\left(\sum_{i=1}^n c_i \right)}{n}$$

The operation sequence is *NOT* known.

The Accounting Method for Queue Simulation

<i>item:</i>	Push into S_1	Pop from S_1	Push into S_2	Pop from S_2
	1	1	1	1

The Accounting Method for Queue Simulation

<i>item:</i>	Push into S_1	Pop from S_1	Push into S_2	Pop from S_2
	1	1	1	1

$$\hat{c}_{\text{ENQ}} = 3$$

$$\hat{c}_{\text{DEQ}} = 1$$

The Accounting Method for Queue Simulation

<i>item:</i>	Push into S_1	Pop from S_1	Push into S_2	Pop from S_2
	1	1	1	1

$$\hat{c}_{\text{ENQ}} = 3$$

$$\hat{c}_{\text{DEQ}} = 1$$

$$\sum_{i=1}^n a_i \geq 0$$

The Accounting Method for Queue Simulation

item: Push into S_1 Pop from S_1 Push into S_2 Pop from S_2
 1 1 1 1

$$\hat{c}_{\text{ENQ}} = 3$$

$$\hat{c}_{\text{DEQ}} = 1$$

$$\sum_{i=1}^n a_i \geq 0 \iff \sum_{i=1}^n a_i = \#S_1 \times 2$$

The Accounting Method for Queue Simulation

$$\hat{c}_{\text{ENQ}} = 3$$

$$\hat{c}_{\text{DEQ}} = 1$$

$$\#S_1 = t$$

	\hat{c}_i	c_i (<i>actual cost</i>)	a_i (<i>accounting cost</i>)
ENQUEUE	3	1	2
DEQUEUE ($S_2 = \emptyset$)	1	1	0
DEQUEUE ($S_2 \neq \emptyset$)	1	$1 + 2t$	$-2t$

Thank
You!



Office 302

Mailbox: H016

hfwei@nju.edu.cn