
Bitonic tour

From Wikipedia, the free encyclopedia

In computational geometry, a **bitonic tour** of a set of point sites in the Euclidean plane is a closed polygonal chain that has each site as one of its vertices, such that any vertical line crosses the chain at most twice.

Contents

- 1 Optimal bitonic tours
- 2 Properties
- 3 Other optimization criteria
- 4 References



Optimal bitonic tours

The **optimal bitonic tour** is a bitonic tour of minimum total length. It is a standard exercise in dynamic programming to devise a polynomial time algorithm that constructs the optimal bitonic tour.^{[1][2]}

The problem of constructing optimal bitonic tours is often credited to Jon L. Bentley, who published in 1990 an experimental comparison of many heuristics for the traveling salesman problem;^[3] however, Bentley's experiments do not include bitonic tours. The first publication that describes the bitonic tour problem appears to be a different 1990 publication, the first edition of the textbook *Introduction to Algorithms* by Thomas H. Cormen, Charles E. Leiserson, and Ron Rivest, which lists Bentley as the originator of the problem.

Properties

The optimal bitonic tour has no self-crossings, because any two edges that cross can be replaced by an uncrossed pair of edges with shorter total length.

When compared to other tours that might not be bitonic, the optimal bitonic tour is the one that minimizes the total amount of horizontal motion, with ties broken by Euclidean distance.^[4]

Other optimization criteria

The same dynamic programming algorithm that finds the optimal bitonic tour may be used to solve other variants of the traveling salesman problem that minimize lexicographic combinations of motion in a fixed number of coordinate directions.^[4]

At the 5th International Olympiad in Informatics, in Mendoza, Argentina in 1993, one of the contest problems involved bitonic tours: the contestants were to devise an algorithm that took as input a set of sites and a collection of allowed edges between sites and construct a bitonic tour using those edges that included as many sites as possible. As with the optimal bitonic tour, this problem may be solved by dynamic programming. [5][6]

References

- 1. *Introduction to Algorithms*, 3rd ed., T. H. Cormen, C. E. Leiserson, R. Rivest, and C. Stein, MIT Press, 2009. Problem 15-3, p. 405.
- 2. Bird, Richard S.; De Moor Oege (1997), The Algebra of Programming, Prentice Hall, p. 213, ISBN 9780135072455.

- 3. Bentley, Jon L. (1990), "Experiments on traveling salesman heuristics" *Proc. 1st ACM-SIAM Symp. Discrete Algorithms (SODA)* (http://portal.acm.org/citation.cfm?id=320186) pp. 91–99.
- 4. Sourd, Francis (2010), "Lexicographically minimizing axial motions for the Euclidean TSP*Journal of Combinatorial Optimization,* **19** (1): 1–15, MR 2579501 (https://www.ams.org/mathscinet-getitem?mr=2579501) doi:10.1007/s10878-008-9154-0 (https://doi.org/10.1007%2Fs10878-008-9154-0)
- 5. IOI'93 (http://olympiads.win.tue.nl/ioi/ioi93/index.html)contest problems and report.
- 6. Guerreiro, Pedro (December 2003), The Canadian Airline Problem and the Bitonic Tour: Is This Dynamic Programming? (http://www.researchgate.net/publication/22839119_The_Canadian_Airline_Problem_and_the_Bitonic _Tour_Is_This_Dynamic_Programming/file/79e4150c0f0cb543bd.pdf(PDF), Departamento de Informática, Faculdade de Ciências e Tecnologia, Universidade Nova de Lisboa

Retrieved from "https://en.wikipedia.org/w/index.php?title=Bitonic tour&oldid=602145829"

Categories: Geometric algorithms | Dynamic programming

- This page was last edited on 2014-04-01, at 02:24:07.
- Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.