

三、语义分析


(1. 符号表)

魏恒峰


hfwei@nju.edu.cn

2023 年 04 月 12 日





符号表



Definition (符号表 (Symbol Table))

符号表是用于保存**各种信息**的**数据结构**。

Definition (符号表 (Symbol Table))


符号表是用于保存**各种信息**的**数据结构**。

Name	Type	Size	Dimension	Line of Declaration	Line of Usage	Address	...
<i>count</i>	int	4	0
<i>str</i>	char[]	5	1

“领域特定语言” (DSL) 通常只有**单作用域** (全局作用域)

```
host=antlr.org  
port=80  
webmaster=parrt@antlr.org
```

“通用程序设计语言” (GPL) 通常需要**嵌套作用域**




```
1 int x;  
  int y;  
2 void a()  
3 {  
    int x;  
    x = 1;  
    y = 2;  
4    { int y = x; }  
    }  
5 void b(int z)  
6 { }
```

```

1 int x;
  int y;
2 void a()
3 {
    int x;
    x = 1;
    y = 2;
4    { int y = x; }
5 void b(int z)
6 { }


```




```

1 int x;
  int y;
2 void a()
3 {
    int x;
    x = 1;
    y = 2;
4    { int y = x; }
5 void b(int z)
6 { }


```



We take a **WRONG** assumption here about FunctionSymbol's scope.

```
public interface Scope {  
    public String getScopeName();           // 有名称吗?  
    public Scope getEnclosingScope();       // 有外部作用域吗?  
    public void define(Symbol sym);          // 在作用域中定义符号  
    public Symbol resolve(String name);      // 根据名称查找  
}
```



全局作用域、函数/方法作用域、局部作用域




```

1 int x;
  int y;
2 void a()
3 {
    int x;
    x = 1;
    y = 2;
4     { int y = x; }
5 }
6 void b(int z)
7 { }



```







Scope	
(m)	<code>setName(String)</code> void
(m)	<code>getSymbols()</code> Map<String, Symbol>
(m)	<code>getEnclosingScope()</code> Scope
(m)	<code>define(Symbol)</code> void
(m)	<code>getName()</code> String
(m)	<code>resolve(String)</code> Symbol

  SymbolTableListener

SymbolTableListener


SymbolTableListener	
f	currentScope Scope
f	globalScope GlobalScope
f	graph SymbolTableTreeGraph
f	localScopeCounter int

SymbolTableListener

f	currentScope	Scope
f	globalScope	GlobalScope
f	graph	SymbolTableTreeGraph
f	localScopeCounter	int
m	enterBlock(BlockContext)	void
m	enterFunctionDecl(FunctionDeclContext)	void
m	enterProg(ProgContext)	void
m	exitBlock(BlockContext)	void
m	exitFormalParameter(FormalParameterContext)	void
m	exitFunctionDecl(FunctionDeclContext)	void
m	exitId(IdContext)	void
m	exitProg(ProgContext)	void
m	exitVarDecl(VarDeclContext)	void
m	getGraph()	SymbolTableTreeGraph


struct/class: 类型作用域

```
①  
② struct A {  
③     int x;  
④     struct B { int y; };  
⑤     B b;  
⑥     struct C {int z; };  
⑦     C c;  
};  
A a;  
  
⑧ void f()  
⑨ {  
⑩     struct D {  
⑪         int i;  
⑫     };  
⑬     D d;  
⑭     d.i = a.b.y;  
⑮ }
```




d.i *a.b.y*

第 6 章: 记录并识别程序中的符号



第 7 章: 管理数据聚集的符号表




第 8.4 节: 验证程序中符号的使用

symtab @ antlr by parrt

symtab @ cs652 by parrt

Thank
You!



Office 926

hfwei@nju.edu.cn