

Search

Go

Training | Contact

Publications The C Book **Preface Introduction** Variables & <u>arithm</u>etic Control flow **Functions Arrays & pointers** Opening shots **Arrays Pointers** Character handling Sizeof & malloc **Function pointers Pointer expressions** Arrays & address-of **Summary Exercises Structures Preprocessor Specialized areas** Libraries **Complete Programs** <u>Answers</u>

Contact Us

Copyright

<u>Publications</u> > <u>The C Book</u> > <u>Arrays & pointers</u> > Function pointers

5.6. Pointers to functions

A useful technique is the ability to have pointers to functions. Their declaration is easy: write the declaration as it would be for the function, say

```
int func(int a, float b);
```

and simply put brackets around the name and a * in front of it: that declares the pointer. Because of precedence, if you don't parenthesize the name, you declare a function returning a pointer:

```
/* function returning pointer to int */
int *func(int a, float b);

/* pointer to function returning int */
int (*func)(int a, float b);
```

Once you've got the pointer, you can assign the address of the right sort of function just by using its name: like an array, a function name is turned into an address when it's used in an expression. You can call the function using one of two forms:

```
(*func) (1, 2);
/* or */
func(1, 2);
```

The second form has been newly blessed by the Standard. Here's a simple example.

```
#include <stdio.h>
#include <stdib.h>

void func(int);

main() {
    void (*fp)(int);

    fp = func;
    (*fp)(1);
    fp(2);
```

Printer-friendly version

The C Book

This book is published as a matter of historical interest. Please read the copyright and disclaimer information.

GBdirect Ltd provides up-to-date training and consultancy in <u>C</u>, <u>Embedded C</u>, <u>C++</u> and a wide range of <u>other subjects based on open standards</u> if you happen to be interested.

```
exit(EXIT_SUCCESS);
}

void
func(int arg) {
    printf("%d\n", arg);
}
```

Example 5.16

If you like writing finite state machines, you might like to know that you can have an array of pointers to functions, with declaration and use like this:

About Us | Training | Consultancy | Software | Publications | Qpen Source | Support | Open Standards | FAQ | Jobs /* then call one */ fparr[5](1, 3.4);

Example 5.17

But we'll draw a veil over it at this point!

Previous section | Chapter contents | Next section