

[This was posted to comp.lang.c by its author, David Anderson, on 1994-05-06.]

# The ``Clockwise/Spiral Rule''

**By David Anderson**

There is a technique known as the ``Clockwise/Spiral Rule" which enables any C programmer to parse in their head any C declaration!

There are three simple steps to follow:

1. Starting with the unknown element, move in a spiral/clockwise direction; when encountering the following elements replace them with the corresponding english statements:

[X] or []

=> Array X size of... or Array undefined size of...

(type1, type2)

=> function passing type1 and type2 returning...

\*

=> pointer(s) to...

2. Keep doing this in a spiral/clockwise direction until all tokens have been covered.
3. Always resolve anything in parenthesis first!

## Example #1: Simple declaration

```
      +-----+
      |  +-+  |
      |  ^   |
char  | *str[10];
      |  ^   |
      |  +---+
      +-----+
```

Question we ask ourselves: What is str?

``str is an...

- We move in a spiral clockwise direction starting with `str' and the first character we see is a `[', so, that means we have an array, so...

``str is an array 10 of...

- Continue in a spiral clockwise direction, and the next thing we encounter is the `\*' so, that means we have pointers, so...

``str is an array 10 of pointers to...

- Continue in a spiral direction and we see the end of the line (the `;'), so keep going and we get to the type `char', so...

``str is an array 10 of pointers to char"

- We have now ``visited" every token; therefore we are done!

## Example #2: Pointer to Function declaration

```
+-----+
|       |
| +---+ |
| | +--+|
| | ^  | |
char *(*fp) ( int, float *);
| | +---+|
| | +-----+|
+-----+
```

Question we ask ourselves: What is fp?

``fp is a...

- Moving in a spiral clockwise direction, the first thing we see is a `)`; therefore, fp is inside parenthesis, so we continue the spiral inside the parenthesis and the next character seen is the `\*`, so...

``fp is a pointer to...

- We are now out of the parenthesis and continuing in a spiral clockwise direction, we see the `(`; therefore, we have a function, so...

``fp is a pointer to a function passing an int and a pointer to float returning...

- Continuing in a spiral fashion, we then see the `\*` character, so...

``fp is a pointer to a function passing an int and a pointer to float returning a pointer to...

- Continuing in a spiral fashion we see the `;`, but we haven't visited all tokens, so we continue and finally get to the type `char`, so...

``fp is a pointer to a function passing an int and a pointer to float returning a pointer to a char"

## Example #3: The ``Ultimate"

```
+-----+
|       |               +---+
|       |               | +--+|
| +---+ |               | ^  | |
| ^  | |               void (*fp) (int));
| +-----+           +-----+
|               |               |
+-----+
```

Question we ask ourselves: What is `signal'?

Notice that signal is *inside* parenthesis, so we must resolve this first!

- Moving in a *clockwise* direction we see '(' so we have...

``signal is a function passing an int and a...

- Hmm, we can use this same rule on 'fp', so... What is fp? fp is also inside parenthesis so continuing we see an '\*', so...

fp is a pointer to...

- Continue in a spiral clockwise direction and we get to '(', so...

``fp is a pointer to a function passing int returning..."

- Now we continue out of the function parenthesis and we see void, so...

``fp is a pointer to a function passing int returning nothing (void)"

- We have finished with fp so let's catch up with 'signal', we now have...

``signal is a function passing an int and a pointer to a function passing an int returning nothing (void) returning...

- We are still inside parenthesis so the next character seen is a '\*', so...

``signal is a function passing an int and a pointer to a function passing an int returning nothing (void) returning a pointer to...

- We have now resolved the items within parenthesis, so continuing clockwise, we then see another '(', so...

``signal is a function passing an int and a pointer to a function passing an int returning nothing (void) returning a pointer to a function passing an int returning...

- *Finally* we continue and the only thing left is the word 'void', so the final complete definition for signal is:

``signal is a function passing an int and a pointer to a function passing an int returning nothing (void) returning a pointer to a function passing an int returning nothing (void)"

The same rule is applied for const and volatile. For Example:

```
const char *chptr;
```

- Now, what is chptr??

``chptr is a pointer to a char constant"

How about this one:

```
char * const chptr;
```

- Now, what is chptr??

``chptr is a constant pointer to char"

Finally:

```
volatile char * const chptr;
```

- Now, what is chptr??

``chptr is a constant pointer to a char volatile."

Practice this rule with the examples found in K&R II on page 122.

---

Copyright © 1993,1994 David Anderson

This article may be freely distributed as long as the author's name and this notice are retained.

---