

2-11 Heapsort

Hengfeng Wei

hfwei@nju.edu.cn

June 20, 2018



O, Ω, Θ

O, Ω, Θ

“What is most efficient way to sort a million 32-bit integers?”

“The bubblesort would be the wrong way to go.”

反馈:

O, Ω, Θ 傻傻分不清。

什么时候用哪个?

6.2 – 6 这道题为什么问的是 Ω , 而不问 O 或 Θ ?

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

MOVE vs. COMPARE

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>			
<i>Worst-case</i>			
<i>Average-case</i>			

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>			$O = \Omega$
<i>Worst-case</i>			$O = \Omega$
<i>Average-case</i>			$O = \Omega$

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$
<i>Worst-case</i>			$O = \Omega$
<i>Average-case</i>			$O = \Omega$

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$
<i>Worst-case</i>	"power" of \mathcal{A}	by example	$O = \Omega$
<i>Average-case</i>			$O = \Omega$

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$
<i>Worst-case</i>	"power" of \mathcal{A}	by example	$O = \Omega$
<i>Average-case</i>	\leq	\geq	$O = \Omega$

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)


Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

By Example.

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

By Example.




Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $O(\log n)$.

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)


Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $O(\log n)$.



$$W(n) \leq H(n)$$

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $O(\log n)$.



$$W(n) \leq H(n)$$

No Examples Here!

Therefore . . .

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Theta(\log n)$.

	O	Ω	Θ
<i>Worst-case</i>	“power” of \mathcal{A}	by example	$O = \Omega$

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.

By Example.

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.

By Example.

Non-proof.

$$\underbrace{\Theta(n)}_{\text{EXTRACT-MAX}} \times \underbrace{\Omega(\log n)}_{\text{MAX-HEAPIFY}} = \Omega(n \log n)$$




Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.




Heap in decreasing order?


Heap in decreasing order?




Heap in decreasing order?




$$T(7) = 2 + 1 + 1 + 1 + 0 + 0 = 5$$






$$T(7) = 2 + 2 + 2 + 1 + 1 + 0 = 8$$




$$T(7) = 2 + 2 + 2 + 1 + 1 + 0 = 8$$


(Ex. 23, Section 5.2.3, TAOCP Vol 3)



$$T(7) = 2 + 2 + 2 + 1 + 1 + 0 = 8$$

(Ex. 23, Section 5.2.3, TAOCP Vol 3)







$$T(7) = 2 + 2 + 2 + 1 + 1 + 0 = 8$$

(Ex. 23, Section 5.2.3, TAOCP Vol 3)


$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor$$






$$T(7) = 2 + 2 + 2 + 1 + 1 + 0 = 8$$

(Ex. 23, Section 5.2.3, TAOCP Vol 3)




$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2$$



$$T(7) = 2 + 2 + 2 + 1 + 1 + 0 = 8$$

(Ex. 23, Section 5.2.3, TAOCP Vol 3)



$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = \Omega(n \log n)$$

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = O(n \log n)$$

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = O(n \log n)$$

No Examples Here!

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = O(n \log n)$$

No Examples Here!

$$\underbrace{\Theta(n)}_{\text{EXTRACT-MAX}} \times \underbrace{O(\log n)}_{\text{MAX-HEAPIFY}} = O(n \log n)$$

Therefore...

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Theta(n \log n)$.

	O	Ω	Θ
<i>Worst-case</i>	"power" of \mathcal{A}	by example	$O = \Omega$

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

$\geq \lfloor m/2 \rfloor$ of m must be nonleaves of that subtree.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

$\geq \lfloor m/2 \rfloor$ of m must be nonleaves of that subtree.

$\geq \lfloor m/2 \rfloor$ of m appear in the first $\lfloor n/2 \rfloor$ positions.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

$\geq \lfloor m/2 \rfloor$ of m must be nonleaves of that subtree.

$\geq \lfloor m/2 \rfloor$ of m appear in the first $\lfloor n/2 \rfloor$ positions.

They must be promoted to the root before being EXTRACT-MAX.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

$\geq \lfloor m/2 \rfloor$ of m must be nonleaves of that subtree.

$\geq \lfloor m/2 \rfloor$ of m appear in the first $\lfloor n/2 \rfloor$ positions.

They must be promoted to the root before being EXTRACT-MAX.

$$\sum_{k=1}^{\lfloor m/2 \rfloor} \lfloor \log k \rfloor = \frac{1}{2} m \log m + O(m)$$

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

$\geq \lfloor m/2 \rfloor$ of m must be nonleaves of that subtree.

$\geq \lfloor m/2 \rfloor$ of m appear in the first $\lfloor n/2 \rfloor$ positions.

They must be promoted to the root before being EXTRACT-MAX.

$$\sum_{k=1}^{\lfloor m/2 \rfloor} \lfloor \log k \rfloor = \frac{1}{2} m \log m + O(m)$$

$$B(n) \geq \frac{1}{4} n \log n + O(n) + B(\lfloor n/2 \rfloor)$$

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Consider the largest $m = \lceil n/2 \rceil$ elements.

The largest m elements form a subtree.

$\geq \lfloor m/2 \rfloor$ of m must be nonleaves of that subtree.

$\geq \lfloor m/2 \rfloor$ of m appear in the first $\lfloor n/2 \rfloor$ positions.

They must be promoted to the root before being EXTRACT-MAX.

$$\sum_{k=1}^{\lfloor m/2 \rfloor} \lfloor \log k \rfloor = \frac{1}{2} m \log m + O(m)$$

$$B(n) \geq \frac{1}{4} n \log n + O(n) + B(\lfloor n/2 \rfloor) \implies B(n) \geq \frac{1}{2} n \log n + O(n)$$

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $O(n \log n)$.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $O(n \log n)$.

By Example.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $O(n \log n)$.

By Example.



“On the Best Case of Heapsort” (1994)




FIG. 2. Initial heap (more detailed).




FIG. 3. (a) Odd i ; (b) contents of the bottom level of τ_{2i-1} , i odd.




FIG. 4. (a) Even i ; (b) contents of the bottom level of τ_{2i-1} , i even.

"On the Best Case of Heapsort" (1994)




FIG. 2. Initial heap (more detailed)




FIG. 3. (a) Odd i ; (b) contents of the bottom level of π_{3i-1} , i odd




FIG. 4. (a) Even; (b) contents of the bottom level of π_{i-1} even

$$B(n) \leq \frac{1}{2}n \log n + O(n \log \log n)$$

Therefore...

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $\Theta(n \log n)$.


	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$

Average-case of HEAPSORT

Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.


Average-case of HEAPSORT

Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.



Average-case of HEAPSORT

Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.



I said simple,
not easy.

“By a surprisingly short counting argument.”



Robert Sedgewick

“By a surprisingly short counting argument.”



Robert Sedgwick



D. E. Knuth

“It is elegant.”

“By a surprisingly short counting argument.”



Robert Sedgwick



D. E. Knuth

“It is elegant. see exercise 30.”

$f(n) \triangleq \# \text{ of heaps of } n \text{ distinct keys } [1 \cdots n]$

$f(n) \triangleq \# \text{ of heaps of } n \text{ distinct keys } [1 \cdots n]$

$$f(n) = \binom{n-1}{m} f(m) f(n-1-m)$$

$f(n) \triangleq$ # of heaps of n distinct keys $[1 \cdots n]$

$$f(n) = \binom{n-1}{m} f(m) f(n-1-m)$$

$$\frac{f(n)}{n!} = \frac{1}{n} \frac{f(m)}{m!} \frac{f(n-1-m)}{(n-1-m)!}$$


$f(n) \triangleq$ # of heaps of n distinct keys $[1 \cdots n]$

$$f(n) = \binom{n-1}{m} f(m) f(n-1-m)$$

$$\frac{f(n)}{n!} = \frac{1}{n} \frac{f(m)}{m!} \frac{f(n-1-m)}{(n-1-m)!}$$

$$f(n) = \frac{n!}{\prod_{1 \leq i \leq n} s_i}$$

$s_i \triangleq$ size of the subtree rooted at i



$$f(13) = \frac{13!}{13 \cdot 7 \cdot 5 \cdot 3 \cdot 3 \cdot 3} = 506880$$

THE ANALYSIS OF HEAPSORT

Russel Schaffer
Robert Sedgewick

CS-TR-330-91

January 1991

Revised January 1992

On the Best Case of Heapsort*

B. Bollobás[†]

*Department of Pure Mathematics, University of Cambridge, Cambridge CB2 1TN,
United Kingdom*

T. I. Fenner

*Department of Computer Science, Birkbeck College, University of London, London
WC1E 7HX, United Kingdom*

and

A. M. Frieze[‡]

*Department of Mathematics, Carnegie Mellon University, Pittsburgh, Pennsylvania
15213*

Received August 14, 1991; revised July 24, 1994

Thank
You!



Office 302

Mailbox: H016

hfwei@nju.edu.cn