

## 2-9 Sorting and Selection

Hengfeng Wei

hfwei@nju.edu.cn

May 28, 2018



# How to Argue?



# How to Argue?



Show that ...

# How to Argue?



Show that ...

Argue that ...

# How to Argue?




Show that ...

Argue that ...


= Prove that ...



## QUICKSORT Invented by Tony Hoare in 1959/1960




## QUICKSORT Invented by Tony Hoare in 1959/1960



`null pointer`



## QUICKSORT Invented by Tony Hoare in 1959/1960



`null pointer`

*"I call it my billion-dollar mistake."*

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

$$T(n) = \min_{0 \leq q \leq n-1} \left( T(q) + T(n - q - 1) \right) + \Theta(n)$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

$$T(n) = \min_{0 \leq q \leq n-1} \left( T(q) + T(n - q - 1) \right) + \Theta(n)$$

$$T(n) = \Omega(n \log n)$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

$$T(n) = \min_{0 \leq q \leq n-1} \left( T(q) + T(n - q - 1) \right) + \Theta(n)$$

$$T(n) = \Omega(n \log n)$$

By substitution.

## Median-of-3 PARTITION (Problem 7 – 5)

**Argue that** in the  $\Omega(n \log n)$  running time of QUICKSORT, the *median-of-3* method affects only the constant factor.



## Median-of-3 PARTITION (Problem 7 – 5)

**Argue that** in the  $\Omega(n \log n)$  running time of QUICKSORT, the *median-of-3* method affects only the constant factor.



## Median-of-3 PARTITION (Problem 7 – 5)

**Argue that** in the  $\Omega(n \log n)$  running time of QUICKSORT, the *median-of-3* method affects only the constant factor.



$$T(n) = \min_{0 \leq q \leq n-1} (T(q) + T(n - q - 1)) + \Theta(n)$$

$$T(n) = \Omega(n \log n)$$




## The $\frac{n}{k}$ -sorted Problem (Problem 8.1 – 4)

Sorts an already  $\frac{n}{k}$ -sorted array

$n$  elements

$\frac{n}{k}$  blocks



$k$  elements

<


not sorted

## The $\frac{n}{k}$ -sorted Problem (Problem 8.1 – 4)

Sorts an already  $\frac{n}{k}$ -sorted array

$n$  elements

$\frac{n}{k}$  blocks



$k$  elements

<

not sorted


$$\Omega(n \log k)$$

## The $\frac{n}{k}$ -sorted Problem (Problem 8.1 – 4)

Sorts an already  $\frac{n}{k}$ -sorted array

$n$  elements

$\frac{n}{k}$  blocks



$k$  elements

<

not sorted

$\Omega(n \log k)$


$O(n \log k)$

## The $\frac{n}{k}$ -sorted Problem (Problem 8.1 – 4)

Sorts an already  $\frac{n}{k}$ -sorted array

$n$  elements

$\frac{n}{k}$  blocks




$k$  elements

not sorted

$$\Omega(n \log k) \quad O(n \log k)$$


$$(k!)^{\frac{n}{k}} \leq L \leq 2^H$$

$\frac{n}{k}$ -sorts an arbitrary array






$\frac{n}{k}$ -sorts an arbitrary array




$O(?)$

$\frac{n}{k}$ -sorts an arbitrary array



$O(?)$      $\Omega(?)$


$\frac{n}{k}$ -sorts an arbitrary array



$O(?)$      $\Omega(?)$

$$L \geq \binom{n}{\underbrace{k, \dots, k}_{\frac{n}{k}}} = \frac{n!}{(k!)^{\frac{n}{k}}}$$

$\frac{n}{k}$ -sorts an arbitrary array



$O(?)$      $\Omega(?)$

$$L \geq \binom{n}{\underbrace{k, \dots, k}_{\frac{n}{k}}} = \frac{n!}{(k!)^{\frac{n}{k}}} \implies \Omega(n \log(n/k))$$







Thank  
You!





Office 302

Mailbox: H016

hfwei@nju.edu.cn