

2-11 Heapsort

Hengfeng Wei

hfwei@nju.edu.cn

June 11, 2018





ALGORITHM 245
 TREESORT 3 [M1]
 ROBERT W. FLOYD (Recd. 22 June 1964 and 17 Aug. 1964)
 Computer Associates, Inc., Woburn, Mass.
 procedure TREESORT 3 (M, n);
 value n; array M; integer n;
 comment TREESORT 3 is a major revision of TREESORT
 [B. W. Floyd, Alg. 118, Comm. ACM 6 (Aug. 1963), 434] sug-
 gested by HEAPSORT [J. W. J. Williams, Alg. 232, Comm.
 ACM 7 (June 1964), 367] from which it differs in being as in place
 sort. It is shorter and probably faster, requiring fewer compar-
 isons and only one division. It sorts the array M[1:n], requiring
 in more than $2 \times (2^{1/p}-2) \times (p-1)$, or approximately $2 \times$
 $n \times (\log(n)-1)$ comparisons and half as many exchanges in
 the worst case to sort $n = 2^{1/p} - 1$ items. The algorithm is
 most easily followed if M is thought of as a tree, with M[i+j-2]
 the father of M[i] for $1 < j \leq n$.



Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

反馈: O, Θ, Ω 傻傻分不清。

什么时候用哪个?

这道题为什么问的是 Ω , 而不问 O 或 Θ ?

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>			
<i>Worst-case</i>			
<i>Average-case</i>			

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>			$O = \Omega$
<i>Worst-case</i>			$O = \Omega$
<i>Average-case</i>			$O = \Omega$

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$
<i>Worst-case</i>			$O = \Omega$
<i>Average-case</i>			$O = \Omega$

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$
<i>Worst-case</i>	"power" of \mathcal{A}	by example	$O = \Omega$
<i>Average-case</i>			$O = \Omega$

Algorithm \mathcal{A}

Inputs \mathcal{I} of size n

	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$
<i>Worst-case</i>	"power" of \mathcal{A}	by example	$O = \Omega$
<i>Average-case</i>	\leq	\geq	$O = \Omega$

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)


Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

By Example.

Worst-case of MAX-HEAPIFY (TC 6.2 – 6)

Show that the **worst-case** running time of MAX-HEAPIFY on an n -element heap is $\Omega(\log n)$.

By Example.



Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.

By Example.

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.

By Example.

Non-proof.

$$\underbrace{\Theta(n)}_{\text{EXTRACT-MAX}} \times \underbrace{\Omega(\log n)}_{\text{MAX-HEAPIFY}} = \Omega(n \log n)$$




Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Omega(n \log n)$.




Heap in decreasing order?

Heap in decreasing order?




Heap in decreasing order?




HARD.


Heap in decreasing order?




HARD.

$$T(12) = 3 + 2 + 2 + 2 + 2 + 2 + 2 + 1 + 1 + 0 + 0 + 0 = 17$$







(Ex. 23, Section 5.2.3, TAOCP Vol 3)




(Ex. 23, Section 5.2.3, TAOCP Vol 3)







(Ex. 23, Section 5.2.3, TAOCP Vol 3)




$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor$$




(Ex. 23, Section 5.2.3, TAOCP Vol 3)



$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2$$



(Ex. 23, Section 5.2.3, TAOCP Vol 3)



$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = \Omega n \log n$$

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = O(n \log n)$$

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = O(n \log n)$$

No Examples Needed!

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $O(n \log n)$.

$$\sum_{r=1}^{n-1} \lfloor \log r \rfloor = n \lfloor \log n \rfloor - 2^{\lfloor \log n \rfloor + 1} + 2 = O(n \log n)$$

No Examples Needed!

$$\underbrace{\Theta(n)}_{\text{EXTRACT-MAX}} \times \underbrace{O(\log n)}_{\text{MAX-HEAPIFY}} = O(n \log n)$$

Therefore...

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Theta(n \log n)$.

Therefore...

Worst-case of HEAPSORT (TC 6.4 – 4)

Show that the **worst-case** running time of HEAPSORT is $\Theta(n \log n)$.

	O	Ω	Θ
<i>Worst-case</i>	"power" of \mathcal{A}	by example	$O = \Omega$

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the best-case running time of HEAPSORT is $\Omega(n \log n)$.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $O(n \log n)$.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $O(n \log n)$.

By Example.

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $O(n \log n)$.

By Example.



Therefore . . .

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $\Theta(n \log n)$.

Therefore...

Best-case of HEAPSORT (TC 6.4 – 5)

Show that when all elements are distinct, the **best-case** running time of HEAPSORT is $\Theta(n \log n)$.


	O	Ω	Θ
<i>Best-case</i>	by example	"weakness" of \mathcal{A}	$O = \Omega$

Average-case of HEAPSORT

Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.

Average-case of HEAPSORT

Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.



Average-case of HEAPSORT


Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.



I said simple,
not easy.

Average-case of HEAPSORT

Assume that all elements are distinct. Show that the **average-case** running time of HEAPSORT is $\Theta(n \log n)$.



I said simple,
not easy.

By an elegant counting argument.

$f(n) \triangleq \# \text{ of heaps of } n \text{ distinct keys}$

$f(n) \triangleq \# \text{ of heaps of } n \text{ distinct keys}$

$$f(n) = \binom{n-1}{m} f(m) f(n-1-m)$$

$f(n) \triangleq \# \text{ of heaps of } n \text{ distinct keys}$

$$f(n) = \binom{n-1}{m} f(m) f(n-1-m)$$

$$\frac{f(n)}{n!} = \frac{1}{n} \frac{f(m)}{m!} \frac{f(n-1-m)}{(n-1-m)!}$$

$f(n) \triangleq \# \text{ of heaps of } n \text{ distinct keys}$

$$f(n) = \binom{n-1}{m} f(m) f(n-1-m)$$

$$\frac{f(n)}{n!} = \frac{1}{n} \frac{f(m)}{m!} \frac{f(n-1-m)}{(n-1-m)!}$$

$$f(n) = \frac{n!}{\prod_{1 \leq i \leq n} s_i}$$

$s_i \triangleq \text{size of the subtree rooted at } i$

$$f(13) = \frac{13!}{13 \cdot 7 \cdot 5 \cdot 3 \cdot 3 \cdot 3} = 506880$$

Thank
You!



Office 302

Mailbox: H016

hfwei@nju.edu.cn