

1-5 数据与数据结构 (I)

魏恒峰


hfwei@nju.edu.cn

2017 年 11 月 13 日




Stackable Permutations

Definition (Stackable Permutations)




Definition (Stackable Permutations)


$$\text{out} = (a_1, \dots, a_n) \xleftarrow[X=0]{S=\emptyset} \text{in} = (1, \dots, n)$$



Definition (Stackable Permutations)




Definition (Stackable Permutations)



Q_1 : Meaning of “read, print, push, pop”?

Definition (Stackable Permutations)




Q_1 : Meaning of “read, print, push, pop”?

Q_2 : Using **only** “read, print, push, pop”?

$$a == X$$

Definition (Stackable Permutations)




Q_1 : Meaning of “read, print, push, pop”?

Q_2 : Using **only** “read, print, push, pop”?

$$a == X \quad a > X \ (a < X)$$

Definition (Stackable Permutations)



Q_1 : Meaning of “read, print, push, pop”?

Q_2 : Using **only** “read, print, push, pop”?

$$a == X \quad a > X \ (a < X) \quad \text{top}(S)$$

DH 2.12: Stackable Permutations

(a) **Show** that the following permutations *are* stackable:

(i) $(3, 2, 1)$

(ii) $(3, 4, 2, 1)$

(iii) $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$

DH 2.12: Stackable Permutations

(a) **Show** that the following permutations *are* stackable:

- (i) $(3, 2, 1)$
- (ii) $(3, 4, 2, 1)$
- (iii) $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$

DH 2.12: Stackable Permutations

(a) **Show** that the following permutations *are* stackable:

- (i) $(3, 2, 1)$
- (ii) $(3, 4, 2, 1)$
- (iii) $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$



DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read print push pop is-empty

X = 0 S = \emptyset in \neq EOF

DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read print push pop is-empty

$X = 0$ $S = \emptyset$ in \neq EOF

```
foreach 'a' in out:
    if (! is-empty(S)
        && 'a' == top(S))
        pop(S, X)
        print(X)
        continue
    else ... // T.B.C
```

DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read print push pop is-empty

$X = 0$ $S = \emptyset$ in \neq EOF

```
foreach 'a' in out:
    if (! is-empty(S)
        && 'a' == top(S))
        pop(S, X)
        print(X)
        continue
    else ... // T.B.C
```

```
else // T.B.C
    while (in  $\neq$  EOF)
        read(X)
        if (X == 'a')
            print(X)
            continue
        else
            push(X, S)
ERR
```


DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read print push pop is-empty

$X = 0$ $S = \emptyset$ in \neq EOF

```
foreach 'a' in out:
    if (! is-empty(S)
        && 'a' == top(S))
        pop(S, X)
        print(X)
        continue
    else ... // T.B.C
```

```
else // T.B.C
    while (in  $\neq$  EOF)
        read(X)
        if (X == 'a')
            print(X)
            continue
        else
            push(X, S)
ERR // How???
```

DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) $(3, 1, 2)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$

DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) $(3, 1, 2)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$

DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) $(3, 1, 2)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$

DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) $(3, 1, 2)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$

$$\text{out} = \cdots a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) $(3, 1, 2)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$

$$\text{out} = \cdots a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

312-Pattern

Theorem (Stackable Permutations)

A permutation (a_1, \dots, a_n) is stackable \iff it is not the case that

312-Pattern : $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_j < a_k < a_i$

Theorem (Stackable Permutations)

A permutation (a_1, \dots, a_n) is stackable \iff it is not the case that

312-Pattern : $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_j < a_k < a_i$

Proof.



NO PROOF WARRANTY



DH 2.12: Stackable Permutations

(c) How many permutations of A_4 *cannot* be obtained by a stack?

$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$

DH 2.12: Stackable Permutations

(c) How many permutations of A_4 *cannot* be obtained by a stack?


$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$



DH 2.12: Stackable Permutations



(c) How many permutations of A_4 *cannot* be obtained by a stack?

$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$



Q : What about A_n ?









Q : Are $S + X$ and S are **equivalent**?





Q : Are $S + X$ and S are **equivalent**?



Q : Are $S + X$ and S are **equivalent**?



Producing the same set of permutations.





Q : Are $S + X$ and S are **equivalent**?



Producing the same set of permutations.

Accepting the same set of *admissible* operation sequences.







By simulations.



By simulations.

Simulate S by $S + X$:

- ▶ Push
- ▶ Pop





By simulations.

Simulate S by $S + X$:

- ▶ Push
- ▶ Pop

Simulate $S + X$ by S :



By simulations.


Simulate S by $S + X$:

- ▶ Push
- ▶ Pop

Simulate $S + X$ by S :

By iterative transformations.






(1, 2, 3) : Push Pop Push Pop Push Pop

(3, 2, 1) : Push Push Push Pop Pop Pop


DH 2.12: Stackable Permutations

How many permutations of $\{1 \cdots n\}$ are stackable on the model S ?



DH 2.12: Stackable Permutations

How many permutations of $\{1 \cdots n\}$ are stackable on the model S ?



Q : How many *admissible* operation sequences of "Push" and "Pop"?

Definition (Admissible Operation Sequences)

An operation sequence of “Push” and “Pop” is *admissible* if and only if

Definition (Admissible Operation Sequences)

An operation sequence of “Push” and “Pop” is *admissible* if and only if

$$(i) \quad \# \text{ of “Push”} = n \quad \# \text{ of “Pop”} = n$$

Definition (Admissible Operation Sequences)

An operation sequence of “Push” and “Pop” is *admissible* if and only if

- (i) # of “Push” = n # of “Pop” = n
- (ii) \forall prefix : (# of “Pop”) \leq (# of “Push”)

Definition (Admissible Operation Sequences)

An operation sequence of “Push” and “Pop” is *admissible* if and only if

- (i) # of “Push” = n # of “Pop” = n
- (ii) \forall prefix : (# of “Pop”) \leq (# of “Push”)

of stackable perms = # of admissible operation sequences

Definition (Admissible Operation Sequences)

An operation sequence of “Push” and “Pop” is *admissible* if and only if

- (i) # of “Push” = n # of “Pop” = n
- (ii) \forall prefix : (# of “Pop”) \leq (# of “Push”)

of stackable perms = # of admissible operation sequences



Theorem

Different admissible operation sequences correspond to different permutations.

Theorem

Different admissible operation sequences correspond to different permutations.

Proof.

Push Push Push Pop Pop **Push**...

Push Push Push Pop Pop **Pop**...



Theorem

The number of admissible operation sequences of “Push” and “Pop” is $\binom{2n}{n} - \binom{2n}{n-1}$.

Theorem

The number of admissible operation sequences of “Push” and “Pop” is $\binom{2n}{n} - \binom{2n}{n-1}$.

Proof: The Reflection Method.


Push : \rightarrow Pop : \uparrow

Theorem

The number of admissible operation sequences of "Push" and "Pop" is $\binom{2n}{n} - \binom{2n}{n-1}$.

Proof: The Reflection Method.

Push : \rightarrow Pop : \uparrow




Theorem

The number of admissible operation sequences of “Push” and “Pop” is $\binom{2n}{n} - \binom{2n}{n-1}$.

Proof: The Reflection Method.

Push : \rightarrow Pop : \uparrow




Theorem

The number of admissible operation sequences of “Push” and “Pop” is $\binom{2n}{n} - \binom{2n}{n-1}$.

Proof: The Reflection Method.

Push : \rightarrow Pop : \uparrow




Theorem


The number of admissible operation sequences of “Push” and “Pop” is $\binom{2n}{n} - \binom{2n}{n-1}$.


Proof: The Reflection Method.


Push : \rightarrow Pop : \uparrow





$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$






























Catalan Number

$(3, 2, 1) : ((()))$ $(1, 2, 3) : ()()()$

For more about “Stackable Permutations” (Section 2.2.1):



Thank
You!