

1-5 数据与数据结构 (II)

魏恒峰

hfwei@nju.edu.cn

2017 年 11 月 27 日







温故而知新


Stackable/Queueable Permutations

Treesort Algorithm on BST

Queueable Permutations




DH 2.14: Queueable Permutations



DH 2.14: Queueable Permutations

$$\text{out} = (a_1, \dots, a_n) \xrightleftharpoons[X=0]{Q=\emptyset} \text{in} = (1, \dots, n)$$



DH 2.14: Queueable Permutations

(a) Show that the permutations given in Exercise 2.12(b) are queueable.

(i) $(3, 1, 2) \implies (3, 2, 1)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$

DH 2.14: Queueable Permutations

(a) Show that the permutations given in Exercise 2.12(b) are queueable.

(i) $(3, 1, 2) \implies (3, 2, 1)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$



DH 2.14: Queueable Permutations

(a) Show that the permutations given in Exercise 2.12(b) are queueable.

(i) $(3, 1, 2) \implies (3, 2, 1)$

(ii) $(4, 5, 3, 7, 2, 1, 6)$



DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0  Q =  $\emptyset$   in != EOF
```

```
foreach 'a'  $\in$  out:
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0   Q =  $\emptyset$    in  $\neq$  EOF
```

```
foreach 'a'  $\in$  out:  
    if ('a' == in)  
        read(X)  
        print(X)
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0  Q =  $\emptyset$   in  $\neq$  EOF
```

```
foreach 'a'  $\in$  out:  
    if ('a' == in)  
        read(X)  
        print(X)  
    else if ('a' > in)  
        add-Q-till('a')
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0  Q =  $\emptyset$   in  $\neq$  EOF
```

```
foreach 'a'  $\in$  out:  
  if ('a' == in)  
    read(X)  
    print(X)  
  else if ('a' > in)  
    add-Q-till('a')  
  else // ('a' < in)  
    cycle-Q-till('a')
```


DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0   Q = {}   in != EOF
```

```
foreach 'a' ∈ out:
    if ('a' == in)
        read(X)
        print(X)
    else if ('a' > in)
        add-Q-till('a')
    else // ('a' < in)
        cycle-Q-till('a')
```

```
add-Q-till('a'):
    while (('x' ∈ in) != 'a')
        read(X)
        add(X, Q)
    read(X)
    print(X)
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0   Q =  $\emptyset$    in != EOF
```

```
foreach 'a'  $\in$  out:
    if ('a' == in)
        read(X)
        print(X)
    else if ('a' > in)
        add-Q-till('a')
    else // ('a' < in)
        cycle-Q-till('a')
```

```
add-Q-till('a'):
    while (('x'  $\in$  in) != 'a')
        read(X)
        add(X, Q)
    read(X)
    print(X)
```

```
cycle-Q-till('a'):
    while (('x'  $\in$  Q) != 'a')
        remove(X, Q)
        add(X, Q)
    remove(X, Q)
    print(X)
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

```
X = 0   Q =  $\emptyset$    in != EOF
```

```
foreach 'a'  $\in$  out:
    if ('a' == in)
        read(X)
        print(X)
    else if ('a' > in)
        add-Q-till('a')
    else // ('a' < in)
        cycle-Q-till('a')
```

```
add-Q-till('a'):
    while (('x'  $\in$  in) != 'a')
        read(X)
        add(X, Q)
    read(X)
    print(X)
```

```
cycle-Q-till('a'):
    while (('x'  $\in$  Q) != 'a')
        remove(X, Q)
        add(X, Q)
    remove(X, Q)
    print(X)
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

Proof.

```
foreach 'a' ∈ out:
  if ('a' >= in)
    add-Q-till('a')
  else // ('a' < in)
    cycle-Q-till('a')
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

Proof.

```
foreach 'a' ∈ out:
  if ('a' >= in)
    add-Q-till('a')
  else // ('a' < in)
    cycle-Q-till('a')
```

```
foreach 'a' ∈ out:
  if ('a' ∈ in)
    add-Q-till('a')
  else // ('a' ∈ Q)
    cycle-Q-till('a')
```




DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

Proof.

```
foreach 'a' ∈ out:  
  if ('a' >= in)  
    add-Q-till('a')  
  else // ('a' < in)  
    cycle-Q-till('a')
```

```
foreach 'a' ∈ out:  
  if ('a' ∈ in)  
    add-Q-till('a')  
  else // ('a' ∈ Q)  
    cycle-Q-till('a')
```



Pseudocode

Pseudocode



Pseudocode



“Executable” at an **abstract** level.

DH 2.14: Queueable Permutations

(b) Prove that every permutation are queueable.

An “AHA!” Proof from 杜星亮.

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

An “AHA!” Proof from 杜星亮.

```
foreach 'a' ∈ in:
  read(X)
  add(X, Q)

foreach 'a' ∈ out:
  cycle-Q-till('a')
```

DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

An “AHA!” Proof from 杜星亮.

```
foreach 'a' ∈ in:
  read(X)
  add(X, Q)

foreach 'a' ∈ out:
  cycle-Q-till('a')
```





DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.



DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.



DH 2.14: Queueable Permutations


(c) Prove that every permutation can be obtained by **two stacks**.



We can similarly speak of a permutation obtained by **two stacks**, if we permit the **push** and **pop** operations on two stacks S and S' .
— DH

DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.



DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.

```
foreach 'a' ∈ in:
    read(X)
    push(X, S)

foreach 'a' ∈ out:
```

DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.

```
foreach 'a' ∈ in:
    read(X)
    push(X, S)

foreach 'a' ∈ out:
    transfer-till(S, S', top(S) == 'a')
```

DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.

```
foreach 'a' ∈ in:
    read(X)
    push(X, S)

foreach 'a' ∈ out:
    transfer-till(S, S', top(S) == 'a')
    transfer-till(S', S, S' == ∅)
```

DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.

DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



```
two-stacks-perm(in, X, S, S')
```

DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



```
two-stacks-perm(in, X, S, S')
```

```
if (! one-stack-perm(in, X, S))  
    two-stacks-perm(in, X, S, S')
```

DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.




```
two-stacks-perm(in, X, S, S')
```

```
if (! one-stack-perm(in, X, S))  
    two-stacks-perm(in, X, S, S')
```

Embedding “transfer” into “one-stack-perm”.


DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



DH 2.15: Algorithm for Queueable Permutations


Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.




`transfer-till(S, S', top(S) == 'a')`

DH 2.15: Algorithm for Queueable Permutations


Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.








```
transfer-till(S, S', top(S) == 'a')  
transfer-till(S', S, S' ==  $\emptyset$ )
```







Step 4: Looking Back!





















~~3 2 1~~



~~3 2 1~~



Theorem (Queueable Permutations)

A permutation (a_1, \dots, a_n) is **queueable** \iff it is not the case that

321-Pattern : $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_i > a_j > a_k$

Theorem (Queueable Permutations)

A permutation (a_1, \dots, a_n) is **queueable** \iff it is not the case that

321-Pattern : $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_i > a_j > a_k$

Proof.

Left as an exercise.



Theorem (# of Queueable Permutations)

The number of queueable permutations of $[1 \cdots n]$ is $\binom{2n}{n} - \binom{2n}{n-1}$.

Theorem (# of Queueable Permutations)


The number of queueable permutations of $[1 \cdots n]$ is $\binom{2n}{n} - \binom{2n}{n-1}$.

Catalan Number Again!

Theorem (# of Queueable Permutations)

The number of queueable permutations of $[1 \cdots n]$ is $\binom{2n}{n} - \binom{2n}{n-1}$.


Catalan Number Again!



Theorem (# of Queueable Permutations)

The number of queueable permutations of $[1 \cdots n]$ is $\binom{2n}{n} - \binom{2n}{n-1}$.

Catalan Number Again!



Theorem (# of Queueable Permutations)

The number of queueable permutations of $[1 \cdots n]$ is $\binom{2n}{n} - \binom{2n}{n-1}$.

Proof.

Left for your research.

Theorem (# of Queueable Permutations)


The number of queueable permutations of $[1 \cdots n]$ is $\binom{2n}{n} - \binom{2n}{n-1}$.

Proof.

Left for your research.



Treesort Algorithm on BST



DH 2.16: Treesort

- (i) Construct an algorithm that transforms a given list of integers into a binary search tree.

DH 2.16: Treesort

- (i) Construct an algorithm that transforms a given list of integers into a binary search tree.

Node:

```
int val = NIL,  
Node left = NULL,  
Node right = NULL
```

DH 2.16: Treesort

- (i) Construct an algorithm that transforms a given list of integers into a binary search tree.

Node:

```
int val = NIL,  
Node left = NULL,  
Node right = NULL
```

```
buildBST(int eles[]):  
    Node root(eles[0])
```

```
foreach e ∈ eles[1..]:  
    insert(root, e)
```


DH 2.16: Treesort

- (i) Construct an algorithm that transforms a given list of integers into a binary search tree.

Node:

```
int val = NIL,  
Node left = NULL,  
Node right = NULL
```

```
buildBST(int eles[]):  
    Node root(eles[0])
```

```
foreach e ∈ eles[1..]:  
    insert(root, e)
```

```
insert(Node T, int e):
```

DH 2.16: Treesort

- (i) Construct an algorithm that transforms a given list of integers into a binary search tree.

Node:

```
int val = NIL,  
Node left = NULL,  
Node right = NULL
```

```
buildBST(int eles[]):  
    Node root(eles[0])
```

```
foreach e ∈ eles[1..]:  
    insert(root, e)
```

```
insert(Node T, int e):  
    if (e < T.val)  
        if (T.left == NULL)  
            T.left = new Node(e)  
        else  
            insert(T.left, e)
```

DH 2.16: Treesort

- (i) Construct an algorithm that transforms a given list of integers into a binary search tree.

Node:

```
int val = NIL,  
Node left = NULL,  
Node right = NULL
```

```
buildBST(int eles[]):  
    Node root(eles[0])
```

```
foreach e ∈ eles[1..]:  
    insert(root, e)
```

```
insert(Node T, int e):  
    if (e < T.val)  
        if (T.left == NULL)  
            T.left = new Node(e)  
        else  
            insert(T.left, e)  
    else // e >= T.val  
        if (T.right == NULL)  
            T.right = new Node(e)  
        else  
            insert(T.right, e)
```

```
procedure put x into a BST t:  
    ... call put x into t's left subtree  
    ... call put x into t's right subtree  
end procedure
```


```
procedure put x into a BST t:
    ... call put x into t's left subtree
    ... call put x into t's right subtree
end procedure
```

should be:

```
procedure put-x-into-BST (t):
    ... call put-x-into-BST (t's left subtree)
    ... call put-x-into-BST (t's right subtree)
end procedure
```

DH 2.16: Treesort

(ii) right; val; left




THE CLASSIC WORK
NEWLY UPDATED AND REVISED




The Art of Computer Programming

VOLUME 1
Fundamental Algorithms
Third Edition

DONALD E. KNUTH

Chapter 2—Information Structures	232
2.1. Introduction	232
2.2. Linear Lists	238
2.2.1. Stacks, Queues, and Deques	238
2.2.2. Sequential Allocation	244
2.2.3. Linked Allocation	254
2.2.4. Circular Lists	273
2.2.5. Doubly Linked Lists	280
2.2.6. Arrays and Orthogonal Lists	298
2.3. Trees	308
2.3.1. Traversing Binary Trees	318
2.3.2. Binary Tree Representation of Trees	334
2.3.3. Other Representations of Trees	348
2.3.4. Basic Mathematical Properties of Trees	362
2.3.4.1. Free trees	363
2.3.4.2. Oriented trees	372
*2.3.4.3. The “infinity lemma”	382
*2.3.4.4. Enumeration of trees	386
2.3.4.5. Path length	399
*2.3.4.6. History and bibliography	406
2.3.5. Lists and Garbage Collection	408
2.4. Multilinked Structures	424
2.5. Dynamic Storage Allocation	435
2.6. History and Bibliography	457





Thank
You!