



(<http://www.popflock.com/>)

Music Genres ▾

Music Festivals ▾

Music Artists ▾

Music Gear ▾

Edmonds' Algorithm



Get Edmonds' Algorithm essential facts below. View [Videos](#) or [join the Edmonds' Algorithm discussion](#). [Add Edmonds' Algorithm](#) to your PopFlock.com topic list for future reference or [share](#) this resource on social media.

Edmonds' Algorithm

In [graph theory](http://www.popflock.com/learn?s=Graph_theory) (http://www.popflock.com/learn?s=Graph_theory), **Edmonds' algorithm** or **Chu-Liu/Edmonds' algorithm** is an [algorithm](http://www.popflock.com/learn?s=Algorithm) (<http://www.popflock.com/learn?s=Algorithm>) for finding a [spanning](http://www.popflock.com/learn?s=Spanning_subgraph) (http://www.popflock.com/learn?s=Spanning_subgraph) [arborescence](http://www.popflock.com/learn?s=Arborescence_(graph_theory)) ([http://www.popflock.com/learn?s=Arborescence_\(graph_theory\)](http://www.popflock.com/learn?s=Arborescence_(graph_theory))) of minimum weight (sometimes called an *optimum branching*). It is the [directed](http://www.popflock.com/learn?s=Directed_graph) (http://www.popflock.com/learn?s=Directed_graph) analog of the [minimum spanning tree](http://www.popflock.com/learn?s=Minimum_spanning_tree) (http://www.popflock.com/learn?s=Minimum_spanning_tree) problem. The algorithm was proposed independently first by Yoeng-Jin Chu and Tseng-Hong Liu (1965) and then by [Jack Edmonds](http://www.popflock.com/learn?s=Jack_Edmonds) (http://www.popflock.com/learn?s=Jack_Edmonds) (1967).

Algorithm

Description

The algorithm takes as input a directed graph $D = \langle V, E \rangle$ where V is the set of nodes and E is the set of directed edges, a distinguished vertex $r \in V$ called the *root*, and a real-valued weight $w(e)$ for each edge $e \in E$. It returns a spanning [arborescence](http://www.popflock.com/learn?s=Arborescence_(graph_theory)) ([http://www.popflock.com/learn?s=Arborescence_\(graph_theory\)](http://www.popflock.com/learn?s=Arborescence_(graph_theory))) A rooted at r of minimum weight, where the weight of an arborescence is defined to be the sum of its edge weights, $w(A) = \sum_{e \in A} w(e)$.

The algorithm has a recursive description. Let $f(D, r, w)$ denote the function which returns a spanning arborescence rooted at r of minimum weight. We first remove any edge from E whose destination is r . We may also replace any set of parallel edges (edges between the same pair of vertices in the same direction) by a single edge with weight equal to the minimum of the weights of these parallel edges.

Now, for each node v other than the root, find the edge incoming to v of lowest weight (with ties broken arbitrarily). Denote the source of this edge by $\pi(v)$. If the set of edges $P = \{(\pi(v), v) \mid v \in V \setminus \{r\}\}$ does not contain any cycles, then $f(D, r, w) = P$.

Otherwise, P contains at least one cycle. Arbitrarily choose one of these cycles and call it C . We now define a new weighted directed graph $D' = \langle V', E' \rangle$ in which the cycle C is "contracted" into one node as follows:

The nodes of V' are the nodes of V not in C plus a *new* node denoted v_C .

- If (u, v) is an edge in E with $u \notin C$ and $v \in C$ (an edge coming into the cycle), then include in E' a new edge $e = (u, v_C)$, and define $w'(e) = w(u, v) - w(\pi(v), v)$.
- If (u, v) is an edge in E with $u \in C$ and $v \notin C$ (an edge going away from the cycle), then include in E' a new edge $e = (v_C, v)$, and define $w'(e) = w(u, v)$.
- If (u, v) is an edge in E with $u \notin C$ and $v \notin C$ (an edge unrelated to the cycle), then include in E' a new edge $e = (u, v)$, and define $w'(e) = w(u, v)$.

For each edge in E' , we remember which edge in E it corresponds to.

Now find a minimum spanning arborescence A' of D' using a call to $f(D', r, w')$. Since A' is a spanning arborescence, each vertex has exactly one incoming edge. Let (u, v_C) be the unique incoming edge to v_C in A' . This edge corresponds to an edge $(u, v) \in E$ with $v \in C$. Remove the edge $(\pi(v), v)$ from C , breaking the cycle. Mark each remaining edge in C . For each edge in A' , mark its corresponding edge in E . Now we define $f(D, r, w)$ to be the set of marked edges, which form a minimum spanning arborescence.

Observe that $f(D, r, w)$ is defined in terms of $f(D', r, w')$, with D' having strictly fewer vertices than D . Finding $f(D, r, w)$ for a single-vertex graph is trivial (it is just D itself), so the recursive algorithm is guaranteed to terminate.

Running time

The running time of this algorithm is $O(EV)$. A faster implementation of the algorithm due to Robert Tarjan (http://www.popflock.com/learn?s=Robert_Tarjan) runs in time $O(E \log V)$ for sparse graphs (http://www.popflock.com/learn?s=Sparse_graph) and $O(V^2)$ for dense graphs. This is as fast as Prim's algorithm (http://www.popflock.com/learn?s=Prim's_algorithm) for an undirected minimum spanning tree. In 1986, Gabow, Galil, Spencer, Compton, and Tarjan produced a faster implementation, with running time $O(E + V \log V)$.

References

- Chu, Y. J.; Liu, T. H. (1965), "On the Shortest Arborescence of a Directed Graph", *Science Sinica*, **14**: 1396-1400
- Edmonds, J. (1967), "Optimum Branchings", *J. Res. Nat. Bur. Standards*, **71B**: 233-240, [doi](http://www.popflock.com/learn?s=Digital_object_identifier:10.6028/jres.071b.032) (http://www.popflock.com/learn?s=Digital_object_identifier:10.6028/jres.071b.032)

[.\(\(//doi.org/10.6028%2Fjres.071b.032\)\)](https://doi.org/10.6028%2Fjres.071b.032)

- [Tarjan, R. E. \(http://www.popflock.com/learn?s=Robert_Tarjan\)](http://www.popflock.com/learn?s=Robert_Tarjan) (1977), "Finding Optimum Branchings", *Networks*, **7**: 25-35, [doi \(http://www.popflock.com/learn?s=Digital_object_identifier:10.1002/net.3230070103\)](http://www.popflock.com/learn?s=Digital_object_identifier:10.1002/net.3230070103) [.\(\(//doi.org/10.1002%2Fnet.3230070103\)\)](https://doi.org/10.1002%2Fnet.3230070103)
- Camerini, P.M.; Fratta, L.; Maffioli, F. (1979), "A note on finding optimum branchings", *Networks*, **9**: 309-312, [doi \(http://www.popflock.com/learn?s=Digital_object_identifier:10.1002/net.3230090403\)](http://www.popflock.com/learn?s=Digital_object_identifier:10.1002/net.3230090403) [.\(\(//doi.org/10.1002%2Fnet.3230090403\)\)](https://doi.org/10.1002%2Fnet.3230090403)
- Gibbons, Alan (1985), *Algorithmic Graph Theory*, Cambridge University press, [ISBN \(http://www.popflock.com/learn?s=International_Standard_Book_Number\) 0-521-28881-9](http://www.popflock.com/learn?s=International_Standard_Book_Number:0-521-28881-9) [.\(\(http://www.popflock.com/learn?s=Special:BookSources/0-521-28881-9\)\)](http://www.popflock.com/learn?s=Special:BookSources/0-521-28881-9)
- Gabow, H. N.; Galil, Z.; Spencer, T.; [Tarjan, R. E. \(http://www.popflock.com/learn?s=Robert_Tarjan\)](http://www.popflock.com/learn?s=Robert_Tarjan) (1986), "Efficient algorithms for finding minimum spanning trees in undirected and directed graphs", *Combinatorica*, **6**: 109-122, [doi \(http://www.popflock.com/learn?s=Digital_object_identifier:10.1007/bf02579168\)](http://www.popflock.com/learn?s=Digital_object_identifier:10.1007/bf02579168) [.\(\(//doi.org/10.1007%2Fbf02579168\)\)](https://doi.org/10.1007%2Fbf02579168)

External links

- [Edmonds's algorithm \(edmonds-alg.\) \(http://edmonds-alg.sourceforge.net/\)](http://edmonds-alg.sourceforge.net/) - An [open source \(http://www.popflock.com/learn?s=Open_source\)](http://www.popflock.com/learn?s=Open_source) implementation of Edmonds's algorithm written in [C++ \(http://www.popflock.com/learn?s=C%2B%2B\)](http://www.popflock.com/learn?s=C%2B%2B) and licensed under the [MIT License \(http://www.popflock.com/learn?s=MIT_License\)](http://www.popflock.com/learn?s=MIT_License). This source is using Tarjan's implementation for the dense graph.

W This article uses material from the Wikipedia page [available here \(http://wikipedia.org/wiki/Edmonds'_algorithm\)](http://wikipedia.org/wiki/Edmonds'_algorithm). It is released under the [Creative Commons Attribution-Share-Alike License 3.0 \(http://creativecommons.org/licenses/by-sa/3.0/\)](http://creativecommons.org/licenses/by-sa/3.0/).