

## 2-4 Recurrences

魏恒峰

hfwei@nju.edu.cn

2018 年 04 月 16 日



## Maximal Sum Subarray (Problem 4.1 – 5)

- ▶ array  $A[1 \cdots n]$ ,  $a_i \geq 0$
- ▶ to find (the sum of) an MS in  $A$

$$A[-2, 1, -3, \boxed{4, -1, 2, 1}, -5, 4]$$

## Maximal Sum Subarray (Problem 4.1 – 5)

- ▶ array  $A[1 \cdots n]$ ,  $a_i \geq 0$
- ▶ to find (the sum of) an MS in  $A$

$$A[-2, 1, -3, \boxed{4, -1, 2, 1}, -5, 4]$$

### Trial and error.

- ▶ try subproblem  $MSS[i]$ : the sum of the MS ( $MS[i]$ ) in  $A[1 \cdots i]$
- ▶ goal:  $mss = MSS[n]$

## Maximal Sum Subarray (Problem 4.1 – 5)

- ▶ array  $A[1 \cdots n]$ ,  $a_i \geq 0$
- ▶ to find (the sum of) an MS in  $A$

$$A[-2, 1, -3, \boxed{4, -1, 2, 1}, -5, 4]$$

### Trial and error.

- ▶ try subproblem  $MSS[i]$ : the sum of the MS ( $MS[i]$ ) in  $A[1 \cdots i]$
- ▶ goal:  $mss = MSS[n]$
- ▶ question: Is  $a_i \in MS[i]$ ?
- ▶ recurrence:

$$MSS[i] = \max\{MSS[i-1], ???\}$$

## Solution.

- ▶ subproblem  $MSS[i]$ : the sum of the MS *ending with*  $a_i$  or 0
- ▶ goal:

$$mss = \max_{1 \leq i \leq n} MSS[i]$$

## Solution.

- ▶ subproblem  $MSS[i]$ : the sum of the MS *ending with*  $a_i$  or 0
- ▶ goal:

$$mss = \max_{1 \leq i \leq n} MSS[i]$$

- ▶ question: where does the  $MSS[i]$  start?
- ▶ recurrence:

$$MSS[i] = \max \{MSS[i-1] + a_i, 0\} \quad (\text{prove it!})$$

## Solution.

- ▶ subproblem  $MSS[i]$ : the sum of the MS *ending with*  $a_i$  or 0
- ▶ goal:

$$mss = \max_{1 \leq i \leq n} MSS[i]$$

- ▶ question: where does the  $MSS[i]$  start?
- ▶ recurrence:

$$MSS[i] = \max \{MSS[i-1] + a_i, 0\} \quad (\text{prove it!})$$

- ▶ initialization:  $MSS[0] = 0$

---

```
1: procedure MSS( $A[1 \cdots n]$ )
2:   MSS[0]  $\leftarrow$  0
3:   for  $i \leftarrow 1$  to  $n$  do
4:     MSS[ $i$ ]  $\leftarrow$   $\max \{ \text{MSS}[i - 1] + A[i], 0 \}$ 
5:   return  $\max_{1 \leq i \leq n} \text{MSS}[i]$ 
```

---



---


```
1: procedure MSS( $A[1 \cdots n]$ )
2:   MSS[0]  $\leftarrow$  0
3:   for  $i \leftarrow 1$  to  $n$  do
4:     MSS[ $i$ ]  $\leftarrow$   $\max \{ \text{MSS}[i - 1] + A[i], 0 \}$ 
5:   return  $\max_{1 \leq i \leq n} \text{MSS}[i]$ 
```

---


---

```
1: procedure MSS( $A[1 \cdots n]$ )
2:   mss  $\leftarrow$  0
3:   MSS  $\leftarrow$  0
4:   for  $i \leftarrow 1$  to  $n$  do
5:     MSS  $\leftarrow$   $\max \{ \text{MSS} + A[i], 0 \}$ 
6:     mss  $\leftarrow$   $\max \{ \text{mss}, \text{MSS} \}$ 
7:   return mss
```

---




Ulf Grenander  $O(n^3) \implies O(n^2)$



Ulf Grenander  $O(n^3) \implies O(n^2)$


Michael Shamos  $O(n \log n)$ , onenight



Ulf Grenander  $O(n^3) \implies O(n^2)$

Michael Shamos  $O(n \log n)$ , onenight

Jon Bentley Conjecture:  $\Omega(n \log n)$




Ulf Grenander  $O(n^3) \implies O(n^2)$

Michael Shamos  $O(n \log n)$ , onenight

Jon Bentley Conjecture:  $\Omega(n \log n)$

Michael Shamos Carnegie Mellon seminar




Ulf Grenander  $O(n^3) \implies O(n^2)$

Michael Shamos  $O(n \log n)$ , onenight

Jon Bentley Conjecture:  $\Omega(n \log n)$

Michael Shamos Carnegie Mellon seminar

Jay Kadane  $O(n)$ ,



Ulf Grenander  $O(n^3) \implies O(n^2)$

Michael Shamos  $O(n \log n)$ , onenight

Jon Bentley Conjecture:  $\Omega(n \log n)$

Michael Shamos Carnegie Mellon seminar

Jay Kadane  $O(n)$ ,  $\leq 1$  minute

# Maximum-product subarray

## Maximum-product subarray (Problem 7.4)

- ▶ Array  $A[1 \dots n]$
- ▶ Find maximum-product subarray of  $A$

(1)  $a_i \in \mathbb{N}$

(2)  $a_i \in \mathbb{Z}$

(3)  $a_i \in \mathbb{R}$



# Maximum-product subarray

## Maximum-product subarray (Problem 7.4)

- ▶ Array  $A[1 \dots n]$
- ▶ Find maximum-product subarray of  $A$

(1)  $a_i \in \mathbb{N}$

(2)  $a_i \in \mathbb{Z}$

(3)  $a_i \in \mathbb{R}$

sum vs. product

# Maximum-product subarray

Subproblem:  $\text{MaxP}[i], \text{MinP}[i]$

		$\frac{1}{2}$	4	-2	5	$-\frac{1}{5}$	8
$\text{MaxP}[i]$	1	$\frac{1}{2}$	4	-2	5	8	64
$\text{MinP}[i]$	1	$\frac{1}{2}$	2	-8	-40	-1	-8

$$\text{MaxP}[i] = \max\{\text{MaxP}[i-1] \cdot a_i, \text{MinP}[i-1] \cdot a_i, a_i\}$$

$$\text{MinP}[i] = \min\{\text{MaxP}[i-1] \cdot a_i, \text{MinP}[i-1] \cdot a_i, a_i\}$$

2d

## Problem (Area-Efficient VLSI Layout)

Embedding a **complete binary tree** into a grid with minimum **area**.

- ▶ Complete binary tree circuit of

$$\# \text{layer} = 3, 5, 7, \dots$$

- ▶ Vertex on grid; no crossing edges
- ▶ Area:

$$\text{area} = \text{width} \times \text{height}$$

## Problem (Area-Efficient VLSI Layout)

Embedding a **complete binary tree** into a grid with minimum **area**.


- ▶ Complete binary tree circuit of


$$\# \text{layer} = 3, 5, 7, \dots$$

- ▶ Vertex on grid; no crossing edges
- ▶ Area:


$$\text{area} = \text{width} \times \text{height}$$








$$H(n) = H\left(\frac{n}{2}\right) + \Theta(1) = \Theta(\log n)$$



$$H(n) = H\left(\frac{n}{2}\right) + \Theta(1) = \Theta(\log n)$$

$$W(n) = 2W\left(\frac{n}{2}\right) + \Theta(1) = \Theta(n)$$





$$H(n) = H\left(\frac{n}{2}\right) + \Theta(1) = \Theta(\log n)$$

$$W(n) = 2W\left(\frac{n}{2}\right) + \Theta(1) = \Theta(n)$$

$$A(n) = \Theta(n \log n)$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$1 \times n$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$1 \times n$$

$$\frac{n}{\log n} \times \log n$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$1 \times n$$

$$\frac{n}{\log n} \times \log n$$

$$\boxed{\sqrt{n} \times \sqrt{n}}$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$1 \times n$$

$$\frac{n}{\log n} \times \log n$$

$$\boxed{\sqrt{n} \times \sqrt{n}}$$

$$H(n) = \Theta(\sqrt{n}), W(n) = \Theta(\sqrt{n}), A(n) = \Theta(n)$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$1 \times n$$

$$\frac{n}{\log n} \times \log n$$

$$\boxed{\sqrt{n} \times \sqrt{n}}$$

$$H(n) = \Theta(\sqrt{n}), W(n) = \Theta(\sqrt{n}), A(n) = \Theta(n)$$

$$H(n) = \square H\left(\frac{n}{\square}\right) + O(\square)$$

$$Q : \boxed{H(n)} \times \boxed{W(n)} = n$$

$$1 \times n$$

$$\frac{n}{\log n} \times \log n$$

$$\boxed{\sqrt{n} \times \sqrt{n}}$$


$$H(n) = \Theta(\sqrt{n}), \quad W(n) = \Theta(\sqrt{n}), \quad A(n) = \Theta(n)$$

$$H(n) = \square H\left(\frac{n}{\square}\right) + O(\square)$$


$$\boxed{H(n) = 2H\left(\frac{n}{4}\right) + \Theta(1)}$$







$H$ -layout



*“VLSI Theory and Parallel Supercomputing”, Charles E. Leiserson, 1989.*

## Binary Search (CLRS 4.5 – 3)


$$T(n) = 2T(n/2) + \Theta(1)$$

---


```
1: procedure BINARYSEARCH( $A, L, R, x$ )
2:   if  $R < L$  then
3:     return  $-1$ 
4:    $m \leftarrow L + (R - 1)/2$ 
5:   if  $A[m] = x$  then
6:     return  $m$ 
7:   else if  $A[m] > x$  then
8:     return BINARYSEARCH( $A, L, m - 1, x$ )
9:   else
10:    return BINARYSEARCH( $A, m + 1, R, x$ )
```

---

$$T(n) = \Theta(n \log n)$$



$$T(n) = \begin{cases} \max \left\{ T(\lfloor \frac{n-1}{2} \rfloor), T(\lceil \frac{n-1}{2} \rceil) \right\} + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$



$$T(n) = \begin{cases} \max \left\{ T(\lfloor \frac{n-1}{2} \rfloor), T(\lceil \frac{n-1}{2} \rceil) \right\} + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$T(n) = \begin{cases} T(\lfloor \frac{n}{2} \rfloor) + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$T(n) = \begin{cases} T(\lfloor \frac{n}{2} \rfloor) + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$T(n) = \begin{cases} T(\lfloor \frac{n}{2} \rfloor) + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$n = 2^k \implies T(n) = k + 1$$



$$T(n) = \begin{cases} T(\lfloor \frac{n}{2} \rfloor) + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$n = 2^k \implies T(n) = k + 1$$

$$2^k \leq n < 2^{k+1} \implies T(n) = k + 1$$

$$T(n) = \begin{cases} T(\lfloor \frac{n}{2} \rfloor) + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$n = 2^k \implies T(n) = k + 1$$

$$2^k \leq n < 2^{k+1} \implies T(n) = k + 1$$

$$T(n) = \lfloor \lg n \rfloor + 1$$

$$T(n) = \begin{cases} T(\lfloor \frac{n}{2} \rfloor) + 1, & n > 2 \\ 1, & n = 1 \end{cases}$$

$$n = 2^k \implies T(n) = k + 1$$

$$2^k \leq n < 2^{k+1} \implies T(n) = k + 1$$

$$T(n) = \lfloor \lg n \rfloor + 1$$

## Theorem

*The worst case time complexity (# of comparisons) of BINARYSEARCH on an input size of  $n$  = # of bits in the binary representation of  $n$ .*



## Analysis of Mergesort in CLRS (# of Comparisons; $a_i : \infty$ not Counted)

- (a) Analyze the **worst case**  $W(n)$  and the **best case**  $B(n)$  time complexity of mergesort *as accurately as possible*.

Explore the relation between them and the binary representations of numbers.

Plot  $W(n)$  and  $B(n)$  and explain what you observe.

- (b) Analyze the **average case**  $A(n)$  time complexity of mergesort.

Plot  $A(n)$  and explain what you observe.

- (c) **Prove that:** The minimum number of comparisons needed to merge two sorted arrays of equal size  $m$  is  $2m - 1$ .

## Analysis of Mergesort in CLRS (# of Comparisons; $a_i : \infty$ not Counted)

- (a) Analyze the **worst case**  $W(n)$  and the **best case**  $B(n)$  time complexity of mergesort *as accurately as possible*.

Explore the relation between them and the binary representations of numbers.

Plot  $W(n)$  and  $B(n)$  and explain what you observe.

- (b) Analyze the **average case**  $A(n)$  time complexity of mergesort.

Plot  $A(n)$  and explain what you observe.

- (c) **Prove that:** The minimum number of comparisons needed to merge two sorted arrays of equal size  $m$  is  $2m - 1$ .




$W(n)$  : Consider  $W(n + 1)$

$$W(n) = W(\lfloor \frac{n}{2} \rfloor) + W(\lceil \frac{n}{2} \rceil) + (n - 1)$$

Thank  
You!





Office 302

Mailbox: H016

hfwei@nju.edu.cn