

## 2-9 Sorting and Selection


Hengfeng Wei

hfwei@nju.edu.cn

May 28, 2018



## How to Argue?













## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .



## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

$$T(n) = \min_{0 \leq q \leq n-1} \left( T(q) + T(n - q - 1) \right) + \Theta(n)$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

$$T(n) = \min_{0 \leq q \leq n-1} \left( T(q) + T(n - q - 1) \right) + \Theta(n)$$

$$T(n) = \Omega(n \log n)$$

## Best-Case Complexity of QUICKSORT (7.4 – 2)

**Show that** QUICKSORT's best-case running time is  $\Omega(n \log n)$ .

$$T(n) = 2T\left(\frac{n}{2}\right) + \Theta(n)$$

$$T(n) = \underbrace{n}_{\text{PARTITION}} \underbrace{\log n}_{\text{Height}} \quad (\text{Recursion Tree})$$

$$T(n) = \min_{0 \leq q \leq n-1} \left( T(q) + T(n - q - 1) \right) + \Theta(n)$$

$$T(n) = \Omega(n \log n)$$

By substitution.

## Median-of-3 PARTITION (Problem 7 – 5)

**Argue that** in the  $\Omega(n \log n)$  running time of QUICKSORT, the *median-of-3* method affects only the constant factor.

## Median-of-3 PARTITION (Problem 7 – 5)

**Argue that** in the  $\Omega(n \log n)$  running time of QUICKSORT, the *median-of-3* method affects only the constant factor.



## Median-of-3 PARTITION (Problem 7 – 5)

**Argue that** in the  $\Omega(n \log n)$  running time of QUICKSORT, the *median-of-3* method affects only the constant factor.



$$T(n) = \min_{0 \leq q \leq n-1} (T(q) + T(n - q - 1)) + \Theta(n)$$


$$T(n) = \Omega(n \log n)$$







Thank  
You!



Office 302

Mailbox: H016

hfwei@nju.edu.cn