

# 1-5 数据与数据结构 (II)

魏恒峰

hfwei@nju.edu.cn

2017 年 11 月 27 日






# 温故而知新

— 孔子

# 温故而知新

— 孔子



Looking Back!


# Stackable/Queueable Permutations

## Treesort Algorithm

# Queueable Permutations




## DH 2.14: Queueable Permutations





## DH 2.14: Queueable Permutations

$$\text{out} = (a_1, \dots, a_n) \xrightleftharpoons[X=0]{Q=\emptyset} \text{in} = (1, \dots, n)$$



## DH 2.14: Queueable Permutations

(a) Show that the permutations given in Exercise 2.12(b) are queueable.

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

## DH 2.14: Queueable Permutations

(a) Show that the permutations given in Exercise 2.12(b) are queueable.

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$



## DH 2.14: Queueable Permutations

(a) Show that the permutations given in Exercise 2.12(b) are queueable.

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$



## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

$X = 0$        $Q = \emptyset$        $in \neq EOF$

```
foreach 'a' ∈ out:
  if ('a' == in)
    read(X)
    print(X)
  else if ('a' > in)
    add-Q-till('a')
  else // ('a' < in)
    cycle-Q-till('a')
```

## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

$X = 0$        $Q = \emptyset$        $in \neq EOF$

```
foreach 'a' ∈ out:
    if ('a' == in)
        read(X)
        print(X)
    else if ('a' > in)
        add-Q-till('a')
    else // ('a' < in)
        cycle-Q-till('a')
```

```
add-Q-till('a'):
    while (('x' ∈ in) != 'a')
        add(X, Q)
    read(X)
    print(X)
```

## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

$X = 0$        $Q = \emptyset$        $in \neq EOF$

```
foreach 'a' ∈ out:
    if ('a' == in)
        read(X)
        print(X)
    else if ('a' > in)
        add-Q-till('a')
    else // ('a' < in)
        cycle-Q-till('a')
```

```
add-Q-till('a'):
    while (('x' ∈ in) != 'a')
        add(X, Q)
    read(X)
    print(X)
```

```
cycle-Q-till('a'):
    while (('x' ∈ Q) != 'a')
        remove(X, Q)
        add(X, Q)
    remove(X, Q)
    print(X)
```



## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

$X = 0$        $Q = \emptyset$        $in \neq EOF$

```
foreach 'a' ∈ out:
    if ('a' == in)
        read(X)
        print(X)
    else if ('a' > in)
        add-Q-till('a')
    else // ('a' < in)
        cycle-Q-till('a')
```

```
add-Q-till('a'):
    while (('x' ∈ in) != 'a')
        add(X, Q)
    read(X)
    print(X)
```

```
cycle-Q-till('a'):
    while (('x' ∈ Q) != 'a')
        remove(X, Q)
        add(X, Q)
    remove(X, Q)
    print(X)
```

## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

Proof.

```
foreach 'a' ∈ out:
  if ('a' >= in)
    add-Q-till('a')
  else // ('a' < in)
    cycle-Q-till('a')
```

## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

Proof.

```
foreach 'a' ∈ out:
  if ('a' >= in)
    add-Q-till('a')
  else // ('a' < in)
    cycle-Q-till('a')
```

```
foreach 'a' ∈ out:
  if ('a' ∈ in)
    add-Q-till('a')
  else // ('a' ∈ Q)
    cycle-Q-till('a')
```




## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

Proof.

```
foreach 'a' ∈ out:
  if ('a' >= in)
    add-Q-till('a')
  else // ('a' < in)
    cycle-Q-till('a')
```

```
foreach 'a' ∈ out:
  if ('a' ∈ in)
    add-Q-till('a')
  else // ('a' ∈ Q)
    cycle-Q-till('a')
```



# Pseudocode

# Pseudocode



# Pseudocode



“Executable” at an abstract level.

## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

An “AHA!” Proof.

```
foreach 'a' ∈ in:  
    add(X, Q)  
  
foreach 'a' ∈ out:  
    cycle-Q-till('a')
```



## DH 2.14: Queueable Permutations

(b) Prove that every permutation are **queueable**.

An “AHA!” Proof.

```
foreach 'a' ∈ in:  
    add(X, Q)  
  
foreach 'a' ∈ out:  
    cycle-Q-till('a')
```





## DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.



## DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.



## DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.



We can similarly speak of a permutation obtained by **two stacks**, if we permit the **push** and **pop** operations on two stacks  $S$  and  $S'$ .

## DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.

2 stacks model

## DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.

2 stacks model

```
foreach 'a' ∈ in:
    read(X)
    push(X, S')

foreach 'a' ∈ out:
    if ('a' ≤ top(S')) // ∈ S'
        transfer-till(S', S, 'a')
    else // ∈ S
        transfer-till(S, S', 'a')
```

## DH 2.14: Queueable Permutations

(c) Prove that every permutation can be obtained by **two stacks**.

2 stacks model

```
foreach 'a' ∈ in:
    read(X)
    push(X, S')

foreach 'a' ∈ out:
    if ('a' <= top(S')) // ∈ S'
        transfer-till(S', S, 'a')
    else // ∈ S
        transfer-till(S, S', 'a')
```

Can you **PROVE** it?

## DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



## DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



## DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



`two-stackable-perm(in, X, S, S')`

## DH 2.15: Algorithm for Queueable Permutations

Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.



```
two-stackable-perm(in, X, S, S')
```

```
if (! stackable-perm(in, X, S))  
    two-stackable-perm(in, X, S, S')
```

## DH 2.15: Algorithm for Queueable Permutations


Extend the algorithm you were asked to design in Exercise 2.13, so that **if** the given permutation **cannot** be obtained by **a stack**, the algorithm will print the series of operations on **two stacks** that will generate it.








```
two-stackable-perm(in, X, S, S')
```




```
if (! stackable-perm(in, X, S))  
    two-stackable-perm(in, X, S, S')
```

Embedding “transfer” into “stackable-perm”.
























3 2 1



3 2 1



## Theorem (Queueable Permutations)

A permutation  $(a_1, \dots, a_n)$  is queueable  $\iff$  it is not the case that


321-Pattern :  $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_i > a_j > a_k$

## Theorem (Queueable Permutations)



A permutation  $(a_1, \dots, a_n)$  is queueable  $\iff$  it is not the case that

321-Pattern :  $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_i > a_j > a_k$

<b>Chapter 2—Information Structures</b>	<b>232</b>
2.1. Introduction	232
2.2. Linear Lists	238
2.2.1. Stacks, Queues, and Deques	238
2.2.2. Sequential Allocation	244
2.2.3. Linked Allocation	254
2.2.4. Circular Lists	273
2.2.5. Doubly Linked Lists	280
2.2.6. Arrays and Orthogonal Lists	298
2.3. Trees	308
2.3.1. Traversing Binary Trees	318
2.3.2. Binary Tree Representation of Trees	334
2.3.3. Other Representations of Trees	348
2.3.4. Basic Mathematical Properties of Trees	362
2.3.4.1. Free trees	363
2.3.4.2. Oriented trees	372
*2.3.4.3. The “infinity lemma”	382
*2.3.4.4. Enumeration of trees	386
2.3.4.5. Path length	399
*2.3.4.6. History and bibliography	406
2.3.5. Lists and Garbage Collection	408
2.4. Multilinked Structures	424
2.5. Dynamic Storage Allocation	435
2.6. History and Bibliography	457







Thank  
You!