

# 1-5 数据与数据结构

魏恒峰

hfwei@nju.edu.cn

2017 年 11 月 06 日

# Permutations




## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .


(1) The “choosing from” method:




## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

(1) The “choosing from” method:





(2) The “inserting into” method:



## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

- (1) The “choosing from” method:      (2) The “inserting into” method:



Prove by mathematical induction on  $n$ .

## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n)$  : # of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$

## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n)$  : # of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$

B.S.  $P(1)$

I.H.  $P(n)$

I.S.  $P(n) \rightarrow P(n+1)$



## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n)$  : # of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$

B.S.  $P(1)$

I.H.  $P(n)$

I.S.  $P(n) \rightarrow P(n+1)$

## DH 2.9: # of Permutations

Prove that the number of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n)$  : # of permutations of  $A_n = \{1 \cdots n\}$  is  $n!$

B.S.  $P(1)$

I.H.  $P(n)$

I.S.  $P(n) \rightarrow P(n+1)$

Choosing from

Inserting into



## DH 2.11: Generate All Permutations

Design an algorithm which, given a positive integer  $N$ , produces all the permutations of  $A_N$ .

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

- ▶ Boolean array  $[1 \cdots n]$

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

- ▶ Boolean array  $[1 \cdots n]$
- ▶ Sort

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

- ▶ Boolean array  $[1 \cdots n]$
- ▶ Sort
- ▶  $\forall x : x \in [1 \cdots n]$
- ▶ check for duplication



# Stackable Permutations

## Definition (Stackable Permutations)

`read(X): in >> X`  
`print(X): out << X`  
`push(X, S): S  $\leftarrow$  X`  
`pop(X, S): X  $\leftarrow$  S`

$Q_1$ : What are  $X$  and out after `print(X)`?

$A_1$ : Elements move around.

$Q_2$ : ' $a$ '  $\geq$   $\leq$   $X$ , `top(S)`?

$A_2$ : Yes.

## Definition (Stackable Permutations)

`read(X): in >> X`       $Q_1$  : What are  $X$  and out after `print(X)`?  
`print(X): out << X`       $A_1$  : Elements move around.  
`push(X, S): S  $\Leftarrow$  X`       $Q_2$  : ' $a$ '  $\geq$   $\leq$   $X$ , `top(S)`?  
`pop(X, S): X  $\Leftarrow$  S`       $A_2$  : Yes.

$$\text{in} = (1, \dots, n) \xrightarrow[X=0]{S=\emptyset} \text{out} = (a_1, \dots, a_n)$$

fig here.

## DH 2.12: Stackable Permutations

(a) Show that the following permutations *are* stackable:

(i)  $(3, 2, 1)$

(ii)  $(3, 4, 2, 1)$

(iii)  $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$

## DH 2.12: Stackable Permutations

(a) Show that the following permutations *are* stackable:

- (i)  $(3, 2, 1)$
- (ii)  $(3, 4, 2, 1)$
- (iii)  $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$



## DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read   print   push   pop   is-empty

```
X = 0  
S = ∅
```

```
foreach 'a' in out:  
    if (! is-empty(S)  
        && 'a' == top(S))  
        pop(S, X)  
        print(X)  
        break  
    else ... // T.B.C
```

```
else // T.B.C  
    while (in != ∅)  
        read(X)  
        if (X == 'a')  
            print(X)  
            break  
        else if (X < 'a')  
            push(X, S)  
        else // (X > 'a')  
            ERR  
ERR
```

## DH 2.12: Stackable Permutations

(b) Prove that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$



## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) (3, 1, 2)

(ii) (4, 5, 3, 7, 2, 1, 6)

(3, 1, 2)

(4, 5, 3, 7, 2, 1, 6)

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i) (3, 1, 2)

(ii) (4, 5, 3, 7, 2, 1, 6)

(3, 1, 2)

(4, 5, 3, 7, 2, 1, 6)

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

312-Pattern

## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable  $\iff$  it is not the case that

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable  $\iff$  it is not the case that

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

Proof.

$$\iff$$


## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable  $\iff$  it is not the case that

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$


Proof.





## Theorem (Equivalence)

*These two models ( $S + X$  and  $S$ ) are equivalent.*



## Theorem (Equivalence)

*These two models ( $S + X$  and  $S$ ) are equivalent.*

Proof.

By simulations.

Simulate  $S$  by  $S + X$ :

- ▶ Push
- ▶ Pop

Simulate  $S + X$  by  $S$ :

By iterative transformations.



## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable (on the model  $S$ )  $\iff$  it is not the case that

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

Proof.



By contradiction.

$a_j < a_k < a_i$ : When  $a_i$  is popped,  $a_j$  and  $a_k$  are on the stack.

$j < k$ :  $a_j$  is above  $a_k$  on the stack.

$a_j < a_k$ : Contradiction.





## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable (on the model  $S$ )  $\iff$  it is not the case that

$$a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

Proof.

$\Leftarrow$

According to our algorithms and by contradiction.

$$a_j \notin \text{in} \wedge a_j \neq \text{top}(S) \implies \exists k > j : a_k > a_j$$

$$a_j, a_k \implies \exists i < j (< k) : a_j < a_k < a_i$$



## DH 2.12: Stackable Permutations

(c) How many permutations of  $A_4$  *cannot* be obtained by a stack?

$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$   
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$

## DH 2.12: Stackable Permutations

How many permutations of  $A_n$  *cannot* be obtained by a stack?

## DH 2.12: Stackable Permutations

How many permutations of  $A_n$  *cannot* be obtained by a stack?

Push : +      Pop : -

$(3, 2, 5, 6, 1, 4) : + + + - - + + - + - - -$

## Definition (Admissible Sequences)

A sequence of “+” and “-” is **admissible** if and only if

## Definition (Admissible Sequences)

A sequence of “+” and “-” is **admissible** if and only if

1. # of “+” =  $n$       # of “-” =  $n$
2.  $\forall$  prefix : (# of “-”)  $\leq$  (# of “+”)

## Definition (Admissible Sequences)

A sequence of “+” and “-” is **admissible** if and only if

1. # of “+” =  $n$       # of “-” =  $n$
2.  $\forall$  prefix : (# of “-”)  $\leq$  (# of “+”)

## Theorem

*Different admissible sequences correspond to different permutations.*

## Definition (Admissible Sequences)

A sequence of “+” and “-” is **admissible** if and only if

1. # of “+” =  $n$       # of “-” =  $n$
2.  $\forall$  prefix : (# of “-”)  $\leq$  (# of “+”)

## Theorem

*Different admissible sequences correspond to different permutations.*

+ + + - - + ...  
+ + + - - - ...



## Theorem (Reflection Method)

*The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .*





Thank  
You!