

# 1-5 数据与数据结构 (I)

魏恒峰

hfwei@nju.edu.cn


2017 年 11 月 06 日

# Permutations

# Permutations

Generating All Permutations  
Stackable/Queueable Permutations

## Generating All Permutations



## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

For  $a_1$ : We have  $n$  choices.

For  $a_2$ : We have  $n - 1$  choices.

For  $\dots$ :  $\dots$

Then, # of perms is

$$n \times (n - 1) \times \dots \times 1 = n!$$



## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

“坊间”证明.

For  $a_1$ : We have  $n$  choices.

For  $a_2$ : We have  $n - 1$  choices.

For  $\dots$ :  $\dots$

Then, # of perms is

$$n \times (n - 1) \times \dots \times 1 = n!$$



## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

“坊间”证明.

For  $a_1$ : We have  $n$  choices.

For  $a_2$ : We have  $n - 1$  choices.

For  $\dots$ :  $\dots$

Then, # of perms is

$$n \times (n - 1) \times \dots \times 1 = n!$$



Prove by mathematical induction on  $n$ .



## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n) : \#$  of perms of  $n$  (distinct) element is  $n!$

## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n)$  : # of perms of  $n$  (distinct) element is  $n!$

B.S.  $P(1)$

I.H.  $P(n)$

I.S.  $P(n) \rightarrow P(n+1)$

## DH 2.9: # of Permutations

Prove that the number of permutations of  $n$  (distinct) elements is  $n!$ .

Prove by mathematical induction on  $n$ .

$P(n)$  : # of perms of  $n$  (distinct) element is  $n!$

B.S.  $P(1)$

I.H.  $P(n)$

I.S.  $P(n) \rightarrow P(n+1)$

$$\underbrace{(n+1)}_{\text{1st choice}} \times \underbrace{n!}_{\text{I.H.}} = (n+1)!$$



## DH 2.11: Generate All Permutations

Design an algorithm which, given a positive integer  $n$ , generates/[prints](#) all the permutations of  $[0 \cdots n)$ .

## DH 2.11: Generate All Permutations

Design an algorithm which, given a positive integer  $n$ , generates/prints all the permutations of  $[0 \cdots n)$ .

```
void perms (A[], n) {  
    if (n == 1)  
        print 'A[0] '  
    else  
        for (int i = 0; i < n; ++i)  
            print 'A[i] '  
            perms(A ← A \ A[i], n - 1)  
            print '\\n'  
}
```

## DH 2.11: Generate All Permutations

Design an algorithm which, given a positive integer  $n$ , generates/prints all the permutations of  $[0 \cdots n)$ .

```
void perms (A[], n) {  
    if (n == 1)  
        print 'A[0] '  
    else  
        for (int i = 0; i < n; ++i)  
            print 'A[i] '  
            perms(A ← A \ A[i], n - 1)  
            print '\\n'  
}
```


generate-perms.c







$$A = [0, 1, 2, 3] \quad n = 4$$



```

void perms (prefix, A[], n) {
    if (n == 1)
        print ' 'prefix ++ A[0] ' '
    else
        for (int i = 0; i < n; ++i)
            perms(prefix ← prefix ++ A[i],
                  A ← A \ A[i], n - 1)
            print ' '\n' '
}

```

```

void perms (prefix, A[], n) {
    if (n == 1)
        print ' 'prefix ++ A[0] ' '
    else
        for (int i = 0; i < n; ++i)
            perms(prefix ← prefix ++ A[i],
                A ← A \ A[i], n - 1)
            print ' '\n'
}


```

```

perms(' ', A, n);

```

# For more about “Generating All Permutations”:



## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

1. Boolean array  $[1 \cdots n]$

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

1. Boolean array  $[1 \cdots n]$

$O(n)$   $O(n)$   
time space

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

1. Boolean array  $[1 \cdots n]$

2. Sort and then scan

$O(n)$   
time

$O(n)$   
space



## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

1. Boolean array  $[1 \cdots n]$

$O(n)$   $O(n)$   
time space

2. Sort and then scan

$O(n \log n)$   $O(1)$   
time space

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

1. Boolean array  $[1 \cdots n]$

$O(n)$   
time

$O(n)$   
space

2. Sort and then scan

$O(n \log n)$   
time

$O(1)$   
space



$O(n)$   
time

$O(1)$   
space

## DH 2.10: Permutation Checking

- ▶ An integer  $n$
- ▶ An array of integers  $P$  of length  $n$

To check whether  $P$  is a permutation of  $1 \cdots n$ ?

1. Boolean array  $[1 \cdots n]$

$O(n)$   
time

$O(n)$   
space

2. Sort and then scan


$O(n \log n)$   
time

$O(1)$   
space



$O(n)$   
time

$O(1)$   
space




# Stackable Permutations

# Stackable Permutations




## Definition (Stackable Permutations)




## Definition (Stackable Permutations)

$$\text{out} = (a_1, \dots, a_n) \xleftarrow[X=0]{S=\emptyset} \text{in} = (1, \dots, n)$$




## Definition (Stackable Permutations)






## Definition (Stackable Permutations)



$Q_1$ : Meaning of “read, print, push, pop”?

## Definition (Stackable Permutations)




$Q_1$  : Meaning of “read, print, push, pop”?

$Q_2$  : Using **only** “read, print, push, pop”?

$$a == X$$

## Definition (Stackable Permutations)




$Q_1$  : Meaning of “read, print, push, pop”?

$Q_2$  : Using **only** “read, print, push, pop”?

$$a == X \quad a > X \ (a < X)$$

## Definition (Stackable Permutations)



$Q_1$  : Meaning of “read, print, push, pop”?

$Q_2$  : Using **only** “read, print, push, pop”?

$$a == X \quad a > X \ (a < X) \quad \text{top}(S)$$

## DH 2.12: Stackable Permutations

(a) **Show** that the following permutations *are* stackable:

(i)  $(3, 2, 1)$

(ii)  $(3, 4, 2, 1)$

(iii)  $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$

## DH 2.12: Stackable Permutations

(a) **Show** that the following permutations *are* stackable:

(i)  $(3, 2, 1)$

(ii)  $(3, 4, 2, 1)$

(iii)  $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$

## DH 2.12: Stackable Permutations

(a) **Show** that the following permutations *are* stackable:

- (i)  $(3, 2, 1)$
- (ii)  $(3, 4, 2, 1)$
- (iii)  $(3, 5, 7, 6, 8, 4, 9, 2, 10, 1)$



## DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read   print   push   pop   *is-empty*

$X = 0$     $S = \emptyset$     $in \neq EOF$



## DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read   print   push   pop   is-empty

$X = 0$     $S = \emptyset$    in  $\neq$  EOF

```
foreach 'a' in out:
    if (! is-empty(S)
        && 'a' == top(S))
        pop(S, X)
        print(X)
        continue
    else ... // T.B.C
```

## DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read   print   push   pop   is-empty

$X = 0$     $S = \emptyset$    in  $\neq$  EOF

```
foreach 'a' in out:
    if (! is-empty(S)
        && 'a' == top(S))
        pop(S, X)
        print(X)
        continue
    else ... // T.B.C
```

```
else // T.B.C
    while (in  $\neq$  EOF)
        read(X)
        if (X == 'a')
            print(X)
            continue
        else
            push(X, S)
ERR
```

## DH 2.13: Stackable Permutations Checking Algorithm

To check whether a given permutation can be obtained by a stack.

read   print   push   pop   is-empty

$X = 0$     $S = \emptyset$    in  $\neq$  EOF

```
foreach 'a' in out:
    if (! is-empty(S)
        && 'a' == top(S))
        pop(S, X)
        print(X)
        continue
    else ... // T.B.C
```

```
else // T.B.C
    while (in  $\neq$  EOF)
        read(X)
        if (X == 'a')
            print(X)
            continue
        else
            push(X, S)
ERR // How???
```

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$

$$\text{out} = \cdots a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

## DH 2.12: Stackable Permutations

(b) **Prove** that the following permutations are *not* stackable:

(i)  $(3, 1, 2)$

(ii)  $(4, 5, 3, 7, 2, 1, 6)$

$(3, 1, 2)$

$(4, 5, 3, 7, 2, 1, 6)$

$$\text{out} = \cdots a_i \cdots a_j \cdots a_k : i < j < k \wedge a_j < a_k < a_i$$

312-Pattern



## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable  $\iff$  it is not the case that

312-Pattern :  $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_j < a_k < a_i$

## Theorem (Stackable Permutations)

A permutation  $(a_1, \dots, a_n)$  is stackable  $\iff$  it is not the case that

312-Pattern :  $out = \dots a_i \dots a_j \dots a_k : i < j < k \wedge a_j < a_k < a_i$

Proof.



NO PROOF WARRANTY



## DH 2.12: Stackable Permutations

(c) How many permutations of  $A_4$  *cannot* be obtained by a stack?

$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$   
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$

## DH 2.12: Stackable Permutations

(c) How many permutations of  $A_4$  *cannot* be obtained by a stack?


$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$   
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$



## DH 2.12: Stackable Permutations



(c) How many permutations of  $A_4$  *cannot* be obtained by a stack?

$(1, 4, 2, 3), (2, 4, 1, 3), (3, 1, 2, 4), (3, 1, 4, 2), (3, 4, 1, 2)$   
 $(4, 1, 2, 3), (4, 1, 3, 2), (4, 2, 1, 3), (4, 2, 3, 1), (4, 3, 1, 2)$

*Q* : What about  $A_n$ ?











$Q$  : Are  $S + X$  and  $S$  are **equivalent**?







$Q$  : Are  $S + X$  and  $S$  are **equivalent**?



$Q$  : Are  $S + X$  and  $S$  are **equivalent**?



Producing the same set of permutations.





$Q$  : Are  $S + X$  and  $S$  are **equivalent**?



Producing the same set of permutations.

Accepting the same set of *admissible* operation sequences.







By simulations.



By simulations.

Simulate  $S$  by  $S + X$ :

- Push
- Pop





By simulations.

Simulate  $S$  by  $S + X$ :

- Push
- Pop

Simulate  $S + X$  by  $S$ :



By simulations.

Simulate  $S$  by  $S + X$ :

- ▶ Push
- ▶ Pop

Simulate  $S + X$  by  $S$ :

By iterative transformations.





## DH 2.12: Stackable Permutations

How many permutations of  $A_n$  *cannot* be obtained by a stack?

## DH 2.12: Stackable Permutations

How many permutations of  $A_n$  *cannot* be obtained by a stack?

Push : +      Pop : -

## DH 2.12: Stackable Permutations

How many permutations of  $A_n$  *cannot* be obtained by a stack?

Push : +      Pop : -

$(1, 2, 3) : + - + - + -$

$(3, 2, 1) : + + + - - -$

## DH 2.12: Stackable Permutations

How many permutations of  $A_n$  *cannot* be obtained by a stack?

Push : +      Pop : -

$(1, 2, 3) : + - + - + -$

$(3, 2, 1) : + + + - - -$

$(3, 2, 5, 6, 1, 4) : + + + - - + + - + - - -$

## Definition (Admissible Sequences)

A sequence of “+” and “−” is *admissible* if and only if

## Definition (Admissible Sequences)

A sequence of “+” and “-” is *admissible* if and only if

1. # of “+” =  $n$       # of “-” =  $n$
2.  $\forall$  prefix : (# of “-”)  $\leq$  (# of “+”)

## Definition (Admissible Sequences)

A sequence of “+” and “-” is *admissible* if and only if

1. # of “+” =  $n$       # of “-” =  $n$
2.  $\forall$  prefix : (# of “-”)  $\leq$  (# of “+”)

## Theorem

*Different admissible sequences correspond to different permutations.*

## Definition (Admissible Sequences)

A sequence of “+” and “-” is *admissible* if and only if

1. # of “+” =  $n$       # of “-” =  $n$
2.  $\forall$  prefix : (# of “-”)  $\leq$  (# of “+”)

## Theorem

*Different admissible sequences correspond to different permutations.*

+ + + - - + ...  
+ + + - - - ...



## Theorem (Reflection Method)

*The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .*

Proof.

$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$

## Theorem (Reflection Method)

*The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .*

Proof.

$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$

+ + - + - - - - + + +

## Theorem (Reflection Method)

The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .

Proof.

$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$

+ + - + - - - - + + +

- - + - + + + - - + + +



## Theorem (Reflection Method)

The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .

Proof.

$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$

+ + - + - - - - + + +

- - + - + + + - - + + +

$$(\# \text{ of "+"}) = (n + 1) \quad (\# \text{ of "-"}) = (n - 1)$$



## Theorem (Reflection Method)

The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .

Proof.

$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$

+ + - + - - - - + + +

- - + - + + + - - + + +

- - + + + +

$$(\# \text{ of "+"}) = (n + 1) \quad (\# \text{ of "-"}) = (n - 1)$$



## Theorem (Reflection Method)

The number of stackable permutations is  $\binom{2n}{n} - \binom{2n}{n-1}$ .

Proof.

$$\underbrace{\binom{2n}{n}}_{\text{all}} - \underbrace{\binom{2n}{n-1}}_{\text{inadmissible}}$$

+ + - + - - - - + + +

- - + - + + + - - + + +

+ + - - - +

- - + + + +

$$(\# \text{ of "+"}) = (n + 1) \quad (\# \text{ of "-"}) = (n - 1)$$



# Catalan Number

# Catalan Number

## Parenthesis

$(3, 2, 1) : ((( )))$        $(1, 2, 3) : ()()()$





# Catalan Number


## Parenthesis

$(3, 2, 1) : ((( )))$        $(1, 2, 3) : ()()()$

## Grid Paths Not above the diagonal:



# For more about “Stackable Permutations”:



Thank  
You!