

Using data in R

Alexandre Courtiol

Leibniz Institute of Zoo and Wildlife Research

June 2018

1 Vector

- Factors

2 Data frames

- what is a data frame
- playing with data frames

3 List

Table of contents

1 Vector

- Factors

2 Data frames

- what is a data frame
- playing with data frames

3 List

Vector

A vector is a sequence of data elements of the same basic type

- Vectors allow the organisation of entities (e.g. numbers, characters. . .) along one dimension which can be indexed

```
height.girls <- c(178, 175, 159, 164, 183, 192)
height.boys <- c(181, 189, 174, 177)
```

```
height.girls[2]
```

```
## [1] 175
```

```
height.boys[3]
```

```
## [1] 174
```

Vector

- They can be combined:

```
(height <- c(height.boys, height.girls))  
## [1] 181 189 174 177 178 175 159 164 183 192
```

Vector continued

- They can be indexed logically (i.e. indexed by anything leading to a vector of booleans):

```
(height > 168)
```

```
## [1] TRUE TRUE TRUE TRUE TRUE TRUE FALSE FALSE TRUE
## [10] TRUE
```

```
height[height > 168]
```

```
## [1] 181 189 174 177 178 175 183 192
```

```
height[!(height == min(height))]
```

```
## [1] 181 189 174 177 178 175 164 183 192
```

```
height[height != min(height)]
```

```
## [1] 181 189 174 177 178 175 164 183 192
```

Factors

- They work with other things than numbers:

```
sex <- c("girl","girl","girl","girl","girl", "girl",
"boy","boy","boy","boy")
sex <- factor(sex)
sex

## [1] girl girl girl girl girl girl boy boy boy boy
## Levels: boy girl
```

```
# Or
sex <- factor(c(rep("girl", times = 6),
                rep("boy", times = 4)))

# Or

sex <- factor(c(rep("girl", times = length(height.girls)),
                rep("boy", times = length(height.boys))))
```

Changing the order of levels of a factor

You have:

```
my_factor1  
## [1] A A B B C  
## Levels: A B C
```

You want:

```
my_factor2  
## [1] A A B B C  
## Levels: C B A
```


Changing the order of levels of a factor

You have:

```
my_factor1  
## [1] A A B B C  
## Levels: A B C
```

You want:

```
my_factor2  
## [1] A A B B C  
## Levels: C B A
```

You do:

```
## Using base:  
my_factor2 <- factor(my_factor1, levels(my_factor1)[c(3, 2, 1)])  
my_factor2  
## [1] A A B B C  
## Levels: C B A
```

Changing the order of levels of a factor

You have:

```
my_factor1
## [1] A A B B C
## Levels: A B C
```

You want:

```
my_factor2
## [1] A A B B C
## Levels: C B A
```

You do:

```
## Using base:
my_factor2 <- factor(my_factor1, levels(my_factor1)[c(3, 2, 1)])
my_factor2
## [1] A A B B C
## Levels: C B A
```

Note: the order of levels influences the output of linear models and plotting functions (e.g. order in the legend of a ggplot) ...

Changing the levels of a factor

You have:

```
my_factor1
## [1] A A B B C
## Levels: A B C
```

You want:

```
my_factor2
## [1] A A A A D
## Levels: A D
```

You do:

```
## Using base:
levels(my_factor1)
## [1] "A" "B" "C"

my_factor2 <- my_factor1
levels(my_factor2) <- c("A", "A", "D") ## in same order!
my_factor2
## [1] A A A A D
## Levels: A D
```

```
## Using dplyr:
my_factor2 <- recode(my_factor1, A = "A", B = "A", C = "D")
my_factor2
## [1] A A A A D
## Levels: A D
```

Data frames

Data frames allow the organisation of entities as a matrix-like structure whose columns have the same length:

```
dataframe.ht <- data.frame(Height = height, Sex = sex)
dataframe.ht
##      Height Sex
## 1      181 girl
## 2      189 girl
## 3      174 girl
## 4      177 girl
## 5      178 girl
## 6      175 girl
## 7      159 boy
## 8      164 boy
## 9      183 boy
## 10     192 boy
```

Data frames

It is good practice to always check their structure:

```
str(dataframe.ht)
## 'data.frame': 10 obs. of  2 variables:
##  $ Height: num  181 189 174 177 178 175 159 164 183 192
##  $ Sex    : Factor w/ 2 levels "boy","girl": 2 2 2 2 2 2 1 1 1 1
```

Data frames

You access the columns by means of the extractor `$`

```
height
## [1] 181 189 174 177 178 175 159 164 183 192

rm(list = c("height", "sex")) # removing original vectors
height
## Error in eval(expr, envir, enclos): object 'height' not found
dataframe.ht$Height #Or: with(data = dataframe.ht, Height)
## [1] 181 189 174 177 178 175 159 164 183 192
```

⇒ What is the average height?

Data frames

Some functions can take a data frame as an input:

```
summary(dataframe.ht)
##      Height      Sex
## Min.   :159.0   boy :4
## 1st Qu.:174.2   girl:6
## Median :177.5
## Mean   :177.2
## 3rd Qu.:182.5
## Max.   :192.0
```

Note: this will be the case of a lot of functions performing statistical tests!

Data frames

How to compute the average height per sex?

- simple

```
mean(dataframe.ht$Height[dataframe.ht$Sex == "boy"])  
## [1] 174.5
```

- more elegant

```
tapply(X = dataframe.ht$Height, INDEX = dataframe.ht$Sex,  
       FUN = mean)  
  
##    boy    girl  
## 174.5 179.0  
  
# Or: with(data = dataframe.ht, tapply(X = Height,  
#   INDEX = Sex, FUN = mean))
```

- even more elegant but dangerous

```
library(dplyr)  
dataframe.ht %>% group_by(Sex) %>% summarize(mean = mean(Height)) ## be aware of the rounding  
  
## # A tibble: 2 x 2  
##   Sex    mean  
##   <fct> <dbl>  
## 1 boy    174.  
## 2 girl   179
```


Data frames

They can also be indexed:

```
dataframe.ht[1, ]  
##   Height Sex  
## 1    181 girl  
dataframe.ht[, 1] # Or: dataframe.ht[, "Sex"]  
## [1] 181 189 174 177 178 175 159 164 183 192
```

Data frames

They can be edited:

```
dataframe.ht[1, 1]
## [1] 181

dataframe.ht[1, 1] <- 171.3
dataframe.ht[1, 1]
## [1] 171.3

dataframe.ht$linenumber <- 1:nrow(dataframe.ht) # add column
ncol(dataframe.ht) # try dim()
## [1] 3

dataframe.ht$linenumber <- NULL # remove column
ncol(dataframe.ht)
## [1] 2
```

Data frames

They can be edited with dplyr way

add column with `mutate()`

```
dataframe.ht <- dataframe.ht %>% mutate(linenumber = 1:nrow(dataframe.ht))
head(dataframe.ht, n= 3)

##   Height Sex linenumber
## 1  171.3 girl          1
## 2  189.0 girl          2
## 3  174.0 girl          3
```

Data frames

They can be edited with dplyr way

add column with `mutate()`

```
dataframe.ht <- dataframe.ht %>% mutate(linenumber = 1:nrow(dataframe.ht))
head(dataframe.ht, n= 3)

##   Height Sex linenumber
## 1  171.3 girl          1
## 2  189.0 girl          2
## 3  174.0 girl          3
```

select columns with `mutate()`

```
dataframe.ht.sex <- dataframe.ht %>% select(Sex)
head(dataframe.ht.sex, n= 3)

##   Sex
## 1 girl
## 2 girl
## 3 girl
```

Data frames

They can be edited with dplyr way

add column with mutate()

```
dataframe.ht <- dataframe.ht %>% mutate(linenumber = 1:nrow(dataframe.ht))
head(dataframe.ht, n= 3)

##   Height Sex linenumber
## 1  171.3 girl          1
## 2  189.0 girl          2
## 3  174.0 girl          3
```

select columns with mutate()

```
dataframe.ht.sex <- dataframe.ht %>% select(Sex)
head(dataframe.ht.sex, n= 3)

##   Sex
## 1 girl
## 2 girl
## 3 girl
```

select rows with mutate()

```
dataframe.ht.female <- dataframe.ht %>% filter(Sex == "girl")
head(dataframe.ht.female, n= 3)

##   Height Sex linenumber
## 1  171.3 girl          1
## 2  189.0 girl          2
## 3  174.0 girl          3
```

reshaping data frame

you have wide data:

```
head(my_df1)
##   age4 Sex linenumber age1 age2 age3
## 1 171.3 girl         1 71.3 146.3 161.3
## 2 189.0 girl         2 89.0 164.0 179.0
## 3 174.0 girl         3 74.0 149.0 164.0
## 4 177.0 girl         4 77.0 152.0 167.0
## 5 178.0 girl         5 78.0 153.0 168.0
## 6 175.0 girl         6 75.0 150.0 165.0

dim(my_df1)
## [1] 10  6
```

you want long data:

```
head(my_df2)
##   Sex Age Height
## 1 girl age1    71.3
## 2 girl age1    89.0
## 3 girl age1    74.0
## 4 girl age1    77.0
## 5 girl age1    78.0
## 6 girl age1    75.0

dim(my_df2)
## [1] 50  3
```

reshaping data frame

you have wide data:

```
head(my_df1)
##   age4 Sex  linenumber age1  age2  age3
## 1 171.3 girl         1 71.3 146.3 161.3
## 2 189.0 girl         2 89.0 164.0 179.0
## 3 174.0 girl         3 74.0 149.0 164.0
## 4 177.0 girl         4 77.0 152.0 167.0
## 5 178.0 girl         5 78.0 153.0 168.0
## 6 175.0 girl         6 75.0 150.0 165.0

dim(my_df1)
## [1] 10  6
```

you want long data:

```
head(my_df2)
##   Sex Age Height
## 1 girl age1    71.3
## 2 girl age1    89.0
## 3 girl age1    74.0
## 4 girl age1    77.0
## 5 girl age1    78.0
## 6 girl age1    75.0

dim(my_df2)
## [1] 50  3
```

you do:

```
my_df2 <- my_df1 %>% gather("Age", "Height", -Sex) %>% arrange(Age)
```

reshaping data frame

you have wide data:

```
head(my_df1)
##   age4 Sex linenumber age1 age2 age3
## 1 171.3 girl          1 71.3 146.3 161.3
## 2 189.0 girl          2 89.0 164.0 179.0
## 3 174.0 girl          3 74.0 149.0 164.0
## 4 177.0 girl          4 77.0 152.0 167.0
## 5 178.0 girl          5 78.0 153.0 168.0
## 6 175.0 girl          6 75.0 150.0 165.0

dim(my_df1)
## [1] 10 6
```

you want long data:

```
head(my_df2)
##   Sex Age Height
## 1 girl age1    71.3
## 2 girl age1    89.0
## 3 girl age1    74.0
## 4 girl age1    77.0
## 5 girl age1    78.0
## 6 girl age1    75.0

dim(my_df2)
## [1] 50 3
```

you do:

```
my_df2 <- my_df1 %>% gather("Age", "Height", -Sex) %>% arrange(Age)
```

one row = one observation, one column = one variable

joining data frame

```
# df_to_merge1 <- my_df2 %>% mutate(ID = imap_chr(paste("ID", seq)))
```

you have df1:

```
# head(my_df2)
dim(my_df2)
## [1] 50 3
```

you have df2:

```
head(my_df2)
##   Sex Age Height
## 1 girl age1  71.3
## 2 girl age1  89.0
## 3 girl age1  74.0
## 4 girl age1  77.0
## 5 girl age1  78.0
## 6 girl age1  75.0
```

extending data frame

cheating data frame

plenty of informative cheatsheets on: <https://www.rstudio.com/resources/cheatsheets/>

Lists

Lists allow the organisation of any set of entities into a single R object:

```
list.ht <- list(girls = height.girls, boys = height.boys)
list.ht
## $girls
## [1] 178 175 159 164 183 192
##
## $boys
## [1] 181 189 174 177
```

Lists

Lists can also be indexed and their elements extracted:

```
list.ht$girls
## [1] 178 175 159 164 183 192
list.ht["boys"] # still a list
## $boys
## [1] 181 189 174 177
list.ht[["boys"]] # vector
## [1] 181 189 174 177
list.ht[[2]][3]
## [1] 174
```

Lists

Some functions can take a list as an input:

```
lapply(list.ht, FUN = mean)
## $girls
## [1] 175.1667
##
## $boys
## [1] 180.25
```

Summary

dataframe.ht

| ## | Height | Sex | linenumber |
|-------|--------|------|------------|
| ## 1 | 171.3 | girl | 1 |
| ## 2 | 189.0 | girl | 2 |
| ## 3 | 174.0 | girl | 3 |
| ## 4 | 177.0 | girl | 4 |
| ## 5 | 178.0 | girl | 5 |
| ## 6 | 175.0 | girl | 6 |
| ## 7 | 159.0 | boy | 7 |
| ## 8 | 164.0 | boy | 8 |
| ## 9 | 183.0 | boy | 9 |
| ## 10 | 192.0 | boy | 10 |

list.ht

```
## $girls
## [1] 178 175 159 164 183 192
##
## $boys
## [1] 181 189 174 177
```

Summary

- `data.frame`

- All columns have same length
- Each column can have its own class (e.g. `numeric`, `factor`, `character`)

- `list`

- Each element can have its own length
- Each element can have its own class (e.g. `numeric`, `factor`, `character`)