

# 122COM: Boyer-Moore Searching

David Croft

Coventry University

david.croft@coventry.ac.uk

2018

# String searching better

A

- Naive search works but is inefficient.
- Obvious solution is not always the best one.
- Think about the problem and what is being searched.
  - Can you be smarter?

Boyer-Moore string searching algorithm.

- 1977.
- Not going to talk about the whole algorithm here.
  - Gets complex.
- Right to left comparison.
- Can skip sections of the text.
  - Don't need to test every position.
  - How?
- Pre-processes the search string.
  - Produce bad character rule table.
  - Will explain how in a minute.

# Boyer-Moore algorithm

- 1 Preprocess the search string to create the “bad character table”.
  - Will explain how in a minute.

example  $\Rightarrow$ 

a	e	l	m	p	x	*
4	6	1	3	2	5	7

- 2 Same as the naive search, position the search string at the start of the main text.
- 3 Compare the strings.
- 4 If strings don't match then in the bad character table lookup the character positioned at the end of the search string.
- 5 Move the search string by the number of positions specified in the table.
- 6 Repeat from step 3.

example  $\Rightarrow$ 

a	e	l	m	p	x	*
4	6	1	3	2	5	7

text = 

t	h	i	s		i	s		a	n		e	x	a	m	p	l	e
---	---	---	---	--	---	---	--	---	---	--	---	---	---	---	---	---	---

  
search = 

e	x	a	m	p	l	e
---	---	---	---	---	---	---

7  
↓

4  
↓

text = 

t	h	i	s		i	s		a	n		e	x	a	m	p	l	e
---	---	---	---	--	---	---	--	---	---	--	---	---	---	---	---	---	---

  
search = 

e	x	a	m	p	l	e
---	---	---	---	---	---	---

6  
↓

text = 

t	h	i	s		i	s		a	n		e	x	a	m	p	l	e
---	---	---	---	--	---	---	--	---	---	--	---	---	---	---	---	---	---

  
search = 

e	x	a	m	p	l	e
---	---	---	---	---	---	---

Creating the bad character table.

- For each character.
  - Except the last.
- Just count number of places between it and end of search string.

example  $\Rightarrow$ 

a	e	l	m	p	x	*
4	6	1	3	2	5	7

Doesn't need to sort or modify the sequence being searched.

- Small amount of pre-processing on the search value.

Worst case.

- Linear time.

Average case

- Sub-linear.

Not the only improved string searching algorithm.

- Knuth-Morris-Pratt.
- Finite State Machine (FSM).
- Rabin-Karp.

# The End