




## Gastronomy Line

High efficiency combi-steam oven



### STEADY COOK TOUCH SERIE 6

**N06ESCTD** Electric ⚡

**N06GSCTD** Gas 🔥

COMBI OVEN • DIRECT STEAM • 6 TRAYS GN1/1 – 60 Pitch • PROGRAMMABLE TOUCH SYSTEM

**THE STEADY COOK TOUCH SYSTEM** is characterized by a 7-inch capacitive touch screen for quick, simple, and intuitive use. It features the MULTICOOK function, allowing simultaneous cooking of foods with different preparation times using a multilevel cooking system. Customizable software, 120 programmable recipes, up to 6 cooking phases each. Fan speed regulation with inverter technology up to 10 levels. Adjustable steam from 0 to 100%. The entire structure is made of AISI 304 stainless steel, and the USB input allows for data storage, software updates, and HACCP data download.

It can manage various **cooking processes**: dry convection cooking, mixed convection-steam cooking, steam cooking, Delta T cooking, low-temperature cooking, sous-vide cooking, grilling, and regeneration.

The core probe and automatic washing system with three washing cycles (Soft - Medium - Hard) are included as standard.

Coven ovens are equipped with a two-step handle for maximum safety and perfect airtight sealing.

Book-style door with double-inspected, thick glass to effectively reduce heat transmission to the outside.

Double liquid collection basin with an integrated draining tray in the door for automatic drainage via direct connection to the drainage system.


Left-hinged door with right-side opening.

#### FEATURES:

code	N06ESCTD - N06GSCTD
outer dim.	862x716x728 mm
inner dim.	584x355x436 mm
number of trays	6 - 1/1 GN
tray distance	60 mm
number of meals	max 70
weight	91 Kg (electric) / 103 Kg (gas)
voltage	415 V~ 3N (electric) / 230 ~ 1N (gas)
power	7,8 kW (electric) / 8,5 kW (gas)

#### OPTIONAL / ACCESSORIES

CORE PROBE  
 AUTOMATIC WASH  
 STAINLESS STEEL SUPPORT  
 OPPOSITE DOOR  
 HOOD  
 STEAM CONDENSER  
 GREASE FILTER  
 GRIDS: Chrome / Stainless Steel / Grill / Poultry  
 TRAYS: Non-stick / Stainless Steel / Mesh / Perforated  
 COVEN WASHING DETERGENT

**home page**

Wide overview, intuitive graphics, function selection.

**Easy and fast.****recipes**

Ability to save customized cooking programs, library of specially designed and tested pre-loaded programs in our laboratories, data update and saving via USB port.

**special cycles**

Multicook with count-up function for a continuous cooking cycle and count-down function where trays with different preparation times complete cooking simultaneously

**usb port****COOKING PROCESSES:**

Manual and automatic cooking.

Temperature: 30 °C – 250 °C.

72 preloaded recipes + 48 customizable recipes.

Up to 6 cooking phases.

Cooks with core probe.

Delta T cooking.

Multicook.

**DELTA T COMBO:** Allows maintaining a constant temperature difference between the core of the product and the cooking chamber. The core temperature probe is the key component of DELTA T COMBO, enabling real-time temperature detection in the core of the raw material until reaching the desired cooking level. The core temperature probe is removable for extended durability.

**STEAM MANAGEMENT:****HUMIDITY CONTROL**

Total control of humidity in the cooking chamber from 0 to 100%.

**DUO STEAM SYSTEM:** Innovative combined system that produces steam, allowing the regulation of humidity percentage. This system allows for the use of:

1) Direct steam 2) Dedicated boiler (optional) 3) Combined use of direct steam and boiler in automatic mode or user-selected manually.

Fast humidity evacuation:

Automatic system with vent valve.

**PREHEATING:** Automatic preheating.

**AIR INVERTER:** The ventilation management through the inverter allows the reversal of the fan rotation and adjustment with 10 levels of speed.

**SELF WASHING MODE:**

Thorough and complete cleaning. The washing system is equipped with an arm with multiple nozzles capable of reaching every corner of the cooking chamber for impeccable cleaning, thanks to three washing cycles (Soft - Medium - Hard).

**TECHNICAL DATA:****STANDARD**

Voltage	ELECTRIC 415 V	GAS 230 V
Phase	~3PH+N+PE	~1PH+N+PE
Power	7,8 kW	8,5 kW ⚡ 0,5
Maximum absorbed current (amperes)	11,2 A	1,52 A
Power cable requirements	H07RN-F 5G x 2.5 mm <sup>2</sup>	H07RN-F 3G x 1.5 mm <sup>2</sup>
Gas connection	-	1/2"
Power cable	Not included	Included
Plug	Not included	Not included

**OPTION A**

Voltage	230 V
Phase	~1PH+N+PE
Power	7,8 kW
Maximum absorbed current (amperes)	34 A
Power cable requirements	H07RN-F 3G x 6 mm <sup>2</sup>

**OPTION B**

Voltage	230 V
Phase	~3PH+PE
Power	7,8 kW
Maximum absorbed current (amperes)	19,5 A
Power cable requirements	H07RN-F4G x 4 mm <sup>2</sup>

**Water connection \*:**

It is essential to always install a water softener upstream of the appliance. The water quality must meet the following characteristics:

Hardness (CaCO<sub>3</sub>) from 3° to 9°F (French degrees).  
Maximum temperature 15 +/- 5°C.

Failure to install an effective water softener leads to the formation of limescale and anomalies in the appliance in a short time.

Tap water:

Drinking water inlet: 3/4"

Network water pressure: from 1.5 to 3 bar

\* USING WATER THAT DOES NOT COMPLY WITH THE MINIMUM STANDARDS SET BY COVEN FOR WATER QUALITY WILL NULLIFY THE WARRANTY.

**INSTALLATION REQUIREMENTS:**

Installations must comply with all local electrical systems, especially the section of electrical connection cables, and regulations for ventilation and hydraulic connection. It is necessary to perform combustion gas analysis in the case of gas ovens.



STEADY COOK TOUCH SERIE 6 Electric/Gas

**N 06 E S C T D / N 06 G S C T D**

\*(1) \*(2) G \*(3) \*(4) \*(5) \*(6) \*(7)

**CODE LEGEND**

- (1) Oven line - **N**, New line
- (2) Number of trays - **06**
- (3) Power supply - "**E**" Electric / "**G**" Gas
- (4) Gastronomy line - "**SC**" (Steady Cook)
- (5) User interface - "**T**" Touch screen
- (6) "**D**" Direct steam
- (7) "**X**" Indirect steam (Boiler)



**COVEN Srl**

Strada Vicinale della Berlia 555  
10146 Torino

Tel. +39 011 18864131  
Fax. +39 011 0121609

[info@coven.it](mailto:info@coven.it)  
[www.coven.it](http://www.coven.it)