

# 한 번에 끝내는 블록체인 개발 A to Z

Chapter 2

네트워크

Chapter 2

네트워크

# 헤더

# 헤더

HTTP 헤더 필드는 요청과 응답 메시지에 추가 정보를 더함. 기본적으로 이름/값 쌍의 목록.

```
willpark@Willui-MacBookPro ~ % curl -I -L www.google.com
HTTP/1.1 200 OK
Content-Type: text/html; charset=ISO-8859-1
P3P: CP="This is not a P3P policy! See g.co/p3phelp for more info."
Date: Sun, 14 Aug 2022 08:27:39 GMT
Server: gws
X-XSS-Protection: 0
X-Frame-Options: SAMEORIGIN
Transfer-Encoding: chunked
Expires: Sun, 14 Aug 2022 08:27:39 GMT
Cache-Control: private
Set-Cookie: 1P_JAR=2022-08-14-08; expires=Tue, 13-Sep-2022 08:27:39 GMT; path=/; domain=.google.com; Secure
Set-Cookie: AEC=AakniG0XOCq6reeFG5_D5dJnwYQevMNYJynL0mo0qBasA0J-MLEtUNaF4U; expires=Fri, 10-Feb-2023 08:27:39 GMT; path=/; domain=.google.com; Secure; HttpOnly; SameSite=lax
Set-Cookie: NID=511=Zxo2C4Mnrqx7rDT5CpJg45XbDn4BilpblfggZuhLvoif1-ZRPtooc00X01pFpToREBGr3NjAEJj4QoadpFKl2BBv1Z1ZR1URy2qGHLvZHLUHjkuFbJm1HvbyOXjDvnK69JPh96rznsJ1Y522zFK0_9Bv9z19ZNabFiZA5Qoq5Mc; expires=Mon, 13-Feb-2023 08:27:39 GMT; path=/; domain=.google.com; HttpOnly
```

# 헤더 종류

## ① 일반(general) 헤더

Date: Sun, 14 Aug 2022  
10:00:00 KST

## ② 요청(request) 헤더

Accept: \*/\*

## ③ 응답(response) 헤더

Content-Type: text/html;  
charset=utf-8

## ④ 엔티티(entity) 헤더

Host: developer.mozilla.org