

---

# **Coarse-grained OpenMM Documentation**

*Release 0.0.1*

**Garrett A. Meek**

**Michael R. Shirts**

**Dept. of Chemical and Biological Engineering  
University of Colorado Boulder**

**Sep 05, 2019**

# CONTENTS

<b>1</b>	<b>Building OpenMM objects for coarse grained modeling</b>	<b>2</b>
1.1	Building an OpenMM System() and Topology() . . . . .	2
1.2	Other tools for building and verifying the OpenMM System() and Topology() . . .	3
<b>2</b>	<b>OpenMM simulation tools for coarse grained modeling</b>	<b>7</b>
2.1	Building OpenMM simulation objects . . . . .	7
2.2	Building and running Yank replica exchange simulations . . . . .	9
2.3	Plotting tools . . . . .	13
2.4	Other simulation tools . . . . .	17
<b>3</b>	<b>Utilities for coarse grained modeling in OpenMM</b>	<b>21</b>
<b>4</b>	<b>Indices and tables</b>	<b>23</b>
	<b>Python Module Index</b>	<b>24</b>
	<b>Index</b>	<b>25</b>

This documentation is generated automatically using Sphinx, which reads all docstring-formatted comments from Python functions in the ‘cg\_openmm’ repository. (See `cg_openmm/doc` for Sphinx source files.)

---

## BUILDING OPENMM OBJECTS FOR COARSE GRAINED MODELING

---

### 1.1 Building an OpenMM System() and Topology()

All OpenMM simulations require a `System()` and a `Topology()`.

Listed below are functions and classes that aid the building of OpenMM `System()` and `Topology()` class objects for coarse grained models with user-defined properties:

`build.cg_build.build_system(cgmodel)`

Builds an OpenMM `System()` object, given a `CGModel()` as input.

**Parameters** `cgmodel` (*class*) – `CGModel()` class object

**Returns** OpenMM `System()` object

**Return type**

`System()`

**Example**

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> system = build_system(cgmodel)
>>> cgmodel.system = system
```

`build.cg_build.build_topology(cgmodel, use_pdbfile=False, pdbfile=None)`

Construct an OpenMM `Topology()` class object for our coarse grained model,

**Parameters**

- `cgmodel` (*class*) – `CGModel()` class object
- `use_pdbfile` (*Logical*) – Determines whether or not to use a PDB file in order to generate the `Topology()`.

- **pdbfile** (*str*) – Name of a PDB file to use when building the topology.

**Returns** OpenMM Topology()

**Return type**

Topology()

**Example**

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> from foldamers.util.iotools import write_pdbfile_without_
    ↳ topology
>>> input_pdb = "top.pdb"
>>> cgmodel = CGModel()
>>> write_pdbfile_without_topology(cgmodel, input_pdb)
>>> topology = build_topology(cgmodel, use_pdbfile=True,
    ↳ pdbfile=input_pdb)
>>> cgmodel.topology = topology
```

**Warning:** When ‘use\_pdbfile’=True, this function will use the `PDBFile()` class object from OpenMM to build the Topology(). In order for this approach to function correctly, the particle names in the PDB file must match the particle names in the coarse grained model.

## 1.2 Other tools for building and verifying the OpenMM System() and Topology()

Shown below are other functions/tools to build and verify the System/Topology:

`build.cg_build.add_force(cgmodel, force_type=None)`

Given a ‘cgmodel’ and ‘force\_type’ as input, this function adds the OpenMM force corresponding to ‘force\_type’ to ‘cgmodel.system’.

**Parameters**

- **cgmodel** – CGModel() class object.
- **type** – class
- **force\_type** (*str*) – Designates the kind of ‘force’ provided. (Valid options include: “Bond”, “Nonbonded”, “Angle”, and “Torsion”)

**Returns** CGModel() class object

**Return type** class

**Returns** An OpenMM Force() object.

**Return type** Force()

**Example**

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> force_type = "Bond"
>>> cgmodel, force = add_force(cgmodel, force_type=force_type)
```

build.cg\_build.add\_new\_elements(cgmodel)

Add coarse grained particle types to OpenMM.

**Parameters** cgmodel (*class*) – CGModel object (contains all attributes for a coarse grained model).

**Returns** particle\_list: a list of the particles that were added to OpenMM’s ‘Element’ List.

**Return type** list

**Example**

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> particle_types = add_new_elements(cgmodel)
```

**Warning:** If the particle names were user defined, and any of the names conflict with existing element names in OpenMM, OpenMM will issue an error exit.

build.cg\_build.get\_num\_forces(cgmodel)

Given a CGModel() class object, this function determines how many forces we are including when evaluating the energy.

**Parameters** cgmodel (*class*) – CGModel() class object

**Returns** Number of forces

**Return type** int

**Example**

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> total_number_forces = get_num_forces(cgmodel)
```

build.cg\_build.test\_force(cgmodel, force, force\_type=None)

Given an OpenMM `Force()`, this function determines if there are any problems with its configuration.

#### Parameters

- **cgmodel** (*class*) – CGModel() class object.
- **force** – An OpenMM Force() object.
- **force\_type** (*str*) – Designates the kind of ‘force’ provided. (Valid options include: “Nonbonded”)

**Returns** ‘success’, a variable designating whether or not the force test passed.

**Return type** Logical

#### Example

```
>>> from simtk.openmm.openmm import NonbondedForce
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> force = NonbondedForce()
>>> force_type = "Nonbonded"
>>> test_result = test_force(cgmodel, force, force_type="Nonbonded")
```

`build.cg_build.test_forces(cgmodel)`

Given a cgmodel that contains positions and an an OpenMM System() object, this function tests the forces for cgmodel.system.

More specifically, this function confirms that the model does not have any “NaN” or unphysically large forces.

#### Parameters

- **cgmodel** – CGModel() class object.
- **type** – class

**Returns** success: Indicates if this cgmodel has unphysical forces.

**Return type** Logical

#### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> pass_forces_test = test_forces(cgmodel)
```

`build.cg_build.verify_system(cgmodel)`

Given a CGModel() class object, this function confirms that its OpenMM System() object is configured correctly.

**Parameters** **cgmodel** (*class*) – CGModel() class object

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> verify_system(cgmodel)
```

**Warning:** The function will force an error exit if the system is invalid, and will proceed as normal if the system is valid.

`build.cg_build.verify_topology(cgmodel)`

Given a coarse grained model that contains a `Topology()` (`cgmodel.topology`), this function verifies the validity of the topology.

**Parameters** `cgmodel` (*class*) – `CGModel()` class object.

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> verify_topology(cgmodel)
```

**Warning:** The function will force an error exit if the topology is invalid, and will proceed as normal if the topology is valid.

`build.cg_build.write_xml_file(cgmodel, xml_file_name)`

Write an XML-formatted forcefield file for a coarse grained model.

### Parameters

- `cgmodel` (*class*) – `CGModel()` class object.
- `xml_file_name` (*str*) – Path to XML output file.

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> xml_file_name = "openmm_cgmodel.xml"
>>> write_xml_file(cgmodel, xml_file_name)
```



## OPENMM SIMULATION TOOLS FOR COARSE GRAINED MODELING

### 2.1 Building OpenMM simulation objects

OpenMM simulations are propagated using a `Simulation()` object.

Shown below are the main tools needed to build OpenMM `Simulation()` objects for coarse grained modeling.

```
simulation.tools.build_mm_simulation(topology, system, positions, temperature=Quantity(value=300.0,  
                                     unit=kelvin), simulation_time_step=None, total_simulation_time=Quantity(value=1.0,  
                                     unit=picosecond), output_pdb=None, output_data=None,  
                                     print_frequency=100,  
                                     test_time_step=False)
```

Build an OpenMM `Simulation()`

#### Parameters

- **topology** (`Topology()`) – OpenMM `Topology()`
- **system** (`System()`) – OpenMM `System()`
- **positions** (`Quantity()` ( `np.array( [cgmodel.num_beads,3] )`, `simtk.unit` )) – Positions array for the model we would like to test
- **temperature** (`SIMTK Unit()`) – Simulation temperature, default = 300.0 K
- **simulation\_time\_step** – Simulation integration time step
- **total\_simulation\_time** – Total run time for individual simulations

- **output\_pdb** (*str*) – Output destination for PDB coordinates, Default = None
- **output\_data** (*str*) – Output destination for non-coordinate simulation data, Default = None
- **print\_frequency** – Number of simulation steps to skip when writing to output, Default = 100
- **test\_time\_step** (*Logical*) – Logical variable determining if a test of the time step will be performed, Default = False

**Returns** OpenMM Simulation() object

**Return type**

Simulation()

**Example**

```
>>> from simtk import unit
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> topology = cgmodel.topology
>>> system = cgmodel.system
>>> positions = cgmodel.positions
>>> temperature = 300.0 * unit.kelvin
>>> simulation_time_step = 5.0 * unit.femtosecond
>>> total_simulation_time = 1.0 * unit.picosecond
>>> output_pdb = "output.pdb"
>>> output_data = "output.dat"
>>> print_frequency = 20
>>> openmm_simulation = build_mm_simulation(topology, system,
    ↳ positions, temperature=temperature, simulation_time_
    ↳ step=simulation_time_step, total_simulation_time=total_simulation_
    ↳ time, output_pdb=output_pdb, output_data=output_data, print_
    ↳ frequency=print_frequency, test_time_step=False)
```

```
simulation.tools.run_simulation(cgmodel, output_directory, total_simulation_time, simulation_time_step,
                                temperature, print_frequency, output_pdb=None, output_data=None)
```

Run OpenMM() simulation

**Parameters**

- **cgmodel** (*class*) – CGModel() object
- **output\_directory** (*str*) – Output directory for simulation data
- **total\_simulation\_time** – Total run time for individual simulations

- **simulation\_time\_step** – Simulation integration time step
- **temperature** – Simulation temperature, default = 300.0 K
- **print\_frequency** – Number of simulation steps to skip when writing to output, Default = 100

### Example

```
>>> import os
>>> from simtk import unit
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> topology = cgmodel.topology
>>> system = cgmodel.system
>>> positions = cgmodel.positions
>>> temperature = 300.0 * unit.kelvin
>>> simulation_time_step = 5.0 * unit.femtosecond
>>> total_simulation_time = 1.0 * unit.picosecond
>>> output_directory = os.getcwd()
>>> output_pdb = "output.pdb"
>>> output_data = "output.dat"
>>> print_frequency = 20
>>> run_simulation(cgmodel, output_directory, total_simulation_time,
    ↳ simulation_time_step, temperature, print_frequency, output_
    ↳ pdb=output_pdb, output_data=output_data)
```

**Warning:** When run with default options this subroutine is capable of producing a large number of output files. For example, by default this subroutine will plot the simulation data that is written to an output file.

## 2.2 Building and running Yank replica exchange simulations

The **Yank** python package is used to perform replica exchange sampling with OpenMM simulations.

Shown below are the main functions and tools necessary to conduct Yank replica exchange simulations with a coarse grained model in OpenMM.

```
simulation.rep_exch.run_replica_exchange(topology, system, po  
                                         sitions, tempera  
                                         ture_list=[Quantity(value=250.0,  
                                         unit=kelvin), Quan  
                                         tity(value=260.0,  
                                         unit=kelvin), Quan  
                                         tity(value=270.0,  
                                         unit=kelvin), Quan  
                                         tity(value=280.0,  
                                         unit=kelvin), Quan  
                                         tity(value=290.0,  
                                         unit=kelvin), Quan  
                                         tity(value=300.0,  
                                         unit=kelvin), Quan  
                                         tity(value=310.0,  
                                         unit=kelvin), Quan  
                                         tity(value=320.0,  
                                         unit=kelvin), Quan  
                                         tity(value=330.0,  
                                         unit=kelvin), Quan  
                                         tity(value=340.0,  
                                         unit=kelvin)], simula  
                                         tion_time_step=None, to  
                                         tal_simulation_time=Quantity(value=1.0,  
                                         unit=picosecond), out  
                                         put_data='output.nc', ver  
                                         bose_simulation=False,  
                                         exchange_attempts=None,  
                                         test_time_step=False, out  
                                         put_directory=None)
```

Run a Yank replica exchange simulation using an OpenMM coarse grained model.

#### Parameters

- **topology** – OpenMM Topology
- **system** – OpenMM System()
- **positions** – Positions array for the model we would like to test
- **temperature\_list** – List of temperatures for which to perform replica exchange simulations, default = [(300.0 \* unit.kelvin).\_\_add\_\_(i \* unit.kelvin) for i in range(-20,100,10)]
- **simulation\_time\_step** – Simulation integration time step
- **total\_simulation\_time** – Total run time for individual simula-

tions

- **output\_data** (*string*) – Name of NETCDF file where we will write simulation data
- **print\_frequency** – Number of simulation steps to skip when writing to output, Default = 100
- **verbose\_simulation** (*Logical*) – Determines how much output is printed during a simulation run. Default = False
- **exchange\_attempts** (*int*) – Number of exchange attempts to make during a replica exchange simulation run, Default = None
- **test\_time\_step** (*Logical*) – Logical variable determining if a test of the time step will be performed, Default = False
- **output\_directory** (*str*) – Path to which we will write the output from simulation runs.

**Returns** replica\_energies: The potential energies for all replicas at all (printed) time steps

#### Return type

replica\_energies: `Quantity()` ( `np.float( [number_replicas,number_simulation_steps] )`, `simtk.unit` )

**Returns** replica\_positions: The positions for all replicas at all (printed) time steps

#### Return type

replica\_positions: `Quantity()` ( `np.float( [number_replicas,number_simulation_steps,cgmodel.num_beads,3] )`, `simtk.unit` )

**Returns** replica\_state\_indices: The thermodynamic state assignments for all replicas at all (printed) time steps

#### Return type

replica\_state\_indices: `Quantity()` ( `np.int64( [number_replicas,number_simulation_steps] )`, `simtk.unit` )

#### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> from cg_openmm.simulation.rep_exch import *
>>> cgmodel = CGModel()
>>> replica_energies, replica_positions, replica_state_indices = run_
    ↪ replica_exchange(cgmodel.topology, cgmodel.system, cgmodel.
    ↪ positions)
```

```
simulation.rep_exch.read_replica_exchange_data(system=None, topology=None, temperature_list=None, output_data='output.nc', print_frequency=None)
```

Read replica exchange simulation data.

### Parameters

- **system** – OpenMM system object, default = None
- **topology** – OpenMM topology object, default = None
- **temperature\_list** – List of temperatures that will be used to define different replicas (thermodynamics states), default = None
- **output\_data** (*str*) – Path to the output data for a Yank, NetCDF-formatted file containing replica exchange simulation data, default = None
- **print\_frequency** (*int*) – Number of simulation steps to skip when writing data, default = None

**Returns** replica\_energies: The potential energies for all replicas at all (printed) time steps

### Return type

replica\_energies: `Quantity()` ( `np.float([number_replicas,number_simulation_steps])`, `simtk.unit` )

**Returns** replica\_positions: The positions for all replicas at all (printed) time steps

### Return type

replica\_positions: `Quantity()` ( `np.float([number_replicas,number_simulation_steps,cgmodel.num_beads,3])`, `simtk.unit` )

**Returns** replica\_state\_indices: The thermodynamic state assignments for all replicas at all (printed) time steps

### Return type

replica\_state\_indices: `Quantity()` ( `np.int64([number_replicas,number_simulation_steps])`, `simtk.unit` )

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> from cg_openmm.simulation.rep_exch import *
```

(continues on next page)

(continued from previous page)

```

>>> cgmodel = CGModel()
>>> replica_energies, replica_positions, replica_state_indices = run_
↳ replica_exchange(cgmodel.topology, cgmodel.system, cgmodel.
↳ positions)
>>> replica_energies, replica_positions, replica_state_indices = _
↳ read_replica_exchange_data(system=cgmodel.system,
↳ topology=cgmodel.topology, temperature_list=, output_data="output.
↳ nc", print_frequency=None)

```

`simulation.rep_exch.make_replica_pdb_files` (*topology*,  
*replica\_positions*)  
 Make PDB files from replica exchange simulation trajectory data

**Parameters**

- **topology** – OpenMM Topology
- **replica\_positions** – Positions array for the replica exchange data for which we will write PDB files

**Returns** file\_list: A list of names for the files that were written.

**Return type** List( str )

**Example**

```

>>> from foldamers.cg_model.cgmodel import CGModel
>>> from cg_openmm.simulation.rep_exch import *
>>> cgmodel = CGModel()
>>> replica_energies, replica_positions, replica_state_indices = run_
↳ replica_exchange(cgmodel.topology, cgmodel.system, cgmodel.
↳ positions)
>>> pdb_file_list = make_replica_pdb_files(cgmodel.topology,
↳ replica_positions)

```

## 2.3 Plotting tools

Shown below are functions which allow plotting of simulation results.

```
simulation.rep_exch.plot_replica_exchange_energies(replica_energies,  
                                                    tempera-  
                                                    ture_list,  
                                                    simula-  
                                                    tion_time_step,  
                                                    steps_per_stage=1,  
                                                    file_name='replica_exchange_energ  
                                                    legend=True,  
                                                    out-  
                                                    put_directory=None)
```

Plot the potential energies for a batch of replica exchange trajectories

### Parameters

- **replica\_energies** (*List( List( float \* simtk.unit.energy for simulation\_steps ) for num\_replicas )*) – List of dimension num\_replicas X simulation\_steps, which gives the energies for all replicas at all simulation steps
- **temperature\_list** – List of temperatures for which to perform replica exchange simulations, default = [(300.0 \* unit.kelvin).\_\_add\_\_(i \* unit.kelvin) for i in range(-20,100,10)]
- **simulation\_time\_step** – Simulation integration time step
- **steps\_per\_stage** (*int*) – The number of simulation steps for individual replica “stages” (period of time between state exchanges), default = 1
- **file\_name** (*str*) – The pathname of the output file for plotting results, default = “replica\_exchange\_energies.png”
- **output\_directory** (*str*) – Path to which we will write the output from simulation runs, Default = None
- **legend** (*Logical*) – Controls whether a legend is added to the plot

..warning:: If more than 10 replica exchange trajectories are provided as input data, by default, this function will only plot the first 10 thermodynamic states. These thermodynamic states are chosen based upon their indices, not their instantaneous temperature (ensemble) assignment.



```
simulation.rep_exch.plot_replica_exchange_summary(replica_states,
                                                    tempera-
                                                    ture_list,
                                                    simula-
                                                    tion_time_step,
                                                    steps_per_stage=1,
                                                    file_name='replica_exchange_state_t',
                                                    legend=True,
                                                    out-
                                                    put_directory=None)
```

Plot the thermodynamic state assignments for individual temperature replicas as a function of the simulation time, in order to obtain a visual summary of the replica exchanges from a Yank simulation.

### Parameters

- **replica\_states** (*List( List( float \* simtk.unit.energy for simulation\_steps ) for num\_replicas )*) – List of dimension num\_replicas X simulation\_steps, which gives the thermodynamic state indices for all replicas at all simulation steps
- **temperature\_list** – List of temperatures for which to perform replica exchange simulations, default = [(300.0 \* unit.kelvin).\_\_add\_\_(i \* unit.kelvin) for i in range(-20,100,10)]
- **simulation\_time\_step** – Simulation integration time step
- **steps\_per\_stage** (*int*) – The number of simulation steps for individual replica “stages” (period of time between state exchanges), default = 1
- **file\_name** (*str*) – The pathname of the output file for plotting results, default = “replica\_exchange\_state\_transitions.png”
- **legend** (*Logical*) – Controls whether a legend is added to the plot
- **output\_directory** (*str*) – Path to which we will write the output from simulation runs, default = None

..warning:: If more than 10 replica exchange trajectories are provided as input data, by default, this function will only plot the first 10 thermodynamic states. These thermodynamic states are chosen based upon their indices, not their instantaneous temperature (ensemble) assignment.

```
simulation.tools.plot_simulation_data(simulation_times,          y_data,
                                     plot_type=None,           out-
                                     put_directory=None)
```

Plot simulation data.

### Parameters

- **simulation\_times** (*List*) – List of simulation times (x data)
- **y\_data** (*List*) – List of simulation data
- **plot\_type** (*str*) – Form of data to plot, Default = None, Valid options include: “Potential Energy”, “Kinetic Energy”, “Total Energy”, “Temperature”

### Example

```
>>> import os
>>> from simtk import unit
>>> simulation_data_file = "output.pdb"
>>> simulation_time_step = 5.0 * unit.femtosecond
>>> simulation_data = read_simulation_data(simulation_data_file,
    ↪simulation_time_step)
>>> simulation_times = simulation_data["Simulation Time"]
>>> y_data = simulation_data["Potential Energy"]
>>> plot_type = "Potential Energy"
>>> plot_simulation_data(simulation_times, y_data, plot_type=
    ↪"Potential Energy")
```

`simulation.tools.plot_simulation_results` (*simulation\_data\_file*,  
*plot\_output\_directory*, *simulation\_time\_step*)

Plot all data from an OpenMM output file

### Parameters

- **simulation\_data\_file** (*str*) – Path to file containing simulation data
- **plot\_output\_directory** (*str*) – Path to folder where plotting results will be written.
- **simulation\_time\_step** – Simulation integration time step

### Example

```
>>> import os
>>> from simtk import unit
>>> simulation_data_file = "output.pdb"
>>> plot_output_directory = os.getcwd()
>>> simulation_time_step = 5.0 * unit.femtosecond
>>> plot_simulation_results(simulation_data_file, plot_output_
    ↪directory, simulation_time_step)
```

## 2.4 Other simulation tools

Shown below are other tools which aid the building and verification of OpenMM simulation objects.

`simulation.tools.get_mm_energy` (*topology*, *system*, *positions*)

Get the OpenMM potential energy for a system, given a topology and set of positions.

### Parameters

- **topology** – OpenMM Topology()
- **system** – OpenMM System()
- **positions** – Positions array for the model we would like to test

**Returns** potential\_energy: The potential energy for the model with the provided positions.

### Return type

`Quantity()` ( float, simtk.unit )

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> topology = cgmodel.topology
>>> system = cgmodel.system
>>> positions = cgmodel.positions
>>> openmm_potential_energy = get_mm_energy(topology, system,
↪positions)
```

`simulation.tools.get_simulation_time_step` (*topology*, *system*, *positions*, *temperature*, *total\_simulation\_time*, *time\_step\_list=None*)

Determine a suitable simulation time step.

### Parameters

- **topology** – OpenMM Topology
- **system** – OpenMM System()
- **positions** – Positions array for the model we would like to test
- **temperature** – Simulation temperature
- **total\_simulation\_time** – Total run time for individual simulations

- **time\_step\_list** (*List*, *default = None*) – List of time steps for which to attempt a simulation in OpenMM.

**Returns** A successfully-tested time step

**Return type**

`SIMTK Unit()`

**Example**

```
>>> from simtk import unit
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> topology = cgmodel.topology
>>> system = cgmodel.system
>>> positions = cgmodel.positions
>>> temperature = 300.0 * unit.kelvin
>>> total_simulation_time = 1.0 * unit.picosecond
>>> time_step_list = [1.0 * unit.femtosecond, 2.0 * unit.
    ↪ femtosecond, 5.0 * unit.femtosecond]
>>> best_time_step, max_force_tolerance = get_simulation_time_
    ↪ step(topology, system, positions, temperature, total_simulation_time,
    ↪ time_step_list=time_step_list)
```

```
simulation.tools.minimize_structure(topology, system, positions, tem-
    perature=Quantity(value=0.0,
    unit=kelvin),
    simulation_time_step=None,
    total_simulation_time=Quantity(value=1.0,
    unit=picosecond),
    output_pdb=None, output_data=None,
    print_frequency=1)
```

Minimize the potential energy

**Parameters**

- **topology** (*Topology()*) – OpenMM topology
- **system** (*System()*) – OpenMM system
- **positions** – Positions array for the model we would like to test
- **temperature** – Simulation temperature
- **total\_simulation\_time** – Total run time for individual simulations
- **output\_pdb** (*str*) – Output destination for PDB-formatted coordinates during the simulation
- **output\_data** (*str*) – Output destination for simulation data

- **print\_frequency** (*int*) – Number of simulation steps to skip when writing data, default = 1

**Returns** positions: Minimized positions

**Return type**

positions: `Quantity()` ( `np.array( [cgmodel.num_beads,3] )`, `simtk.unit` )

**Returns** potential\_energy: Potential energy for the minimized structure.

**Return type**

potential\_energy: `Quantity()` ( `np.array( [cgmodel.num_beads,3] )`, `simtk.unit` )

**Example**

```
>>> from simtk import unit
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> topology = cgmodel.topology
>>> system = cgmodel.system
>>> positions = cgmodel.positions
>>> temperature = 300.0 * unit.kelvin
>>> total_simulation_time = 1.0 * unit.picosecond
>>> simulation_time_step = 1.0 * unit.femtosecond
>>> output_pdb = "output.pdb"
>>> output_data = "output.dat"
>>> print_frequency = 20
>>> minimum_energy_structure, potential_energy, openmm_simulation_
    ↳ object = minimize_structure(topology, system, positions,
    ↳ temperature=temperature, simulation_time_step=simulation_time_
    ↳ step, total_simulation_time=total_simulation_time, output_
    ↳ pdb=output_pdb, output_data=output_data, print_frequency=print_
    ↳ frequency)
```

`simulation.tools.read_simulation_data(simulation_data_file, simulation_time_step)`

Read OpenMM simulation data

**Parameters**

- **simulation\_data\_file** (*str*) – Path to file that will be read
- **simulation\_time\_step** – Time step to apply for the simulation data

**Example**

```
>>> from simtk import unit
>>> simulation_data_file = "output.dat"
>>> simulation_time_step = 5.0 * unit.femtosecond
>>> data = read_simulation_data(simulation_data_file, simulation_
    ↳time_step)
```

```
simulation.rep_exch.get_minimum_energy_ensemble (topology,
                                                  replica_energies,
                                                  replica_positions,
                                                  ensemble_size=5,
                                                  file_name=None)
```

Get an ensemble of low (potential) energy poses, and write the lowest energy structure to a PDB file if a file\_name is provided.

### Parameters

- **topology** – OpenMM Topology()
- **replica\_energies** (*List( List( float \* simtk.unit.energy for simulation\_steps ) for num\_replicas )*) – List of dimension num\_replicas X simulation\_steps, which gives the energies for all replicas at all simulation steps
- **replica\_positions** (*np.array( ( float \* simtk.unit.positions for num\_beads ) for simulation\_steps )*) – List of positions for all output frames for all replicas
- **file\_name** – Output destination for PDB coordinates of minimum energy pose, Default = None

**Returns** ensemble: A list of poses that are in the minimum energy ensemble.

**Return type** List ( np.array( ( float \* simtk.unit.positions for num\_beads ) for simulation\_steps ) )

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> from cg_openmm.simulation.rep_exch import *
>>> cgmodel = CGModel()
>>> replica_energies, replica_positions, replica_state_indices = run_
    ↳replica_exchange(cgmodel.topology, cgmodel.system, cgmodel.
    ↳positions)
>>> ensemble_size = 5
>>> file_name = "minimum.pdb"
>>> minimum_energy_ensemble = get_minimum_energy_ensemble(cgmodel.
    ↳topology, replica_energies, replica_positions, ensemble_
    ↳size=ensemble_size, file_name=file_name)
```

## UTILITIES FOR COARSE GRAINED MODELING IN OPENMM

This page details the functionality of utilities in `cg_openmm/src/utilities/util.py`.

`utilities.util.distance(positions_1, positions_2)`

Calculate the distance between two particles, given their positions.

### Parameters

- **positions\_1** (`Quantity()` ( `np.array( [3] )`, `simtk.unit` )) – Positions for the first particle
- **positions\_2** – Positions for the first particle

**Returns** distance: Distance between two particles

### Return type

`Quantity()` ( `float`, `simtk.unit` )

### Example

```
>>> from foldamers.cg_model.cgmodel import CGModel
>>> cgmodel = CGModel()
>>> particle_1_coordinates = cgmodel.positions[0]
>>> particle_2_coordinates = cgmodel.positions[1]
>>> particle_distance = distance(particle_1_coordinates, particle_2_
↪coordinates)
```

`utilities.util.get_box_vectors(box_size)`

Given a simulation box length, construct a vector.

**Parameters** **box\_size** – Length of individual sides of a simulation box

**Returns** **box\_vectors**: Vectors to use when defining an OpenMM simulation box.

### Return type

**box\_vectors**: List( `Quantity()` `float` , `simtk.unit` )

`utilities.util.lj_v(positions_1, positions_2, sigma, epsilon)`

`utilities.util.set_box_vectors(system, box_size)`

Impose a set of simulation box vectors on an OpenMM simulation object.

**Parameters**

- **system** (`System()`) – OpenMM `System()`
- **box\_size** – Length of individual sides of a simulation box

**Returns** system: OpenMM system object

**Return type**

`System()`



## INDICES AND TABLES

- genindex
- modindex
- search

## PYTHON MODULE INDEX

### **b**

`build.cg_build`, 3

### **s**

`simulation.rep_exch`, 20

`simulation.tools`, 17

### **u**

`utilities.util`, 21

## INDEX

### A

`add_force()` (in module *build.cg\_build*), 3  
`add_new_elements()` (in module *build.cg\_build*), 4

### B

`build.cg_build(module)`, 2, 3  
`build_mm_simulation()` (in module *simulation.tools*), 7  
`build_system()` (in module *build.cg\_build*), 2  
`build_topology()` (in module *build.cg\_build*), 2

### D

`distance()` (in module *utilities.util*), 21

### G

`get_box_vectors()` (in module *utilities.util*), 21  
`get_minimum_energy_ensemble()` (in module *simulation.rep\_exch*), 20  
`get_mm_energy()` (in module *simulation.tools*), 17  
`get_num_forces()` (in module *build.cg\_build*), 4  
`get_simulation_time_step()` (in module *simulation.tools*), 17

### L

`lj_v()` (in module *utilities.util*), 21

### M

`make_replica_pdb_files()` (in module *simulation.rep\_exch*), 13

`minimize_structure()` (in module *simulation.tools*), 18

### P

`plot_replica_exchange_energies()` (in module *simulation.rep\_exch*), 13  
`plot_replica_exchange_summary()` (in module *simulation.rep\_exch*), 14  
`plot_simulation_data()` (in module *simulation.tools*), 15  
`plot_simulation_results()` (in module *simulation.tools*), 16

### R

`read_replica_exchange_data()` (in module *simulation.rep\_exch*), 11  
`read_simulation_data()` (in module *simulation.tools*), 19  
`run_replica_exchange()` (in module *simulation.rep\_exch*), 9  
`run_simulation()` (in module *simulation.tools*), 8

### S

`set_box_vectors()` (in module *utilities.util*), 22  
`simulation.rep_exch(module)`, 9, 13, 20  
`simulation.tools(module)`, 7, 15, 17

### T

`test_force()` (in module *build.cg\_build*), 4  
`test_forces()` (in module *build.cg\_build*), 5

### U

`utilities.util(module)`, 21

## V

`verify_system()` (*in module*  
*build.cg\_build*), 5

`verify_topology()` (*in module*  
*build.cg\_build*), 6

## W

`write_xml_file()` (*in module*  
*build.cg\_build*), 6