CS315 · ALGORITHMS ANALYSIS & DESIGN

Midterm 472 Solutions

From L1 to L7

Muharib

01 Solution Q1: matrix chain

The idea: multiplying a `p × q` matrix by a `q × r` matrix costs `p·q·r` operations. We want the parenthesization with the smallest total. We fill the table from short chains to long chains.

```
m[i, j] = min over k of:   m[i, k] + m[k+1, j] + cost
```

```
cost = (rows of i) × (cols of k) × (cols of j)
```

1 Chains of two matrices

```
AB  =  4 × 5 × 8  =  160
```

```
BC  =  5 × 8 × 3  =  120
```

```
CD  =  8 × 3 × 7  =  168
```

2 Chains of three matrices

```
ABC:   A(BC)  =  0 + 120 + 4 × 5 × 3  =  180     ← min
       (AB)C  =  160 + 0 + 4 × 8 × 3  =  256
BCD:   B(CD)  =  0 + 168 + 5 × 8 × 7  =  448
       (BC)D  =  120 + 0 + 5 × 3 × 7  =  225     ← min
```

3 The full chain ABCD

```
A(BCD)    =  0 + 225 + 4 × 5 × 7    =  365
(AB)(CD)  =  160 + 168 + 4 × 8 × 7  =  552
(ABC)D    =  180 + 0 + 4 × 3 × 7    =  264     ← min
```

	A	B	C	D
A	0	160	180	**264**
B	—	0	120	225
C	—	—	0	168
D	—	—	—	0

```
Minimum operations = 264
```

```
Best order of multiplication:   ((A(BC))D)
```

The order comes from tracing the choices back: ABCD split as `(ABC)D`, and ABC split as `A(BC)`.

02 Solution Q2: True / False + MCQ

#	Answer	Reason
1	**True**	A character that occurs more often gets a shorter code.
2	**False**	Greedy takes the best current choice, which does not give the optimum for every DP problem. Matrix chain and LCS, for example, cannot be solved greedily.
3	**False**	The slide writes only `T(MERGE)`, and the merge works on `n` elements, not $\frac{n}{2}$.
4	**False**	The same environment **and the same inputs** must be used.
5	**True**	The words of the Lecture 1 slide.
6	**c**	Dynamic programming stores the results of sub-problems and reuses them.

In item 6 the word NOT is superfluous. The intended wording is "uses the past results".

03 Solution Q3: LCS

We build a table whose rows are the letters of `X` and whose columns are the letters of `Y`, with a first row and column of zeros. Each cell is computed like this:

```
X[i] = Y[j]:   c[i, j] = c[i−1, j−1] + 1        diagonal + 1
```

```
X[i] ≠ Y[j]:   c[i, j] = max(top, left)
```

	⌀	A	B	C	A	D	F
⌀	0	0	0	0	0	0	0
A	0	1	1	1	1	1	1
C	0	1	1	2	2	2	2
B	0	1	2	2	2	2	2
A	0	1	2	2	3	3	3
E	0	1	2	2	3	3	3
D	0	1	2	2	3	4	4

```
Length = 4
```

```
The subsequence:   1)  ABAD      2)  ACAD
```

The length is the last cell of the table. We recover the letters by walking back from the last cell: when the two letters match we take the letter and move diagonally, otherwise we move to the larger of top and left. The coloured cells are the path of `ABAD`. When top and left are equal we may go either way, which is where the second answer `ACAD` comes from.

```
Check:   X = A C B A E D   →   A . B A . D   and   A C . A . D
```

```
         Y = A B C A D F   →   A B . A D .   and   A . C A D .
```

04 Solution Q4: hash table

Key	4	13	49	6	40	33
k mod 9	4	4	4	6	4	6

Index	Chain
0	∅
1	∅
2	∅
3	∅
4	4 → 13 → 49 → 40
5	∅
6	6 → 33
7	∅
8	∅

Four keys leave remainder 4 when divided by 9, so they all sit in cell 4 in the order they arrived: `4 → 13 → 49 → 40`. Cell 6 holds `6 → 33`. The other cells are empty.