CS315 · ALGORITHMS ANALYSIS & DESIGN

Lecture 4 Dynamic Programming

Midterm summary · CLRS Chapter 15

Muharib

What's inside

01 The idea

02 When to use DP (the two properties)

03 Matrix-chain multiplication

04 Example: four matrices (slides)

05 Example: six matrices (slides)

06 Longest common subsequence (LCS)

01 The idea

DP solves a problem from smaller subproblems and stores each subproblem's result in a table so it is never recomputed. It works from the smallest up (bottom-up).

Dynamic programming is an optimization method based on the **principle of optimality** (Bellman, 1950s):
"Every optimal policy consists only of optimal sub-policies."

The Fibonacci example

```
F(n) = F(n−1) + F(n−2)
```

```
Recursive:  each call makes 2 calls  →  O(2ⁿ)
```

```
            (a lot of repeated work)
```

```
DP:         fib[1] = fib[2] = 1
```

```
            for i = 3 to n:  fib[i] = fib[i−1] + fib[i−2]
```

```
            →  O(n)
```

02 When to use DP (the two properties)

Property	Meaning
Optimal sub-structure	An optimal solution contains optimal solutions to its subproblems.
Overlapping sub-problems	The same subproblem is revisited repeatedly.

The difference from divide and conquer: there the subproblems are independent and do not repeat; in DP they repeat, so we store them.

The four steps

1. Characterize the structure of an optimal solution.
2. Recursively define the value of an optimal solution.
3. Compute the value of an optimal solution, typically bottom-up.
4. Construct an optimal solution from the computed information.

Applications: matrix-chain multiplication, longest common subsequence and optimal binary search trees.

Asked in the midterm

An algorithm which uses the past results and uses them to find new results is → **Dynamic programming**

When DP is applied, it takes far less time than methods that don't take advantage of overlapping sub-problems. → **True**

Greedy algorithm can solve all the dynamic programming problems. → **False**

03 Matrix-chain multiplication

We have matrices to multiply. The order does not change the result, but it changes the number of multiplications. Goal: the minimum count and its parenthesization.

```
A (p×q) · B (q×r)  =  C (p×r)        cost = p · q · r
```

Slide example: three matrices

```
A = 10×100,   B = 100×5,   C = 5×50
```

```
((AB)C):  AB = 10·100·5 = 5,000
```

```
          (10×5)·C = 10·5·50 = 2,500
```

```
          total = 7,500
```

```
(A(BC)):  BC = 100·5·50 = 25,000
```

```
          A·(100×50) = 10·100·50 = 50,000
```

```
          total = 75,000
```

Same result with a tenth of the work, which is why DP is used to find the best order.

The recurrence

```
m[i, i] = 0
```

```
m[i, j] = min over i ≤ k < j of
```

```
          m[i, k] + m[k+1, j] + p(i−1)·p(k)·p(j)
```

```
s[i, j] = the k that gave the minimum
```

`p` is the list of dimensions: matrix `Ai` is `p(i−1) × p(i)`. Fill the table from short chains (length 2) up to the longest.

04 Example: four matrices (slides)

```
A0 = 10×5,  A1 = 5×8,  A2 = 8×4,  A3 = 4×10
```

```
Length 2:
A0A1 = 10·5·8 = 400
A1A2 = 5·8·4 = 160
A2A3 = 8·4·10 = 320
Length 3:
A0(A1A2) = 160 + 10·5·4 = 360   ✓
(A0A1)A2 = 400 + 10·8·4 = 720
A1(A2A3) = 320 + 5·8·10 = 720
(A1A2)A3 = 160 + 5·4·10 = 360   ✓
Length 4:
A0(A1A2A3)    = 360 + 10·5·10 = 860
(A0A1)(A2A3)  = 400 + 320 + 10·8·10 = 1,520
(A0A1A2)A3    = 360 + 10·4·10 = 760     ✓
```

	A0	A1	A2	A3
A0	0	400	360	**760**
A1	–	0	160	360
A2	–	–	0	320
A3	–	–	–	0

```
Minimum = 760        Order: ((A0(A1A2))A3)
```

Adding `A4 = 10×6` gives 820 with the order `A0((A1A2)(A3A4))`:

	A0	A1	A2	A3	A4
A0	0	400	360	760	**820**
A1	–	0	160	360	520
A2	–	–	0	320	432
A3	–	–	–	0	240
A4	–	–	–	–	0

05 Example: six matrices (slides)

```
A1 = 10×20, A2 = 20×5, A3 = 5×15, A4 = 15×50, A5 = 50×10, A6 = 10×15
```

```
p = 10, 20, 5, 15, 50, 10, 15
```

```
m[1,3] = min{ 0 + 1500 + 10·20·15 , 1000 + 0 + 10·5·15 }
       = min{ 4500, 1750 } = 1750
m[2,4] = min{ 0 + 3750 + 20·5·50 , 1500 + 0 + 20·15·50 }
       = min{ 8750, 16500 } = 8750
m[3,5] = min{ 0 + 7500 + 5·15·10 , 3750 + 0 + 5·50·10 }
       = min{ 8250, 6250 } = 6250
m[4,6] = min{ 0 + 7500 + 15·50·15 , 7500 + 0 + 15·10·15 }
       = min{ 18750, 9750 } = 9750
```

	A1	A2	A3	A4	A5	A6
A1	0	1000	1750	7250	7750	**8750**
A2	–	0	1500	8750	7250	8500
A3	–	–	0	3750	6250	7000
A4	–	–	–	0	7500	9750
A5	–	–	–	–	0	7500
A6	–	–	–	–	–	0

The `s` table says where to split. `s[1,6] = A2` means `(A1A2)(A3…A6)`; then `s[3,6] = A5` and `s[3,5] = A4`:

s	A1	A2	A3	A4	A5	A6
A1	–	A1	A2	A2	A2	A2
A2	–	–	A2	A2	A2	A2
A3	–	–	–	A3	A4	A5
A4	–	–	–	–	A4	A5
A5	–	–	–	–	–	A5
A6	–	–	–	–	–	–

```
Minimum = 8750        Order: ((A1A2)(((A3A4)A5)A6))
```

06 Longest common subsequence (LCS)

A subsequence keeps the letters in order but not necessarily adjacent. From `ABACDABAB`: `ABA` and `ACA` are valid; `DCA` is not (wrong order).

```
c[i, 0] = c[0, j] = 0
```

```
X[i] = Y[j]:   c[i, j] = c[i−1, j−1] + 1        diagonal + 1   (↖)
```

```
X[i] ≠ Y[j]:   c[i, j] = max(c[i−1, j], c[i, j−1])
```

```
               larger of top (↑) and left (←)
```

Fill the table row by row. The answer is in the last cell. To recover the string, trace back from the last cell, taking the letter on each diagonal move.

Slide example: X = ABCBDAB, Y = BDCABA

	∅	B	D	C	A	B	A
∅	0	0	0	0	0	0	0
A	0	0	0	0	1	1	1
B	0	**1**	1	1	1	2	2
C	0	1	1	**2**	2	2	2
B	0	1	1	2	2	**3**	3
D	0	1	2	2	2	3	3
A	0	1	2	2	3	3	**4**
B	0	1	2	2	3	4	4

```
Length = 4        LCS = BCBA    (BCAB and BDAB are also correct)
```

Gold cells: the letters taken. Light cells: the traceback path.

Repeats in the midterm

LCS of X = ACBAED and Y = ABCADF → length 4: ACAD or ABAD (472, 462, 451)

Matrix chain A = 4×5, B = 5×8, C = 8×3, D = 3×7 → 264, ((A(BC))D) (472, 451)

Running time: LCS `O(mn)`; matrix chain `O(n³)`.