


Selected-run evidence status: completed_unassessed

Geometry

Undeformed geometry

Exterior shape from the selected mesh



Mesh-derived exterior • source geometry unchanged

Undeformed geometry from selected mesh. Exterior shape derived from the selected run's mesh; this is not a CAD render.


Mesh

Mesh overview and local detail

Mesh nodes	22673	
Tetrahedral elements	78906	
Meshed parts	2	
Nominal element size	4.0	mm
Minimum mean-ratio quality	0.0853	0-1

Mesh overview

Undeformed exterior mesh




Exterior mesh faces • undeformed geometry

Mesh overview. Undeformed exterior topology of the selected case, verified against its recorded solved-mesh hashes.

Pad-root refinement detail

Pad-root region



Exterior mesh faces • undeformed geometry

Pad-root refinement detail. Positive pad-root region, $X = 112\text{--}150\text{ mm}$. Mesh metadata records a 0.65 target factor (2.6 mm local target).

Mean-ratio quality describes element shape and does not establish stress or time-step convergence.

Setup

Recorded selected-case model

Initial impact velocity	50	m/s
Requested simulation duration	0.3	ms
Foam depth	203.2	mm
Foam width	41.275	mm
Foam height	152.4	mm
Foam element size	10	mm
Initial contact gap	0.1	mm
Contact friction coefficient	0.1	dimensionless
Foam curve scale	1	dimensionless
Time-step scale	0.6	dimensionless
Requested state-output interval	0.01	ms
Startup mass-scaling DT2MS	-1.5e-07	s
Termination time-step ratio	0.01	dimensionless
Motor mass	0.1616	kg
Moving mass	0.7413749	kg
Pusher mass	0.5797749	kg
Initial kinetic energy	926.7187	J

Recorded material, contact and boundary assumptions

- Both offset clamshell shells are flexible; four local perfectly clamped closure-bolt collars. Seam contact allows opening elsewhere. No bolt preload, slip or failure qualification.
- Motor loaded upper-bound inertia distributed over actual bore nodes; no motor housing stiffness or exact inertia tensor.
- PA12-CF10 elastic isotropic proxy $E=1806.6\text{MPa}$ $\nu=.35$ density 1060; print +Z motor axes. No strength/failure claims.
- No fracture, erosion, motor thrust, carrier, released endcap or invented 35g hardware allowance.
- Rigid 8mm aluminum spreaders initially stationary; fixed x,y and rotations, free z without travel limit.


- Front and rear pusher bore-quadrant averages follow fixed zero-clearance coaxial guide axes through eight disjoint LINEAR_GLOBAL X/Y equations; every Z DOF is free. Cable compliance and clearance are idealized.
- All axial stopping reaction passes through transient contact; no axial guide constraint.
- Foam rear z fixed, x/y free: frictionless fixed backing; sides unconfined.
- MAT057 synthetic loading and unloading; HU=.05 BETA=0 DAMP=.1 SHAPE=1 FAIL=0. Not a product material model.
- Generic foam anchored at one catalog point; remaining curve chosen for nonbottoming comparative stop.
- Startup-only local mass scaling requested; added mass and inertia error MUST be assessed from solver output.
- Mesh, timestep, energy and momentum require independent assessment.

Solve

Recorded run status	completed_unassessed	
Recorded reached simulation time	0.299978	ms
Recorded requested simulation time	0.3	ms
Recorded solver wall time	205.219	s
Recorded termination state	normal_termination_confirmed	

Separate solve charts


Contact force resultant



Contact force resultant.

projects/offset_clamshell_impact_20260922/cases/clamshell-contact-diagnostic-v2/assessment/contact_histories.csv


Mass-weighted forward velocity



Mass-weighted forward velocity.

projects/offset_clamshell_impact_20260922/cases/clamshell-contact-diagnostic-v2/assessment/time_histories.csv


Moving assembly travel



Moving assembly travel.

projects/offset_clamshell_impact_20260922/cases/clamshell-contact-diagnostic-v2/assessment/time_histories.csv


Foam compression



Foam compression.

projects/offset_clamshell_impact_20260922/cases/clamshell-contact-diagnostic-v2/assessment/time_histories.csv


Regional P99 von Mises stress



Regional P99 von Mises stress.

projects/offset_clamshell_impact_20260922/cases/clamshell-contact-diagnostic-v2/assessment/stress_histories.csv

Global energy



Global energy.

projects/offset_clamshell_impact_20260922/cases/clamshell-contact-diagnostic-v2/assessment/global_energy_histories.csv

Results

Run 029 - impact evidence

Evidence status: completed_unassessed. This report describes only extracted evidence from the selected run. Numerical checks alone do not establish physical qualification.

Geometry and model setup

Recorded model item	Value
kind	impact
assembly kind	offset_clamshell
pusher kg	0.579775
body kg	0.289858
cable cap kg	0.289917
lower shell kg	0.289858
upper shell kg	0.289917
motors kg	0.1616
moving kg	0.741375
initial ke J	926.719
spreader each kg	0.135871

Solved mesh

Recorded mesh source: mesh_4mm_repaired. Mesh and timestep convergence are not established by these histories.

Motion and stopping event

Signed forward velocity, travel and foam compression are measured histories. Negative forward velocity denotes rebound; a partial history cannot establish the complete stopping event.

Measured result	Value	Unit
Peak stopping force	251546	N
Maximum travel	10.7649	mm

Measured result	Value	Unit
Peak regional P99 (outer pad)	120.565	MPa
Last extracted time	0.300068	ms
Final forward velocity	32.2231	m/s

Regional stress and energy

Regional P99 values are elastic demand measures across saved states, not printed-part strength predictions. Force peaks and percentile peaks can occur at different times.


Numerical checks and qualification

Extracted numerical check	Evidence
normal termination	true
requested time reached	true
binary matches nodout	true
moving mass consistent	true
initial energy error below 0p5pct	true
energy balance error below 5pct	true
hourglass below 5pct initial energy	true
sum abs nonfriction contact energy below 5pct initial energy	true
contact impulse momentum error below 5pct	true
no axial spc on moving or guide nodes	true
rigid guides leave only axial translation free	true
no prescribed motion	true
no detected deletion	true
positive sampled foam jacobians	true
first stop captured	false
foam compression below 80pct	true
mass scaling disabled or quantified below 0p1pct moving mass	true
all transverse guide equations satisfied and no axial equation	true

Images, animations and source evidence


clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.010 ms



clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.230 ms




Elastic stress demand / generic foam — no failure prediction

deformation_0023_0.230ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.300 ms




Elastic stress demand / generic foam — no failure prediction

deformation_0030_0.300ms.png

clamshell-contact-diagnostic-v2
 Rigid motion removed; deformation 1x; original outline gray


t = 0.300 ms



Elastic stress demand / generic foam — no failure prediction


deformation_0031_0.300ms.png

clamshell-contact-diagnostic-v2 | comparative elastic pusher / generic foam; no failure prediction




histories.png

Sampled offset-clamshell joint kinematics




joint-kinematics.png



stress-propagation-deformation.png


clamshell-contact-diagnostic-v2 t = 0.010 ms
Rigid motion removed; deformation 1x; original outline gray



Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_0001_0.010ms.png

clamshell-contact-diagnostic-v2 t = 0.060 ms
Rigid motion removed; deformation 1x; original outline gray




Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_0006_0.060ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.230 ms




Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_0023_0.230ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.300 ms




Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_0030_0.300ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.300 ms




Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_0031_0.300ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.010 ms

IMPACT FACE (-Z)



Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_impact_0001_0.010ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray

t = 0.300 ms

IMPACT FACE (-Z)




Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_impact_0030_0.300ms.png

clamshell-contact-diagnostic-v2
Rigid motion removed; deformation 1x; original outline gray


t = 0.010 ms

TOP (+Z)




Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_top_0001_0.010ms.png



Display saturates at 160 MPa; raw peak 563.7 MPa elastic proxy

stress_top_0030_0.300ms.png




- ▲ Generic foam
- ▲ Fixed backing
- ▲ Aluminum plates
- ▲ Lower shell
- ▲ Upper shell

Speed 50.00 m/s
Compression L/R
-0.0% / -0.0%
Travel -0.0 mm
Load 0.00 kN
Time 0.000 ms


world_0000_0.000ms.png

- ▲ Generic foam
- ▲ Fixed backing
- ▲ Aluminum plates
- ▲ Lower shell
- ▲ Upper shell

Speed 32.57 m/s
Compression L/R
2.3% / 2.3%
Travel 6.2 mm
Load 20.29 kN
Time 0.160 ms



world_0016_0.160ms.png



world_0031_0.300ms.png

- cable_guide_motion.csv
- contact_energy_by_interface.csv
- contact_energy_components.csv
- contact_histories.csv
- global_energy_histories.csv
- joint_histories.csv
- joint_metrics.json
- metrics.json
- part_energy_histories.csv
- sampled_planar_penetration.csv
- spc_histories.csv
- stress_histories.csv
- time_histories.csv

- [weighted_guide_constraints.csv](#)

Generated from selected-run extracted evidence; no authored report is available. Animation figures and their captions are excluded from this PDF; animations remain available in the standalone HTML.