

Original Line® Cylinders

Your configured part number: M-045-D

Additional accesories: (D-166-3)

Features and Benefits

- Maintenance Free Performance:
- Lubed for life w/proprietary synthetic blend grease
- Blue and Improved design doubles previous cylinder life
- Added Strength:
- Piston to rod connection is threaded, sealed, and riveted securely in place
- Roll formed rod threads on both ends
- Aluminum alloy piston with blow-by flats
- Low Breakaway:
- Inflatable, wear compensating, U-cup rod and piston seals
- Breakaway slots on each end cap for fast seal inflation

Engineering Specifications

Pressure Rating: 250 PSI

Temperature Range:

Buna N seals: -20° F (-29° C) to 200° F (90° C)

Fluoroelastomer seals for high temperatures (up to 400° F)

available

Magnetic piston option: max. operating temp. is 185° F

Materials:

Rod: High strength carbon steel and stainless steel available

Body: 304 stainless steel

End Caps: 6061 aluminum (RoHS compliant)

Rod Bushings: Oil-impregnated bronze except (5/16", 7/16", 9/16"

single acting)

Service and Design Capabilities

- Catalog models available in 4 days or less
- · Custom design capabilities for your needs
- Common modifications include:
- Custom rod threads/lengths
- Customer logo/part# on cylinder body
- Additional standard port sizes/locations
- Special lubricants (FDA approved, etc.)
- Anodized or nickel plated end caps
- Clean room design with Krytox lubrication
- Special spring forces

Bimba Manufacturing Company Monee, IL 60449-0068 Telephone: 708.534.8544

Toll Free: 800-44-BIMBA Email: cs@bimba.com www.bimba.com Leaders in Actuation.

